

FINAL BOREHOLE LOG AND SUMMARY OF TEST RESULTS MLW - 3b

PROJECT: <u>Pasig-Marikina River Channel Imp. Proj.</u> LOCATION: <u>Kapasigan, Pasig City</u> BH NO: <u>BMLW-3</u> DATE DRILLED: <u>06 - 07 March 2001</u>	GROUND ELEV. (MLLW = Zero Datum) <u>+ 9.946</u> STATION NO.: <u>00 + 950</u> WEATHER: <u>FAIR</u>	DEPTH OF WATER: <u>1.50</u> m DATE MEASURED: <u>06 Mar. 2001</u> TIME MEASURED: <u>7:00 AM</u>
COORDINATES: <u>1610663.750</u> N, <u>507768.250</u> E		

DEPTH, m	SAMPLE NO.	RECOVERY (%)	LOG SYMBOL	CLASSIFICATION	RQD	DESCRIPTION	BLOWS (SPT)			STANDARD PENETRATION TEST (SPT) (N-VALUE)					NATURAL MOIST. CONTENT, %	TOTAL UNIT WEIGHT, g/cc	ATTERBERG LIMITS		SPECIFIC GRAVITY	UNCONFINED COMP. TEST		SIEVE ANALYSIS % PASSING SIEVE												
							15 cm	15 cm	15 cm	10	20	30	40	50			LIQUID LIMIT, %	PLASTICITY INDEX, %		STRENGTH kg/cm ²	STRAIN %, %	4	10	40	20									
21	SS-20	100		CH		Sandy CLAY; gray; 6% fine sand; 94% high plasticity clay; VERY STIFF.	6	7	8																									
22	SS-21	100		CH			7	10	11						38		65	45	260												100	94		
23	SS-22	100		SM		Silty SAND; gray; 34% non-plastic silt with little amount of coarse to medium sand; 63% fine sand; MEDIUM DENSE.	5	8	10																									
24	SS-23	100		SM			9	11	11						23				2.63												100	99	97	34
25	SS-24	67		CL		Sandy CLAY; gray; little amount of medium sand; 46% fine sand; 53% medium plasticity clay; VERY STIFF.	10	12	15						26		45	24	2.62													100	99	53
26						END OF BOREHOLE (25.00 m)																												
27																																		
28																																		
29																																		
30																																		
31																																		
32																																		
33																																		
34																																		
35																																		
36																																		
37																																		
38																																		
39																																		
40																																		

	BASIC TECHNOLOGY AND MANAGEMENT CORPORATION 2nd Floor Prudential Bank Building, 1377 A. Mabini St., Ermita, Manila	MACHINE: <u>ACKER ACE</u> DRILLER: <u>A. TENERIFE</u> SUPERVISOR: <u>M. VILLAFUERTE</u>	LEGEND: SS - SPLIT SPOON SAMPLE WS - WASH SAMPLE UDS - UNDISTURBED SAMPLE CR - CORE SAMPLE W/ HYDROMETER ANALYSIS
--	---	--	---

図5-3-3 (86/221) 柱状図 (フェーズI実施分)

FINAL BOREHOLE LOG AND SUMMARY OF TEST RESULTS **MLW - 4**

PROJECT: **Pasig-Marikina River Channel Imp. Proj.**
 LOCATION: **Caniogan, Pasig City**
 BOREHOLE NO: **BMLW-4** DATE DRILLED: **02 - 03 March 2001**

GROUND ELEV. (MLLW = Zero Datum) **+ 10.385**
 STATION NO.: **1 + 450**
 WEATHER: **FAIR**
 COORDINATES: **1611158.500 N, 507850.100 E**

DEPTH OF WATER: **1.50** m
 DATE MEASURED: **02 Mar. 2001**
 TIME MEASURED: **2:00 PM**

DEPTH (m)	SAMPLE NO.	RECOVERY (%)	LOG SYMBOL	CLASSIFICATION	RQD	DESCRIPTION	BLOWS (SPT)			STANDARD PENETRATION TEST (SPT) (N-VALUE)					NATURAL MOIST. CONTENT, %	TOTAL UNIT WEIGHT, g/cc	ATTERBERG LIMITS		SPECIFIC GRAVITY	UNCONFINED COMP. TEST		SIEVE ANALYSIS % PASSING SIEVE							
							15 cm	15 cm	15 cm	10	20	30	40	50			LIQUID LIMIT, %	PLASTICITY INDEX, %		STRENGTH kg/cm ²	STRAIN %	4	10	40	200				
1	SS-1	89	[Symbol]			Sandy CLAY; dark gray; 11% fine sand; 88% high plasticity clay; VERY SOFT.	1	0	0					68		73	54	2.60											
2	SS-2	89	[Symbol]	CH			1	0	0																				
3	SS-3	56	[Symbol]	CH		Sandy CLAY; brownish gray; 16% gravel; 18% fine to coarse sand; 66% medium to high plasticity clay; SOFT.	2	3	0					52		58	33	2.62											
4	SS-4	89	[Symbol]				1	1	1																				
5	SS-5	89	[Symbol]				1	2	1																				
6	UDS-1	100	[Symbol]	SC		Gravelly Clayey SAND; dark gray; 14% gravel; 27% medium to high plasticity clay; 73% fine sand; VERY LOOSE.	PRESSED							49	1.65	59	40	2.62			Cc 0.320	Pc 1.040							
7	UDS-2	100	[Symbol]			Sandy CLAY; brownish gray; 0-2% gravel; 7-9% fine to coarse sand; 89-93% medium to high plasticity clay; SOFT.	PRESSED							54	1.62	59	38	2.60	0.0940	8.000			100	99	99	93			
8	SS-6	89	[Symbol]	CH			2	1	2					61		65	36	2.62					100	97	93	91			
9	UDS-3	100	[Symbol]				PRESSED							66	1.46	56	27	2.61	0.1420	7.429			96	94	91	89			
10	SS-7	89	[Symbol]			Silty SANDY; GRAVEL; dark greenish gray; 16% non-plastic silt w/ traces of coarse and medium sand; 12% fine sand; 53% angular to sub-angular gravel; VERY DENSE.	2	2	2																				
	SS-8	100	[Symbol]	GM			50							39				2.64											
11	SS-9	NR	[Symbol]				50																						
12	CR-1	89	[Symbol]		0																								
13	CR-2	85	[Symbol]	ST	50	Tuffaceous SANDSTONE; light brown to light gray; contains some pumice clast; moderately weathered; broken; SOFT.	CORING							10	1.62														
14	CR-3	48	[Symbol]		25		CORING																						
15	CR-4	77	[Symbol]		20		CORING																						
16	CR-5	58	[Symbol]		29		CORING																						
17	CR-6	52	[Symbol]		35		CORING																						
18	CR-7	56	[Symbol]	LT	0	Lapilli TUFF; gray to light brown; slightly to moderately weathered; slightly broken; Moderately SOFT.	CORING																						
19	CR-8	44	[Symbol]		16		CORING																						
20	CR-9	85	[Symbol]	ST	70	SANDSTONE; brownish gray; coarse grained; slightly broken; Moderately SOFT. (END OF BOREHOLE (20.00))	CORING																						

BASIC TECHNOLOGY AND MANAGEMENT CORPORATION
 2nd Floor Prudential Bank Building,
 1377 A. Mabini St., Ermita, Manila

MACHINE: **ACKER ACE**
 DRILLER: **E. RIEZA**
 SUPERVISOR: **M. ESTAURA**

LEGEND:
 [Symbol] SS - SPLIT SPOON SAMPLE
 [Symbol] WS - WASH SAMPLE
 [Symbol] UDS - UNDISTURBED SAMPLE
 [Symbol] CR - CORE SAMPLE
 [Symbol] * WI - HYDROMETER ANALYSIS

図5-3-3 (87/221) 柱状図 (フェーズI実施分)

FINAL BOREHOLE LOG AND SUMMARY OF TEST RESULTS MLW - 5

PROJECT: Pasig-Marikina River Channel Imp. Proj. GROUND ELEV. (MLLW = Zero Datum) + 11.990 DEPTH OF WATER: 1.68 m

LOCATION: Caniogan, Pasig City STATION NO.: 1 + 825 DATE MEASURED: 03 Mar. 2001

BH NO: BMLW-5 DATE DRILLED: 02 - 05 March 2001 WEATHER: FAIR TIME MEASURED: 4:00 PM

COORDINATES: 1611518.655 N, 507942.100 E

DEPTH, m	SAMPLE NO.	RECOVERY (%) SAMPLE	LOG SYMBOL	CLASSIFICATION	RQD	DESCRIPTION	BLOWS (SPT)			STANDARD PENETRATION TEST (SPT) (N-VALUE)					NATURAL MOIST. CONTENT, %	TOTAL UNIT WEIGHT, g/cc	ATTERBERG LIMITS		SPECIFIC GRAVITY	UNCONFINED COMP. TEST		SIEVE ANALYSIS % PASSING SIEVE					
							15 cm	15 cm	15 cm	10	20	30	40	50			LIQUID LIMIT, %	PLASTICITY INDEX, %		STRENGTH kg/cm ²	STRAIN %, %	4	10	40	200		
1	SS-1	78	[Symbol]	SC		Silty SAND; gray; 34% non-plastic silt with little amount of medium sand; 65% fine sand; VERY LOOSE.	1	1	1							50			2.63				100	99	3		
2	SS-2	89	[Symbol]				1	2	2																		
3	SS-3	100	[Symbol]				2	2	2							67	70	46	2.60				100	99	97	94	
4	SS-4	100	[Symbol]	CH		Sandy CLAY; gray; little amount of coarse and medium sand; 3-10% fine sand; 89-94% high plasticity clay; SOFT TO FIRM.	2	3	3													Cc 0.540	Pc 1.200				
5	UDS-1	100	[Symbol]				PRESSED									57	1.52	61	40	2.60		0.638	5.143		100	99	81
6	SS-5	78	[Symbol]			Sandy CLAY; brown; little amount of coarse sand; 9% medium sand; 37% fine sand; 52% high plasticity clay. STIFF TO HARD.	5	2	10																		
7	SS-6	91	[Symbol]				19	41	9/3							53		72	47	2.62				100	98	89	5
8	CR-1	52	[Symbol]		0	Fine TUFF; light brown; highly weathered; broken interbedded with coarse-grained sandstone and siltstone; SOFT To Moderately HARD.	CORING																				
9	CR-2	38	[Symbol]	Tf	23		CORING									16	1.40					37.175	2.205				
10	CR-3	49	[Symbol]		36		CORING																				
11	CR-4	49	[Symbol]	ST	13	Tuffaceous SANDSTONE; brownish gray to gray; moderately weathered; interbedded with siltstone and medium-grained sandstone; Moderately HARD.	CORING																				
12	CR-5	77	[Symbol]		38		CORING									21	1.48					9.850	13.50				
13	CR-6	51	[Symbol]	Tf	23	Fine TUFF; light brown; moderately weathered; Moderately HARD.	CORING									14	1.65					62.881	2.174				
14	CR-7	32	[Symbol]		0	Tuffaceous SANDSTONE; light brown; highly weathered; contains great amount of volcanic clast; Moderately HARD.	CORING																				
15	CR-8	34	[Symbol]	ST	10	Tuffaceous SANDSTONE; gray; moderately weathered; contains great amount of gravel-sized volcanic clast; broken; Moderately HARD.	CORING																				
16	CR-9	33	[Symbol]		19		CORING																				
17						END OF BOREHOLE (16.00 m)																					







 BASIC TECHNOLOGY AND MANAGEMENT CORPORATION 2nd Floor Prudential Bank Building, 1377 A. Mabini St., Ermita, Manila	MACHINE: <u>ACKER ACE</u> DRILLER: <u>A. TENERIFE</u> SUPERVISOR: <u>M. VILLAFUERTE</u>	LEGEND:  SS - SPLIT SPOON SAMPLE  WS - WASH SAMPLE  UDS - UNDISTURBED SAMPLE  CR - CORE SAMPLE  W/ - HYDROMETER ANALYSIS
---	---	---

図5-3-3 (88/221) 柱状図 (フェーズI実施分)

FINAL BOREHOLE LOG AND SUMMARY OF TEST RESULTS MLW - 6a

PROJECT: Pasig-Marikina River Channel Imp. Proj.
 LOCATION: Maybunga, Pasig City
 BMLW-6 DATE DRILLED: 16 - 17 March 2001

GROUND ELEV. (MLLW = Zero Datum) + 11.256
 STATION NO.: 2 + 450
 WEATHER: FAIR
 COORDINATES: 1612022.100 N, 508267.750 E

DEPTH OF WATER: 3.00 m
 DATE MEASURED: 16 Mar. 2001
 TIME MEASURED: 10:00 AM

SAMPLE NO.	RECOVERY (%)	SAMPLE LOG SYMBOL	CLASSIFICATION	ROD	DESCRIPTION	BLOWS (SPT)			STANDARD PENETRATION TEST (SPT) (N-VALUE)					NATURAL MOIST. CONTENT, %	TOTAL UNIT WEIGHT, g/cc	ATTERBERG LIMITS		SPECIFIC GRAVITY	UNCONFINED COMP. TEST		SIEVE ANALYSIS							
						15 cm	15 cm	15 cm	10	20	30	40	50			LIQUID LIMIT, %	PLASTICITY INDEX, %		STRENGTH kg/cm ²	STRAIN %, %	4	10	40	20				
1	89	[Symbol]	CH		Silty CLAY; dark gray; contains 8% fine to medium sand; 92% high plasticity clay; STIFF TO VERY SOFT.	3	4	5						34	69	46	2.60											
2	89	[Symbol]			Sandy CLAY; dark gray; contains little amount of medium sand; 36% fine sand; 59% high plasticity clay; SOFT.	1	1	1																				
3	89	[Symbol]				2	2	2						43	53	32	2.61					99	98	95	54			
4	89	[Symbol]	SM		Silty SAND; dark gray; 20% non-plastic silt; 13% medium sand; 67% fine sand; MEDIUM DENSE TO LOOSE.	3	6	6						30			2.63							100	87	21		
5	89	[Symbol]				4	3	2																				
6	89	[Symbol]				1	1	1						43	72	49	2.60						99	98	97	91		
7	89	[Symbol]				1	1	1																				
8	89	[Symbol]				1	1	1																				
9	89	[Symbol]				1	1	2						49	73	44	2.60						100	99	99	91		
10	89	[Symbol]				3	3	4																				
11	89	[Symbol]				2	3	3																				
12	89	[Symbol]	CH		Silty CLAY; dark gray to brown; 89-98% high plasticity clay with 1-11% fine to medium sand; presence of shell fragments; SOFT TO VERY STIFF.	3	4	7						38	73	52	2.60						100	99	98	81		
13	89	[Symbol]				2	3	3																				
14	89	[Symbol]				4	4	5																				
15	89	[Symbol]				6	10	12						29	61	40	2.60						99	99	99	91		
16	89	[Symbol]				10	12	13																				
17	89	[Symbol]				5	7	7																				
18	89	[Symbol]				8	9	9						34	72	46	2.60						100	99	96	91		
19	89	[Symbol]				5	5	7																				
20	89	[Symbol]				8	11	17																				

BTA BASIC TECHNOLOGY AND MANAGEMENT CORPORATION
 2nd Floor Prudential Bank Building,
 1377 A. Mabini St., Ermita, Manila

MACHINE: ACKER ACE
 DRILLER: E. RIEZA
 SUPERVISOR: M. VILLAFUERTE

LEGEND:
 [Symbol] SS - SPLIT SPOON SAMPLE
 [Symbol] WS - WASH SAMPLE
 [Symbol] UDS - UNDISTURBED SAMPLE
 [Symbol] CR - CORE SAMPLE
 [Symbol] * W/ HYDROMETER ANALYSIS

FINAL BOREHOLE LOG AND SUMMARY OF TEST RESULTS **MLW - 6b**

PROJECT: Pasig-Marikina River Channel Imp. Proj. GROUND ELEV. (MLLW = Zero Datum) + 11.256 DEPTH OF WATER: 3.00 m
 LOCATION: Maybunga, Pasig City STATION NO.: 2 + 450 DATE MEASURED: 16 Mar. 2001
 BOREHOLE NO.: BMLW-6 DATE DRILLED: 16 - 17 March 2001 WEATHER: FAIR TIME MEASURED: 10:00 AM
 COORDINATES: 1612022.100 N, 508267.750 E

DEPTH, m	SAMPLE NO.	RECOVERY (%) SAMPLE	LOG SYMBOL	CLASSIFICATION	RQD	DESCRIPTION	BLOWS (SPT)			STANDARD PENETRATION TEST (SPT) (N-VALUE)					NATURAL MOIST. CONTENT, %	TOTAL UNIT WEIGHT, g/cc	ATTERBERG LIMITS		SPECIFIC GRAVITY	UNCONFINED COMP. TEST		SIEVE ANALYSIS % PASSING SIEVE						
							15 cm	15 cm	15 cm	10	20	30	40	50			LIQUID LIMIT, %	PLASTICITY INDEX, %		STRENGTH kg/cm ²	STRAIN %	4	10	40	200			
21	SS-21	89	[Symbol]	CH		Silty CLAY; dark gray to brown; 99% high plasticity clay; HARD.	14	22	28						24	83	60	2.60								100	98	
22	SS-22	68	[Symbol]				16	24	26 14																			
23	SS-23	70	[Symbol]				17	23	27 13							22	78	50	2.60									100
23						END OF BOREHOLE (22.98 m)																						
24																												
25																												
26																												
27																												
28																												
29																												
30																												
31																												
32																												
33																												
34																												
35																												
36																												
37																												
38																												
39																												
40																												



BASIC TECHNOLOGY AND MANAGEMENT CORPORATION
 2nd Floor Prudential Bank Building,
 1377 A. Mabini St., Ermita, Manila

MACHINE: ACKER ACE
 DRILLER: E. RIEZA
 SUPERVISOR: M. VILLAFUERTE

- LEGEND:
- SS - SPLIT SPOON SAMPLE
 - WS - WASH SAMPLE
 - UDS - UNDISTURBED SAMPLE
 - CR - CORE SAMPLE
 - * W/ HYDROMETER ANALYSIS

図5-3-3 (90/221) 柱状図 (フェーズI実施分)

FINAL BOREHOLE LOG AND SUMMARY OF TEST RESULTS **MLW - 7a**

PROJECT: **Pasig-Marikina River Channel Imp. Proj.**
 LOCATION: **Maybunga, Pasig City**
 BOREHOLE NO.: **BMLW-7** DATE DRILLED: **14 - 15 February 2001**

GROUND ELEV. (MLLW = Zero Datum) **+ 10.548**
 STATION NO.: **2 + 950**
 WEATHER: **FAIR**

DEPTH OF WATER: **2.70** m
 DATE MEASURED: **14 Feb. 2001**
 TIME MEASURED: **7:00 AM**

COORDINATES: **1612393.100** N, **508621.100** E

SAMPLE NO.	RECOVERY (%) SAMPLE	LOG SYMBOL	CLASSIFICATION	RQD	DESCRIPTION	BLOWS (SPT)			STANDARD PENETRATION TEST (SPT) (N-VALUE)					NATURAL MOIST. CONTENT, %	TOTAL UNIT WEIGHT, g/cc	ATTERBERG LIMITS		SPECIFIC GRAVITY	UNCONFINED COMP. TEST		SIEVE ANALYSIS % PASSING SIEVE			
						15 cm	15 cm	15 cm	10	20	30	40	50			LIQUID LIMIT, %	PLASTICITY INDEX, %		STRENGTH kg/cm ²	STRAIN %	4	10	40	200
1 SS-1	89	[Symbol]	CH		Gravelly Sandy CLAY; dark gray; 10% fine sand; 7% gravel; 81% high plasticity clay; VERY SOFT.	1	0	0						63		66	42	2.62			93	92	91	81
2 SS-2	89	[Symbol]				1	0	0																
3 SS-3	89	[Symbol]	SM		Gravelly Silty SAND; greenish to dark gray; 13% sub-angular gravel; 23% non-plastic silt; 14% coarse sand, 28% medium sand; 22% fine sand; MEDIUM DENSE.	6	9	12						54				2.64			87	73	45	23
4 SS-4	89	[Symbol]				6	9	10																
5 SS-5	89	[Symbol]				5	6	3																
6 SS-6	89	[Symbol]			Sandy CLAY; dark gray; 17% medium sand; 18% fine sand w/ traces of coarse sand and decayed wood; 58% high plasticity clay; SOFT.	2	1	2						55		57	35	2.62			100	93	76	58
7 UDS-1	89	[Symbol]			Silty CLAY; dark gray; 87-93% high plasticity clay with traces of fine sand; SOFT.	PRESSED								62	1.46	62	36	2.60	0.1026	10.857	99	98	97	93
8 UDS-2	100	[Symbol]				PRESSED								50	1.57	56	35	2.60	1.099	2.286	96	95	94	87
9 UDS-3	100	[Symbol]	CH		Sandy CLAY; dark gray; 10% fine sand; 81% high plasticity silty clay. VERY SOFT.	PRESSED								65	1.68	66	44	2.61	1.085	5.714	98	94	91	81
10 SS-7	89	[Symbol]				4	3	4																
11 SS-8	89	[Symbol]			Silty CLAY; dark gray; 98% high plasticity silty clay; FIRM.	5	3	8																
12 SS-9	89	[Symbol]				2	2	3						44		88	67	2.60			100	99	98	
13 SS-10	89	[Symbol]				3	3	2																
14 SS-11	89	[Symbol]				3	3	6						34		57	35	2.62			100	99	49	
15 SS-12	89	[Symbol]	SC		Clayey Sand; dark gray; 49% high plasticity clay; 50% fine sand; MEDIUM DENSE.	8	8	15																
16 SS-13	89	[Symbol]				7	9	12																
17 SS-14	89	[Symbol]				7	7	10																
18 SS-15	89	[Symbol]				8	9	13						35		40	19	2.63			96	89	65	46
19 SS-16	89	[Symbol]	SM		Clayey Silty SAND; dark gray; 46% low plasticity clayey silt; 24% medium sand, 19% fine sand with little amount of coarse sand and gravel; MEDIUM DENSE To DENSE.	22	17	21																
20 SS-17	67	[Symbol]				10	6	8																

BASIC TECHNOLOGY AND MANAGEMENT CORPORATION
 2nd Floor Prudential Bank Building,
 1377 A. Mabini St., Ermita, Manila

MACHINE: **ACKER ACE**
 DRILLER: **E. RIEZA**
 SUPERVISOR: **M. VILLAFUERTE**

LEGEND:
 [Symbol] SS - SPLIT SPOON SAMPLE
 [Symbol] WS - WASH SAMPLE
 [Symbol] UDS - UNDISTURBED SAMPLE
 [Symbol] CR - CORE SAMPLE
 [Symbol] * W/ HYDROMETER ANALYSIS

FINAL BOREHOLE LOG AND SUMMARY OF TEST RESULTS **MLW - 7b**

PROJECT: Pasig-Marikina River Channel Imp. Proj.
 LOCATION: Maybunga, Pasig City
 ID NO: BMLW-7 DATE DRILLED: 14 - 15 February 2001

GROUND ELEV. (MLLW = Zero Datum) + 10.548
 STATION NO.: 2 + 950
 WEATHER: **FAIR**

DEPTH OF WATER: 2.70 m.
 DATE MEASURED: 14 Feb. 2001
 TIME MEASURED: 7:00 AM

COORDINATES: 1612393.100 N, 508621.100 E

SAMPLE NO.	RECOVERY (%)	LOG SYMBOL	CLASSIFICATION	RQD	DESCRIPTION	BLOWS (SPT)			STANDARD PENETRATION TEST (SPT)					NATURAL MOIST. CONTENT, %	TOTAL UNIT WEIGHT, g/cc	ATTERBERG LIMITS		SPECIFIC GRAVITY	UNCONFINED COMP. TEST		SIEVE ANALYSIS % PASSING SIEVE				
						15 cm	15 cm	15 cm	(N-VALUE)							LIQUID LIMIT, %	PLASTICITY INDEX, %		STRENGTH kg/cm ²	STRAIN W, %	4	10	40	200	
1 SS-18	67				Silty Gravelly SAND; dark brown; 14% non-plastic silt; 31% rounded to sub-rounded gravel; 24% medium sand with 31% coarse and fine sand; DENSE.	15	14	24	10	20	30	40	50	15				2.64		69	53	29	14		
2 SS-19	89					7	10	14																	
3 SS-20	75		SM			11	27	23																	
4 SS-21	56					Silty Gravelly SAND; light brown to reddish brown; 12% non-plastic silt; 26% gravel; 62% coarse to fine sand; VERY DENSE.	27	25	25						16				2.64		74	54	27	12	
5 SS-22	56						22	26	24																
6					END OF BOREHOLE (25.00 m)																				
7																									
8																									
9																									
10																									
11																									
12																									
13																									
14																									
15																									
16																									
17																									
18																									
19																									
20																									

BASIC TECHNOLOGY AND MANAGEMENT CORPORATION
 2nd Floor Prudential Bank Building,
 1377 A. Mabini St., Ermita, Manila

MACHINE: ACKER ACE
 DRILLER: E. RIEZA
 SUPERVISOR: M. VILLAFUERTE

LEGEND:
 SS - SPLIT SPOON SAMPLE
 WS - WASH SAMPLE
 UDS - UNDISTURBED SAMPLE
 CR - CORE SAMPLE
 W/HYDROMETER ANALYSIS

図5-3-3 (92/221) 柱状図 (フェーズI実施分)

FINAL BOREHOLE LOG AND SUMMARY OF TEST RESULTS **MLW - 8a**

PROJECT: Pasig-Marikina River Channel Imp. Proj.

LOCATION: Rosario, Pasig City

BH NO: BMLW-8 DATE DRILLED: 11 - 13 February 2001

GROUND ELEV. (MLLW = Zero Datum) + 9.425

STATION NO.: 3 + 450

WEATHER: FAIR

DEPTH OF WATER: 2.00

DATE MEASURED: 11 Feb. 2001






TIME MEASURED: 4:00 PM

COORDINATES: 1612863.650 N, 508796.100 E

SAMPLE NO.	RECOVERY (%) SAMPLE	LOG SYMBOL	CLASSIFICATION	RQD	DESCRIPTION	BLOWS (SPT)			STANDARD PENETRATION TEST (SPT)					NATURAL MOIST. CONTENT, %	TOTAL UNIT WEIGHT, g/cc	ATTERBERG LIMITS		SPECIFIC GRAVITY	UNCONFINED COMP. TEST		SIEVE ANALYSIS % PASSING SIEV			
						15 cm	15 cm	15 cm	(N-VALUE)							LIQUID LIMIT, %	PLASTICITY INDEX, %		STRENGTH kg/cm ²	STRAIN W, %	4	10	40	200
1 SS-1	67	[Symbol]	CH		Sandy CLAY; dark gray; 28-39% fine sand; 54-71% high plasticity clay with little amount of medium sand; VERY SOFT.	1	0	0	10	20	30	40	50	80		58	38	2.61			100	99	7	
2 SS-2	89	[Symbol]	CH		Sandy CLAY; dark gray; 5% medium sand; 78% high plasticity clay; trace of gravel; contains little amount of coarse and fine sand. VERY STIFF TO FIRM.	1	0	0						73				2.62			100	97	93	5
3 SS-3	67	[Symbol]	GC		Clayey GRAVEL; dark gray; 33% medium plasticity clay; 66% sub-angular gravel; LOOSE.	6	8	9								57	33	2.62	Cc 0.250	Pc 1.150	94	90	85	7
4 SS-4	78	[Symbol]	GC			2	2	4						41										
5 UDS-1	89	[Symbol]				PRESSED								20	1.84		2.66			34	34	34	3	
6 UDS-2	89	[Symbol]			Silty CLAY; dark gray; 96% high plasticity clay with little amount of fine to medium sand; FIRM.	PRESSED								66	1.48	69	45	2.60	Cc 1.090	Pc 2.550				
7 SS-5	89	[Symbol]	CH		Sandy CLAY; dark gray, 15% fine sand; 85% high plasticity clay; FIRM.	2	3	3											Cc 0.435	Pc 1.300				
8 UDS-3	89	[Symbol]				PRESSED								43	1.59	56	33	2.60			100	98	8	
9 SS-6	89	[Symbol]	CH		Silty CLAY; dark gray to brownish gray; 91-99% high plasticity clay; contains little amount of fine to medium sand; presence of shell fragments; STIFF TO FIRM.	3	6	6						76		69	37	2.60			100	98	96	9
10 SS-7	89	[Symbol]	CH			3	3	4																
11 SS-8	89	[Symbol]	CH			3	3	4																
12 SS-9	89	[Symbol]	CH			2	3	3						48		69	41	2.60			100	99	9	
13 SS-10	89	[Symbol]	CH			3	3	4																
14 SS-11	89	[Symbol]	CH			4	6	9																
15 SS-12	89	[Symbol]	CH			9	9	12						42		65	35	2.60			100	99	9	
16 SS-13	89	[Symbol]	CH		Silty CLAY; brownish gray; 90-97% high plasticity clay; contains little amount of fine to medium sand; presence of shell fragments; VERY STIFF.	6	7	9																
17 SS-14	89	[Symbol]	CH			9	13	15																
18 SS-15	89	[Symbol]	CH			7	8	11						36		77	45	2.60			100	99	9	
19 SS-16	89	[Symbol]	CH			6	10	11																
20 SS-17	67	[Symbol]	CH			7	10	12																

BASIC TECHNOLOGY AND MANAGEMENT CORPORATION
 2nd Floor Prudential Bank Building,
 1377 A. Mabini St., Ermita, Manila

MACHINE: ACKER ACE
 DRILLER: E. RIEZA
 SUPERVISOR: M. VILLAFUERTE

LEGEND:
 SS - SPLIT SPOON SAMPLE
 WS - WASH SAMPLE
 UDS - UNDISTURBED SAMPLE
 CR - CORE SAMPLE
 W/ HYDROMETER ANALYSIS

FINAL BOREHOLE LOG AND SUMMARY OF TEST RESULTS **MLW - 8b**

PROJECT: Pasig-Marikina River Channel Imp. Proj.

GROUND ELEV. (MLLW = Zero Datum) + 9.425

DEPTH OF WATER: 2.00 m

LOCATION: Rosario, Pasig City

STATION NO.: 3 + 450

DATE MEASURED: 11 Feb. 2001

BH NO: BMLW-8 DATE DRILLED: 11 - 13 February 2001

WEATHER: FAIR

TIME MEASURED: 4:00 PM

COORDINATES: 1612863.650 N, 508796.100 E

SAMPLE NO.	RECOVERY (%)	LOG SYMBOL	CLASSIFICATION	RQD	DESCRIPTION	BLOWS (SPT)			STANDARD PENETRATION TEST (SPT)					NATURAL MOIST. CONTENT, %	TOTAL UNIT WEIGHT, g/cc	ATTERBERG LIMITS		SPECIFIC GRAVITY	UNCONFINED COMP. TEST		SIEVE ANALYSIS			
						15 cm	15 cm	15 cm	(N-VALUE)							LIQUID LIMIT, %	PLASTICITY INDEX, %		STRENGTH kg/cm ²	STRAIN %	4	10	40	200
21	SS-18	89			Silty CLAY; brown to grayish brown; 86-94% high plasticity clay; contains little amount of sub-rounded gravel and fine sand; STIFF TO VERY STIFF.	14	5	8							36	70	39	2.61			94	92	90	86
22	SS-19	89				5	8	8																
23	SS-20	89	CH			5	7	7																
24	SS-21	78				5	4	7							44	69	37	2.61			97	96	96	94
25	SS-22	78				8	8	8																
26	SS-23	78			7	9	10																	
27	SS-24	78	ML		Sandy SILT; gray; 44% fine sand; 54% slightly plastic silty fines; HARD.	10	17	26						28			2.62			100	99	98	54	
28	SS-25	100	CH		Sandy CLAY; greenish gray; 12% fine sand; 84% medium to high plasticity clay with shell fragments; VERY STIFF.	9	9	12						28	59	34	2.61			98	97	96	84	
29					END OF BOREHOLE (28.00 m)																			
30																								
31																								
32																								
33																								
34																								
35																								
36																								
37																								
38																								
39																								
40																								

BTA BASIC TECHNOLOGY AND MANAGEMENT CORPORATION
 2nd Floor Prudential Bank Building,
 1377 A. Mabini St., Ermita, Manila

MACHINE: _____
 DRILLER: _____
 SUPERVISOR: _____






LEGEND:
 SS - SPLIT SPOON SAMPLE
 WS - WASH SAMPLE
 UDS - UNDISTURBED SAMPLE
 CR - CORE SAMPLE
 W/ HYDROMETER ANALYSIS

図5-3-3 (94/221) 柱状図 (フェーズI実施分)

FINAL BOREHOLE LOG AND SUMMARY OF TEST RESULTS MLW - 9

PROJECT: Pasig-Marikina River Channel Imp. Proj.
LOCATION: Rosario Bridge, Pasig City
BH NO: BMLW-9 **DATE DRILLED:** 09 - 10 February 2001

GROUND ELEV. (MLLW = Zero Datum) + 10.475
DEPTH OF WATER: 1.00
STATION NO.: 4 + 250
DATE MEASURED: 09 Feb. 2001
WEATHER: FAIR
TIME MEASURED: 2:00 PM
COORDINATES: 1613659.850 N, 508831.100 E

DEPTH, m	SAMPLE NO.	RECOVERY (%) SAMPLE	LOG SYMBOL	CLASSIFICATION	RQD	DESCRIPTION	BLOWS (SPT)			STANDARD PENETRATION TEST (SPT) (N-VALUE) 10 20 30 40 50	NATURAL MOIST. CONTENT, %	TOTAL UNIT WEIGHT, g/cc	ATTERBERG LIMITS		SPECIFIC GRAVITY	UNCONFINED COMP. TEST		SIEVE ANALYSIS % PASSING SIEV			
							15 cm	15 cm	15 cm				LIQUID LIMIT, %	PLASTICITY INDEX, %		STRENGTH kg/cm ²	STRAIN N, %	4	10	40	200
1	SS-1	67				Sandy CLAY; gray; 10-28% fine sand; 71-88% high plasticity clay; VERY SOFT.	1	0	0		71	72	48	2.61							
2	SS-2	67					1	0	0												
3	SS-3	67					1	0	0		73	70	49	2.60			100	99	98	8	
4	SS-4	89				Sandy CLAY; gray to dark gray; traces of coarse sand; 7-13% medium sand; 4-32% fine sand, 52-83% high plastic clay; SOFT TO FIRM.	1	1	2		57			2.62			99	97	84	7	
5	SS-5	78					6	6	7												
6	SS-6	100					1	2	2		74	73	46	2.61			99	94	87	8	
7	UDS-1	100		CH			PRESSED				C 52 kpa				Cc 0.470	Pc 1.040					
8	UDS-2	100				Silty CLAY; dark gray; 12-16% coarse to fine sand; 2-10% sub-angular gravel and gravel-sized shell fragments; 78-82% high plasticity clay; FIRM TO STIFF.	PRESSED				50	1.56	56	30	2.61			90	84	80	7
9	SS-7	100					2	3	4												
10	SS-8	89					3	3	6												
11	SS-9	100					3	5	8		46	78	56	2.60			100	99	9		
12	SS-10	89				Silty CLAY; greenish gray to grayish to brown; 97% high plasticity clay with little amount of fine sand; STIFF.	4	5	6												
13	SS-11	89					5	6	8												
14	SS-12	100					50, 10														
15	CR-1	91		ST	34	SANDSTONE; light grayish brown; moderately to highly weathered; generally broken; HARD	CORING				17	1.57				41.799	1.359				
16	SS-13	100		SM SW	0	Gravelly Silty SAND; gray; 13% angular gravel; 22% non-plastic silt; 26% medium sand; 30% fine sand w/ traces of coarse sand; VERY DENSE.	CORING				49			2.64			87	78	52	2	
17	CR-3	89		ST	25	SANDSTONE; light grayish brown; moderately to highly weathered; generally broken; SOFT.	CORING				23	1.50				19.900	2.059				
18	CR-4	67			0		CORING														
19							CORING														
20	CR-5	21		SS	12	SILTSTONE; light gray; highly weathered; generally broken; HARD.	CORING				22	1.49					66.441	2.688			

END OF BOREHOLE (20.00 m)

BASIC TECHNOLOGY AND MANAGEMENT CORPORATION
 2nd Floor Prudential Bank Building,
 1377 A. Mabini St., Ermita, Manila

MACHINE: ACKER ACE
DRILLER: E. RIEZA
SUPERVISOR: M. VILLAFUERTE

LEGEND:

- SS - SPLIT SPOON SAMPLE
- WS - WASH SAMPLE
- UDS - UNDISTURBED SAMPLE
- CR - CORE SAMPLE
- W/ HYDROMETER ANALYSIS

FINAL BOREHOLE LOG AND SUMMARY OF TEST RESULTS **MLW - 10**

PROJECT: **Pasig-Marikina River Channel Imp. Proj.**
 LOCATION: **Rosario, Pasig City**
 BOREHOLE NO: **BMLW-10** DATE DRILLED: **08 - 09 February 2001**

GROUND ELEV. (MLLW = Zero Datum) **+ 10.202**
 STATION NO.: **4 + 500**
 WEATHER: **FAIR**

DEPTH OF WATER: **2.60** m
 DATE MEASURED: **02 Mar. 2001**
 TIME MEASURED: **1:00 PM**

COORDINATES: **1613908.500** N, **508788.750** E

DEPTH, m	SAMPLE NO.	RECOVERY (%)	LOG SYMBOL	CLASSIFICATION	RQD	DESCRIPTION	BLOWS (SPT)			STANDARD PENETRATION TEST (SPT)					NATURAL MOIST. CONTENT, %	TOTAL UNIT WEIGHT, g/cc	ATTERBERG LIMITS		SPECIFIC GRAVITY	UNCONFINED COMP. TEST		SIEVE ANALYSIS % PASSING SIEVE			
							15 cm	15 cm	15 cm	(N-VALUE)							LIQUID LIMIT, %	PLASTICITY INDEX, %		STRENGTH kg/cm ²	STRAIN %	4	10	40	200
1	SS-1	89		ML		Sandy SILT; gray; 13% sub-angular gravel; traces of coarse sand; 10% medium sand; 26% fine sand; 44% non-plastic silt. VERY SOFT to SOFT.	1	0	1	10	20	30	40	50	38	44	17	2.63			87	80	70	4	
2	SS-2	89		SM		Gravelly Silty SAND; gray; 29% gravel; 34% non-plastic silt; 15% coarse sand; 11% medium sand; 11% fine sand; LOOSE.	1	2	2																
3	SS-3	89					1	2	3						27	43	16	2.64			71	56	45	3	
4	SS-4	89					3	2	2																
5	SS-5	89					3	2	3																
6	SS-6	89				Sandy CLAY; gray to brownish gray; 90-92% high plasticity clay with 8-10% sand; SOFT to STIFF.	2	3	3						52	68	40	2.60			100	99	95	9	
7	SS-7	89		CH			2	2	3																
8	SS-8	89					2	3	3																
9	SS-9	89					4	3	3						61	78	49	2.60			100	99	98	9	
10	SS-10	89					4	6	6																
11	SS-11	89				Sandy CLAY; brownish gray; 86% high plasticity clay; 12% sand with very little amount of gravel; VERY STIFF.	3	5	10																
12	SS-12	89					6	10	13						44	85	58	2.60			98	96	94	8	
13	SS-13	89		SM SW		Gravelly Silty SAND; grayish brown; 16% angular gravel; 33% non-plastic silt; 7% coarse sand; 20% medium sand; 24% fine sand; DENSE.	9	15	21						27			2.63			84	77	57	3	
14	SS-14	100		CH		Sandy CLAY; grayish brown; 13% medium sand; 23% fine sand with little amount of coarse sand; 62% high plasticity clay; HARD.	16	28	22/5						24	59	37	2.61			100	98	85	6	
15	SS-15	78		SM		Silty SAND; grayish brown; 23% angular gravel; 22% non-plastic silt; 21% coarse sand; 20% medium sand; 14% fine sand; VERY DENSE.	40	50/3							30			2.64			77	56	36	2	
16	CR-1	45			0		CORING																		
17	CR-2	35			0	Lapilli TUFF; grayish brown; moderately to highly weathered; broken; HARD.	CORING								18	1.68					97.229	4.430			
18	CR-3	44			0		CORING								18	1.74					77.391	32.50			
19	CR-4	52			0		CORING																		
20	CR-5	78			0		CORING																		
						END OF BOREHOLE (20.00 m)																			

BASIC TECHNOLOGY AND MANAGEMENT CORPORATION
 2nd Floor Prudential Bank Building,
 1377 A. Mabini St., Ermita, Manila

MACHINE: **ACKER ACE**
 DRILLER: **J. MADERA**
 SUPERVISOR: **M. VILLAFUERTE**

LEGEND:
 SS - SPLIT SPOON SAMPLE
 WS - WASH SAMPLE
 UDS - UNDISTURBED SAMPLE
 CR - CORE SAMPLE
 W/ - HYDROMETER ANALYSIS

図5-3-3 (96/221) 柱状図 (フェーズI実施分)

FINAL BOREHOLE LOG AND SUMMARY OF TEST RESULTS **MLW - 11**

PROJECT: **Pasig-Marikina River Channel Imp. Proj.**
 LOCATION: **Caniogan, Pasig City**
 H NO: **BMLW-11** DATE DRILLED: **06 - 07 February 2001**

GROUND ELEV. (MLLW = Zero Datum) **+ 9.321**
 STATION NO.: **5 + 000**
 WEATHER: **FAIR**


DEPTH OF WATER: **3.20** m
 DATE MEASURED: **06 Feb. 2001**
 TIME MEASURED: **1:00 PM**

COORDINATES: **1614397.650** N, **508753.650** E

SAMPLE NO.	RECOVERY (%)	LOG SYMBOL	CLASSIFICATION	RQD	DESCRIPTION	BLOWS (SPT)			STANDARD PENETRATION TEST (SPT) (N-VALUE)	NATURAL MOIST. CONTENT, %	TOTAL UNIT WEIGHT, g/cc	ATTERBERG LIMITS		SPECIFIC GRAVITY	UNCONFINED COMP. TEST		SIEVE ANALYSIS % PASSING SIEVE			
						15 cm	15 cm	15 cm				LIQUID LIMIT, %	PLASTICITY INDEX, %		STRENGTH kg/cm ²	STRAIN W, %	4	10	40	200
1	SS-1	89	CH		Sandy CLAY; gray; 10% fine sand with traces of decayed wood; 88% high plasticity clay; VERY SOFT.	1	1	1		52	63	41	2.60			100	99	98	8	
2	SS-2	89		Silty CLAY; dark gray; 99% high plasticity clay; SOFT.	1	2	2													
3	SS-3	89			2	2	2			69	61	33	2.60			100	99	99	9	
4	SS-4	89		Gravelly Sandy CLAY; dark gray; 11% fine to medium sand with 6% gravel; 83% high plasticity clay; SOFT.	2	3	3			79	62	33	2.61			94	93	88	8	
5	CR-1	93	LT	28	Lapilli TUFF; dark brown; gray; slightly to moderately weathered, broken; HARD.	CORING				14	1.65			36.508	1.079					
6	CR-2	55		26		CORING				15	1.74				103.378	3.961				
7	CR-3	60		12		CORING				16	1.74				129.824	3.817				
8	CR-4	70		45		CORING				14	1.83				98.945	2.648				
9	CR-5	60		21		CORING				17	1.72				96.832	3.215				
10	CR-6	56		34		CORING				20	1.66				128.830	3.780				
11	CR-7	30		19		CORING				14	1.71				93.769	3.282				
12	CR-8	35		14		CORING				17	2.22				129.203	3.205				
13	CR-9	17		0		CORING														
14	CR-10	20		0		CORING														
15	CR-11	20		0		CORING														
16					END OF BOREHOLE (15.00 m)															

BTA BASIC TECHNOLOGY AND MANAGEMENT CORPORATION
 2nd Floor Prudential Bank Building,
 1377 A. Mabini St., Ermita, Manila

MACHINE: **ACKER ACE**
 DRILLER: **J. MADERA**
 SUPERVISOR: **M. VILLAFUERTE**

LEGEND:

 SS - SPLIT SPOON SAMPLE
 WS - WASH SAMPLE
 UDS - UNDISTURBED SAMPLE
 CR - CORE SAMPLE
 W/ - HYDROMETER ANALYSIS

FINAL BOREHOLE LOG AND SUMMARY OF TEST RESULTS **MLW - 12**

PROJECT: Pasig-Marikina River Channel Imp. Proj.
 LOCATION: PBM Steel, Mangahan, Pasig City
 BHN NO: BMLW-12 DATE DRILLED: 02 - 05 February 2001

GROUND ELEV. (MLLW = Zero Datum) + 10.868
 STATION NO.: 5 + 500
 WEATHER: FAIR
 COORDINATES: 1614899.500 N, 508770.250

DEPTH OF WATER: 1.20
 DATE MEASURED: 02 Feb. 2001
 TIME MEASURED: 1:00 PM

DEPTH, m	SAMPLE NO.	RECOVERY (%)	LOG SYMBOL	CLASSIFICATION	RQD	DESCRIPTION	BLOWS (SPT)			STANDARD PENETRATION TEST (SPT) (N-VALUE) 10 20 30 40 50	NATURAL MOIST. CONTENT, %	TOTAL UNIT WEIGHT, g/cc	ATTERBERG LIMITS		SPECIFIC GRAVITY	UNCONFINED COMP. TEST		SIEVE ANALYSIS % PASSING SIEVE		
							15 cm	15 cm	15 cm				LIQUID LIMIT, %	PLASTICITY INDEX, %		STRENGTH kg/cm ²	STRAIN %	4	10	40
1	SS-1	89				Silty SAND; brownish gray; contains little amount of medium sand; 12% non-plastic silt; 86% fine sand; VERY LOOSE.	1	1	0		40			2.63						
2	SS-2	89		SM			2	2	2											
3	SS-3	78				Silty Gravelly SAND; brownish gray; 8% non-plastic silt; 35-42% sub-rounded to angular gravel; 2-13% coarse sand; 7-30% medium sand; 14-41% fine sand; DENSE To VERY DENSE.	1	6	29		21			2.65		58	56	49		
4	SS-4	80					17	20	30		19			2.65		65	52	22		
5	SS-5	100		GW		Sandy Gravel; grayish brown; contains 17% sand; 4% non-plastic silt, 79% sub-rounded to sub-angular gravel; VERY DENSE.	17	50	14		16			2.66		21	14	8		
6	CR-1	19			0		CORING													
6	SS-6	100			10	Lapilli TUFF; grayish brown; moderately to highly weathered; broken; HARD.	CORING													
6	CR-2	95					CORING													
7	CR-3	57			44		CORING				22	1.62			49.365	1.834				
8	CR-4	39		LT	0	Lapilli TUFF, grayish brown; moderately weathered; broken; Modertately HARD.	CORING													
9	CR-5	67			10		CORING													
10	CR-6	68			0		CORING													
11	CR-7	36			0	Lapilli TUFF; grayish brown; highly weathered; generally broken; HARD.	CORING													
11	SS-7	67		GM		Silty Sandy GRAVEL; yellowish brown; 19% coarse sand; 20% medium sand with traces of non-plastic silt; 43% sub-angular gravel; VERY DENSE.	26	20	22		36			2.65		57	38	18		
12	SS-8	67		SM		Silty SAND; light brown; 32% non-plastic silt with little amount of sub-angular gravel; 22% medium sand; 33% fine sand and traces of coarse sand; MEDIUM DENSE.	3	6	5											
13	SS-9	67					4	5	7		44			2.63		96	87	65		
14	SS-10	89		GM		Silty Sandy Gravel; yellowish brown; coarse to fine sand; considerable amount of non-plastic silt; angular gravel; MEDIUM DENSE.	9	8	15											
15	SS-11	89		GW			11	10	15											
16	SS-12	100				Silty Sandy Gravel; grayish brown to brown; 37% predo-minantly medium sand; 10% non-plastic silt; 53% tuff gravel; VERY DENSE. (16.60M)	31	37	13		25			2.66		47	34	18		
17	CR-8	100			24		50	5												
17	CR-8	100		Tf			CORING				26	1.66			65.649	1.932				
18	CR-9	89			23	Fine TUFF; gray; moderately weathered; broken; HARD.	CORING				20	1.69			1.246	0.543				
19	CR-10	89			10		CORING													
20	CR-11	89		SS	0	SILTSTONE; greenish gray; highly weathered; SOFT.	CORING													

BASIC TECHNOLOGY AND MANAGEMENT CORPORATION
 2nd Floor Prudential Bank Building,
 1377 A. Mabini St., Ermita, Manila

MACHINE: ACKER ACE
 DRILLER: E. RIEZA
 SUPERVISOR: M. VILLAFUERTE

LEGEND:

 SS - SPLIT SPOON SAMPLE
 WS - WASH SAMPLE
 UDS - UNDISTURBED SAMPLE
 CR - CORE SAMPLE
 W/ HYDROMETER ANALYSIS

図5-3-3 (98/221) 柱状図 (フェーズI実施分)

FINAL BOREHOLE LOG AND SUMMARY OF TEST RESULTS **MLW - 13**

PROJECT: **Pasig-Marikina River Channel Imp. Proj.**
 LOCATION: **Ugong Pasig, Left Side Offshore**
 BOREHOLE NO: **BMLW-13** DATE DRILLED: **01 - 02 Feb. 2001**

GROUND ELEV. (MLLW = Zero Datum) **+ 12.410**
 STATION NO.: **6 + 000**
 WEATHER: **FAIR**
 COORDINATES: **1614959.500 N, 509115.500 E**
 DEPTH OF WATER: **2.80**
 DATE MEASURED: **01 Feb. 2001**
 TIME MEASURED: **3:00 PM**

DEPTH, m	SAMPLE NO.	RECOVERY (%)	LOG SYMBOL	CLASSIFICATION	RQD	DESCRIPTION	BLOWS (SPT)			STANDARD PENETRATION TEST (SPT)					NATURAL MOIST. CONTENT, %	TOTAL UNIT WEIGHT, g/cc	ATTERBERG LIMITS		SPECIFIC GRAVITY	UNCONFINED COMP. TEST		SIEVE ANALYSIS		
							15 cm	15 cm	15 cm	(N-VALUE)							LIQUID LIMIT, %	PLASTICITY INDEX, %		STRENGTH kg/cm ²	STRAIN %	4	10	40
1	SS-1	89	[Symbol]	CH		Sandy CLAY ; dark brownish; gray; 68% high plasticity clay; 15% fine sand and 14% medium sand; STIFF.	5	6	8	10	20	30	40	50	44	56	36	2.61			100	97	83	6
2	SS-2	100	[Symbol]	CL		Sandy CLAY ; grayish brown; 51% medium plasticity clay with 42% fine sand; VERY STIFF.	6	8	14						24	48	26	2.61			100	93		
3	SS-3	89	[Symbol]	SM		Silty SAND ; brown; 37% medium sand; 18% fine sand; 14% coarse sand with 29% non-plastic silt; MEDIUM DENSE.	11	14	16						17			2.63			98	84	47	
4	SS-4	89	[Symbol]	CH		Sandy Silty CLAY ; grayish brown; 91% highly plastic clay; VERY STIFF.	10	13	14						34	54	33	2.60			100	99	96	
5	SS-5	91	[Symbol]	CH		Sandy CLAY ; light brown; 73% high plasticity clay with 13% fine sand and 12% medium sand; HARD.	15	26	24/3						37	59	37	2.61			100	98	86	7
6	SS-6	100	[Symbol]	SM		Silty SAND ; brown; 47% medium sand; 20% fine sand and 11% coarse sand; 20% non-plastic fines; VERY DENSE.	30	50	10						30			2.63			98	87	40	2
7	CR-1	27	[Symbol]		0	SANDSTONE ; light grayish brown; medium to coarse-grained; highly weathered; broken; SOFT.	CORING																	
8	CR-2	28	[Symbol]		0		CORING																	
9	CR-3	45	[Symbol]		40	SANDSTONE ; gray; coarse-grained, moderately weathered; Moderately HARD.	CORING			5	1.51								21.049	1.313				
10	CR-4	30	[Symbol]	ST	0		CORING																	
11	CR-5	21	[Symbol]		0	Tuffaceous SANDSTONE ; light gray; fine to medium grained; moderately to highly weathered; generally broken; Moderately HARD TO SOFT.	CORING																	
12	CR-6	29	[Symbol]		22		CORING			29	1.54								53.649	2.077				
13	CR-7	16	[Symbol]		0		CORING																	
14	CR-8	25	[Symbol]	SS	0	Tuffaceous SILTSTONE ; brown; completely weathered; VERY SOFT.	CORING																	
15	CR-9	15	[Symbol]		0		CORING																	
16						End of Borehole (15.00 m)																		

BASIC TECHNOLOGY AND MANAGEMENT CORPORATION
 2nd Floor Prudential Bank Building,
 1377 A. Mabini St., Ermita, Manila

MACHINE: _____
 DRILLER: _____
 SUPERVISOR: _____

LEGEND:

 SS - SPLIT SPOON SAMPLE
 WS - WASH SAMPLE
 UDS - UNDISTURBED SAMPLE
 CR - CORE SAMPLE
 * W/ HYDROMETER ANALYSIS

図5-3-3 (99/221) 柱状図 (フェーズI実施分)

FINAL BOREHOLE LOG AND SUMMARY OF TEST RESULTS **MLW - 14**

PROJECT: **Pasig-Marikina River Channel Imp. Proj.**
 LOCATION: **Left Side Offshore, Manggahan, Pasig**
 BOREHOLE NO: **BMLW-14** DATE DRILLED: **27 - 29 January 2001**

GROUND ELEV. (MLLW = Zero Datum) **+ 11.414**
 STATION NO.: **6 + 450**
 WEATHER: **FAIR**
 COORDINATES: **1614615.500 N, 509415.750 E**

DEPTH OF WATER: **3.60** m
 DATE MEASURED: **27 Jan. 2001**
 TIME MEASURED: **3:00 PM**

SAMPLE NO.	RECOVERY (%)	LOG SYMBOL	CLASSIFICATION	RQD	DESCRIPTION	BLOWS (SPT)			STANDARD PENETRATION TEST (SPT)					NATURAL MOIST. CONTENT, %	TOTAL UNIT WEIGHT, g/cc	ATTERBERG LIMITS		SPECIFIC GRAVITY	UNCONFINED COMP. TEST		SIEVE ANALYSIS % PASSING SIEVE			
						15 cm	15 cm	15 cm	(N-VALUE)							LIQUID LIMIT, %	PLASTICITY INDEX, %		STRENGTH kg/cm ²	STRAIN %	4	10	40	20
1 SS-1	89		CH		Sandy CLAY; gray; 9-23% fine to medium sand; 76-90% high plasticity clay; FIRM TO STIFF.	5	3	2	10	20	30	40	50	44	57	36	2.61				100	87	76	
2 SS-2	89		CH			5	5	6						44	63	38	2.60			100	99	96	90	
3 SS-3	89		SM		Silty SAND; dark gray; 17% non-plastic silt; 42% medium sand; 35% fine sand with little amount of coarse sand; LOOSE TO MEDIUM DENSE.	2	3	4						39	55	36	2.61					100	77	
4 SS-4	78		SM			4	3	5																
5 SS-5	89		CL		Sandy Clay; dark gray; 17% medium sand with trace of fine sand; contains little amount of coarse sand; 70% medium plasticity clay. FIRM.	7	8	8						21			2.63			100	94	52	17	
6 SS-6	89		CL			5	4	3						61	47	26	2.61			99	95	78	70	
7 SS-7	89		CH			3	3	4						49	68	45	2.60			100	96	90		
8 SS-8	89		CH		Silty CLAY; dark gray to brownish gray; 11% fine sand with little amount of medium sand; 88-93% high plasticity clay; FIRM TO VERY STIFF.	3	4	5																
9 SS-9	89		CH			5	7	7						43	62	38	2.60			100	99	88*		
10 SS-10	89		CH			10	7	7																
11 SS-11	89		CH			9	13	15						39	69	38	2.60			100	99	98	93*	
12 SS-12	89		CH			10	10	16						45	65	44	2.60			100	95	88*		
13 SS-13	89		CH		Silty CLAY; light gray to grayish brown; 88-98% high plasticity clay with traces of medium to fine sand; VERY STIFF.	9	10	9																
14 SS-14	89		CH			8	11	12																
15 SS-15	89		CH			8	10	12						45	89	60	2.60			100	99	98*		
16 SS-16	91		GC		Sandy Clayey GRAVEL; brown; 23% fine sand with traces of medium sand; 32% sub-angular gravel; 37% high plasticity clay; VERY DENSE.	24	35	3						49	62	39	2.64			68	68	60	37	
17 SS-17	57		GC			20	32	5																
18 SS-18	100		ML		Sandy SILT; light brown to brown; 45% fine sand; 53% slightly plastic silt; HARD.	19	33	5						61			2.61			100	98	53*		
19 SS-19	91		SM		Silty SAND; light brown to brown; 52-61% fine sand w/ little amount of medium sand; VERY DENSE.	25	32	3						60			2.63			100	97	45		
20 SS-20	67		SM		End of Borehole (19.85 m)	20	50	15						48			2.63			100	97	36		

BTA BASIC TECHNOLOGY AND MANAGEMENT CORPORATION
 2nd Floor Prudential Bank Building,
 1377 A. Mabini St., Ermita, Manila

MACHINE: **ACKER ACE**
 DRILLER: **J. MADERA**
 SUPERVISOR: **M. ESTAURA**
M. VILLAFUERTE

LEGEND:

 SS - SPLIT SPOON SAMPLE
 WS - WASH SAMPLE
 UDS - UNDISTURBED SAMPLE
 CR - CORE SAMPLE
 W/ - HYDROMETER ANALYSIS

図5-3-3 (100/221) 柱状図 (フェーズI実施分)