

**GOVERNMENT OF THE KINGDOM OF THAILAND
MINISTRY OF INTERIOR
EXPRESSWAY AND RAPID TRANSIT AUTHORITY OF THAILAND**

***Feasibility Study
on
The Second Stage Expressway System
in
The Greater Bangkok***

**FINAL REPORT
VOLUME I : TEXT**

NOVEMBER, 1983

JAPAN INTERNATIONAL COOPERATION AGENCY

SDF

83 136 (2 4)

115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

JICA LIBRARY



1030702[3]

**GOVERNMENT OF THE KINGDOM OF THAILAND
MINISTRY OF INTERIOR
EXPRESSWAY AND RAPID TRANSIT AUTHORITY OF THAILAND**

Feasibility Study

on

The Second Stage Expressway System

in

The Greater Bangkok

**FINAL REPORT
VOLUME I : TEXT**

NOVEMBER, 1983

JAPAN INTERNATIONAL COOPERATION AGENCY

国際協力事業団	
受入 月日 '84. 3. 29	122
登録No. 10156	61.4
	SDF

PREFACE


In response to the request of the Government of the Kingdom of Thailand, the Government of Japan decided to extend technical cooperation in conducting a feasibility study on the Second Stage Expressway System in the Greater Bangkok and entrusted the study to the Japan International Cooperation Agency (JICA). The JICA sent to Thailand a study team headed by Mr. Akira Shikichi which stayed in Bangkok from June 1982 to August 1983 and worked under the guidance of the Supervisory Committee chaired by Mr. Shigeomi Samukawa, Hanshin Expressway Public Corporation.

The team held discussions with the officials concerned of the Government of Thailand on the foregoing system and conducted a field survey in Thailand. Subsequently, further studies were made in Japan and the present report has been prepared.

I hope that this report will serve for the implementation of the system and contribute to the promotion of friendly relations between our two countries.

I wish to express my deep appreciation to the officials concerned of the Government of the Kingdom of Thailand for their close cooperation extended to the team.

November 1983


A handwritten signature in black ink, appearing to read 'Keisuke Arita', is written over a horizontal line.

Keisuke Arita


President

Japan International Cooperation Agency

PERSPECTIVES OF THE SECOND STAGE EXPRESSWAY SYSTEM




MAKKASAN INTERCHANGE





FLYOVER - RAMA IV ROAD


PROJECT LOCATION MAP





LEGEND:

-  SECOND STAGE EXPRESSWAY SYSTEM
-  FIRST STAGE EXPRESSWAY SYSTEM

MAP OF PROJECT AREA



LEGEND :

-  SECOND STAGE EXPRESSWAY SYSTEM
-  FIRST STAGE EXPRESSWAY SYSTEM

SUMMARY AND RECOMMENDATIONS




TABLE OF CONTENTS

1. PROJECT BACKGROUND	S-1
2. STUDY	S-1
2.1 Study Objectives	S-1
2.2 Phasing	S-1
3. FINDINGS AND RECOMMENDATIONS	S-2
3.1 Route Components of the Project	S-3
3.2 Optimum Routes	S-3
3.3 Evaluation of the Expressway Alternatives	S-3
3.4 Future Traffic Volume on the Expressway	S-3
3.5 Estimated Project Cost and Implementation Schedule	S-4
3.6 Economic Indicators	S-6
3.7 Financial Aspects	S-6
3.8 Recommendations	S-7
4. NECESSITY AND EFFECT OF THE PROJECT	S-9
4.1 Necessity of the Project	S-9
4.2 Effect of the Project	S-12
5. GENERAL FEATURES OF THE EXPRESSWAY	S-14
5.1 Main Features	S-14
5.2 Supporting Facilities	S-14

1. PROJECT BACKGROUND

The Greater Bangkok Area has been and will continue to be, the main focus of human activities in the Kingdom, generating social and economic benefits that have important multiplier effects over the rest of the country. The population increase in Bangkok leads to a continuing expansion of the urban area and an intensified land use in the built-up area.

The rapid urban expansion in the Greater Bangkok Area has entailed inevitably various urban problems and these have become increasingly serious especially in the central business district and its fringe areas. Inadequacy of basic infrastructures, inappropriate land use, housing shortage and the great need to improve the transportation network are the main problems.

The necessity to strengthen the road network in the Greater Bangkok Area by providing an expressway network is primarily due to the recent increase in vehicle traffic demand accompanying the development of the area. The First Stage Expressway System was thus planned to link the major highways from the north, the south and the east to relieve the traffic congestion in Bangkok. The Din Daeng-Port and Bang Na-Port sections were opened to traffic in October 1981 and January 1983, respectively. Under such circumstances, it is urgent to develop the Second Stage Expressway System since the road traffic demand in the area is foreseen to be extremely large.



TRAFFIC CONGESTION IN SUKHUMVIT ROAD

2. STUDY

2.1 Study Objectives

The overall objective of the Study is to determine the technical, economic and financial feasibility of, and to prepare an optimum program for, the construction of the Second Stage Expressway System.

2.2 Phasing

The Study Area covers the Greater Bangkok Area (Bangkok, Nonthaburi and Samut Prakan). The Study has been divided into Phase I and Phase II to meet the requirement of the work and time schedule. In general, this comprises as follows:

(1) Phase I Study

Phase I Study essentially consists of the traffic forecast and the screening of the Second Stage Expressway components, and comprises the following works:

- Collection and Analysis of Data;
- Traffic Study;
- Expressway Network Planning and Inception Traffic Assignment;
- Inception Engineering Studies for the Established Second Stage Expressway Network;
- Provisional Cost Estimates;
- Provisional Economic Evaluation; and
- Identification of the High Priority Routes.

(2) Phase II Study

The routes, namely the North-South Route (hereinafter called the “N-S Route”) and the East Route were selected for the feasibility study as a result of Phase I Study.

Briefly, the Phase II Study comprises the following tasks:

- Collection and Analysis of Additional Data;
- Traffic Surveys and Studies;
- Traffic Assignment;
- Finalization of the Route Locations;
- Preliminary Engineering Design;
- Cost Estimates;
- Economic Evaluation;
- Financial Study;
- Foreseeable Economic and Social Impact Studies; and
- Formulation of Implementation Program.

3. FINDINGS AND RECOMMENDATIONS

In the road network of the Greater Bangkok Area, the expressway network forms the backbone, and the Second Stage Expressway System is an integral part of this expressway network. The aims of the Second Stage Expressway System Project (the Project) are:

- Meet the needs of the ever-growing vehicle traffic in the Greater Bangkok Area and facilitate improved traffic flows for the enhancement of urban activities;
- Form a nucleus of a road network for the Greater Bangkok Area together with the existing major roads, and provide connections to the First Stage Expressway System so as to allow a smooth flow of vehicle traffic into and away from the city centers; and
- Manage the expressway network as a tollway system, an efficient way of road system development, which will levy a toll from users who obtain benefits from the utilization of the expressway.

3.1 Route Components of the Project

As a result of the studies executed in the two phases, N-S Route and East Route were selected (Table 1).

TABLE 1 ROUTES COMPRISED IN THE SECOND STAGE EXPRESSWAY SYSTEM

Designation	Length of Route
North-South Route	19.2 km approx.
East Route	8.7 km approx.
Total Length	27.9 km approx.

3.2 Optimum Routes

Among the several alternative route locations for each of the components, the proposed routes were chosen to be subjected to further detailed study and eventually led to four alternative expressway development plans.

3.3 Evaluation of the Expressway Development Alternatives

Evaluation of above mentioned four alternative expressway development plans (Fig. 1) reveals that the most viable development plan is the Alternative R-1. This alternative calls for the construction of the easternmost expressway segment of the East Route to be postponed.




FIG. 1 THE SES ALTERNATIVES

3.4 Future Traffic Volume on the Expressway

- (1) Traffic volume in the expressway network of both the First and Second stage Expressway Systems was forecast as 594 thousand trips per day in 2000. This indicates that the present trips in the First Stage Expressway System will jump 7.4 times, and 13% of all of the trips estimated in the Greater Bangkok Area will use the expressway network.

- (2) The average traffic volume per kilometer in 2000 is estimated as 108,000 vehicles per day. By comparing this with the designed traffic capacity of the expressways, the average congestion rate is calculated to be 60%. An average trip length on the expressways is estimated as 12 km.
- (3) Upon completion of the project, traffic volume on the First Stage Expressway System will increase by 20%. Also the traffic volume on the ordinary roads within the central urbanized area will decrease by about 14% with the completion of the Second Stage Expressway System.
- (4) It is foreseen that the expressway network will be mainly used by passenger cars rather than by trucks and buses (Table 2).

TABLE 2 VEHICLE COMPOSITION IN YEAR 2000

Vehicle Type	Expressway Systems	GBA Road Network
Passenger Car	82.1%	75.8%
Bus	1.5%	1.4%
Light Truck	10.4%	12.9%
Heavy Truck	6.0%	9.9%
Total	100.0%	100.0%

- (5) The estimated traffic volumes on the expressway network in the year 2000 is shown in Fig. 2.
- (6) The result of overall traffic forecast shows that even after the completion of the Second Stage Expressway System there will still remain a traffic problem in the Greater Bangkok Area. Therefore, efforts at strengthening the ordinary road network by appropriate agencies should be continued to avoid the traffic problems which are foreseen in very near future.

3.5 Estimated Project Costs and Implementation Schedule

- (1) The total project costs in 1983 prices and current prices of the Second Stage Expressway System are:
 - 1) ฿ 16,790 million (in 1983 prices) ; and
 - 2) ฿ 26,200 million (1983 prices plus 6% p.a. escalation allowance).
- (2) Following shows the summary of estimated project costs (Table 3) in 1983 prices:

TABLE 3 ESTIMATED PROJECT COST

Designation	Cost in million Baht		
	Foreign Currency Portion	Local Currency Portion	Total
Construction Cost	5,750 (51.6%)	5,380 (48.4%)	11,130 (100%)
Land Acquisition and Compensation Cost	-	3,480	3,480
Contingencies and Others	870 (39.9%)	1,310 (60.1%)	2,180 (100%)
TOTAL	6,620 (39.4%)	10,170 (60.6%)	16,790 (100%)




FIG. 2 ESTIMATED TRAFFIC VOLUMES, IN THE YEAR 2000

- (3) The implementation of the Project requires an extremely large investment. For this reason, and to obtain maximum economic and financial benefit a staged construction approach is recommended as shown in the following figure (Fig. 3).




FIG. 3 RECOMMENDED IMPLEMENTATION SCHEDULE OF THE SECOND STAGE EXPRESSWAY SYSTEM PROJECT

3.6 Economic Indicators

The economic indicators for the Expressway development alternatives are shown as follows (Table 4):

TABLE 4 ECONOMIC ANALYSIS

Development Alternative	Present Worth of Benefit at $i = 12\%$ (in ₦ million)	B/C Ratio at $i = 12\%$	IRR (%)
1) R-1	6,094.2	1.65	17.0
2) ST-2	5,889.0	1.60	16.7
3) R-2	5,015.7	1.52	16.1
4) R-4	4,757.0	1.51	16.0

It is found that the R-1 alternative indicates the highest return while the differences of the return among these plans are quite small. The R-1 is recommended as the SES development plan (Fig. 4).

3.7 Financial Aspects

The cost-revenue relationship was studied under the same basic conditions of the economic analysis together with the recommended toll fare levels (Table 7). Following are the results of the financial analysis of the Alternative R-1 :




FIG. 4 EXPRESSWAY ROUTES AND CONSTRUCTION SEGMENTS

Present Worth of Surplus at $i = 12\%$	Financial Revenue/Cost Ratio at $i = 12\%$	Financial IRR
฿ 0.2 million	1.0	12.0%

Alternative options of the funding schedule are studied as shown below (Table 5). An overall interest charge should be kept at a low level in order to yield surplus under the constraint of the financial return of 12%.

It is recommended that the option (a) or another combination of funds which minimizes the overall interest burden to the debt should be sought. It is forecast that all loans can be paid back by year 2006 if all the estimated cash flow surplus is allocated for the refunding.

TABLE 5 ALTERNATIVE FUNDING SCHEDULE

Finance	Option (a)		Option (b)		Option (c)	
	Percent	Interest	Percent	Interest	Percent	Interest
Government Investment	20 ¹	-	-	-	20	-
Loan A (grace period 10 years) ⁴	40 ²	$i = 3\%$	40	$i = 3\%$	40	$i = 8\%$
Loan B (grace period 5 years) ⁴	40 ³	$i = 12\%$	60	$i = 12\%$	40	$i = 15\%$
Repayable all loans by	2006		2012		non-payable	

- Notes:
1. Equivalent to the percentage of right-of-way acquisition cost.
 2. Equivalent to the percentage of foreign currency component.
 3. Equivalent to the percentage of local currency component.
 4. After the grace period, the repayment over twenty years for Loan A and ten years for Loan B.

3.8 Recommendations

- (1) The Second Stage Expressway System is planned to form an inner ring expressway in the central urbanized area together with the First Stage Expressway System and to provide two trunk radial routes in the core area of the Greater Bangkok Area extending north and east. Thus, the development of the Second Stage Expressway System will not only strengthen the road network in the Greater Bangkok Area, but also greatly increase the use of the First Stage Expressway System.
- (2) The implementation of the construction of the Second Stage Expressway System should be effected at the earliest possible date, before land acquisition and compensations become more difficult due to the extraordinarily rapid development of the urban area, especially within the ring formed by the expressways.
- (3) Delay of implementation would entail increasingly difficult traffic management during construction due to increased traffic congestion in the existing road network and would result in increased construction time and cost.
- (4) The construction of the Second Stage Expressway System requires a large investment. For this reason a staged construction program is recommended, commencing detailed

engineering design early in 1985 and completing the construction of the last priority segment in 1995.

- (5) The priority for construction of the different segments of the Second Stage Expressway System should be as follows, from the viewpoints of land acquisition and compensation as well as by traffic demand (Table 6 and Fig. 3).

TABLE 6 CONSTRUCTION SEGMENT AND PRIORITY

Construction Priority	Construction Segment	Route
1	N-3 and E-1	N-S and East Routes
2	N-2	N-S Route
3	N-1	N-S Route
4	E-2	East Route
5	N-4 and N-5	N-S Route
6	E-3	East Route

- (6) The adoption of a flat tariff system is recommended for the expressway network which comprises the First and Second Stage Expressway Systems. The recommended toll fare levels are shown in Table 7.

TABLE 7 RECOMMENDED TOLL FARE LEVELS

Applicable Expressway	Year	Fare at 1983 Prices	
		Toll Fare in Baht	
		Small Vehicle	Large Vehicle
First Stage Expressway System, 1st and 2nd Legs	1982-1987	10	20
Entire First Stage Expressway System and Second Stage Expressway System Segments Opened by Stage	1988-1995	15	25
Entire First and Second Stage Expressway Systems	After 1996	20	30

4. NECESSITY AND EFFECT OF THE PROJECT

4.1 Necessity of the Project

- (1) To serve and maintain Greater Bangkok as a well functioned capital city, the development of the Second Stage Expressway System is urgently needed (Fig. 5). The result of the Study shows the following socio-economic growth by the year 2000 in the Greater Bangkok Area (Fig. 6).
- The estimated total urbanized area in 2000 is about 1.5 times that of 1982.
 - Although the growth rate has been forecast to taper off somewhat in the future, the population is expected to continue to grow to 8.7 million by 2000; and




FIG. 5 FUTURE LAND USE AND EXPRESSWAY SYSTEMS

- The economy of the Greater Bangkok Area is characterized by the dominance of the tertiary sector. The gross product will expand from 133 billion Baht of 1982 to 280 billion Baht in 2000 in terms of 1972 prices.









Description	1982	2000	Ratio
Urbanized Area	 51,200 hectares	 78,000 hectares	1.52
Population	 6,432,000 persons	 8,726,000 persons	1.36
Gross Provincial Product (at 1972 prices)	 132,700 million Baht	 280,000 million Baht	2.11
Vehicle Trips	 2,223,000 trips/day	 4,425,000 trips/day	1.99

FIG. 6 CHANGES OF SOCIO-ECONOMIC AND TRAFFIC SITUATION IN THE GREATER BANGKOK AREA

- (2) Planned as an integral part of the expressway network in the Greater Bangkok, the Second Stage Expressway System is expected to play the following important roles:
- Maintenance of urban activities by avoiding serious traffic congestions;
 - Breaking a deadlock in road development which is facing a great right-of-way difficulty; and
 - Supplement any to the function of the First Stage Expressway System and the Mass Transit System.
- a) It is foreseen that a continued increase in the vehicular traffic demand will deteriorate further the traffic congestion on the roads which has already reached an intolerable level. Present and future traffic demand in the Greater Bangkok Area is summarized in the following table (Table 8).

TABLE 8 DAILY TRAFFIC DEMAND IN GREATER BANGKOK AREA

Items	1982	2000	2000/1982
Person trips ('000)	8,555	13,260	1.55
Vehicle trips ('000)	2,223	4,425	1.99

- b) In parallel with the development of the First Stage Expressway System, the Government is promoting the strengthening of other road networks in the Greater Bangkok Area. However, a difficulty in right-of-way acquisition is a roadblock in the at-grade road network strengthening/development programme in urbanized areas.
- c) The First Stage Expressway System is planned to link the major highways from the north, the south and the east to relieve the traffic congestion in Bangkok, with a total length of 27 km. However, this expressway system serves only a few corridors without giving access to other important parts of the Greater Bangkok Area. Under the increasing traffic demand in the area, the expansion of the expressway network within the framework of the Second Stage Expressway System is an urgent necessity.

4.2 Effect of the Project

- (1) The development of the Second Stage Expressway System will improve the traffic condition in the Greater Bangkok Area, especially in its central urbanized area. Accordingly, the transport mobility and accessibility in the Greater Bangkok Area will be greatly improved.
- (2) Since the Greater Bangkok Area is a population concentrated city, transportation services have a great impact on urban well-being, as well as on the national economic growth. The result of the Study revealed that the reduction of traffic costs would reach to approximately 14 million Baht a day by the year of 2000 (Table 9 and Fig. 7).

TABLE 9 OVERALL TRAFFIC COST

Cost in million Baht per day in 1983 prices

Items	1982 ¹	2000		
		With FES	With FES & SES	Ratio (3)/(2)
	(1)	(2)	(3)	(4)
Vehicle running cost	60.74	154.87	152.66	0.98
Passengers' time cost	12.30	68.05	56.33	0.83
Total vehicle operating cost	73.04	222.90	208.99	0.94

Notes: 1 Traffic cost in 1982 was simulated on the road network assuming that the Port-Bang Na section was already opened.

- FES : First Stage Expressway System
- SES : Second Stage Expressway System

- (3) The Second Stage Expressway System will provide a vital portion of the expressway network in the Metropolis and distribute traffic around the area, preventing serious traffic congestion which would otherwise occur in certain radial and circumferential roads. There will be a reduction of 20% in vehicle-hours and an increase of 24% in average travelling speed if the Second Stage Expressway System is developed (Table 10 and Fig. 7).

TABLE 10 AVERAGE TRAFFIC SPEED AND AVERAGE EXPRESSWAY TRIPS

Items	1982 ¹ (1)	2000		
		With FES (2)	With FES & SES (3)	Ratio (3)/(2) (4)
		Average traffic speed in GBA (km/hr)	38.3	22.4
Vehicle hours ('000 Hr/day) in GBA	571	2286	1871	0.80
Average expressway trips per day ('000)	76	269	594	2.20

Notes 1 Traffic demand in 1982 was simulated on the road network assuming that the Port-Bang Na section was already opened

- GBA Greater Bangkok Area
- FES First Stage Expressway System
- SES Second Stage Expressway System

(4) Land use in the Greater Bangkok Area will be improved by the development of the Second Stage Expressway System, as inefficient concentrations can be decentralized and inefficient dispersions can be intergrated. Existing community overcrowding will be reduced by the growth of new communities promoted by investors and inhabitants in the Greater Bangkok Area and the establishment of better communities will enhance the comfort of the area.










Items	1982	2000		Ratio (3)/(2)
	(1)	(2) with FES	(3) with FES & SES	
Overall Traffic Cost (in 1983 prices)	Assuming Bang Na Section opened  73.0 million Baht per day	 222.9 million Baht per day	 209.0 million Baht per day	0.94
Average Traffic Speed	 38.3 km/hr	 22.4 km/hr	 27.7 km/hr	1.24
Average Expressway Trips	 76,000 trips/day	 269,000 trips/day	 594,000 trips/day	2.21

FIG. 7 EFFECT OF THE PROJECT

5. GENERAL FEATURES OF THE SECOND STAGE EXPRESSWAY SYSTEM

5.1 Main Features

- (1) The Second Stage Expressway System consists of the following two routes:
 - a) The North-South Route runs in a northerly direction for a route length of 19.2 km from the planned Dao Khanong-Port Section of the First Stage Expressway System to the national road No. 31; and
 - b) The East Route of 8.7 km length runs easterly from the connecting point with the North-South Route to Phra Khanong-Bang Kapi road.
- (2) Both of these routes are inter-related and are indispensable to the expressway network in the Greater Bangkok Area. A part of the North-South Route and the initial stretch of the East Route are intended to compose an integral part of the ring expressway which together with the Din Daeng-Port-Bang Khlo section of the First Stage Expressway System will serve the central urbanized area of Bangkok.

The Expressway is planned to be 6 lanes except for a stretch between the Middle Ring Road and the terminus of the North-South Route where 4 lanes are planned (Fig. 8).

5.2 Supporting Facilities

(1) Toll Collection Facilities

The First and Second Stage Expressway Systems will be operated adopting the flat tariff and on-ramp toll collection system. The locations of the on and off ramps have been determined as shown in Fig. 4.

Toll gate structures, refuge islands, toll booths, toll buildings and equipment installation in each booth and toll buildings are included in the cost.

(2) Expressway Lighting and Other Electrical System

Scope of application in the Project covers the following locations and facilities:


- Throughways of the Expressway;
- Interchanges including rampways, and through lanes and at-grade intersections;
- On-off ramps including toll plazas;
- Toll building interior lighting;
- Subsystems such as closed circuit TV system, signs, control system, etc.; and
- Emergency power units for the toll buildings and other facilities (i.e. pump station for the undercrossing structure).

(3) Traffic Control System and Traffic Signs


The following systems are provided for the Expressway

- Closed circuit TV network for the surveillance of traffic;
- Emergency telephones installed on the roadside of the Expressway at 1 kilometer interval;

6-LANE ELEVATED EXPRESSWAY



4-LANE ELEVATED EXPRESSWAY



NOTE: The figures with asterisk show absolute minimum values. They shall be substituted by 5 meters of desirable minimum values to provide set back distance where the viaducts are planned within the row of the existing or planned streets.

FIG. 8 TYPICAL CROSS SECTIONS OF THE EXPRESSWAY

- Variable traffic signs (i.e. matrix sign) and guide signs (refer to discussions presented below); and
- Traffic detectors installed at each toll plaza and on the through traffic lanes.

When a traffic jam occurs in the expressway the result is more serious compared with the case of the arterial street, since the expressway system is not able to cater readily for detour or route change for the vehicles which are already driven thereon.

By the time the expressway network has the addition of the SES, it is expected that traffic demands would be considerably jumped up. Thus, it would become urgent to prevent the deterioration of the service level of the expressway. In case of the expressway system, the countermeasures for the above are provided frequently by means of strict traffic regulations such as booth control and the closure of critical on-ramp(s).

TABLE OF CONTENTS




TABLE OF CONTENTS

PREFACE

PROJECT LOCATION MAP AND MAP OF PROJECT AREA

	Page
SUMMARY AND RECOMMENDATIONS	1-1
CHAPTER 1 INTRODUCTION	1-1
1.1 Project Background	1-1
1.2 Study Objectives	1-2
1.3 Scope of Work	1-2
1.4 Study Approach and Execution of Study	1-2
1.4.1 General	1-2
1.4.2 Basic Policies of the Study	1-2
1.4.3 Execution of the Study	1-3
1.5 Conduct of the Study	1-6
1.6 Organization of the Project Team	1-7
1.7 Report Procedure	1-9
1.8 Abbreviations	1-9
CHAPTER 2 SOCIO-ECONOMIC CHARACTERISTICS	2-1
2.1 General	2-1
2.2 The Country	2-1
2.2.1 Development in the Past	2-1
2.2.2 Development in the Future	2-3
2.3 The Greater Bangkok Area	2-3
2.3.1 Development in the Past	2-3
2.3.2 Development in the Future	2-6
2.4 Zones	2-6
CHAPTER 3 LAND USE AND POPULATION	3-1
3.1 Urban Development	3-1
3.2 Population and Employment	3-8
3.2.1 Population	3-8
3.2.2 Employed Persons	3-8
3.2.3 Zonal Population and Employment	3-10
3.3 Characteristics in Population and Employment Changes: 1982-2000	3-10
3.3.1 Overall Characteristics	3-10
3.3.2 Population and Employment	3-13
CHAPTER 4 ROAD TRANSPORT SYSTEM AND TRAFFIC CHARACTERISTICS	4-1
4.1 General	4-1

4.2	Roads and Traffic	4-1
4.2.1	Road Network.	4-1
4.2.2	Traffic Characteristics	4-4
4.3	Traffic Survey	4-9
4.3.1	Person Trip Home Interview	4-9
4.3.2	Bus and Rail Passenger Interview	4-12
4.4	Registered Vehicles	4-13
4.4.1	Classification	4-13
4.4.2	Zonal Distribution of Private Cars	4-13
4.4.3	Number of Buses	4-15
4.5	Origin and Destination Tables in 1982	4-15
4.5.1	Methodology	4-15
4.5.2	Establishment of the 1982 OD Tables	4-17
CHAPTER 5 FUTURE ORIGIN – DESTINATION MATRICES		5-1
5.1	General	5-1
5.2	Establishment of 2000 OD Tables	5-1
5.2.1	Number of Passenger Cars in Future Years	5-1
5.2.2	Future Transport Facilities	5-5
5.2.3	Future OD Matrices	5-10
CHAPTER 6 EXPRESSWAY NETWORK PLANNING AND TRAFFIC FORECAST		6-1
6.1	Expressway Planning in GBA	6-1
6.1.1	Objective	6-1
6.1.2	Necessity of Expressway Network	6-1
6.1.3	Policies for Expressway Network Planning	6-4
6.2	Tolled Expressways	6-6
6.3	Expressway Network Study for GBA	6-7
6.3.1	Step 1 Study	6-7
6.3.2	Step 2 Study	6-10
6.3.3	Step 3 Study	6-17
6.3.4	Step 4 Study	6-17
6.4	Traffic Assignment	6-20
6.4.1	Methodology	6-20
6.4.2	Assignment Conditions	6-20
6.4.3	Expressway Traffic Diversion Model	6-27
6.4.4	Traffic Assignment Cases	6-31
6.4.5	Screening Procedure by Traffic Assignment to Establish the SES	6-33
6.4.6	Determination of SES Route Network	6-33
6.4.7	Estimated Traffic Assignment Results	6-35

CHAPTER 7	BUS SERVICE THROUGH THE EXPRESSWAY	7-1
7.1	General	7-1
7.2	Field Survey	7-2
7.2.1	Passenger Interview and Bus Trip Counting.....	7-2
7.2.2	The Survey Result	7-2
7.3	Analysis of Bus Operation on the SES	7-7
7.3.1	BMTA Bus Operation Statistics	7-10
7.3.2	Bus Routes and Trips in the SES Corridors	7-11
7.3.3	Alternative Bus Service Plans	7-13
7.3.4	Location of Bus Bays	7-17
7.3.5	Forecasted Public Bus Trips Using the Expressway	7-19
7.4	Bus Bay Design	7-25
7.4.1	Background	7-25
7.4.2	Engineering Considerations.....	7-25
7.4.3	Cost Estimates of Bus Bay.....	7-28
7.5	Assessment	7-28
7.5.1	The Alternatives	7-28
7.5.2	Economic Analysis	7-29
7.5.3	Financial Analysis	7-29
7.5.4	Conclusion and Recommendation	7-30
CHAPTER 8	FINALIZATION OF THE ROUTE LOCATION	8-1
8.1	General	8-1
8.2	Objective Routes	8-1
8.3	Methodology of the Study	8-1
8.4	Salient Features of the Objective Routes	8-3
8.5	Route Descriptions of the Alternatives	8-4
8.5.1	General	8-4
8.5.2	North – South Route	8-4
8.5.3	East Route	8-8
8.6	Comparison of Alternative Routes	8-13
8.7	Findings and Conclusion	8-13
8.7.1	Findings	8-13
8.7.2	Conclusion	8-14
CHAPTER 9	ENGINEERING STUDY	9-1
9.1	General	9-1
9.2	Study Approach	9-1
9.3	Basic Data	9-1
9.3.1	Aerial Photographs and Photo Mosaics	9-1
9.3.2	Topographical Maps	9-1

9.3.3	Ground Survey	9-2
9.3.4	Soils and Materials Survey	9-2
9.4	Design Standards	9-2
9.4.1	General	9-2
9.4.2	Geometric Design Standards	9-2
9.4.3	Structural Design Standard	9-12
9.4.4	Drainage Design Standard	9-14
9.5	Road Capacity and Number of Lanes	9-14
9.5.1	Assigned Traffic Volume	9-14
9.5.2	Road Capacity	9-14
9.5.3	Determination of Number of Traffic Lanes	9-18
9.6	Preliminary Geometric Design of Expressway	9-19
9.6.1	General	9-19
9.6.2	Preliminary Geometric Design	9-19
9.6.3	Descriptions of the ROW.	9-20
9.6.4	Consideration of Crossing Facilities	9-20
9.7	Preliminary Design of Interchanges	9-21
9.7.1	General	9-21
9.7.2	Preliminary Design of Makkasan Interchange	9-22
9.7.3	Preliminary Design of Bang Khlo and Phaya Thai Interchanges (3-Leg Interchanges)	9-24
9.8	Preliminary Design of On and Off Ramps	9-26
9.8.1	General	9-26
9.8.2	Traffic Volume and Number of Lanes of On/Off-Ramps.	9-26
9.8.3	Locations and Types of On-Off Ramps	9-28
9.8.4	Number of Toll Booths	9-28
9.9	Preliminary Design of At-Grade Intersections	9-31
9.9.1	General	9-31
9.9.2	Estimated Traffic Volume	9-31
9.9.3	Capacity Analysis	9-31
9.9.4	Lane Arrangement for At-Grade Intersections	9-31
9.10	Alternative Expressway Planning Schemes at the Victory Monument	9-34
9.10.1	General	9-34
9.10.2	Alternative "A" (Overcrossing Scheme)	9-34
9.10.3	Alternative "B" (Undercrossing Scheme)	9-34
9.10.4	Appraisal of Alternatives	9-36
9.10.5	Considerations for the Preservation of the Environment of the Victory Monument	9-37
9.10.6	Conclusion	9-37
9.11	Comparative Study of Viaduct and Embankment Scheme	9-37
9.11.1	General	9-37
9.11.2	Characteristics of Each Scheme	9-38
9.11.3	Appraisal of Alternative Scheme and Conclusion	9-38

9.12	Utilization of Spaces under the Viaduct	9-39
9.12.1	General	9-39
9.12.2	Joint Development Plan	9-40
9.12.3	Tentative Suggestion of Non-Expressway Facilities	9-43
9.13	Study of Viaduct and other Structures	9-43
9.13.1	General Concepts Adopted to Determine Viaduct Types	9-43
9.13.2	Determination of the Design Features of Structures	9-46
9.13.3	Study of the Undercrossing Structure	9-49
9.13.4	Design Elements of the Planned Structures	9-51
9.14	Preliminary Design of Pavement	9-51
9.14.1	Selection of Type of Pavement	9-51
9.14.2	Design of Rigid Pavement	9-54
9.15	Soils and Materials Study	9-55
9.15.1	Engineering Geology of the Project Area	9-55
9.15.2	Soils and Materials Survey	9-56
9.15.3	Description of Sub-Surface Soils along the Proposed Expressway Routes	9-57
9.15.4	Materials Sources	9-61
9.15.5	Foundation Studies	9-63
9.16	Hydrological Study	9-67
9.16.1	Study Purpose	9-67
9.16.2	Site Surveys	9-67
9.16.3	Meteorology	9-67
9.16.4	General View of Existing Drainage Environment	9-67
9.16.5	Rainfall	9-70
9.16.6	Run – Off	9-72
9.16.7	Hydraulic Design Principles and Study Results	9-73
9.16.8	Flood Stage and At-Grade Expressway Grade Level	9-73
9.16.9	Drainage Study of the Victory Monument Undercrossing	9-75
9.17	Expressway Lighting and Other Electrical Systems	9-78
9.17.1	General	9-78
9.17.2	Scope of Application	9-78
9.17.3	Design Standards of Expressway Lighting	9-78
9.17.4	Design Illumination Intensities of the Expressway	9-78
9.17.5	Design Features of the Expressway Lighting and Emergency Power Unit	9-78
9.18	Traffic Control System	9-80
9.18.1	General	9-80
9.18.2	Evaluation of Existing Traffic Control System	9-80
9.18.3	Recommendations	9-83
9.19	Emergency Telephone System	9-87
9.19.1	General	9-87
9.19.2	Evaluation of Existing Emergency Telephone System	9-87
9.19.3	Recommendations	9-87

9.20	Toll Collection System	9-88
9.20.1	General	9-88
9.20.2	Evaluation of Existing Toll Collection System	9-88
9.20.3	Toll Collection Facilities in the SES	9-90
9.20.4	Recommendations	9-91
9.21	Traffic Signs	9-91
9.21.1	General	9-91
9.21.2	Evaluation of Existing Traffic Sign System	9-91
9.21.3	Types of Variable Message Signs	9-93
9.21.4	Recommendations	9-93
CHAPTER 10 ENVIRONMENTAL IMPACT STUDY		10-1
10.1	General	10-1
10.2	Study Purpose	10-1
10.3	Basic Premises of the Study	10-1
10.4	Project Description and Environmental Background	10-2
10.5	Favorable Environmental Impacts.	10-2
10.6	Summary of Adverse Effects and their Mitigation	10-3
10.7	Conclusions.	10-5
CHAPTER 11 ESTIMATED CONSTRUCTION AND MAINTENANCE COST.		11-1
11.1	General	11-1
11.2	Unit Cost by Work Items	11-2
11.3	Land Acquisition and Compensation	11-2
11.4	Construction Cost	11-2
11.5	Maintenance Cost	11-4
CHAPTER 12 ECONOMIC ANALYSIS		12-1
12.1	General	12-1
12.1.1	Approach	12-1
12.1.2	Conditions	12-1
12.2	Phase I Study	12-2
12.2.1	Alternatives	12-2
12.2.2	Traffic Cost	12-2
12.2.3	Benefits	12-7
12.2.4	Investment and Maintenance Cost	12-8
12.2.5	Cost-Benefit Analysis	12-8
12.2.6	Conclusion of Phase I Study	12-10
12.3	Phase II Study	12- 11
12.3.1	Alternative Plans of SES	12-11
12.3.2	Traffic Cost and Benefits	12- 12
12.3.3	Cost of Investment, Operation and Maintenance	12-12

12.3.4	Cost Benefit Analysis	12-13
12.3.5	Conclusion	12-15
CHAPTER 13	TOLL REVENUE AND FINANCIAL ANALYSIS	13-1
13.1	General	13-1
13.2	Present Situation	13-1
13.2.1	Policy Determination	13-1
13.2.2	Toll Fare Level of FES	13-2
13.3	Toll Fare	13-2
13.3.1	Types of Toll Fare	13-2
13.3.2	The System Considered for the SES	13-3
13.3.3	Toll Fare Level of SES	13-3
13.4	Financial Analysis	13-4
13.4.1	Conditions	13-4
13.4.2	Revenue and Expenditure	13-5
13.4.3	Conclusion	13-6
CHAPTER 14	IMPLEMENTATION PLAN	14-1
14.1	General	14-1
14.2	Project Costs	14-1
14.3	Stage Construction	14-1
14.4	Implementation Schedule	14-3
ANNEX "A"	SCOPE OF WORK	A-1

