F I G U R E

Fig.3-1 FLOW REGIME AT TANGKULAP



Fig. 3-2 LAND CAPABILITY MAP

(DOWNSTREAM OF PROPOSED DAMSITE)



Source : The Land Capability Classification of Sabah, Volume 2.

Fig. 3-3 PROFILE OF THE KINABATANGAN RIVER AND TRIBUTARIES



Fig. 3-4 CHANNEL WIDTH DISTRIBUTION



Fig. 3-5 PRESENT FLOW CAPACITY



NOTE : No.n is the number of cross-section.

Fig. 3-6 INUNDATION AREA IN THE LOWER BASIN



Fig. 3-7 PRESENT CROPPING PATTERN



Fig. 3-8 ADMINISTRATIVE DIVISION



Fig. 3-9 SABAH GENERATING STATIONS,1978



Fig. 3-10 DAIRY LOAD CURVE OF SANDAKAN



Fig. 4-1 LOCATION OF POSSIBLE DAMSITES



Fig. 4-2 DISTRIBUTION OF KAMPUNG BY GROUND HEIGHT



Fig. 4-3 SUBMERGED AREA BY BALAT DAM



Fig. 4-4 ALLOCATION OF RESERVOIR STORAGE CAPACITY



Fig. 4-5 DISTRIBUTION OF STANDARD PROJECT AND DESIGN FLOOD DISCHARGE

Unit : m^3/s



Fig. 4-6 HYDROGRAPHS OF STANDARD PROJECT AND DESIGN FLOOD





Fig. 4-7 LEAST CONSTRUCTION COST OF DAM AND RIVER IMPROVEMENT



Fig. 4-8 POTENTIAL AGRICULTURAL DEVELOPMENT AREA



Fig. 4-9 PROPOSED AGRICULTURAL DEVELOPMENT AREA



Fig. 4-10 FARMING ORGANIZATION



Note : Total required manpower would be 4007.

( ) ; Number of required stuff.

Fig. 4-11 PROPOSED CROPPING PATERN AND METEOROLOGICAL CONDITION



Fig. 4-12 PROPOSED AREA FOR PADDY DEVELOPMENT

Lokan Area :

Block No.	Area (ha)
1	860
2	960
3	2,750
4	3,780
5	1,130
6	2,220
7	1,880
8	1,240
9	810
Total	15,630

Lamag Area :

Block No.	Area (ha)
10	1,860
11	2,960
12	4,240
13	2,780
14	2,120
15	2,960
16	1,240
Total	18,160

Koyah Area :

Block No.	Area (ha)
17	2,160
18	1,010
19	1,000
20	1,860
21	1,180
22	1,610
23	1,390
Total	10,210

LEGEND

○ : Block Number (23 blocks)

● : Proposed Rice Mill (11 places)

★ : Proposed Pumping Station (23 stations)

Proposed area for paddy development : 44,000 ha.



Fig. 4-13 REQUIRED RESERVOIR CAPACITY FOR WATER REQUIREMENT



Fig. 4-14 FLOW DIAGRAM OF MAXIMUM DIVERSION REQUIREMENT



Fig. 4-15 COMPARISON OF GENERATING TYPE



Fig. 4-16 ROUTE MAP OF TRANSMISSION LINE



Fig. 5-1 PLAN OF BALAT DAM



Fig. 5-1 PLAN OF BALAT DAM




Sungai Kinabatangan
S. Lafungan
Pokok-Pokok
Belukar
SUB DAM NO.3
SUB DAM NO.4
0
0.5
1.0 km

Fig. 5-2 PROFILE ALONG AXIS OF DAM



Fig. 5-3 TYPICAL CROSS-SECTION OF DAM



Note :

D.F.W.L. : Desigh Flood Water Level
S.W.L. : Surcharge Water Level
N.W.L. : Normal Water Level
L.W.L. : Low Water Level

LEGEND:

① Core
② Random
③ Rock
④ Drain
⑤ Coffer Dam

0 10 20 30 40 50m

Fig. 5-4 PLAN OF OUTLET FACILITY



Fig. 5-5 TYPICAL LAYOUT OF FIELD STRUCTURE



Fig. 5-6 PLAN AND CROSS-SECTION OF HYDRO POWER STATION



Fig. 6-1 CONSTRUCTION SCHEDULE



A T T A C H M E N T

ATTACHMENT : MEMBER OF SURVEY TEAM AND ADVISORY COMMITTEE

Survey Team

Team Leader	Mr. Katsuhisa Abe
Hydrologist	Mr. Makoto Migita (1st Stage)
- do -	Mr. Kazumi Nobe (2nd Stage)
Geologist	Mr. Takuji Murakami
Flood Control Engineer	Mr. Akio Shichijugari
Dam and Hydro Power Engineer	Mr. Tadashi Kudo
Irrigation Engineer	Mr. Takafumi Suzuki
Agronomy	Mr. Keisaku Kobayashi
Regional Planner	Mr. Eiji Nishita
Socio-Economist	Mr. Yoshiharu Matsumoto

Advisory Committe

Head	Mr. Eiichi Yoshitake
Flood Control	Mr. Mitsuaki Mizuno
Regional Plan	Mr. Keiichi Inoue
Agricultural Development Plan	Mr. Masataka Kurosawa
Hydro Power	Mr. Masatoshi Furuichi (1st Stage)
- do -	Mr. Isao Yamamoto (2nd Stage)
Power Development Plan	Mr. Masao Makino
Coordinator	Mr. Hitonori Ono