

DIMENSIONS OF CHECK GATES TYPE - A



Discharge (m ³ /s)	L ₁	L ₂	L ₃	L ₄	B	n	H ₁	Drop+2.0m	Drop+1.5m	Drop+1.0m	Drop+0.5m	H ₂	h ₁	h ₂	Gate
200 ~ 150	3,000	4,000	4,500	7,000	2,500	4	2,500	3,200	2,700	2,200	1,700	2,500	750	500	25 x 20 ^m
150 ~ 100	•	•	•	•	•	3	•	•	•	•	•	•	•	•	•
100 ~ 50	•	•	•	•	•	2	•	•	•	•	•	•	•	•	•
50 ~ 20	•	•	•	•	•	1	•	•	•	•	•	•	650	•	•
20 ~ 10	•	3,000	•	6,000	1,500	1	1,800	•	•	•	•	1,800	450	•	15 x 15


TYPE - B


Discharge (m ³ /s)	L ₁	L ₂	L ₃	B	n	H	Gate
200 ~ 150	3,000	4,000	4,500	2,500	4	2,500	25 x 20 ^m
150 ~ 100	•	•	•	•	3	•	•
100 ~ 50	•	•	•	•	2	•	•
50 ~ 20	•	•	•	•	1	•	•
20 ~ 10	•	3,000	•	1,500	1	1,800	15 x 15
10 ~ 0.5	•	•	•	1,000	1	1,500	10 x 10
0.5 ~	1,500	2,000	3,000	600	1	800	—

DIMENSIONS OF DROPS


Discharge (m ³ /s)	L ₁	L ₂	L ₃	B	H ₁	H ₂	h ₁	h ₂
50 ~ 1.0	3,000	5,000	10,000	5,000	3,000	2,500	1,000	800
50 ~ 2.0	3,000	4,000	6,000	2,000	2,000	2,000	800	500
20 ~ 1.2	•	3,000	•	1,500	1,800	1,800	600	•
12 ~ 0.8	•	•	4,000	1,200	1,500	1,500	400	•
0.8 ~ 0.6	2,000	2,000	•	1,000	1,200	1,200	300	300
0.6 ~ 0.4	•	•	3,000	•	1,000	1,000	200	•
0.4 ~ 0.2	•	•	•	•	800	800	—	•
0.2 ~ 0.1	•	•	•	•	500	500	—	•





 MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
Check Gate & Drop
 JAPAN INTERNATIONAL COOPERATION AGENCY




PLAN
SCALE - A



PROFILE
SCALE - A




PLAN
SCALE - A




PROFILE
SCALE - A

DIMENSION OF CROSS DRAINS


TYPE	Culvert Discharge (m ³ /sec)	L ₁	L ₂	L ₃	L ₄	L ₅	B	A
TYPE - A	6.0 ~ 3.0	7,000	3,000	40,000 ~ 30,000	3,000	7,000	2,500	1
	3.0 ~ 2.0	6,000	2,500	40,000 ~ 30,000	2,500	6,000	2,000	1
	2.0 ~ 1.2	5,000	2,000	40,000 ~ 30,000	2,000	5,000	1,500	1
	1.2 ~ 0.8	5,000	2,000	40,000 ~ 30,000	2,000	5,000	1,200	1
TYPE - B	0.8 ~ 0.6	4,500	1,500	40,000 ~ 30,000	1,500	4,500	1,000	1
	0.6 ~ 0.4	4,000	1,500	40,000 ~ 25,000	1,500	4,000	φ 900	1
	0.4 ~ 0.2	4,000	1,500	40,000 ~ 25,000	1,500	4,000	φ 700	1




PLAN
SCALE - B




PROFILE
SCALE - B




SECTION A-A
SCALE - C




SECTION A-A
SCALE - A




PLAN
SCALE - D




PROFILE
SCALE - D



SECTION B-B
SCALE - C



SECTION B-B
SCALE - B



DEMONSTRATIONS OF CULVERTS


TYPE	Discharge (m ³ /sec)	L ₁	L ₂	B	H	t	Pipe φ	n
TYPE - A	16.48	3,000	7,000	2,500	2,500	400	—	2
	10.0-6.0	2,000	5,000	2,500	2,500	300	—	2
	6.0-3.0	·	·	·	·	·	·	·
	3.0-2.0	·	·	2,000	2,000	250	·	·
TYPE - B	2.0-1.0	1,500	4,000	1,500	1,500	·	·	·
	1.0-0.6	·	·	1,000	1,000	200	·	·
	0.6-0.4	1,000	3,000	1,300	2,000	·	φ 900	·
	0.4-0.1	·	·	1,100	1,800	·	φ 700	·

MINISTRY OF PUBLIC WORKS
DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
FEASIBILITY STUDY ON KARIAN
MULTIPURPOSE DAM CONSTRUCTION PROJECT


Culvert & Cross Drain

JAPAN INTERNATIONAL COOPERATION AGENCY

BRIDGE TYPE - A




PLAN
SCALE - A




PROFILE
SCALE - A


BRIDGE TYPE - B




PLAN
SCALE - B



SECTION A-A
SCALE - B




PROFILE
SCALE - B




SECTION A-A
SCALE - B

SPILL WAY AND WASTE WAYS




PLAN
SCALE - B




PROFILE
SCALE - B


DIMENSIONS OF SPILL WAY & WASTE WAYS








Discharge (m ³ /s)	B	n	L ₁	L ₂
16.48 ~ 9.0	2,000	2	15,000 ~ 10,000	15,000 ~ 5,000
9.0 ~ 4.5	1,500	2	15,000 ~ 5,000	15,000 ~ 5,000
4.5 ~ 2.5	1,500	1	10,000 ~ 5,000	15,000 ~ 5,000
2.5 ~ 2.0	1,200	1	10,000 ~ 5,000	15,000 ~ 5,000
2.0 ~ 1.0	1,000	1	10,000 ~ 5,000	15,000 ~ 5,000



SECTION A-A
SCALE - B





 MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
 Bridge, Spillway & Wasteway
 JAPAN INTERNATIONAL COOPERATION AGENCY



DEMENSION OF SYPHONS

No.	L ₁ (m)	L ₂ (m)	L ₃ (m)	B ₁	B ₂	B ₃	H ₁	H ₂	h	S	EL. (m)
No. 1	478.0	20.0	10.7	10,500	5,850	2,625	2,700	10,000	2,041	4,050	35.084
No. 2	2,048.0	25.0	10.7	9,200	5,850	2,625	2,500	12,000	1,814	3,750	33.719
No. 3	2,598.0	25.0	8.0	6,400	3,100	1,250	2,200	12,000	1,568	3,300	31.257
No. 4	8.0	10.0	5.0	3,000	2,000	750	1,900	1,500	1,373	2,850	13.806


MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
 Siphon
 JAPAN INTERNATIONAL COOPERATION AGENCY

A P P E N D I X - H
R I V E R I M P R O V E M E N T

APPENDIX - H

RIVER IMPROVEMENT

TABLE OF CONTENTS

	<u>Page</u>
1. INTRODUCTION	H-1
2. PRESENT CONDITION OF CIUJUNG RIVER	H-3
2.1 General Condition	H-3
2.2 Existing Structures	H-4
2.3 Flow Capacity	H-5
2.4 Sand Gathering	H-7
3. FLOOD DAMAGE	H-9
3.1 General	H-9
3.2 Flood Damage Survey	H-9
3.3 Average Annual Decrement of Flood Damage	H-12
4. FLOOD RUNOFF	H-14
4.1 Rainfall-Runoff Model and Basic Data	H-14
4.2 Rainfall and Flood Runoff Analysis	H-16
4.3 Probable Flood Discharge under Present River Condition	H-17
5. FLOOD CONTROL PLAN	H-19
5.1 General	H-19
5.2 Basic High Water	H-20
5.3 Flood Regulation by Karian Dam	H-21
5.4 Design Flood Discharge Distribution	H-23
6. RIVER IMPROVEMENT	H-25
6.1 General	H-25
6.2 Design Principle	H-26
6.3 River Structure	H-29

	<u>Page</u>
7. CONSTRUCTION PLAN AND ESTIMATE OF COST AND BENEFIT	H-30
7.1 Construction Plan	H-30
7.2 Cost Estimate	H-32
7.3 Benefit	H-34
8. FUTURE PROBLEMS	H-36
REFERENCE	H-40

LIST OF TABLES

		<u>Page</u>
Table H-1	CHARACTERISTICS OF CIUJUNG RIVER BASIN	H-41
Table H-2	CIUJUNG RIVER WATER LEVEL ELEVATION BY NON-UNIFORM FLOW CALCULATION	H-42
Table H-3	INUNDETED AREA FROM PAMARAYAN TO RANGKASBITUNG	H-43
Table H-4	APPRAISEMENT OF HOUSES AND BUILDINGS, AND HOUSEHOLD EFFECTS OR STORED GOODS AT 1984 PRICE LEVEL	H-44
Table H-5	RATE OF APPRAISEMENT OF HOUSEHOLD EFFECTS BY INUNDETED DEPTH ABOVE FLOOD LEVEL	H-44
Table H-6	DAMAGE RATE OF INUNDETED HOUSES AND BUILDINGS	H-45
Table H-7	DAMAGE RATE OF INUNDETED PROPERTIES	H-45
Table H-8	NUMBER OF INUNDETED HOUSES AND BUILDINGS FROM PAMARAYAN TO RANGKASBITUNG	H-46
Table H-9	INUNDETED CROP AREA FROM PAMARAYAN TO RANGKASBITUNG	H-47
Table H-10	CROP DAMAGE VALUES FROM PAMARAYAN TO RANGKASBITUNG BY FLOOD IN NOV. 1981 AND NOV. 1983	H-48
Table H-11	ACTUAL FLOOD DAMAGE AT 1984 PRICE	H-49
Table H-12	CALCULATED CHART OF AVERAGE ANNUAL DAMAGE	H-49
Table H-13	DALLY RAINFALL IN NOVEMBER 1981	H-50
Table H-14	COIFFICIENT OF THIESSEN PLYGON ON NOV. 1981 STORM	H-51
Table H-15	AVERAGE RIVER BASIN DALLY RAINFALL OF NOV. 1981 STORM	H-52
Table H-16	COEFFICIENT OF CONVERSION (RAVE/RI) TO THE BASIN-MEAN RAINFALL	H-52
Table H-17	STORAGE FUNCTION COEFFICIENT OF SUBBASIN AND CHANNEL	H-53
Table H-18	COEFFICIENT OF PROBABLE RAINFALL IN SUBBASIN	H-54

	<u>Page</u>
Table H-19 PROBABLE FLOOD DISCHARGE UNDER PRESENT RIVER CONDITION	H-55
Table H-20 EXPERIENCED ANNUAL MAXIMUM FLOOD DISCHARGE DATA AT KRAGILAN AND RANGKASBITUNG	H-56
Table H-21 FLOOD DISCHARGE DISTRIBUTION OF CIUJUNG RIVER	H-57
Table H-22 CALCULATION RESULTS OF FLOOD REGULATION BY KARIAN DAM	H-58
Table H-23 ALTERNATIVE PLANS OF RIVER IMPROVEMENT	H-59
Table H-24 REQUIRED CONSTRUCTION WORKS FOR CASE-2	H-60
Table H-25 REQUIRED LAND ACQUISITION AND COMPENSATION FOR CASE-2	H-61
Table H-26 RIVER IMPROVEMENT CONSTRUCTION COST (CASE-2)	H-62
Table H-27 (1) ANNUAL DISBURSMENT SCHEDULE OF RIVER IMPROVEMENT COST (CASE-2)	H-63
Table H-27 (2) ANNUAL DISBURSMENT SCHEDULE OF SHEARD KARIAN DAM COSTRUCTION COST BY FLOOD CONTROL SECTER	H-63

LIST OF FIGURES

		<u>Page</u>
Fig. H-1	RIVER BASIN AROUND PROJECT AREA	H-64
Fig. H-2 (1)	PROFILE OF CIUJUNG RIVER BASIN	H-65
Fig. H-2 (2)	CIUJUNG RIVER BASIN DIAGRAM	H-65
Fig. H-3	PAMARAYAN WEIR	H-66
Fig. H-4	RANGKASBITUNG BY PASS PLAN	H-67
Fig. H-5	GROYNE ON CIBERANG AND UPPER CIUJUNG RIVER	H-68
Fig. H-6	RATING CURVE AND MANNING'S ROUGHNESS COEFFICIENT BY NOV. 1981 FLOOD	H-69
Fig. H-7	PROFILE OF CIUJUNG RIVER BED MATERIALS	H-70
Fig. H-8 (1)	PRESENT LONGITUDINAL WATER LEVEL PROFILE OF CIUJUNG RIVER	H-71
Fig. H-8 (2)	PRESENT LONGITUDINAL WATER LEVEL PROFILE OF UPPER CIUJUNG RIVER	H-72
Fig. H-9 (1)	FLOW CAPACITY AND CHARACTERISTICS OF CIUJUNG RIVER	H-73
Fig. H-9 (2)	FLOW CAPACITY AND CHARACTERISTICS OF UPPER CIUJUNG RIVER	H-74
Fig. H-10	INUNDED AREA ALONG CIUJUNG RIVER FROM PAMARAYAN TO RANGKASBITUNG	H-75
Fig. H-11	RELATION BETWEEN FLOOD DISCHARGE AND DAMAGE	H-76
Fig. H-12	SUBBASIN AND CHANNEL FOR RUNOFF ANALYSIS	H-77
Fig. H-13	RAINFALL-RUNOFF MODEL DIAGRAM	H-78
Fig. H-14 (1)	HOURLY RAINFALL DATA IN NOVEMBER 1981	H-79
Fig. H-14 (2)	HOURLY RAINFALL DATA IN NOVEMBER 1981	H-80
Fig. H-15	THIESSEN POLYGON IN NOVEMBER 1981 STORM	H-81
Fig. H-16	DISCHARGE HYDROGRAPH OF NOV. 1981 FLOOD	H-82
Fig. H-17	FLOOD REGULATION EFFECTS BY KARIAN DAM ACCORDING TO SPILLWAY CREST LENGTH	H-83
Fig. H-18	HYDROGRAPH OF FLOOD REGULATION BY KARIAN DAM	H-84
Fig. H-19	BASIC HIGH WATER AND DESIGN FLOOD HYDROGRAPH	H-85
Fig. H-20	DESIGN DISCHARGE DISTRIBUTION OF CIUJUNG RIVER	H-86
Fig. H-21	ALTERNATIVE PLANS OF RIVER IMPROVEMENT	H-87

	<u>Page</u>
Fig. H-22	TYPICAL CROSS SECTION OF DYKE AND INSPECTION ROAD H-88
Fig. H-23 (1)	PLANE ARRANGEMENT (CASE-2) H-89
Fig. H-23 (2)	PLANE ARRANGEMENT (CASE-2) H-90
Fig. H-24	MEANDERING CHARACTERISTICS OF CIUJUNG RIVER H-91
Fig. H-25 (1)	LONGITUDINAL PROFILE OF CIUJUNG RIVER (CASE-2) H-92
Fig. H-25 (2)	LONGITUDINAL PROFILE OF UPPER CIUJUNG RIVER (CASE-2) H-93
Fig. H-26	EFFECT OF DREDGING AND SHORT CUT ON WATER LEVEL AT RANGKASBITUNG H-94
Fig. H-27 (1)	CROSS SECTION OF CIUJUNG RIVER (CASE-2) H-95
Fig. H-27 (2)	CROSS SECTION OF CIUJUNG AND CIBERANG RIVER (CASE-2) H-96
Fig. H-27 (3)	CROSS SECTION OF UPPER CIUJUNG RIVER (CASE-2) H-97
Fig. H-28	GROYNE H-98
Fig. H-29 (1)	DRAINAGE CULVERT (TYPE-I,II) H-99
Fig. H-29 (2)	DRAINAGE CULVERT (TYPE-III) H-100

APPENDIX-H

RIVER IMPROVEMENT

1. INTRODUCTION

The principal rivers in the Project Area are the Ciujung, the Cibereum and the Cibanten rivers as shown in Fig. H-1. The Ciujung river occupies the major portion of the Project Area, followed by the Cibereum and the Cibanten rivers.

The Ciujung river is the largest and the most important river in the Project Area with a total catchment area of 1,850 km² at its estuary. In the upstream basin, it splits into three main tributaries at Rangkasbitung where the catchment area comes to 1,383 km², or about 75% of the whole Ciujung basin, comprising 594 km² for the Upper Ciujung, 331 km² for the Ciberang and 458 km² for the Cisimeut river basins.

The average annual runoff of the Ciujung river amounts to 3.35 billion m³ which is remarkably biased to the rainy season. Besides, the flood outflow from splitted three main tributaries join almost coincidentally at Rangkasbitung due to the topographic condition in the basin. Accordingly the flood events have been frequent giving damage on the downstream reaches especially in and around Rangkasbitung.

The lower reaches of the Ciujung river have already been provided with dykes, of which some sections were recently improved by PROSIDA. However, the rest of the Ciujung river has no special provision for flood mitigation except a few groynes at some places.

In the Master Plan study, firstly the whole section of the Ciujung river from the river mouth to Rangkasbitung was subject to the study of river improvement. The study was made, with a design scale of 50-year return period as the overall master plan level, on several alternative plans in combination with flood regulation by proposed upstream dams.

However, the study revealed that every alternative plan would require an excessively heavy investment so far as the present socio-economic level in the basin was concerned.

Accordingly, considering the pressing requirement for flood mitigation in and around Rangkasbitung, the first stage plan was studied with a lesser design scale of 10-year return period and in a shortened river section focussing on Rangkasbitung. The section from the Pamarayan weir to Rangkasbitung was subject to the river improvement study, taking account of its improvement effect of lowering the flood water level at Rangkasbitung by dredging and short cuts.

After the comparative study on several first stage alternative plans, the first stage plan F-2, which consists of the flood regulation by Karian dam and the river improvement of 1/10 design scale in the upstream section from the Pamarayan weir, was found to be the most advantageous from the economic viewpoint.

Thus the flood control for the Ciujung river in the Master Plan was finally concluded as follows:

- Judging from the present socio-economic condition of the Ciujung river basin, the flood control will presently be focussed on the flood mitigation in and around Rangkasbitung,
- The proposed Karian reservoir will be provided with a flood control storage to regulate the flood outflow from the Ciberang river, and
- Besides, considering the unregulated flood outflow from the Upper Ciujung and the Cisimeut river basins, a river improvement plan will be set up for the river section from Pamarayan to Rangkasbitung to protect the flood-prone area in and around Rangkasbitung.

Accordingly the river section from Pamarayan weir to Rangkasbitung will be considered as the objective study section for river improvement in the Feasibility Study, together with the flood regulation by the Karian reservoir.

2. PRESENT CONDITION OF CIUJUNG RIVER

2.1 General Condition

The configuration of the Ciujung river and its major tributaries are shown in Fig. H-2 and Table H-1. The present condition of the objective river section and downstream reaches of the Ciujung river are briefly described in the following.

The river section from the estuary to Kragilan has the riverbed gradient ranging from 1/6,000 to 1/5,000 and the river width ranging from 170 to 100 m. This section has already been provided with dykes on both river banks. Recently the additional river improvement works were completed by PROSIDA with the design flood discharge of 1,100 m³/sec.

The river section of about 18.8 km from Kragilan to the Pamarayan weir has the mean riverbed gradient of 1/3,200 and the river width ranging from 100 to 150 m. A remarkable river bend exists about 3 km upstream from the Kragilan bridge, which has resulted in some collapse of river bank. The embankments of left and right primary canals for the Ciujung irrigation scheme, located on both banks of the Ciujung river, form the boundary of flooded area stretching along the river.

Small tributaries joining the main stream, especially the Cikambuy river with a catchment of 48 km², have troubles of interior inundation.

The river section of about 17 km from the Pamarayan weir to Rangkasbitung, has the mean riverbed gradient of about 1/3,000 and the river width ranging from 100 to 150 m. The sedimentation is remarkable on the riverbed upstream from the Pamarayan weir, which may aggravate the flood water stage. Many meanders exist in the upper reaches of this section, which have resulted in collapse of river bank. The configuration of the confluence of the Ciberang river is intricate, leading to collapses of downstream river bank.

Outflow from the Ciberang, the Cisimeut and the Upper Ciujung rivers, which join at Rangkasbitung, have frequently given damage to the city. Some short cut works have already been provided on the large bends of the Ciberang and the Ciujung rivers around Rangkasbitung to protect the city.

On the Ciberang river, the section of about 3.5 km from Rangkasbitung to the Cisimeut confluence has the mean riverbed gradient of about 1/2,500 and the river width of about 100 m. Some groynes are provided near the Cisimeut confluence and on a river bend near Rangkasbitung.

The Upper Ciujung river, for about 5.5 km upstream from the Ciberang confluence has the mean riverbed gradient about 1/2,400 and the river width of about 70 m. Some groynes and bank protection are provided on river bends near Rangkasbitung to protect the road and village yard.

2.2 Existing Structures

The main structures along the Ciujung river are the Pamarayan weir, several bridges and groynes.

(1) Pamarayan weir

The Pamarayan weir is an important structure on the Ciujung river, which was completed in 1918 to divert the river water into the Ciujung irrigation scheme. The weir has a total crest length of 160 m with 10 gates of 12 m in span and 6 m in height. During the flood in November 1981, the gate hoists were operated by manpower, however, they were motorized with diesel engine driven generator in 1982. Severe bank erosion and scouring in the river section directly downstream from the weir were recently rehabilitated by PROSIDA (Ref, Fig. H-3).

(2) Bridges

The following seven bridges cross over the Ciujung river.

- Tirtayasa bridge	3.3 km from river mouth
- Gas-pipeline bridge	17.7 km from river mouth
- Kragilan bridge	18.3 km from river mouth
- Highway bridge	18.6 km from river mouth
- Rangkasbitung railway bridge	54.8 km from river mouth
- Rangkasbitung road bridge	54.8 km from river mouth
- Ciberang bridge	56.8 km from river mouth

Besides, there is a bypass plan (Ref. Fig. H-4) to alleviate the congestion of traffic in Rangkasbitung City, and a part of its construction work has been already started. Along with this, there is a project to build a bridge across the Ciujung river (53.9 km from the river mouth), though no construction work has been started yet.

(3) Bank protection (groyne)

Along the Ciberang, Cisimeut and Upper Ciujung rivers around Rangkasbitung, there is a plan to installl groynes in the section confrouting with flood flow for the purpose of bank protection, and construction work is being carried forward. The present condition of the said work and the structure of the groyne are as shown in Fig. H-5 (1) and Fig. H-5 (2).

2.3 Flow Capacity

(1) Objective river section

A study will be made of the flow capacity in the following sections:

- Ciujung river (18.4 km from Pamarayan weir to Ciberang river confluence)
- Ciberung river (14.0 km from Ciujung river confluence to Karian dam site)
- Upper Ciujung river (17.6 km from Ciberang river confluence)

The cross sections to be used in this study are based on the data supplied by P3SA for each river, of which the cross sections of the Ciujung river and Ciberang river were surveyed in 1982 and the cross section of the Upper Ciujung river was surveyed in 1984. The longitudinal distances between each section were measured on the topographic map of 1/5,000 scale prepared by P3SA in 1984.

(2) Calculation method and roughness coefficient

The flow capacity is estimated by non-uniform flow calculation for each river section. The Manning's roughness coefficient (n) is determined by applying the relation between the water-level and the flow rate during the flood in November, 1981 to the estimated rating curve (Ref. Table H-2, Fig. H-6) by non-uniform flow calculation obtained on the assumption that $n = 0.035$, 0.03 and 0.025 . Then, at the Kragilan bridge, $n = 0.0292$ and at Rangkasbitung, $n = 0.0274$ (Ref. Fig. H-6). Also, n is determined by the law of friction resistance against running water of riverbed material by the use of a typical mean grain size and riverbed gradient in each section, according to the results of survey on riverbed material (Ref. Fig. H-7). Then, on the lower stream from the Pamarayan weir, $n = 0.026 \sim 0.028$; on its upper stream, $n = 0.029$. Thus, the Manning's roughness coefficient (n) used to calculate the flow capacity of the Ciujung river is assumed to be 0.03 , considering the meanderings and bank resistance of the river.

(3) Calculated water level and flow capacity

The water level of the Ciujung river in the present channel condition for the discharge of $500 \sim 1,500 \text{ m}^3/\text{s}$ is calculated as shown in Fig. H-8. Also, the flow capacity at ground height on the left and right banks in each calculated section is determined as shown in Fig. H-9. As a result, the average flow capacity may be summarized

as follows:

River section	Flow capacity (m ³ /s)
<u>Ciujung River</u>	
Pamarayan weir to Rangkasbitung	400
<u>Ciberang River</u>	
Rangkasbitung to Cisimeut river confluence	400
Upstream of Cisimeut river confluence	300
<u>Upper Ciujung River</u>	
Ciberang river confluence to 8 Km	300
8 Km to 18 Km	200

2.4 Sand Gathering

Sand in the riverbed of the Ciujung river has been gathered as materials of construction works, which has shown an increasing prospect recently. The volume of gathered sand has recently amounted to about 120,000 m³ annually in the river section upstream from the Pamarayan weir. Careful observation and management would be necessary, because the performance of gathering sand in the river may have some problems on the stability of the river channel when the gathering volume exceeds the supply from the upstream catchment.

The actual condition of gathering sand in the river is as shown in the following table, according to the survey conducted by the Regional Office of DPUP.

	Downstream of Pamarayan weir	Upstream of Pamarayan weir
Annual gathering volume	60,000 m ³ /year	120,000 m ³ /year
Number of employees	about 80	about 200
Local price	3000~4000 Rp/m ³	1500~2000 Rp/m ³
Price including transportation cost	4000~6000 "	4000~5000 "

These are values estimated on regular licensed gatherers. If unlicensed gathering is included, the actual volume of sand gathered is expected to increase by about 30% over the above-mentioned figures, that is, it is estimated that sand of about 240,000 m³ is being gathered annually on the whole.

3. FLOOD DAMAGE

3.1 General

A flood damage survey around the objective section of the Ciujung river was conducted by the Study Team assisted by P3SA staff. The survey was based on the data from Regional Offices DPUP and information obtained in the flooded area. The collected data consist of the inundated area, number of submerged buildings, area of flooded farmland, and submerged depth. As a result of survey, the inundated situations caused by the floods in November 1981 and November 1983 are revealed clearly. The flood in November 1981 is reported to have inflicted the largest damage in the past.

3.2 Flood Damage Survey

Damage caused by the flood in November 1981 and November 1983 are assessed under the following method provided with economic condition for evaluation. The unit prices of crops are commonly based on the farm gate price on this agro-economic study. The houses, buildings and household effects are objectively estimated in view of net economic viability.

(1) Inundated area

Based on the topographic map of 1/5,000 scale newly prepared by P3SA and the land use map of 1/25,000 scale which was drawn up during 1977/1978, the inundated areas caused by the floods in November 1981 and November 1983 are divided according to the form of land use and submerged depth. Table H-3 shows the inundated area during the floods in November 1981 and November 1983, classified by the submerged depth, on the river section from the Pamarayan weir to Rangkasbitung. The situation of land utilization in and around the area inundated by the flood of November, 1981 is as shown in Fig. H-10.

(2) Damage to houses and buildings, and household effects

Based on the data obtained from the inquiries made at the flooded site, damage of submerged houses and household effects are estimated, using the following conditions:

- i) Based on the data from BAPPEDA Rangkasbitung and from the results of the said inquiries, unit damage values of houses and household effects are set at the appraisalment given in Table H-4.
- ii) As the estimated damage of household effects differs depending on the submerged depth, the rate as shown in Table H-5 is used, which is obtained by referring to values used in other surveys conducted in Indonesia, for example, that for Ular river.
- iii) The floor level of houses is set at 10 cm above ground level.
- iv) As for the damage rate of houses and household effects, values adopted in the Outline of Economic Survey on Flood Control prepared by the Ministry of Construction, Japan are used as shown in Tables H-6 and H-7.

Total number of submerged houses and buildings caused by the flood in November 1981 and November 1983 are tabulated in Table H-8. Total damages to houses and buildings, and household effects and stored goods caused by the above mentioned floods are estimated under the aforementioned conditions, amounting to Rp.3815 x 10⁶ by the November 1981 flood and Rp.1103 x 10⁶ by the November 1983 flood for the area from Pamarayan to Rangkasbitung.

(3) Damage to Crops

The form of utilization of farm land in the inundated area by the flood in November, 1981 and the flood in November, 1983 is classified on the basis of a 1/25,000-scale land utilization map. Flooded areas classified by form are shown in Table H-9. In the paddy fields within the inundated area, no crops had been planted at the time of flooding mentioned above, hence it is assumed that the crops have suffered no damage, taking into account the present condition of cultivation. Cassava and maize are cultivated in most of flooded fields, and therefore, both are regarded as typical field crops. The average damage ratios to cassava and maize are assumed to be 10% and 100% respectively. In flooded orchards, banana and bamboo are planted together, and the bamboo plays a role of protecting fruit trees, thus suffering little flood damage.

Thus, the amount of the relevant crop damage is calculated by multiplying of the unit damage value, damage ratio and net planted area. Whereas, the unit damage value is determined on the basis of gross output by multiplying the farm gate prices in 1984 of cassava & maize and the mean cropping yield at the inundated area, with deduction of the prospective portion of the production input to be ignored after the inundation. Damage to farm crops during the flood in November, 1981 and the flood in November, 1983 in the section from Pamarayan to Rangkasbitung are RP. 34 million and RP. 19 million, respectively. Details are shown in Table H-10 (1) and Table H-10 (2).

(4) Loss due to suspension of business activities

Following the method adopted in the Outline of Economic Survey on Flood Control, the loss due to suspension of business activities is set at 6% of the total damage to buildings and household effects.

(5) Damage to public works and agricultural facilities

As detailed data on the damage to public works and agricultural facilities are not available, the method described in the Outline of Economic Survey on Flood Control is adopted in present survey. For the area from Pamarayan to Rangkasbitung, the damage rate is estimated at 90.5% of the damage amount of buildings and household effects.

(6) Total flood damage

When the above-mentioned damages are totalled, the whole damage caused by the floods in November 1981 and November 1983 amounts to Rp. 7,531 million and Rp. 2,187 million, respectively for the area from Pamarayan to Rangkasbitung. Table H-11 gives the breakdown.

3.3 Average Annual Decrement of Flood Damage

The average annual decrement of flood damage is estimated as follows.

- From the result of non-uniform flow calculation of the Ciujung river, the non-damage flood discharge at Rangkasbitung is estimated at about $500 \text{ m}^3/\text{s}$ which will approximately correspond to the probability of 1/1 under the present river condition.
- From the discharge rating curve at Rangkasbitung gauging station (Fig. H-11 (1)) the flood discharge in November 1981 is estimated at $1,150 \text{ m}^3/\text{s}$ based on the flood mark at Rangkasbitung bridge. In the same way, the flood discharge in November 1983 is estimated at $665 \text{ m}^3/\text{s}$. The relation between flood discharge and damage is shown in Fig. H-11 (2).
- From the result of flood runoff analysis, which will be given in 4 "Flood runoff" of Paragraph 4.3 "Flood Control Plan", the flood discharge of $1,150 \text{ m}^3/\text{s}$ in November 1981 will correspond to the probability of about 1/8 under the present river condition. In the same way, the flood discharge of $665 \text{ m}^3/\text{s}$ in November 1983 will correspond to about 1/2 under the same condition.

- Annual flood damage of other probability will be estimated by interpolation or extrapolation based on above figures of damage and probability.
- Thus the average annual decrement of flood damage on the probability of 1/10 will be estimated at about Rp. 2.57 billion in the river section from the Pamarayan weir to Rangkasbitung (Ref. Table H-12).

4. FLOOD RUNOFF

4.1. Rainfall-Runoff Model and Basic Data

(1) Rainfall-runoff model

To determine the design high-water discharge of a river, it is necessary to use a rainfall-runoff model for grasping the characteristics of catchment, channel and flooding and for adequately estimating the mitigation of inundation by river improvement and the effect of flood regulation by dam. In the present study, the storage function method is used to make runoff analysis of the flood in November, 1981, for which the hourly data of rainfall and river discharge are available. The basic formulas used in the storage function method are as follows:

i) Runoff from subbasin

Basic formula

$$\left. \begin{aligned} s &= kq^p \\ \frac{ds}{dt} &= f \cdot R_{ave} - q \end{aligned} \right\} \text{----- (4-1)}$$

Where k, p ; constants for basin

s ; depth of storage (mm)

q ; depth of runoff (mm/hr)

f ; primary runoff ratio

R_{ave} ; average rainfall in a basin (mm/hr)

dt ; calculation time (hr)

Adding the base runoff Q_b to the above, the total basin runoff Q will be obtained from the equation as follows:

$$Q = \frac{1}{3.6} f_1 \cdot A \cdot q + \frac{1}{3.6} (1-f_1) \cdot A \cdot q_{sa} + Q_b \text{----- (4-2)}$$

Where f_1 ; primary runoff ratio

q_{sa} ; depth of runoff by rainfall after point of saturation (mm/hr)

Q_b ; base runoff (m^3/s)

Q ; total runoff from basin (m^3/s)

ii) Calculation for a river channel and flooding area.

$$\frac{ds}{dt} = I_j - Q \text{ ----- (4-3)}$$

$$\left. \begin{aligned} S &= KQ^p - T_1Q && \text{River Channel} \\ S &= KQ^p && \text{Flooding area (non velocity)} \end{aligned} \right\} \text{----- (4-4)}$$

Where I_j ; inflow into a river channel (m^3/s)

$Q_1(t) = Q(t+T_1)$; discharge at the lower boundary
of a river channel taking account
of a time lag (m^3/s)

S ; apparent storage, in a river channel and
flooding area ($m^3/s \cdot hr$)

T_1 ; time lag (hr)

Prior to applying the storage function to the runoff analysis of the Ciujung river, a rainfall-runoff model was prepared by dividing the catchment and river channel at the confluences of principal tributaries, the Pamarayan weir, Kragiran Bridge and other principal points (Ref. Fig. H-12 and H-13).

(2) Basic data

Constants k , p , f_1 , etc. in the storage function can be obtained through its verification by hydrologic data on flood events in the past. The flood in November, 1981 will be adopted for the verification of the storage function, because it is the only flood event of which the hourly data of rainfall and river discharge are available in the basin. As the gauging station at Rangkasbitung was washed away during that flood, the discharge data at Kragilan gauging station are employed for the verification of the equation constants. (Ref. Fig. H-16). On the other hand, the raingauge stations and daily rainfall data concerning the flood in November, 1981 are as shown in Fig. H-15 and Table H-13. Also, the rainfall patterns on five raingauge stations, where hourly rainfall data were obtained, are shown in Fig. H-14.

4.2 Rainfall and Flood Runoff Analysis

(1) Rainfall analysis

Regarding rainfall to be used in the calculation of runoff from each subbasin, the basin-mean rainfall by the Thiessen method will be used.

The Thiessen polygon and coefficients obtained by the raingauge stations where daily and hourly data on the flood in November, 1981 are available are as shown in Fig. H-15 and Table H-14. The results of calculations on the basin-mean rainfall during the flood in November, 1981 are as shown in Table H-15. Also, regarding the basin-mean hourly rainfall in each subbasin, from the data obtained by the five observation stations where hourly data are available, one of them is to be selected on the basis of the following considerations and its rainfall pattern is to be adopted.

- i) The station must be located within the subbasin.
- ii) The station must be located near the subbasin.
- iii) The station must have superior correlation with the basin-mean daily rainfall during the flood in November 1981

The basin-mean hourly rainfall will be estimated in such a way that the total rainfall (R_i) observed by the station adopted will agree with the total basin-mean rainfall (R_{ave}). Representative station number in each subbasin and the coefficient of conversion to the basin-mean rainfall (R_{ave}/R_i) are as shown in Table H-16.

(2) Runoff analysis

Constants of storage function are to be determined by trial calculation so that they will agree with the observed discharge during the flood in November, 1981. In this analysis, verification calculation is to be performed by estimating the constants of basin storage function k and p , primary run-off coefficient f_1 , saturation rainfall R_{sa} , channel storage function (considering inundation) and other constants, so that the calculated discharge at the Kragilan point will match the observed discharge.

The relation between the calculated discharge and the observed discharge at Kragilan is as shown in Fig. H-16. The constants of subbasin and river channel used in this calculation are as shown in Table H-17. The calculated discharge and the observed discharge at each point are as shown in the following table.

	(Unit: m ³ /s)		
	Kragilan	Pamarayan	Rangkasbitung
Observed discharge	1070	1330	1150
Calculated discharge	1080	1173	1284

4.3 Probable Flood Discharge under Present River Condition

(1) Estimated probable discharge

Probable flood discharges for the return periods of 5 years, 10 years, 25 years and 50 years are calculated on the basis of rainfall analysis (Ref. Table H-17) and runoff study of the November 1981 flood. Calculation results is as listed in Table H-19 (1) corresponding to specific return periods. They are summarized as follows:

Return period (year)	Q _{pro} (m ³ /s)	
	10 yrs	50 yrs
Kragilan Gauge	1070	1440
Pamarayan Weir	1120	1590
Rangkasbitung	1220	1730

Where, Q_{pro} shows the probable flood discharge corresponding to specific return period in the present river condition.

The hyetograph used in the calculation is based on the probable daily rainfall in each subbasin according to the analytical results of Appendix B Hydrology. The rainfall pattern is established in such a way as to match the 24-hour hyetograph when the total rainfall becomes the largest during the rainfall storm in November, 1981 (Ref. Table H-18).

(2) Probable flood discharge by observed flow data

On the other hand, the results of calculations on probable discharges according to experienced annual maximum flood discharge data (Ref. Table H-20) at Kragilan and Rangkasbitung are as shown in Table H-19 (2). From these results, the return periods of discharges $1070 \text{ m}^3/\text{s}$ at Kragilan and $1150 \text{ m}^3/\text{s}$ at Rangkasbitung during the flood in November 1981 are estimated at 15 years in both areas.

5. FLOOD CONTROL PLAN

5.1 General

(1) Study principle

As described in 1. Introduction, the flood control plan in this study is focussed on flood mitigation in and around Rangkasbitung.

The proposed Karian reservoir is located at no great distance from Rangkasbitung, which will be very effective to regulate the flood outflow from the Ciberang river. However, it has a relatively small catchment of 288 km², occupying only about 20% of the whole catchment area at Rangkasbitung, which totals to 1,383 km² comprising catchments of the Ciberang, the Cisimeut and the Upper Ciujung rivers.

Accordingly, considering the unregulated flood outflow from the Cisimeut and the Upper Ciujung rivers, a river improvement plan will be set up to protect the objective floodprone areas together with the flood regulation by the proposed Karian reservoir.

(2) Design scale

The level of flood control plan in Indonesia has generally been set up for the return period ranging from 20 to 50 years, sometimes with lesser return periods for the first stage.

Although the Study Area remains in its rather depressed situation at present, it has a prospective advantage for development as follows. It has a favourable location on the main route linking Jakarta and Sumatra. The construction of new Jakarta-Marak highway is well under way. The land use will be promoted by proposed improvement and development of Ciujung, Cicinta and K-C-C irrigation schemes. Further industrial development is expected in the Study Area. All of these will accrue increase of population and enhancement of economic activities in the Project Area.

Accordingly, considering the importance of the Area and possible improvement of its socio-economic condition mentioned above, the proposed Karian dam will be planned to have a flood control storage for the design flood inflow of 50-year return period.

The level of river improvement will be planned with lesser return period of 10 years, taking account of the present socio-economic condition of the area and other instances of river improvement in Indonesia.

The lower reaches of the Ciujung river have already been improved recently with the design flood discharge of $1,100 \text{ m}^3/\text{s}$, which will be re-estimated to correspond to a flood of around 15-year return period at the Kragilan gauge if derived from its flood flow data from 1970 through 1983 (Ref. Table H-19 (2)).

Thus the river improvement for the objective section will be planned with the design flood of 10-year return period, taking account of flood regulation by the proposed Karian reservoir and also good correspondence with the design flood discharge of downstream reaches.

5.2 Basic High Water

The concept of the basic high water will be employed for the flood control planning in this study. The basic high water is a basic flood-hydrograph which is used as the basis for flood control planning. It is estimated under the condition of no flood regulation measures and no flooding along the river course. The basic high water is generally derived from the design storm rainfall of a probability of exceedance corresponding to the required safety of flood control.

Based upon the estimated basic high water, the flood control plan will be set up with the optimum distribution of projected flood discharge into the river improvement and the flood regulation measures such as the dam, the retarding basin and the diversion channel.

Employing the storage function and considering the river-channel condition without flooding, the basic high water at main points along the Ciujung, the Ciberang and the Upper Ciujung rivers are estimated as shown in Table H-21 corresponding to specific return periods. They are summarized as follows.

<u>Basic High Water (m³/s)</u>		
Return period (years)	10 yrs	50 yrs
Kragilan gauge (Ciujung)	1,500	2,100
Pamarayan weir (Ciujung)	1,300	1,900
Rangkasbitung (Ciujung)	1,300	1,900
Karian dam site (Ciberang)	550	800

The computed basic high water will be used as the basis for flood control planning. The flood control plan of the Ciujung river will be set up by distributing the projected flood discharge into flood regulation by the proposed Karian reservoir and the river improvement.

5.3 Flood Regulation by Karian Dam

The flood regulation at the proposed Karian dam will be planned by an ungated overflow-type spillway with its overflow crest positioned at the full supply level of the reservoir.

(1) Equation for flood regulation by Karian dam

The flood regulation by Karian dam is calculated as follows:

$$V(t+\Delta t) = V(t) + \left(\frac{Q_i(t) + Q_i(t+\Delta t)}{2} - \frac{Q_o(t) + Q_o(t+\Delta t)}{2} \right) \Delta t \quad \text{---- (5-1)}$$

$$Q_o = C.L. h^{3/2}$$

Where: V; Storage Volume (m³) (=f(h))

Q_i; Inflow discharge (m³/s)

Q_o; Outflow discharge (m³/s)

C; Discharge coefficient (=2.0)
L; Spillway crest length (m)
h; Overflow depth (m)
 Δt ; Interval of calculation time (sec)
(t), (t+ Δt); Suffix of calculation time

(2) Estimated effect of flood regulation by Karian dam

The required storage volume for flood control is estimated at 33 million m³ above the ungated overflow crest, which will regulate the flood inflow of 800 m³/s, corresponding to the basic high water of 50-year return period, to the outflow of 210 m³/s at the dam site.

For the basic high water of 10-year return period, the inflow of 550 m³/s will be regulated to the outflow of 160 m³/s at the dam site. This plan is based upon the undermentioned study. The effect of flood regulation at Karian dam is calculated with respect to four cases in the crest length of ungated overflow type spillway, i.e., L = 30 m, 40 m, 50 m, 70 m and 100 m. The stage-capacity curve of Karian reservoir used in this calculation is shown in Appendix-K Dam and Reservoir. The results of calculation on the effect of flood regulation at the proposed Karian dam site corresponding to each crest length (L) are as shown in Table H-22 (1). Also, discharge at Rangkasbitung, Pamarayan and Kragilan after flood regulation by Karian dam for the flood discharge of 10-year return period (10-year basic high water) corresponding to each crest length L are as shown in Fig. H-17.

As a result, taking into consideration correspondence with the PROSIDA's design discharge 1100 m³/s downstream from Kragilan, topographic restrictions on the right abutment of the Karian dam site, etc., the spillway crest length L is assumed to be 50 m. Meanwhile, the results of calculation on the effect of flood regulation at the dam site for the return periods of 5 years, 10 years and 25 years with L=50 m are as shown in Table H-22 (2) (Ref. Fig. H-18).

5.4 Design Flood Discharge Distribution

The design flood discharge distribution along the river is estimated, based upon the basic highwater of 10-year return period and taking account of the effect of flood regulation by the Karian reservoir, as shown in Table H-21 and Figs. H-19 and H-20. They are summarized as follows:

		Basic high water (m ³ /s)	Design flood discharge (m ³ /s)
Kragilan	(Ciujung)	1,500	1,100 ^{/ 1}
Pamarayan	(Ciujung)	1,300	1,100
Rangkasbitung	(Ciujung)	1,300	1,100
Rangkasbitung	(Upper Ciujung)	700	700
Rangkasbitung	(Ciberang)	900	700

^{/ 1} Under the present river condition from Kragilan to Pamarayan.

The above table shows that, under the present river condition in the section from Kragilan to Pamarayan, the flood of 10-year return period at Kragilan will coincides with the design flood of 1,100 m³/s by PROSIDA after flood regulation by the Karian reservoir and river improvement on the objective section.

Accordingly, if the river section from Kragilan to the Pamarayan weir is subject to improvement sometime in the future, an careful study will be necessary of its effect on the lower reaches and the counter-measures to be taken.

Table H-21 shows calculated values of flood discharge with 100 m³/s or 10 m³/s order up. Raw calculated values may be given as shown in the following table, and it is evident that some effect of flood control by Karian dam can be obtained for Rangkasbitung and the downstream of Kragilan as well.

Present Condition

(Unit: m³/s)

Point	Return Period (years)			
	5	10	25	50
Kragilan	929	1063	1333	1439
Rangkasbitung	999	1216	1495	1728

After Completion of the Project

(Karian Dam + River Improvement)

(Unit: m³/s)

Point	Return Period (years)			
	5	10	25	50
Kragilan	919	1045	1310	1417
Rangkasbitung	896	1082	1340	1567

6. RIVER IMPROVEMENT

6.1 General

Main problems concerned in the flood control of the Ciujung river will be enumerated such as aggravation of the highwater level in the upstream reaches from the Pamarayan weir due to sediment on the riverbed, remarkable meanderings in the river section upstream thereof, and severe bank erosion liable to collapse around Rangkasbitung near the confluence of the Ciberang and the Upper Ciujung rivers. Their countermeasures will be contemplated as follows.

- Dredging of riverbed in the upstream reaches from the Pamarayan weir.
- A series of short cut in the section of meanderings between 8.3 km point and 15.5 km point upstream from the Pamarayan weir.
- Improvement of the Ciberang - Upper Ciujung confluence around Rangkasbitung by short cut.
- Provision of groynes and revetments on river bends and meanderings confronting with flood flow.

Three alternative plans are studied to find out the most reasonable plan, with consideration on the riverbed stabilization, execution and economic aspects as presented in Table H-23 and Fig. H-21. They will be summarized as follows.

Section	Case 1	Case 2	Case 3
Pamarayan Weir			
to 15.5 km (No.85)	Dredging of River Bed and Embankment		
15.5 km to 22.7 km (No.64)	Short Cut	Short Cut	Dredging ^{/1} and Embankment
Around Rangkasbitung	Short Cut ^{/2}	Embankment	Embankment
Improvement Length (Km)	21.5	22.9	25.0
Construction Cost (x 10 ⁶ Rp)	15,060	13,790	13,780

^{/1} River improvement along the present river channel.

^{/2} Improvement of Ciberang - Upper Ciujung confluence by short cut.

From technical viewpoints on river improvement and maintenance, the most desirable plan will be case-1 followed by case-2. However, considering the economic aspects as well, case-2 will be proposed to be subject to the preliminary design and economic analysis in this Report.

6.2 Design Principle

River improvement must be planned in such a way as to allow a design discharge in safety with consideration given to plane, longitudinal and cross-sectional arrangements as a whole, and to provide a stable river channel taking into account utilization during normal times as well. The undermentioned Ciujung river improvement plan (Case 2) has been selected as a result of studying the three alternatives above and taking into account the above-mentioned basic principle and economic aspects.

(1) Manning's roughness coefficient "n"

The improved cross section of the river will be designed with the Manning's roughness coefficient "n" of 0.030, taking account of the result of analyses on rivebed materials and considering river meanderings, bank erosion and planning safety.

(2) Typical cross section of dyke (Ref. Fig. H-22)

The typical cross section of dyke will be designed with crown width of 4 m at minimum and both side-slopes of 1:2, considering the stability of dyke and a function of maintenance road. A freeboard of 1 m will be provided above the design high water level.

The berm of 3 m width will be provided in 3 to 5 m height from the crown on the riverside slope of the dyke, and in 2 to 3 m height from the crown on the land-side slope, considering the possible seepage within the embankment.

(3) Plane arrangement (Ref. Fig. H-23)

Generally, the plane arrangement of the dyke and the river channel will be designed to be in smooth accomodation with expected flood flow, however, a series of short cut will be designed on developed meanderings in the river section between 8.3 km and 15.0 km upstream from the Pamarayan weir, to increase the flow capacity and to stabilize the river channel.

These short cuts will be provided in the section where the length of the present river channel increase more then 2 times owing to meanderings. The meandering characteristics of the Ciujung river are as shown in Fig. H-24, and the section No. 85~65 in which the ratio of increase in river channel length β (Ref. Fig. H-24) owing to meanderings is larger than 1 corresponds to this. The length of the present river channel of 18.3 km, between the Pamarayan weir and Rangkasbitung, will be reduced to 15.2 km by designed short cuts.

(4) Longitudinal profile arrangement (Ref. Fig. H-25)

The riverbed elevation upstream from the Pamarayan weir has risen to around EL. 8.0 m at present, which is about 3 m higher above the sill of the weir. The heavy sedimentation has raised the flood water stage which has resulted in aggravation of flood condition along the river.

The longitudinal river profile will be designed with an improved riverbed slope, starting from around the sill elevation of the weir and linking to the present riverbed elevation near the lower end of the short cut section. Lowering of the riverbed will be done by dredging.

The design high water level will be decided starting from the design HWL EL. 11.0 m at the Pamarayan weir and according to the design river cross-section. The location of the short cut is shown in Fig. H-23. The change in channel length and riverbed gradient by short cut is summarized below .

	Channel Length L (km)	Riverbed Gradient I	
Present	18.26	1/3000	
After Short Cut	15.24	1/3000	1/2310
Reduction	3.02	-	

Meanwhile, for reference, the result of study on the effect of lowering of water level at Rangkasbitung for the design high-water discharge of 1100 m³/s in the present river channel condition is described below.

The lowering of water level will be 0.32 m by dredging, 0.72 m by short cut, and 0.9 m by both dredging and short cut (Ref. Fig. H-26).

(5) Cross-sectional arrangement

For the river section with ample space at present, the double cross section will be designed. Considering the required flow capacity and topography of the objective section, the improved river width and the riverbed width will be designed mostly as follows:

	Ciujung	Ciberang	Upper Ciujung
Improved river width (m)	100	85	70
Improved riverbed width (m)	60	50	50

The cross section in the alternative plan (Case-2) is shown in Fig. H-27. In this case, the design river width and channel configuration are to be the same in each alternative plan, and the design flood water level and embankment height are to be based on the needed water level according to the non-uniform flow calculation.

6.3 River Structure

(1) Groyne and revetment:-

The types of groyne and revetment will have to be selected according to the river characteristics with consideration upon economic aspects and maintenance as well. For the Ciujung river, piled groynes and gabion revetment will be designed on river banks confronting with flood flow (Ref. Fig. H-28).

(2) Treatment of small tributary confluence

The treatment of small tributary confluence will be designed by the open levee, if the interior ground lies above the high-water level of the Ciujung river. However, the sluice will be designed if the high-water level of the Ciujung river exceeds the interior ground level. The sluice will be designed by three types type-I (H 1.5 m x B 1.5 m x 1), type-II (H 2.0 m x B 2.5 m x 2) and type-III (H 3.0 m x B 3.0 m x 2), according to dimension of the tributary (Ref. Fig. H-29).

(3) Other facilities

The maintenance road will be designed on the crown of the dyke with gravel surface (Ref. Fig. H-22 (2)). In the section of open levee, some connection with the existing road will be provided.

The drainage ditch will be designed at the land-side toe of the dyke according to the topography, if necessary.

7. CONSTRUCTION PLAN AND ESTIMATE OF COST AND BENEFIT

7.1 Construction plan

(1) Main works

The main items of channel improvement works in the Ciujung river are dredging, excavation and embankment. The work volume of the main items according to the proposed plan (Case 2) referred to in Chapter VI is as shown below (Ref. Table H-24).

Dredging	$560 \times 10^3 \text{ m}^3$
Excavation	$1404 \times 10^3 \text{ m}^3$
Embankment	$521 \times 10^3 \text{ m}^3$

In addition, there are groynes and gabion revetments in the sections confronting with flood flow, and drainage culvert.

(2) Preparatory works

Preparatory works are composed of,

- Transportation road and access road,
- Office and quarters,
- Topographic survey and soil survey for detailed design and supervision, and
- Other works (Clearing works must be executed at the sites of embankment and excavation and some other temporary works will be required.)

(3) Construction plan

Required construction works, land acquisition and compensation for river improvement referred to in Chapter VI are as shown in Table H-24 and H-25. The construction plan of main civil works is described below.

- Dredging

Dredging will be carried out in the river section for about 8.3 km upstream from the Pamarayan weir. According to the result of field survey, this section has the water depth from 2 m to 6 m and riverbed materials are mostly of sandy nature on the surface. A 1,000 HP diesel dredger will be employed with an average dredging capacity of about 25,000 m³ per month. Spoil from dredging will be deposited in spoil banks nearby the river.

- Excavation

Excavation will be carried out mainly by bulldozer, backhoe and dragline. Excavated soil will be conveyed by dump trucks and partly be utilized for embankment. The rest of them will be deposited in the old channel, which has an enough capacity of about 2.1 million m³ to receive the soil from dredging and excavation.

- Embankment

Embankment will be carried out with materials from borrow pits nearby and partly with excavated soils by a combination of bulldozer, backhoe, vibration roller and vibration compacter. The embankment height will be mostly from 2 m to 3 m in the lower section and mostly from 1 m to 2 m around the city of Rangkasbitung.

(4) Construction schedule

Construction work is to be executed in the order considering the effect of decreasing water level on Rangkasbitung. Dredging up to No. 85 Point upstream from the Pamarayan weir will be started at first and will be completed in 3 years. Next, short cut work will be executed in the section from No.85 point to No.64 point, which is most effective to lower the flood stage of Rangkasbitung, and embankment will be carried out from the Pamarayan weir to No.64 point. Finally, construction work centers around embankment upstream from No.64 point including upper Ciujung and Ciberang rivers.

7.2 Cost Estimate

(1) Composition of construction cost

The construction cost of river improvement works consists of earth work, bank protection, sluice and equipment, land acquisition, engineering services and administration and physical contingency. The construction cost is estimated on the basis of prices in 1984. Also, estimation is made using the following exchange rate as of 1984.

US\$1 = Rp. 1050 = ¥240

The construction cost consists of costs required for civil works land acquisition and house compensation, engineering services and administration cost, and contingency.

The cost required for civil works consists of costs for preparatory works, main civil works and the miscellaneous. The cost for civil works is estimated by multiplying work quantity by unit cost. The cost for preparatory works is assumed to be 8% of the total cost of the main civil works and the miscellaneous is assumed to be 10% of the total cost of preparatory and civil works.

For administration and engineering services, the foreign currency portion is assumed to be 15% and the local currency portion 8% against the total of direct construction cost, and land acquisition cost. The physical contingency is assumed at 15% of the total cost of the above. Price contingency is taken into account at annual escalation rate of 5% for foreign currency portion and 12% for local currency portion.

(2) Construction cost

The work quantities and construction cost are shown in Table H-26 with their breakdowns. With regard to the proposed plan (Case 2), the cost of river improvement alone is summarized below with the breakdown of foreign and local currency portions.

(Unit: Rp. x 10⁶)

Item	Foreign Currency	Local Currency	Total
1. Direct Construction cost	5,320	3,973	10,293
2. Land Acquisition	0	404	404
3. Administration and Engineering	949	350	1,299
4. Physical Contingency	1,091	710	1,801
<u>Sub-total</u>	<u>8,360</u>	<u>5,437</u>	<u>13,797</u>
5. Price Contingency	2,433	4,463	6,896
<u>Total</u>	<u>10,793</u>	<u>9,900</u>	<u>20,693</u>

Also, the shared Karian dam construction cost by flood control sector is shown as follows:

Item	Foreign Currency	Local Currency	Total
1. Direct Construction cost	3,443	2,719	6,162
2. Land Acquisition	0	1,444	1,444
3. Administration and Engineering	517	332	849
4. Physical Contingency	595	674	1,269
<u>Sub-total</u>	<u>4,555</u>	<u>5,169</u>	<u>9,724</u>
5. Price Contingency	1,374	3,854	5,228
<u>Total</u>	<u>5,929</u>	<u>9,023</u>	<u>14,952</u>

Construction cost of Karian dam is shown in Appendix-J Dam and Reservoir. The cost of intake and tunnel which is required for purposes other than flood control is deducted from the total Karian dam construction cost. Then, this cost is allocated at the ratio of flood control storage ($33 \times 10^6 \text{ m}^3$) to active storage ($252 \times 10^6 \text{ m}^3$).

Also, the Table H-27 shows the annual disbursement schedule for river improvement.

(3) Operation, maintenance and replacement cost

Annual operation and maintenance cost is assumed to be 0.5% of the direct construction cost estimated above. As for the replacement of the facilities, it is considered that the metal structures such as gates, are replaced only once during the entire period of the project life. The total replacement cost for the gates of box culvert is estimated at Rp. $1,746 \times 10^6$.

7.3 Benefit

(1) Average annual flood damage decrement

Generally, the benefit by flood control is referred to as the amount of flood damage mitigated through river improvement and flood regulation by dam. The average annual damage in and around Rangkasbitung upstream from the Pamarayan weir in the Ciujung river is estimated at Rp. 2.57×10^6 as shown in Section 3.3. When river improvement work in the Ciujung river and construction of Karian dam are completed, there will be no flood damage up to a design scale of 10-year return period. Accordingly, the amount of average annual flood damage decrement will be Rp. 2.57×10^6 .

(2) Other benefits

- Besides, the installation of groyne and revetment will prevent the destruction of housing land, roads, farmland, etc. caused by the collapse of river banks during flood. The contents of evaluation on damage will include the price of land destroyed, house construction and moving costs, the cost of construction of a road in another route, reduction in the output owing to a decrease in the planting area, etc.

For reference, according to the result of field survey, the area of land destroyed in the past 10 to 20 years is assumed to be as follows:

housing land	:	0.65 ha
road	:	0.85 ha
wet paddy field	:	0.3 ha
upland crop field	:	1.0 ha

The prices of these land, reconstruction cost and a decrease in crop production are assumed to be approximately Rp. 247×10^6 in current price. In terms of average annual damage, this amount is equivalent to Rp. 16.7×10^6 , and this can be expected as a benefit brought about through prevention of the collapse of river banks.

- Moreover, as secondary effect by river improvement in the Ciujung river, the following two points can be considered: One is "Land on the right bank of the Ciberang river along the old river channel in Rangkasbitung as well as on the right bank downstream from the railway bridge will be protected against flood damage and can be utilized as housing land.", and the other is "Sand in the Ciujung river is currently in demand as construction material, and river sand found in the areas from Kragilan over to Rangkasbitung is being gathered (Ref. Section 2.4). From this point of view, dredged sand in the upstream of Pamarayan can also be utilized as construction material."

8. FUTURE PROBLEMS

In the present survey, measures for flood control in and around Rangkasbitung have mainly been studied and a river improvement plan for the section upstream from the Pamarayan weir has been proposed. The problems that have been made clear in the present study and the matters that should be investigated before making the detailed design may be summarized as follows.

(1) Improvement of hydrologic data

- Only a series of hydrologic data on the flood in November, 1981 has been used for the flood runoff analysis in this study. However, regarding the constants of storage function, it will be desirable to verify other flood events and confirm their appropriateness.
- For that purpose, it will be necessary to set up automatic rain gauge stations in the Ciberang, Cisimeut and Upper Ciujung river basins to record hourly rainfall in each basin.
- As for river stage and discharge data, efforts should be made to improve the accuracy of rating curves through continuous observation and discharge measurement during high water stage at Kragilan, Pamarayan weir and Rangkasbitung. Also, discharge measurement during high water stage at Sabagi gauging station will be important in grasping the runoff characteristics of the Ciberang river.

(2) Survey

- For the detailed design, it will be necessary to newly carry out plane, longitudinal and cross-sectional surveys.
- The range of these surveys will be from the Pamarayan weir to Rangkasbitung including the Ciberang river (up to the Cisimeut river confluence) and the Upper Ciujung river (up to 5 km from the Ciberang river confluence).

- In order to improve the precision of flood survey and make clear the river-channel plan and the compensation quantity, the plane map should be provided with 0.5 m contours in the inundated area along river channels, and the size and location of houses, as well as roads, bridges and tributaries should be plotted in the plane map. Also, the scale should be 1/2500.
- Longitudinal and cross-sectional surveys should be conducted at intervals of 250 m and should also include bridges, principal tributaries and confluences.

(3) Soil survey

- A soil survey will be required in working out a dredging plan, designing short-cut sections, embankment, box culverts, etc. and drawing up an execution plan.
- The survey should include boring and sampling according to its purpose in the stage of detailed design. Relevant tests should also be carried out.

(4) Types of groyne and treatment of confluence at Rangkasbitung

- In the present survey, piled groynes have been proposed considering the good achievements in Japan. However, their effect may vary with the meandering characteristics of the river, riverbed materials and riverbed gradient. When executing construction work, therefore, it will be desirable to execute in good order and make necessary improvements while watching the effects of groynes.
- If all construction works must be completed within 3 years like the present plan, it is desirable to determine the installation locations and intervals of groynes in such a way that a sufficient effect can be obtained by hydraulic model test and other similar river experiences.

- Especially, for treatment of the confluence of the Upper Ciujung and Ciberang rivers, it is desirable that groynes and revetments be selected on the basis of a careful study using hydraulic model tests, because these rivers are located adjacent to an urban district and important facilities such as road bridge, and railway bridge.

(5) Study on riverbed stabilization

- The stabilization of the riverbed can be predicted by examining the longitudinal distribution of sediment transport. The proposed channel in the present plan, has been determined along the present riverbed gradient. It is desirable that its stability be confirmed by a sediment transport formula adding further survey on riverbed materials with sampling at intervals of 1 - 2 km.

(6) Flood control in downstream reaches from Pamarayan weir

The river section downstream from Kragilan has recently been improved, leaving the section between Kragilan and the Pamarayan weir to be subject to problem in the future.

If the river section between Pamarayan and Kragilan is subject to improvement sometime in the future, a careful study will be necessary beforehand of its influence on the lower reaches downstream from Kragilan and the countermeasures to be taken. The study should be made with some additionally necessary data by preparatory surveys such as longitudinal, cross-sectional and plane topographic surveys along the objective river section and also by analyses of riverbed materials.

For reference, some considerations on the above-mentioned river improvement will be given below, based on the results of the present study and the local condition.

i) Roughness coefficient and flow capacity of lower reaches

Beforehand planning the river improvement downstream from the Pamarayan weir, it would be necessary to investigate the roughness coefficient within the lower reaches and to confirm the flow capacity thereof.

The investigation of roughness coefficient should be made by aforementioned analyses of riverbed materials and observed data on water stage and discharge at Kragilan gauging station.

The roughness coefficient within the lower reaches may be expected to have a smaller value than that of upper reaches from the Pamarayan weir, considering the smooth alignment of the river and the smaller grain size of riverbed material as seen from Fig. H-7.

ii) Shortcut and internal drainage

A shortcut may be planned on a large river bend upstream from Kragilan to stabilize the river channel and also to improve the internal drainage of the Cikambuy river which flows down by K-C-C district.

iii) Conservation of flood-retarding effect

To plan conservation of flood-retarding effect in the river section between Kragilan and the Pamarayan weir, some proper area may be specified for conservation of flood-retarding effect by surveying topography and land use, or some retarding basin may be planned to mitigate the flood burden on the lower reaches.

However, judging from the difference of basic high water peaks at Pamarayan and Kragilan on Fig. H-20, the flood discharge at Kragilan will be increased by about 200 m³/sec after improvement of the objective section. Perhaps this discharge increment will not be covered by above-mentioned suggestions and an additional improvement might be necessary on the river section downstream from Kragilan.

REFERENCE

1. "Design drainage project, Ciujung sub-project final report, vol.1 main report, PROSIDA, May 1981.
2. Guideline BP 5B, "Maximum recorded floods in Indonesia updated 1984", Binnie & Partners, Hunting Technical Services.
3. "Report of November 1981 flood", Seksi pengairan Serang, November 1981.
4. "Report of November 1981 flood", Seksi pengairan Pandeglang-Rangkasbitung, November 1981.
5. "Report of flood in Banten", P3SA DPU, November 1981.
6. "Manual for river and sabo works in Japan", Ministry of construction, Japan, 1976.
7. "Outline of economic survey on flood control", Ministry of construction, Japan, March 1980.
8. "Laporan penyelidikan hidrolis dengan model river training Sungai Ciujung di udik bendung Pamarayan", DPMA, Augustus 1982.
9. "Nota perhitungan pengamanan dan rencana biaya Sungai Ciujung di seksi pengairan Serang", DPUP Jawa Barat, September 1978.
10. "Study report on Padang area flood control project", Appendix, JICA, December 1983.

Table H-1

CHARACTERISTICS OF CIUJUNG RIVER BASIN

River Name/Point	Cachment Area CA (km ²)	Length of River Course L (km)	River Slope I	Form Factor F (=A/L ²)
<u>Ciujung River.</u>				
River Mouth	1850	142	1/6000 to 1/5000	0.092
Kragilan Bridge	1812	124	1/3200	0.118
Pamarayan Weir	1451	105	1/3000	0.132
Rangkasbitung	1383	87		0.184
<u>Upper Ciujung River.</u>				
Ciberang River Confluence	594	77	1/2400 to 1/70	0.149
Cibeet River Confluence	273	52		0.089
<u>Ciberang River.</u>				
Ciujung River Confluence	789	87	1/2500	0.105
Cisimeut River Confluence	305	83	1/1800	0.044
Karian Dam Site	288	72	1/1800 to 1/40	0.056
<u>Cisimeut River.</u>				
Ciberang River Confluence	458	64	1/2000	0.114
Ciminyak River Confluence	221	55	1/2000 to 1/40	0.074

Table H-2 CIUJUNG RIVER WATER LEVEL ELEVATION
BY NON-UNIFORM FLOW CALCULATION

Unit: Elevation (m)

No.	Point	n	Discharge Q (m ³ /s)					
			500	750	1000	1250	1500	2000
183	Jeunging	0.025	0.777	1.734	2.451	2.810	3.202	3.931
		0.030	1.111	2.075	2.652	3.134	3.568	4.368
		0.035	1.421	2.320	2.940	3.456	3.924	4.790
150	Kragilan	0.025	3.143	4.216	5.075	5.769	6.394	7.496
		0.030	3.597	4.736	5.623	6.380	7.055	8.247
		0.035	4.006	5.194	6.132	6.938	7.659	8.935
	Pamarayan	0.025	7.899	8.824	9.630	10.349	11.006	12.197
		0.030	8.256	9.276	10.155	10.941	11.663	12.966
		0.035	8.594	9.703	10.652	11.504	12.285	13.695
58	Rangkasbitung	0.025	15.673	16.601	17.388	18.093	18.742	19.913
		0.030	16.060	17.070	17.940	18.713	19.419	20.700
		0.035	16.416	17.510	18.448	19.284	20.035	21.438

Remarks : No. : Measuring Point

n ; Mannings roughness coefficient

Water level of Jeunging and Kragilan by M/P study
report (July 1983).

Table H-3

INUNDATED AREA FROM PAMARAYAN

TO RANGKASBITUNG (Nov. 1981 & Nov. 1983 - Flood)

(Unit: ha)

Land Use	Inundated Depth (m)					Total	
	0.00	0.50	1.00	1.50	2.00		
	to 0.49	to 0.99	to 1.49	to 1.99	to 2.49		
November 1981 Flood	Wet Paddy Field	180	30	10	-	10	230
	Upland Crop Field	110	170	160	200	100	740
	Tree Crop	50	30	40	20	10	150
	Village	10	20	25	10	5	70
	Others	10	20	20	-	10	60
	<u>Total</u>	<u>360</u>	<u>270</u>	<u>225</u>	<u>230</u>	<u>135</u>	<u>1,250</u>
November 1983 Flood	Wet Paddy Field	10	10	-	-	-	20
	Upland Crop Field	180	150	50	-	-	380
	Tree crop	30	10	10	-	-	50
	Village	20	10	5	-	-	35
	Others	10	10	-	-	-	20
	<u>Total</u>	<u>250</u>	<u>190</u>	<u>65</u>	-	-	<u>505</u>

Table H-4 APPRAISEMENT OF HOUSES AND BUILDINGS,
AND HOUSEHOLD EFFECTS OR STORED GOODS
OF 1984 PRICE LEVEL

(Unit: Rp.10⁶)

Kind of Houses and Buildings	Appraisement		Total
	Houses and Buildings	Household Effects or Stored Goods	
Residence	4.2	1.8	6.0
Shop	4.2	4.2	8.4
School	36.0	3.6	39.6
Mosque	12.0	3.6	15.6

Table H-5 RATE OF APPRAISEMENT OF HOUSEHOLD EFFECTS
BY INUNDATED DEPTH ABOVE FLOOD LEVEL

(Unit: %)

Kind of Houses and Buildings	Inundated Depth above Floor level (m)						
	0 to 0.5	0.5 to 1.0	1.0 to 1.5	1.5 to 2.0	2.0 to 2.5	2.5 to 3.0	over 3.0
Residence	55	80	90	95	99	100	100
Shop	40	65	75	90	95	99	100
School & Mosque	55	85	95	99	100	100	100

Table H-6 DAMAGE RATE OF INUNDATED
HOUSES AND BUILDINGS

Inundated Depth above Floor (m)	Damage Rate
0 - 0.49	0.053
0.50 - 0.99	0.072
1.00 - 1.49	0.109
1.50 - 1.99	0.109
2.00 - 2.49	0.534

Source: Outline of Economic Survey on Flood Control,
Ministry of Construction, Japan

Table H-7 DAMAGE RATE OF INUNDATED PROPERTIES

Kind of Properties	Damage Rate
Household Effects of Residence	0.690
Stored Good of Shop	0.597
Properties of School, Mosque	0.632

Source: Outline of Economic Survey on flood Control,
Ministry of Construction, Japan

Table H-8

NUMBER OF INUNDATED HOUSES AND BUILDINGS
FROM PAMARAYAN TO RANGKASBITUNG
 (Nov. 1981 and Nov. 1983 - Flood)

(Unit: number)

	Kind of Houses and Buildings	Inundated Depth (m)					Total
		0.00 to 0.49	0.50 to 0.99	1.00 to 1.49	1.50 to 1.99	2.00 to 2.49	
November 1981 Flood	Residence	280	600	1,020	440	60	2,400
	Shop	5	10	20	10	0	45
	School	0	2	0	0	2	4
	Mosque	1	4	15	4	2	26
	<u>Total</u>	<u>286</u>	<u>616</u>	<u>1,055</u>	<u>454</u>	<u>64</u>	<u>2,475</u>
November 1983 Flood	Residence	730	250	30	-	-	1,010
	Shop	15	5	-	-	-	20
	School	-	-	2	-	-	2
	Mosque	10	3	1	-	-	14
	<u>Total</u>	<u>755</u>	<u>258</u>	<u>33</u>	-	-	<u>1,046</u>

Table H-9 INUNDATED CROP AREA FROM PAMARAYAM
TO RANGKASBITUNG
(Nov. 1981 and Nov. 1983 - Flood)

(Unit:ha)

Crops	Nov. 1981	Nov. 1983
Wetland Paddy	-	-
Upland Crops		
Maize	600	330
Cassava	140	50
Sub-total	<u>740</u>	<u>380</u>
Tree Crop ^{/1}	150	50
<u>Total</u>	<u>890</u>	<u>430</u>

Remark: /1 = Mixed planting of banana and bamboo

Table H-10 CROP DAMAGE VALUES FROM PAMARAYAM
TO RANGKASBITUNG BY FLOOD IN NOV. 1981
AND NOV. 1983

(1) Nov. 1981 Flood

Crops	Gross Inundated Area (ha)	Net Planted Area (ha)	Unit Damage Value (Rp/ha)	Average Damage Factor	Damage Value ^{/1} (Rp 10 ⁶)
Wetland and Paddy	-	-	-	-	-
Upland Crops					
Maize	600	480	68,000	1.00	32.6
Cassava	140	56	300,000	0.10	1.7
Sub-total	<u>740</u>	<u>536</u>			
Tree Crops	150	75	-/2	-	-
<u>Total</u>	<u>890</u>	<u>611</u>			<u>34.3</u>

(2) Nov. 1983 Flood

Crops	Gross Inundated Area (ha)	Net Planted Area (ha)	Unit Damage Value (Rp/ha)	Average Damage Factor	Damage Value ^{/1} (rp 10 ⁶)
Wetland Paddy	-	-	-	-	-
Upland Crops					
Maize	330	264	68,000	1.00	18.0
Cassava	50	20	300,000	0.10	0.6
Sub-total	<u>380</u>	<u>284</u>			
Tree Crops	50	25	-/2	-	-
<u>Total</u>	<u>430</u>	<u>309</u>			<u>18.6</u>

Remarks: /1 = Values based on the market price at the end of 1984

/2 = No crop damage occurred

Table H-11 ACTUAL FLOOD DAMAGE
AT 1984 PRICE
 (Nov. 1981 - Nov. 1983 - Flood)

(Unit: Rp 10⁶)

Item	Nov. 1981	Nov. 1983
Houses and Buildings, Household Effects	3,815.0	1,103.3
Crops	34.3	18.6
Suspension of Business Activities	228.9	66.2
Public Facilities	3,452.6	998.5
Total	7,530.8	2,186.6

Table H-12 CALCULATED CHART OF AVERAGE
ANNUAL DAMAGE

(Unit: Rp x 10⁶)

Probability	Occurrence Probability	Amount of Damage	Average Amount of Damage	(4) (1) x (3)	Average Annual Damage
	(1)	(2)	(3)		
1/1 (1.000)		0			0
1/s (0.500)	0.500	2,186.6	1,093.3	546.7	546.7
1/8 (0.125)	0.375	7,530.8	4,858.7	1,822.0	2,368.7
1/10 (0.100)	0.025	8,300.0	7,915.4	197.9	2,566.6

Table H-13

DAILY RAINFALL IN NOVEMBER 1981

Unit ; mm

Rainfall Gauging Station No.	Name	D a t e																Total
		9	10	11	12	13	14	15	16	17	18							
9	Bojong Datar	-	194.0	3.0	16.0	90.0	57.0	-	227.0	75.0	112.0	774.0						
22	Cimanuk	-	100.0	-	-	52.0	9.0	16.0	115.0	28.0	19.0	339.0						
23	Serang	16.5	-	-	-	-	15.0	19.0	50.0	-	-	100.5						
23 E	Cipanas	5.5	-	-	-	5.0	-	7.5	26.0	2.0	-	46.0						
24	B a r o s	73.0	40.0	-	-	15.0	-	42.0	63.0	22.0	-	255.0						
24 A	N y a p a h	-	7.0	-	-	8.0	5.0	14.0	30.0	-	19.0	83.0						
24 B	P e t i r	-	-	-	-	5.0	8.0	-	-	-	-	15.0						
26	Pandeglang	9.0	90.0	-	-	45.0	1.0	11.0	60.0	73.0	8.0	297.0						
26 B	Cileles	10.3	-	5.0	70.0	31.0	100.0	75.0	25.0	10.0	-	326.3						
30 B	Cikeusik	30.0	30.0	-	40.0	30.0	40.0	65.0	60.0	45.0	90.0	430.0						
31 C	Cipucang Pare	41.0	90.0	-	2.0	33.0	18.0	6.0	45.0	10.0	15.0	260.0						
37	Rangkasbitung	51.0	-	13.0	30.0	-	8.0	46.0	54.0	8.0	-	210.0						
37 B	Cikadu	-	32.0	-	24.0	-	-	48.0	68.0	-	-	172.0						
43 B	Cilaki	-	83.0	10.0	30.0	90.0	34.0	68.0	30.0	-	-	345.0						
44	Cipanas	30.0	10.0	3.0	70.0	20.0	-	20.0	80.0	-	-	233.0						
A.13	Bolang Baji	0.8	-	-	6.4	2.1	4.2	15.8	20.9	1.6	-	51.8						
B.24	Gunung Tunggul	85.9	1.0	6.4	83.5	20.4	31.0	96.3	0.0	3.9	-	328.4						
B.28	Konkol Cisdang	2.8	36.3	14.5	12.3	5.7	24.0	80.7	2.3	-	-	178.6						
B.36	Bantar Jaya	76.8	-	1.3	77.8	14.1	5.6	62.8	45.1	7.5	-	291.0						
B.38	Bojong Barang	-	-	2.0	68.5	19.8	16.1	65.6	49.5	13.9	0.4	235.8						
B.45	Ranca Songgom	-	-	9.7	1.0	1.9	19.7	120.5	24.5	7.0	0.9	185.2						

Table H-14 COEFFICIENT OF THIESEN POLYGON ON NOVEMBER 1981 STORM

(Unit %)

Rain Gauging Station No.	Karian Dam	Ciberang Cisimeut Conf.	Cisimeut Conf.	Ciberang Ciujung Conf.	Upper Ciujung Ciberang Conf.	Rangkas-bitung Upper Basin to Kragilan	Rangkas-bitung	Kragilan
Sub Basin No.	1	2,3	1,4	5,6,7	1to7	Stol2	1to12	
9	-	-	-	2.47	1.06	-	0.81	
22	-	-	-	8.74	3.76	-	2.87	
23 E	-	-	-	-	-	11.08	2.62	
24	-	-	-	-	-	12.58	2.97	
24 A	-	-	-	-	-	26.25	6.21	
26	-	-	-	16.71	7.18	9.78	7.79	
26 B	-	-	-	13.49	5.80	-	4.42	
30 B	-	-	-	-	-	2.19	0.54	
31 C	-	-	-	0.91	0.39	-	0.30	
37	-	0.99	1.54	6.21	4.22	30.63	10.47	
37 B	14.36	18.15	1.54	-	5.56	7.49	6.02	
43 B	24.87	23.48	49.51	8.67	25.30	-	19.31	
44	59.02	55.73	-	-	12.29	-	9.38	
B 24	-	-	19.80	10.99	11.28	-	8.61	
B 28	-	-	-	21.88	9.40	-	7.17	
B 36	1.75	1.65	15.95	-	5.65	-	4.31	
B 38	-	-	9.46	0.14	3.19	-	2.44	
B 45	-	-	2.20	9.79	4.92	-	3.76	
Total	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00
CA (Km ²)	288	305	458	594	1383	429	1812	

Remarks Sub basin No; Ref. Fig. H-12

CA ; Catchment area

Table H-15 AVERAGE RIVER BASIN DAILY RAINFALL
OF NOV. 1981 STORM

(Unit: mm)

Basin Name	Ciberang	Cisimeut	Upper Ciujung	Rangkasbitung (upstream)	Rangkasbitung to Kragilan
Sub Basin No.	1.	2.3	5.6-7	1 to 7	8 to 12
Date 9	18.48	30.04	16.48	21.52	26.94
10	30.87	41.78	44.63	40.15	18.72
11	4.16	7.02	7.25	6.46	3.98
12	48.36	50.82	26.38	40.23	11.86
13	32.61	52.8	39.27	37.64	9.59
14	8.15	25.94	30.07	23.37	4.73
15	37.31	73.05	60.28	60.06	29.97
16	64.52	29.98	38.39	41.69	47.49
17	0.20	3.56	19.57	9.69	13.56
18	0.0	0.05	5.98	2.59	7.74
Total	244.66	315.04	288.30	283.40	174.58

Table H-16 COEFFICIENT OF CONVERSION (R_{ave}/R_i)
TO THE BASIN MEAN RAINFALL

Item	River Basin					
	Ciberang	Cisimeut	Upper Ciujung	Rangkasbitung to Kragilan		
Subbasin No.	<u>1</u>	<u>4</u>	<u>2,3</u>	<u>5</u>	<u>6.7</u>	<u>8,9,10,11,12</u>
R_{ave} (mm)	244.6	244.6	315.0	288.3	281.3	174.6
Rainfall Gauging Station No.	B-24	B-38	B-24	B-28	B-45	B-36
R_i (mm)	328.4	235.8	328.4	178.6	185.2	291.0
R_{ave}/R_i	0.745	1.037	0.959	1.614	1.519	0.600

Remarks: R_{ave} : Subbasin average total rainfall
 R_i : Point total rainfall of each rainfall station

Table H-17

STORAGE FUNCTION COEFFICIENT OF SUBBASIN AND CHANNEL

CHARACTERISTICS AND STORAGE FUNCTION
COEFFICIENT OF SUB-BASIN

Basin No.	Area CA (Km ²)	River Length in watershed L (km)	Average Slope in watershed I	K	P	TI (hr)	Base flow (m ³ /s)	River basin of quaternary volcanic products	River basin of other products	f1	Rsa (mm)
1.	305	72.0	1/80	94.61	0.333	3.3	4.5	41 (%)	59 (%)	0.82	177
2.	179	41.0	1/85	79.46	"	1.9	2.6	31	69	0.84	162
3.	279	63.5	1/85	91.93	"	2.9	4.2	35	65	0.83	170
4.	26	7.0	1/230	61.04	"	0	0.4	0	100	0.93	100
5.	273	51.5	1/110	93.60	"	2.4	4.0	16	84	0.89	132
6.	241	29.5	1/65	66.59	"	1.3	3.5	47	53	0.5	194
7.	80	22.5	1/40	50.25	"	1.0	1.2	64	36	0.75	228
8.	68	12.5	1/220	72.97	"	0	1.0	0	100	0.93	100
9.	41	17.5	1/500	107.32	"	0.8	0.6	53	47	0.78	206
10.	126	36.5	1/90	85.21	"	1.7	1.8	0	100	0.93	100
11.	48	17.0	1/550	109.72	"	0.8	0.7	56	44	0.77	212
12.	146	31.0	1/90	73.32	"	1.4	2.1	0	100	0.93	100

Remarks: K, P: Coefficients of storage function for basin
 TI : Time lag (hr)
 f1 : primary run off ratio
 Rsa : Rainfall until point of saturation

STORAGE FUNCTION COEFFICIENT OF CHANNELS

Channels No.	Length L (km)	TI (hr)	K	P	Qc (m ³ /s)	Nov. 1981 Year Flooding Area (Km ²)
A	11.3	2.25	26.20	0.63	500	7.43
B	7.4	1.47	16.90	0.62	500	2.17
C	18.3	3.35	63.00	0.55	400	8.42
D	3.1	0.75	9.72	0.62	400	2.47
E	10.8	1.88	12.30	0.66	300	(1.61)
F	8.9	1.77	15.48	0.65	300	(1.61)
G	7.9	2.00	13.20	0.67	300	1.61
H	18.0	4.17	24.90	0.67	200	(1.61)

Remarks: TI : time lag (hr)
 K, P: coefficients of storage function for channel
 Qc : flow capacity of channel (m³/s)
 () : assumed flooding area of E, F, and H channel to be equal to that of G channel, 1.61 km²

STORAGE FUNCTION OF FLOODING (UNDER PRESENT CONDITION)

A		B		C		D		E		F		G		H	
Q	S	Q	S	Q	S	Q	S	Q	S	Q	S	Q	S	Q	S
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
200	738	200	451	180	1096	50	110	50	162	140	384	50	182	50	342
300	953	300	580	300	1450	100	169	100	257	300	631	100	289	100	545
500	1314	500	797	400	1700	300	334	300	531	500	879	300	603	300	819
800	1900	800	1400	600	3650	500	1364	500	1364	800	1050	500	1364	500	1364
1100	5180	1100	2100	1100	5000	600	1652	700	1943	1100	1650	700	1943	700	1943
1300	5900	1300	2600	1300	5900	700	1943			1300	2050				
1500	8800	1500	3100	1500	6700	800	2235			1500	2500				
2000	15000	2000	4500	2000	8800	1000	2825								

Remarks: A; B----- H; channel number
 Q : discharge (m³/s)
 S : Channel and flooding storage (m³/s. hr)

Table H-18 COEFFICIENT OF PROBABLE RAINFALL IN SUBBASIN

River Name Point	Catchment Area (Km ²)	Area Reduction Factor a	Subbasin No	Point Rainfall Station No.	R _{pro} (mm)				
					R ₂₄	1/50	1/25	1/10	1/5
<u>Ciberang River</u>									
Karian dam site	288	0.82	1	B-24	96.3	217 (1.84)	198 (1.69)	172 (1.47)	152 (1.29)
Cisimeut Confluence	305	0.80	1	B-24	96.3	212 (1.76)	194 (1.62)	168 (1.40)	148 (1.28)
Ciujung Confluence	789	0.63	1 to 3	B-24	96.3	205 (1.34)	185 (1.21)	157 (1.03)	135 (0.88)
			4	B-38	108.3	200 (1.19)	179 (1.08)	150 (0.91)	126 (0.79)
<u>Cisimeut River</u>									
Ciberang Confluence	458	0.75	2.3	B-24	96.3	236 (1.56)	211 (1.39)	177 (1.17)	149 (0.98)
<u>Upper Ciujung River</u>									
Ciberang Confluence	594	0.76	5	B-28	80.7	236 (2.22)	211 (1.99)	177 (1.67)	149 (1.40)
			6.7	B-45	141.5	215 (1.27)	193 (1.13)	163 (0.95)	139 (0.80)
<u>Ciujung River</u>									
Rangkasbitung	1383	0.61	1 to 3	B-24	96.3	215 (1.36)	193 (1.22)	163 (1.03)	139 (0.88)
			4	B-38	108.3	205 (1.21)	185 (1.09)	157 (0.92)	135 (0.78)
			5	B-28	80.7	215 (1.63)	193 (1.46)	163 (1.23)	139 (1.05)
			6.7	B-45	141.5	200 (0.93)	179 (0.91)	155 (0.70)	118 (0.60)
Rangkasbitung to Kragilan	1812	0.60	8 to 12	B-36	100.9	179 (1.06)	161 (0.96)	155 (0.92)	118 (0.70)

Remarks: Subbasin No. : Ref. Fig. H-12

R₂₄ : maximum 24 hr point rainfall

R_{pro} : Probable daily rainfall by Thiessen Method

() : Coefficient of probable subbasin rainfall hyetograph

(= a · R_{pro}/R₂₄)

$\bar{r}_{ave}(t) = r(t) \cdot (a \cdot R_{pro}/R_{24})$

r : denoted hourly rainfall (mm)

Table H-19 PROBABLE FLOOD DISCHARGE UNDER PRESENT CONDITION

(1) Estimated probable flood discharge by storage function

(Unit: m³/s)

Point	Return Period (years)			
	5	10	25	50
Kragilan	929	1063	1333	1439
Pamarayan	925	1114	1372	1582
Rangkasbitung	999	1216	1495	1728

(2) Estimated probable flood discharge by observed flood date (Gumbel Method)

(Unit: m³/s)

Point	Return Period (years)				
	5	10	15	25	50
Kragilan	892	1013	1081	1165	1279
Rangkasbitung	852	1008	1096	1205	1351

Table H-20

EXPERIENCED ANNUAL MAXIMUM FLOODDISCHARGE DATA AT KRAGILAN AND RANGKASBITUNG

Kragilan			Rangkasbitung		
Ranking	Year	Discharge (m ³ /s)	Ranking	Year	Discharge (m ³ /s)
1	80 81	1070.00	1	80 81	1150
2	73 74	905.20	2	78 79	772
3	75 76	860.99	3	77 78	712
4	71 72	834.48	4	76 77	697
5	70 71	771.07	5	75 76	688
6	76 77	764.17	6	82 83	665
7	74 75	736.80	7	71 72	637
8	69 70	694.57	8	79 80	590
9	82 83	678.00	9	73 74	552
10	72 73	639.60	10	74 75	534
11	79 80	607.31	11	72 73	510
12	78 79	517.88	12	81 82	222
13	81 82	439.00			

Table H-21

FLOOD DISCHARGE DISTRIBUTION OF CIUJUNG RIVER

Estimate Point	Basic High Water					After Flood regulation by Karian dam				
	Return Period (years)					Return Period (years)				
	5	10	25	50	50	5	10	25	50	
<u>Ciujung River</u>										
Kragilan Bridge	1200 (1000)	1500 (1200)	1800 (1400)	2100 (1600)	2100 (1600)	950	1100	1300	1500	
Pamarayan Weir	1100	1300	1600	1900	1900	950	1100	1400	1600	
Rangkasbitung	1100	1300	1600	1900	1900	900	1100	1400	1600	
<u>Upper Ciujung River</u>										
Rangkasbitung	550	700	950	1100	1100	550	700	950	1100	
<u>Ciberang River</u>										
Ciujung River Confluence	700	900	1100	1200	1200	550	700	850	950	
Cisimeut River Confluence	450	550	700	800	800	150	200	220	250	
Karian dam Site	450	550	700	800	800	((140)) 450	((160)) 550	((190)) 700	((210)) 800	
<u>Cisimeut River</u>										
Ciberang River Confluence	450	650	850	1000	1000	450	650	850	1100	

Remarks : () ; under present condition of channel between Kragilan and Pamarayan
 (()) ; Karian dam outflow discharge

Table H-22 CALCULATION RESULT OF FLOOD REGULATION BY KARIAN DAM

(1) RELATION OF SPILLWAY CREST LENGTH AND FLOOD CONTROL EFFECT
(Under Flood of 50 year Return Period)

Iteme	Spillway Crest Length (m)				
	30	40	50	70	100
Inflow Discharge Q_i ($m^3/5$)	800	800	800	800	800
Outflow Discharge Q_o ($m^3/5$)	155	194	208	249	295
$Q_i - Q_o$	645	616	592	551	505
Overflow depth h (m)	1.88	1.74	1.62	1.46	1.29
Storage Volume V ($\times 10^6 m^3$)	31.4	28.9	27.0	24.2	21.3
Disign Storage Volume $1.2V$ ($\times 10^6 m^3$)	37.7	34.7	32.4	29.0	25.5

(2) RELATION OF PROBABLE FLOOD AND FLOOD CONTROL EFFECT
(Under Spillway Crest Length $L = 50$ m)

Item	Return Period (Years)			
	5	10	25	50
Inflow Peak discharge Q_i (m^3/s)	450	550	690	800
Outflow peak discharge Q_o (m^3/s)	140	160	190	210
$Q_i - Q_o$ (m^3/s)	310	390	500	590
Storage Volume V ($\times 10^6 m^3$)	19.6	21.8	24.9	27.0
Over flow depth h (m)	1.19	1.32	1.51	1.62

Table H-23 ALTERNATIVE PLAN OF RIVER IMPROVEMENT

Item	Case-1	Case-2	Case-3
Improvement Length (km)	21.5	22.9	25.0
Required Construction Main Works			
Dredging (x 10 ³ m ³)	559.9	559.9	1,052.5
Excavation (")	1,904.5	1,404.0	533.6
Embankment (")	624.0	674.3	534.8
Land Acquisition and Compensation			
Land	129.4	125.9	60.9
Houses	121	99	99
Construction Cost (Rp. x 10 ⁶)			
Direct Construction Cost	11,241	10,293	10,254
Land Acquisition & Compensation	443	404	397
Administration & Engineering Services	1,415	1,299	1,332
Physical Contingency	1,965	1,801	1,798
<u>Sub-total</u>	<u>15,064</u>	<u>13,797</u>	<u>13,781</u>
Prince Contingency	7,562	6,896	6,479
<u>Total</u>	<u>22,626</u>	<u>20,693</u>	<u>20,260</u>
Benefit (Rp. x 10 ⁶ /yr)	2,570	2,570	2,570
EIRR	10.1	10.5	10.5

Table H-24

REQUIRED CONSTRUCTION WORKS FOR CASE-2

Item	Unit	Ciujung River			Ciberang		Upper Ciujung		Total
		Pamarayan Weir to No.85 (a)	No.85 to No.65 (Short Cut) (b)	No.65 to No.55 (c)	No.54 to No.40 (c)	No.58 to No.46 (e)			
Distance	m	8351	3530	3283	3300	4410	22,874		
Dredging	x10 ³ m ³	559.9	-	-	-	-	559.9		
Excavation (1)	"	141.9	480.0	100.1	-	88.5	810.5		
" (2)	"	-	580.0	-	-	-	580.0		
" (3)	"	-	-	8.9	-	4.6	13.5		
Embankment (1)	"	-	-	-	69.1	-	69.1		
" (2)	"	223.6	-	78.7	-	-	302.3		
" (3)	"	-	248.8	-	-	54.1	302.9		
Sod facing	x10 ³ m ²	131.1	96.7	64.9	41.2	36.9	370.8		
Wet masonry	"	-	-	2.8	-	-	2.8		
Dry masonry	"	-	47.4	-	-	-	47.4		
Gabion	x10m ³	3.9	-	1.1	1.1	0.6	6.7		
Groyn	pc	105	-	30	30	15	180.0		
Drainage	x10 ³ m	4.2	7.0	1.6	1.5	2.2	16.5		
Culvert Box									
I (1.5m x 1.5m x 1)	pc	-	-	-	1	-	1		
II (2.5m x 2.0m x 2)	"	-	-	-	1	-	1		
III (3.0m x 3.0m x 2)	"	1	-	1	-	-	2		
Inspection Road	x10 ³ m	16.7	7.1	6.4	6.2	8.7	45.1		

Remarks: Excavation (1); common
 " (2); common, for short cut, Embankment (1); borrowed materials (L = 1.0 km)
 " (3); softrock " (2) " (L = 0.5 km)
 " (3); softrock " (3) excavated materials

Table H-25 REQUIRED LAND ACQUISITION AND COMPENSATION FOR CASE-2

Item	Ciujung River			Upper Ciujung River		Total
	Pamarayan Weir to No.85	Short Cut No.85 to No.64	Rangkasbitung No.64 to No.55	Ciberang River Rangkasbitung No.54 to No.40	Ciujung River No.58 to No.43	
(1) Land (ha)						
Paddy field	2.84	1.46	0.29	0.21	0.39	5.19
Upland	53.97	27.78	5.50	4.23	7.45	98.93
Forest and field	4.37	3.67	0.72	0.55	0.98	10.29
Settlement	0.53	-	0.43	1.80	0.68	3.44
Others	5.65	1.46	0.29	0.26	0.39	8.05
<u>Total</u>	67.36	34.37	7.23	7.05	9.89	125.90
(2) Compensation (nos)						
Permanent house	1	-	6	2	-	9
Semi permanent house	5	-	19	4	2	30
Emergency house	10	-	39	7	4	60
<u>Total</u>	16	-	64	13	6	99

Table H-26 RIVER CONSTRUCTION COST (CASE-2)

Unit :10 ⁶					
Item	Unit	Q'ty	F.C.	L.C.	Total
1. Direct Construction Cost			6,320	3,973	10,293
Preparatry works/			468	296	764
Civil works					
Dredging	10 ³ m ³	559.9	2,077	487	2,564
Excavetion (1)	10 ³ m ³	810.5	314	400	714
Excavetion (2)	10 ³ m ³	580.0	950	664	1,614
Excavetion (3)	10 ³ m ³	13.5	22	19	41
Embankment (1)	10 ³ m ³	69.1	187	114	301
Embankment (2)	10 ³ m ³	302.3	583	353	936
Embankment (3)	10 ³ m ³	302.9	159	108	267
Sodfacing	10 ³ m ³	370.8	-	70	70
Wet masonry	10 ³ m ³	2.8	40	34	73
Dry masonry	10 ³ m ³	47.4	434	379	812
Cabion	10 ³ m ³	6.7	56	146	202
Groyn	PC	180.0	75	235	310
Drainage ditch	10 ³ m ³	16.5	75	94	169
Culvbert Box					
I (1.5mx1.5mx1)	PC	1.0	34	7	41
II (2.5mx2.0mx1)	PC	1.0	53	35	88
III (3.0mx3.0mx2)	PC	2.0	116	77	193
Inspection Road	10 ³ m ³	45.1	145	121	266
Miscellaneous			532	334	866
2. Land Acquisition and Compensation			-	404	404
3. Adminjstration and Engineering Services			949	350	1,299
4. Physical Contingency			1,091	710	1,881
<u>Total</u>			8,360	5,437	13,797
6. Price Contingency			2,433	4,463	6,896
Grand Total			10,793	9,900	20,693


Table H-27(1) ANNUAL DISBURSMENT SCHEDULE OF RIVER IMPROVEMENT COST (CASE-2)

	(Unit : Rp. 10 ⁶)											
	1986		1987		1988		1989		1990		1991	
	F.C.	L.C.	F.C.	L.C.	F.C.	L.C.	F.C.	L.C.	F.C.	L.C.	F.C.	L.C.
1. Direct Construction Cost	6320	3793			970	576	2180	1380	2421	1568	749	449
2. Land Acquisition		404		211		112		31				
3. Administration and Engineering Services	949	350	395	198	55	37	123	76	136	76	42	32
4. Physical Contingency	1091	710	76	38	150	104	337	218	374	232	116	70
<u>Total</u>	<u>8360</u>	<u>5437</u>	<u>471</u>	<u>236</u>	<u>1175</u>	<u>829</u>	<u>2640</u>	<u>1755</u>	<u>2931</u>	<u>1878</u>	<u>907</u>	<u>551</u>
5. Price Contingency	2433	4463	48	37	253	475	729	1388	997	1830	369	667
<u>Grand Total</u>	<u>10793</u>	<u>9900</u>	<u>519</u>	<u>273</u>	<u>1428</u>	<u>1304</u>	<u>3369</u>	<u>3093</u>	<u>3928</u>	<u>3708</u>	<u>1276</u>	<u>1218</u>


Table H-27(2) ANNUAL DISBURSMENT SCHEDULE OF SHARED KARIAN DAM CONSTRUCTION COST BY FLOOD CONTROL SECTOR

	(Unit : Rp. 10 ⁶)											
	1986		1987		1988		1989		1990		1991	
	F.C.	L.C.	F.C.	L.C.	F.C.	L.C.	F.C.	L.C.	F.C.	L.C.	F.C.	L.C.
1. Direct Construction Cost	5523	3472			848	503	1905	1206	2116	1371	654	392
2. Land Acquisition		343				95	68					
3. Administration of Engineering Services	829	305	345	173	48	32	107	66	119	68	37	28
4. Physical Contingency	953	618	66	33	42	131	295	190	327	202	101	61
<u>Total</u>	<u>7305</u>	<u>4738</u>	<u>411</u>	<u>206</u>	<u>1027</u>	<u>720</u>	<u>2307</u>	<u>1530</u>	<u>2562</u>	<u>1641</u>	<u>792</u>	<u>481</u>
5. Price Contingency	2125	3891	42	27	221	413	637	1166	871	1598	322	582
<u>Grand Total</u>	<u>9430</u>	<u>3629</u>	<u>453</u>	<u>238</u>	<u>1248</u>	<u>1133</u>	<u>2944</u>	<u>2696</u>	<u>3433</u>	<u>3239</u>	<u>1114</u>	<u>1063</u>

(1) PROFILE OF CIUJUNG RIVER BASIN



(2) CIUJUNG RIVER BASIN DIAGRAM









 MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
 (1) Profile of Ciujung River Basin
 (2) Ciujung River Basin Diagram
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. H-3





 MINISTRY OF PUBLIC WORKS
DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
FEASIBILITY STUDY ON KARIAN
MULTIPURPOSE DAM CONSTRUCTION PROJECT

Pamarayan Weir

JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. H-4





 MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT

Rangkusbitung By-pass Plan

JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. H-5










 MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
 Groyne on Ciberang and Upper
 Ciujung River
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. H-6



MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
**Rating Curve and Manning's Roughness
 Coefficient by Nov. 1981 Flood**
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. H-7



SUMPLE NO.	DISTANCE OF FROM TO RIVER MOUTH X (km)	D50/1 (mm)	Dn/2 (mm)	Pn/3 (%)
CIUJUNG RIVER				
U-11	15.7	0.4	0.7	76.2
U-8	20.8	0.3	0.5	89.9
U-6	21.0	0.3	0.5	86.5
U-5	27.5	1.3	2.1	89.5
U-10	27.9	1.0	1.6	73.3
U-4	37.4	1.0	2.1	84.9
U-7	38.2	0.6	1.5	78.0
U-3	43.5	0.5	0.8	79.3
U-2	53.1	0.3	0.6	80.7
UPPER CIUJUNG RIVER				
U-1	58.0	0.4	0.8	79.2
CIBERANG RIVER				
B-3	56.5	0.35	1.1	86.3
B-2	58.0	1.0	3.2	78.8
B-1	59.0	0.7	2.5	78.8
CISIMEUT RIVER				
S-1	59.0	1.5	3.1	73.2
S-2	62.5	0.4	0.7	87.2

REMARKS /1; 50% grain size
 /2; AVERAGE GRAIN SIZE
 /3; PERCENTAGE OF AVERAGE GRAIN SIZE



MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT

Profile of Ciujung River Bed
 Materials

JAPAN INTERNATIONAL COOPERATION AGENCY

(1) PRESENT LONGITUDINAL WATER LEVEL PROFILE OF CIUJUNG RIVER




Fig. H-8(1)




 MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
**Present Longitudinal Water Level
 Profile of Ciujung River**
 JAPAN INTERNATIONAL COOPERATION AGENCY


Fig. H-8(2)

(2) PRESENT LONGITUDINAL WATER LEVEL PROFILE OF UPPER CIUJUNG RIVER




MINISTRY OF PUBLIC WORKS
DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
FEASIBILITY STUDY ON KARIAN
MULTIPURPOSE DAM CONSTRUCTION PROJECT
Present Longitudinal Water Level
Profile of Upper Ciujung River
JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. H-9(1)



MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
**Flow Capacity and Characteristics
 of Cijung River**
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. H-9(2)






 MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
**Flow Capacity and Characteristics
 of Upper Ciujung River**
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. H-10





SCALE



Nov. 1981 Flood
Inundated Area



LEGEND


-  : Village
-  : Paddy Field
-  : Upland Field
-  : Plantation




MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
 Inundated Area Along Ciujung River
 from Pamarayan to Rangkasbitung

JAPAN INTERNATIONAL COOPERATION AGENCY

(1) OBSERVED RATING CURVE AT RANGKASBITUNG (DPMA) Fig. H-11



(2) RELATION BETWEEN FLOOD DISCHARGE AND DAMAGE
(Upstream from Pamarayan)




MINISTRY OF PUBLIC WORKS
DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
FEASIBILITY STUDY ON KARIAN
MULTIPURPOSE DAM CONSTRUCTION PROJECT

Relation between Flood Discharge
and Damage

JAPAN INTERNATIONAL COOPERATION AGENCY


Fig. H-12






SCALE
5 0 5 10 (km)

MINISTRY OF PUBLIC WORKS
DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
FEASIBILITY STUDY ON KARIAN
MULTIPURPOSE DAM CONSTRUCTION PROJECT
Subbasin and Channel for
Runoff Analysis
JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. H-13



LEGEND




-  sub-basin
-  channel & inundated area
-  calculation point No.



MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT

Rainfall-Runoff Model Diagram




JAPAN INTERNATIONAL COOPERATION AGENCY



MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
 Hourly Rainfall data
 in November 1981

JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. H-14(2)





 MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
 Hourly Rainfall data
 in November 1981
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. H-15





Fig. H-16



MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT

Discharge Hydrograph
 of Nov. 1981 Flood

JAPAN INTERNATIONAL COOPERATION AGENCY

(Basic highwater of 10 year return period)








Fig. H-18





 MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
 Hydrograph of Flood Regulation
 by Karian Dam
 JAPAN INTERNATIONAL COOPERATION AGENCY


(10 YEAR RETURN PERIOD)



Under present condition with flooding in the section from Kragilan to Pamarayan weir


 MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
 Basic High Water and
 Design Flood Hydrograph
 JAPAN INTERNATIONAL COOPERATION AGENCY

(10-Year Return Period)



Unit : m³/s

() : Basic High Water

* : Design Discharge by PROSIDA




MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT

Design Discharge Distribution
 of Ciujung River

JAPAN INTERNATIONAL COOPERATION AGENCY


Fig. H-21




MINISTRY OF PUBLIC WORKS
DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
FEASIBILITY STUDY ON KARIAN
MULTIPURPOSE DAM CONSTRUCTION PROJECT
Alternative Plans
of River Improvement

JAPAN INTERNATIONAL COOPERATION AGENCY

TYPICAL CROSS SECTION OF DYKE



INSPECTION ROAD




MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT





Typical Cross Section of Dyke
 and Inspection Road

JAPAN INTERNATIONAL COOPERATION AGENCY


Fig. H-23(1)



LEGEND


-  : Embankment
-  : Drainage Culvert
-  : Excavation Line
-  : Groyne

SCALE
0 500 1000(m)





 MINISTRY OF PUBLIC WORKS
DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
FEASIBILITY STUDY ON KARIAN
MULTIPURPOSE DAM CONSTRUCTION PROJECT


Plane Arrangement (Case-2)

JAPAN INTERNATIONAL COOPERATION AGENCY



LEGEND

-  : Embankment
-  : Drainage Culvert
-  : Excavation Line
-  : Groyne





 MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
 Plane Arrangement (Case-2)
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. H-24





Fig. H-25(1)



Proposed Plan	HWL Gradient	1/1550	1/2430	1/2650	1/3280			
	River Bed Gradient	L=9266	1/3040	L=9123	1/2310			
	Top-of Levee (ELm)	12.00 12.05	13.55	16.13	18.27 18.44			
	High Water (ELm)	11.00 11.05	12.55 12.91	15.13 16.07	17.27 17.44 17.63 17.67			
	River Bed (ELm)	6.00	6.76 6.94	7.85	11.07 11.27 11.53 11.60			
Distance (m)	0 85 735 955	2403 2953	5703	8351 9351 9851 10851	11881 12311 14011 14470 15089 15239 16076	17082 18214 18714	20014	22744
Section NO.	P.W. 103 100 99	95 94	90	85 S83 S82 S80	65 64 60 58 55 54	50 45 40 39	35	30






 MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
 Longitudinal Profile of
 Cijung River (Case-2)
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. H-25(2)




 MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
**Longitudinal Profile of
 Upper Ciujung River (Case-2)**
 JAPAN INTERNATIONAL COOPERATION AGENCY



EFFECT OF UNDER DISCHARGE 1100 m³/s


ITEM	WATER LEVEL	DRAW DOWN
	EL (m)	
PRESENT CONDITION	18.08	---
ONLY DREDGING AT PAMARAYAN TO NO.85	17.76	0.32
ONLY SHORT CUT (NO.85~64)	17.36	0.72
DREDGING AND SHORT CUT	17.18	0.90



MINISTRY OF PUBLIC WORKS
DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
FEASIBILITY STUDY ON KARIAN
MULTIPURPOSE DAM CONSTRUCTION PROJECT

Effect of Dredging and Short Cut
on Water Level at Kangkasbitung

JAPAN INTERNATIONAL COOPERATION AGENCY




MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT

Cross Section of Ciujung River
 (Case-2)



JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. H-27(2)



MINISTRY OF PUBLIC WORKS
 DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
 FEASIBILITY STUDY ON KARIAN
 MULTIPURPOSE DAM CONSTRUCTION PROJECT
 Cross Section of Ciujung and
 Ciberang River (Case-2)
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 27(3)




MINISTRY OF PUBLIC WORKS
DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
FEASIBILITY STUDY ON KARIAN
MULTIPURPOSE DAM CONSTRUCTION PROJECT

Cross Section of Upper Ciujung
River (Case-2)

JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. H-28



MINISTRY OF PUBLIC WORKS
DIRECTORATE GENERAL OF WATER RESOURCES DEVELOPMENT
FEASIBILITY STUDY ON KARIAN
MULTIPURPOSE DAM CONSTRUCTION PROJECT

Groyne

JAPAN INTERNATIONAL COOPERATION AGENCY