

2000年10月1日現在

2000年10月1日現在

2000年10月1日現在

2000年10月1日現在

2000年10月1日現在


2000年10月1日現在

2000年10月1日現在

フィリピン共和国
公共事業省

マヨン火山砂防基本計画
ヤワ川支川パウブラボド川砂防施設

設計報告書



1980年2月

国際協力事業団

国際協力事業団		
受入 月日	84. 4. 21	118
		55.3
登録No. 03750		SDF

ま え が き

マヨン砂防洪水防ぎ基本計画の調査実施要綱及び実施計画書に定められた作業範囲に従って、調査団は1979年10月中旬より、フィリピン政府公共事業省タスク・フォース (Task Force for Flood Control and Related Activities) の事務所において、砂防施設の設計作業を行なった。

本設計は1979年10月22日に行なわれた調査団とタスク・フォースとの打合せに基づき、下記の地点および砂防施設について実施したものである。

地 点 — ヤワ川支川パワブラボド川

施 設 — 上流の砂防ダム1基、中流部の導流堤2基
及び下流部の床固め工

ただし、下流部については、床固め工のみならず、堤防を含めた河川改修についても検討を行なった。

本報告書は、上記砂防施設の設計、施工方法、工事費見積りの他、堤防及び根固め工を含む河川改修をも網羅している。

本報告書はタスク・フォースの緊密な協力の下に作成されたものである。

目 次

I	概 要	1
1.1	背 景	1
1.2	地 点 選 定	1
1.3	施 設 選 定	2
II	砂防施設の概要	4
III	施 設 設 計	8
3.1	砂 防 ダ ム	8
3.2	導 流 堤	10
3.3	河 川 改 修	11
IV	工 事 数 量	16
V	施工計画及び工事工程	17
VI	工 事 費	19

付 録 I 設 計 計 算 書

付 録 II 施 工 計 画 及 び 工 事 工 程

付 録 III 工 事 費 積 算

付 録 IV 設 計 図 面 集

I 概 要

1.1 背 景

フィリピン政府と国際協力事業団との間で合意されたマヨン火山砂防洪水防ぎ基本計画調査実施要綱、及び調査団が提出し、タスク・フォースにより承認された調査実施計画書にしたがい、調査団は、1980年に実施予定の全体基本計画に先だて、代表的な砂防施設の設計を1979年度に実施した。

ここにまとめられた詳細設計は、1980年度の全体基本計画の中で優先度の高いものとして選ばれると期待される設計対象地点、及び施設について実施したものである。

1.2 地点選定

計画対象地域内には、マヨン火山山腹に源を発する多くの急流河川がある。これらの河川は現在も多量の土砂を生産し、中下流部の土砂及び洪水被害の原因となっている。調査団は現場踏査の結果、ヤワ川の支川パウブラボド川を砂防施設設計の対象河川に選定した。その理由は下記の通りである。

- 1) 堤防、流路工及び床固め工等の河川施設は、計画対象地域内河川の詳細な、かつ総合的な調査検討の後設計されるべきである。詳細な検討を行わずに不適当な設計を実施にうつした場合、河道の安定に予期せぬ問題が発生するおそれがある。

このような観点から、数多くの支流分流が複雑に交錯するキナリ川は1979年度に実施すべき詳細設計の対象から除外した。

- 2) 計画対象地域内には、多量の土砂の流出によって、土砂及び洪水被害をもたらしている急流河川が多く、また、重要なインフラストラクチュア、家屋、農地等も存在する。なかでも、ナシン川、カマリグ川、マニニラ川、ヤワ川等の被害は深刻である。

これらの川の中から、下記の理由により、ヤワ川の支川であるパウブラボド川を実施設計の対象河川に選定した。

- a) ヤワ川の侵食は激しく、その上流から大量の土砂を流出している。また、中流には広大な荒廃地が広がっている。洪水時上流からの土石流が、中流域のココナツ林、村落、農地に被害をもたらし、さらに下流では、いくつかの村落、国道、レガスビ市等が、洪水被害におびやかされている。
- b) ヤワ川は、河道延長約20 Kmで4本の支川を持つ計画対象地域内では比較的小さな

河川である。この4支川のうち、2支川の荒廃が特に激しく多量の土砂を流出している。

一つは最上流に位置する支川であり、いま一つは最下流の支川でパウブラボド川と呼ばれている。パウブラボド川はその下流にレガスビ市の人口密集地をひかえ、非常に重要な河川である。

- c) フィリッピン側の、技術者に対する砂防洪水防ぎよ技術の移転を考えた場合、数種の砂防施設を1つの河川にまとめて設計を実施することは非常に有効であろう。
- d) 設計の対象河川として、パウブラボド川を選定するための経済評価は1980年度に実施する基本計画の中に包含されることになるが、パウブラボド川の砂防施設は、経済的に妥当であると評価されるものと期待できる。

1.3 施設選定

前述したようにパウブラボド川は、その上流で非常に多量の土砂を流出している。この土砂は中流部に堆積し、下流に影響を及ぼす2次的侵食及び2次的土砂流出の直接の原因となっている。下流部にはココナッツ、米等の農地や村落があり、常時土石流及び洪水の被害の危険にさらされている。

このような流域の状況から、つぎのような対策の実施が望ましい。

- 1) 土砂の生産を減少させるために、上流部に砂防ダムを築造する。
- 2) 上記砂防ダム直下流に低い高さの砂防ダム、即ち、床固め工を行う。これらのダムは、相互に関連して、河床及び流路の安定に寄与するであろう。
- 3) 現在膨大な土砂の堆積により荒廃している中流部に練石積み導流堤を建設し、遊砂地を造成する。この遊砂地は、洪水時の土砂の流出を一時抑制し、非洪水時に、堆積した土砂を下流に流す機能を有するものとする。
- 4) ヤワ川との合流点に近い下流域では堤防の築造により、流路を安定させる。パウブラボド川には、既存の施設として一部堤防が築造されており、その部分では、流路が堤防により規制されているが、部分的な土砂の堆積や、逆に部分的な河床の侵食が見られる。上流部における砂防施設建設が進むと、下流への土砂の供給が次第に減少し、下流部の河床低下を引越し、場合によっては堤防基礎洗掘の原因となる。これを防ぐためには、堤防基礎の根固め工及び河床の床固め工が必要となる。

上述した砂防施設は、同時にすべてを建設せず、建設による河川の状況の変化を注意深くみながら段階的に施工するべきである。第一期工事とし、下記の施設の建設が望ましい。

- a) 最上流部に砂防ダム

b) 中流部に導流堤からなる遊砂地

c) 堤防築造、並びに沈枠による根固め工及び床固め工

今年度の設計は上記の砂防施設について実施する。

Ⅱ 砂防施設の概要

前章に述べたように、第一期工事分の下記の砂防施設の設計を行った。

- 1) 上流部の砂防ダム (1 基)
- 2) 中流部の導流堤 (2 基)
- 3) 堤防、根固め工及び床固め工を含む河川改修

上記施設の概要及び地勢、構造の諸元はつぎの通りである。

砂 防 ダ ム

地 勢

標 高	約 E L. 4 0 0 m
流 域 面 積	2.5 Km ²
ダム上流部流路長	3.8 Km
ダム上流部平均河床勾配	1/2.3
ダム地点河床勾配	1/11.1

主砂防ダム

型 式	重力式コンクリートダム
堤 頂	
越 流 部	E L. 3 9 8.5 5 m
非 越 流 部	E L. 4 0 2.0 5 m
堤 高	
越 流 部	1 0.0 m
非 越 流 部	1 3.5 m
堤 長	
全 体	7 9.5 m
越 流 部	3 0.0 m
堤 頂 幅	3.0 m
堤体上流側法勾配	1 : 0.4
堤体下流側法勾配	1 : 0.2
設計洪水流量 (100 年確率洪水)	1 0 3.1 m ³ /S
土砂堆積容量	1 3,0 0 0 m ³
堤 体 積	5,2 2 0 m ³

副砂防ダム

型	式	重力式コンクリートダム
堤	高	
	越流部	5.0 m
	非越流部	7.5 m
堤	長	
	全体	57.5 m
	越流部	30.0 m
堤	頂幅	2.0 m
堤体上流側法勾配		1 : 0.4
堤体下流側法勾配		1 : 0.2
堤	体積	1,170 m ³

導流堤

地勢

流域面積	7.3 km ²
上流部流路延長	7.8 km
上流部平均河床勾配	1/38
導流堤地点河床勾配	1/16

第1導流堤

型	式	練石積
堤	高	4.5 m
堤	長	200 m
側法勾配（表法、裏法とも）		1 : 0.7

第2導流堤

型	式	練石積
堤	高	4.5 m
堤	長	162 m
側法勾配（表法、裏法とも）		1 : 0.7

河川改修

地勢

位	置	ヤワ川合流点より 3,910 m 上流まで
---	---	-----------------------

流域面積	ヤワ川合流点 10.5 Km ²
流路延長	バワブラボド川全長 8.0 Km
平均河床勾配	バワブラボド川全体 1/15
	河川改修対象区間 1/17～1/43
流路	
延長	2,800 m
幅員	60 m
計画河床勾配	1/17.5～1/28.1
堤防	
型式	盛土（表法練石張り）
延長	
左岸－全体	2,799 m
既設	1,447 m
新設	1,352 m
右岸－全体	2,808 m
既設	204 m
新設	2,604 m
盛土量	62,800 m ³
練石張り面積	3,956 m ²
根固め工	
型式	玉石詰め沈枠
寸法	2.0 m（幅）× 2.0 m（長さ）× 0.8 m（深さ）
配列	3 列
沈枠総数	6,993 個
床固め工－Aタイプ	
型式	玉石詰め沈枠
寸法	2.0 m（幅）× 2.0 m（長さ）× 0.8 m（深さ）
箇所数	9 ケ所
沈枠総数	970 個
床固め工－Bタイプ	
型式	玉石詰めコンクリート十字ブロック

寸	法	2.0 m (幅) × 2.0 m (長さ) × 0.8 m (深さ)
箇	所	2 ヶ所
ブ	ロ	3 0 5 個
ッ	ク	
総	数	

Ⅲ 施 設 設 計

3.1 砂 防 ダ ム

1) 位 置

砂防ダムサイトは、パウブラボド川上流、標高約400 mに位置し、地形的には土石流の流出口のような地形となっている。この地点から下流域では河道両サイドの比高は、3～5 m程度と低く、ダムサイトとしての適地は見当らない。

2) ダ ム 形 式

砂防ダムの形式には、重力タイプ、枠タイプ、ブロックタイプ等数種のタイプがあるが、パウブラボド川のように急流荒廃河川で、土石流の発生が予測される河川には重力タイプ以外は適さないので一般的な重力式砂防ダムを採用する。

3) ダ ム 高

この砂防ダムの目的は、主として溪岸の側方侵食の防止及び軽減であり、土石流を捕捉あるいはコントロールするものではない。

地形条件からは、高さ15～20 m程度のダムの築造は可能であるが、経済的観点からそのような高いダムは必ずしも適当ではない。

土石流による側方侵食は溪岸の低い部分で生じていると判断され、砂防ダムは堆砂により溪岸を保護するように築造すべきである。

このような考え方から、砂防ダムの有効高を7 mとして設計する。

河床の堆積物の厚さは相当深いものと推定され、ダムはフローティングタイプとならざるを得ない。砂防ダムの根入れは基礎洗掘に対する安全性から3 mとし、上記有効高7 mを加えて水通し天端までの高さは10 mとする。

袖部の高さは2.5 mの水通し高さ、袖の勾配による高さ1 mを加え13.5 mとする。このことについては次節で述べる。

4) 水 通 し 部

水通し部は100年確率洪水流量に対して設計する。パウブラボド川においては流量資料が得られないので、レガスビ市の日雨量記録から合理式を用いて、100年確率洪水流量を計算する。含砂を見込んだ100年確率洪水流量は103.1 m³/secとなる。

砂防ダムの水通し幅は一般に現況河川の幅と同程度、或は多少小さめにとる。現況河川幅はほぼ40～50 mであり、ダム直下流の兩岸侵食に対する余裕を見込んで水通し幅は30 mとする。水通し幅30 mに対する越流水深は1.6 mとなり、0.9 mの余裕高を見込

んで、洪水疎通の為の水通し高さを2.5 mとする。また、袖勾配を1 mの高さまで1:15の勾配をつけ、袖を含めたダム高は13.5 mとする。

詳細は添付の設計図面集を参照のこと。

5) ダム本体の形状

天端厚、上、下流のり勾配等の構造の詳細は下記のように設計した。

ダム天端は土石流の衝撃に耐えるよう3 mの厚さとする。下流側のり勾配は、一般に水通し部からの落石による損傷を避けるように設計すべきであり、ここでは1:0.2の勾配を採用した。

転倒、滑動及び内部応力に対する堤体の安全性を考慮し上流側のり勾配は1:0.4とした。堤体は以下の条件を満足するよう設計した。

i) 転倒に対する安全性から合力の作用点は堤敷のミドル・サードに入らなければならない。

ii) 滑動に対する安全率は1.2以上でなければならない。

iii) 基礎に作用する応力は、70 ton/m²以下でなければならない。これは、基礎が締った土砂礫の場合の推定許容支持力である。

本設計の結果をまとめると下記の通りである。

転倒に関する安全性

$$e = 1.39 \text{ m} < \frac{B}{3} \times \frac{1}{2} \left(= \frac{9.00 \text{ m}}{3} \times \frac{1}{2} = 1.50 \text{ m} \right)$$

ここに e : 偏心距離

B : 堤敷幅

滑動に対する安全率 $2.5 > 1.2$

基礎地盤応力 $38 \text{ ton/m}^2 < 70 \text{ ton/m}^2$

堤体の安定計算の詳細は付録Iを参照のこと。

6) 前庭保護

本ダム直下の洗掘の防止と堤体の安全の保持のため本ダムの下流、前庭部に副ダムを築造する。副ダムの高さは、主ダムとの重複高3.0 m、根入れ深さ3.0 m、及び重複高と根入れ深さの重複分1.0 mを差し引いて5.0 mとする。副ダムは、それによって形成される水褥池で水通し部からの落下水脈のエネルギーを十分に減勢するように、主ダムから22.0 mの距離に設置する。

副ダムの詳細は設計図面集を参照のこと。

3.2 導 流 堤

1) 位 置

導流堤は、パワブラボド川の中流に配置する。導流堤は遊砂地の1つの構成要素であり、遊砂地は最終的には多くの導流堤及び横工等により、構成されるものである。しかしながら、これらの構造物は段階的に築造すべきであり、まず第一段階として、2基の導流堤の築造を提案する。これら2基の導流堤は標高約165 m、河川改修の開始点近くに設置する。

2) 型 式

導流堤は、土石流の衝撃力に十分耐え得る様に内部を砂礫材料で盛立て、表法、裏法面とも練石積で保護した構造とする。

3) 堤 高

導流堤が築造される付近では、明確な流路は形成されていない。それゆえ実際の川幅は、この様な流れに用いられる経験式に基づいて推定した。必要川幅は約30 mとなる。また、水深は1.1 mとなる。この地点においては、流向は定まらず、河床の洗掘、上昇による河床変動は激しいものと考えられるので、導流堤の有効高は十分余裕を見込んで3.0 mとし、根入れは洗掘に対する安全を保持するため1.0 m以上とする。したがって、導流堤の高さは約4.5 mとなる。

4) 堤 長

懸案地点では明確な流路が形成されず、土砂堆積の多い広大な荒廃地となっており、水流は蛇行している。流れが、遊砂地から逃げないように規制するためには地形条件を考慮すると、やや長い導流堤が必要である。

以上のことから導流堤の長さを次のように決定する。

№1 導 流 堤 $L = 200\text{ m}$

№2 導 流 堤 $L = 162\text{ m}$

5) 標準断面

導流堤の法勾配は洪水の越水を極力さけるため、表法、裏法とも1 : 0.7で設計する。天端幅は、土石流の衝撃力と導流堤の安全性を考慮して3.0 mとする。導流堤脚部は洗掘が予想されるので根固めコンクリートブロックを設置する。

3.3 河川改修

3.3.1 基本的考察

レガスビ市技術部は、1979年10月現在、パウブラボド川の下流区間において左岸側1,447 m、右岸側204 mの堤防建設をすでに実施しており、さらに、既設堤防から上下流に向けて、既設堤防を延長して行くことを計画している。

パウブラボド川は上流からの多量の土砂の流入により現在なお安定していない。そのような河川の全区間にわたって、堤防や永久河川構造物を一度に建設することは危険な場合もありうる。砂防施設や河川改修の進展に伴う河川の変化を観察しつつ、段階的に建設して行くべきであろう。

既設堤防の脚部は各所において、侵食や洗掘を受けており、早急に根固め工を実施する必要がある。この侵食や洗掘は上流の砂防工事の進行とともにさらに深刻なものとなろう。

本章では、先づ、河川改修計画を行なうとともに、それに伴う河川構造物の設計を行なう。

3.3.2 河川改修計画

1) 河道現況

現況河道の流下能力、流砂能力を河川縦断図、横断図及び河床材料調査結果より推定すると、付録IのFig. 4.2 のようになる。図より、以下の事が判る。

(I) 現河道幅は30 mないし100 mで、平均60 mとなっている。

(II) 流下能力はほぼ0 m³/secから500 m³/sec 以上と、大きく変化している。特にSta. 1+100 からSta. 2+400までの区間は、余裕高なしと仮定しても、後述の50年確率洪水流量の240 m³/sec よりかなり小さい。又、既設堤防より上流、すなわち、Sta. 2+800より上流では、流路は大きく広がっており、かつ、定まった河道もないため、流下能力を規定しがたい。

(III) 流砂能力は上、下流間で約3倍の開きがあるが、流砂問題の複雑さ、現在の流砂公式の精度を考慮すれば、この程度の差は河道にとってそれほど重大なものではなからう。パウブラボド川はヤワ川本川の河口より約2.3 Km上流の地点で、ヤワ本川と合流するため、ヤワ本川とパウブラボド川とは流砂量についても、お互いに関連する。パウブラボド川の縦横断形状は、理論的には、ヤワ本川とパウブラボド川との流砂能力が平衡状態になるよう定められるべきである。もし、パウブラボド川からヤワ本川へ余分な流砂が供給されたならば、ヤワ本川の河床が上昇し、堆砂が起るであろう。したがって、パウブラボド川の流砂量はヤワ本川への流入許容量に制限されるべきである。河床材料試験

結果及び水文資料に基づく概略検討によれば、上述の条件を満足するパワブラボド川の平衡河床勾配は、現況河床勾配が $1/43 \sim 1/17$ であるのに対して $1/80$ と推定される。この平衡勾配 $1/80$ は上流部における砂防施設が完全に実施された場合に実現されるであろう一つの理想的な勾配を示すものであり、それほど短期間に実現するものではないであろう。現状では、ヤワ本川とパラブラボド川には、かなりの相異があり、パワブラボド川の流砂能力がかなり小さくなっている。以上の考察から、上流の砂防工事が河川の安定のために最も重要であると判断できる。

2) 基本計画

(I) 計画洪水流量

河川改修計画及びそれに伴う構造物の設計対象洪水はパラブラボド川の河川規模を考慮して 50 年確率洪水流量を採用する。ただし、対象地点には既往洪水資料がないので、砂防ダムの設計と同様、日雨量より算定すると、50 年確率洪水流量は $240 \text{ m}^3/\text{sec}$ (流域面積 10.5 km^2 、比流量 $22.86 \text{ m}^3/\text{sec}$) となる。ただし、砂防ダムの設計では土砂の含有を見込んだが河川設計では考慮しないものとする。

(II) 対象区間

河川改修対象区間は、ヤワ本川合流点より、その上流の Sta. $3+900$ 、すなわち、遊砂地までとする。前述のように、Sta. $1+100$ より Sta. $3+900$ までの区間では、既設堤防のある区間を除いては、計画洪水流量である 50 年確率洪水流量に対し流下能力が不足している。したがって、この区間を第 1 期改修区間として取り上げる。

残りの区間、すなわち Sta. $0+000$ から Sta. $1+100$ までの区間は将来改修するものとする。ただし、将来における改修は、河川の変化を観察しつつ、実施時に再度検討することが必要である。

(III) 河道幅

前述のように、現河道幅は平均約 60 m となっているが、安定はしていない。したがって、現実的な河道幅はレジーム理論に基づく経験式により算定すると、約 60 m となる。さらに、既設堤防区間が $60 \sim 90 \text{ m}$ の幅で施工されていることを考慮し計画河道幅を 60 m と決定する。

(IV) 法線

現河道は下流区間でかなり蛇行しているため、法線はできるだけ滑らかになるよう修正した方がよい。法線は下記の事項を考慮し、設計した。

a) 法線はできるだけ現況とうりとする。

b) 河道の曲率半径は川幅の 10 倍以上とする。

但し、地形上それが確保できない場合は、川幅の 5 倍まで許容する。

c) 既設堤防はそのままとする。

d) 家屋及び田畑等はできるだけ避けるものとする。

(V) 縦断

前述のように、パウブラボド川の平衡河床勾配は、上述の砂防工事が完了したものと仮定すると、約 $1/80$ となる。しかしながら、この勾配は理想的な勾配であり、それほど短期間には実現しないであろう。したがって、河川縦断は現時点では、工事費を最小にするように、できるだけ現河床勾配に合せ計画し、計画河床勾配は $1/17.5$ から $1/28.1$ とする。

(VI) 横断

パウブラボド川は全区間にわたって、非常に急流な河川であることから、河道断面は単断面を採用する。断面寸法は、流れを等流と仮定して、マニング式により算定する。

また、余裕高は 1.0 m とした。標準断面の詳細は設計図面集を参照のこと。

(VII) 河川構造物

以上の河川改修計画に伴い必要となる河川構造物は堤防、根固め工、床固め工及び農業用取水施設であり、以下の章において、各々の設計について述べる。

3.3.3 堤防

1) 位置

改修河川の全区間の兩岸に堤防を建設するものとする。既設堤防延長 $1,651\text{ m}$ を含め、総延長は $5,607\text{ m}$ となる。

2) 型式

堤防は河床から採取される土砂にて築造し、法面は練石張りを施す。

3) 堤防高及び天端幅

計画縦断、横断及び現況横断面より、設計洪水流量 $240\text{ m}^3/\text{sec}$ を流すためには、堤防高は余裕高 1.0 m を含めて、計画河床高上 $2.0\text{ m} \sim 2.1\text{ m}$ となる。又、天端幅は 3.0 m とする。

4) 法勾配及び法面保護

改修計画区間は流速が $4.3 \sim 5.1\text{ m/sec}$ とかなり速いので、法面の侵食を受けることが予想され、法面保護が必要である。法面保護工としては練石張りが適当である。なお、練

石張りの表面には河道の粗度を増加させるために、玉石を露出させる。

つぎに、法勾配については、下記の条件のもとに、円弧すべり面法による安定計算を行ない、表法、裏法とも 1 : 2.5 を採用した。

盛土材料の単位体積重量 (土砂)	2.0 t/m ³
水の単位体積重量	1.0 t/m ³
盛土材料の内部摩擦角	$\phi = 35^\circ$
地震力	無視

上記条件に基づくと、すべりに対する堤防の安全率は約 1.2 となる。

5) 基礎工

法面保護工の基礎は幅 1.0 m、高さ 1.0 m のコンクリート基礎とし、また、洗掘に対するため 1.0 m の根入れを行なう。

6) 既設堤防の取扱い

既設堤防の法勾配は 1 : 0.6 ~ 1 : 1.8 となっており、補強が必要である。但し、1 期工事は緊急に必要な堤防の建設を主眼にしていること、かつ、既設堤防が早急には破壊されないであろうことからこの補強工事は 1 期工事には含めない。

3.3.4 根固め工

パワブラボド川は非常な急流河川であり、土砂の洗掘、堆積に伴う河床変動が予想され、そのため堤防前面が局部的に洗掘をうける恐れがある。このような洗掘から堤防の脚部を守る目的で、枠工による根固め工を堤防前面に設置する。

枠工は木製枠に玉石をつめた構造とし、その諸元は日本の工事実績 (付録 I、Fig. 4. 49 及び 4.50 参照) を参考にして幅 2.0 m × 長さ 2.0 m × 高さ 0.8 m (重量約 4.0 t) とし、堤防前面に 3 列配置して、それぞれ鉄筋で連結する。

根固め工の詳細については設計図面集を参照のこと。

3.3.5 床固め工

1) 目的

パワブラボド川には多量の土砂流出があるために、現在のところ縦侵食のおきる可能性は少ないが、河道の彎曲部外側のような個所では局所的な洗掘の生じる恐れがある。さらに上流域の砂防工事や河川改修の進展に伴ってこのような洗掘傾向が増大すると予想される。そこでこのような洗掘を防止する目的で床固めを設置するものとする。

2) 位 置

将来、河床がほぼ安定状態に達する迄に、100～300 mの間隔で床固め工が必要となるが、当面は下記に示すような限られた地点にのみ床固め工を設置する。

- a. 河床勾配の変化点
- b. 彎曲部の末端
- c. 河川横断道路及び農業用水施設の直下流
- d. 最上流端

3) 型 式

床固めのタイプとしては2タイプを考える。ひとつは根固め工と同様の寸法の木製枠に玉石をつめた枠工(重量約4.0 t)とし、もうひとつは幅2.0 m×長さ2.0 m×高さ0.8 mのコンクリートブロック(重量約3.5 t)とする。その諸元は日本の工事実績(付録I、Fig. 4. 51 参照)を参考にして決定した。コンクリートブロックの床固め工は、河川改修区間の最上流端と取水施設設置予定地点の直下流とに設置する。

床固め工の詳細については、設計図面集を参照のこと。

3.3.6 取 水 施 設

バワ部落地先の既設堤防区間の右岸側から河川水の取水が行なわれている。今回の計画ではこの位置にも堤防が建設されるために、堤防下を横過して現在と同様の取水が可能なように、取水施設を設置する必要がある。

取水施設は取水口とパイプカルバート・沈砂池・角落しとからなる。角落しのしめ忘れによる人工洪水が起らないように、洪水時には十分注意して角落しを操作すべきである。

取水施設の詳細については、設計図面集を参照のこと。

Ⅳ 工 事 数 量

砂防ダム、導流堤及び付帯構造物を含めた河川改修工事の主要工事数量は以下の通りである。本設計で算出された工事数量はマヨン火山砂防及び洪水防禦プロジェクトのうち第1期工事に関するものである。

砂防ダム（主ダムおよび副ダムを含む）

土砂掘削工	1 1,6 0 0 m^3
岩掘削工	3 8 0 m^3
コンクリート工	7,1 7 0 m^3

№1 導流堤

土砂掘削工	3,5 9 0 m^3
岩掘削工	1,7 2 0 m^3
コンクリート工	5 6 0 m^3
練り石積工	2,2 9 0 m^3

№2 導流堤

土砂掘削工	4,3 1 0 m^3
盛土工	1,1 3 0 m^3
コンクリート工	6 9 0 m^3
練り石積工	1,7 2 0 m^3

河川改修

堤防

土砂掘削工	8 7,9 0 0 m^3
盛土工	6 2,8 0 0 m^3
コンクリート工	9,1 4 0 m^3
練り石積工	3 2,3 8 0 m^3
沈 枠	6,9 9 3 個

床固め工－Aタイプ

土砂掘削工	3,1 8 0 m^3
沈 枠	9 7 0 個

床固め工－Bタイプ

土砂掘削工	1,1 7 0 m^3
コンクリート十字ブロック	3 0 5 個

農業用水施設

一 式

V 施工計画及び工事工程

5.1 概 要

第1期工事の工事工程及び施工計画の概要を以下に述べる。当計画に含まれる工事は次の通りである。

1) 仮設工事

2) 本 工 事

砂 防 ダ ム

導 流 堤

堤 防

床 固 め 工

農業用取水施設

5.2 工 事 工 程

前述の各工事の工程は以下の仮定に基づき、また以下の点を考慮して検討する。

- 1) 機械、資材等の搬入を含め、仮設工事は1980年4月から着工するものとする。
- 2) 本工事は1980年11月から1985年7月の60ヶ月間で建設するものとする。工事期間中の雨期施工は降雨および出水状況を勘案して行なう。
- 3) 砂防ダムおよび導流堤を含めた砂防工事は工事着工後2年間で完了するものとする。
- 4) 堤防、床固め工および農業用取水施設を含めた河川工事は工事着工後約5年間で建設するものとする。

ここで、河川工事は、工事期間約5年間で工事進捗率を低く計画したが、これは河川工事の急速施工は砂防ダムおよび河川工事による河川状況の変化による予期せぬ危険性が考えられるためである。

5.3 施 工 計 画

工事は全て現地施工業者が、請負方式で実施するものとして計上する。

又資機材、施工機械はフィリピン国内で調達可能なものを使用するものとする。

本工事の着工前に次に示す仮設工事を行なう必要がある。

1) 工 事 用 道 路

2) 仮 設 建 物

3) 電 気 設 備

4) 給 水 設 備

仮設工事規模は工事数量、工事工程、施工計画等を勘案して以下の設備規模が必要である。

1) 工 事 用 道 路	延長 4,000 m
2) 仮 設 建 物	930 m ²
工事関連建物	230 m ²
宿 舎	700 m ²
3) 電 力 設 備	75 KW
コンクリートプラント	15 KW
修 理 工 場	30 KW
宿 舎	30 KW
4) 給 水 設 備	
工 事 用 水	16 m ³ /日
(給水車による供給)	

当工事で使用する施工機械および台数は次の通りである。

施 工 機 械	仕 様	台 数
ブルドーザー	21 ton	2
ブルドーザー	11 ton	2
トラクタショベル	1.4 m ³	2
バックホウ	0.6 m ³	2
ダンプトラック	6 ton	8
トラッククレーン	20 ton	1
振 動 ロ ー ラ	3 ton	1
ラ ン マ ー	60~100 kg	8
シ ン カ ー	20 kg	5
エアコンプレッサ	10 m ³ /min	1
簡易コンクリートプラント	0.75 m ³	1
コンクリートミキサ	0.2 m ³	5
アジテータトラック	1.7 m ³	3
棒状パイプレータ	60 m	5
棒状パイプレータ	40 m	20
ゼ ネ レ ー タ	15 KW	1
ゼ ネ レ ー タ	30 KW	2
水 中 ポ ン プ	3.5 HP	4
普通トラック	6 ton	1

各工事の施工計画は本報告書の付録Ⅱに詳細に説明してある。

Ⅵ 工 事 費

ここでは、第一期工事の工事費を下記の条件の下で見積る。

- 1) 労務者、資材及び機械の単価は1979年11月時点のレガスピにおける単価である。
(レガスピで入手不可能な資材、機械については、マニラの単価に基づいている。)
- 2) 工事は請負方式で、現地業者が実施するものとする。
- 3) 工事費は、請負工事費、技術費、管理費及び予備費からなる。
- 4) 工事費の積算はフィリピン政府、公共事業省で使用している積算基準に基づいて行う。

以上の条件で積算した工事費をまとめると下記の通り。

第 一 期 工 事 の 工 事 費

内 容	工事費(ペソ)
1. 請 負 工 事 費	
1) 直 接 工 事 費	
仮 設 備 費	2,088,000
砂 防 ダ ム	2,222,000
導 流 堤 Ⅰ	857,000
導 流 堤 Ⅱ	734,000
堤 防	9,221,000
床 固 め 工 A タイプ	271,000
床 固 め 工 B タイプ	269,000
農業用取水設備	18,000
小 計 (1)	15,680,000
2) 予備費(直接工事費の5%)	784,000
小 計 (2)	16,464,000
3) 利 潤 (小計(2)の10%)	1,646,000
4) 現場経費および一般管理費(小計(2)の5%)	823,000
請 負 工 事 費 計	18,933,000
2. 技 術 費	732,000
3. 管 理 費	947,000
4. 予 備 費	6,688,000
総 工 事 費	27,300,000

上記見積工事費の内訳は付録Ⅲを参照のこと。

APPENDIX I

DESIGN CALCULATION

APPENDIX I - DESIGN CALCULATION

TABLE OF CONTENTS

	Page
I. GENERAL	I-1
II. SABO DAM	I-2
2.1 General	I-2
2.2 Design Flood	I-3
2.3 Design of Overflow Section	I-10
2.4 Design of Dam Body	I-14
2.5 Stability Calculation	I-16
2.6 Protection Works for Sabo Dam's Apron	I-20
III. SPUR DIKE	I-25
3.1 General	I-25
3.2 Design Flood	I-25
3.3 Height of Spur Dike	I-27
3.4 Foot Protection	I-28
IV. RIVER CANALIZATION	I-32
4.1 General	I-32
4.2 Flood Analysis	I-33
4.3 Sediment Study	I-37
4.4 Discharge Capacity of the Present Pawa-Burabod River	I-40
4.5 Design of River Channel	I-42
4.6 Design of Levee	I-43

LIST OF FIGURES

	Page
Fig. 1.1 General Plan of Pawa-Burabod River	I-46
Fig. 1.2 Profile of Pawa-Burabod River	I-47
Fig. 2.1 Probable Daily Rainfall at Legaspi	I-5
Fig. 2.2 Relation between α and Drainage Area	I-11
Fig. 2.3 Overflow Section	I-12
Fig. 2.4 Relation between Overflow Depth and Discharge	I-13
Fig. 2.5 Designed Overflow Section	I-14
Fig. 2.6 Typical Section of Dam Body	I-18
Fig. 2.7 Arrangement of Sub-dam	I-21
Fig. 3.1 Concrete Block for Foot Protection	I-30
Fig. 4.1 Basin Map of Yawa River	I-48
Fig. 4.2 Present Condition of Pawa-Burabod River	I-49
Fig. 4.3 Typical Cross Section	I-50
Fig. 4.4 Grain Size Distribution Curve of Yawa River Bed Materials (Y-1)	I-51
Fig. 4.5 Grain Size Distribution Curve of Yawa River Bed Materials (Y-2)	I-52
Fig. 4.6 Grain Size Distribution Curve of Yawa River Bed Materials (Y-3)	I-53
Fig. 4.7 Grain Size Distribution Curve of Yawa River Bed Materials (Y-4)	I-54
Fig. 4.8 Grain Size Distribution Curve of Yawa River Bed Materials (Y-5)	I-55
Fig. 4.9 Grain Size Distribution Curve of Yawa River Bed Materials (Y-6)	I-56
Fig. 4.10 Profile of Main Yawa River	I-57
Fig. 4.11 Cross Sections of Main Yawa River	I-58
Fig. 4.12 Cross Sections of Main Yawa River	I-59

		<i>Page</i>
Fig. 4.13	H - Q, R, T Curve of Main Yawa River	I-60
Fig. 4.14	H - Q, R, T Curve of Main Yawa River	I-61
Fig. 4.15	H - Q, R, T Curve of Pawa-Burabod River	I-62
Fig. 4.16	H - Q, R, T Curve of Pawa-Burabod River	I-63
Fig. 4.17	H - Q, R, T Curve of Pawa-Burabod River	I-64
Fig. 4.18	H - Q, R, T Curve of Pawa-Burabod River	I-65
Fig. 4.19	H - Q, R, T Curve of Pawa-Burabod River	I-66
Fig. 4.20	H - Q, R, T Curve of Pawa-Burabod River	I-67
Fig. 4.21	H - Q, R, T Curve of Pawa-Burabod River	I-68
Fig. 4.22	H - Q, R, T Curve of Pawa-Burabod River	I-69
Fig. 4.23	H - Q, R, T Curve of Pawa-Burabod River	I-70
Fig. 4.24	H - Q, R, T Curve of Pawa-Burabod River	I-71
Fig. 4.25	H - Q, R, T Curve of Pawa-Burabod River	I-72
Fig. 4.26	H - Q, R, T Curve of Pawa-Burabod River	I-73
Fig. 4.27	H - Q, R, T Curve of Pawa-Burabod River	I-74
Fig. 4.28	H - Q, R, T Curve of Pawa-Burabod River	I-75
Fig. 4.29	H - Q, R, T Curve of Pawa-Burabod River	I-76
Fig. 4.30	H - Q, R, T Curve of Pawa-Burabod River	I-77
Fig. 4.31	H - Q, R, T Curve of Pawa-Burabod River	I-78
Fig. 4.32	H - Q, R, T Curve of Pawa-Burabod River	I-79
Fig. 4.33	H - Q, R, T Curve of Pawa-Burabod River	I-80
Fig. 4.34	H - Q, R, T Curve of Pawa-Burabod River	I-81
Fig. 4.35	H - Q, R, T Curve of Pawa-Burabod River	I-82
Fig. 4.36	H - Q, R, T Curve of Pawa-Burabod River	I-83
Fig. 4.37	H - Q, R, T Curve of Pawa-Burabod River	I-84
Fig. 4.38	H - Q, R, T Curve of Pawa-Burabod River	I-85

		Page
Fig. 4.39	Dominant Flow of Pawa-Burabod River	I-86
Fig. 4.40	Dominant Flow of Pawa-Burabod River	I-87
Fig. 4.41	Dominant Flow of Pawa-Burabod River	I-88
Fig. 4.42	Dominant Flow of Pawa-Burabod River	I-89
Fig. 4.43	Dominant Flow of Pawa-Burabod River	I-90
Fig. 4.44	Dominant Flow of Pawa-Burabod River	I-91
Fig. 4.45	Dominant Flow of Pawa-Burabod River	I-92
Fig. 4.46	Dominant Flow of Pawa-Burabod River	I-93
Fig. 4.47	Dominant Flow of Pawa-Burabod River	I-94
Fig. 4.48	Standard Relation between Levee Slope and Levee Height due to Soil Classification	I-95
Fig. 4.49	Example of Foot Protection in Japan	I-95
Fig. 4.50	Example of Foundation Width in Japan	I-96
Fig. 4.51	Example of Weight of Concrete Block for Groundsill in Japan	I-97

LIST OF TABLES

	Page
Table 2.1 Probable Daily Rainfall at Legaspi	I-6
Table 2.2 Flood Velocity	I-7
Table 2.3 Mud Concentration	I-9
Table 2.4 Peak Run-off in Mud Flow (100-year Probable Flood)	I-10
Table 2.5 Overflow Depth	I-13
Table 2.6 Dam Slope	I-16
Table 2.7 Moment Calculation	I-17
Table 2.8 Types of Foundation and Allowable Bearing Capacity	I-20
Table 4.1 Drainage Area	I-34
Table 4.2 Run-off Coefficient	I-34
Table 4.3 Time of Flood Concentration	I-35
Table 4.4 Average Rainfall Intensity in a Period of "Time of Flood Concentration"	I-35
Table 4.5 Calculation of Peak Discharge	I-36
Table 4.6 Relation between Drainage Area and Specific Discharge	I-36
Table 4.7 Sediment Discharge in the Yawa River	I-38
Table 4.8 Sediment Discharge in the Pawa-Burabod River (1.5-year Probable Flood 70 m ³ /sec)	I-38
Table 4.9 Summary of Sediment Discharge	I-39
Table 4.10 Discharge Capacity of Present River Condition	I-41
Table 4.11 Equilibrium River Bed Slope	I-43
Table 4.12 Check of Discharge Capacity	I-50
Table 4.13 Stability Calculation of Levee	I-44
Table 4.14 Standard Weight of Foot Protection in Japan	I-95

		Page
Table 4.15	Non-uniform Flow Calculation	I-98
Table 4.16	Non-uniform Flow Calculation	I-99
Table 4.17	Non-uniform Flow Calculation	I-100
Table 4.18	Non-uniform Flow Calculation	I-101
Table 4.19	Non-uniform Flow Calculation	I-102
Table 4.20	Calculation of Sediment Load	I-103

I. GENERAL

This is the design calculation report of the sabo facilities to be constructed in the Pawa-Burabod river, a tributary of the Yawa river which is located in south-eastern slope of the Mayon Volcano.

This report is an appendix to be attached to the main report of "Design Report on Sabo Facilities in the Pawa-Burabod River, A Tributary of the Yawa River, February 1980".

The report deals with the design calculations of Sabo facilities involving the Sabo dam, spur dikes, and river canalization works including river channel, levees, cribworks and groundsills.

II. SABO DAM

2.1 General

The proposed Sabo dam is located in the upstream reaches of the Pawa-Burabod river at about EL.400 m.

The topographic condition of the basin and the principal features of the dam are summarized below:

Topography

Location	About EL.400 m
Drainage area	2.5 km ²
River length upstream of the dam site	4.4 km
Average river bed slope for the above	1 / 2.3
River bed slope at the dam site	1 / 11.1

Main Dam

Type	Concrete gravity type
Crest elevation	
Overflow section	EL.398.55 m
Non-overflow section	EL.402.05 m
Height	
Overflow section	10.0 m
Non-overflow section	13.5 m
Crest length	
Total	79.5 m
Overflow section	30.0 m
Crest width	3.0 m
Upstream slope of dam body	1 : 0.4
Downstream slope of dam body	1 : 0.2
Design flood (100-year flood)	103.1 m ³ /s
Trap capacity	13,000 m ³
Concrete volume of dam body	5,220 m ³

Sub-dam

Type	Concrete gravity type
Height	
Overflow section	5.0 m
Non-overflow section	7.5 m
Crest length	
Total	57.5 m
Overflow section	30.0 m
Crest width	2.0 m
Upstream slope of dam body	1 : 0.4
Downstream slope of dam body	1 : 0.2
Concrete volume	1,170 m ³


Hereunder, calculation of design flood, design of overflow section, stability of dam body, and protection works for the dam apron are presented.

2.2 Design Flood

The design flood for Sabo dams is generally taken as either 100-year probable flood or the recorded maximum flood, whichever is the larger, according to the Japanese standard.

Since flood data are not available in this project area, 100-year probable flood is applied for the design of the Sabo dam and the design flood is estimated from rainfall data by applying the Rational Formula.

The estimation of design flood is proceeded by the following procedure:



1) Probable Daily Rainfall

No rainfall record is available in this project basin. Legaspi rain-gage station has a long-term daily rainfall record and also is nearest to the project basin. Therefore, Legaspi is selected as a representative station for the said basin.

The probable daily rainfall is computed by three methods of Iwai's, Hazen's and Gumbel's one and shown in Table 2.1 and Fig. 2.1 using the recorded annual maximum daily rainfalls mentioned in the report of "Bicol River Basin Comprehensive Water Resources Development Study", which cover 27 years from 1949 to 1975.

The 100-year probable daily rainfall for design flood is estimated at 595 mm/24-hr by Hazen's method which indicates the largest values among three methods.

Fig 2.1 Probable Dally Rainfall
at Legaspi




Table 2.1 Probable Daily Rainfall at Legaspi

Return Period (year)	Probability	Probable Daily Rainfall (mm)		
		IWAI	HAZEN	GUMBEL
1.01	0.9901	59	71	84
1.5	0.6667	149	140	144
2	0.5000	180	170	184
4	0.2500	240	235	258
5	0.2000	257	256	280
8	0.1250	291	301	324
10	0.1000	307	323	344
20	0.0500	355	396	405
25	0.0400	371	421	424
40	0.0250	403	476	465
50	0.0200	418	504	484
80	0.0125	450	565	524
100	0.0100	465	595	543
200	0.0050	513	697	602
250	0.0040	528	732	621
400	0.0025	561	809	661
500	0.0020	577	848	680
1000	0.0010	626	977	739

2) Time of Flood Concentration

Time of flood concentration is given by the following formula after Kraven.

$$T = L/w \quad \dots\dots\dots (2.1)$$

where, T : time of flood concentration (sec.)
 L : river length upstream from the dam site (m)
 w : flood velocity which is empirically
 given as shown in Table 2.2 below (m/sec)

Table 2.2 Flood Velocity

River bed slope	> 1/100	1/100-1/200	< 1/200
w (m/sec)	3.5	3.0	2.1

Since average river bed slope is 1/2.3 which is steeper than 1/100, w is taken at 3.5 m/sec from the above table. Thus, T is calculated below:

$$T = \frac{4.4\text{km} \times 1,000}{3.5 \text{ m/sec}} = 1,257 \text{ sec} = 21 \text{ min.}$$

3) Rainfall intensity

Dr. Ito's formula expressed below is used for the calculation of rainfall intensity.

$$R_t = \frac{R_{24}}{24} \cdot \frac{24}{100} \cdot \left(\frac{34,710}{T^{1.35} + 1,520} \right) \quad \dots\dots (2.2)$$

where, R_t : mean rainfall intensity in a period of
 time, T (mm/hr)
 R_{24} : rainfall in a 24-hr duration (mm)
 T : time of flood concentration (min)

According to Table 2.1, the 100-year probable rainfall in a 24-hr duration is taken as 595 mm at Legaspi station.

But, Legaspi is located at the low elevation, so that the above values should be used after being increased in an appropriate rate, because it is known that the rainfall generally increases with the elevation and the project area is located at an elevation of more than 400 m while the elevation at Legaspi station is 19 m.

In this study, the above probable rainfall, 595 mm, is increased 10 per cent referring to the empirical standard in Japan, in which the annual rainfall amount increases at 5 to 10 per cent per 500 m in elevation.

Finally, the probable rainfall for design flood comes to 660 mm/24-hr and the rainfall intensity for the time of flood concentration (= 21 min.) is calculated by equation (2.2) as,

$$R_t = 144.9 \text{ mm/hr}$$

4) Peak run-off

The Rational Formula expressed below is used for calculation of peak run-off.

$$Q_p = \frac{1}{3.6} \times f \times A \times R_t \quad \dots\dots\dots (2.3)$$

where, Q_p : peak run-off (m^3/sec)
 f : run-off coefficient (= 0.80)
 A : drainage area (km^2)
 R_t : mean rainfall intensity during the time of flood concentration (mm/hr)

Adopting $f=0.80$, $A=2.5 \text{ km}^2$ and $R_t=144.9 \text{ mm/hr}$, the peak run-off of 100-year probable flood is calculated at $Q_p \text{ 100-year} = 80.5 \text{ m}^3/\text{sec}$.

5) Mud concentration in mudflow

Mud concentration in mudflow is given by Takahashi's formula which is expressed in the following form:

$$C = \frac{\rho \cdot \tan \theta}{(\sigma - \rho)(\tan \phi - \tan \theta)} \dots\dots\dots (2.4)$$

where, C : mud concentration

ρ : density of water (gram/cm³)

$\tan \theta$: gradient of river bed slope

σ : density of river bed materials
(gram/cm³)

ϕ : internal friction angle of river bed materials (°)

It has been generally recognized that Sabo dam construction will change its upstream river bed slope to about 1/2 to 2/3 of the original river bed slope according to the flow condition. Generally said, in case of flow dominant to mudflow, the river bed will be changed to about 2/3 of the original river bed slope.

In the proposed dam site, the flow regime would be assumed to be mud flow since the river bed slope is so steep as 1/11.1. Therefore, the planned river bed slope in the upstream of the Sabo dam is assumed to be 1/17 (= 1/11.1 x 2/3).

Assuming the other constants in equation (2.4) as

$$\rho = 1.0 \text{ g/cm}^3 \quad \tan \theta = 1/17$$

$$\sigma = 2.5 \text{ g/cm}^3$$

$$\phi = 20^\circ$$

Mud concentration is calculated as follows.

Table 2.3 Mud Concentration (C)

	River Bed Slope	Mud Concentration
Original river	1/11.1	0.219
After construction of Sabo dam	1/17.0	0.129

6) Peak run-off in mud flow

Peak run-off in mud flow is calculated by the following formula.

$$Qp' = Qp \times \frac{1}{1-c} \dots\dots\dots (2.5)$$

where, Qp : peak run-off (m^3/sec)
 c : mud concentration

Peak run-off in mud flow for 100-year probable flood is thus calculated as follows:

Table 2.4 Peak Run-off in Mud Flow
(100-year probable flood)

	Peak Run-off (water)	Mud Concentration	Peak Run-off (mud flow)
Original river condition	80.5 m^3/sec	0.219	103.1 m^3/sec
After construction of Sabo dam	80.5 "	0.129	92.4 "

2.3 Design of Overflow Section

Overflow section of the Sabo dam should be designed to keep safety of dam against flood flow. Firstly, the width of overflow section (crest length of overflow section) will be decided and then the height of overflow opening will be decided hereunder.

1) Width of overflow section (crest length of overflow section)


Study will firstly be made of the practicable river width, which is preferable to be adopted as the width of overflow section of the Sabo dam.

The practicable river width in case of rivers without levees or dikes is empirically given by the following formula.

$$B = \alpha \cdot Q^{1/2} \dots\dots\dots (2.6)$$

where, B : river width (m)
Q : mud flow peak run-off (m³/sec)
α : coefficient shown in Fig. 2.2

Fig. 2.2 Relation between α and Drainage Area



In case of Mayon Projects, it may be taken at 4, since the drainage area at the proposed dam site is 2.5 km². Therefore, the river width is calculated as follows by adopting 100-year probable flood.

$$B = 4 \times 103.1^{1/2} = 40.6 \text{ m}$$

From the topographic features at the dam site, the river width in the downstream of the dam will be about 50 m.

Based upon the above studies, the width of overflow section is decided at 30 m taking some allowance to prevent scouring in the dam abutment.


2) Overflow depth

Overflow depth is calculated by the following formula.

$$Q = \frac{2}{15} \times C \times h_o \times \sqrt{2 \times g \times h_o} \times (3 b_o + 2 b_l) \quad \text{---(2.7)}$$

where, Q : discharge (m^3/sec)
 C : coefficient of contraction ($= 0.6$)
 g : acceleration of gravity (9.8 m/sec^2)
 h_o : overflow depth (m)
 b_o : base width of overflow section (30 m)
 b_l : flow width in water surface (m)

Fig. 2.3 Overflow Section



Adopting $m = 0.5$


$$b_l = b_o + 0.5 h_o + 0.5 h_o = 30 + h_o$$

substituting the above to eq. (2.7),

$$\begin{aligned} Q &= \frac{2}{15} \times 0.60 \times h_o \times \sqrt{2 \times 9.8 \times h_o} \times \{ 3 \times 30 + 2 \times (30 + h_o) \} \\ &= 0.708 h_o^{2/3} \times (75 + h_o) \quad \text{..... (2.8)} \end{aligned}$$

The above equation is graphically shown in Fig. 2.4.

Fig. 2.4 Relation between Overflow Depth and Discharge



From Fig. 2.5, the overflow depth corresponding to the design flood is obtained below.


Table 2.5 Overflow Depth

Condition	Peak Run-off (mud flow)	Overflow Depth
Original river condition	103.1 m ³ /sec	1.53 m
After construction of Sabo dam	92.4 "	1.43 "

(Overflow crest length = 30 m)

As the results of the above calculation, overflow depth is assumed at 1.6 m taking some allowance and rounded up the calculated figures.

Fig. 2.5 Designed Overflow Section



2.4 Design of Dam Body

The mechanism of mudflow has not been made clear so far. The height of Sabo dam is empirically decided so as to be effective to reduce the energy of mudflow referring to the past engineering experiences, structures actually constructed and economical conditions.

In general, the height of more than 7 m is proposed to be effective to control the mudflow.

In case of Mayon Project, the main Sabo dam is designed with a total height of 10.0 m at overflow section based upon the topographic conditions as well as the considerations of the erosion control effect especially for side erosion.

The other structural features such as crest width, down and upstream slopes of dam body, etc. are designed below.

1) Width of crest

Width of dam crest in overflow section is decided at 3.00 m so that the dam crest will not be destroyed by mud flow.

2) Downstream slope

The downstream slope of Sabo dams are generally designed to avoid destruction due to heavy materials (cobbles and boulders) falling down over the crest. Therefore, a slope of 1:0.2 is adopted.

3) Upstream slope

Considering the safety of dam body against overturning, for which stability will be checked in the next paragraph, the upstream slope of dam is decided at 1:0.4.

The upstream slope of Sabo dams can be decided by the following formula in general.

$$(1 + \alpha)m^2 + \{ 2 \times (n + \beta) + n(4\alpha + r) + 2\alpha\beta \} m + \alpha\beta(4m + \alpha) + (3n\beta + \beta^2 + n^2) - (1 + 3\alpha) = 0 \quad \dots\dots\dots (2.9)$$

where, H : height of dam at overflow section (m)
 b : width of crest (m)
 ho : overflow depth (m)
 m : upstream slope
 n : downstream slope
 W_o : density of water including earth
 (= 1.1 ton/m³)
 W_c : density of concrete (2.5 ton/m³)

with W_o = 1.1 ton/m³ and W_c = 2.4 ton/m³, other variables of eq. 2.9 are tabulated for convenience in Table 2.6.

Table 2.6 Dam Slope

$w_o = 1.1, w_c = 2.4$

$\frac{h}{H}$	$\frac{h}{H}$	0.00	0.10	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	1.00
0.00	0.625	0.713	0.782	0.837	0.883	0.921	0.954	0.982	1.007	1.029	1.048	
0.02	0.600	0.689	0.758	0.814	0.860	0.899	0.932	0.960	0.985	1.007	1.027	
0.04	0.575	0.665	0.735	0.791	0.837	0.876	0.909	0.938	0.963	0.985	1.005	
0.06	0.549	0.640	0.711	0.767	0.814	0.853	0.887	0.916	0.941	0.963	0.983	
0.08	0.523	0.615	0.686	0.743	0.790	0.830	0.864	0.893	0.918	0.941	0.963	
0.10	0.496	0.589	0.664	0.719	0.767	0.807	0.841	0.870	0.896	0.918	0.938	
0.12	0.469	0.563	0.636	0.694	0.743	0.783	0.817	0.847	0.873	0.895	0.916	
0.14	0.441	0.537	0.610	0.670	0.718	0.759	0.794	0.823	0.850	0.872	0.893	
0.16	0.413	0.510	0.584	0.644	0.694	0.735	0.770	0.800	0.826	0.849	0.870	
0.18	0.384	0.482	0.558	0.619	0.669	0.710	0.746	0.776	0.803	0.826	0.847	
0.20	0.354	0.454	0.531	0.593	0.643	0.685	0.721	0.752	0.779	0.803	0.824	
0.22	0.324	0.426	0.504	0.567	0.618	0.660	0.697	0.728	0.755	0.779	0.800	
0.24	0.294	0.397	0.477	0.540	0.592	0.635	0.672	0.704	0.731	0.755	0.777	
0.26	0.262	0.368	0.449	0.513	0.566	0.610	0.647	0.679	0.707	0.731	0.753	
0.28	0.231	0.339	0.421	0.486	0.539	0.584	0.622	0.654	0.682	0.707	0.729	
0.30	0.198	0.308	0.392	0.459	0.513	0.558	0.596	0.629	0.658	0.683	0.705	
0.32	0.165	0.278	0.363	0.431	0.486	0.532	0.570	0.604	0.633	0.658	0.681	
0.34	0.131	0.246	0.334	0.402	0.458	0.505	0.544	0.578	0.608	0.633	0.656	
0.36	0.096	0.214	0.304	0.374	0.431	0.478	0.518	0.552	0.582	0.608	0.632	
0.38	0.060	0.182	0.273	0.345	0.403	0.451	0.492	0.526	0.557	0.583	0.607	
0.40	0.024	0.149	0.242	0.315	0.374	0.423	0.465	0.500	0.531	0.558	0.582	
0.42	-0.013	0.115	0.211	0.285	0.346	0.395	0.438	0.474	0.505	0.532	0.557	
0.44	-0.051	0.081	0.179	0.255	0.316	0.367	0.410	0.447	0.479	0.507	0.531	
0.46	-0.091	0.046	0.146	0.224	0.287	0.339	0.383	0.420	0.452	0.481	0.506	
0.48	-0.131	0.010	0.113	0.193	0.257	0.310	0.355	0.393	0.426	0.454	0.480	

By adopting the following values, the upstream slope of Sabo dam can be calculated;

$$\begin{aligned}
 H &= 10.0 \text{ m} & h_o &= 1.60 \text{ m} & b &= 3.00 \text{ m} \\
 W_o &= 1.1 \text{ ton/m}^3 & W_c &= 2.4 \text{ ton/m}^3 & n &= 0.2
 \end{aligned}$$

$$\alpha = \frac{h_o}{H} = \frac{1.60}{10.00} = 0.16$$

$$\beta = \frac{b}{H} = \frac{3.00}{10.00} = 0.30$$

$$r = \frac{W_c}{W_o} = \frac{2.4}{1.1} = 2.18$$

From Table 2.5, "m" is obtained at about 0.36. Taking some allowance, $m = 0.40$ is adopted.

2.5 Stability Calculation

For the designed dam body in the previous chapter, stability analysis is made hereunder. The stability of gravity type dams should be checked in the following terms.


- a. Stability against overturning
- b. Stability against sliding
- c. Stability against bearing

The typical section of dam body is shown in Fig. 2.6. For calculation on overturning, summation of causing and restraining moments will be taken at the toe with the former considered negative (-) and latter positive (+). The results of calculation are shown in Table 2.7.

Table 2.7 Moment Calculation

Forces (Tons)	Lever Arm (m)	Moment (t.m)
$C_1 = \frac{1}{2} \times 2 \times 10 \times 2.4 = 24.00$	$2 \times \frac{2}{3} = 1.33$	+ 32.00
$C_2 = 3 \times 10 \times 2.4 = 72.00$	$2 \times \frac{3}{2} = 3.50$	+ 252.00
$C_3 = \frac{1}{2} \times 4 \times 10 \times 2.4 = 48.00$	$5 + \frac{1}{3} \times 4 = 6.33$	+ 304.00
$W_1 = 1.6 \times 3 \times 1.1 = 5.28$	$2 + \frac{3}{2} = 3.50$	+ 18.48
$W_2 = 1.6 \times 4 \times 1.1 = 7.40$	$5 + \frac{1}{2} \times 4 = 7.00$	+ 51.80
$W_3 = \frac{1}{2} \times 10 \times 4 \times 1.1 = 22.00$	$5 + \frac{2}{3} \times 4 = 7.67$	+ 168.67
$W_4 = \frac{1}{2} \times 10 \times (1.6 + 11.6) \times 1.1 = 72.60$	$\frac{10}{3} \times (10 + 3 \times 1.6) \div (10 + 2 \times 1.6) = 3.74$	- 271.52
	$\Sigma =$	+ 555.43
$R_v = C_1 + C_2 + C_3 + W_1 + W_2 + W_3 = 178.68$	d	- 178.68d

Fig. 2.6 Typical Section of Dam Body



The point where the base reaction falls can now be readily calculated by taking summation of moments at the toe considering the total amount of external forces against that caused by the vertical component of reaction, that is R_v ,

$$555.43 - 178.68d = 0$$

$$d = 3.11 > B/3 \quad (= \frac{9.00}{3} = 3.00 \text{ m})$$

This means that the reaction fell within the middle third of base.

Internal stresses will be calculated based upon the following formula:

$$\sigma = \frac{R_v}{B} \left(1 \pm \frac{6e}{B} \right) \dots\dots\dots (2.10)$$

where, σ : internal stress (ton/m²)
 R_v : total base pressure (ton)
 e : eccentricity $(= \frac{B}{2} - d)$ (m)
 B : width of dam base (m)

From Fig. 2.6

$$e = \frac{B}{2} - d = \frac{9.00}{2} - 3.11 = 1.39$$

Taking stress at the toe as

$$\sigma_1 = \frac{178.68}{9.00} \left(1 + \frac{6 \times 1.39}{9.00} \right) = 38.25 \text{ ton/m}^2$$

Taking stress at the heel as

$$\sigma_2 = \frac{178.68}{9.00} \left(1 - \frac{6 \times 1.39}{9.00} \right) = 1.46 \text{ ton/m}^2$$

From the above computations it is concluded that no tension will occur anywhere on the dam foundation. Safety factor against sliding taking $f = 0.70$

$$F.S.S = \frac{f \times R_v}{RH} = \frac{0.70 \times 178.68}{72.6} = 2.46 > 1.2$$

This Sabo dam site's foundation is judged as compacted gravel and sand. The allowable bearing capacity is therefore assumed to be 70-110 ton/m² from the Table 2.8. As preceeding computation, the stress at the toe of dam is 38.25 ton/m², so it's pressure is allowable.

Table 2.8 Types of Foundation and
Allowable Bearing Capacity


Type of Foundation	Bearing Capacity (ton/m ²)
Hard rock	160 - 270
Soft rock	70 - 160
Compacted gravel, earth and sand	70 - 110
Coarse sand and cobble stone	30 - 70
Sand and clay	20

From the preceeding computations, it can be concluded that the design is satisfactory.

2.6 Apron Protection

For preventing the erosion just downstream of the main dam and thus for keeping stability of the main dam, a sub-dam is to be constructed in the downstream of the main dam to form apron.

Fig. 2.7 Arrangement of Sub-dam



1) Overflow depth

The water depth at overflow section of main dam is calculated by Manning's formula assuming that the main dam is filled with debris and sediment load and the flow becomes uniform.

$$Q = AV' \quad \dots\dots\dots (2.11)$$

$$V' = V \times \frac{\rho}{\rho + C(\sigma - \rho)} \quad \dots\dots\dots (2.12)$$

$$V = \frac{1}{n} R^{2/3} I^{1/2} \quad \dots\dots\dots (2.13)$$

where, Q : discharge including earth (m^3/sec)
 A : flow area (m^2)
 V : velocity (m/sec)
 V' : velocity including earth (m/sec)
 R : hydraulic radius (m)
 I : assumed future river bed slope upstream from Sabo dam (about 1/17)
 ρ : density of water (ton/m^3)
 C : mud concentration
 σ : density of river bed materials (ton/m^3)
 n : Manning's roughness coefficient

Substituting the following values to eq. (2.11), (2.12) and (2.13), the overflow depth (h_o) is obtained as

$$h_o = 0.77 \text{ m}$$

2) Distance between main dam and sub-dam

The distance between main dam and sub-dam (L) is given by the following equation.

$$L \geq \ell + X + b_2 \dots\dots\dots (2.14)$$

$$\ell = V_o \cdot \left\{ \frac{2 (H_1 + 0.5 h_o)}{g} \right\}^{1/2}$$

$$V_1 = \sqrt{2 \cdot g \cdot (H_1 + h_o)}$$

$$X = \beta \cdot h_j \quad \beta: 4.5 - 5.0$$

$$V_o = q_o / h_o$$

$$h_1 = q_1 / V_1$$

$$h_j = \frac{h_1}{2} \cdot (\sqrt{1 + 8F^2} - 1)$$

$$F_1 = V_1 / \sqrt{g \cdot h_1}$$

where, ℓ : distance between point A and B (m)
 X : distance of hydraulic jump (m)
 b_2 : sub-dam crest width (m)
 V_o : overflow velocity at main dam (m/sec)
 g : gravity acceleration (m/sec²)
 h_j : depth of hydraulic jump (m)
 V_1 : flow velocity at point B (m/sec)
 h_1 : super critical flow depth before hydraulic jump (m)
 q_o : discharge per unit width at main dam crest (m³/sec/m)
 q_1 : discharge per unit width at point B (m³/sec/m)
 F : Froude number before hydraulic jump

The calculation is made by the following procedure.

- (i) overflow velocity at main dam (V_o)

$$V_o = \frac{103.1}{0.5 \times (30 + 30 + 0.7) \times 0.77}$$

$$= 4.40 \text{ m}$$

- (ii) distance of water fall reach (ℓ)

$$\ell = 4.40 \times \left\{ \frac{2 \times (7.0 \times 0.5 \times 0.77)}{98} \right\}^{1/2}$$

$$= 5.40 \text{ m}$$

- (iii) velocity of water falling at point B (V_1)

$$V_1 = \sqrt{2 \times 9.8 \times (7 + 0.77)}$$

$$= 12.34 \text{ m/sec}$$

- (iv) super critical flow depth before hydraulic jump (h_1)

$$h_1 = (103.1/30)/12.34$$

$$= 0.28 \text{ m}$$

- (v) Froude number before hydraulic jump (F_1)

$$F_1 = 12.34 / \sqrt{9.8 \times 0.28}$$

$$= 7.45$$

- (vi) depth of hydraulic jump (h_j)

$$h_j = \frac{0.28}{2} \times (\sqrt{1 + 8 \times 7.45^2} - 1)$$

$$= 2.81 \text{ m}$$

- (vii) distance of hydraulic jump (X)

$$X = 4.5 \times 2.81 \quad (\mathcal{O} = 4.5)$$

$$= 12.66 \text{ m}$$

- (viii) distance between main dam and sub-dam (L)

$$L \geq 5.40 + 12.66 + 2.00$$

$$= 20.06 \text{ m}$$

From the result of above calculation, the distance between main dam and sub-dam is determined as 22 m taking some allowance.

3) Height of sub-dam

The height of sub-dam is empirically given by the equation below.

$$H_2 = \alpha H \dots\dots\dots (2.15)$$

where, H_2 : overlap height shown in Fig. 2.7 (m)
 α : coefficient (1/3 - 1/4)
 H : main dam height (m)

Substituting $H=10$ to above euqation, the overlap height is calculated at 2.5 m to 3.0 m. Taking sub-dam height as 5.0 m and foundation depth as 3.0 m, the overlap height is estimated at 2.75 m at the sub-dam site and it satisfies the above conditions. Therefore, the height of 5.0 m is adopted.

III. SPUR DIKE

3.1 General

Sand retarding basin is proposed to be constructed in the middle reaches with spur dikes, cross dikes, training dikes, etc.

Such retarding basin seems not practical to be constructed at once because of very wide areas to cover, and further it may be dangerous to construct it at once because there are many unknown factors involved in retarding basin. From such considerations, two dikes (spur dikes) only are proposed to be constructed for the first.

These dikes aim at preventing mud flow from entering into the villages of Pawa, Bonga, Burabod, etc. so that mud flow can be sustained in the middle reaches.

The topographic condition of the basin and the principal features of the spur dikes are summarized below.

Topography

Drainage area	7.3 km ²
River length upstream of river canalization	7.8 km
Average river bed slope	1/3.8
River bed slope around the spur dikes	1/16

3.2 Design Flood

The design flood is calculated by the same method applied for the Sabo dam design. The 1.5-year probable flood and 50-year probable flood are estimated herein. The former flood is used for estimating the practicable river width and the latter for designing of structures of the spur dikes.

1) Probable daily rainfall

From Fig. 2.1 and Table 2.1, the probable daily rainfalls for the return periods of 1.5-year and 50-year are 140 mm and 504 mm respectively by Hazen's method.

The above values are used by adding 10 per cent according to the reason mentioned in previous chapter.

$$R_{24} \text{ 1.5-year} = 160 \text{ mm/24-hr}$$

$$R_{24} \text{ 50-year} = 560 \text{ mm/24-hr}$$

2) Time of flood concentration

Using Kraven's Formula

$$T = \frac{7,200}{3.5} = 2,229 \text{ sec} = 37 \text{ min.}$$

3) Rainfall intensity

Dr. Ito's Formula will be used for this calculation from eq. 2.2 previously presented.

$$R_t \text{ 1.5-year} = 33.6 \text{ mm/hr}$$

$$R_t \text{ 50-year} = 117.7 \text{ mm/hr}$$

4) Peak run-off

Using Rational Formula

$$Q_p \text{ 1.5-year} = 47.4 \text{ m}^3/\text{sec}$$

$$Q_p \text{ 50-year} = 165.9 \text{ m}^3/\text{sec}$$

5) Mud flow concentration

Using Takahashi's Formula

$$C = 0.138$$

From eq. 2.5 the peak run-off in mud flow is obtained as follows.

$$Q_p \text{ 1.5-year} = 55.0 \text{ m}^3/\text{sec}$$

$$Q_p \text{ 50-year} = 192.5 \text{ m}^3/\text{sec}$$

3.3 Height of Spur Dike

1) Practicable river width

In the proposed area for retarding basin, streams form no definite channel section. Therefore, practicable river width is estimated by eq. 2.6 and Fig. 2.2 as previously presented. In this case, assuming that river width is formed by dominant flow, it is calculated by applying 1.5-year probable flood.

$$B = 4 \times 55.0^{1/2} = 29.7 \div 30 \text{ m}$$

2) Design high water level

Assuming the river width of 30 m calculated above and rectangular section of river channel, the approximate water depth at the time of design flood will be calculated by applying Manning's formula.

$$h = \left(\frac{n \cdot Q}{B \cdot I^{1/2}} \right)^{3/5} \dots\dots\dots (3.1)$$

where, h : water depth (m)
 n : Manning's roughness coefficient
 Q : run-off (m³/sec)
 B : river width (m)
 I : river bed slope

Substituting the values previously calculated, water depth is obtained as:

$$h = \left(\frac{0.045 \times 192.5}{30 \times 0.0625^{1/2}} \right)^{3/5} = 1.09 \text{ m}$$

3) Height of spur dike

In the proposed area, the stream has no definite flow direction. Besides, severe river bed variation is anticipated by scouring and deposition. Therefore, the height of spur dikes is taken at 3.0 m above ground surface taking enough allowance. Foundation of spur dikes will be designed to reach 1 m depth or more below ground surface. Thus the height of spur dike will be 4.0 m at lowest.

3.4 Foot Protection

As mentioned above, the river bed is anticipated to be scoured severely by flood. To prevent damage from scouring, a foot protection concrete block will be provided close to the base of the dike.

In this case, the volume of concrete block will be calculated based on the tractive force of the stream and thrust force.

1) Tractive force

The tractive force of stream is calculated using the following equation:

$$T = \rho \cdot g \cdot R \cdot I \dots\dots\dots (3.2)$$

where, T : tractive force (ton·m/sec²)
 ρ : density of water (ton/m³)
 g : acceleration of gravity (m/sec²)
 R : hydraulic radius (m)
 I : slope of river bed

The density of water will be calculated considering mud flow, using concentration of mud flow. From preceeding calculations, mud flow concentration, $C = 0.138$. This gives, $\rho = 1.0958 \doteq 1.1$.

Assuming the channel cross section is rectangle, hydraulic radius is assumed to be equal to the water depth. Substituting the above values in eq. (3.2), $\rho = 1.1 \times 9.8 \times 1.09 \times 0.0625 = 0.7344$ ton·m/sec²

2) Critical tractive force

By Iwagaki's Formula, the relation between diameter of river bed materials and critical tractive force is shown in the following expression.

$$\begin{array}{lcl}
 U_*^2 c = 80.9 \cdot d & d > 0.303 & \\
 = 134.6 \cdot d^{33/21} & 0.118 \leq d \leq 0.303 & \\
 = 55.0 \cdot d & 0.0565 \leq d \leq 0.118 & \\
 = 8.41 \cdot d^{11/32} & 0.0065 \leq d \leq 0.0565 & \\
 = 226 \cdot d & d < 0.0065 &
 \end{array} \left. \vphantom{\begin{array}{l} \\ \\ \\ \\ \end{array}} \right\} \dots\dots\dots (3.3)$$

$$U_* = \sqrt{\tau/\rho} \dots\dots\dots (3.3')$$

where, $U_* c$: critical friction velocity (cm/sec)
 d : diameter of material (cm)
 U_* : friction velocity (cm/sec)

The critical diameter of river bed material corresponding to the above tractive force is calculated by the following equation;

$$0.7344 \times 10^4 \times \frac{1}{1.1} = 80.9 \cdot d$$

$$d = 83 \text{ cm} = 0.83 \text{ m}$$

in terms of weight, this diameter is equivalent to $4/3 \times \pi \times (\frac{0.83}{2})^3 \times 2.5 = 0.748$ tons.

3) Thrust force

The thrust force for block is expressed in the form.

$$F = C_o \cdot W_o \cdot \epsilon \cdot S \cdot \frac{V^2}{2g} \dots\dots\dots (3.4)$$


where, F : thrust force (ton)
 C_o : coefficient of drag (= 1.0)
 W_o : density of water (= 1.1) (ton/m³)
 ϵ : coefficient of correction (= 1.0)
 S : surface area of block against flow (m²)
 V : velocity of flow (m/sec)
 g : acceleration of gravity (= 9.8 m/sec²)

The velocity of flow is calculated by using Manning's Formula expressed below.

$$\begin{aligned}
 V &= \frac{1}{n} \cdot R^{2/3} \cdot I^{1/2} \\
 &= \frac{1}{0.045} \times 1.09^{2/3} \times 0.0625^{1/2} \\
 &= 5.88 \text{ m/sec}
 \end{aligned}$$

The surface area against the flow is taken as 2 m^2 assuming the shape of concrete block shown in Fig. 3.1.

Fig. 3.1 Concrete Block for Foot Protection



Substituting above values to eq. (3.4), the thrust force is calculated as

$$\begin{aligned}
 F &= 1.0 \times 1.1 \times 1.0 \times 2 \times \frac{5.88^2}{2 \times 9.8} \\
 &= 3.881 \text{ tons}
 \end{aligned}$$

On the other hand, the resisting force of concrete block is calculated by the following equation.

$$R = \tan \phi \left(1 - \frac{W_o}{W_c}\right)W \dots\dots\dots (3.6)$$

where, R : resisting force of block
 ϕ : friction angle between block and river bed
 W_o : density of water (= 1.1)
 W_c : density of concrete (= 2.4)
 W : weight of concrete block

Letting ϕ be 35° , eq. (3.6) is changed as below.

$$R = \tan 35^\circ \left(1 - \frac{1.1}{2.4}\right)W = 0.379W$$

Therefore, the weight of concrete block is given as follows assuming that the resisting force of block is equal to the thrust force of flow.

$$\begin{aligned} 0.379W &= 3.881 \\ W &= 10.24 \text{ tons} \end{aligned}$$

Now, taking $\ell=3.0\text{m}$ and $e=0.3\text{m}$ in Fig. 3.1, the weight of concrete block comes to 27.36 tons as calculated below and it is enough to resist the thrust force of flow.

$$W = \{ 2 \times 3 + 2 \times 1.35 \times 2 \} \times 2.4 = 27.36 \text{ tons}$$

IV. RIVER CANALIZATION

4.1 General

The river canalization will be adopted for the lower reaches of the Pawa-Burabod river. The topographic condition of the basin and the principal features of the river canalization are summarized below.

Topography

Drainage area	10.5 km ²
River length	11.0 km for total length of the Pawa-Burabod river
Average river bed slope	1 : 15 for whole river length
River bed slope	1/43 to 1/17 for the reaches subject to canalization

River channel

Length	2,800 m
Channel width	60 m
River bed slope	1/28.1 - 1/17.5

Levee

Type	Sand and gravel fill with slope protection by wet masonry wall
Length	
Left bank - Total	2,799 m
- Existing	1,447 m
- New	1,352 m
Right bank - Total	2,808 m
- Existing	204 m
- New	2,604 m
Embankment volume	62,800 m ³
Wet masonry wall	3,956 m

Cribworks

Type	Log crib filled by cobble stone
Size and arrangement	Three lines with crib of 2.0m long x 2.0m wide x 0.8m depth
Total no. of cribs	6,993 nos.

Groundsills

Type	Type A	Log crib, 2.0m long x 2.0m wide x 0.8m depth filled by cobble stone
	Type B	Cross concrete block, 2.0m long x 2.0m wide x 0.8m depth
Number of groundsill		
	Type A	9 nos.
	Type B	2 nos.
Number of blocks		
	Type A (crib)	970 nos.
	Type B (concrete block)	305 nos.

4.2 Flood Analysis

1) General

Since no run-off data are available in the lower Pawa-Burabod river, probable flood is estimated from rainfall data. The calculation method is the same as applied in the previous chapters.

The probable flood is estimated herein about 1.01-yr., 1.5-yr., 5-yr., 10-yr., 30-yr. and 50-yr. flood respectively. These floods are utilized for the analysis of sediment load and practicable river width and the 50-yr. flood will be applied as the design flood of river canalization and the related structures.

The flood calculation will be made hereunder at the selected three base points as shown in Fig. 4.1, i.e.

No. 1 B.P	At the junction of the Yawa river and the Pawa-Burabod river for the drainage area of the main Yawa
-----------	---

No. 2 B.P At the junction of the Yawa river and the
Pawa-Burabod river for the drainage area
of the Pawa-Burabod river

No. 3 B.P River mouth of the main Yawa river

2) Drainage area

Drainage area at each base point is estimated as shown in Table 4.1.

Table 4.1 Drainage Area

Base Point	Drainage Basin	Drainage Area (km ²)
No. 1	No. I	53.5
No. 2	No. II	10.5
No. 3	No. III	6.0 (Sub-basin)
No. 3	No. I,II,III	70.0 (Total)

3) Run-off coefficient

Run-off coefficient in each divided sub-basin is estimated below
considering topography, geology and land use.

Table 4.2 Run-off Coefficient

Drainage Basin	Basin Area	Run-off Coefficient	Remarks
No. I	53.5	0.6	Farm land
No. II	10.5	0.7	Mountaneous area
No. III	6.0	0.6	Farm land
Total	70.0	0.62	Weighted

4) Time of flood concentration

Time of flood concentration is calculated by Kraven's formula as
previously presented. The results of calculation are summarily shown
below.

Table 4.3 Time of Flood Concentration

Base Point	L (m)	I	V (m/s)	t (min.)
No. 1	15,500	1/40	3.5	75
No. 2	11,000	1/15	3.5	50
No. 3	18,000	1/50	3.5	85 (Total)

5) Average rainfall intensity in a period of "Time of Flood Concentration"

By using Ito's formula previously presented, rainfall intensity is calculated for each return period at every site. The results of calculation are shown below.

Table 4.4 Average Rainfall Intensity in a Period of "Time of Flood Concentration"

Return Period (year)	24 (mm)	r (mm/hr)		
		Point No. 1 (t=75 min.)	Point No. 2 (t=50 min.)	Point No. 3 (Total) (t=85 min.)
1.01	80	15	16	14
1.5	160	30	32	29
5	290	54	59	52
10	360	67	73	65
30	490	91	99	88
50	560	104	113	101

6) Peak run-off

Peak run-off is calculated by Rational formula by applying the values obtained above. The results are as summarized below.

Table 4.5 Calculation of Peak Discharge

Return Period (year)	Peak Discharge : Q (m ³ /sec)		
	Specific Discharge : q (m ³ /sec/km ²)		
	Point No. 1	Point No. 2	Point No. 3 (Total)
	(f=0.60) (A=53.5 km ²) (t=75 min.)	(f=0.70) (A=10.5 km ²) (t=50 min.)	(f=0.62) (A=70.0 km ²) (t=85 min.)
1.01	140 (2.62)	40 (3.81)	170 (2.43)
1.5	270 (5.05)	70 (6.67)	350 (5.00)
5	490 (9.16)	130 (12.38)	630 (9.00)
10	600 (11.21)	150 (14.29)	790 (11.29)
30	820 (15.33)	210 (20.00)	1,070 (15.29)
50	930 (17.38)	240 (22.86)	1,220 (17.43)

The 50-year probable flood is used as the design flood for the Pawa-Burabod river. The calculated value will be appropriate comparing with the Japanese standard which are represented by the relation between the drainage area and specific discharge shown in Table 4.6.

Table 4.6 Relation between Drainage Area and Specific Discharge

Drainage Area (km ²)	0-5	5-10	10-20	20-40	40-60	60-80	80-100
Specific Discharge (m ³ /sec/km ²)	28	25	20	15	12	10	8

The 1.5-year probable flood is used for the study of sediment discharge capacity in the Yawa river and the Pawa-Burabod river assuming that such scale of flood is dominant to form a river channel or to be approximately such average run-off as to give average sediment discharge during a hydrological year, so called dominant flow, which is shown in the figures from Fig. 4.39 to Fig. 4.47.

4.3 Sediment Study

1) Sediment in the Yawa River

Aiming at grasping the sediment balance in the main Yawa river and the Pawa-Burabod river, sediment discharge in the Yawa river will firstly be estimated at the point of junction of the Yawa river and the Pawa-Burabod river.

The sediment discharge is calculated by using Brown's formula below.

$$\frac{Q_s}{U_* \cdot d_m \cdot T} = K \left\{ \frac{U_*^2}{(\sigma/\rho - 1) \cdot g \cdot d_m} \right\}^2 \dots\dots\dots (4.1)$$

where, Q_s : sediment discharge (m³/sec)
 U_* : friction velocity (m/sec)
 $U_* = \sqrt{gRI}$
 g : acceleration of gravity (9.8 m/sec²)
 R : hydraulic radius (m)
 I : river bed slope
 d_m : mean diameter of river bed materials
($d_{65} = 0.001$ m)
 T : river width (m)
 K : constant (=1.0)
 σ : density of river bed materials
(2.5 g/cm³)
 ρ : density of water (1.0 g/cm³)

Eq. 4.1 can be rewritten by substituting the above figures as follows:

$$Q_s = 1,390 (RI)^{2.5} \cdot T \dots\dots\dots (4.2)$$

By using eq. (4.2), the sediment discharge was calculated as shown in Table 4.7 and 4.20.

Table 4.7 Sediment Discharge in the Yawa River

	1.5-year Probable Flood	Sediment Discharge at 1.5-year Probable Flood (average)
Yawa river upstream	270 m ³ /sec	0.40 - 0.49 (0.45)
Yawa river downstream	340 "	0.65 - 1.20 (0.92)
Difference		(0.47)

*Figures in () show the average.

2) Sediment discharge in the Pawa-Burabod river

By applying the same calculation method and equation, the sediment discharge is also calculated at several points along the Pawa-Burabod river. The results of calculation is as follows:

Table 4.8 Sediment Discharge in the Pawa-Burabod River
(1.5-year probable flood 70 m³/sec)

Station	Sediment Discharge
Sta. 0 + 100	1.5 m ³ /sec
0 + 200	1.9
0 + 300	1.7
0 + 400	1.7
0 + 500	1.3
0 + 600	1.6
0 + 700	1.6
0 + 900	1.7
1 + 000	1.5
1 + 100	1.4
1 + 300	1.6
1 + 500	2.4
1 + 600	7.2
1 + 700	3.0
1 + 800	6.6
1 + 900	5.7
2 + 000	7.2

Station	Sediment Discharge
Sta. 2 + 100	3.1 m ³ /sec
2 + 200	2.9
2 + 400	5.4
2 + 500	5.8
2 + 600	5.4
2 + 700	5.1
2 + 800	5.0
Average	3.42
Range	1.2 - 7.3

3) Consideration

Sediment discharge at 1.5-year probable flood at the Yawa river and the Pawa-Burabod river are summarized below.

Table 4.9 Summary of Sediment Discharge

Rivers	Sediment Discharge
Pawa-Burabod river	1.2 - 7.3 (3.42)
Yawa river	
Downstream from junction	0.65 - 1.20 (0.92)
Upstream from junction	0.40 - 0.49 (0.45)

From the above, the following can be supposed:

1. The difference of sediment discharges between the upstream Yawa and downstream Yawa is about 0.47.
2. Sediment discharge in the Pawa-Burabod is considerably larger than that in the Yawa river.

3. Therefore, theoretically, the allowable sediment discharge to the Yawa river is 0.47 while the present sediment discharge there is 3.42.

4. Therefore, the upper Sabo works in the Yawa river is needed.

The above calculation gives only suggestive figures or qualitative characteristics, since sediment problems are very much complicated and difficult to be clarified in quantitative.

4.4 Discharge Capacity of the Present Pawa-Burabod River

Discharge capacity of the Pawa-Burabod river under the present condition is estimated at several points along the river course. The discharge capacity is calculated by non-uniform flow calculation method.

$$\frac{Q^2}{2gA_1^2} + H_1 + \frac{n^2 Q^2 \ell}{2} \left(\frac{1}{A_1^2 R_1^{4/3}} + \frac{1}{A_2^2 R_2^{4/3}} \right) = \frac{Q^2}{2gA_2^2} + H_2$$

where, Q : discharge (m³/sec)
 g : gravity acceleration (9.8 m/sec²)
 A : flow area (m²)
 H : water level (m)
 n : coefficient of roughness (= 0.045)
 ℓ : distance (m)
 R : hydraulic radius (m)
 Suffix 1 : downstream section
 Suffix 2 : upstream section

Based on the surveyed cross section, and profiles, the discharge capacity is calculated as shown below.

Table 4.10 Discharge Capacity of Present River Condition

Station	Critical Discharge Capacity	Discharge Capacity at Water Level with 1 m Allowance
Sta. 0 + 100	more than 500 m ³ /sec	more than 500 m ³ /sec
0 + 200	"	410
0 + 300	"	190
0 + 400	"	more than 500
0 + 500	360	80
0 + 600	290	80
0 + 700	250	50
0 + 900	320	100
1 + 000	400	90
1 + 100	170	40
1 + 300	250	30
1 + 500	0	0
1 + 600	130	10
1 + 700	120	10
1 + 800	400	100
1 + 900	320	160
2 + 000	320	100
2 + 100	220	30
2 + 200	200	10
2 + 400	210	30
2 + 500	more than 500	more than 500
2 + 600	"	"
2 + 700	"	"
2 + 800	"	"
more upstream	inundated	inundated

Since 50-year probable flood is 240 m³/sec, the river reach between Sta. 1 + 100 and Sta. 2 + 400 has less capacity, and the more upstream reaches from Sta. 2 + 800 has no any discharge capacity because of no definite river channel there, and inundation has been frequently occurred.

4.5 Design of River Channel

The river channel will be canalized between Sta. 1 + 100 and Sta. 3 + 900.

1) Channel width

The practicable river channel width is calculated by the following empirical formula.

$$B = 3.5 \sim 7.0 \sqrt{Q} \quad \dots\dots\dots (4.4)$$

where, B : practicable river width (m)
Q : run-off (m³/sec)

Assuming that dominant flow to form a river bed is 1.5-year flood (70 m³/sec), the practicable river channel width is calculated at 29-59 m. If the designed flood, 50-year probable flood (240 m³/sec) is applied, the practicable river width is calculated at 54 m to 108 m.

The present river width varies from about 30 m to 100 m, 60 m on an average. From the above considerations, the designed river width is taken at 60 m.

2) Equilibrium bed slope

If allowable sediment discharge, which may be discharged out into the Yawa river from the Pawa-Burabod river, is taken for the design sediment discharge for the Pawa-Burabod river, the equilibrium bed slope is calculated by the following formula.

$$H = \left(\frac{nQ}{\sqrt{I} T} \right)^{3/5} \quad \dots\dots\dots (4.5)$$

and

$$Q_s = 1,390 (HI)^{2.5} T \quad \dots\dots\dots (4.6)$$

From the above two equations, Q_s is rewritten as follows:

$$Q_s = 1,390 n^{1.5} Q^{1.5} I^{1.75} / T^{0.5}$$

where, $n=0.045$ $T=50$ m to be assumed

$$Q_s = 1.88 Q^{1.5} \times I^{1.75}$$

$$I_s = 0.7 Q_s^{0.57} / Q^{0.86} \dots\dots\dots (4.7)$$

By using equation (4.7) the equilibrium river bed slope is calculated as follows.

Table 4.11 Equilibrium River Bed Slope

Flood	Peak Run-off	Allowable Sediment Load	Equilibrium River Bed Slope
1.5-year	70 m ³ /sec	0.5 m ³ /sec	1/82
50-year	240 "	1.8 "	1/114

From the above calculation results, the equilibrium river bed slope will be about 1/80.

3) River cross section

For the design discharge of 240 m³/sec, and river width designed 60 m, the cross section is calculated by Manning's formula assuming the slope of revetment is 1:2.5. The results of calculation are summarily shown in Fig. 4.2 and Table 4.12.

4.6 Design of Levee

Existing levee has the following principal dimensions.

Crest width	5-7 m
Slope	1:0.6 - 1:1.8

According to the check calculation of stability such steep slope levee seems dangerous in case that heavy rain occurs and the embankment materials are saturated by rainwater. Therefore, the levee with more gentle slope is applied. Typical levee section is assumed as follows:


Crest width	3 m
Slope	1 : 2.5

Stability calculation of the typical design above is made by the circular arc method under the following conditions.

Density of embankment material	2.0 ton/m ³
Internal friction angle	$\phi = 35^\circ$

The calculation results are shown in Table 4.13.

Table 4.13 Stability Calculation of Levee



$$F_s = \frac{\sum W' \cos \theta \tan \phi}{\sum W \sin \theta} \dots\dots\dots (4.8)$$

where, $\gamma = \gamma_{sat} = 2.0 \text{ (ton/m}^3\text{)}$
 $\gamma' = \gamma_{sat} - 1.0 = 1.0 \text{ (ton/m}^3\text{)}$
 $\phi = 35^\circ$

No.	A (m ²)	Θ (°)	W = γ · A (ton/m)	W' = γ' · A (ton/m)	tan φ	W sin Θ (ton/m)	W' cos Θ x tan φ (ton/m)
1	0.45	43	0.90	0.45	0.70	0.61	0.23
2	1.21	33	2.42	1.21	0.70	1.32	0.71
3	1.50	22	3.00	1.50	0.70	1.12	0.97
4	1.45	13	2.90	1.45	0.70	0.65	0.99
5	1.15	6	2.30	1.15	0.70	0.24	0.80
6	0.78	-4	1.56	0.78	0.70	-0.11	0.54
7	0.28	-10	0.56	0.28	0.70	-0.10	0.19
Total						3.74	4.44

$$F_s = \frac{4.44}{3.74} = 1.19$$












Fig. 1.1 General Plan of Pawa - Burabod River






abod River









I-46

Fig.1.2 Profile of Pawa - Burabod River




Fig. 4.1


Basin Map of Yawa River

Scale = 1 : 50,000

Legend

Y-1 Sieve Test Pit No.

--- Basin Boundary



Base Point	Basin No.	Drainage Area (km ²)
①	I	53.5
②	II	10.5
③	III	6.0
	TOTAL	70.0

Fig.4.2 Present Condition of Pawa - Burabod River




Fig. 4.3 Typical Cross Section VS = 1 : 100 HS = 1 : 500




Table 4.12 Check of Discharge Capacity

Section \ Item	Design Flood Discharge Q (m ³ /sec)	Roughness Coefficient n	River Bed Slope I	Flow Area A (m)	Wetted Perimeter S (m)	Hydraulic Radius R (m)	Flow Velocity V (m/sec)	Calculated Discharge Qc (m ³ /sec)	Froude Number Fr	Remarks
Sta. 0 + 000 Sta. 1 + 100 Sta. 1 + 100	240	0.045	1 / 45.8	67.3	55.5	1.21	3.73	251	1.08	Super Critical Flow
Sta. 2 + 300 Sta. 3 + 100 Sta. 3 + 100	240	0.045	1 / 28.1	57.5	55.4	1.04	4.30	247	1.35	
Sta. 2 + 300 Sta. 3 + 100 Sta. 3 + 100	240	0.045	1 / 20.6	52.5	55.4	0.95	4.73	248	1.55	
Sta. 3 + 100 Sta. 3 + 700 Sta. 3 + 700	240	0.045	1 / 17.5	52.5	55.4	0.95	5.13	269	1.68	

Fig. 4.4 Grain Size Distribution Curve of Yawa River Bed Materials

Location : Bogtong

Test Pit No : Y - 1 (See Fig. 4.1)




Fig. 4.5 Grain Size Distribution Curve of Yawa River Bed Materials

Location : Bogtong

Test Pit No : Y-2 (See Fig. 4.1)




Fig. 4.6 Grain Size Distribution Curve of Yawa River Bed Materials

Location : Yawa

Test Pit No : Y-3 (See Fig.4.1)




Fig. 4.7 Grain Size Distribution Curve of Yawa River Bed Materials

Location : Malabog

Test Pit No : Y-4 (See Fig. 4.1)




Fig. 4.8 Grain Size Distribution Curve of Yawa River Bed Materials

Location : Budiad

Test Pit No : Y-5 (See Fig. 4.1)




Fig. 4.9 Grain Size Distribution Curve of Yawa River Bed Materials

Location : Bonga

Test Pit No : Y-6 (See Fig. 4-1)




Fig.4.10 Profile of Main Yawa River

VS = 1 : 200
HS = 1 : 20,000




Fig.4.11 Cross Section of Main Yawa River $s = 1 : 200$





Fig. 4.12 Cross Section of Main Yawa River S = 1 : 200





Fig. 4.13 H~Q, R, T Curve of Main Yawa River

STA.1+000 ($n=0.045$, $I=1/280$)



STA.2+000 ($n=0.045$, $I=1/210$)






Fig. 4.14 H~Q, R, T Curve of Main Yawa River

STA. 3 + 000 ($n=0.045, I=1/210$)



STA. 4 + 000 ($n=0.045, I=1/210$)






Fig. 4.16 H~Q, R, T Curve of Pawa - Burabod River




Fig. 4.17 H~Q, R, T Curve of Pawa - Burabod River




Fig. 4.18 H ~ Q, R, T Curve of Pawa - Burabod River




Fig. 4.19 H~Q, R, T Curve of Pawa - Burabod River




Fig. 4.20 H~Q, R, T Curve of Pawa - Burabod River




Fig. 4.21 H~Q, R, T Curve of Pawa - Burabod River




Fig. 4.22 H~Q, R, T Curve of Pawa - Burabod River




Fig. 4.23 H~Q, R, T Curve of Pawa - Burabod River




Fig. 4.24 H~Q, R, T Curve of Pawa - Burabod River




Fig. 4.25 H~Q, R, T Curve of Pawa - Burabod River




Fig. 4.26 H~Q, R,T Curve of Pawa - Burabod River




Fig. 4. 27 H~Q, R, T Curve of Pawa - Burabod River




Fig. 4. 28 H~Q, R, T Curve of Pawa - Burabod River




Fig. 4. 29 H~Q, R, T Curve of Pawa - Burabod River




Fig. 4.30 H~Q, R, T Curve of Pawa - Burabod River




Fig. 4. 31 H~Q, R,T Curve of Pawa - Burabod River




Fig. 4.32 H~Q, R, T Curve of Pawa - Burabod River





Fig. 4.33 H~Q, R, T Curve of Pawa - Burabod River






Fig. 4.35 H~Q, R, T Curve of Pawa - Burabod River




Fig. 4. 36 H~Q, R, T Curve of Pawa - Burabod River




Fig. 4.37 H~Q, R, T Curve of Pawa - Burabod River




Fig. 4.38 H~Q, R, T Curve of Pawa - Burabod River




Fig. 4.39 Dominant Flow of Pawa - Burabodo River

Caluculation Table(Sta,0+300)

Return Period (yr)	Discharge (m ³ /s)	Water Level (EL.m)	River Width (m)	Hydraulic Depth (m)	Sediment Discharge per Flood Qs(m ³ /sec)
1.01	40	14.0	29.0	0.6	0.93
1.50	70	14.35	41.0	0.67	1.73
5.00	130	14.7	52.0	0.83	3.74
10.00	150	14.85	57.0	0.9	5.02
30.00	210	15.1	64.0	1.05	8.29
50.00	240	15.2	65.5	1.1	9.53




Fig.4.40 Dominant Flow of Pawa – Burabodo River

Calculation Table (Sta. 0+600)

Return Period (yr)	Discharge (m ³ /s)	Water Level (EL. m)	River Width (m)	Hydraulic Depth (m)	Sediment Discharge per Flood Qs (m ³ /sec)
1.01	40	20.60	29.0	0.45	0.45
1.50	70	20.90	34.0	0.70	1.60
5.00	130	21.26	38.5	0.93	3.48
10.00	150	21.40	39.5	1.03	4.88
30.00	210	21.65	42.0	1.20	7.60
50.00	240	21.80	48.0	1.30	10.60





Fig. 4.41 Dominant Flow of Pawa - Burabodo River

Calculation Table (Sta. 1+000)

Return Period (yr)	Discharge (m^3/s)	Water Level (EL.m)	River Width (m)	Hydraulic Depth (m)	Sediment Discharge per Flood ($Q_s/m^2/sec$)
1.01	40	29.60	34.0	0.55	0.87
1.50	70	29.85	38.0	0.65	1.48
5.00	130	30.10	43.0	0.85	3.28
10.00	150	30.25	44.5	0.92	4.14
30.00	210	30.45	48.0	1.10	6.98
50.00	240	30.53	50.0	1.13	7.78



Frequency / 150 years at (times)

Sediment Discharge $Q_s \times \Delta t$ (m^3/s)

Fig. 4.42 Dominant Flow of Pawa - Burabodo River

Calculation Table (Sta. 1+600)

Return Period (yr)	Discharge (m^3/s)	Water Level (EL. m)	River Width (m)	Hydraulic Depth (m)	Sediment Discharge per Flood $Q_s(m^3/sec)$
1.01	40	49.90	31.0	0.63	3.58
1.50	70	50.10	400	0.75	7.15
5.00	130	50.25	48.5	0.85	11.85
10.00	150	50.30	49.5	0.90	13.96
30.00	210	50.50	53.0	1.00	19.45
50.00	240	50.60	53.5	1.07	23.25




Fig. 4.43 Dominant Flow of Pawa - Burabodo River

Caluculation Table (Sta. 1+800)

Return Period (yr)	Discharge (m^3/s)	Water Level (EL. m)	River Width (m)	Hydraulic Depth (m)	Sediment Discharge per Flood (Q_{sm}/sec)
1.01	40	56.80	31.0	0.73	5.18
1.50	70	56.90	31.5	0.80	6.62
5.00	130	57.15	33.5	0.98	11.69
10.00	150	57.20	34.5	1.04	13.96
30.00	210	57.45	36.5	1.20	21.13
50.00	240	57.55	37.0	1.27	24.68




Fig. 4.44 Dominant Flow of Pawa – Burabodo River

Calculation Table (Sta. 2+000)

Return Period (yr)	Discharge (m^3/s) (EL.m)	Water Level (EL.m)	River Width (m)	Hydraulic Depth (m)	Sediment Discharge per Flood (Q_s) (m^3/sec)
1.01	40	62.65	28.0	0.70	4.21
1.50	70	62.85	29.5	0.85	7.21
5.00	130	63.17	33.0	1.05	13.68
10.00	150	63.25	33.5	1.13	16.69
30.00	210	63.55	36.5	1.33	27.32
50.00	240	63.70	38.0	1.40	32.34





Fig. 4.45 Dominant Flow of Pawa - Burabodo River

Calculation Table (Sta. 2+500)

Return Period (yr)	Discharge (m^3/s)	Water Level (EL.m)	River Width (m)	Hydraulic Depth (m)	Sediment Discharge per Flood ($Qs/m^3/sec$)
1.01	40	83.0	29.0	0.47	3.02
1.50	70	83.2	34.5	0.57	5.82
5.00	130	83.45	43.5	0.68	11.41
10.00	150	83.55	45.0	0.75	15.08
30.00	210	83.80	52.5	0.86	24.77
50.00	240	83.85	53.0	0.90	28.01



Frequency / 150 years at (times)

Fig. 4.46 Dominant Flow of Pawa - Burabodo River

Calculation Table (Sta. 2+600)

Return Period (yr)	Discharge (m ³ /s)	Water Level (EL. m)	River Width (m)	Hydraulic Depth (m)	Sediment Discharge per Flood Q _s (m ³ /sec)
1.01	40	88.30	35.0	0.40	2.44
1.50	70	88.50	40.0	0.55	6.17
5.00	130	88.80	46.5	0.72	14.07
10.00	150	88.90	48.0	0.80	18.90
30.00	210	89.10	54.0	0.90	28.54
50.00	240	89.20	57.0	0.95	34.49




Fig. 4.47 Dominant Flow of Pawa - Burabodo River

Calculation Table (Sta. 2+700)

Return Period (yr)	Discharge (m^3/s)	Water Level (EL. m)	River Width (m)	Hydraulic Depth (m)	Sediment Discharge per Flood (m^3/sec)
1.01	40	93.30	73.0	0.28	2.08
1.50	70	93.40	73.0	0.40	5.08
5.00	130	93.55	74.5	0.50	9.99
10.00	150	93.58	74.5	0.60	14.29
30.00	210	93.70	76.0	0.70	21.43
50.00	240	93.80	77.0	0.80	30.32




Fig. 4. 48 Standard Relation between Levee Slope and Levee Height due to Soil Classification




Fig. 4. 49 Example of Foot Protection in Japan





Table. 4. 14 Standard Weight of Foot Protection in Japan

Flow Velocity (m/sec)	~ 2	2~4	4~
Weight of Block(tons/unit)	0.5~1	1~4	2~6

Fig 4. 50 Example of Foundation width in Japan




Legend

- | | |
|--------------------------|---------------------------|
| 1 ... Ibi River (LR) | 13 ... Ohoi River |
| 2 ... Nagara River (LR) | 14 ... Abe River |
| 3 ... Kiso River (LR) | 15 ... Joganji River (LR) |
| 4 ... Shonai River | 16 ... Ida River |
| 5 ... Yahagi River | 17 ... Kumano River |
| 6 ... Tenryu River (LR) | 18 ... Sho River (MR) |
| 7 ... Kiku River | 19 ... Jintsu River (MR) |
| 8 ... Kano River | 20 ... Sho River (UR) |
| 9 ... Koyabe River | 21 ... Jintsu River (UR) |
| 10 ... Jintsu River (LR) | 22 ... Joganji River (MR) |
| 11 ... Sho River (LR) | 23 ... Joganji River (UR) |
| 12 ... Toyo River | |

Note: * - Depth at design high-water level
 UR - Upper Reach
 MR - Middle Reach
 LR - Lower Reach

Fig 4.51 Example of Weight of Concrete Block for Ground-Sill in Japan



Note ; * Depth at design high Water level

NON-UNIFORM FLOW CALCULATION OF PAWA-BURABOD RIVER (Table 4.15)

CASE NO.	1	(Q = 50 m ³ /sec)	A	R	V	N	Q	DX	A*R** (2/3)	FROUD	IE
NO	H										
2+800	97.700	14.6	0.653	3.429	0.045	50.0	0.		9.600	0.1628E 01	0.6845E-01
2+700	93.337	26.5	0.362	1.838	0.045	50.0	-100.00		13.448	0.1003E 01	0.2799E-01
2+600	98.167	15.7	0.425	3.179	0.045	50.0	-100.00		8.889	0.1538E 01	0.6407E-01
2+500	93.123	16.8	0.528	2.285	0.045	50.0	-100.00		10.948	0.1312E 01	0.4223E-01
2+400	77.836	15.3	0.458	3.272	0.045	50.0	-100.00		9.078	0.1545E 01	0.6144E-01
2+300	70.338	21.5	0.554	2.330	0.045	50.0	-200.00		14.482	0.1000E 01	0.2414E-01
2+200	66.229	16.4	0.453	3.040	0.045	50.0	-100.00		9.705	0.1442E 01	0.5375E-01
2+100	62.523	19.2	0.694	2.606	0.045	50.0	-100.00		15.034	0.1000E 01	0.2240E-01
1+900	59.155	13.4	0.783	3.731	0.045	50.0	-100.00		11.385	0.1347E 01	0.3906E-01
1+800	56.715	19.8	0.654	2.531	0.045	50.0	-100.00		14.881	0.1000E 01	0.2286E-01
1+700	52.723	14.9	0.542	3.352	0.045	50.0	-100.00		9.910	0.1455E 01	0.5154E-01
1+600	49.772	19.6	0.661	2.545	0.045	50.0	-100.00		14.914	0.1000E 01	0.2276E-01
1+500	45.573	17.9	0.369	2.792	0.045	50.0	-100.00		9.206	0.1469E 01	0.5974E-01
1+400	38.473	22.2	0.518	2.252	0.045	50.0	-200.00		14.315	0.1000E 01	0.2470E-01
1+300	32.653	16.5	0.675	3.022	0.045	50.0	-200.00		12.734	0.1175E 01	0.3122E-01
1+200	29.655	19.2	0.540	2.609	0.045	50.0	-100.00		12.709	0.1134E 01	0.3134E-01
0+900	27.381	20.5	0.607	2.438	0.045	50.0	-100.00		14.699	0.1000E 01	0.2343E-01
0+800	23.478	21.3	0.561	2.343	0.045	50.0	-200.00		14.509	0.1000E 01	0.2405E-01
0+700	20.771	19.0	0.589	2.634	0.045	50.0	-100.00		13.338	0.1096E 01	0.2846E-01
0+600	17.861	19.6	0.535	2.547	0.045	50.0	-100.00		12.938	0.1112E 01	0.3025E-01
0+500	15.511	22.7	0.497	2.207	0.045	50.0	-100.00		14.217	0.1000E 01	0.2505E-01
0+400	14.145	20.6	0.604	2.433	0.045	50.0	-100.00		14.694	0.1000E 01	0.2345E-01
0+300	11.791	19.8	0.648	2.529	0.045	50.0	-100.00		14.807	0.1004E 01	0.2309E-01
0+200	8.020	13.9	0.667	3.597	0.045	50.0	-100.00		10.608	0.1407E 01	0.4499E-01

CASE NO.	2 (Q = 100 m ³ /sec)									
NO	H	A	R	V	N	Q	DX	A*R** (2/3)	FROUD	IE
2+800	98.050	26.4	0.628	3.789	0.045	100.0	0.	19.351	0.1528E 01	0.5408E-01
2+700	93.456	34.9	0.476	2.864	0.045	100.0	-100.00	21.286	0.1326E 01	0.4469E-01
2+600	88.689	28.3	0.640	3.534	0.045	100.0	-100.00	21.020	0.1411E 01	0.4583E-01
2+500	93.370	25.4	0.637	3.936	0.045	100.0	-100.00	18.818	0.1575E 01	0.5719E-01
2+400	78.138	26.0	0.698	3.842	0.045	100.0	-100.00	20.481	0.1469E 01	0.4828E-01
2+300	70.599	31.7	0.747	3.157	0.045	100.0	-200.00	26.065	0.1167E 01	0.2981E-01
2+200	66.515	26.9	0.670	3.713	0.045	100.0	-100.00	20.625	0.1449E 01	0.4740E-01
2+100	62.988	29.3	0.951	3.419	0.045	100.0	-100.00	28.291	0.1120E 01	0.2530E-01
1+900	59.684	23.2	1.107	4.317	0.045	100.0	-100.00	24.786	0.1311E 01	0.3296E-01
1+800	57.024	29.0	0.896	3.446	0.045	100.0	-100.00	26.971	0.1163E 01	0.2784E-01
1+700	53.081	25.0	0.763	3.998	0.045	100.0	-100.00	20.890	0.1462E 01	0.4641E-01
1+600	50.176	35.9	0.791	2.784	0.045	100.0	-100.00	30.732	0.1000E 01	0.2144E-01
1+500	45.762	27.1	0.558	3.695	0.045	100.0	-100.00	18.337	0.1580E 01	0.6022E-01
1+400	39.791	37.1	0.742	2.696	0.045	100.0	-200.00	30.405	0.1000E 01	0.2191E-01
1+300	33.094	28.9	0.802	3.456	0.045	100.0	-200.00	24.987	0.1232E 01	0.3243E-01
1+200	29.966	30.3	0.770	3.302	0.045	100.0	-100.00	25.435	0.1202E 01	0.3130E-01
1+100	28.282	35.5	0.812	2.819	0.045	100.0	-100.00	30.864	0.1000E 01	0.2126E-01
0+900	23.800	34.5	0.791	2.902	0.045	100.0	-200.00	29.480	0.1042E 01	0.2330E-01
0+800	21.123	30.6	0.829	3.266	0.045	100.0	-100.00	27.028	0.1146E 01	0.2772E-01
0+700	18.158	30.8	0.741	3.243	0.045	100.0	-100.00	25.259	0.1203E 01	0.3174E-01
0+600	15.935	38.3	0.696	2.612	0.045	100.0	-100.00	30.075	0.1000E 01	0.2239E-01
0+500	14.560	36.3	0.773	2.751	0.045	100.0	-100.00	30.615	0.1000E 01	0.2161E-01
0+400	12.176	32.4	0.850	3.083	0.045	100.0	-100.00	29.117	0.1068E 01	0.2389E-01
0+300	8.449	24.6	0.830	4.060	0.045	100.0	-100.00	21.745	0.1424E 01	0.4283E-01
Station Number	Water Level (EL.m)	Flow Area (m ²)	Hydraulic Radius (m)	Flow Velocity (m/sec)	Roughness Coefficient	Discharge (m ³ /sec)	Distance (m)		Prude Number	Energy Gradient

NON-UNIFORM FLOW CALCULATION OF PAJA-BURABOD RIVER (Table 4.16)

CASE NO.	3	(Q = 150 m ³ /sec)										
N0	A	R	V	H	q	DX	A-R**(2/3)	FROUD	IE			
24800	36.0	0.727	4.172	0.045	150.0	0.	29.080	0.1563E 01	0.5388E-01			
24700	44.4	0.595	3.376	0.045	150.0	-100.00	31.420	0.1399E 01	0.4615E-01			
24600	39.2	0.792	3.931	0.045	150.0	-100.00	32.658	0.1411E 01	0.4272E-01			
24500	33.9	0.740	4.429	0.045	150.0	-100.00	27.711	0.1645E 01	0.5933E-01			
24400	34.6	0.869	4.333	0.045	150.0	-100.00	31.520	0.1485E 01	0.4586E-01			
24300	40.0	0.905	3.750	0.045	150.0	-200.00	37.439	0.1259E 01	0.3251E-01			
24200	70.793	0.905	4.187	0.045	150.0	-100.00	31.953	0.1461E 01	0.4491E-01			
24100	35.6	0.838	4.187	0.045	150.0	-100.00	41.320	0.1184E 01	0.2669E-01			
24000	63.262	1.130	3.930	0.045	150.0	-100.00	39.581	0.1278E 01	0.2908E-01			
14900	60.097	1.387	4.714	0.045	150.0	-100.00	36.800	0.1311E 01	0.3364E-01			
14800	57.225	1.040	4.183	0.045	150.0	-100.00	33.235	0.1439E 01	0.4125E-01			
14700	33.5	0.990	4.484	0.045	150.0	-100.00	40.263	0.1165E 01	0.2811E-01			
14600	50.337	0.882	3.425	0.045	150.0	-100.00	29.250	0.1557E 01	0.5325E-01			
14500	45.942	0.738	4.189	0.045	150.0	-100.00	47.233	0.1001E 01	0.2042E-01			
14400	39.049	0.925	3.015	0.045	150.0	-200.00	36.569	0.1267E 01	0.3407E-01			
14300	41.9	0.816	3.582	0.045	150.0	-200.00	39.693	0.1193E 01	0.2892E-01			
14200	41.6	0.933	3.608	0.045	150.0	-100.00	47.692	0.1000E 01	0.2003E-01			
14100	48.6	0.972	3.086	0.045	150.0	-200.00	43.312	0.1100E 01	0.2429E-01			
04700	44.4	0.965	3.381	0.045	150.0	-100.00	41.835	0.1152E 01	0.2603E-01			
04600	40.9	1.036	3.670	0.045	150.0	-100.00	36.858	0.1280E 01	0.3354E-01			
04500	39.2	0.910	3.822	0.045	150.0	-100.00	46.779	0.1000E 01	0.2082E-01			
04400	51.6	0.864	2.909	0.045	150.0	-100.00	46.997	0.1000E 01	0.2063E-01			
04300	14.835	0.889	2.951	0.045	150.0	-100.00	44.270	0.1082E 01	0.2325E-01			
04200	44.3	0.999	3.386	0.045	150.0	-100.00	32.604	0.1456E 01	0.4286E-01			
04100	33.9	0.945	4.431	0.045	150.0	-100.00						

CASE NO.	4	(Q = 200 m ³ /sec)	A	R	V	N	q	DX	A-R** (2/3)	FROUD	IE
24800	98.400	43.1	0.802	4.638	0.045	200.0	0.	37.228	0.1654E 01	0.5845E-01	
24700	93.712	54.0	0.709	3.706	0.045	200.0	-100.00	42.884	0.1407E 01	0.4404E-01	
24600	89.035	46.7	0.891	4.282	0.045	200.0	-100.00	43.241	0.1449E 01	0.4332E-01	
24500	83.738	41.9	0.834	4.769	0.045	200.0	-100.00	37.154	0.1668E 01	0.5868E-01	
24400	78.554	42.1	1.009	4.752	0.045	200.0	-100.00	42.347	0.1511E 01	0.4517E-01	
24300	70.970	47.6	1.051	4.200	0.045	200.0	-200.00	49.212	0.1309E 01	0.3345E-01	
24200	66.911	43.5	0.984	4.599	0.045	200.0	-100.00	43.008	0.1481E 01	0.4379E-01	
24100	63.512	46.2	1.292	4.326	0.045	200.0	-100.00	54.842	0.1216E 01	0.2693E-01	
14900	60.476	40.6	1.549	4.931	0.045	200.0	-100.00	54.294	0.1266E 01	0.2748E-01	
14800	57.420	42.5	1.179	4.709	0.045	200.0	-100.00	47.398	0.1385E 01	0.3606E-01	
14700	53.547	40.6	1.188	4.926	0.045	200.0	-100.00	45.546	0.1444E 01	0.3903E-01	
14600	50.489	51.3	0.967	3.902	0.045	200.0	-100.00	50.112	0.1268E 01	0.3226E-01	
14500	46.104	43.6	0.900	4.583	0.045	200.0	-100.00	40.680	0.1543E 01	0.4895E-01	
14400	39.160	55.8	1.028	3.585	0.045	200.0	-200.00	56.838	0.1129E 01	0.2507E-01	
14300	33.636	54.5	0.933	3.667	0.045	200.0	-200.00	52.101	0.1212E 01	0.2984E-01	
14200	30.410	49.4	1.041	4.045	0.045	200.0	-100.00	50.782	0.1266E 01	0.3141E-01	
04900	28.796	61.0	1.099	3.280	0.045	200.0	-100.00	64.919	0.1000E 01	0.1922E-01	
04700	24.214	53.4	1.107	3.744	0.045	200.0	-200.00	57.180	0.1136E 01	0.2477E-01	
04600	21.630	50.3	1.206	3.975	0.045	200.0	-100.00	57.018	0.1156E 01	0.2491E-01	
04500	18.524	46.7	1.062	4.286	0.045	200.0	-100.00	48.586	0.1328E 01	0.3431E-01	
04400	16.364	63.5	1.014	3.151	0.045	200.0	-100.00	64.055	0.1000E 01	0.1974E-01	
04300	15.064	63.7	1.006	3.139	0.045	200.0	-100.00	63.952	0.1000E 01	0.1981E-01	
04200	12.702	55.1	1.094	3.632	0.045	200.0	-100.00	58.483	0.1109E 01	0.2368E-01	
04100	8.976	42.8	1.054	4.669	0.045	200.0	-100.00	44.352	0.1453E 01	0.4118E-01	

(Table 4.17)

NON-UNIFORM FLOW CALCULATION OF PAWA-BURABOD RIVER

CASE NO. 5 (Q = 250 m³/sec)

NO	H	A	R	V	N	Q	DX	A*R**(2/3)	FROUD	IE
2+800	98.550	51.1	0.377	4.892	0.045	250.0	0.	46.812	0.169E 01	0.5776E-01
2+700	93.811	61.4	0.799	4.069	0.045	250.0	-100.00	52.851	0.1455E 01	0.4531E-01
2+600	89.248	55.9	0.971	4.471	0.045	250.0	-100.00	54.822	0.1450E 01	0.4211E-01
2+500	83.881	49.2	0.918	5.084	0.045	250.0	-100.00	46.452	0.1695E 01	0.5866E-01
2+400	78.716	49.2	1.127	5.084	0.045	250.0	-100.00	53.249	0.1530E 01	0.4464E-01
2+300	71.128	54.2	1.174	4.564	0.045	250.0	-200.00	60.956	0.1346E 01	0.3406E-01
2+200	67.075	50.6	1.113	4.945	0.045	250.0	-100.00	54.291	0.1497E 01	0.4294E-01
2+100	63.716	53.8	1.416	4.644	0.045	250.0	-100.00	67.874	0.1247E 01	0.2747E-01
1+900	60.791	49.2	1.679	5.084	0.045	250.0	-100.00	69.448	0.1254E 01	0.2624E-01
1+800	57.597	48.9	1.301	5.113	0.045	250.0	-130.00	58.253	0.1432E 01	0.3730E-01
1+700	53.740	47.2	1.364	5.302	0.045	250.0	-100.00	57.981	0.1450E 01	0.3765E-01
1+600	50.602	57.2	1.071	4.367	0.045	250.0	-100.00	59.922	0.1348E 01	0.3525E-01
1+500	46.253	50.8	1.049	4.919	0.045	250.0	-100.00	52.457	0.1534E 01	0.4599E-01
1+400	39.268	61.7	1.130	4.050	0.045	250.0	-200.00	66.966	0.1217E 01	0.2822E-01
1+300	33.305	64.4	1.091	3.881	0.045	250.0	-200.00	68.262	0.1187E 01	0.2716E-01
1+200	30.569	57.1	1.132	4.380	0.045	250.0	-100.00	61.982	0.1315E 01	0.3294E-01
1+100	29.008	72.4	1.216	3.452	0.045	250.0	-100.00	82.515	0.1000E 01	0.1859E-01
0+900	24.385	61.6	1.237	4.056	0.045	250.0	-200.00	71.006	0.1165E 01	0.2510E-01
0+800	21.838	59.1	1.351	4.229	0.045	250.0	-100.00	72.268	0.1162E 01	0.2423E-01
0+700	18.677	53.3	1.214	4.689	0.045	250.0	-100.00	60.675	0.1359E 01	0.3438E-01
0+600	16.517	72.8	1.130	3.432	0.045	250.0	-100.00	79.014	0.1031E 01	0.2027E-01
0+500	15.234	75.0	1.133	3.332	0.045	250.0	-100.00	81.556	0.1000E 01	0.1903E-01
0+400	12.906	65.4	1.184	3.822	0.045	250.0	-100.00	73.220	0.1122E 01	0.2361E-01
0+300	9.153	50.2	1.188	4.983	0.045	250.0	-100.00	56.269	0.1461E 01	0.3997E-01

CASE NO. 6 (Q = 300 m³/sec)

NO	H	A	R	V	N	Q	DX	A*R**(2/3)	FROUD	IE
2+800	98.700	60.7	0.951	4.942	0.045	300.0	0.	58.709	0.1619E 01	0.5288E-01
2+700	93.989	67.4	0.868	4.454	0.045	300.0	-100.00	61.308	0.1527E 01	0.4849E-01
2+600	89.416	65.5	1.054	4.583	0.045	300.0	-100.00	67.789	0.1426E 01	0.3966E-01
2+500	84.007	55.6	0.994	5.396	0.045	300.0	-100.00	55.382	0.1729E 01	0.5942E-01
2+400	78.871	56.0	1.239	5.360	0.045	300.0	-100.00	64.563	0.1538E 01	0.4372E-01
2+300	71.262	61.0	1.289	4.918	0.045	300.0	-200.00	72.244	0.1384E 01	0.3492E-01
2+200	67.215	56.9	1.247	5.273	0.045	300.0	-100.00	65.900	0.1509E 01	0.4197E-01
2+100	63.900	60.7	1.528	4.943	0.045	300.0	-100.00	80.505	0.1277E 01	0.2812E-01
1+900	61.081	57.5	1.799	5.214	0.045	300.0	-100.00	85.093	0.1242E 01	0.2517E-01
1+800	57.736	54.9	1.406	5.463	0.045	300.0	-100.00	68.919	0.1472E 01	0.3837E-01
1+700	53.922	53.4	1.530	5.622	0.045	300.0	-100.00	70.852	0.1452E 01	0.3631E-01
1+600	50.703	62.6	1.168	4.791	0.045	300.0	-100.00	69.442	0.1416E 01	0.3779E-01
1+500	46.392	57.6	1.188	5.211	0.045	300.0	-100.00	64.568	0.1527E 01	0.4372E-01
1+400	39.371	67.4	1.226	4.453	0.045	300.0	-200.00	77.169	0.1285E 01	0.3040E-01
1+300	33.963	73.6	1.238	4.072	0.045	300.0	-200.00	84.885	0.1170E 01	0.2529E-01
1+200	30.707	64.5	1.206	4.653	0.045	300.0	-100.00	73.045	0.1354E 01	0.3416E-01
0+900	29.176	93.2	1.327	3.605	0.045	300.0	-200.00	100.509	0.1000E 01	0.1804E-01
0+800	24.544	69.5	1.355	4.314	0.045	300.0	-100.00	85.164	0.1184E 01	0.2513E-01
0+700	22.029	67.3	1.485	4.458	0.045	300.0	-100.00	87.592	0.1169E 01	0.2375E-01
0+600	18.820	59.5	1.356	5.038	0.045	300.0	-100.00	72.951	0.1382E 01	0.3425E-01
0+500	16.619	79.7	1.206	3.764	0.045	300.0	-100.00	90.280	0.1095E 01	0.2236E-01
0+400	15.394	85.6	1.253	3.504	0.045	300.0	-100.00	99.506	0.1000E 01	0.1841E-01
0+300	13.076	75.0	1.261	4.000	0.045	300.0	-100.00	87.539	0.1138E 01	0.2378E-01
0+200	9.318	57.2	1.321	5.247	0.045	300.0	-100.00	68.854	0.1458E 01	0.3844E-01

NON-UNIFORM FLOW CALCULATION OF PAJA-BURABOD RIVER (Table 4.18)

CASE NO.	7 (Q = 350 m ³ /sec)										8 (Q = 400 m ³ /sec)									
	N	A	R	V	N	Q	DX	A*R*(2/3)	FROUD	IE	N	A	R	V	N	Q	DX	A*R*(2/3)	FROUD	IE
2+800	98.800	67.1	1.001	5.216	0.045	350.0	0.	67.136	0.1666	0.5504E-01	0.045	73.5	1.050	5.442	0.045	400.0	0.	75.949	0.1696	0.5617E-01
2+700	93.987	74.7	0.956	4.684	0.045	350.0	-100.00	72.539	0.1530E 01	0.4714E-01	0.045	81.6	1.032	4.901	0.045	400.0	-100.00	83.367	0.1541E 01	0.4662E-01
2+600	89.535	72.5	1.125	4.928	0.045	350.0	-100.00	78.412	0.1454E 01	0.4033E-01	0.045	78.9	1.209	5.067	0.045	400.0	-100.00	89.618	0.1472E 01	0.4034E-01
2+500	84.115	61.7	1.088	5.669	0.045	350.0	-100.00	65.313	0.1736E 01	0.5815E-01	0.045	67.5	1.176	5.930	0.045	400.0	-100.00	75.146	0.1747E 01	0.5738E-01
2+400	79.004	61.8	1.336	5.963	0.045	350.0	-100.00	74.369	0.1565E 01	0.4414E-01	0.045	72.7	1.444	5.963	0.045	400.0	-100.00	85.886	0.1585E 01	0.4413E-01
2+300	71.393	67.1	1.414	5.215	0.045	350.0	-200.00	84.533	0.1401E 01	0.3471E-01	0.045	68.1	1.527	5.503	0.045	400.0	-200.00	96.379	0.1423E 01	0.3488E-01
2+200	67.342	62.6	1.367	5.592	0.045	350.0	-100.00	77.094	0.1528E 01	0.4174E-01	0.045	72.7	1.483	5.875	0.045	400.0	-100.00	88.531	0.1541E 01	0.4134E-01
2+100	64.076	62.4	1.633	5.194	0.045	350.0	-100.00	93.445	0.1298E 01	0.2841E-01	0.045	68.1	1.746	5.465	0.045	400.0	-100.00	106.111	0.1321E 01	0.2878E-01
1+900	61.317	65.0	1.931	5.388	0.045	350.0	-100.00	100.714	0.1239E 01	0.2446E-01	0.045	73.2	2.102	5.603	0.045	400.0	-100.00	117.164	0.1234E 01	0.2360E-01
1+800	57.908	60.7	1.507	5.767	0.045	350.0	-100.00	79.769	0.1501E 01	0.3898E-01	0.045	66.0	1.596	6.059	0.045	400.0	-100.00	90.153	0.1532E 01	0.3986E-01
1+700	54.091	59.2	1.682	5.914	0.045	350.0	-100.00	83.687	0.1457E 01	0.3542E-01	0.045	64.9	1.826	6.165	0.045	400.0	-100.00	96.935	0.1457E 01	0.3448E-01
1+600	50.800	67.8	1.260	5.166	0.045	350.0	-100.00	79.045	0.1470E 01	0.3970E-01	0.045	62.9	1.826	6.165	0.045	400.0	-100.00	88.522	0.1517E 01	0.4135E-01
1+500	46.522	63.9	1.318	5.480	0.045	350.0	-100.00	76.771	0.1525E 01	0.4209E-01	0.045	69.8	1.347	5.512	0.045	400.0	-100.00	89.084	0.1524E 01	0.4083E-01
1+400	39.471	72.8	1.319	4.805	0.045	350.0	-200.00	87.615	0.1336E 01	0.3232E-01	0.045	78.0	1.411	5.729	0.045	400.0	-200.00	98.155	0.1379E 01	0.3363E-01
1+300	34.105	82.0	1.376	4.267	0.045	350.0	-200.00	101.479	0.1162E 01	0.2409E-01	0.045	78.0	1.411	5.728	0.045	400.0	-200.00	117.941	0.1160E 01	0.2329E-01
1+200	30.841	71.7	1.278	4.885	0.045	350.0	-100.00	84.360	0.1381E 01	0.3486E-01	0.045	78.6	1.347	5.088	0.045	400.0	-100.00	95.999	0.1400E 01	0.3523E-01
0+900	29.334	93.4	1.432	3.746	0.045	350.0	-100.00	118.722	0.1000E 01	0.1760E-01	0.045	103.2	1.533	3.875	0.045	400.0	-100.00	137.235	0.1000E 01	0.1720E-01
0+700	24.688	77.2	1.457	4.535	0.045	350.0	-200.00	99.210	0.1200E 01	0.2520E-01	0.045	84.4	1.554	4.738	0.045	400.0	-200.00	115.271	0.1214E 01	0.2525E-01
0+600	22.208	76.0	1.566	4.608	0.045	350.0	-100.00	102.627	0.1176E 01	0.2364E-01	0.045	84.4	1.638	4.744	0.045	400.0	-100.00	99.945	0.1184E 01	0.2360E-01
0+500	18.964	65.8	1.499	5.316	0.045	350.0	-100.00	86.250	0.1387E 01	0.3335E-01	0.045	71.9	1.638	5.562	0.045	400.0	-100.00	99.945	0.1388E 01	0.3244E-01
0+400	16.704	85.4	1.269	4.097	0.045	350.0	-100.00	100.163	0.1161E 01	0.2473E-01	0.045	90.8	1.329	4.405	0.045	400.0	-100.00	109.771	0.1221E 01	0.2689E-01
0+300	15.543	95.7	1.366	3.458	0.045	350.0	-100.00	117.773	0.1000E 01	0.1788E-01	0.045	105.4	1.471	3.796	0.045	400.0	-100.00	136.327	0.1000E 01	0.1743E-01
0+200	13.218	84.0	1.327	4.169	0.045	350.0	-100.00	101.368	0.1156E 01	0.2414E-01	0.045	92.7	1.390	4.316	0.045	400.0	-100.00	115.439	0.1169E 01	0.2431E-01
0+100	9.482	64.1	1.454	5.459	0.045	350.0	-100.00	82.290	0.1446E 01	0.3663E-01	0.045	70.8	1.575	5.648	0.045	400.0	-100.00	95.871	0.1438E 01	0.3525E-01

CASE NO. 8 (Q = 400 m³/sec)

CASE NO.	7 (Q = 350 m ³ /sec)										8 (Q = 400 m ³ /sec)									
	N	A	R	V	N	Q	DX	A*R*(2/3)	FROUD	IE	N	A	R	V	N	Q	DX	A*R*(2/3)	FROUD	IE
2+800	98.900	73.5	1.050	5.442	0.045	400.0	0.	75.949	0.1696	0.5617E-01	0.045	73.5	1.050	5.442	0.045	400.0	0.	75.949	0.1696	0.5617E-01
2+700	94.075	81.6	1.032	4.901	0.045	400.0	-100.00	83.367	0.1541E 01	0.4662E-01	0.045	81.6	1.032	4.901	0.045	400.0	-100.00	89.618	0.1472E 01	0.4034E-01
2+600	89.634	78.9	1.209	5.067	0.045	400.0	-100.00	89.618	0.1472E 01	0.4034E-01	0.045	78.9	1.209	5.067	0.045	400.0	-100.00	96.935	0.1457E 01	0.3448E-01
2+500	84.215	67.5	1.176	5.930	0.045	400.0	-100.00	75.146	0.1747E 01	0.5738E-01	0.045	67.5	1.176	5.930	0.045	400.0	-100.00	85.886	0.1585E 01	0.4413E-01
2+400	79.118	67.1	1.444	5.963	0.045	400.0	-100.00	85.886	0.1585E 01	0.4413E-01	0.045	72.7	1.444	5.963	0.045	400.0	-100.00	96.379	0.1423E 01	0.3488E-01
2+300	71.513	72.7	1.527	5.503	0.045	400.0	-200.00	96.379	0.1423E 01	0.3488E-01	0.045	68.1	1.527	5.503	0.045	400.0	-200.00	88.531	0.1541E 01	0.4134E-01
2+200	67.464	68.1	1.483	5.875	0.045	400.0	-100.00	88.531	0.1541E 01	0.4134E-01	0.045	72.7	1.483	5.875	0.045	400.0	-100.00	106.111	0.1321E 01	0.2878E-01
2+100	64.220	73.2	1.746	5.465	0.045	400.0	-100.00	106.111	0.1321E 01	0.2878E-01	0.045	68.1	1.746	5.465	0.045	400.0	-100.00	117.164	0.1234E 01	0.2360E-01
1+900	61.515	71.4	2.102	5.603	0.045	400.0	-100.00	117.164	0.1234E 01	0.2360E-01	0.045	73.2	2.102	5.603	0.045	400.0	-100.00	90.153	0.1532E 01	0.3986E-01
1+800	58.044	66.0	1.596	6.059	0.045	400.0	-100.00	90.153	0.1532E 01	0.3986E-01	0.045	66.0	1.596	6.059	0.045	400.0	-100.00	96.935	0.1457E 01	0.3448E-01
1+700	54.254	64.9	1.826	6.165	0.045	400.0	-100.00	88.522	0.1517E 01	0.4135E-01	0.045	64.9	1.826	6.165	0.045	400.0	-100.00	88.522	0.1517E 01	0.4135E-01
1+600	50.891	72.6	1.347	5.512	0.045	400.0	-100.00	89.084	0.1524E 01	0.4083E-01	0.045	72.6	1.347	5.512	0.045	400.0	-100.00	98.155	0.1379E 01	0.3363E-01
1+500	46.645	69.8	1.411	5.729	0.045	400.0	-200.00	98.155	0.1379E 01	0.3363E-01	0.045	69.8	1.411	5.729	0.045	400.0	-200.00	117.941	0.1160E 01	0.2329E-01
1+400	39.566	78.0	1.411	5.728	0.045	400.0	-200.00	117.941	0.1160E 01	0.2329E-01	0.045	78.0	1.411	5.728	0.045	400.0	-200.00	95.999	0.1400E 01	0.3523E-01
1+300	34.235	89.8	1.506	4.456	0.045	400.0	-100.00	95.999	0.1400E 01	0.3523E-01	0.045	89.8	1.506	4.456	0.045	400.0	-100.00	137.235	0.1000E 01	0.1720E-01
1+200	30.971	78.6	1.347	5.088	0.045	400.0	-100.00	137.235	0.1000E 01	0.1720E-01	0.045	78.6	1.347	5.088	0.045	400.0	-100.00	115.271	0.1214E 01	0.2525E-01
0+900	29.486	103.2	1.533	3.875	0.045	400.0	-200.00	115.271	0.1214E 01	0.2525E-01	0.045	103.2	1.533	3.875	0.045	400.0	-200.00	99.945	0.1244E 01	0.2525E-01
0+700	24.824	84.4	1.554	4.738	0.045	400.0	-200.00	99.945	0.1244E 01	0.2525E-01	0.045	84.4	1.554	4.738	0.045	400.0	-200.00	117.178	0.1184E 01	0.2360E-01
0+600	22.378	84.3	1.638	4.744	0.045	400.0	-100.00	99.945	0.1184E 01	0.2360E-01	0.045	84.3	1.638	4.744	0.045	400.0	-100.00	99.945	0.1388E 01	0.3244E-01
0+500	19.104	71.9	1.638	5.562	0.045	400.0	-100.00	99.945	0.1388E 01	0.3244E-01	0.045	71.9	1.638	5.562	0.045	400.0	-100.00	109.771	0.1221E 01	0.2689E-01
0+400	16.784	90.8	1.329	4.405	0.045	400.0	-100.00	109.771	0.1221E 01	0.2689E-01	0.045	90.8	1.329	4.405	0.045	400.0	-100.00	136.327	0.1000E 01	0.1743E-01
0+300	15.680	105.4	1.471	3.796	0.045	400.0	-100.00	136.327	0.1000E 01	0.1743E-01	0.045	105.4	1.471	3.796	0.045	400.0	-100.00	115.439	0.1169E 01	0.2431E-01
0+200	13.356	92.7	1.390	4.316	0.045	400.0	-100.00	115.439	0.1169E 01	0.2431E-01	0.045	92.7	1.390	4.316	0.045	400.0	-100.00	95.871	0.1438E 01	0.3525E-01
0+100	9.633	70.8	1.575	5.648	0.045	400.0	-100.00	95.871	0.1438E 01	0.3525E-01	0.045	70.8	1.575	5.648	0.045	400.0	-100.00	82.290	0.1446E 01	0.3663E-01

NON-UNIFORM FLOW CALCULATION OF PAWA-BURABOD RIVER (Table 4.19)

CASE NO.	H	A	Q	N	Q	DX	A-R** (2/3)	FROUD	IF
2+800	99.000	79.9	1.100	0.045	450.0	0.	85.142	0.1715E 01	0.5657E-01
2+700	94.156	88.0	1.102	0.045	450.0	-100.00	93.857	0.1557E 01	0.4655E-01
2+600	89.731	85.3	1.292	0.045	450.0	-100.00	101.180	0.1483E 01	0.4006E-01
2+500	84.310	72.9	1.259	0.045	450.0	-100.00	84.959	0.1758E 01	0.5681E-01
2+400	79.227	72.2	1.547	0.045	450.0	-100.00	96.530	0.1601E 01	0.4401E-01
2+300	71.624	78.0	1.631	0.045	450.0	-200.00	108.023	0.1444E 01	0.3514E-01
2+200	67.531	73.4	1.593	0.045	450.0	-100.00	100.115	0.1552E 01	0.4091E-01
2+100	64.348	78.5	1.863	0.045	450.0	-100.00	119.527	0.1342E 01	0.2904E-01
1+900	61.704	77.5	2.265	0.045	450.0	-100.00	133.722	0.1232E 01	0.2293E-01
1+800	58.167	71.2	1.674	0.045	450.0	-100.00	100.303	0.1562E 01	0.4076E-01
1+700	54.414	70.5	1.968	0.045	450.0	-100.00	110.728	0.1453E 01	0.3345E-01
1+600	50.976	77.1	1.429	0.045	450.0	-100.00	97.847	0.1559E 01	0.4283E-01
1+500	46.763	75.5	1.559	0.045	450.0	-100.00	101.514	0.1525E 01	0.3979E-01
1+400	39.655	82.9	1.501	0.045	450.0	-200.00	108.725	0.1415E 01	0.3469E-01
1+300	34.358	97.1	1.628	0.045	450.0	-200.00	134.299	0.1161E 01	0.2274E-01
1+200	31.082	85.1	1.417	0.045	450.0	-100.00	107.404	0.1418E 01	0.3555E-01
0+900	29.613	111.8	1.655	0.045	450.0	-100.00	156.371	0.1000E 01	0.1677E-01
0+800	24.953	91.3	1.646	0.045	450.0	-200.00	127.313	0.1227E 01	0.2530E-01
0+700	22.534	92.3	1.705	0.045	450.0	-100.00	131.703	0.1193E 01	0.2364E-01
0+600	19.241	77.9	1.774	0.045	450.0	-100.00	114.152	0.1386E 01	0.3147E-01
0+500	16.860	95.9	1.385	0.045	450.0	-100.00	119.150	0.1274E 01	0.2888E-01
0+400	15.811	114.7	1.573	0.045	450.0	-100.00	155.092	0.1000E 01	0.1705E-01
0+300	13.488	101.1	1.452	0.045	450.0	-100.00	129.564	0.1181E 01	0.2443E-01
0+200	9.779	77.3	1.692	0.045	450.0	-100.00	109.799	0.1429E 01	0.3401E-01

CASE NO.	H	A	R	N	Q	DX	A-R** (2/3)	FROUD	IE
2+800	99.100	87.4	1.185	0.045	500.0	0.	97.805	0.1680E 01	0.5292E-01
2+700	94.214	92.6	1.152	0.045	500.0	-100.00	101.506	0.1606E 01	0.4885E-01
2+600	89.840	92.3	1.385	0.045	500.0	-100.00	114.726	0.1470E 01	0.3846E-01
2+500	84.396	77.8	1.334	0.045	500.0	-100.00	94.295	0.1777E 01	0.5694E-01
2+400	79.335	77.2	1.650	0.045	500.0	-100.00	107.786	0.1611E 01	0.4358E-01
2+300	71.728	82.8	1.727	0.045	500.0	-200.00	119.267	0.1467E 01	0.3559E-01
2+200	67.695	78.5	1.699	0.045	500.0	-100.00	111.836	0.1560E 01	0.4048E-01
2+100	64.472	83.5	1.975	0.045	500.0	-100.00	131.539	0.1360E 01	0.2926E-01
1+900	61.987	83.4	2.423	0.045	500.0	-100.00	150.529	0.1230E 01	0.2234E-01
1+800	58.284	76.1	1.748	0.045	500.0	-100.00	110.410	0.1588E 01	0.4153E-01
1+700	54.568	75.9	2.103	0.045	500.0	-100.00	124.607	0.1451E 01	0.3260E-01
1+600	51.058	81.5	1.507	0.045	500.0	-100.00	107.166	0.1596E 01	0.4408E-01
1+500	46.875	81.0	1.671	0.045	500.0	-100.00	113.991	0.1526E 01	0.3896E-01
1+400	39.742	87.7	1.587	0.045	500.0	-200.00	119.348	0.1445E 01	0.3554E-01
1+300	34.473	103.9	1.742	0.045	500.0	-200.00	150.389	0.1163E 01	0.2233E-01
1+200	31.176	90.8	1.509	0.045	500.0	-100.00	119.431	0.1432E 01	0.3549E-01
1+100	29.734	119.9	1.775	0.045	500.0	-100.00	175.757	0.1000E 01	0.1639E-01
0+900	25.068	97.6	1.745	0.045	500.0	-200.00	141.443	0.1239E 01	0.2530E-01
0+800	22.662	99.6	1.762	0.045	500.0	-100.00	145.313	0.1208E 01	0.2397E-01
0+700	19.381	84.0	1.914	0.045	500.0	-100.00	129.523	0.1374E 01	0.3018E-01
0+600	16.930	100.6	1.437	0.045	500.0	-100.00	128.097	0.1325E 01	0.3083E-01
0+500	15.937	123.6	1.670	0.045	500.0	-100.00	174.048	0.1000E 01	0.1671E-01
0+400	13.594	108.9	1.501	0.045	500.0	-100.00	142.746	0.1197E 01	0.2484E-01
0+300	9.930	84.1	1.813	0.045	500.0	-100.00	124.994	0.1411E 01	0.3240E-01

Table 4.20 Calculation of Sediment Load

Return Period	Item	Main Yawa River Downstream from Confluence with Pawa-Burabod River			Main Yawa River upstream from Confluence with Pawa-Burabod River		
		Sta.1+000	Sta.2+000	Average	Sta.3+000	Sta.4+000	Average
1.01 Year	Q (m ³ /s)	170	170		140	140	
	R (m)	1.7	1.8		1.3	1.3	
	I	1/280	1/210		1/210	1/210	
	U* (m/s)	0.24	0.29		0.25	0.25	
	T (m)	48	38		40	52	
	Q _s (m ³ /s)	0.29	0.36	0.3	0.17	0.22	0.2
	Q _s /Qx100	0.17	0.21	0.2	0.12	0.16	0.1
1.5 Year	Q	350	350		270	270	
	R	2.7	2.8		1.8	1.8	
	I	1/280	1/210		1/210	1/210	
	U*	0.31	0.36		0.29	0.29	
	T	51	42		42	52	
	Q _s	0.65	1.20	0.9	0.40	0.49	0.4
	Q _s /Qx100	0.19	0.35	0.3	0.15	0.18	0.2
5 Year	Q	630	630		490	490	
	R	3.8	3.8		2.7	2.5	
	I	1/280	1/210		1/210	1/210	
	U*	0.36	0.42		0.35	0.34	
	T	53	43		45	53	
	Q _s	1.58	2.63	2.1	1.17	1.14	1.2
	Q _s /Qx100	0.25	0.42	0.3	0.24	0.23	0.2
10 Year	Q	790	790		600	600	
	R	4.0	4.3		2.9	2.7	
	I	1/280	1/210		1/210	1/210	
	U*	0.37	0.45		0.37	0.35	
	T	53	43		46	53	
	Q _s	1.80	3.59	2.7	1.43	1.38	1.4
	Q _s /Qx100	0.23	0.46	0.3	0.24	0.23	0.2
30 Year	Q	1,070	1,070		820	820	
	R	4.9	5.0		3.3	3.5	
	I	1/280	1/210		1/210	1/210	
	U*	0.41	0.48		0.39	0.40	
	T	53	43		48	53	
	Q _s	2.98	5.23	4.1	2.07	2.64	2.4
	Q _s /Qx100	0.28	0.48	0.4	0.25	0.32	0.3
50 Year	Q	1,220	1,220		930	930	
	R	5.3	5.3		3.6	3.8	
	I	1/280	1/210		1/210	1/210	
	U*	0.43	0.50		0.41	0.42	
	T	53	43		50	53	
	Q _s	3.63	6.05	4.8	2.49	3.24	2.9
	Q _s /Qx100	0.30	0.49	0.4	0.27	0.35	0.3

APPENDIX II

CONSTRUCTION PLAN AND SCHEDULE

APPENDIX II - CONSTRUCTION PLAN AND SCHEDULE

TABLE OF CONTENTS

	Page
1. PREAMBLE	II-1
2. PRINCIPAL FEATURES OF STRUCTURES	
2.1 The Kind of Works and Main Structures	II-1
3. CONSTRUCTION TIME SCHEDULE	II-3
4. BASIC CONDITIONS	
4.1 Construction Time Target	II-4
4.2 Workable Days and Hours for the Construction Works	II-4
4.3 Coefficient of Earth Volume Conversion	II-5
4.4 Hourly Production Rate of Construction Equipment	II-5
5. PREPARATORY WORKS	
5.1 Access Road	II-5
5.2 Temporary Buildings	II-6
5.3 Power Supply System	II-7
5.4 Water Supply System	II-7
5.5 Cement Supply	II-8
5.6 Aggregate Supply	II-8
5.7 Batching and Mixing Plant	II-8
6. CONSTRUCTION METHOD	
6.1 Sabo Dam	II-9
6.1.1 General	II-9
6.1.2 Major Work Quantities	II-10
6.1.3 Main Dam	II-10
(1) Earthwork	II-10
(2) Concrete Works	II-11
6.1.4 Sub Dam	II-12

	Page
6.2 Spur Dike	II-12
6.2.1 General	II-12
6.2.2 Major Work Quantities	II-13
6.2.3 Construction Method	II-13
6.3 Levee	II-14
6.3.1 General	II-14
6.3.2 Major Work Quantities	II-15
6.3.3 Construction Method	II-15
(1) Earthwork	II-16
(2) Related Structures and Wet Masonry	II-16
(3) Cribwork	II-16
6.4 Groundsill	II-17
6.4.1 General	II-17
6.4.2 Major Work Quantities	II-17
6.4.3 Construction Method	II-18
6.5 Irrigation Intake	II-18
7. MAIN CONSTRUCTION EQUIPMENT	II-18

ANNEX

Hourly Production Rate of Construction Equipment

1. PREAMBLE

This is a report on construction planning and schedule for the Sabo facilities to be constructed in the Pawa-Burabod river, a tributary of the Yawa river which is located in a south-eastern slope of the Mayon Volcano near Legagpi City. The Pawa-Burabod river is taken up as a site (river) subject to the detailed design for the Mayon Volcano Sabo and Flood Control Project in accordance with the mutual agreement between TFFCRA and the STUDY TEAM.

The Sabo facilities herein subject to the formulation of planning and schedule comprise a Sabo dam, two spur dikes and channel works involving levee, cribwork, ground-sill, and irrigation intake.

All the above structures construction is herein referred to as the Project all inclusive.

2. PRINCIPAL FEATURES OF STRUCTURES

The construction works include a Sabo dam with sub-dam, two spur dikes, levees, groundsills and an irrigation intake. The Sabo dam is located at El. 400.00 meters and the two spur dikes are at El. 190.00 meters approximately. The levees are located in the reaches from El. 100.00 meters near the Bonga village to the confluence of the Yawa river.

2.1 The Kind of Works and Main Structures

The kind of works and main structures are summarized below:

Sabo Dam No. 1

(1) Main Dam

Type	Concrete gravity
Height of overflow section :	10.00 m dam

Crest length of dam	79.50 m
Crest elevation of overflow section	398.55 m
Dam volume	5,750 cu.m.

(2) Sub-Dam

Type	Concrete gravity dam
Height of overflow section	5.00 m
Crest length of dam	57.50 m
Crest elevation of overflow section	391.80 m
Dam volume	1,420 cu.m.

Spur Dike

(1) Spur Dike No. 1

Type	Embankment protected by wet masonry
Length	200 m
Embankment volume	1,720 cu.m.
Slope	1:0.7
Wet masonry	2,290 sq.m.

(2) Spur Dike No. 2

Type	Embankment protected by wet masonry
Length	162 m
Embankment volume	1,130 cu.m.
Slope	1:0.7
Wet masonry	1,720 sq.m.

Levees

Type	Embankment protected by wet masonry on the river side
Levee length	3,956 m
Embankment volume	62,800 cu.m.
Wet masonry	32,380 sq.m.

Crib work	6,993 nos.
<u>Groundsill</u>	
(1) Type-A	
Type	Timber log crib
Crib work	970 nos.
(2) Type-B	
Type	Cross type concrete block
Crib work	305 nos.
<u>Irrigation Intake</u>	L.S.

3. CONSTRUCTION TIME SCHEDULE

All the construction works are assumed to be commenced from August 1980, and will be completed by July 1985 through a period of five years. The date of commencement is assumed to be required four months for preparation of tendering and evaluation after detail design completed.

Construction works will be commenced at first from the construction of the access road which will be completed within the period of two months from the beginning of August 1980.

Earthwork of the Sabo dam and levee is to be commenced from the beginning of November 1980, after providing construction facilities.

Concrete works of the Sabo dam including main dam and sub-dam are to be started immediately after the excavation is completed, and are to be completed by late February 1982 within the period of fourteen months.

Since the spur dikes are located near the levee work site, the construction thereof is to be performed in parallel work each other, considering convenience of the seasonable period during the levee construction period.

The levee works are to be started from the beginning of November 1980 and will be completed by late July 1985 through approximately five years.

The ground-sills and the irrigation intake are to be constructed at the seasonable period in the parallel work with levee.

More detailed information on the construction time schedule is shown in Fig. 3.1.

4. BASIC CONDITIONS

In working out the construction method and time schedule, basic conditions for construction planning are assumed as follows:

4.1 Construction Time Target

All the construction works will be completed by the end of July 1985 and construction period is to be five years.

Tender preparations for the construction works are assumed to be finished up by the end of July 1980.

4.2 Workable Days and Hours for the Construction Works

4.2.1 Workable Days

Generally, civil works will be affected by weather conditions, especially by rainfall. Workable days for the construction works are estimated as follows:

Calendar days	365 days per year
Unworkable days caused by rainfall more than 15mm/days	57 "
National holidays	12 "
Unworkable days caused by Labor Law	104 "

Unworkable days caused by rainfall are assumed to duplicate 50 percent of national holidays and unworkable days caused by Labor Law. Therefore workable days are estimated as follows:

Workable days

$$365 - 57 \times 0.5 - 12 - 104 = 221 \text{ days per year}$$

Average workable days per month

$$221 \text{ days} \div 12 \text{ month} = 18 \text{ days per month}$$

4.2.2 Daily Working Hours

Working hours a day are estimated 8 hours taking consideration of standard working hours in the Philippines. In this construction planning, working hours are estimated without considering overtime and 2-shift system.

4.3 Coefficient of Earth Volume Conversion

Coefficient of earth volume conversion is assumed in consideration of soil mechanical properties. Convertible coefficient is estimated as shown in Annex.

4.4 Hourly Production Rate of Construction Equipment

Hourly production rate of main construction equipments is estimated as shown in Annex.

5. PREPARATORY WORKS

5.1 Access Road

Existing road from Legaspi City reaches near the Bonga village.

Access roads to the site of levee, ground-sills, irrigation intake and spur dikes are planned in the

river bed. Construction cost of this road is to be considered to include in excavation of river bed.

After completion of levee, the crest can be used for the access road.

For the construction of the Sabo dam, access road is required to lead into the site of Sabo dam from the Bonga village. Route alignment of access road is to be located on the right side of Pawa-Burabod.

The feature of access road is shown as follows:

Distance	4,000 m
Road width	5.5 m
Road gradient	7.0 %

The access road is to be constructed by dozing of bulldozer and the pavement is not necessary for it.

5.2 Temporary Buildings

Buildings are classified into two groups; 1) construction buildings and 2) residential buildings. Both groups require the area as shown below:

Description	Area of Buildings
Construction buildings	
Office	100 sq.m.
Repair shop	50 sq.m.
Warehouse	30 sq.m.
Cement store	40 sq.m.
Magazine	10 sq.m.
Residential buildings	
Staff quarter	100 sq.m.
Labor camp	600 sq.m.

Residential buildings and office are to be tentatively located in the area near the Bonga village.

The land area required is estimated at 2,000 sq.m.

5.3 Power Supply System

All construction equipment and plants are planned to be of diesel engine and/or gasoline engine driven type except portable batching plant for sabo dam construction.

Electric supply is to be limited to the temporary building, and batching plant.

In whole construction period, portable generators will be required for the execution of the works.

Power requirement: The total required capacity of construction plant and facilities including those for the government and contractor's quarter is to be decided as follows:

i) Portable batching plant	15 KW
ii) Repair shop	30 KW
iii) Quarter camp	30 KW

5.4 Water Supply System

Water supply is required for concrete works and life water. Life water for the office and residential quarter is required to deliver from Legaspi City. Construction water is available from the water seeping from riverbed near Bonga village.

Water required in the construction is as shown below:

Residential : Life water is assumed to be supplied from Legaspi City (15 cu.m./day)

Construction:

Concrete mixing	10 cu.m./day
Curing the concrete	6 cu.m./day
and others	

Construction water is pumped up by centrifugal pumps, transported by water tanker and stored in a water tank with a capacity for one day consumption.

5.5 Cement Supply

Cement is delivered from Legaspi City to the work site and is stocked in a cement store which has a capacity of about 3 to 7 days consumption. Considering concrete placing schedule, it is required to stock more than 1300 bags of cement.

5.6 Aggregate Supply

Aggregates both fine and coarse are supplied and purchased from river deposit. It is not necessary to provide crushing and screening plant.

Aggregates are stocked in the field close to batching and mixing plant.

5.7 Batching and Mixing Plant

Batching and mixing plant of Sabo dam is to be installed near the dam site area. Concrete placing schedule is planned, as follows:

Concrete volume	5,750 cu.m.
Average placing concrete a day	50 cu.m./day
Maximum placing concrete a day	75 cu.m./day

Therefore, considering the required output (75 cu.m./day) of the construction mixers and batching time (around 15 times)), it is necessary to provide the mixer with 0.75 cu.m. one component drum.

Placing concrete except for Sabo dam uses 0.2 cu.m. class light mixer. The light mixer is to be transferred to the other work site to meet the

requirements of works.

Area of batching and mixing plant including aggregates stock piles is to be required 500 sq.m.

6. CONSTRUCTION METHOD

Taking the construction time schedule and local circumstances into consideration, the construction method is worked out together with the selection of equipments. Especially, the construction method is planned in consideration of available materials and equipments in the Philippines.

6.1 Sabo Dam

6.1.1 General

The concrete gravity type Sabo dam is constructed across the Pawa-Burabod river. The dam consists of a main dam and a sub-dam.

The main dam is 10.00 m in height, the sub-dam is 5.00 m in height.

The main dam will be completed at the end of December 1981, through the concrete placing period of twelve months from early January 1981. The sub-dam will be carried out in the period of two months before the completion of the main dam for preventing the scouring at the downstream portion of the main dam.

Through the rainy season is the period from July to December, considering the rainfall data, it is possible to work in rainy season. Annual workable days for construction is estimated 221 days.

The dam foundation consists of deposit of sand and gravel, rubble and boulder. Right abutment com-

prises rock and left abutment comprises deposit.

Constructing the Sabo dam, special river diversion and care of river are not required and flood discharge in rainy season will be overflowed at the dam during construction.

Therefore, no work item of river diversion and care of river is involved in work quantity.

6.1.2 Major Work Quantity

Major work quantities for the dam works are as follows:

Works	Work Quantity
Earthwork (Dam Foundation)	
Excavation, common	11,600 cu.m
Excavation, rock	380 cu.m
Backfill	840 cu.m
Concrete	
Main dam	5,220 cu.m
Sub dam	1,170 cu.m
Backfill concrete	780 cu.m

6.1.3 Main Dam

(1) Earthwork

Prior to placing concrete, the excavation works of dam foundation will be started from the beginning of November 1980.

Common materials of abutment and riverbed are excavated by 21 ton class bulldozer and are loaded by 1.4 cu.m class tractor shovel into 6 ton dump truck to haul them to the spoil bank within the distance of 500 m.

Since rock excavation of right abutment amounts small quantity, it is performed drilling and blasting by hand with jackhammer.

Boulders are gathered by bulldozer. They are crushed by drilling and blasting if necessary and are removed to the deposit area out of riverbed.

Main construction equipments to be used for the works are listed as follows:

<u>Equipment</u>	<u>Type and Size</u>	<u>Numbers</u>
Bulldozer with ripper	21 ton	1
Bulldozer	11 ton	1
Tractor shovel	1.4 cu.m	2
Dump truck	6 ton	4
Air compressor	106 ps	1
Jackhammer	24 kg	3
Pickhammer	7 kg	6

(2) Concrete Works

Main dam includes four transverse joints and max. monolith (concrete block unit) width is 25.00 m. Considering the batching and mixing plant capacity, placing concrete in monolith is estimated at max. 75 cu.m/day. Therefore, main dam concrete requires one longitudinal joint in the early placing period for the construction. Joint grouting there is not necessary.

Placing height is planned to be 0.50 m/lift in considering capacity of batching and mixing plant, temperature control of concrete without cooling pipe, and suitability of construction method. Concrete is placed into unit of monolith under layer method.

Prior to place the concrete on rock and previous concrete, clearing of surface is to be required.

Concrete is to be mixed by portable batching and mixing plant, complete, with 0.75 cu.m one component drum. Concrete is to be placed into agitator truck of 1.7 cu.m and is transported to the spot of placing concrete of dam. Concrete is placed into concrete bucket with 0.80 to 1.00 cu.m and concrete bucket is to be handled into monolith by 20 ton truck crane.

During placing concrete, concrete is to be compacted by flexible internal vibrator of more than 60 mm diameter.

After placing concrete, curing concrete is to be required until placing fresh concrete. Curing is to be made by water and hemp clothes.

Main construction equipment to be used for the works are listed below:

Equipment	Type and Size	No.
Portable batching and mixing plant	0.75 cu.m x 1 completed unit excluding belt conveyor	1 set
Agitator truck	1.7 cu.m.	3
Truck crane	20 ton	1
Concrete bucket	0.8 - 1.0 cu.m	4
Concrete vibrator	60 mm. dia.	5

6.1.4 Sub Dam

The construction of sub dam is to be performed on the same process and method of main dam works.

6.2 Spur Dikes

6.2.1 General

Spur dikes are to be constructed as embankment protected by wet masonry and are formed to a gradient

of riverbed accompaniment. As shown on the Drawings, the crest elevation varies from upstream downwards. As shown on the construction time schedule, spur dike works are lapped with levee works.

6.2.2 Major Work Quantity

Major work quantities for the spur dikes are as follows:

Work	Work Quantity	
	Spur Dike No. 1	Spur Dike No. 2
Excavation, in common	3590 cu.m	4310 cu.m
Embankment	1720 cu.m	1130 cu.m
Backfilling cobble of masonry	1280 cu.m	790 cu.m
Riprap bedding	470 cu.m	380 cu.m
Backfill	1990 cu.m	1600 cu.m
Concrete	560 cu.m	690 cu.m
Wet masonry	2290 sq.m	1720 sq.m

6.2.3 Construction Method

Excavation under ground surface is to be performed by 21 ton class bulldozer and 0.6 cu.m class backhoe and is loaded by 1.4 cu.m class tractor shovel into 6 ton dump truck.

Embankment materials are to be the selected materials less than 20 cm dia. gathered from river deposit. The selected materials are transported at the work site and spreaded by 11 ton class bulldozer over the surface by 20 cm. thick compacted layer, and compacted by 3 to 4 ton vibratory roller with passing more than 4 times on material. At the embankment spot of adjacent cobble stone behind masonry, materials are compacted by rammer and tamper.

Then there seems not to have effect in compaction of the materials because of its dry condition yet,

the moisture content is to be again adjusted to secure the required content by spraying water through hose or water tanker over the materials.

Embankment is performed in parallel wet masonry works, because of slope is steep as shown drawings. Embankment and wet masonry are to be limited approximately 1.00 m high for construction speed and after finishing one layer, next embankment and wet masonry are to be started.

All works except excavation and embankment are performed by hand. Concrete is to be mixed by light mixer at work site, is transported by one-wheel concrete trucks and compacted by internal vibrator of 40 to 45 mm dia.

Rubble stones of wet masonry are to be supplied from river deposit in the Pawa-Burabod.

Main construction equipments to be used for the works are listed below:

Equipment	Type and Size	Numbers
Bulldozer	21 ton	1
Bulldozer	11 ton	1
Tractor shovel	1.4 cu.m	1
Dump truck	6 ton	1
Vibratory roller	3 to 4 ton	1
Rammer and tamper	80 to 100 kg	2
Light mixer	0.2 cu.m	2
Internal vibrator	40 to 45 mm	4

6.3 Levee

6.3.1 General

Levees are constructed on the both banks along the Pawa-Burabud river. The length of levees are

approximately 4 km from the confluence of the Yawa river toward sabo dam site. Levee height is about 2.0 to 2.1 m above the original riverbed and both slope gradient is 1 : 2.5.

Embankment surface is protected by wet masonry along the whole length of levee and at toe of embankment, three raw cribs are to be required along the levee to protect scouring caused by flood flow.

Levee is to be commenced from the beginning of November 1980 and will be completed at the end of June 1985. Levee, wet masonry and crib works are lapped with each others.

Geological conditions of riverbed in the area of construction of levee consists mainly of sand and gravel.

6.3.2 Major Work Quantity

Major work quantities for the levee and wet masonry are as follows:

<u>Work</u>	<u>Work Quantity</u>
Earthwork	
Excavation, common	87,900 cu.m
Embankment	62,800 cu.m
Backfill cobble stone	13,280 cu.m
Filling rubble in crib	14,150 cu.m
Backfill in crib	10,560 cu.m
Concrete	9,140 cu.m
Wet masonry	32,380 sq.m
Crib work	6,993 nos.

6.3.3 Construction Method

(1) Earthwork

Excavation and embankment of levee are to be ahead of wet masonry and crib works. Excavation underground surface and in the riverbed is to be performed by 21 ton class bulldozer and 0.6 cu.m class backhoe. Excavated materials are loaded by 1.4 cu.m class tractor shovel into 6t dump truck and are transported to the deposit area within 500 m. Boulders to be impossible to transport by dump trucks are gathered, removed and filled under proposed ground level of riverbed.

Embankment materials are to be the selected materials less than 20 cm dia. from river deposit. The method of embankment is similar with the construction of spur dike.

(2) Related Structures and Wet Masonry

After the excavation and embankment are completed for some ten meters long, gravel base is placed directly on the embankment slope by hand and foundation concrete and wet masonry works are conducted continuously. After the part of masonry works is completed, crib work will be commenced. All these works are constructed by hand.

Rubbles of wet masonry are to be supplied and transported by tractor shovel as selected materials from river deposit.

Concrete is to be mixed by light mixer at work site, is transported by one-wheel concrete trucks and compacted by internal vibrator of 40 to 45 mm dia.

(3) Crib Work

Crib work is to be commenced continuously after finished wet masonry portions. The cribs to be

furnished and installed in work site and rubbles are transported by tractor shovel and filled in the crib by hand. Crib materials are used coconut trunk supplied from coconut plants and equivalent to materials timber logs.

Main construction equipments to be used for the work are listed below:

Equipment	Type and Size	Numbers
Bulldozer	21 ton	1
Bulldozer	11 ton	1
Tractor shovel	1.4 ton	2
Dump truck	6 ton	4
Vibrating roller	3 to 4 ton	1
Rammer and tamper	80 to 100 kg	4
Light mixer	0.2 cu.m	3
Concrete vibrator	40 to 45 mm	10

6.4 Groundsill

6.4.1 General

Groundsills are to be provided in the riverbed at right angles to the levee. Groundsills involve two type ones, one is the timber log crib and the other is the cross type concrete block groundsill as shown on the Drawing, as type-A and type-B respectively.

The space of groundsills are to be classified approximately 100 m, 150 m and 300 m towards the upstream of Pawa Burabod from the confluence of Yawa river. The numbers of groundsill are eleven including two cross type concrete block groundsills.

6.4.2 Major Quantity

Major work quantities for the groundsills are

as follows:

Work	Work Quantity
Type - A	
Excavation, in common	3,180 cu.m
Backfill for groundsill	440 cu.m
Filling rubble in crib	1,960 cu.m
Crib work	970 nos.
Type - B	
Excavation, in common	1,170 cu.m
Backfill for groundsill	160 cu.m
Filling rubble in the	
space of concrete block	860 cu.m
Concrete (365 nos. block)	430 cu.m

6.4.3 Construction Method

The construction of groundsill is to be performed on the same process and method of levee and pavement works and it is to be planned as a part of levee and pavement works. All construction equipments are transported from other works.

6.5 Irrigation Intake

Irrigation intake is to be constructed near No. 7 groundsill. Earthwork for irrigation intake is included in the construction of levee and after completing the structure, embankment and backfilling are to be commenced by the same method of levee. Quantities of irrigation intake are shown in the Bill of Quantity.

7. MAIN CONSTRUCTION EQUIPMENTS

Main construction equipments to be used on this

project are summarized as follows:

Equipment	Type and Size	Nos.
Bulldozer	21 ton	2
Bulldozer	11 ton	2
Tractor shovel	1.4 cu.m	4
Backhoe	0.6 cu.m	2
Dump truck	6 ton	8
Track crane	20 ton	1
Vibratory roller	3 ton	1
Rammer and tamper	60 to 100 kg	8
Jackhammer	20 kg	5
Pick hammer	7 kg	10
Air compressor	10 cu.m/min.	1
Portable butchering and mixing plant	0.75 cu.m	1
Light mixer	0.2 cu. m	5
Agitator truck	1.7 cu.m	3
Concrete Vibrator	60 mm dia.	5
Concrete Vibrator	40 mm. dia.	20
Generator	15 KW	1
Generator	30 KW	2
Water pump	3.5 ps	4
Ordinary truck	6 ton	1

ANNEX

HOURLY PRODUCTION RATE OF CONSTRUCTION EQUIPMENT

1. The Foundation on the Calculation of Output

1.1 Formula of Output is shown below for each equipment, considering with the works and job-management factor.

1.2 Coefficient of Earth Volume Conversion

In the result of investigation of the site, excavating and embankment materials are classified into common and rock. Common material is defined to contain sand, gravel, stone and boulder. Rock material is defined to be the materials which requires drilling and blasting. Convertible coefficient is estimated as follows:

Coefficient Material	Bank Volume	Loose Volume	Compacted Volume
Common Material	1.00 (1.05)	1.15 (1.21)	0.95 (1.00)
Rock Material	1.00 (0.77)	1.60 (1.23)	1.30 (1.00)

1.3 Job-management Factor

Job-management factor is to be affected by weather conditions, working sites, materials, available equipments, skill of operators and so forth.

2. Bulldozer

2.1 Excavating and Gathering (Dozing)

$$Q = \frac{60 \times Q_1 \times E \times F}{C_m}$$

where; Q : Output per hour (cu.m/hr)

Q1 : Mouldboard capacity (cu.m.)
 E : Job-management factor
 F : Coefficient of Earth Volume Conversion
 Cm : Cycle time (min.)
 $Cm = 0.038 \times D + 0.33$
 D : Hauling Distance (m)

(1) Common Material, Bank Volume

	D	Cm	Q1	E	F	Q
	20	1.09	2.89	0.6	1/1.15	83
Bulldozer, 21t	30	1.47	2.89	0.6	1/1.15	62
	50	2.23	2.89	0.5	1/1.15	34

(2) Rock Material, Bank Volume

	D	Cm	Q1	E	F	Q
Bulldozer, 2HRP	20	1.09	2.89	0.5	1/1.60	50

(3) Common Material, Compacted Volume

	D	Cm	Q1	E	F	Q
Bulldozer, 21t	20	1.09	2.89	0.6	1/1.21	78

2.2 Spreading

$$Q = \frac{W \times V \times D \times E \times F}{N1}$$

where; Q : Output per hour (cu.m/hr)
 W : Effective Spreading width (m)
 V : Working speed (m/hr)
 D : Spreading depth (m)
 E : Job-management factor
 F : Coefficient of Earth Volume Conversion
 N1 : Number of spreading

(1) Common Material, Compacted Volume

	W	V	D	E	F	N1	Q
Bulldozer 11t	3.0	2000	0.3	0.7	1.0	6	210

2.3 Compacting

$$Q = \frac{V \times B2 \times E \times D \times F}{N}$$

where; Q : Output per hour (cu.m/hr)

B2 : Effective Compaction width (m)

E : Job-management factor

D : Compacted depth (m)

F : Coefficient of earth volume
conversion

N : Number of compaction

V : Working speed (m/hr)

(1) Common Material, Compacted Volume

	V	B2	E	D	F	N	Q
Bulldozer 11t	3000	0.32	0.7	0.3	1.0	6	34

3. Backhoe

$$Q = \frac{3600 \times Q2 \times E \times F}{Cm}$$

where; Q : Output per hour (cu.m/hr)

Q2 : Handling volume per cycle (cu.m)

Q2 = Q1 x B

Q1 : Bucket capacity (struck)

B : Coefficient of bucket

E : Job-management factor

F : Coefficient of earth volume conversion

Cm : Cycle Time (sec.)

		Q2	E	F	Cm	Q
Backhoe	0.2m ³	0.16	0.6	1/1.15	36	8
Backhoe	0.4m ³	0.32	0.6	1/1.15	36	17
Backhoe	0.6m ³	0.48	0.6	1/1.15	36	25

4. Tractor Shovel

$$Q = \frac{60 \times Q2 \times E \times F}{Cm}$$

where; Q : Output per hour (cu.m/hr)

Q2 : Handling volume per cycle (cu.m.)

$$Q2 = Q1 \times B$$

Q1 : Bucket capacity (heaped)

B : Coefficient of bucket

E : Job-management factor

F : Coefficient of earth volume conversion

Cm : Cycle time, loading and spotting (min.)

(1) Tractor Shovel, 1.4m³ Class

	Q2	E	F	Cm	Q
Common, Bank	1.05	0.75	1/1.15	0.93	44
Common, Compacted	1.05	0.75	1/1.24	0.93	42
Rock, Bank	0.91	0.6	1/1.60	0.93	22
Rock, Compacted	0.91	0.6	1/1.23	0.93	29

(2) Tractor Shovel, 1.8m³ Class

	Q2	E	F	Cm	Q
Common, Bank	1.35	0.75	1/1.15	0.93	57
Common, Compacted	1.35	0.75	1/1.21	0.93	54
Rock, Bank	1.17	0.6	1/1.60	0.93	28
Rock, Compacted	1.17	0.6	1/1.23	0.93	37

5. Dump Truck

$$Q = \frac{60 \times Q2 \times E \times F}{Cm}$$

Where, Q : Output per hour (cu.m/hr)
 Q2 : Loading volume per cycle (cu.m)
 E : Job-management Factor
 F : Coefficient of Earth Volume
 Conversion
 Cm : Cycle Time (min)

(1) Cycle Time

$$Cmt = \frac{Cms \times n}{60 \times Es} + \frac{D}{V1} + \frac{D}{V2} + t$$

Where, Cmt : Cycle time of dump truck
 Cms : Cycle time of loading equipment
 n : Number of cycle of loading - equipment for one unit dump truck
 Es : Job-management factor of loading equipment
 D : Hauling Distance (m)
 V1 : Hauling Speed (m/min)
 V2 : Returning Speed (m/min)
 t : Dumping and spotting time (min)

Distance	V1	V2	D/V1	D/V2	$\frac{Cms \cdot n}{60 \cdot Es}$	t	Cmt
200	166	166	1.2	1.2	4.8	1.7	8.9
300	166	250	1.8	1.2	4.8	1.7	9.5
400	250	250	1.6	1.6	4.8	1.7	9.7
500	250	250	2.0	2.0	4.8	1.7	10.5
1000	333	417	3.0	2.4	4.8	1.7	11.9
2000	333	500	6.0	4.0	4.8	1.7	16.5

(2) Output per hour

Q2 : Loading volume per cycle

Dump Truck	6t	4.0 cu. m
"	8t	5.3 cu. m
"	10t	6.7 cu. m

E : Job-Management Factor, E = 0.85

1) Dump Truck, 6t

	200	300	400	500	1000	2000	F
Common, Bank	19.9	18.7	18.3	16.9	14.9	10.8	1/1.15
Common, Compacted	18.9	17.7	17.4	16.1	14.2	10.2	1/1.21
Rock, Bank	14.3	13.4	13.1	12.1	10.7	7.7	1/1.6
Rock, Compacted	18.6	17.5	17.1	15.8	13.9	10.4	1/1.23

ii) Dump Truck, 8t

	200	300	400	500	1000	2000
Common, Bank	26.4	24.7	24.2	22.4	19.7	14.3
Common, Compacted	25.0	23.4	23.1	21.3	18.8	13.5
Rock, Bank	18.9	17.7	17.4	16.0	14.2	10.2
Rock, Compacted	24.6	23.2	22.7	20.9	18.4	13.4

iii) Dump Truck 10t

	200	300	400	500	1000	2000
Common, Bank	33.3	31.3	30.7	28.3	25.0	18.1
Common, Compacted	31.7	29.6	29.1	27.0	23.8	17.1
Rock, Bank	24.0	22.4	21.9	20.3	17.9	12.9
Rock, Compacted	31.2	29.3	28.6	26.5	23.3	16.9

6. Vibrating Roller

$$Q = \frac{V \times B^2 \times E \times D \times F}{N}$$

Where, Q : Compacted Volume per hour (cu.m/Hr)

V : Working Speed (m/Hr)

E : Job-management Factor


D : Compacted depth (m)

F : Coefficient of earth volume conversion

N : Number of Compaction

	V	B ²	E	D	F	N	Q
Vibrating 3-4t	2000	0.90	0.6	0.30	1.0	6	54

Fig. 3.1 CONSTRUCTION TIME SCHEDULE



APPENDIX III

ESTIMATE OF CONSTRUCTION COST

APPENDIX-III ESTIMATE OF CONSTRUCTION COST

TABLE OF CONTENTS

	Page
1. GENERAL	III-1
2. CONTRACT COST (DIRECT COST)	
2.1 Material Cost	III-1
2.2 Labor Cost	III-2
2.3 Equipment Cost	III-2
2.4 Breakdown and Unit Price	III-3
2.5 Contract Cost (Direct Cost)	III-4
3. INDIRECT COST	
3.1 Engineering Cost	III-5
3.2 Administration Cost	III-5
3.3 Contingency	III-5
4. CONSTRUCTION COST	III-6
5. DISBURSEMENT SCHEDULE	III-8

ANNEX I Priced Bill of Quantities

ANNEX II Breakdown of Unit Price

1. GENERAL

Construction cost of the construction of Sabo facilities of the Pawa-Burabod river, a tributary of Yawa river, under the MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT is estimated in considering local conditions of the Philippines, as available equipments and materials, suitability of construction method, working rules, etc.

Construction cost comprises Contract Cost and Indirect Cost. Contract Cost includes direct cost of material, labor, PD#390 and equipment, and contingencies, Contractor's profit and surcharges. Indirect cost includes Engineering cost, Administration cost and contingencies of physical and price escalation.

Contract cost and indirect cost are estimated on the basis of the Government estimate procedure and all unit price and summary cost are in local currency, pesos and centavos.

2. CONTRACT COST (DIRECT COST)

2.1 Material Cost

Main material cost is presented in the table below. It is based on the price in Albay on November 1979. The material which is not available in Albay is estimated on the basis of the price in Manila.

Material cost estimated is to be purchase price at the Project Site, including transportation cost.

<u>Material Cost</u>		
<u>Material</u>	<u>Unit</u>	<u>Local Currency (PESO)</u>
Gasoline	liter	2.82
Light Oil	liter	2.68
Lubricant	liter	10.04
Grease	kg	19.82
Cement, Portland	ton	700.00
Aggregate, Fine	cu.m	25.00
Aggregate, Coarse	cu.m	35.00
Reinforcement bar	ton	4,300.00
Timber	cu.m	1,101.70
Plywood	cu.m	2,648.00
Dynamite	kg	50.00

2.2 Labor Cost

Direct daily wages of local labor applied to the construction cost estimates are presented in the table below. Labor wages estimated are based on the price in Albay on November 1979.

The labor cost estimated does not include any daily overtime and overtime for Sunday and Holiday. Working days a week and working hours a day are assumed five days and eight hours respectively according to Labor Law in the Philippines.

Daily Wages of Local Labor

<u>Classification</u>	<u>Wage Rate (PESO)</u>
Foreman	24.84
Mechanic	17.55
Electrician	17.25
Operator, heavy equipment	23.65
Operator, light equipment	19.36
Assistant operator	17.55
Driver, dump truck	19.36
Carpenter	17.55
Mason	17.55
Concrete worker	16.25
Reinforcement worker	16.25
Skilled labor	17.55
Common labor	16.25

2.3 Equipment Cost

Equipment cost is estimated on the basis of depreciation cost, repair cost and administrative cost in considering daily rental rate in the Philippines. Equipment cost is not included in the material cost and labor cost respectively.

Major equipment cost is estimated as hourly cost and daily cost, and is listed in the table below.

Construction Equipment Cost

<u>Description</u>	<u>Hourly Cost</u> (PESO/Hr. or Day)
Bulldozer, 21 ton	350 P/Hr
Bulldozer, 11 ton	160 P/Hr
Backhoe, 0.6 cu.m	190 P/Hr
Tractor Shovel, 1.4 cu.m	110 P/Hr
Dump Truck, 6 ton	80 P/Hr
Track Crane, 15 to 20 ton	230 P/Hr
Portable Batch Plant, 0.75 cu.m	210 P/Hr
Concrete Mixer, 0.2 cu.m	200 P/Day
Hand Hammer, 20 kg	30 P/Day
Pick Hammer, 7 kg	10 P/Day
Air Compressor, 7 cu.m/min	320 P/Day
Vibratory Roller, 3 ton to 4 ton	80 P/Hr
Truck Mixer, 1.7 cu.m	60 P/Hr
Tamper and Rammer, 60 to 100 kg	50 P/Hr

2.4 Breakdown and Unit Price

Unit price is estimated as the direct cost as shown in the report of ANNEX II Breakdown of Unit Price, and the Unit Price comprises total cost of materials (a), labor (b), PD#390 (c) and equipment expense (d).

The cost of PD#390 in the Breakdown of Unit Price includes the cost of Leaves, Medical and Insurance of Social Security System for employed labor, and is the cost of 4.5 percent of labor cost (b) as specified Presidential Decree in the Philippines.

Unit price of each item for civil works presented in the Bill of Quantities is estimated in accordance with the said composition, condition and the proposed construction method presented in the report of Appendix II.

2.5 Contract Cost (Direct Cost)

Contract Cost (Direct cost) in the Proposed Schedule is presented below:

- 1) Direct Cost (Estimated Cost)

Section - 1	General
Section - 2	Sabo Dam
Section - 3	Spur Dike No.1
Section - 4	Spur Dike No.2
Section - 5	Levee
Section - 6	Groundsill, Type A
Section - 7	Groundsill, Type B
- 2) Contingency
- 3) Contractor's Profit
- 4) Surcharges

Estimated contract cost is shown in the table of Estimated Construction Cost and it is estimated on the basis of the Government estimate procedure as follows:

Contingency is the cost of five percent (5 %) of the direct cost

Contractor's profit is the cost of ten percent (10 %) of the sum of direct cost plus contingencies.

This percentage is based on the Memorandum on the 1st of April, 1973, as allowable Percentage of Contractor's Profit.

Surcharges are the cost of five percent (5 %) of the sum of direct cost and contingencies.

3. INDIRECT COST

Indirect cost for the Government comprises Engineering Cost, Administration Cost and Contingencies. These indirect costs are shown in the table of Estimated Construction Cost.

3.1 Engineering Cost

Engineering cost is the cost of 353,000 ₦ plus two percent of the contract cost. This engineering cost is estimated on the basis of the Memorandum on the 1st of April, 1973 of a new schedule of engineering surcharges for all Public Works Project.

3.2 Administration Cost

Administration cost is the cost of five percent (5 %) of the contract cost.

3.3 Contingency

The contingency is provided to cope with unforeseen physical conditions and price escalation due to inflation.

The rate of physical contingency varies with conditions of construction and the physical contingency is influenced by the following factors:

- 1) Physical conditions of construction site
- 2) Technically unknown difficulty
- 3) Exactness of investigation and study undertaken
- 4) Exactness and base of cost estimate
- 5) Exactness of work quantity calculation
- 6) Variation in design
- 7) Occurrence of unforeseen condition due to natural phenomena
- 8) Exactness of estimate of construction period

In view of the above conditions, the physical contingency is estimated to be ten percent (10 %) of the contract cost.

The rate of price escalation contingency varies with inflation in the Philippines. On the assumption that the annual escalation rate is seven percent and the cost of price escalation is basis of disbursement schedule, the price contingency is estimated in the table of Disbursement Schedule.

4. CONSTRUCTION COST

The summary of the estimated construction cost is presented below. The priced bill of quantities is as shown ANNEX I.

<u>Estimated Construction Cost</u>		
<u>Description</u>		<u>Cost (PESO)</u>
1. Contract Cost		
1) Direct Cost (Estimated Cost)		
Section-1 General		2,088,000.00
Section-2 Sabo dam		2,222,000.00
Section-3 Spur dike No.1		857,000.00
Section-4 Spur dike No.2		734,000.00
Section-5 Levee		9,221,000.00
Section-6 Groundsill, Type A		271,000.00
Section-7 Groundsill, Type B		269,000.00
Section-8 Irrigation intake		18,000.00
Sub-total (1)		15,680,000.00
2) Contingency (5% of sub-total (1))		784,000.00
Sub-total (2)		16,464,000.00
3) Contractor's Profit (10% of sub-total (2))		1,646,000.00
4) Surcharges (5% of sub-total (2))		823,000.00
<u>Contract Cost</u>		<u>18,933,000.00</u>
2. Engineering Cost		732,000.00
3. Administration Cost		947,000.00
4. Contingency (Physical and escalation)		6,688,000.00
<u>Total Construction Cost</u>		<u>27,300,000.00</u>

Engineering Cost and Contractor's Profit

December 15, 1976

MEMORANDUM For:
The Assistant Director
All Chiefs of Division
All Regional Supervisors
All Public Works District and
City Engineers
This Bureau

Effective April 1, 1973, a new schedule of engineering surcharges for all Public Works projects will be adopted for the observance and compliance of all concerned as follows:

Estimate Cost of Projects	Engineering Surcharges
₱50.00 and below	10 of Estimated Cost
Over ₱50,000.00 up to ₱100,000.00	₱5,000 plus (0.08) (Estimated Cost over ₱50,000)
Over ₱100,000.00 up to ₱500,000.00	₱9,000 plus (0.06) (Estimated Cost over ₱100,000)
Over ₱500,000.00 up to ₱1,000,000.00	₱33,000 plus (0.05) (Estimated Cost over ₱500,000)
Over ₱1.0 M. up to ₱2.0 M.	₱58,000 plus (0.04) (Estimated Cost over ₱2.0 M.)
Over ₱2.0 M. up to ₱5.0 M.	₱98,000 plus (0.035) (Estimated Cost over ₱2.0 M.)
Over ₱5.0 M. up to ₱10.0 M.	₱203,000 plus (0.03) (Estimated Cost over ₱5.01 M.)
Over ₱10.0 M.	₱353,000 plus (0.02) (Estimated Cost over ₱10.0 M.)

This supersedes the memorandum of this Office dated
March 19, 1973

(SGD.) DESIDERIO ANOLIN
Director of Public Works

Allowable Percentage of Contractor's Profit

Not exceeding ₱100,000.00	15%
Over ₱100,000.00 but not exceeding ₱300,000.00	14%
Over ₱300,000.00 but not exceeding ₱500,000.00	13%
Over ₱500,000.00 but not exceeding ₱700,000.00	12%
Over ₱700,000.00 but not exceeding ₱900,000.00	11%
Over ₱900,000.00	10%

5. DISBURSEMENT SCHEDULE

The disbursement schedule is estimated as shown below based on the construction cost and the construction time schedule previously presented.

Disbursement Schedule

<u>Description</u>	(Unit in 1,000 ₪)					
	<u>1980</u>	<u>1981</u>	<u>1982</u>	<u>1983</u>	<u>1984</u>	<u>Total</u>
1. Contract Cost						
1) Direct cost						
General	2,088					2,088
Sabo dam		2,222				2,222
Spur dike, No.1			857			857
Spur dike, No.2			734			734
Levee	332	1,974	1,974	1,974	1,974	9,221
Groundsill, Type A			21	125	125	271
Groundsill, Type B			269			269
Irrigation intake			18			18
2) Contingency	121	210	193	105	105	784
3) Contractor's profit	254	441	406	220	220	1,646
4) Surcharges	127	220	204	110	110	823
2. Engineering Cost	113	196	181	98	98	732
3. Administration Cost	146	253	234	127	127	947
4. Contingency						
1) Physical	293	508	469	254	254	1,899
2) Price escalation	223	799	1,146	857	1,111	4,789
Total	<u>3,697</u>	<u>6,823</u>	<u>6,706</u>	<u>3,870</u>	<u>4,124</u>	<u>27,300</u>

ANNEX I

Priced Bill of Quantities

BILL OF QUANTITIES

SECTION - 1

GENERAL

Item No.	Description	Quantity	Unit	Rate	Amount	
					PESO	: CEN
1.01	Access road for Sabo dam	Lump	Sum		237,700.00	
1.02	Temporary Buildings	Lump	Sum		319,000.00	
1.03	Electric Supply	Lump	Sum		713,200.00	
1.04	Water Supply	Lump	Sum		647,800.00	
1.05	Geological Investigation, Check Survey and Redesign	Lump	Sum		170,000.00	
Grand Total to General					2,087,700.00	

SECTION - 2

SABO DAM (Main and Sub Dam)

Item No.	Description	Quantity	Unit	Rate	Amount	
					PESO	: CEN
<u>Earthwork</u>						
2.01	Excavation, in common, in foundation of main dam	7,300	cu.m	16.57	120,961.00	
2.02	Excavation, in common, in foundation of sub dam	4,300	cu.m	16.57	71,251.00	
2.03	Excavation, in rock, in foundation of sub-dam	250	cu.m	70.14	17,535.00	
2.04	Excavation, in rock, in foundation of main dam	130	cu.m	70.14	9,118.20	
2.05	Backfill for main dam and sub dam	840	cu.m	18.94	15,909.60	

Item No.	Description	Quantity	Unit	Rate	Amount	
					PESO	: CEN
<u>Concrete and Formwork</u>						
2.06	Concrete, type A, in main dam	320	cu.m	296.72	94,950.40	
2.07	Concrete, type A, in sub dam	230	cu.m	296.72	68,245.60	
2.08	Rubble concrete, in main dam	4,900	cu.m	237.96	1,166,004.00	
2.09	Rubble concrete, in sub dam	940	cu.m	237.96	223,682.40	
2.10	Backfill concrete, type B, in main dam	530	cu.m	258.35	136,925.50	
2.11	Backfill concrete, type B, in sub dam	250	cu.m	258.35	64,587.50	
2.12	Form work, F2 finish, in main dam	1,400	sq.m	79.85	111,790.00	
2.13	Form work, F2 finish, in sub dam	420	sq.m	79.85	33,537.00	
2.14	Form work, F1 finish, in main dam	1,400	sq.m	36.76	51,464.00	
2.15	Form work, F1 finish, in sub dam	350	sq.m	36.76	12,866.00	
<u>Miscellaneous</u>						
2.16	Furnishing and placing 300 mm dia concrete drain pipe in main dam	11	lin.m	302.76	3,330.36	
2.17	Furnishing and installing water stop in main dam	40	lin.m	94.19	3,767.60	
2.18	Furnishing and placing joint filler in main dam	220	sq.m	60.30	13,266.00	
2.19	Furnishing and placing joint filler in sub dam	40	sq.m	60.30	2,412.00	
Grand Total to Sabo Dam					2,221,603.16	

SECTION - 3
SPUR DIKE NO. 1

Item No.	Description	Quantity	Unit	Rate	Amount	
					PESO	: CEN
<u>Earthwork</u>						
3.01	Excavation, in common, at the toe of embankment	3,590	cu.m	16.57	59,486.30	
3.02	Embankment for spur dike	1,720	cu.m	21.80	37,496.00	
3.03	Backfilling cobble stone behind wet masonry	1,280	cu.m	41.49	53,107.20	
3.04	Riprap bedding	470	cu.m	30.60	14,382.00	
3.05	Backfill under ground surface	1,990	cu.m	18.94	37,690.60	
<u>Concrete and Formwork</u>						
3.06	Concrete, type B, in foot protection block	110	cu.m	235.05	25,855.50	
3.07	Concrete, type B, at crest of embankment	260	cu.m	235.05	61,113.00	
3.08	Concrete, type B, in foundation of wet masonry	190	cu.m	235.05	44,659.50	
3.09	Formwork F1 finish, in foot protection block	440	sq.m	36.76	16,174.40	
3.10	Formwork F1 finish, in foundation of wet masonry	670	sq.m	36.76	24,629.20	
3.11	Formwork F1 finish for concrete in joint	100	sq.m	36.76	3,676.00	
3.12	Formwork F1 finish for concrete in backfilling	2,290	sq.m	36.76	84,180.40	
<u>Wet Masonry</u>						
3.13	Backfill Concrete, type B, behind wet masonry	920	cu.m	235.05	216,246.00	
3.14	Wet-rubble masonry	2,290	sq.m	52.24	119,629.60	
3.15	Inter locking mortar in wet masonry	120	cu.m	429.02	51,482.40	
3.16	Joint filler	100	sq.m	60.30	6,030.00	
3.17	Reinforcing bar, 16mm, dia	0.21	5on	4,799.48	1,007.89	
Ground Total to Spur Dike No.1					856,845.99	

SECTION - 4
SPUR DIKE NO. 2

Item No.	Description	Quantity	Unit	Rate	Amount	
					PESO	: CEN
<u>Earthwork</u>						
4.01	Excavation, in common, at the toe of embankment	4,310	cu.m	16.57	71,416.70	
4.02	Embankment for spur dike	1,130	cu.m	21.80	24,634.00	
4.03	Riprap bedding	380	cu.m	30.60	11,628.00	
4.04	Backfill under ground surface	1,600	cu.m	18.94	30,304.00	
4.05	Backfill cobble stone behind wet masonry	790	cu.m	41.49	32,777.10	
<u>Concrete and Formwork</u>						
4.06	Concrete, type B, in foot protection block	330	cu.m	235.05	77,566.50	
4.07	Concrete, type B, at crest of embankment	200	cu.m	235.05	47,010.00	
4.08	Concrete, type B, in foundation of wet masonry	160	cu.m	235.05	37,608.00	
4.09	Formwork F1 finish, in foot protection block	1,320	sq.m	36.76	48,523.20	
4.10	Formwork F1 finish, in foundation of wet masonry	530	sq.m	36.76	19,482.80	
4.11	Formwork F1 finish, for concrete joint wet masonry	70	sq.m	36.76	2,573.20	
4.12	Formwork F1 finish for concrete in backfilling	1,720	sq.m	36.76	63,227.20	
<u>Wet Masonry</u>						
4.13	Backfill concrete, type B, behind wet masonry	560	sq.m	235.05	131,628.00	
4.14	Wet-rubble masonry	1,720	cu.m	52.24	89,852.80	
4.15	Joint filler	70	sq.m	60.30	4,221.00	
4.16	Inter locking mortar in wet masonry	90	cu.m	429.02	38,611.80	
4.17	Reinforcing bar 16 mm. dia	0.51	ton	4,799.48	2,447.73	
Grand Total to Spur Dike No.2					733,512.03	

SECTION - 5

LEVEE

Item No.	Description	Quantity	Unit	Rate	Amount	
					PESO	: CEN
<u>Earthwork</u>						
5.01	Excavation, in common, in foundation of levee and river bed	87,900	cu.m	16.57	1,456,503.00	
5.02	Embankment for levee	62,800	cu.m	21.80	1,369,040.00	
5.03	Backfill cobble stone behind wet masonry and at toe of levee	13,280	cu.m	41.49	550,987.20	
5.04	Filling rubble, in cribwork	14,150	cu.m	30.60	432,990.00	
5.05	Backfill in cribwork	10,560	cu.m	18.94	200,006.40	
<u>Concrete and Formwork</u>						
5.06	Concrete, type B, in top protection block	380	cu.m	235.05	89,319.00	
5.07	Backfill concrete, type B, behind wet masonry	4,860	cu.m	235.05	1,142,343.00	
5.08	Concrete, type B, in foundation of wet masonry	3,900	cu.m	235.05	916,695.00	
5.09	Formwork F1 finish, in top protection block	1,860	sq.m	36.76	68,373.60	
5.10	Formwork F1 finish, in wet masonry	1,680	sq.m	36.76	61,756.80	
5.11	Formwork F1 finish, in foundation of wet masonry	8,190	sq.m	36.76	301,064.40	
<u>Cribwork</u>						
5.12	Coconut trunk	151,050	lin.m	5.43	820,201.50	
5.13	Split bamboo	279,720	lin.m	0.50	139,860.00	
5.14	Reinforcing bar, 1/2 mm. in. dia.	23.4	ton	4799.48	112,307.83	

Item No.	Description	Quantity	Unit	Rate	Amount	
					PESO	: CEN
<u>Miscellaneous</u>						
5.15	Joint filler, in top protection block	19	sq.m	60.30	1,145.70	
5.16	Joint filler, in wet masonry	489	sq.m	60.30	29,486.70	
5.17	Joint filler, in foundation of wet masonry	196	sq.m	60.30	11,818.80	
5.18	Weep hole, 5 cm. dia.	716	lin.m	30.69	21,974.04	
<u>Wet Masonry</u>						
5.19	Wet masonry	32,380	sq.m	46.18	1,495,308.40	
Grand Total to Levee					9,221,181.37	

SECTION - 6
GROUNDSILL, TYPE - A

Item No.	Description	Quantity	Unit	Rate	Amount	
					PESO	: CEN
<u>Earthwork</u>						
6.01	Excavation, in common	3,180	cu.m	16.57	52,692.60	
6.02	Backfill, in groundsill	440	cu.m	18.94	8,333.60	
6.03	Filling rubble, in cribwork	1,960	cu.m	30.60	59,976.00	
<u>Cribwork</u>						
6.04	Coconut trunk	20,950	lin.m	5.43	113,758.50	
6.05	Split bamboo	38,800	lin.m	0.50	19,400.00	
6.06	Reinforcing bar, 12 mm. dia.	3.5	ton	4799.48	16,798.18	
Grand Total to Groundsill, Type A					270,958.88	

SECTION - 7
GROUNDSILL, TYPE - B

Item No.	Description	Quantity	Unit	Rate	Amount	
					PESO	: CEN
<u>Earthwork</u>						
7.01	Excavation, in common	1,170	cu.m	16.57	19,386.90	
7.02	Backfill, in ground-sill	160	cu.m	18.94	3,030.40	
7.03	Filling rubble, in cross concrete block	860	cu.m	30.60	26,316.00	
<u>Cross Concrete Block</u>						
7.04	Concrete, Type A	430	cu.m	255.10	109,693.00	
7.05	Formwork F1 finish	1,950	sq.m	36.76	71,682.00	
7.06	Reinforcing bar	8.0	ton	4799.48	38,395.84	
Grand Total to Groundsill, Type B					268,504.14	

SECTION - 8
IRRIGATION INTAKE

Item No.	Description	Quantity	Unit	Rate	Amount	
					PESO	: CEN
<u>Concrete and Formwork</u>						
8.01	Concrete, Type C, in intake	9.4	cu.m	298.70	2,807.78	
8.02	Concrete, Type C, in sedimentary tank	7.2	cu.m	298.70	2,150.64	
8.03	Formwork F1 finish, in intake	37	sq.m	36.76	1,360.12	
8.04	Formwork F2 finish, in intake	12	sq.m	79.85	958.20	
8.05	Formwork F1 finish, in sedimentary tank	22	sq.m	36.76	808.72	
8.06	Formwork F2 finish, in sedimentary tank	15	sq.m	79.85	1,197.75	
<u>Furnishing and Placing bars</u>						
8.07	Reinforcing bar, in intake	0.61	ton	4799.48	2,927.68	
8.08	Reinforcing bar, in sedimentary tank	0.63	ton	4799.48	3,023.67	
<u>Miscellaneous</u>						
8.09	Finishing and placing 600 mm. dia. concrete drain pipe	8.0	lin.m	378.19	3,033.52	
Grand Total to Irrigation Intake					18,268.08	

ANNEX II

Breakdown of Unit Price

Breakdown of Unit Price

Item No. _____ Work Site General

Work Access Road

Price 237,700 ₪

Remark : Width 5.50 m, Length 4,000 m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Light oil		ℓ	147.00			2.68	393.96
Lubricant		ℓ	3.50			10.04	35.14
Grease		kg	0.11			19.82	2.18
Sub total							431.28
b. Labor							
Foreman		M.D	0.500			24.84	12.42
Operator		M.D	1.000			23.65	23.65
Assistant operator		M.D	1.000			17.55	17.55
Common labor		M.D	2.000			16.25	32.50
Sub total							86.12
c. PD #390	4.5% of b						3.88
d. Equipment expense							
Bulldozer	21 ton	Hr	7.00			350.00	2,450.00
Total							2,971.28
Construction cost for Access Road							
(2,971.28 ₪/50 m/day) @4,000 m							
= 237,700 ₪							

Breakdown of Unit Price

Item No. _____ Work Site General

Work Temporary Buildings

Price 319,000 P

Remark : _____

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
Buildings							
Office		sq.m	100.00			400.00	40,000
Temporary Building		sq.m	130.00			300.00	39,000
(Repair shop, Warehouse, Cement store, Magazine, etc.)							
Staff Quarter		sq.m	100.00			400.00	40,000
Labor Camp		sq.m	600.00			300.00	180,000
Sub total							299,000
Land Reclamation							
Reclamation		sq.m	2,000.00			10.00	20,000
Total							319,000

Breakdown of Unit Price

Item No. _____ Work Site General

Work Water Supply

Price 647,800 ₱

Remark : _____

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Gasolin		ℓ	2.10			2.82	5.92
Light oil		ℓ	56.00			2.68	150.00
Lubricant		ℓ	1.60			10.04	16.06
Grease		kg	0.08			19.82	1.59
Sub total							173.57
b. Labor							
Driver		M.D	1.00			19.36	19.36
Common labor		M.D	1.00			16.25	16.25
Sub total							35.61
c. PD #390	4.5% of b						1.60
d. Equipment expense							
Water pump	200 ℓ/min	Day	2.00			20.00	40.00
Water tanker	1,750 ℓ	Day	1.00			240.00	240.00
Sub total							280.00
Total							490.78
The cost of Water Supply							
490.78 ₱/day x 22 days x 12 months							
x 5 years = 647,800 ₱							

Breakdown of Unit Price

Item No. _____ Work Site General

Work Electric Supply

Price 713,200 ₱

Remark : Diesel generator for Temporary Buildings

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Fuel	For Buildings						123,500
	20kW x 6Hr x 0.8 x 30 days x 12 month						
	x 5 years = 172,800 kWh						
	172,800kWh + 0.75 x 0.2 x 2.68 ₱						
	= 123,500 ₱						
	For Repair shop						34,700
	15kW x 6Hr x 0.5 x 18 days x 12 month						
	x 5 years = 48,600 kWh						
b. Labor							
Electrician		M.D	1,800			17.55	31,600
Common labor		M.D	3,600			16.25	58,500
c. PD #390	4.5% of b						4,100
d. Equipment expense							
Diesel generator	25 kVA	Day	1,800			160.00	288,000
Diesel generator	20 kVA	Day	1,080			160.00	172,800
Total							713,200

Breakdown of Unit Price

Item No. _____ Work Site Subo dam, Spur dike, Groundsill

Work Excavation, in common

Price 16.57 P/cu.m

Remark : 300 cu.m/day

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Material							
Light oil		ℓ	362.40			2.68	971.23
Lubricant		ℓ	10.20			10.04	102.41
Grease		kg	0.532			19.82	10.54
Sub total							1,084.18
b. Labor							
Foreman		M.D	1.000			24.84	24.84
Operator		M.D	1.49			23.65	35.24
Assistant operator		M.D	1.49			17.55	26.15
Driver		M.D	2.54			19.36	49.17
Common labor		M.D	4.00			16.25	65.00
Sub total							200.40
c. PD#390	4.5% of b						9.02
d. Equipment expense							
Bulldozer	21 ton	Hr	3.60			350.00	1,260.00
Tractor shovel	1.4 m ³	Hr	6.80			110.00	748.00
Dump truck	6 ton	Hr	17.80			80.00	1,424.00
Sub total							3,432.00
e. Spoil banking		cu.m	300.00			0.82	246.00
Total							4,971.60

Breakdown of Unit Price

Item No. _____ Work Site Sabo dam

Work Excavation, in rock

Price 70.14 P/cu.m

Remark : 100 cu.m/day

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Light oil		ℓ	244.80			2.68	656.06
Lubricant		ℓ	6.95			10.04	69.78
Grease		kg	0.37			19.82	7.33
Sub total							733.17
b. Labor							
Foreman		M.D	0.50			24.84	12.42
Operator		M.D	0.94			23.65	22.23
Assistant operator		M.D	0.94			17.55	16.50
Driver		M.D	1.86			19.36	36.01
Common labor		M.D	2.00			16.25	32.50
Sub total							119.66
c. PD#390	4.5% of b						5.38
d. Equipment expense							
Bulldozer	21 ton	Hr	2.00			350.00	700.00
Tractor shovel	1.4 m ³	Hr	4.55			110.00	500.50
Dump truck	6 ton	Hr	13.00			80.00	1,040.00
Sub total							2,240.50
e. Blasting		cu.m	100.00			38.19	3,819.00
f. Spoil banking		cu.m	100.00			0.96	96.00
Total							7,013.71

Breakdown of Unit Price

Item No. _____ Work Site Sabo dam, Spur dike, Levee

Work Backfill

Price 18.94 P/cu.m

Remark : 100 cu.m/day

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Light oil		ℓ	117.86			2.68	315.87
Lubricant		ℓ	3.30			10.04	33.13
Grease		kg	0.17			19.82	3.37
Sub total							352.37
b. Labor							
Foreman		M.D	0.50			24.84	12.42
Operator		M.D	0.52			23.65	12.30
Assistant operator		M.D	0.52			17.55	9.13
Driver		M.D	0.76			19.36	14.71
Common labor		M.D	2.00			16.25	32.50
Sub total							81.06
c. PD#390	4.5% of b						3.65
d. Equipment expense							
Bulldozer	21 ton	Hr	1.28			350.00	448.00
Tractor shovel	1.4 m ³	Hr	2.38			110.00	261.80
Dump truck	6 ton	Hr	5.29			80.00	423.20
Sub total							1,133.00
e. Filling with hand		cu.m	100.00			3.24	324.00
Total							1,894.08

Breakdown of Unit Price

Item No. _____ Work Site Spur dike, Levee

Work Embankment

Price 21.80 P/cu.m

Remark : 100 cu.m/day

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Light oil		ℓ	130.10			2.68	348.67
Lubricant		ℓ	4.61			10.04	46.28
Grease		kg	0.19			19.82	3.77
Sub total							398.72
b. Labor							
Foreman		M.D	0.50			24.84	12.42
Operator		M.D	0.85			23.65	20.10
Assistant operator		M.D	0.85			17.55	14.92
Driver		M.D	0.76			19.36	14.71
Common labor		M.D	2.00			16.25	32.50
Sub total							94.65
c. PD#390	4.5% of b						4.26
d. Equipment expense							
Bulldozer	21 ton	Hr	1.28			350.00	448.00
Tractor shovel	1.4 m ³	Hr	2.38			110.00	261.80
Dump truck	6 ton	Hr	5.29			80.00	423.20
Bulldozer	11 ton	Hr	0.48			160.00	76.80
Vibratory roller		Hr	1.85			80.00	148.00
Sub total							1,357.80
e. Filling with hand		cu.m	100.00			3.24	324.00
Total							2,179.43

Breakdown of Unit Price

Item No. _____ Work Site Spur dike, Levee

Work Backfilling cobble stone behind wet masonry

Price 41.49 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Sand and gravel		cu.m	1.100			35.00	38.50
Gasoline		ℓ	0.060			2.82	0.17
Sub total							38.67
b. Labor							
Foreman		M.D	0.007			24.84	0.17
Skilled labor		M.D	0.014			17.55	0.25
Common labor		M.D	0.114			16.25	1.85
Sub total							2.27
c. PD#390	4.5% of b						0.10
d. Equipment expense							
Rammer	80 - 100 kg	Day	0.009			50.00	0.45
Total							41.49

Breakdown of Unit Price

Item No. _____ Work Site Spur dike,

Work Riprap bedding

Price 30.60 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
Supplying rubble	stone	cu.m	1.000			25.16	25.16
Filling with hand		cu.m	1.000			5.44	5.44
Total							30.60

Breakdown of Unit Price

Item No. _____ Work Site Levee, Groundsill

Work Filling rubble in crib work

Price 30.60 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
Supplying rubble	stone	cu.m	1.000			25.16	25.16
Filling with hand		cu.m	1.000			5.44	5.44
Total							30.60

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Excavation with hand, sand and gravel

Price 10.60 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
b. Labor							
Foreman		M.D	0.010			24.84	0.25
Skilled labor		M.D	0.100			17.55	1.76
Common labor		M.D	0.500			16.25	8.13
Sub total							10.14
c. PD#390	4.5% of b						0.46
Total							10.60

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Excavation with hand, weathered rock

Price 49.12 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Light oil		ℓ	3.700			2.68	9.92
Lubricant		ℓ	0.150			10.04	1.51
Grease		kg	0.010			19.82	0.20
Sub total							11.63
b. Labor							
Foreman		M.D	0.021			28.84	0.52
Driller		M.D	0.214			17.55	3.76
Skilled labor		M.D	0.043			17.55	0.75
Common labor		M.D	0.214			16.25	3.48
Sub total							8.51
c. PD#390	4.5% of b						0.38
d. Equipment expense							
Air compressor	3.5 m ³ /min	Day	0.143			190.00	27.17
Pickhammer	7 kg	Day	0.143			10.00	1.43
Sub total							28.60
Total							49.12

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Filling with hand, sand and gravel

Price 3.24 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
b. Labor							
Foreman		M.D	0.014			24.84	0.35
Skilled labor		M.D	0.027			17.55	0.47
Common labor		M.D	0.140			16.25	2.28
Sub total							3.10
c. PD#390	4.5% of b						0.14
Total							3.24

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Filling with hand, rock and rubble

Price 5.44 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
b. Labor							
Foreman		M.D	0.024			24.84	0.60
Skilled labor		M.D	0.046			17.55	0.81
Common labor		M.D	0.234			16.25	3.80
Sub total							5.21
c. PD#390	4.5% of b						0.23
Total							5.44

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Spoil Banking, sand and gravel

Price 0.82 P/cu.m

Remark : 100 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Light oil		ℓ	4.723			2.68	12.66
Lubricant		ℓ	0.095			10.04	0.95
Grease		kg	0.006			19.82	0.12
Sub total							13.73
b. Labor							
Foreman		M.D	0.005			24.84	0.15
Operator		M.D	0.045			23.65	1.07
Assistant operator		M.D	0.045			17.55	0.79
Common labor		M.D	0.900			16.25	14.63
Sub total							16.64
c. PD#390	4.5% of b						0.75
d. Equipment expense							
Bulldozer	11 ton	Hr	0.317			160.00	50.72
Total							81.84

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Excavating rock with hand

Price 63.63 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Light oil		ℓ	4.300			2.68	11.52
Lubricant		ℓ	0.137			10.04	1.38
Grease		kg	0.004			19.82	0.08
Sub total							12.98
b. Labor							
Foreman		M.D	0.080			24.84	1.99
Driller		M.D	0.850			17.55	14.92
Common Labor		M.D	0.850			16.25	13.81
Sub total							30.72
c. PD#390	4.5% of b						1.38
d. Equipment expense							
Pickhammer	7.5 kg	Day	0.159			10.00	1.59
Air compressor	7 m ³ /min	Day	0.053			320.00	16.96
Sub total							18.55
Total							63.63

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Spoil Banking, weathered rock and rock

Price 0.96 P/cu.m

Remark : 100 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Light oil		ℓ	6.616			2.68	17.73
Lubricant		ℓ	0.133			10.04	1.34
Grease		kg	0.009			19.82	0.18
Sub total							19.25
b. Labor							
Foreman		M.D	0.006			24.84	0.15
Operator		M.D	0.063			23.65	1.49
Assistant operator		M.D	0.063			17.55	1.11
Common labor		M.D	0.127			16.25	2.06
Sub total							4.81
c. PD#390	4.5% of b						0.22
d. Equipment expense							
Bulldozer	11 ton	Hr	0.444			160.00	71.04
Total							95.32

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Excavating rock with explosive

Price 38.19 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Taper rod	22 mm. dia	No	0.005			340.00	1.70
Cross bit	36 mm. guage	No	0.005			900.00	4.50
Dinamite		kg	0.010			50.00	0.50
Detonator		No	1.000			6.00	6.00
Light oil		ℓ	2.440			2.68	6.54
Lubricant		ℓ	0.080			10.04	0.80
Grease		kg	0.002			19.82	0.04
Sub total							20.08
b. Labor							
Foreman		M.D	0.005			24.84	0.12
Driller		M.D	0.300			17.55	5.27
Powderman		M.D	0.100			17.55	1.76
Common labor		M.D	0.200			16.25	3.25
Sub total							10.04
c. PD#390	4.5% of b						0.47
d. Equipment expense							
Jack hammer	20 kg	Day	0.040			30.00	1.20
Air compressor	7 m ³ /min	Day	0.020			320.00	6.40
Sub total							7.60
Total							38.19

Breakdown of Unit Price

Item No. _____ Work Site Sabo dam

Work Concrete, type A

Price 296.72 ₱/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
Concrete material		cu.m	1,000				198.15
Mixing concrete (Portable batcher)		cu.m	1,000				34.60
Carrying concrete		cu.m	1,000				22.90
Placing concrete (concrete bucket)		cu.m	1,000				40.11
Curing concrete		cu.m	1,000				0.96
Total			.				296.72

Breakdown of Unit Price

Item No. _____ Work Site Sabo dam

Work Concrete, rubble concrete

Price 237.96 ₱/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
Concrete, type A		cu.m	0.75			296.72	222.54
Rubble aggregate		cu.m	0.25			61.67	15.42
Total							237.96

Breakdown of Unit Price

Item No. _____ Work Site Sabo dam, Rubble concrete

Work Rubble aggregate

Price 61.67 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Light oil		ℓ	3.500			2.68	9.38
Lubricant		ℓ	0.245			10.04	2.46
Grease		kg	0.035			19.82	0.69
Rubble aggregate		cu.m	1.000			25.16	25.16
Sub total							37.69
b. Labor							
Foreman		M.D	0.005			24.84	0.13
Concrete worker		M.D	0.400			16.25	6.50
Common labor		M.D	0.200			16.25	3.25
Operator		M.D	0.050			23.65	1.18
Assistant operator		M.D	0.050			17.55	0.88
Sub total							11.94
c. PD #390	4.5% of b						0.54
d. Equipment expense							
Track crane	15 ton	Hr	0.050			230.00	11.50
Total							61.67

Breakdown of Unit Price

Item No. _____ Work Site Sabo dam

Work Backfill concrete, type B

Price 258.35 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
Concrete material		cu.m	1.000				178.10
Mixing concrete (Portable batcher)		cu.m	1.000				34.60
Carrying concrete		cu.m	1.000				22.90
Placing concrete (chute)		cu.m	1.000				22.75
Curing concrete		cu.m	1.000				0.96
Total							258.35

Breakdown of Unit Price

Item No. _____ Work Site Spur dike

Work Concrete, type B, in foot protection block,
at crest of embankment, in wet masonry

Price 235.05 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
Concrete material		cu.m	1.000				178.10
Mixing concrete (Light mixer)		cu.m	1.000				33.24
Placing concrete		cu.m	1.000				22.75
Curing concrete		cu.m	1.000				0.96
Total							235.05

Breakdown of Unit Price

Item No. _____ Work Site Levee

Work Concrete, type B, in top protection block,
in wet masonry

Price 235.05 P/cu.m

Remark : 1 cu.m

[illegible]

Breakdown of Unit Price

Item No. _____ Work Site Cross concrete block

Work Concrete, type A

Price 255.10 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
Concrete material		cu.m	1.000				198.15
Mixing concrete (Light mixer)		cu.m	1.000				33.24
Placing concrete		cu.m	1.000				22.75
Curing concrete		cu.m	1.000				0.96
Total			.				255.10

Breakdown of Unit Price

Item No. _____ Work Site Irrigation intake

Work Concrete, type C

Price 298.70 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
Concrete material		cu.m	1.000				241.75
Mixing concrete (Light mixer)		cu.m	1.000				33.24
Placing concrete		cu.m	1.000				22.75
Curing concrete		cu.m	1.000				0.96
Total							298.70

Breakdown of Unit Price

Item No. _____ Work Site Spur dike, wet masonry

Work Mixing mortar with hand, 1:3

Price 429.02 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Portland cement		ton	0.530			700.00	371.00
Aggregate	Fine	cu.m	1.050			25.00	26.25
Sub total							397.25
b. Labor							
Foreman		M.D	0.030			24.84	0.75
Skilled labor		M.D	0.300			17.55	5.27
Common labor		M.D	1.500			16.25	24.38
Sub total							30.40
c. PD #390	4.5 % of b						1.37
Total							429.02

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Concrete material, type A

Price 198.15 ₪/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material			.				
Portland cement		ton	0.215			700.00	150.50
Aggregate	Fine	cu.m	0.520			25.00	13.00
Aggregate	Coarse	cu.m	0.990			35.00	34.65
Sub total							198.15

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Concrete material, type B

Price 178.10 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Portland cement		ton	0.185			700.00	129.50
Aggregate	Fine	cu.m	0.530			25.00	13.25
Aggregate	Coarse	cu.m	1.010			35.00	35.35
Sub total							178.10

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Mixing concrete with light mixer, 0.2 cu.m

Price 33.24 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Light oil		ℓ	0.556			2.68	1.49
Lubricant		ℓ	0.010			10.04	0.10
Sub total							1.59
b. Labor							
Foreman		M.D	0.012			24.84	0.30
Concrete worker		M.D	0.123			16.25	2.00
Common labor		M.D	0.368			16.25	5.98
Sub total							8.28
c. PD #390	4.5 % of b						0.37
d. Equipment expense							
Concrete mixer	0.2 m ³	Day	0.100			230.00	23.30
Total							33.24

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Mixing concrete with portable batcher, 0.75 cu.m

Price 34.60 P/cu.m

Remark : 1 cu.m/day

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Light oil		ℓ	0.900			2.68	2.41
Lubricant		ℓ	0.034			10.04	0.34
Grease		kg	0.002			19.82	0.04
Sub total							2.79
b. Labor							
Foreman		M.D	0.006			24.84	0.15
Operator		M.D	0.048			19.36	0.93
Mechanic		M.D	0.024			17.55	0.42
Electrician		M.D	0.024			17.55	0.42
Common labor		M.D	0.214			16.25	3.48
Sub total							5.40
c. PD #390	4.5 % of b						0.24
d. Equipment expense							
Concrete mixer	0.75 m ³	Hr	0.067			210.00	14.07
Belt conveyor		Day	0.032			90.00	2.88
Bulldozer	3 ton	Hr	0.111			60.00	6.66
Generator	20 kVA	Day	0.016			160.00	2.56
Sub total							26.17
Total							34.60

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Carrying concrete with agitator truck, 1.7 cu.m

Price 22.90 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Light oil		ℓ	2.188			2.68	5.87
Lubricant		ℓ	0.078			10.04	0.79
Grease		kg	0.001			19.82	0.02
Sub total							6.68
b. Labor							
Foreman		M.D	0.005			24.84	0.13
Driver		M.D	0.053			19.36	1.03
Sub total							1.16
c. PD #390	4.5 % of b						0.06
d. Equipment expense							
Agitator	1.7 m ³	Hr	0.250			60.00	15.00
Total							22.90

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Placing concrete with hand

Price 22.75 ₱/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Gasoline		ℓ	2,300			2.82	6.49
b. Labor							
Foreman		M.D	0.053			24.84	1.32
Concrete worker		M.D	0.525			16.25	8.53
Common labor		M.D	0.263			16.25	4.27
Sub total							14.12
c. PD #390	4.5 % of b						0.64
d. Equipment expense							
Vibrator	45 mm.dia	Day	0.050			30.00	1.50
Total							22.75

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Placing concrete with concrete bucket

Price 40.11 P/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Gasoline		ℓ	2.000			2.82	5.64
Light oil		ℓ	0.460			2.68	1.23
Lubricant		ℓ	0.015			10.04	0.15
Grease		kg	0.003			19.82	0.06
Sub total							7.08
b. Labor							
Foreman		M.D	0.045			24.84	1.12
Operator		M.D	0.023			23.65	0.54
Assistant operator		M.D	0.023			17.55	0.40
Concrete worker		M.D	0.450			16.25	7.31
Common labor		M.D	0.225			16.25	3.66
Sub total							13.03
c. PD #390	4.5 % of b						0.59
d. Equipment expense							
Truck crane	16 ton	Hr	0.077			230.00	17.71
Concrete bucket	0.6 m ³	Day	0.005			40.00	0.20
Vibrator	45 mm. dia	Day	0.050			30.00	1.50
Sub total							19.41
Total							40.11

Breakdown of Unit Price

Item No. _____ Work Site _____

Work _____ Curing concrete with mat _____

Price _____ 0.96 P/cu.m _____

Remark : _____ 1 cu.m _____

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
b. Labor							
Foreman							
Concrete worker		M.D	0.001			24.84	0.03
Common labor		M.D	0.005			16.25	0.08
Sub total		M.D	0.050			16.25	0.81
							0.92
c. PD #390	4.5 % of b						0.04
Total							0.96

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Formwork F1

Price 36.76 P/sq.m

Remark : 1 sq.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Timber	Plank	cu.m	0.010			1,101.70	11.02
Timber	Square	cu.m	0.008			1,101.70	8.82
Timber	Log	cu.m	0.002			1,101.70	2.21
Nail		kg	0.380			8.00	3.04
Annealed iron wire		kg	0.070			8.50	0.60
Sub total							25.69
b. Labor							
Foreman		M.D	0.002			24.84	0.05
Carpenter		M.D	0.417			17.55	7.32
Common Labor		M.D	0.198			16.25	3.22
Sub total							10.59
c. PD #390	4.5 % of b						0.48
Total							36.76

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Formwork F2

Price 79.85 P/sq.m

Remark : 1 sq.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Plywood		cu.m	0.011			2,648.00	29.13
Timber	square	cu.m	0.016			1,101.70	17.63
Nail		kg	0.470			8.00	3.76
Timber	log	cu.m	0.005			1,101.70	5.51
Annealed iron wire		kg	0.100			8.50	0.85
Sub total							56.88
b. Labor							
Foreman		M.D	0.059			24.84	1.47
Carpenter		M.D	0.891			17.55	15.63
Common Labor		M.D	0.300			16.25	4.88
Sub total							21.98
c. PD #390	4.5% of b						0.99
Total							79.85

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Reinforcing bar, deformed bar

Price 4,799.48 ₱/ton

Remark : 1 ton

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Deformed bar		ton	1,030			4,300.00	4,429.00
Annealed iron wire		kg	4,000			8.50	42.50
Sub total							4,471.50
b. Labor							
Foreman		M.D	0.880			24.84	21.86
Reinforcement worker		M.D	8.800			16.25	143.00
Common Labor		M.D	9,200			16.25	149.50
Sub total							313.86
c. PD #390	4.5 % of b						14.12
Total							4,799.48

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Waterstop, width 300 mm

Price 94.19 P/m

Remark : 1 Lin.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Water stop	P.V.C	Lin.m	1.000			90.00	90.00
b. Labor							
Foreman		M.D	0.030			24.84	0.75
Concrete worker		M.D	0.100			16.25	1.63
Common Labor		M.D	0.100			16.25	1.63
Sub total							4.01
c. PD #390	4.5 % of b						0.18
Total							94.19

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Joint filler, expansion joint

Price 60.30 P/sq.m

Remark : 1 sq.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Joint filler	Elastite	sq.m	1.050			55.00	57.75
b. Labor							
Foreman		M.D	0.030			24.84	0.75
Carpenter		M.D	0.050			17.55	0.88
Common labor		M.D	0.050			16.25	0.81
Sub total							2.44
c. PD #390	4.5% of b						0.11
Total							60.30

Breakdown of Unit Price

Item No. _____ Work Site _____

Work R.C pipe, 300 mm. dia.

Price 302.76 P/m

Remark : 1 Lin.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
R.C. pipe	300 mm	Lin.m	1.000			290.00	290.00
Portland cement		ton	0.006			700.00	4.20
Aggregate	Fine	cu.m	0.009			25.00	0.23
Sub total							294.43
b. Labor							
Foreman		M.D	0.020			24.84	0.50
Pipe fitter		M.D	0.165			16.25	2.68
Common labor		M.D	0.295			16.25	4.79
Sub total							7.97
c. PD #390	4.5% of b						0.36
Total							302.76

Breakdown of Unit Price

Item No. _____ Work Site _____

Work R.C pipe, 600 mm. dia.

Price 378.19 ₱/m

Remark : 1 Lin.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
R.C. pipe	600 mm.	Lin.m	1.000			355.00	355.00
Portland cement		ton	0.010			700.00	7.00
Aggregate	Fine	cu.m	0.013			25.00	0.33
Sub total							362.33
b. Labor							
Foreman		M.D	0.050			24.84	1.24
Pipe fitter		M.D	0.255			16.25	4.14
Common Labor		M.D	0.603			16.25	9.80
Sub total							15.18
Total							378.19

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Wet rubble masonry, spur dike

Price 52.24 P/sq.m

Remark : 1 sq.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Rubble		cu.m	0.300			25.16	7.55
Portland cement		ton	0.028			700.00	19.60
Aggregate	Fine	cu.m	0.080			25.00	2.00
Aggregate	Coarse	cu.m	0.152			35.00	5.32
Light oil		ℓ	0.095			2.82	0.27
Sub total							34.74
b. Labor							
Foreman		M.D	0.030			24.84	0.75
Mason		M.D	0.198			17.55	3.47
Concrete worker		M.D	0.025			16.25	0.41
Common Labor		M.D	0.610			16.25	9.91
Sub total							14.54
c. PD #390	4.5 % of b						0.66
d. Equipment expense							
Concrete Mixer	0.2 m ³	Day	0.010			230.00	2.30
Total							52.24

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Wet-rubble masonry, Levee work

Price 46.18 P/sq.m

Remark : 1 sq.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Rubble		cu.m	0.150			25.16	3.77
Portland cement		ton	0.028			700.00	19.60
Aggregate	Fine	cu.m	0.080			25.00	2.00
Aggregate	Coarse	cu.m	0.152			35.00	5.32
Light oil		ℓ	0.095			2.82	0.27
Sub total							30.96
b. Labor							
Foreman		M.D	0.025			24.84	0.62
Mason		M.D	0.168			17.55	2.95
Concrete worker		M.D	0.021			16.25	0.34
Common Labor		M.D	0.520			16.25	8.45
Sub total							12.36
c. PD #390	4.5 % of b						0.56
d. Equipment expense							
Concrete mixer	0.2 m ³	Day	0.010			230.00	2.30
Total							46.18

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Weep hole, 5 cm. dia.

Price 30.69 P/m

Remark : 1 Lin.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
P.V.C pipe		Lin.m	1.000			28.50	28.50
b. Labor							
Foreman		M.D	0.010			24.84	0.25
Common labor		M.D	0.113			16.25	1.84
Sub total							2.09
c. PD #390	4.5 % of b						0.10
Total							30.69

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Crib work

Price 5.43 P/m

Remark : 1 No. timber length 21.6 m/No.

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material							
Coconut trunk		Lin.m	21.600			3.00	64.80
Tie wire		kg	3.000			8.00	24.00
Sub total							88.80
b. Labor							
Foreman		M.D	0.100			24.84	2.48
Common Labor		M.D	0.730			16.25	11.86
Carpenter		M.D	0.730			17.55	12.81
Sub total							27.15
c. PD #390	4.5 % of b						1.22
Total							117.17

Breakdown of Unit Price

Item No. _____ Work Site _____

Work Supplying rubble stone
from riverbed

Price 25.16 ₱/cu.m

Remark : 1 cu.m

Particular	Description	Unit	Q'ty	Currency		Currency	
				Unit Cost	Amount	Unit Cost	Amount
a. Total cost of material			-				
Light oil		ℓ	1.600			2.68	4.29
Lubricant		ℓ	0.045			10.04	0.45
Grease		kg	0.001			19.82	0.02
Sub total							4.76
b. Labor							
Foreman		M.D	0.005			24.84	0.12
Common labor		M.D	0.400			16.25	6.50
Operator		M.D	0.100			23.65	2.37
Sub total							8.99
c. PD #390	4.5% of b						0.41
d. Equipment expense							
Tractor shovel		Hr	0.100			100.00	11.00
Total							25.16

APPENDIX IV

DESIGN DRAWINGS

THE REPUBLIC OF THE PHILIPPINES
MINISTRY OF PUBLIC WORKS
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT
SABO FACILITIES IN THE PAWA – BURABOD RIVER
A TRIBUTARY OF THE YAWA RIVER

DESIGN DRAWINGS

FEBRUARY 1980

JAPAN INTERNATIONAL COOPERATION AGENCY



MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT

SABO FACILITIES IN THE PAWA – BURABOD RIVER

A TRIBUATARY OF THE YAWA RIVER


LIST OF DESIGN DRAWINGS


D.W.G NO.	TITLE OF DRAWING	D.W.G NO.	TITLE OF DRAWING
M.V.S-D 001	LOCATION MAP OF THE PAWA-BURABOD RIVER	M.V.S-D 015	RIVER CANALIZATION, PROFILE (2-2)
M.V.S-D 002	NO.1 SABO DAM, GENERAL PLAN	M.V.S-D 016	RIVER CANALIZATION, CROSS SECTION (10-1)
M.V.S-D 003	NO.1 SABO DAM, STRUCTURAL DETAIL (1)	M.V.S-D 017	" (10-2)
M.V.S-D 004	NO.1 SABO DAM, STRUCTURAL DETAIL (2)	M.V.S-D 018	" (10-3)
M.V.S-D 005	SPUR DIKES, GENERAL PLAN	M.V.S-D 019	" (10-4)
M.V.S-D 006	NO.1 SPUR DIKE, PLAN, PROFILE & SECTION	M.V.S-D 020	" (10-5)
M.V.S-D 007	NO.2 SPUR DIKE, PLAN, PROFILE & SECTION	M.V.S-D 021	" (10-6)
M.V.S-D 008	RIVER CANALIZATION, PLAN (6-1)	M.V.S-D 022	" (10-7)
M.V.S-D 009	" (6-2)	M.V.S-D 023	" (10-8)
M.V.S-D 010	" (6-3)	M.V.S-D 024	" (10-9)
M.V.S-D 011	" (6-4)	M.V.S-D 025	" (10-10)
M.V.S-D 012	" (6-5)	M.V.S-D 026	RIVER CANALIZATION, TYPICAL CROSS SECTION
M.V.S-D 013	" (6-6)	M.V.S-D 027	RIVER CANALIZATION, STRUCTURAL DETAIL OF LEVEE
M.V.S-D 014	RIVER CANALIZATION, PROFILE (2-1)	M.V.S-D 028	RIVER CANALIZATION, STRUCTURAL DETAIL OF GROUNDSTALL
		M.V.S-D 029	RIVER CANALIZATION, IRRIGATION INTAKE




Legend	
	Provincial boundary
	First and second class roads
	village, town
Y-0	Denotes site and Number of Sieving
	Test Pit for river bed materials

MINISTRY OF PUBLIC WORKS			
TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES			
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT, PHILIPPINES			
DRAWN BY	DESIGNED BY	BY	TITLE OF DRAWING
DATE	Feb. 1980	SCALE	AS SHOWN
DRAWING NO.	M.V.S - D 001		LOCATION MAP OF THE PAWA-BURABOD RIVER
JAPAN INTERNATIONAL COOPERATION AGENCY			






PLAN




B-B SECTION







C-C SECTION

Scale 0 5 10 20M




A-A SECTION

MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MANILA, PHILIPPINES			
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT			
CHECKED BY	DESIGNED BY	DRAWN BY	TITLE OF DRAWING
DATE Feb. 1980	SCALE AS SHOWN		NO. 1 SABO DAM
DRAWING NO. MVS D-003			STRUCTURAL DETAILS (II)
JAPAN INTERNATIONAL COOPERATION AGENCY			



MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MANILA, PHILIPPINES			
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT			
CHECKED BY	DESIGNED BY	DRAWN BY	TITLE OF DRAWING
DATE	SCALE	AS SHOWN	NO. 1 SABO DAM STRUCTURAL DETAILS (2)
DRAWING NO.	M.V.S.-D 004		
JAPAN INTERNATIONAL COOPERATION AGENCY			





MINISTRY OF PUBLIC WORKS	
TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES	
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT, PHILIPPINES	
ORDERED BY: DIRECTOR OF PROJECT	
DATE: Feb. 1980	SCALE: AS SHOWN
DRAWING NO: MVS-D-005	TITLE: SPUR DIKS GENERAL PLAN
JAPAN INTERNATIONAL COOPERATION AGENCY	





Distance	0.000	13.000	4.000	17.000	5.000	21.000	22.000	20.000	16.000	19.000	10.000	20.000	19.000	13.000	14.000	36.000
Accumulated Distance	0.000	13.000	17.000	34.000	39.000	60.000	82.000	102.000	118.000	137.000	147.000	167.000	186.000	199.000	213.000	255.000
Ground Elevation	164.000	164.750	163.000	166.000	167.000	168.000	169.000	170.000	171.000	172.000	173.000	174.000	175.000	176.000	178.400	177.000
Formation Height of Top of Spur Dike		167.750			170.000						176.000				179.000	
Original Ground Surface Slope		1/13.0				1/16.0						1/22.0				

**MAYON VOLCANO
SABO AND FLOOD CONTROL PROJECT**

CHECKED BY	DESIGNED BY	DRAWN BY	TITLE OF DRAWING NO. 1 SPUR DIKE PLAN, PROFILE & SECTIONS
DATE Feb. 1980	SCALE AS SHOWN		
DRAWING NO. M.V.S.-D 006			
JAPAN INTERNATIONAL COOPERATION AGENCY			




Distance	0.000	10.000	5.000	8.000	16.000	20.000	4.000	8.000	7.000	13.000	23.000	30.000	10.000	7.000	7.000	8.000	0.000
Accumulated Distance	0.000	10.000	15.000	23.000	39.000	59.000	63.000	71.000	78.000	91.000	114.000	144.000	154.000	161.000	168.000	176.000	176.000
Ground Elevation	182.000	183.000	183.300	184.000	185.000	186.000	186.000	186.000	187.000	188.000	189.000	190.000	191.000	192.000	193.000	194.000	195.000
Formation Height of Top of Spur Dike		186.300						190.000		192.000							
Original Ground Surface Slope	1/10.5				1/16.8	Level		1/7.0		1/20.0		Level				1/6.0	



PLAN OF FOOT PROTECTION RUBBLE CONCRETE BLOCK

MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MANILA, PHILIPPINES	
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT	
CHECKED BY: DESIGNED BY: DRAWN BY:	TITLE OF DRAWING
DATE: Feb. 1980	NO. 2 SPUR DIKE
DRAWING NO. M.V.S.-D.007	PLAN, PROFILE & SECTION
JAPAN INTERNATIONAL COOPERATION AGENCY	



Scale
0 10 20 30 40 50 100 Meters




LOCATION DIAGRAM

MINISTRY OF PUBLIC WORKS
TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES
MAYON VOLCANO SABO AND FLOOD CONTROL
PROJECT, PHILIPPINES


CHECKED BY: [Signature] DATE: Feb. 1980
DESIGNED BY: [Signature] SCALE: AS SHOWN
DRAWING NO. MVS-D 008


TITLE OF DRAWING
RIVER CANALIZATION
PLAN (6-1)


JAPAN INTERNATIONAL COOPERATION AGENCY



MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT, PHILIPPINES	
CHECKED BY DESIGNED BY DRAWN BY DATE Feb. 1980 DRAWING NO. MVS-D 010	TITLE OF DRAWING RIVER CANALIZATION PLAN (6-3) JAPAN INTERNATIONAL COOPERATION AGENCY







Scale
0 10 20 30 40 50 100 Meters

LOCATION DIAGRAM

MINISTRY OF PUBLIC WORKS
TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES
MAYON VOLCANO SABO AND FLOOD CONTROL
PROJECT, PHILIPPINES

CHECKED BY: DESIGNED BY: DRAWN BY: TITLE OF DRAWING:
DATE: Feb. 1980 SCALE: AS SHOWN
DRAWING NO. M.V.S - D 013 RIVER CANALIZATION
PLAN (6-6)

JAPAN INTERNATIONAL COOPERATION AGENCY

Horizontal Scale



EL (m)

80.000

70.000

60.000

50.000

40.000

30.000


20.000

10.000

0.000



Legend

- Present River Bed
- Top of Existing Levee
- Ground Level of Leftside
- Ground Level of Rightside




Station No.	Sec-Right Levee		Future Extension		L-Section		R-Section	
	Left Levee	Right Levee	L=1,100 m		L=360 m		L=1,210 m	
0+000	0	0	0	0	0	0	0	0
100	100	100	100	100	100	100	100	100
200	200	200	200	200	200	200	200	200
300	300	300	300	300	300	300	300	300
400	400	400	400	400	400	400	400	400
500	500	500	500	500	500	500	500	500
600	600	600	600	600	600	600	600	600
700	700	700	700	700	700	700	700	700
800	800	800	800	800	800	800	800	800
900	900	900	900	900	900	900	900	900
1+000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000
100	1,100	1,100	1,100	1,100	1,100	1,100	1,100	1,100
200	1,200	1,200	1,200	1,200	1,200	1,200	1,200	1,200
300	1,300	1,300	1,300	1,300	1,300	1,300	1,300	1,300
400	1,400	1,400	1,400	1,400	1,400	1,400	1,400	1,400
500	1,500	1,500	1,500	1,500	1,500	1,500	1,500	1,500
600	1,600	1,600	1,600	1,600	1,600	1,600	1,600	1,600
700	1,700	1,700	1,700	1,700	1,700	1,700	1,700	1,700
800	1,800	1,800	1,800	1,800	1,800	1,800	1,800	1,800
900	1,900	1,900	1,900	1,900	1,900	1,900	1,900	1,900
2+000	2,000	2,000	2,000	2,000	2,000	2,000	2,000	2,000
300	2,100	2,100	2,100	2,100	2,100	2,100	2,100	2,100
400	2,200	2,200	2,200	2,200	2,200	2,200	2,200	2,200
500	2,300	2,300	2,300	2,300	2,300	2,300	2,300	2,300
600	2,400	2,400	2,400	2,400	2,400	2,400	2,400	2,400
700	2,500	2,500	2,500	2,500	2,500	2,500	2,500	2,500
800	2,600	2,600	2,600	2,600	2,600	2,600	2,600	2,600
900	2,700	2,700	2,700	2,700	2,700	2,700	2,700	2,700
1+000	2,800	2,800	2,800	2,800	2,800	2,800	2,800	2,800
200	2,900	2,900	2,900	2,900	2,900	2,900	2,900	2,900
300	3,000	3,000	3,000	3,000	3,000	3,000	3,000	3,000
400	3,100	3,100	3,100	3,100	3,100	3,100	3,100	3,100
500	3,200	3,200	3,200	3,200	3,200	3,200	3,200	3,200
600	3,300	3,300	3,300	3,300	3,300	3,300	3,300	3,300
700	3,400	3,400	3,400	3,400	3,400	3,400	3,400	3,400
800	3,500	3,500	3,500	3,500	3,500	3,500	3,500	3,500
900	3,600	3,600	3,600	3,600	3,600	3,600	3,600	3,600
2+000	3,700	3,700	3,700	3,700	3,700	3,700	3,700	3,700
300	3,800	3,800	3,800	3,800	3,800	3,800	3,800	3,800
400	3,900	3,900	3,900	3,900	3,900	3,900	3,900	3,900
500	4,000	4,000	4,000	4,000	4,000	4,000	4,000	4,000
600	4,100	4,100	4,100	4,100	4,100	4,100	4,100	4,100
700	4,200	4,200	4,200	4,200	4,200	4,200	4,200	4,200
800	4,300	4,300	4,300	4,300	4,300	4,300	4,300	4,300
900	4,400	4,400	4,400	4,400	4,400	4,400	4,400	4,400
2+000	4,500	4,500	4,500	4,500	4,500	4,500	4,500	4,500

MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MANILA . PHILIPPINES			
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT			
CHECKED BY	DESIGNED BY	DRAWN BY	TITLE OF DRAWING
DATE	SCALE	AS SHOWN	RIVERCANALIZATION PROFILE (2-1)
DRAWING NO. M.V.S-D 014			
JAPAN INTERNATIONAL COOPERATION AGENCY			



- Legend
- : Present River Bed
 - - - : Top of Existing Levee
 - - - : Ground Level of Leftside
 - - - : Ground Level of Rightside



Station No.	Distance (m)	Accumulated Distance (m)	Formation Height of River Bed (m)	Design Flood Water Level (m)	Top of Levee (m)	Planned River Bed Slope	Existing Levee				Existing River Bed Slope														
							R-1 Section L = 1.210m	R-2 Section L = 2.41m	R-2' Section L = 1.153m																
							Existing Levee L = 1.447m		L-2 Section L = 992m																
2+000	100	2,000	63.425	64.525	69.083	28.1	72.642	76.200	81.050	83.900	85.900	89.750	95.600	100.450	105.300	110.150	115.000	120.717	126.433	132.150	137.867	143.583	149.300	154.950	161.650
100	100	2,100	66.983	68.083	71.642	20.6	75.200	79.050	84.900	89.750	94.600	99.450	104.300	109.150	114.000	118.717	123.433	128.150	132.867	137.583	142.300	147.000	151.700	156.400	161.100
200	100	2,200	70.542	71.642	75.200	20.6	78.100	82.000	87.900	92.750	97.600	102.450	107.300	112.150	117.000	121.717	126.433	131.150	135.867	140.583	145.300	150.000	154.700	159.400	164.100
300	100	2,300	74.100	75.200	78.800	20.6	81.700	85.600	91.500	96.350	101.200	106.050	110.900	115.750	120.600	125.400	130.200	135.000	139.800	144.600	149.400	154.200	159.000	163.800	168.600
400	100	2,400	77.650	78.800	82.500	20.6	85.250	89.100	95.000	100.850	105.700	110.550	115.400	120.250	125.100	130.000	134.800	139.600	144.400	149.200	154.000	158.800	163.600	168.400	173.200
500	100	2,500	81.200	82.500	86.400	20.6	88.800	92.650	98.550	104.400	109.250	114.100	118.950	123.800	128.650	133.500	138.300	143.100	147.900	152.700	157.500	162.300	167.100	171.900	176.700
600	100	2,600	84.750	86.400	90.300	20.6	92.350	96.200	102.100	107.950	112.800	117.650	122.500	127.350	132.200	137.050	141.900	146.700	151.500	156.300	161.100	165.900	170.700	175.500	180.300
700	100	2,700	88.300	90.300	94.200	20.6	95.900	99.750	105.650	111.500	116.350	121.200	126.050	130.900	135.750	140.600	145.400	150.200	155.000	159.800	164.600	169.400	174.200	179.000	183.800
800	100	2,800	91.850	94.200	98.100	20.6	99.450	103.300	109.250	115.100	120.950	125.800	130.650	135.500	140.350	145.200	150.050	154.900	159.700	164.500	169.300	174.100	178.900	183.700	188.500
900	100	2,900	95.400	98.100	102.000	20.6	103.000	106.850	112.800	118.650	124.500	129.350	134.200	139.050	143.900	148.750	153.600	158.400	163.200	168.000	172.800	177.600	182.400	187.200	192.000
1000	100	3,000	98.950	102.000	106.000	20.6	106.550	110.400	117.150	123.000	128.850	133.700	138.550	143.400	148.250	153.100	157.950	162.750	167.550	172.350	177.150	181.950	186.750	191.550	196.350






MINISTRY OF PUBLIC WORKS
TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES
MANILA, PHILIPPINES

MAYON VOLCANO
SABO AND FLOOD CONTROL PROJECT

CHECKED BY: DESIGNED BY: DRAWN BY:
DATE: 1980 AS SHOWN
DRAWING NO: M.V.S-D 015


TITLE OF DRAWING
RIVER CANALIZATION
PROFILE (2-2)

JAPAN INTERNATIONAL COOPERATION AGENCY




MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MANILA PHILIPPINES			
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT			
CHECKED BY	DESIGNED BY	DRAWN BY	TITLE OF DRAWING
DATE	Feb. 1980	SCALE	AS SHOWN
DRAWING NO.			RIVER CANALIZATION CROSS SECTION (10-1)
MVS-D 016			
JAPAN INTERNATIONAL COOPERATION AGENCY			


STA. 0+400





STA. 0+500



STA. 0+600




STA. 0+700




MINISTRY OF PUBLIC WORKS			
TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES			
MANILA PHILIPPINES			
MAYON VOLCANO			
SABO AND FLOOD CONTROL PROJECT			
CHECKED BY	DESIGNED BY	DRAWN BY	TITLE OF DRAWING
DATE	SCALE		RIVER CANALIZATION
Feb. 1980	AS SHOWN		CROSS SECTION (10-2)
DRAWING NO. M.V.S-0 017			
JAPAN INTERNATIONAL COOPERATION AGENCY			


STA. 0+800





STA. 0+900



STA. 1+000




STA. 1+100




MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MANILA, PHILIPPINES			
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT			
CHECKED BY	DESIGNED BY	DRAWN BY	TITLE OF DRAWING
DATE	Feb, 1980	SCALE	AS SHOWN
DRAWING NO.	M.V.S-D 018		RIVER CANALIZATION CROSS SECTION (10-3)
JAPAN INTERNATIONAL COOPERATION AGENCY			


STA. 1+200





STA. 1+300



STA. 1+400




STA. 1+500




MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MANILA, PHILIPPINES			
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT			
CHECKED BY	DESIGNED BY	DRAWN BY	TITLE OF DRAWING
DATE	SCALE	AS SHOWN	RIVER CANALIZATION CROSS SECTION (10-4)
Feb. 1980			
DRAWING NO.	M.V.S-D 019		
JAPAN INTERNATIONAL COOPERATION AGENCY			


STA. 1+600





STA. 1+700



STA. 1+800




STA. 1+900




MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MANILA, PHILIPPINES			
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT			
CHECKED BY	DESIGNED BY	DRAWN BY	TITLE OF DRAWING
DATE	Feb. 1980	SCALE	AS SHOWN
DRAWING NO.	M.V.S - D 020	RIVER CANALIZATION CROSS SECTION (10-5)	
JAPAN INTERNATIONAL COOPERATION AGENCY			


STA. 2+000




STA. 2+100



STA. 2+200




STA. 2+300




MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MANILA, PHILIPPINES			
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT			
CHECKED BY	DESIGNED BY	DRAWN BY	TITLE OF DRAWING
DATE	Feb. 1980	SCALE	AS SHOWN
DRAWING NO.	M.V.S-D 021		RIVER CANALIZATION, CROSS SECTION (10-6)
JAPAN INTERNATIONAL COOPERATION AGENCY			


STA. 2+400




STA. 2+500



STA. 2+600




STA. 2+700




MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MANILA . PHILIPPINES			
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT			
CHECKED BY	DESIGNED BY	DRAWN BY	TITLE OF DRAWING RIVER CANALIZATION CROSS SECTION (10-7)
DATE	Feb. 1980	SCALE	
	AS SHOWN		
DRAWING NO.	M.V. 5 - D 022		
JAPAN INTERNATIONAL COOPERATION AGENCY			


STA. 2+800




STA. 2+900



STA. 3+000




STA. 3+100




MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MANILA . PHILIPPINES			
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT			
CHECKED BY		DESIGNED BY	
DATE		SCALE	
Feb. 1980		AS SHOWN	
DRAWING NO.		TITLE OF DRAWING	
M.V.S - D 023		RIVER CANALIZATION CROSS SECTION (10-8)	
JAPAN INTERNATIONAL COOPERATION AGENCY			


STA. 3+200




STA. 3+300



STA. 3+400




STA. 3+500




MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MANILA, PHILIPPINES			
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT			
CHECKED BY	DESIGNED BY	DRAWN BY	TITLE OF DRAWING
DATE	Feb. 1980	SCALE	AS SHOWN
DRAWING NO.	M.V.S-D	024	RIVER CANALAZITION CROSS SECTION (10-9)
JAPAN INTERNATIONAL COOPERATION AGENCY			


STA. 3+600





STA. 3+700



STA. 3+800




STA. 3+900




MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MANILA, PHILIPPINES			
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT			
CHECKED BY	DESIGNED BY	DRAWN BY	TITLE OF DRAWING
DATE	Feb. 1980	SCALE	RIVER CANALIZATION
DRAWING NO.	M.V.S-D 025	AS SHOWN	CROSS SECTION (10-10)
JAPAN INTERNATIONAL COOPERATION AGENCY			


STA.0+000 ~ STA.1+100




STA.1+100 ~ STA.2+300



STA.2+300 ~ STA.3+700



TYPICAL CROSS SECTION



MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MANILA . PHILIPPINES			
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT			
CHECKED BY	DESIGNED BY	DRAWN BY	TITLE OF DRAWING RIVER CANALIZATION TYPICAL CROSS SECTION
DATE Feb. 1990	SCALE AS SHOWN		
DRAWING NO M.V.S-D 026			
JAPAN INTERNATIONAL COOPERATION AGENCY			





TABLE OF DIMENSION				
Section	B	H	L	Remarks
Sta. 0+000 ~ Sta. 1+100 (Future Extension)	5,750	1,300	8,887	
Sta. 1+100 ~ Sta. 2+300 (R ₁ , L ₁)	5,250	1,100	8,348	
Sta. 2+300 ~ Sta. 3+900 (R ₂ , R ₂ , L ₂)	5,000	1,000	8,079	



MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MANILA, PHILIPPINES			
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT			
CHECKED BY	DESIGNED BY	DRAWN BY	TITLE OF DRAWING
DATE	Feb. 1980	SCALE	AS SHOWN
DRAWING NO.	M.V.S-D 027		RIVER CANALIZATION STRUCTURAL DETAIL OF LEVEE
JAPAN INTERNATIONAL COOPERATION AGENCY			










TABLE OF DIMENSION

Section	H	B ₁	B ₂	B ₃
Sta. 0+000 ~ Sta. 1+100	1,300	48,500	5,750	2,550
Sta. 1+100 ~ Sta. 2+300	1,100	49,500	5,250	3,050
Sta. 2+300 ~ Sta. 3+700	1,000	50,000	5,000	3,300




DETAILS OF CROSS CONCRETE BLOCK


MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MANILA, PHILIPPINES			
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT			
CHECKED BY	DESIGNED BY	DRAWN BY	TITLE OF DRAWING
DATE	SCALE	AS SHOWN	RIVER CANALIZATION STRUCTURAL DETAIL OF GROUNTSILL
DRAWING NO. MVS-D-028			JAPAN INTERNATIONAL COOPERATION AGENCY




P L A N



A-A SECTION



P R O F I L E



MINISTRY OF PUBLIC WORKS TASK FORCE FOR FLOOD CONTROL AND RELATED ACTIVITIES MANILA, PHILIPPINES			
MAYON VOLCANO SABO AND FLOOD CONTROL PROJECT			
CHECKED BY	DESIGNED BY	DRAWN BY	TITLE OF DRAWING
DATE	SCALE	AS SHOWN	RIVER CANALIZATION
DRAWING NO.	M.V.S-D 029		IRRIGATION INTAKE
JAPAN INTERNATIONAL COOPERATION AGENCY			

