













LEGEND				
18speedbudsestoj	Boundary of sub-area K			
	Boundary of catchment			
	Flow direction			
(A) (B)	nill			
и и и и и и	Paddy field			
	Estimated built-up area by the year 2020			
①→ 0.51	Proposed lateral canals (): Canal No. 0.51: Design discharge in m3/sec			
1 →	Proposed culverts crossing the Route 13 [I]: Culvert No.			

Canal No.	Length (m)	Width (m)	Height (#)	51ope (0/00)	Copacity (m3/m)	Design Discharge
1	370	0.60	0.80	2.70	0.60	0.51
2	390	0.80	0.00	1.50	0.88	0.68
-3	270	i.00	1.00	1.50	1.24	1.08
4	230	0.70	0.70	1.50	0.48	0.39
5	230	1.30	1.30	1.50	2.50	
.6	310	0.60	0.60	1.50	0.32	0.56
				Design		
Culvert	Length	width	Height	Discharge	.	
No.	(m)	(n)	(m)	(n3/s)		
3	30	1.25	1.75	1.42		
. 2	20	1.50	1.50	2.26		
3	20	1.00	1.00	0.26	•	
	Remarks:	(1) Doth	canal and	culvert	are rect	angular.
		(2) Diner	ision is	described	in inner	size.

Fig. 9.1 Proposed Plan of Lateral Canals in System for Sub-area K

LAO PEOPLE'S DEMOCRATIC REPUBLIC
FEASIBILITY STUDY ON IMPROVEMENT
OF DRAINAGE SYSTEM IN VIENTIANE
JAPAN INTERNATIONAL COOPERATION AGENCY





