

THE GOVERNMENT OF THE REPUBLIC OF INDONESIA

THE STUDY ON URBAN DRAINAGE
AND
WASTEWATER DISPOSAL PROJECT
IN
THE CITY OF JAKARTA

FEASIBILITY STUDY
SUPPORTING REPORT

MARCH 1991

JAPAN INTERNATIONAL COOPERATION AGENCY

SSS

~~OR(5)~~

91-012

THE STUDY ON URBAN DRAINAGE AND
WASTEWATER DISPOSAL PROJECT IN THE CITY OF JAKARTA

FEASIBILITY STUDY
SUPPORTING REPORT

50

JICA LIBRARY



1089791 [6]

2224⁰

THE GOVERNMENT OF THE REPUBLIC OF INDONESIA

**THE STUDY ON URBAN DRAINAGE
AND
WASTEWATER DISPOSAL PROJECT
IN
THE CITY OF JAKARTA**

**FEASIBILITY STUDY
SUPPORTING REPORT**

MARCH 1991

JAPAN INTERNATIONAL COOPERATION AGENCY

国際協力事業団

22230

TABLE OF CONTENTS

	Page
Table of Contents	i
List of Tables	v
List of Figures	xi

I. URBAN DRAINAGE

I-1 CENGKARENG WEST URBAN DRAINAGE

Chapter 1 Project Area	
1.1 General	I-1
1.2 Existing and Future Land Use	I-2
1.3 Objective Drainage Basin	I-3
Chapter 2 Flood and Flood Damages	
2.1 Flood Conditions	I-11
2.2 Flood Damage	I-11
Chapter 3 Drainage Improvement Plan	
3.1 Design Flood Discharge	I-20
3.2 Design Boundary Water Level	I-23
3.3 Alternative Studies for Drainage Basin (A)	I-26
3.4 Alternative Studies for Drainage Basin (B)	I-28
3.5 Alternative Studies for Drainage Basin (C and D)	I-31
3.6 Alternative Studies for Drainage Basin (E)	I-34
3.7 Proposed Drainage Improvement Plan	I-38
Chapter 4 Cost Estimation and Implementation Schedule	
4.1 Basis of Cost Estimation	I-67
4.2 Unit Construction Cost	I-67
4.3 Estimate Project Cost	I-68
4.4 Operation and Maintenance Cost	I-69
4.5 Implementation Schedule	I-69

Chapter 5 Project Evaluation	
5.1 Economic Benefits and Costs	I-79
5.2 Project Evaluation	I-80
5.3 Environmental Assesment	I-81

I-2 SEPAK RIVER IMPROVEMENT

Chapter 1 Project Area	
1.1 General	I-99
1.2 Existing Drainage System	I-99
Chapter 2 Flood and Flood Damages	
2.1 Flood Conditions	I-102
2.2 Flood Damages	I-102
Chapter 3 Proposed River Improvement	
3.1 Objective River Section	I-107
3.2 Design Flood Discharge	I-107
3.3 Proposed River Profile and Cross Section	I-107
3.4 Proposed Construction Works and Land Acquisition	I-108
Chapter 4 Cost Estimaete	I-113

I-3 BOJONG DRAINAGE IMPROVEMENT

Chapter 1 Project Area	
1.1 General	I-116
1.2 Existing Drainage System	I-116
Chapter 2 Flood and Flood Damages	
2.1 Flood Conditions	I-123
2.2 Flood Damages	I-123
Chapter 3 Drainage Improvement Plan	
3.1 Assessment of Existing Drainage Capacity	I-130
3.2 Proposed Channel Improvement Plan	I-131
Chapter 4 Cost Estimate	I-140

I-4 MARUYA ILIR DRAINAGE IMPROVEMENT

Chapter 1	Project Area	I-141
Chapter 2	Flood and Flood Damages	
2.1	Flood Conditions.....	I-143
2.2	Flood Damages.....	I-143
Chapter 3	Drainage Improvement Plan	
3.1	Existing Drainage System	I-150
3.2	Existing Flow Capacity of Channel and Culvert	I-150
3.3	Proposed Drainage Improvement Plan	I-151
3.4	Proposed Construction Works and Land Acquisition	I-153
Chapter 4	Cost Estimate	I-164

II. SEWERAGE

Chapter 1	SEWERAGE SERVICE AREA	
1.1	General	II-1
1.2	Division of Sewerage Zone	II-1
1.3	Conventional and Interceptor Areas	II-3
Chapter 2	DESIGN WASTEWATER DISCHARGE	
2.1	Specific Wastewater Generation	II-10
2.2	Design Wastewater Discharge	II-10
Chapter 3	ALTERNATIVE STUDY OF TREATMENT PLANT	
3.1	General	II-15
3.2	Design Criteria	II-15
3.3	Alternative Plan A	II-16
3.4	Alternative Plan B	II-17
3.5	Alternative Plan C	II-18
3.6	Conclusion	II-19
Chapter 4	ALTERNATIVE STUDY OF CONVEYANCE SEWER ROUTE	
4.1	Optimum Construction Method	II-25
4.2	Selection of Alternative Route	II-26

4.3	Alternative A	II-27
4.4	Alternative B	II-28
4.5	Comparative Evaluation	II-30
Chapter 5	PROPOSED SEWERAGE DEVELOPMENT PLAN	
5.1	Collection System	II-37
5.2	Conveyance Sewer	II-38
5.3	Treatment Plant	II-39
Chapter 6	PROJECT AND COST ESTIMATE	
6.1	Costruction Plan	II-65
6.2	Project Cost Estimate	II-68
Chapter.7	IMPLEMENTATION PROGRAMME	
7.1	Project Phasing	II-102
7.2	Implementation Programme	II-107
7.3	Disbursement Schedule	II-108
Chapter 8	ECONOMIC, SOCIAL AND ENVIRONMENTAL EVALUATION	
8.1	Nos. of Beneficiaries	II-114
8.2	Reduction of Pollution Load	II-115
8.3	Reduction of Waterborne Disease	II-117
8.4	Environmental Assesment	II-118
Chapter 9	FINANCIAL EVALUATION	
9.1	People's Willingness to Pay	II-145
9.2	Sewerage Service Charge of JSSP	II-146
9.3	Affordability and Contribution of High Rise Building	II-147
9.4	Proposed Sewerage Charges	II-149
9.5	Financial Analysis	II-151
Chapter 10	INSTITUTIONAL ASPECTS	
10.1	Existing Status of Institutional Aspects of JSSP	II-197
10.2	Basic Philosophy of PDAL Jakarta	II-198
10.3	Proposed Institutional Aspects	II-199

LIST OF TABLES

	Page
I. URBAN DRAINAGE	
I-1 CENGKARENG WEST URBAN DRAINAGE	
Chapter 1 PROJECT AREA	
Table 1.1.1 Main Features of Existing Drainage System	I-5
Chapter 2 FLOOD AND FLOOD DAMAGES	
Table 1.2.1 Estimated Number of Properties in Inundation Area	I-14
Table 1.2.2 Estimated Number of Vehicles on Road by Type and by Inundation Area	I-15
Table 1.2.3 Average Annual Flood Damages by Inundation Area	I-16
Table 1.2.4 Summary of Estimated Average Annual Flood Damages ("Without Project" Case)	I-17
Chapter 3 DRAINAGE IMPROVEMENT PLAN	
Table 1.3.1 Design Discharge and Main Features of Proposed Channel	I-42
Table 1.3.2 Construction Cost for Alternative Plans	I-46
Table 1.3.3 Design Flood Discharge Distribution of Proposed Channel System	I-50
Table 1.3.4 Profile and Cross Section of Proposed Channel	I-51
Chapter 4 COST ESTIMATION AND IMPLEMENTATION SCHEDULE	
Table 1.4.1 Labour Cost, Rental Cost of Equipment and Material Cost	I-70
Table 1.4.2 Unit Construction Cost	I-72
Table 1.4.3 Break-down of Project Cost	I-73
Table 1.4.4 Direct Construction and Land Acquisition /Compensation Costs for Drainage Basin	I-74

Chapter 5 PROJECT EVALUATION

Table 1.5.1	Economic Costs of Cengkareng West Urban Drainage Project	I-91
Table 1.5.2	Cost Benefit Streams	I-92
Table 1.5.3	Cumulative Cost Benefit Streams	I-93
Table 1.5.4	Cumulative Cost Benefit Streams at Discount Rate of 10%	I-94
Table 1.5.5	Computation of NPV and B/C	I-95
Table 1.5.6	Computation of EIRR	I-95
Table 1.5.7	Environmental Impacts	I-96
Table 1.5.8	Negative Impacts and Management Measures	I-97

I-2 SEPAK RIVER IMPROVEMENT

Chapter 2 FLOOD AND FLOOD DAMAGES

Table 2.2.1	Estimated Number of Properties in Inundation Areas	I-103
Table 2.2.2	Estimated Number of Vehicles on Roads by Type by Inundation Area	I-104
Table 2.2.3	Summary of Estimated Average Annual Flood Damages ("Without Project" Case)	I-105

Chapter 4 COST ESTIMATE

Table 2.4.1	Break-down of Project Cost	I-114
Table 2.4.2	Direct Construction and Land Acquisition Cost	I-114

I-3 BOJONG DRAINAGE IMPROVEMENT

Chapter 2 FLOOD AND FLOOD DAMAGES

Table 3.2.1	Estimated Number of Properties in Inundation Areas	I-124
Table 3.2.2	Estimated Number of Vehicles on Road by Type and Inundation Area	I-125
Table 3.2.3	Average Annual Flood Damages by Inundation Area	I-126
Table 3.2.4	Summary of Estimated Average Annual Flood Damages	I-127

Chapter 3 DRAINAGE IMPROVEMENT PLAN

Table 3.3.1	Existing Flow Capacity of Drainage Channel	I-132
Table 3.3.2	Main Features of Proposed Channel	I-133

I-4 MARUYA ILIR DRAINAGE IMPROVEMENT

Chapter 2 FLOOD AND FLOOD DAMAGES

Table 4.2.1	Estimated Number of Properties in Inundation Areas	I-144
Table 4.2.2	Estimated Number of Vehicles on Road by Type and by Inundation Area	I-145
Table 4.2.3	Average Annual Flood Damages by Inundation Area	I-146
Table 4.2.4	Summary of Estimated Average Annual Flood Damages ("Without Project" Case)	I-147

Chapter 3 DRAINAGE IMPROVEMENT PLAN

Table 4.3.1	Existing Flow Capacity of Drainage Channel	I-155
Table 4.3.2	Break-down of Construction Works and Land Acquisition & Compensation by Channel	I-156

Chapter 4 COST ESTIMATE

Table 4.4.1	Break-down of Construction Cost	I-165
Table 4.4.2	Break-down of Direct Construction and Land Acquisition Cost by Channel	I-166

II. SEWERAGE

Chapter 1 SEWERAGE SERVICE AREA

Table 1.1	Service Area and Served Population	II-5
Table 1.2	Service Area and Served Population in 2000 by Sub-zone	II-6

Chapter 2 DESIGN WASTEWATER DISCHARGE

Table 2.1	Specific Wastewater Generation	II-13
Table 2.2	Design Wastewater Discharge by Sub-zone in 2000.....	II-14

Chapter 3 ALTERNATIVE STUDY OF TREATMENT PLANT

Table 3.1	Estimated Construction and O & M Costs of Three (3) Alternatives	II-20
-----------	---	-------

Chapter 4 ALTERNATIVE STUDY OF CONVEYANCE SEWER ROUTE

Table 4.1	Length of Main & Trunk Sewers of Each Alternative	II-31
Table 4.2	Length of Main & Trunk Sewers of Each Earth Covering Depth	II-31

Chapter 5	PROPOSED SEWERAGE DEVELOPMENT PLAN	
Table 5.1	Numbers of House Connection by Sub-zone	II-41
Table 5.2	Tertiary and Secondary Sewers in Sewerage Area	II-42
Table 5.3	Proposed Collection Sewer by Sub-zone	II-43
Table 5.4	Lift Pump Station at Kel. Jelambar Baru	II-44
Table 5.5	Proposed Conveyance Sewer	II-44
Table 5.6	Treatment Plant at Pluit Pond	II-45
Chapter 6	PROJECT AND COST ESTIMATE	
Table 6.1	Project Cost of Sewerage Development	II-70
Table 6.2	Breakdown of Direct Construction Cost	II-70
Table 6.3	Construction Cost of Secondary/Tertiary Sewer	II-71
Table 6.4	Construction Cost of Main/Trunk Sewer	II-72
Table 6.5	Construction Cost of Conveyance Sewer	II-73
Table 6.6	Construction Cost of Lift Pump Station	II-74
Table 6.7	Construction Cost of Treatment Plant	II-75
Table 6.8	Main Sewer Construction Cost by Sub-zone, by Diameter and by Earth Covering Depth	II-76
Table 6.9	Trunk Sewer Construction Cost by Sub-zone, by Diameter and by Earth Covering Depth	II-78
Table 6.10	Manhole Construction Cost by Sub-zone, by Diameter and by Earth Covering Depth	II-80
Table 6.11	Unit Construction Cost of Collection Sewer by Diameter and by Earth Covering Depth	II-82
Table 6.12	Breakdown of Collection Sewer Unit Cost.....	II-83
Table 6.13	Unit Construction Cost of Manhole by Diameter and by Manhole Height	II-95
Table 6.14	Labour Wages	II-96
Table 6.15	Rental Cost of Equipment	II-96
Table 6.16	Fuel and Materials Cost	II-97
Table 6.17	O&M Cost for Central Sewerage Zone	II-98
Table 6.18	Breakdown of O&M Cost for Central Sewerage Zone	II-99
Chapter 7	IMPLEMENTATION PROGRAMME	
Table 7.1	Alternative of Project Phasing	II-109
Table 7.2	Implementation Programme of Sewerage Development ...	II-110
Table 7.3	Disbursement Schedule	II-111

Chapter 8	ECONOMIC, SOCIAL AND ENVIRONMENTAL EVALUATION	
Table 8.1	Number of Properties in the Central Sewerage Zone in 1988	II-132
Table 8.2	Existing and Future Pollution Load as BOD by Pollution Sources in the Project Area	II-136
Table 8.3	Number of Properties in the Central Sewerage Zone in 2010	II-137
Table 8.4	Benefits in Terms of Reduction of Medical Costs	II-141
Table 8.5	Environmental Impacts	II-142
Table 8.6	Negative Impact and Management Measures	II-143
Chapter 9	FINANCIAL EVALUATION	
Table 9.1	Total Willingness to Pay of Households and Establishments/Institutions for Sewerage Services by Kelurahan in 1988	II-157
Table 9.2	Total Willingness to Pay of Households and Establishments/Intitutions for Sewerage Services by Kelurahan in 2010	II-159
Table 9.3	Total Wilingness to Pay for Sewerage Service by Type of Properties	II-161
Table 9.4	Tariff of Sewerage Discharge Services based on Floor Area	II-162
Table 9.5	Estimated Revenues from High Rise Buildings - Central Sewerage Zone	II-163
Table 9.6	Estimated Revenues from High Rise Buildings - Project Area	II-164
Table 9.7	Estimated Revenues from High Rise Buildings - JSSP Area	II-165
Table 9.8	Estimated Project Costs - Central Sewerage Zone	II-166
Table 9.9	Estimated Project Costs - Project Area	II-167
Table 9.10	Estimated Project Costs - JSSP Area	II-168
Table 9.11	Sewerage Charges per Unitary Discharges of Wastewater.....	II-169
Table 9.12	Proposed Preconditions and Assumptions for Financial Analysis.....	II-170

Table 9.13	Alternative Assumptions Case I for Financial Analysis	II-172
Table 9.14	Alternative Assumptions Case II for Financial Analysis	II-173
Table 9.15	Alternative Assumptions Case III for Financial Analysis ..	II-174
Table 9.16	Alternative Assumptions Case IV for Financial Analysis ...	II-176
Table 9.17	Financial Statement - Proposed Plan	II-178
Table 9.18	Financial Statement (Project Area) - Proposed Plan	II-181
Table 9.19	Financial Statement - Alternative Case I.....	II-184
Table 9.20	Financial Statement - Alternative Case II.....	II-187
Table 9.21	Financial Statement - Alternative Case III.....	II-190
Table 9.22	Financial Statement - Alternative Case IV.....	II-193

LIST OF FIGURES

		Page
I. URBAN DRAINAGE		
I-1 CENGKARENG WEST URBAN DRAINAGE		
Chapter 1	PROJECT AREA	
Fig.1.1.1	Location of Project Area	I-6
Fig.1.1.2	Existing Land Use of Project Area (1990)	I-7
Fig.1.1.3	Future Land Use of Project Area (2005)	I-8
Fig.1.1.4	Objective Drainage Basin	I-9
Fig.1.1.5	Existing Drainage System	I-10
Chapter 2	FLOOD AND FLOOD DAMAGES	
Fig.1.2.1	Habitual Inundation Area (Cengkareng West Urban Drainage)	I-18
Fig.1.2.2	Potential Inundation Area (Cengkareng West Urban Drainage)	I-19
Chapter 3	DRAINAGE IMPROVEMENT PLAN	
Fig.1.3.1	Longitudinal Section of Cengkareng Floodway	I-52
Fig.1.3.2	Location of Alternative Channel Improvement for Basin A & B.	I-53
Fig.1.3.3	Location of Alternative Channel Improvement for Basin C/D & E	I-54
Fig.1.3.4	Location of Proposed Channel Improvement	I-55
Fig.1.3.5	Design Flood Discharge Distribution of Proposed Channel	I-56
Fig.1.3.6	Profile and Cross Section of Tanjungan River	I-57
Fig.1.3.7	Profile and Cross Section of Kamal River	I-58
Fig.1.3.8	Profile and Cross Section of Proposed Padongkelan Channel	I-61
Fig.1.3.9	Profile and Cross Section of Proposed Kali Gede & Kali Bor Channel	I-62
Fig.1.3.10	Profile and Cross Section of Proposed Saluran Cengkareng Channel	I-63

Fig.1.3.11	Profile and Cross Section of Proposed New Channel of Basin (A)	I-64
Fig.1.3.12	Structure of Sluice Gate and Revetment	I-65
Fig.1.3.13	Structure of Highway Crossing	I-66
Chapter 5	PROJECT EVALUATION	
Fig.1.5.1	Location of Proposed Channel Improvement	I-98
I-2	SEPAK RIVER IMPROVEMENT	
Chapter 1	PROJECT AREA	
Fig.2.1.1	Location of Project Area	I-101
Chapter 2	FLOOD AND FLOOD DAMAGES	
Fig.2.2.1	Habitual and Potential Inundation Area (Sepak River Improvement)	I-106
Chapter 3	DRAINAGE IMPROVEMENT PLAN	
Fig.2.3.1	Profile and Cross Section of Proposed Kreo River	I-109
Fig.2.3.2	Profile and Cross Section of Sepak River	I-110
Fig.2.3.3	Profile and Cross Section of Kembangan River	I-111
Fig.2.3.4	Cross Section of Bank Protection, Inspection Road and Side Ditch	I-112
I-3	BOJONG DRAINAGE IMPROVEMENT	
Chapter 1	PROJECT AREA	
Fig.3.1.1	Location of Project Area	I-118
Fig.3.1.2	Original and Extended Housing Development Area	I-119
Fig.3.1.3	Existing Channel Networks	I-120
Fig.3.1.4	Existing Retarding Basin	I-121
Fig.3.1.5	Existing Pump Station	I-122
Chapter 2	FLOOD AND FLOOD DAMAGES	
Fig.3.2.1	Habitual Inundation Area (Bojong Drainage Improvement)	I-128
Fig.3.2.2	Potential Inundation Area (Bojong Drainage Improvement)	I-129

Chapter 3	PROPOSED RIVER IMPROVEMENT	
Fig.3.3.1	Design Flood Runoff Hydrograph at Bojong Area	I-134
Fig.3.3.2	Mass Curve Calculation of Pump Drainage	I-135
Fig.3.3.3	Profile of Proposed Channel	I-136
Fig.3.3.4	Structure of Proposed Open Channel and Pipe	I-139
I-4	MARUYA ILIR DRAINAGE IMPROVEMENT	
Chapter 1	PROJECT AREA	
Fig.4.1.1	Location of Project Area	I-142
Chapter 2	FLOOD AND FLOOD DAMAGES	
Fig.4.2.1	Habitual Inundation Areas (Maruya Ilir Drainage Improvement)	I-148
Fig.4.2.2	Potential Inundation Area (Maruya Ilir Drainage Improvement)	I-149
Chapter 3	DRAINAGE IMPROVEMENT PLAN	
Fig.4.3.1	Existing Drainage System	I-157
Fig.4.3.2	Proposed Drainage System	I-158
Fig.4.3.3	Profile and Cross Section of Proposed Channel	I-159
Fig.4.3.4	Location of Proposed Bridge and Inspection Road	I-162
Fig.4.3.5	Structure of Proposed Revetment and Bridge	I-163
II.	SEWERAGE	
Chapter 1	SEWERAGE SERVICE AREA	
Fig 1.1	Specific Wastewater Discharge Distribution and Sewerage Sub-Zones of Project Area.....	II-7
Fig.1.2	Divided Sewerage Sub-Zone.....	II-8
Fig.1.3	Delineated Conventional and Interceptor Area.....	II-9
Chapter 3	DESIGN WASTEWATER DISCHARGE	
Fig.3.1	Aerated Lagoon in the Pluit Pond (Alternative Plan A)	II-21
Fig.3.2	Aerated Lagoon in Kel. Kamal Muara (Alternative Plan B)	II-22

Fig.3.3	Aerated Lagoon in the Sea (Alternative Plan C)	II-23
Fig.3.4	Objective Facilities of Each Alternative Plan.....	II-24
Chapter 4	ALTERNATIVE STUDY OF CONVEYANCE SEWER ROUTE	
Fig.4.1	Alternative Plan A (Single Conveyance Sewer).....	II-32
Fig.4.2	Alternative Plan B (Double Conveyance Sewer).....	II-33
Fig.4.3	Profile of Single Conveyance Sewer (Alternative Plan A)	II-34
Fig.4.4	Profile of Western Conveyance Sewer (Alternative Plan B)	II-35
Fig.4.5	Profile of Eastern Conveyance Sewer (Alternative Plan B).....	II-36
Chapter 5	PROPOSED SEWERAGE DEVELOPMENT PLAN	
Fig.5.1	Location of Sample Sewer Design.....	II-46
Fig.5.2	Sewer Design in Typical Area Type A.....	II-47
Fig.5.3	Sewer Design in Typical Area Type B	II-48
Fig.5.4	Sewer Design in Typical Area Type C.....	II-50
Fig.5.5	Proposed Lift Pump Station.....	II-51
Fig.5.6	Proposed Conveyance Sewer Alignment.....	II-54
Fig.5.7	Profile of Conveyance Sewer.....	II-55
Fig.5.8	Proposed Inflow Pump Station.....	II-56
Fig.5.9	Layout of Treatment Plant of Central Zone.....	II-60
Fig.5.10	Flow-Diagram and Water-Level of Pluit Treatment Plant.....	II-61
Fig.5.11	Layout of Pump Station and Control Building.....	II-62
Fig.5.12	Layout of Drying Bed.....	II-63
Fig.5.13	Typical Section of Embankment of Aerated Lagoon	II-64
Chapter 6	PROJECT AND COST ESTIMATE	
Fig.6.1	Boring Location.....	II-100
Fig.6.2	Geological Profile.....	II-101
Chapter 7	IMPLEMENTATION PROGRAMME	
Fig.7.1	Service Area in the First Phase of Alternative A.....	II-112
Fig.7.2	Service Area in the First Phase of Alternative B.....	II-113

Chapter 8	ECONOMIC, SOCIAL AND ENVIRONMENTAL EVALUATION	
Fig.8.1	Location of Project Area	II-144
Chapter 9	FINANCIAL EVALUATION	
Fig.9.1	Location of High Rise Buildings in the Central Sewerage Zone in 1990.....	II-196
Chapter 10	INSTITUTIONAL ASPECTS	
Fig.10.1	Proposed Organizational Structure of PDAL Jakarta.....	II-205

I. URBAN DRAINAGE

I - 1

CENKARENG WEST URBAN DRAINAGE

I. URBAN DRAINAGE

I-1 CENGKARENG WEST URBAN DRAINAGE

Chapter 1 PROJECT AREA

1.1 General

The Project Area covers the north west low-lying area of Jakarta City with an area of 4,700 ha. It is encompassed by the administrative boundary of DKI Jakarta to the west, Mookervart River to the south and Cengkareng Floodway to the east (See Fig. 1.1.1). The following eight (8) Kelurahan are included in the Project Area.

- Kamal Muara, Kamal, Tegal Alur, Pegadungan, Kali Deres, Cengkareng Timur, Kapuk and Cengkareng Barat

The population of the Project Area was estimated to be 263,281 in 1988. It is expected to increase to 455,740 in 2010.

The Project Area is undergoing a rapid land development. The on-going major land development projects are :

- (1) Padongkelan Barat Housing Development by PERUM PERUMNAS: 340 ha
- (2) Taman Kencana Housing Development by Private Company: 55 ha
- (3) Taman Surya Housing Development by Private Company: 30 ha
- (4) Citra Garden Housing Development by Private Company: 80 ha
- (5) Mandar Permai Resort Area Development by Private Company: 430 ha

Location of the above development areas are shown in Fig.1.1.2.

The urban land developments will increase properties in the flood prone areas on one hand and on the other hand, will increase flood runoff peak of the drainage basin. It will results n creation of new flood problems.

New urban drainage system shall be constructed in advance of such urban developments to cope with expected new flood problems in the future.

1.2 Existing and Future Land Use

The existing land use pattern of the Project Area is classified into four (4) categories : residential area, commercial & institutional area, industrial area and green area based on the map of "Atlas DKI Jakarta" published in 1990 as shown in Fig. 1.1.2.

Land area of the respective categories are shown below.

Land Use	Area (ha)	Ratio (%)
Residential	1,410	30
Commercial & Institutional	705	15
Industrial	235	5
Green	2,350	50
Total	4,700	100

The future land use pattern in 2005 were estimated in DKI Jakarta Structure Plan 2005. In the Structure Plan, the future land use is classified into 13 categories as shown in Fig 1.1.3.

Those detailed future land classifications are summarized as follows.

Land Use	Area (ha)	Ratio (%)
Residential	2,350	50
Commercial & Institutional	705	15
Industrial	470	10
Green	1,175	25
Total	4,700	100

Urban land area including residential, commercial & institutional and industrial ones of the Project Area will increase from 2,350 ha or 50% in 1990 to 3,525 ha or 75% in 2005.

1.3 Objective Drainage Basin

The southern fringe area of 570 ha in the Project Area, which is located along the Mookervart River, drains directly into the Mookervart River through the existing minor drainage networks. No significant flood problems are identified in this area at present. It is considered that this area will be free from flooding even in future due to its advantageous topographical conditions. Hence, this area is excluded from the objective drainage basin.

Moreover, the Mandar Permai Resort Development Area of 430 ha, which is located in the north east fringe of the Project Area, is also excluded from the objective drainage basin. It is because this area will be provided with an independent drainage system by the developer and storm water of the area will be discharged directly into the Jakarta Bay.

Based on the above considerations, the objective drainage basin of 3,800 ha for drainage planning is delineated as shown in Fig 1.1.4.

The objective drainage basin is divided into five (5) sub-drainage basins based on the existing drainage system (See Fig. 1.1.5).

- (1) Drainage basin A covers a catchment area of 777 ha. Storm water is drained directly into the Jakarta Bay through the Tanjungan River with a total length of 3.2 km. The river width is in the range of 2 m and 5 m. The river gradient is approximately 1/3,000.
- (2) Drainage basin B drains a catchment area of 1,637 ha of the Kamal River and its tributaries also into the Jakarta Bay. The total river length is 11.8 km. The river width ranges from 3 m to 18 m. The river gradient is 1/2,000 - 1/3,000.
- (3) Drainage basin C consists of the channels of Kali Gede and Kali Bor. Storm water of the basin of 563 ha is drained into the Mookervart River. The total river length is 4.8 km. The river width and slope are 2-4 m and 1/2,000 respectively.

- (4) Drainage basin D covers a catchment area of 331 ha of the Saluran Cengkareng channel. Storm water is drained into the Cengkareng Floodway through the Padongkelan channel of the drainage basin E. Total length of the Saluran Cengkareng channel is 4.5 km. Its river width and slope is 2-6 m and 1/2,000 respectively.
- (5) Drainage basin E drains a catchment area of 515 ha of the Padongkelan channel into the Cengkareng Floodway. Most part of the basin is undergoing housing development. A sluice gate is provided at the confluence to the Cengkareng Floodway to control backwater of the Cengkareng Floodway. Total length of the Padongkelan channel is 1.1 km. Its river width and gradient is 2-5 m and 1/2,000 respectively.


The above five (5) drainage basins and five (5) channels are further divided into 15 sub-basins and 18 channel sections respectively as shown in Fig. 1.1.5.

The main features the existing drainage system are summarized in Table 1.1.1.


Table 1.1.1

Main Features of Existing Drainage System

River Reaches	Catchment Area (ha)	River Length (km)	River Width (m)	River Gradient
Drainage System A				
Tanjungan R. (a0-a3)	777	3.15	2-5	1:3,000
Drainage System B				
Upper Kamal R. (b1-b2)	464	2.30	3-10	1:2,000
Middle Kamal R. (b2-b5)	590	3.18	10-14	1:3,000
Lower Kamal R. (b5-b6)	184	1.88	14-18	1:3,000
Right Tributary (b7-b3)	152	1.60	3-4	1:3,000
Left Tributary (b8-b2)	247	2.80	4-10	1:3,000
Total	1,637	11.76		
Drainage System C				
Kali Gede R. (c0-c2)	563	3.43	2-4	1:2,000
Kali Bor R. (c2-c4)	0	1.33	4	1:2,000
Total	563	4.76		
Drainage System D				
Upper Saluran Cengkareng (d0-d1)	139	1.65	2-4	1:2,000
Lower saluran Cengkareng (d1-d2)	192	2.88	4-6	1:2,000
Total	331	4.53		
Drainage System E				
Padongkelan R. (e2-e4)	515	1.14	2-5	1:2,000
Total	3,813	25.34		



THE STUDY ON URBAN DRAINAGE AND WASTE WATER DISPOSAL PROJECT IN THE CITY OF JAKARTA




LEGENDA

	PERUMAHAN DAN FASILITASNYA = Residences and its Facilities		CAMPURAN PERUMAHAN / BANGUNAN UMUM = Residence & Public Building Mixed		INDUSTRI / PERGUDANGAN K D B RENDAH = Industry / Store House
	FASILITAS UMUM = Public Facilities		CAMPURAN PERUMAHAN / INDUSTRI KECIL = Residence & Small Industry Mixed		PERUMAHAN K D B RENDAH = Housing / Residence (B B C)
	PEMERINTAHAN = Government		CAMPURAN INDUSTRI / BANGUNAN UMUM = Residence & Small Industry Mixed		HIJAU TANPA BANGUNAN = Green Belt
	JASA / KOMERSIL / PERKANTORAN = Service / Commercial / Office		BANGUNAN UMUM / K D B RENDAH = Public Building (Building Base Coefficient)		SALURAN AIR / WADUK = Channel / Reservoir
	INDUSTRI = Industries				

FIG. 1.1.2

EXISTING LAND USE OF PROJECT AREA(1990)

THE STUDY ON URBAN DRAINAGE AND WASTE WATER DISPOSAL PROJECT IN THE CITY OF JAKARTA



LEGENDA

	PERUMAHAN DAN FASILITASNYA = Residences and its Facilities		CAMPURAN PERUMAHAN / BANGUNAN UMUM = Residence & Public Building Mixed		INDUSTRI / PERGUDANGAN K D B RENDAH = Industry / Store House
	FASILITAS UMUM = Public Facilities		CAMPURAN PERUMAHAN / INDUSTRI KECIL = Residence & Small Industry Mixed		PERUMAHAN K D B RENDAH = Housing / Residence (B B C)
	PEMERINTAHAN = Government		CAMPURAN INDUSTRI / BANGUNAN UMUM = Residence & Small Industry Mixed		HIJAU TANPA BANGUNAN = Green Belt
	JASA / KOMERSIL / PERKANTORAN = Service / Commercial / Office		BANGUNAN UMUM / K D B RENDAH = Public Building (Building Base Coefficient)		SALURAN AIR / WADUK = Channel / Reservoir
	INDUSTRI = Industries				

FIG. 1.1.3

FUTURE LAND USE OF PROJECT AREA (2005)

THE STUDY ON URBAN DRAINAGE AND WASTE WATER DISPOSAL PROJECT IN THE CITY OF JAKARTA





FIG. 1.1.4

OBJECTIVE DRAINAGE BASIN

THE STUDY ON URBAN DRAINAGE AND WASTE WATER DISPOSAL PROJECT IN THE CITY OF JAKARTA



Length of Drainage Channel

Basin	Route	Length(km)	
		Existing	New Channel
A	a0-a1	1.10	
	a1-a2	0.45	
	a2-a3	1.60	
	a4-a2		1.70
	a5-a4		2.20
Sub Total		3.15	4.00
B	b0-b1		0.60
	b1-b2	2.30	
	b2-b3	1.00	
	b3-b4	0.30	
	b4-b5	1.88	
	b5-b6	1.88	
	b7-b3	(1.60)	
	b8-b2	(2.80)	
	Sub Total	11.76	0.60
	C	c0-c1	1.95
c1-c2		1.48	
c2-c3		0.45	
c3-c4		0.88	
Sub Total		4.76	
D	d0-d1	1.65	
	d1-d2	2.80	
	Sub Total	4.53	
	Sub Total		
E	e1-e1		0.75
	e1-e2		1.00
	e2-e3	0.95	
	e3-e4	0.10	
	Sub Total	1.05	1.75
Total	20.94	6.43	

Catchment Area of Sub Basin

Basin	Sub-basin	Area(km ²)
A	A-1	1.9
	A-2	1.41
	A-3	2.11
	A-4	2.35
	Sub Total	7.77
	B	B-1
	B-2	2.47
	B-3	2.18
	B-4	1.52
	B-5	3.72
	B-6	1.84
Sub Total		16.37
C	C-1	3.32
	C-2	2.31
Sub Total		5.63
D	D-1	1.39
	D-2	1.92
	Sub Total	
E	Sub Total	5.15
	TOTAL	38.23

FIG. 1.1.5 EXISTING DRAINAGE SYSTEM

THE STUDY ON URBAN DRAINAGE AND WASTE WATER DISPOSAL PROJECT IN THE CITY OF JAKARTA

Chapter 2 FLOOD AND FLOOD DAMAGES

2.1 Flood Conditions

An on-the-spot interview survey was conducted to know the flood conditions of the Project Area. It was found out that there are 10 potential inundation areas, out of which six (6) areas are habitually inundated. The total hectareage of the potential inundation areas reaches 474.3 ha, while that of the habitual inundation areas comes to 273.4 ha.

The depth of inundation in the potential inundation areas ranges from 30 cm to 60 cm, and the duration of inundation in the same areas falls between one (1) day to 10 days. In the habitual inundation areas, inundation depth and duration are 20 to 50 cm, and one (1) to seven (7) days, respectively. (Refer to Fig. 1.2.1 and 1.2.2)

Habitual flooding occurs twice a year on average, while the return period of potential flooding is estimated at approximately 40 years.

2.2 Flood Damage

2.2.1 Methodology for Estimation of Average Annual Flood Damages

The steps to arrive at the estimation of average annual flood damages are presented in Appendix B, Supporting Report of Master Plan. Firstly inundation areas by return period are determined through the past inundation maps and on-the-spot interview survey. Also, based on such a survey, average inundation depth and duration by return period and by inundation area are estimated.

Secondly, based on the survey results, the quantitative relationships between inundation depth/duration and direct flood damage ratio by type of property are established.

Thirdly, the relationships between return period and inundation depth/duration are formulated. It means that the relationships between return period and inundation depth/duration by inundation area are

established. Also, it means that the relationships between return period and flood damage ratio by type of property and inundation area are established.

Fourthly, average unit value of property by type in 1988 and 2010 is estimated. At the same time, the number of property by type and by inundation area in 1988 and 2010 is estimated.

Fifthly, the third and fourth steps are combined together. Employing probability density functions, average annual flood damages to property by inundation area in 1988 and 2010 are estimated. Eventually, average annual flood damages to property in the Project Area in the two (2) years are worked out (for details ref. Appendix B, Supporting Report of Master Plan).

Average annual flood damages in terms of income losses due to the closure of shops and factories in time of floods are estimated in the same manner.

As the third component, flood damages to traffic is significant. In time of floods, the drivers of vehicles are usually forced to slow down their vehicle operating speed. Unit vehicle operating cost rises as the speed is lessened. Also, it takes a longer time for a driver to reach destination due to lower speed and/or round-about routes he is forced to take.

That is to say, incremental vehicle operating cost and time cost will be incurred when flood hits the Project Area. From the average traffic damages per vehicle by type and the number of vehicles on road by type by inundation area in 1988 and 2010, traffic damages by type of vehicles by inundation area in the two (2) years will be estimated (ref. Appendix B, Supporting Report of Master Plan).

Besides the above-mentioned three kinds of flood damages, flood damages to unspecified property and infrastructure were taken into account using fixed coefficients.

2.2.2 Average Annual Flood Damages

The number of property by type and by inundation area for 1988 and 2010 is shown in Table 1.2.1. The figures for 2010 were estimated based on the land use plan and economic forecast. Also, the number of vehicles by type and by inundation area for the two (2) years is shown in Table 1.2.2. The figures for 2010 are projected based on the economic forecast.

As Table 1.2.3 shows, average annual flood damages in terms of direct damages to properties amount to Rp. 999 million as of 1988. Likewise, income losses due to shop closure and damage to traffic amount to Rp. 12 million and Rp. 8 million, respectively. In the target year of 2010, direct damages to properties will reach Rp. 5,352 million. Similarly, income losses and traffic damages will reach Rp. 124 million and Rp. 29 million, respectively. It is to be noted that flood damages are estimated to increase by five (5) to 10 times from 1988 to 2010.

As is shown in Table 1.2.4, average annual flood damages as of 1988 are estimated at Rp. 1,262 million, which would multiply by 5.6 times to Rp. 7,085 million in 2010 if no urban drainage projects were implemented.

Table 1.2.1 Estimated Number of Properties in Inundation Areas
- Cengkareng West Urban Drainage -

Inundation Area No.	House	Shop	Factory
1 Year 1988			
1	15	1	1
2	672	6	4
3	208	2	1
4	1,217	5	4
5	957	7	7
6	467	4	4
7	352	4	1
8	508	4	4
9	301	4	1
10	191	0	1
Total	4,888	37	28
2 Year 2010			
1	98	5	4
2	1,130	12	14
3	350	4	4
4	2,401	91	14
5	1,453	18	16
6	709	9	8
7	607	10	4
8	772	9	8
9	534	9	7
10	339	6	4
Total	8,393	173	84

Sources : Statistik Wilayah 1988 and JICA

Table 1.2.2 Estimated Number of Vehicles on Road by Type and by Inundation Area - Cengkareng West Urban Drainage -

Inundation Area No.	Passenger Car	Bus	Truck	Motor Cycle	Total
1 Year 1988					
1	13	4	6	25	49
2	53	18	23	102	197
3	17	6	7	32	61
4	199	68	86	382	735
5	47	16	20	91	174
6	23	8	10	44	85
7	44	15	19	85	163
8	25	9	11	48	93
9	19	7	8	37	71
10	12	4	5	23	45
Total	453	154	195	870	1,673
2 Year 2010					
1	39	19	21	79	158
2	159	76	85	322	642
3	49	24	26	100	199
4	592	285	316	1,203	2,396
5	141	68	75	286	569
6	69	33	37	139	278
7	132	63	70	267	533
8	75	36	40	152	302
9	57	27	31	116	231
10	36	17	19	74	147
Total	1,348	648	720	2,739	5,455

Sources : Statistik Wilayah 1988 and JICA

Table 1.2.3 Average Annual Flood Damages by Inundation Area
- Cengkareng West Urban Drainage -

(Unit : Rp.)

Inundation Area No.	Direct Damages to Properties *	Income Losses due to Shop Closure **	Damages to Traffic
1 Year 1988			
1	7,641,000	707,000	229,000
2	55,461,000	877,000	929,000
3	0	95,000	288,000
4	779,666,000	6,093,000	3,467,000
5	92,247,000	2,709,000	823,000
6	43,054,000	1,059,000	402,000
7	0	91,000	771,000
8	20,584,000	692,000	437,000
9	0	98,000	335,000
10	0	62,000	213,000
Total	998,653,000	12,482,000	7,894,000
2 Year 2010			
1	99,570,000	7,184,000	832,000
2	232,089,000	7,559,000	3,378,000
3	0	827,000	1,047,000
4	4,410,645,000	82,034,000	12,599,000
5	365,171,000	14,622,000	2,991,000
6	166,975,000	5,712,000	1,460,000
7	0	699,000	2,801,000
8	77,673,000	3,716,000	1,589,000
9	0	1,299,000	1,217,000
10	0	825,000	773,000
Total	5,352,123,000	124,477,000	28,687,000

Note : * Related properties : house, shop and factory

** Related properties : shop and factory

Source : JICA

Table 1.2.4 Summary of Estimated Average Annual Flood Damages
 ("Without Project" Case) - Cengkareng West Urban Drainage -

(Unit : Rp.)


Item	1988	2010
1 Direct Damages to Property		
1) House	934,091,000	4,416,614,000
2) Shop	14,154,000	499,171,000
3) Factory	50,407,000	436,338,000
4) Other Specified Property ^{1/}	31,712,000	392,072,000
Sub-Total	1,030,364,000	5,744,195,000
2. Indirect Damages		
1) Income Losses due to Shop Closure		
(1) Shop	926,000	32,671,000
(2) Factory	11,555,000	91,805,000
(3) Other Specified Property ^{2/}	837,000	7,120,000
Sub-Total	13,318,000	131,596,000
2) Traffic Damages		
(1) Time Cost	2,373,000	8,492,000
(2) Incremental VOC	5,520,000	20,195,000
Sub-Total	7,893,000	28,687,000
Total (1.+2.)	1,051,575,000	5,904,478,000
3. Damages to Other Unspecified Property Including Infrastructure		
(1. + 2.) x 20 %	210,315,000	1,180,896,000
Grand Total (1.+2.+3.)	1,261,890,000	7,085,374,000

Note : ^{1/}: Hotel, Restaurant, Hospital, Office, School, (Primary, Junior General Hight & High) and Religious Facilities (Mosque, Church & Temple)

^{2/}: Hotel, Restaurant and Hospital

Damages to other specified property were estimated based on the ratios between the number of shops/factories and that of other specified property.

Source : JICA





	Depth (m)	Area (ha)	Duration
1	0.3	20.3	2 days
2	0.3	40.5	4 hours
4	0.5	133.6	7 days
5	0.2	44.5	1 day
6	0.2	20.3	1 day
8	0.2	14.2	5 hours

FIG. 1.2.1

HABITUAL INUNDATION AREA
(CENKARENG WEST URBAN DRAINAGE)

THE STUDY ON URBAN DRAINAGE AND WASTE WATER DISPOSAL PROJECT IN THE CITY OF JAKARTA



	Depth (m)	Area (ha)	Duration
1	0.4	22.5	7 days
2	0.3	66.8	1 day
3	0.5	20.7	1 days
4	0.6	169.5	10 days
5	0.3	62.3	4 days
6	0.5	30.4	1 day
7	0.5	27.3	1 day
8	0.4	33.1	1 day
9	0.5	25.5	1 day
10	0.5	16.2	1 day

FIG. 1.2.2 POTENTIAL INUNDATION AREA (CENKARENG WEST URBAN DRAINAGE)

Chapter 3 DRAINAGE IMPROVEMENT PLAN

3.1 Design Flood Discharge

3.1.1 Design Flood Frequency

The design flood frequency of the urban drainage channels located outside the Banjir Canals is determined as shown below based on the guidelines of the Government of Indonesia (Refer to Appendix G, Supporting Report of Master Plan).

<u>Catchment Area (ha)</u>	<u>Frequency (Year)</u>
Less than 10	1
$10 < A < 100$	2
$100 < A < 500$	5
Greater than 500	10

While, the objective drainage basin is drained by five (5) existing drainage systems of which respective catchment areas are shown below (See Fig.1.1.5).

<u>Existing Drainage System</u>	<u>Catchment Area (ha)</u>
Basin A: Tanjungan River	777
Basin B: Kamal River	1,637
Basin C: Kali Gede/Kali Bor Channel	563
Basin D: Saluran Cengkareng Channel	331
Basin E: Padongkelan Channel	515
Total	3,823

The drainage systems of A, B, C and E cover a catchment area larger than 500 ha. Design flood frequency of 10-year is applied for these drainage systems. The 10-year flood frequency is also applied for the drainage system D although its catchment area is smaller than 500 ha. This is because the drainage systems of D and E are hydraulically connected.

3.1.2 Flood Run-off Calculation

(1) Calculation Method

Flood peak run-off of the objective urban drainage channels are calculated by using the following Rational Formula.

$$Q_p = \frac{1}{3.6} \cdot f \cdot ra \cdot A$$

Where,

Q_p : Flood peak run-off (m^3/s)

f : Run-off coefficient

ra : Basin average rainfall intensity during flood concentration time (mm/hr)

A : Catchment area (km^2)

(i) Run-off Coefficient (f)

The flood run-off coefficient varies according to the land use patterns of the basin. It is assumed as given below.

Residential Area : $f=0.50$

Commercial & Institutional Area : $f=0.70$

Industrial Area : $f=0.60$

Other Areas (farmland/open space) : $f=0.20$

(ii) Basin Average Rainfall Intensity

Point rainfall intensity curve with a 10-year frequency of the Project Area is given below.

$$r_p : \frac{8571}{t^{1/1.02} + 50.1} \quad \text{for } t \leq 180 \text{ min.}$$

$$r_p : \frac{8973}{t^{1/1.02} + 68.0} \quad \text{for } t > 180 \text{ min.}$$

Where,

r_p = Point rainfall intensity (mm/hr)

t = Duration time (min.)

The basin average rainfall intensity (r_a) is obtained by multiplying the point rainfall intensity by the rainfall reduction factors.

For the rainfall reduction factors, refer to Appendix G, Supporting Report of Master Plan.

(iii) Concentration Time (t_c)

Concentration time (t_c) of flood run-off consists of overland time (t_1) and drain time (t_2).

$$t_c = t_1 + t_2 \text{ (min.)}$$

The overland time is a flood concentration time along the longest time route from the catchment boundary to the uppermost point of the objective urban drainage channel. The overland time is estimated by assuming that :

$$\text{Route Length} = \frac{\text{Catchment Area}}{\text{Length of Objective Drainage Channel}}$$

Flow Velocity = 0.4 m/s.

The drain time is flood concentration time in the objective urban drainage channel. In the drain time calculation, flow velocity is assumed as follows.

<u>Velocity</u>	<u>Channel Gradient</u>
$v = 2.0 \text{ m/s}$	$\frac{1}{200} < I$
$v = 1.5$	$\frac{1}{500} < I \leq \frac{1}{200}$
$v = 1.0$	$\frac{1}{1000} < I \leq \frac{1}{500}$
$v = 0.5$	$I \leq \frac{1}{1000}$

3.2 Design Boundary Water Level

Drainage of the Project Area is affected by water level of the sea, Cengkareng Floodway and Mookervart River. The design boundary water level at the sea, Cengkareng Floodway and Mookervart River are determined as follows.

3.2.1 Tide Level

According to the Master Plan for Drainage and Flood Control of Jakarta, 1973, the tidal movement in the Jakarta bay is mainly a single day tide with one high and one low tide per 24 hours. The tide levels applied for the Master Plan are as follows.

Spring Tide (High High Water)	:	P.P. + 1.15
Average High Water (H. W.)	:	P.P. + 0.90
Slack Tide High Water	:	P.P. + 0.80
Mean Sea Level (M.S.L.)	:	P.P. + 0.60
Slack Tide Low Water	:	P.P. + 0.40
Average Low Water	:	P.P. + 0.25
Spring Tide (Low Low Water)	:	P.P. + 0.00

Note: P.P. (Priok Pile) means the tidal gauging station located at the Tanjung Priok harbour.

In 1988, a check survey of the sea water level was conducted for the East Jakarta Flood Control Project. It confirmed that the tide levels applied for the 1973 Master Plan is still valid. (See, East Jakarta Flood Control Project, Design Report I, Vol. IV Hydrology and River, Feb. 1989).

Based on the above information, design tide level of this drainage plan is determined as P.P. + 1.20.

3.2.2 Cengkareng Floodway

The Cengkareng floodway constructed in 1983 drains floods of the rivers of Pesanggrahan, Upper Angke, Sepak and Mookervart into the Bay of Jakarta. Its catchment area is 445 km² at the confluence of the Mookervart River. It is 7.5 km in length and has a discharge capacity of 390 m³/s, equivalent to a 100-year floods. The river profile is shown in Fig. 1.3.1.

(1) Flood Discharge

Flood discharge with 100-year, 25-year and 2-year is estimated as follows (Refer to Cengkareng Drain System Study, April 1981).

100-year floods : $Q_{100} = 390 \text{ m}^3/\text{s}$ (Design flood discharge)
 25-year floods : $Q_{25} = 280 \text{ m}^3/\text{s}$
 2-year floods : $Q_2 = 150 \text{ m}^3/\text{s}$

Further, JICA Study Team estimated the 10-year flood discharge at $Q_{10} = 220 \text{ m}^3/\text{s}$.

(2) Flood Water Level at Estuary and Cengkareng Weir Downstream

Flood water levels at the estuary and at just downstream of the Cengkareng Weir were also estimated for the 100-year, 25-year and 2-year floods as follows, in the above-mentioned study (See Fig.1.3.1). The Cengkareng Weir is located at 5.82 km river distance from the estuary.

	<u>Estuary</u>	<u>Cengkareng Weir Downstream</u>
100-year floods	P.P. + 1.80 m	P.P. + 3.25 m
25-year floods	P.P. + 1.50 m	P.P. + 2.45 m
2-year floods	P.P. + 1.25 m	P.P. + 1.75 m

JICA Study Team estimated the water level of 10-year floods as follows.

	<u>Estuary</u>	<u>Cengkareng Weir Downstream</u>
10-year floods	P.P. + 1.40 m	P.P. + 2.10 m

(3) Flood Water Level at Padongkelan Barat Drain Outlet

The outlet of the Padongkelan Barat Drain is located at 4.26 km river distance from the estuary. Based on the above-mentioned water levels, the water level of various frequency floods at the outlet of the Padongkelan Barat Drain is estimated as follows.

100-year floods (390 m ³ /s)	: P.P + 2.90 m
25-year floods (280 m ³ /s)	: P.P + 2.20 m
10-year floods (220 m ³ /s)	: P.P + 1.90 m
2-year floods (150 m ³ /s)	: P.P + 1.65 m

3.2.3 Mookervart River

The Mookervart River drains an area of 72 km². Its water level is affected by the backwater of the Cengkareng Floodway.

The water level at the confluence to the Cengkareng Floodway is estimated for various frequency floods of the Cengkareng Floodway as follows (Refer to Cengkareng Drain System Study April, 1981).

<u>Cengkareng Flood</u>	<u>Mookervart Water Level</u>
100-year	P.P. + 3.55 m
25-year	P.P. + 2.70 m
2-year	P.P. + 1.90 m

The river slope of the Mookervart is also estimated at 0.0003 in the above-mentioned study.

Based on the above information, JICA Study Team estimated water level of the Mookervart River at the confluence of Kali Bor (4.5 km upstream from the confluence to the Cengkareng Floodway) for various frequency floods as follows.

<u>Flood Frequency</u>	<u>Confluence of Kali Bor</u>
100-year	P.P. + 4.90 m
25-year	P.P. + 4.05 m
10-year	P.P. + 3.80 m
2-year	P.P. + 3.25 m

3.3 Alternative Studies for Drainage Basin (A)

The following two (2) alternative plans are considered for the drainage improvement of the Drainage Basin (A).

- (i) Improvement of existing drainage system
- (ii) Diversion to Cengkareng Floodway

3.3.1 Improvement of Existing Drainage System (Case A-I)

(1) General

In this plan, the existing Tanjungan River is improved for the reaches of 3.2 km from Point a₀ to the estuary (Point a₃). Moreover, 4.0 km of new drainage channel is excavated between Point a₂ and Point a₅ along the Toll Road to drain the upper catchment area.

Location of the proposed channel improvement is shown in Fig. 1.3.2.

(2) Design Flood Discharge

The design flood discharge for the respective sections along the existing Tanjungan River and proposed new drainage channel is

estimated based on the calculation method described in the previous Section 3.1 as shown in Table 1.3.1(1).

(3) Main Features of Proposed Channel

The main features including length, gradient, width and depth for the respective sections of the proposed channel are also shown in Table 1.3.1(1).

3.3.2 Diversion to Cengkareng Floodway (Case A-II)

(1) General

This plan proposes to divert the uppermost sub-basin (A-4) of 235 ha to the Cengkareng Floodway to reduce the flood discharge in the downstream reaches.

This sub-basin is mostly covered by swamp land with a low elevation of 1.5 m at present. However, the swamp land will be fully developed for industrial use in future (See Fig. 1.1.3). In fact, industrial land development by reclamation has been completed in some parts and is on-going in other parts. Elevation of such land reclamation is P.P. 3.0 - 4.0 m which is higher than the design flood water level of the Cengkareng Floodway of P.P. 2.9 m (Refer to Section 3.2.2). Hence, gravity drainage to the Cengkareng Floodway is applied in this plan.

This plan includes the following drainage improvements.

- Improvement of the existing Tanjungan River of 3.2 km (a₀ - a₃)
- Excavation of a new drainage channel of 1.7 km (a₄ - a₂) to drain the sub-basin (A-2) to the Jakarta Bay
- Excavation of a new drainage channel of 2.3 km (a₄ - a₅) to direct the sub-basin (A-4) to the Cengkareng Floodway

Location of the proposed channel improvement is shown in Fig. 1.3.2.

(2) Design Flood Discharge

The design flood discharge for the respective sections along the existing Tanjungan River and proposed new channel is determined as shown in Table 1.3.1(1).

(3) Main Features of Proposed Channel

The main features for the respective sections of the proposed channel are also shown in Table 1.3.1(1).

3.3.3 Comparative Evaluation

The required major construction works, land acquisition area and construction costs for the above two (2) alternative plans are shown below (For details, refer to Table 1.3.2(1)).

<u>Item</u>	<u>Case A-I</u>	<u>Case A-II</u>
Channel Excavation (m ³)	111,000	94,200
Embankment (m ³)	26,000	27,000
Revetment Works (m ²)	38,500	38,500
Land Acquisition (ha)	10.9	10.5
Construction Cost (million Rp.)	9,752	9,541

Note: Construction cost includes direct construction cost, and land acquisition and compensation costs.

The construction costs of both cases are almost the same. No significant advantages of the diversion project are identified.

Improvement of the existing drainage system (Case A-I) is recommended.

3.4 Alternative Studies for Drainage Basin (B)

The following two (2) alternative plans are considered for the drainage improvement of the Drainage Basin (B).

- (i) Improvement of existing drainage system
- (ii) Diversion to Tanjungan River

3.4.1 Improvement of Existing Drainage System (Case B-I)

(1) General

In this plan, the existing main courses of the Kamal River is improved for the reaches of 7.4 km from Point b₁, to the estuary (Point b₆). In addition, 0.7 km of new drainage channel is excavated between Point b₀ and Point b₁ to drain the uppermost area. No improvement works are proposed for the left tributary (b₈ - b₂) and right tributary (b₇ - b₃) since they have a sufficient flow capacity.

Location of the proposed channel improvement is shown in Fig. 1.3.2.

(2) Design Flood Discharge

The design flood discharge for the respective sections along the existing main courses of the Kamal River is shown in Table 1.3.1(2).

(3) Main Features of Proposed Channel

The main features for the respective sections of the proposed channel are also shown in Table 1.3.1(2).

3.4.2 Diversion to Tanjungan River (Case B-II)

(1) General

This plan diverts floods of the upstream basin of the Kamal River to the Tanjungan River. A diversion channel is constructed between Point b₄ of the Kamal River and Point a₁ of the Tanjungan River to divert the sub-basins of B-1, B-2, B-3 and B-4 with a total catchment area of 1,081 ha. Total length of the proposed diversion channel is 1.5 km.

Location of the proposed channel improvement is shown in Fig. 1.3.2.

(2) Design Flood Discharge

Design flood discharge distribution for the diversion channel is determined so that no channel improvement may be required for the downstream reaches of the Kamal River after completion of the diversion channel.

The design discharge for the downstream reaches of the Kamal River in the alternative plan Case B-I is $47 \text{ m}^3/\text{s}$. While, the existing flow capacity of the reaches is estimated to be $30 \text{ m}^3/\text{s}$. Hence, the exceeding discharge of $17 \text{ m}^3/\text{s}$ shall be diverted. The design discharge of the Tanjungan River is increased by $17 \text{ m}^3/\text{s}$.

The proposed design flood discharge distribution for the Kamal River, diversion channel and Tanjungan River is shown in Table 1.3.1(2).

(3) Main Features of Proposed Channel

The main features of the proposed channels of the Kamal, diversion and Tanjungan are also shown in Table 1.3.1(2).

3.4.3 Comparative Evaluation

Economical efficiency of the above two (2) alternatives are compared in terms of construction cost of the following two (2) cases.

- (i) Total of the independent drainage improvement plans for Drainage Basin (A) and Drainage Basin (B) (Case A-I plus Case B-I)
- (ii) Integrated drainage improvement plan of Drainage Basin (A) and Drainage Basin (B) (Case B-II)

The major construction works, land acquisition area and construction cost for the above two (2) cases are shown below (For details, refer to Table 1.3.2(2)).

<u>Item</u>	<u>Case A-I+Case B-I</u>	<u>Case B-II</u>
Channel Excavation (m ³)	340,000	399,000
Embankment (m ³)	50,000	102,000
Revetment Works (m ²)	91,400	92,900
Land Acquisition (ha)	28.4	24.1
Construction Cost (million Rp.)	26,184	26,379

Note: Construction cost includes direct construction cost, and land acquisition and compensation costs.

The construction costs of both cases are almost the same. No significant advantages of the diversion project are identified. Improvement of the existing drainage system (Case B-I) is recommended.

3.5 Alternative Studies for Drainage Basin (C and D)

The following two (2) alternative plans are considered for the drainage improvement of the Drainage Basin (C and D).

- (i) Improvement of existing drainage system
- (ii) Diversion to Mookervart River

3.5.1 Improvement of Existing Drainage System (Case C/D-I)

(1) General

The Drainage Basin (C) of 563 ha is drained by the drainage channels of Kali Gede and Kali Bor into the Mookervart River. The Drainage Basin (D) of 331 ha is discharged by the Saluran Cengkareng drainage channel into the Cengkareng Floodway through the Padongkelan drainage channel.

The flood water levels of the Mookervart River and Cengkareng Floodway for 10-year flood are P.P. 3.8 m and P.P. 1.9 m respectively (Refer to Section 3.2). While, ground elevation of the Drainage Basin C and D are estimated as follows.

Sub-basin C-1 and C-2	}	Residential area	: higher than 4.5 m
Sub-basin D-1		Paddy field	: higher than 4.0 m
Sub-basin D-2		: Mostly higher than 2.7 m	
			lowest elevation is 2.0 m

Based on the above facts, gravity drainage is applied for both drainage basins.

The proposed channel improvement reaches are:

(Drainage Basin C)

- Kali Gede : 3.4 km from Point c_0 to Point c_2
- Kali Bor : 1.3 km from Point c_2 to the confluence to Mookervart River (Point c_4)

(Drainage Basin D)

- Saluran Cengkareng: 4.6 km from Point d_0 to the confluence to Padongkelan drainage channel (Point d_2)

Location of the proposed channel improvements are shown in Fig. 1.3.3.

(2) Design Flood Discharge

The design flood discharge for the respective sections along the existing drainage channels of Kali Gede, Kali Bor and Saluran Cengkareng is shown in Table 1.3.1(3).

(3) Main Features of Proposed Channel

The main features for the respective sections of the proposed channel are also shown in Table 1.3.1(3).

3.5.2 Diversion to Mookervart River (Case C/D-II)

(1) General

The sub-basin (D-1) of 139 ha of the Drainage Basin (D) is diverted into the Mookervart River through the drainage channel of Kali Bor. The drainage channel of Saluran Cengkareng drains only the sub-basin (D-2).

As a result, the catchment area of the Drainage Basin (C) increases from 563 ha to 702 ha, while that of the Drainage Basin (D) decreases from 331 ha to 192 ha.

The proposed channel improvement reaches are:

(Drainage Basin C)

- Kali Gede : 3.4 km from Point c_0 to Point c_2
- Diversion channel : 1.7 km from Point d_1 to Point d_0
- Kali Bor : 1.3 km from Point c_2 to the confluence to Mookervart River (Point c_4)

(Drainage Basin D)

- Saluran Cengkareng: 2.9 km from Point d_1 to the confluence to Padongkelan drainage channel (Point d_2)

Location of the proposed channel improvement is shown in Fig. 1.3.3.

(2) Design Flood Discharge

The design flood discharge for the respective sections of the drainage channels of Kali Gede, diversion, Kali Bor and Salurang Cengkareng is shown in Table 1.3.1(3).

(3) Main Features of Proposed Channel

The main features for the respective sections of the proposed channel are also shown in Table 1.3.1(3).

3.5.2 Comparative Evaluation

The major construction works, land acquisition area and construction cost of the above two (2) alternative plans for the Drainage Basin C and D are compared as follows (For details, refer to Table 1.3.2(3)).

<u>Item</u>	<u>Case C/D-I</u>	<u>Case C/D-II</u>
Channel Excavation (m ³)	95,000	87,000
Embankment (m ³)	42,100	42,100
Revetment Works (m)	81,100	81,100
Land Acquisition (ha)	9.5	9.1
Construction Cost (million Rp.)	14,991	14,575

Note: Construction cost includes direct construction cost, and land acquisition and compensation costs.

The construction costs of both cases are almost the same. No significant advantages of the diversion are identified.

Improvement of the existing drainage system (Case C/D-I) is recommended.

3.6 Alternative Studies for Drainage Basin (E)

The Drainage Basin (E) covers 515 ha of the catchment area of the Padongkelan drainage channel of which 340 ha is being developed for housing estate.

Ground elevation of the Drainage Basin (E) is mostly higher than P.P. 2.7 m. The lowest elevation is P.P. 2.0 m equivalent to 15-year flood water level of the Cengkareng Floodway (Refer to Section 3.2). Pump drainage is not efficient because it will work only once in 15 years on an average.

Hence, the following two (2) alternatives are considered for the drainage improvement of this area.

- (i) Gravity Drainage to Cengkareng Floodway
- (ii) Diversion to Tanjungan River

3.6.1 Improvement of Existing Drainage System (Case E-I)

(1) General

This is a gravity drainage to the Cengkareng Floodway. The existing Padongkelan drainage channel is improved for the reaches of 1.1 km from Point e₂ to the confluence to the Cengkareng Floodway (Point e₄). In addition, the existing channel is extended upstream to Point e₀ to drain the upper channel area of the Drainage Basin (E). A new drainage channel is excavated between Point e₀ and Point e₂.

Location of the proposed channel improvement is shown in Fig. 1.3.3.

(2) Design Flood Discharge

The design flood discharge for the respective sections along the existing Padongkelan drainage channel and extended drainage channel is determined as shown in Table 1.3.1(4).

(3) Main Features of Proposed Channel

The main features of the respective sections of the proposed channel are also shown in Table 1.3.1(4).

3.6.2 Diversion to Tanjungan River (Case E-II)

(1) General

The existing Padongkelan drainage channel is provided with a sluice gate at the confluence to the Cengkareng Floodway to prevent floods

from the Cengkareng Floodway. The gate is closed when the water level of the Cengkareng Floodway exceeds P.P. 2.0 m.

In this alternative plan, the existing Padongkelan drainage channel is diverted to the Tanjungan River to overcome the above problems.

The proposed plan includes the following channel improvement works.

- Improvement of the existing drainage channel for the reaches of 1.1 km from the confluence to the Cengkareng Floodway (Point e4) to Point e2.
- Excavation of a new drainage channel of 2.5 km from Point e2 to Point a4.
- Enlargement of the proposed drainage channel of the Drainage Basin (A) for the reaches of 7.3 km from Point a4 to the estuary of the Tanjungan River (a3).

Location of the proposed channel improvement is shown in Fig. 1.3.3.

(2) Design Flood Discharge

The design flood discharge for the respective sections along the existing Padongkelan drainage channel, new drainage channel and proposed drainage channel of the Drainage Basin (A) is determined as shown in Table 1.3.1(4).

(3) Main Features of Proposed Channel

The main features for the respective sections of the proposed channel are also shown in Table 1.3.1(4).

3.6.3 Comparative Evaluation

Economical efficiency of the above two (2) alternatives are compared in terms of the construction cost of the following two (2) cases.

- (i) Total of the independent drainage improvement plans for Drainage Basin (E) and Drainage Basin (A) (Case E-I plus Case A-I)
- (ii) Integrated drainage improvement plan of Drainage Basin (E) and Drainage Basin (A) (Case E-II)

The major construction works, land acquisition area and construction cost for the above two (2) cases are shown below (For details, refer to Table 1.3.2(4)).

<u>Item</u>	<u>Case E-I + Case A-I</u>	<u>Case E-II</u>
Channel Excavation (m ³)	145,200	300,000
Embankment (m ³)	40,000	45,000
Revetment Works (m ³)	61,400	91,200
Land Acquisition (ha)	14.9	20.4
Construction Cost (million Rp.)	14,947	20,733

Note: Construction cost includes direct construction cost, and land acquisition and compensation costs.

The plan of gravity drainage to the Cengkareng Floodway is more economical than the diversion to the Tanjungan River. In addition, it is considered difficult to maintain the design channel section of the latter plan due to its gentle slope of 1/8,500.

Case E-I is recommended.