





CRACK DIAGRAM OF PIER



CRACK DIAGRAM OF ABUTMENT



LEGEND OF DAMAGE (CONCRETE)

TYPE OF DAMAGES	INDICATION
CRACK #	
FLACKING	
REBAR EXPOSURE	
FREE LINE	
HONEY COMB	
WEAR / EROSION	
WATER STAIN	
OTHERS	

* □ - MAXIMUM CRACK WIDTH
○ - THE LENGTH OF CRACK

STANDARD DRAWING OF CRACK DIAGRAM FOR SUBSTRUCTURE

NOTE : CRACK DIAGRAM OF GIRDERS INDICATED BY IS SHOWN ABOVE.

ANNEX - E
OPERATION MANUALS AND RECORDING FORMS
OF SEMI AND NON DESTRUCTIVE EQUIPMENT

TABLE OF CONTENTS

Method of Sampling for Sulphate and Chloride Test.....	E-1
Method of Carrying out The Carbonation Test.....	E-4
Method of Carrying out Rebar Location and Rebar Cover Survey by Using Proformeter	E-6
Instruction Manual on the Use of Half-cell Corrosion..... Potential Meter	E-10
Measurement Method for Estimation of Concrete Strength..... by Schmidt Hammer	E-14
Method of Measurement for Estimation of Concrete Strength... by Ultrasonic Pulse Velocity (UPV) Measurement	E-17
Concrete Repair.....	E-20
Measurement Method for a Steel Hardness by Echo Tip.....	E-21
Steel Thickness Measurement Using Ultrasonic Thickness..... Meter	E-26

LIST OF TABLES


Table E-1	Table for Converting from "L" Value to..... Brinell Hardness	E-23
Table E-2	A Table for Converting from..... Brinell Hardness	E-24

LIST OF TABLES

Fig. E-1	Minimum Spacing for Five Testing Points.....	E-21
----------	--	------

METHOD OF SAMPLING FOR SULPHATE AND CHLORIDE TEST

1. Mark the test location using maker pen or spray paint. Avoid taking samples on concrete surface when there is plastering and the test location so chosen should be free from reinforcing bar. (Use the proformeter to locate the rebar).
2. Prepare the concrete surface to be tested. Any mud stains, binnacles and salt built up to be removed.
3. 3 number of concrete dust samples shall be taken at various depth on each test location. The depth at which the sample is to be taken shall be 0-20, 21-40, 41-60mm and it is measured from concrete surface.
4. Method of collecting concrete sample is as follows:-
 - i - Set the depth marker on the drill bit to the depth required (eg. set depth marker to 20mm for sampling depth of 0-20mm).
 - ii - Drill the concrete for a depth of 20mm through a new plastic bag as shown in the diagram below. If drilling is not at the soffit then use the spoon provided to collect the dust sample.



- iii- Transfer the concrete dust samples to a **NEW** plastic beg, seal and marked the sample as follows:-

<p style="text-align: center;">BRIDGE NO SAMPLE NO/DEPTH</p>
--

- iv - Discard the plastic bag used to collect the concrete sample in (i) above. (IT SHOULD NOT BE USED TWICE)
- v - Repeat procedure (i) to (iv) above for concrete depth 21-40mm and 41-60mm (but set the depth marker accordingly). Concrete dust sample for each depth shall be stored in a separate plastic bag.
- vi - Upon completion of taking 3 samples at each test location, put all 3 bags containing samples at various depth in a bigger plastic bag. Mark the bag as follows:-

BRIDGE NO SAMPLE NO/MEMBER

- vii - Record the test location and sample number in the appropriate sketches and table respectively in the inspection sheets.
5. Send the concrete dust sample to the laboratory for chemical analysis in accordance with BS 1881: Part 124:1988. The interpretation of sulphate and chloride test result is as follows:-

(i) Sulphate test

PERCENTAGE OF SULPHATE	PROBABILITY OF ATTACK
Less than 4%	Probability of sulphate attack is small
Greater than 4%	High probability of sulphate attack

(ii) Chloride test

PERCENTAGE OF CHLORIDE BY WT. OF CEMENT	CONDITION OF CONCRETE AROUND THE REBAR	RISK OF CORROSION
Less than 0.4%	1. Carbonated 2. Uncarbonated & cement with <8% tricalcium aluminate 3. Uncarbonated & cement with >8% tricalcium aluminate	High Moderate Low
0.4% to 1%	1. As above 2. As above 3. As above	High High Moderate
Greater than 1.0%	All cases	High

RECORD OF SAMPLING FOR CHLORIDE AND SULPHATE TEST

Bridge No : _____

Date of survey : _____

Inspector : _____

Sampling No	LOCATION	
	Chloride Sampling	Sulphate Sampling
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		

METHOD OF CARRYING OUT THE CARBONATION TEST

1. Mark the test location using marker pen or spray paint. Avoid carrying out the test on concrete surface where there is plastering. The test location so chosen should also be free from reinforcing bar. (Use the proformeter to locate the rebar).
2. Make a 50mm deep x 20mm diameter hole in the concrete member to be tested using electric drill.
3. Remove all concrete dust from the hole by blowing it with a rubber blower and clean the remaining dust with the brush provided.
4. Immediately spray the newly exposed concrete surface with 1% phenolphthalein solution which is a colourless solution.
5. See colour changes on the concrete surface. The area which has changed to purple indicates that the concrete is still alkaline, hence has not been carbonated.
6. Measure the depth of concrete in the hole where there is no colour change (to be measured from the surface of the concrete). The depth where there is no colour change indicates that the concrete is not more alkaline i.e. it has been carbonated.
7. Place the colour reference indicator and black board (on which the location of the test, member and bridge No. has been written on) adjacent to the test location. Take the photograph of the concrete test area while maintaining measurement equipment in the hole, for record purposes.
8. Record in the inspection sheets provided, the test location, bridge No. and result of carbonation test (Carbonation depth).
9. Carbonation test could also be carried out on concrete member which has been broken out such as in the half-cell test, chloride sampling, sulphate sampling and rebar survey. In such cases spray the phenolphthalein solution on the freshly exposed concrete surface (for detail procedure of the test please Repeat item 3 to 8 above).

CARBONATION DEPTH

Bridge No : _____


Date of survey : _____

Inspector : _____

No	TEST LOCATION	MEMBER	CARBONATION DEPTH (mm)	PHOTO NO

METHOD OF CARRYING OUT REBAR LOCATION AND REBAR COVER SURVEY BY USING PROFORMETER

1. The Proformeter is a rebar detector equipment with the setup at shown in the sketch below. (Note; the pin of the probe cable plug should be cleaned from time to time).




2. The method of using proformeter to detect the reinforcement is as follows;
 - i) Connect the SPOT PROBE to the instrument by means of cable. Keep the probe away from all metal object.
 - ii) Switch on the equipment. Hold the probe away from you and be sure that it is well away from any metal object. Then reset the button in proformeter-3 and in case of proformeter-2 turn the tuning knob to bring the pointer to the " ∞ " mark. Set the rotary selector knob to 3.
 - iii) Place the probe on the concrete surface where the test is to be carried out.
 - iv) Move the spot probe slowly until a beeping sound is produced by the instrument in case of proformeter-3 and by the maximum value as indicated by the pointer in case of proformeter-2. This indicates that there is rebar directly under the cross marker of the spot probe.

NOTE:

There are cases where the rebar may be close together. In such cases a lot of practice and experience in using the proformeter-2 is required. The graph below illustrates how the pointer deflection of the proformeter-2 moves as a function of the interval between the rebar when the probe is moved across the structure perpendicular to the rebar position. In case

of proformeter-3 there is less problem. However if the rebar is too close (similar to those shown on the right hand side of the sketch below), breakout survey may be necessary for both version of equipment (an experienced user may be able to use his/her engineering judgment in determining the location and the number of rebar detected).



- v) Mark the location of the rebar detected using marker pen or chalk.
 - vi) Two measurements permit very precise determination of the direction of a rebar by simply joining the two measured points together. Repeat item (iii) to (v) above until all the rebar in the concrete has been detected.
3. The method of using proformeter to detect depth of cover to the reinforcement is as follows;
- i) Connect the SPOT PROBE to the instrument by means of cable. Keep the probe away from all metal object.
 - ii) Switch on the equipment. Hold the probe away from you and be sure that it is well away from any metal object. Then reset the button in proformeter-3 and in case of proformeter-2 turn the tuning knob to bring the pointer to the "∞" mark. Set the rotary selector knob to "16" for proformeter-3 and set it to "D" in case of proformeter-2.
 - iii) Place the probe on the concrete surface and exactly above the axis of the rebar. Read off the cover depth.

- iv) Where the cover detected is less than 10mm, remove the probe and then place the 20mm spacer between the probe and the concrete surface. Read off the depth of cover again. The actual depth of cover shall be obtained by deducting 20mm from the read off value.
 - v) Where the depth of cover detected is more than 60mm, switch off the instrument and replace the spot probe with DEPTH PROBE. Repeat step (ii) to (iii) above.
- 4. Diameter of the rebar could not be determined accurately using proformeter. Therefore minimal breakout of the concrete cover is required.
 - 5. Record the diameter, spacing and cover of the rebar in the record form provided.

inspector


[illegible]

INSTRUCTION MANUAL ON THE USE OF HALF-CELL CORROSION POTENTIAL METER

1. Prepare the concrete surface to be tested as follows:-
 - i - Layout a grid pattern of the test and rebar locations at 500mm centers covering the entire area to be tested. (use proformeter to locate the rebar)
 - ii - Mark each test location with spray paint.
 - iii- Remove all asphalt, waterproofing layers, paint etc. from each test location (the size of test spot shall be about 40mm diameter).
 - iv - Completely expose one rebar by breaking out the concrete about 40mm x 60mm in size (the breakout area should be kept minimal).
 - v - Wet the test points with the electrical contact solution at least 10 minutes before testing.
2. Mix the electrical contact solution in the plastic bucket. To ensure a standardize potential drop the mixing volume of the electrical contact solution shall be kept constant. The mixing volume shall be as follows:-

Wetting agent	:	100 ml.
Portable water	:	20 l.
3. Prepare the half cell electrode as follows:-
 - i - Unscrew the top of a new electrode and fill it to the top with distilled water then screw it back tightly.
 - ii - Shake the electrode for 2 to 3 minutes Ensure that excess CuSO_4 (copper sulphate) crystal remain at the bottom; if not, add a little bit more CuSO_4 .
 - iii- Tie the sponge to the bottom end of the electrode with a rubber band.
4. Complete the half cell electrical circuit as follows:-
 - i - Brush the reinforcing bar.
 - ii - Clamp the ORANGE colour electrical wire directly to the reinforcing steel.
 - iii- Ensure that the other end of ORANGE colour electrical wire is connected to the positive (RED-centre) terminal of the voltmeter.


- iv - Connect one end of the BLACK electrical wire to the negative (black) terminal of the volt meter and the other end to the half-cell.
- v - Ensure that proper connection has been made as shown in the diagram below;



5. Method of operating the half cell equipment is as follows:-
- i - Switch the voltmeter to 'DC' position.
 - ii - Place the range switch to "2V" position.
 - iii- Place the input resistance switch in the 25 M- Ω (million-Ohm) position.
 - iv - Wet the sponge attached to the electrode.
 - v - Place the electrode against the prepared location on the concrete surface, adjacent to the marked spot.
 - vi - Steady reading between 0 to -0.60 volts should be obtained within 10 second (slight variation in the second digit is normal). All reading must be rounded off to the nearest 0.01V.
 - vii- If the reading is not negative sign or if the reading is about zero then check for a disconnected or broken test lead AND repeat the test.
 - viii-Record the potential reading in the form attached.

6. Presentation and interpretation of result of corrosion survey is as follows:-

- i) - The half-cell test result shall be presented in the form of an equipotential contour map as shown below;



- ii)- The test gives the indication of area of the concrete in which active corrosion is taking place and the probability of corrosion may be interpreted based on the table below:-

ELECTRICAL POTENTIAL	PROBABILITY OF CORROSION
Greater than -0.20 V	Greater than 90% probability where corrosion will NOT occur.
-0.20 V to -0.35 V	- Not Conclusive -
Less than -0.35 V	Greater than 90% probability where active CORROSION is taking place.

ESTIMATION OR RE-BAR CORRODED BY HALF CELL POTENTIOMETER


Bridge No. : _____
 Date of Survey : _____
 Inspector : _____

MEMBER AND LOCATION :										
COLUMN	VOLTAGE									
ROW	A	B	C	D	E	F	G	H	I	J
1										
2										
3										
4										
5										
6										
7										
8										
9										
10										
11										
12										
13										
14										
15										
16										
17										
18										
19										
20										

SKETCH	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
	A																			
	B																			
	C																			
	D																			
	E																			
	F																			
	G																			
	H																			
	I																			
	J																			

MEASUREMENT METHOD FOR ESTIMATION OF CONCRETE STRENGTH BY SCHMIDT HAMMER

1. Prepare the concrete surface to be tested. Any plasterwork, and coating must be removed. Any uneven surface shall be smoothened with carborundum stone or with power grinder.
2. Number of measurement points per member to be measured shall be 20 points and to be marked on the concrete surface using chalk or marker pen as shown below.



3. Method of operating the schmidt hammer is as follows;
 - i- Hold the Schmidt Hammer at right angle to the concrete surface. Press the plunger against the concrete surface to be tested (Careful! do not touch the release button).
 - ii- Remove the hammer from the test spot and it will be automatically reset and ready for next test.
 - iii- Upon completion of testing at all the 20 points, open the chart housing and read the REBOUND VALUE (R).
 - iv- Once the test is completed, lock the plunger by pushing the plunger all the way in while pressing the push-button.

4. Method of determination of concrete strength is as follows;


- i- The rebound hammer has been calibrated with the hammer vertical down with the member to be tested positioned horizontally. If the concrete surface is not vertical, The Rebound Value "R" shall be adjusted accordingly using the correction table as shown below.

**Correction of the Test Hammer Indications
for Non-Horizontal Impacts.**

Rebound value $R\alpha$	Correction for inclination angle α			
	upwards		downwards	
	+90°	+45°	-45°	-90°
10	-	-	+2.4	+3.2
20	-5.4	-3.5	+2.5	+3.4
30	-4.7	-3.1	+2.3	+3.1
40	-3.9	-2.6	+2.0	+2.7
50	-3.1	-2.1	+1.6	+2.2
60	-2.3	-1.6	+1.3	+1.7

- ii- Averaged out the Rebound Value "R". Any obvious "off shoots" reading are to be eliminated and repeat the impact test if the variation is too wide. Enter Rebound Value (R) in the Recording form attached (similar to UPV recording sheets).

- iii- The Cube Compressive strength may be obtained based on the Mean Value of "R" using the Graph below.




Bridge No. _____
 Date of Survey _____
 Inspector _____

E - 16

METHOD OF MEASUREMENT FOR ESTIMATION OF CONCRETE STRENGTH BY ULTRASONIC PULSE VELOCITY (UPV) MEASUREMENT

1. Locate all reinforcement bar at the test area using profor-meter and mark its location on the concrete surface.
2. Mark the UPV test location and the selected location to be tested should be free from reinforcing bar.
3. Prepare the concrete surface to be tested. Any binnacles shall be removed and the concrete surface to be smoothened and leveled with power grinder.
4. Number of measurements per member to be measured shall be 3 points and to be marked on the concrete surface using marker pen. The measurement location is as shown below.



5. Adjust the reading of the instrument each time the instrument is used or changes are made to the setup of the equipment such as transducers are interchanged, the use of different transducers and the use of different length of cable. The method of setting up and adjustment of the equipment is as follows:
 - a- Apply a thin layer of couplant (petroleum jelly) to the transducers

- b- Press transducers against both ends of the reference bar.
 - c- Adjust the zero reading of the instrument accordingly.
6. Method of operating UPV instrument is as follows:
- i- Apply a thin layer of couplant (petroleum jelly) to the transducers.
 - ii- Place the transmitting and receiving transducers on the concrete surface firmly at a fixed distance as shown in the sketch above.
 - iii- Read directly on digital display screen of the UPV the transmission time (UPV meter reading)
 - iv- Plot the transmission time (UPV meter reading) on the graph paper.
 - v- Draw the best straight line through the points on the graph plotted in (iv) above. If the points indicates discontinuity, it indicates that there is defects such as crack, hence result is not reliable. In such instances UPV test has to be carried out on another nearby location.
 - vi- Record the UPV meter reading in the recording form attached.
7. Method of determination of concrete strength is as follows:
- i- Obtain the Schmidt Hammer reading (R)
 - ii- The concrete strength could then be calculated using the following formula:
 - a- In cases where the concrete cement ratio is unknown:-

$$\text{Concrete Strength (Kg/cm}^2\text{)} = 11.8 R + 129 V_{pc} - 642$$
 - b- In cases where the concrete cement ratio is known:-

$$\text{Concrete Strength (Kg/cm}^2\text{)} = 9.2 R + 74 V_{pc} - 4.3 (W/C) - 74$$
- Where; R = Rebound Value of Schmidt Hammer
- $$V_{pc} = \text{Ultrasonic Pulse Velocity (Km/s)}$$
- $$= \frac{\text{Distance of UPV probe "L" (Transmission Time)}}$$

Bridge No. _____
 Date of Survey _____
 Inspector _____

E - 19

CONCRETE REPAIR

1. The amount of concrete actually broken off shall always be kept minimal.
2. Ensure that all concrete repair equipment used such as steel trowel, measuring cylinder, mixing bucket, water container etc. is thoroughly cleaned.
3. Ensure that the phenolphthaleine used to test for carbonation test has dried up. Use wire brush to clean the steel and any loose concrete material shall also be removed.
4. Mix a small amount of Armatec 108 based on the mixing proportion by volume as follows;

Liquid (Component A) : 1.0 Part
Grey Powder (Component B): 3.0 Part.
5. Brush Armatec around the steel to a thickness of about 1mm. and all excess material shall be discarded (remember that it has a pot life of only 30 minutes).
6. Leave Armatec for 2 - 3 hours to dry.
7. Mix Sikatop 123/3 Bonding Bridge coat using the mixing proportion by volume as follows;


Liquid (Component A) : 1.0 Part
Grey Powder (Component B): 3.0 Part.
8. Wet the breakout area with clean water (do not use river water).
9. Apply Bonding Bridge on raw concrete surfaces as well as on any previously patched Sikatop surfaces.
10. Mix thoroughly Sikatop 122HB mortar using the mixing proportion by volume as follows;

Liquid (Component A) : 1.0 Part
Grey Powder (Component B): 4.5 Part.
11. Apply a thin layer of Sikatop mortar with trowel (up to 10mm thick at a time) to a maximum of 40mm for vertical surface and 25mm for overhead application. All excess material shall be discarded (The mortar has a pot life of 50 minutes).
12. Wait until Sikatop mortar has set before applying a another layer. Repeat procedure 7 to 11 as required.


MEASUREMENT METHOD FOR A STEEL HARDNESS BY ECHO TIP

1. Mark the test location on the steel member to be tested. At each test location measure and mark 5 test points at centre to centre spacing not less than 3 mm as shown in Fig. E - 1.

Fig.E-1 Minimum spacing for five testing points







2. Any rust or paint should be removed completely at the location where the measurement is to be taken on the steel member.
3. Method of operating the Echotip equipment is as follows;
 - i - Place the impact device firmly at the surface of steel surface to be tested as shown in the sketch below.



- ii - Move the plunger reset gear down until "click" sound is heard. This will reset the instrument.
- iii- Press the impact device release button once.
- iv - Read and record the digital display of the steel hardness value ("L" value) on the Echotip display screen.

- v - Repeat step (i) to (iii) for the other 4 test points at each test location.
- vi - In general, the echotip equipment which is measuring the steel hardness has been calibrated with impact device at vertical position. If the position of the impact device is not vertically down as shown in the sketch above then the "L" value measured has to be adjusted as follows

Adjustment of "L" value at different position				
MEASURED "L"VALUE	Subtracting the following value from the measured value			
				
300	6	12	20	29
350	6	12	19	27
400	5	11	18	25
450	5	10	17	24
500	5	10	16	22
550	4	9	15	20
600	4	8	14	19
650	4	8	13	18

vii- If five measured "L" value differ by more than 15, please repeat the measurement again after all rust or paint around measurement location has been removed completely.

viii-Repeat step (i) to (vi) above for other test location as required.

4. Convert the "L" values to Brinell hardness by using a conversion table supplied by manufacturer of Echo Tip as shown in Table E-1.
5. Finally the Brinell hardness may also be converted to steel tensile strength by using another conversion table which is provided by JIS (Japanese Industrial Standards) as shown in Table E-2.

Table E-1 Table for converting from
"L" value to Brinell hardness

" L "	Brinell	" L "	Brinell	" L "	Brinell
Value	Hardness	Value	Hardness	Value	Hardness
300	80	390	131	482	204
302	81	392	133	484	206
304	81	394	134	490	208
306	82	396	136	492	209
308	83	398	137	494	211
310	84	400	138	496	213
312	85	402	140	498	215
314	86	404	141	500	221
316	87	406	143	502	222
318	88	408	144	504	224
320	90	410	145	506	226
322	91	412	147	508	228
324	92	414	148	510	230
326	93	416	150	512	232
328	94	418	151	514	234
330	95	420	153	516	236
332	96	422	154	518	238
334	97	424	156	520	240
336	98	426	159	522	242
338	99	428	160	524	244
340	100	430	162	526	246
342	101	432	164	528	248
344	103	434	165	530	250
346	104	436	167		
348	105	438	168		
350	106	440	170		
352	107	442	172		
354	108	444	173		
356	110	446	175		
358	111	448	176		
360	112	450	178		
362	113	452	180		
364	115	454	181		
366	116	456	183		
368	117	458	185		
370	118	460	186		
372	120	462	188		
374	121	464	190		
376	122	468	192		
378	123	470	193		
380	125	472	195		
382	126	474	197		
384	127	476	199		
386	129	478	200		
388	130	480	202		

" L "	Converted
Value	Deviation
200	9
300	10
400	13
500	16
600	20
700	
800	
900	

Table E- 2 A table for converting from Brinell hardness to a steel tensile strength


Steel Tensile Strength MPa (Kg/mm2)	Brinell Hardness	
825 (84)	247	247
805 (82)	243	243
795 (81)	238	238
780 (79)	233	233
765 (78)	228	228
730 (75)	219	219
695 (71)	209	209
670 (68)	200	200
635 (65)	190	190
605 (62)	181	181
580 (59)	171	171
545 (56)	162	162
515 (53)	152	152
490 (50)	143	143
455 (46)	133	133
425 (44)	124	124
390 (40)	114	114
-	105	105
-	95	95
-	90	90
-	86	86
-	81	81

Bridge No. _____ : _____
 Date of Survey _____ : _____
 Inspector _____ : _____


E - 25

STEEL THICKNESS MEASUREMENT USING ULTRASONIC THICKNESS METER

1. Mark the test location using spray paint and prepare the steel surface to be measured. The number of measurement location varies, depending on the type of steel member as shown in (2) below. Any surface rust, scaling and partial peeling of paint should be removed by using wire brush.
2. Only single measurement is required to be made at each test location. The measurement location per member to be tested is as shown below:-
 - (i) Steel thickness measurement location for steel beam is as shown in the diagram below;



- (ii) Steel thickness measurement location for steel buckle plate is as shown in the diagram below;



3. Set the velocity of sound setting on top of the ultrasonic meter to 5910 (which is the velocity of sound in iron). DO NOT CHANGE THIS SETTING for the subsequent use of the equipment.
4. Method of operating the ultrasonic steel thickness meter is as follows:-
 - i - Connect the probe to the main unit.
 - ii - Calibrate the probe (The probe has to be calibrated very frequently). Use soft cloth or paper to clean the surface of the test piece.
 - iii- Clean the probe contact surface (ie steel surface to be tested) with soft cloth or paper.
 - iv - Press "PW" button on the front face of the main unit (This will switch on the unit).
 - v - Coat the surface of the test piece with contact medium (ULTRASONIC PULSE CANNOT TRAVEL THROUGH THE TEST PIECE WITHOUT THE MEDIUM).
 - vi - Place the probe against the test piece. Turn the "Zero Adjust Nob" situated on the left hand side of the main unit until the reading 10.00mm. is obtained.
 - vii- Now the instrument is ready for measuring the thickness of the steel member.
5. Coat the probe with contact medium and place the probe against the steel to be measured.
6. Read the thickness of the steel directly from the digital display screen on the meter.
7. Record the thickness in the record sheets provided.

STEEL THICKNESS FOR BUCKLE PLATE

BRIDGE NO. : _____

DATE OF SURVEY : _____

INSPECTOR : _____

MEMBER	POINT	O	$l/2$	l
	B l			
	B c			
	B r			
	B l			
	B c			
	B r			
	B l			
	B c			
	B r			
	B l			
	B c			
	B r			
	B l			
	B c			
	B r			
	B l			
	B c			
	B r			
	B l			
	B c			
	B r			
	B l			
	B c			
	B r			
	B l			
	B c			
	B r			

STEEL THICKNESS FOR BEAM

BRIDGE NO. : _____
 DATE OF SURVEY : _____
 INSPECTOR : _____

MEMBER	POINT	O	$l/2$	l
	FU l			
	FUr			
	Wt			
	FL l			
	FLr			
	FU l			
	FUr			
	Wt			
	FL l			
	FLr			
	FU l			
	FUr			
	Wt			
	FL l			
	FLr			
	FU l			
	FUr			
	Wt			
	FL l			
	FLr			
	FU l			
	FUr			
	Wt			
	FL l			
	FLr			

ANNEX - F
DAMAGE RATING CRITERIA

TABLE OF CONTENTS

	Page
1. Corrosion.....	F-1
2. Cracks.....	F-1
4. Falling Off (Bolts, Nuts & Rivets).....	F-2
5. Rupture.....	F-2
6. Paint Deterioration.....	F-3
7. Cracks.....	F-3
8. Flaking and Rebar Exposure.....	F-4
9. Free Lime.....	F-5
11. Wear and Abrasion.....	F-6
12. Slipping Off.....	F-6
14. Slab Cracks.....	F-7
15. Abnormal Spacing of Gap (Joint).....	F-8
16. Difference in Level (Bridge Approach & Joints).....	F-9
17. Pot Hole.....	F-9
18. Pavement Cracks.....	F-10
19. Rutting.....	F-10
21. Material Deterioration.....	F-11
22. Water Leak And Ponding Water.....	F-11
23. Abnormal Noise.....	F-12
24. Abnormal Vibration.....	F-12
25. Abnormal Deflection.....	F-13
26. Deformation.....	F-13
27. Sediment Accumulation/Vegetation.....	F-14
28. Settlement.....	F-14
29. Abnormal Movement.....	F-15
30. Dip.....	F-16
31. Scouring.....	F-16
32. Defect.....	F-17
33. Erosion.....	F-18

LIST OF FIGURES

Fig F-1	Location & Type of Typical Cracks.....	F-19
	in RC/PC Superstructures	
Fig F-2	Location & Type of Typical Cracks.....	F-20
	in PC Structures	
Fig F-3	Location & Type of Typical Cracks.....	F-21
	in Substructures	

DAMAGE RATING CRITERIA

1. CORROSION

Corrosion is the most common damage in steel because the main raw material is iron which is easily oxidized in the natural environment. Although it is a progressive damage and is not difficult to detect, it is important to prevent its progress during maintenance.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Section loss	Rust on the surface
	e.g	The surface of steel material has expanded due to corrosion or sectional part is reduced due to the disappearance of the corroded part.	Rust pitting on the surface.
Range (Z)	Grade	Widely	Locally
	e.g	Corrosion or rust is expanding all over the member.	Corrosion or rust exist only locally within the water leaking area.

- RATING

(Y)	(Z)	Secondary Member	Main Member
Major	Major	4	4
	Minor	3	4
Minor	Major	3	4
	Minor	2	3

2. CRACKS

Most cracks originate around the connection points. These points should be paid careful attention during inspection.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Detected	-
	e.g	-	-

- RATING

Y	All Members
Major	4

4. FALLING OFF (BOLTS, NUTS & RIVETS) - LOOSE CONNECTIONS

Connections generally with high tension bolts and rivets and in particular, bearing anchor bolts are mainly subject to this problem and need checking.

		Effects on load bearing capacity and durability	
		Major	Minor
Range (Z)	Grade	Connection :Many bearing rollers, etc:fallen off	Connection: a few bearing rollers, etc. Just before falling off.
	e.g	Falling off of 2 pieces of or more per splice part. Falling off of bearing roller etc.	Falling off of 1 piece per connection part.

- RATING

(Z)	All Members
Major	4
Minor	3

5. RUPTURE

It is a damage often detected on attached structures such as railings, joints, etc. but as it may also be detected on superstructures and substructures, all steel materials shall be subject to this checking.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Detected	-
	e.g	Rupture caused by corrosion or collision	

- RATING

(Y)	All Members
Major	4

6. PAINT DETERIORATION

The degree of paint deterioration is expressed in terms of 'depth', the condition of paint flaking i.e. peeling is regarded as a serious effect (Major) and that of colour changes to a lesser extent (Minor). Also, the range of deterioration is expressed by 'extension', if the condition is extended to all the part, it is regarded as a serious effect (Major) and if it is limited to a local area of the part, not so serious effect (Minor).

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Paint peeling off	Paint colour changed
	e.g	Paint of girder , railings etc. peel off	Paint of girder, railings etc.changed due to deterioration
Range (Z)	Grade	Widely	Locally
	e.g	Paint deterioration extends all over the steel part.	Paint deterioration exist only locally on steel part.

- RATING

(Y)	(Z)	All Members
Major	Major	3
	Minor	2
Minor	Major	2
	Minor	1

7. CRACKS

This is the most common damage to concrete materials and there are various causes such as design, construction, materials and environment. As these causes are very important for the evaluation of the level of damage, the judgment shall be done at first in the column 'position or pattern' (X) with consideration to location of cracks and its type, with reference to typical cracks shown in the figures attached.

		Effects on load bearing capacity and durability	
		Major	Minor
Position or Pattern (X)	Grade	Critical	Uncritical
	e.g	Superstructure common to RC and PC:1,2,3,4,5,6,7,8,12 only.PC: 1,2,3,4, Substructure : 3,5,6,7,8,9, 10,11,12	Superstructure: common to RC and PC 9,10,11 only. PC : 6,7,8, Substructure:1,2,4
Depth (Y)	Grade	Wide	Hair Line
	e.g	RC Structure: 0.3mm or more PC Structure: 0.2mm or more	RC structure:less than 0.2mm PC structure:less than 0.1mm
Range (Z)	Grade	Interval	Interval
	e.g	Less than 50cm	50 cm or more

- RATING

X	Y	Z	Main Member	Secondary Member
Major	Major	Major Minor	5 4	4 3
	Minor	Major Minor	3 3	2 2
Major	Major	Major Minor	4 3	4 3
	Minor	Major Minor	2 1	2 1



Fig. F-1 Location & Type of Typical Cracks in RC/PC superstructures

Fig. F-2 Location & Type of Typical Cracks in PC superstructures

Fig. F-3 Location & Type of Typical Cracks in substructures

8. FLAKING AND REBAR EXPOSURE

In the case of rebar exposure due to flaking of concrete or insufficient cover is considered as major and in the case of only flaking as minor. The grade of extension of damage is expressed in terms of the quantity, separately for superstructure and substructure and this can be considered as a standard.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Rebar is exposed	Flaking only
	e.g		
Range (Z)	Grade	Damage on large area	Damage on small area
	e.g	Substructure: 1.0 sq.m or more Superstructure: 0.1 sq.m or more	Substructure Less than 1 sq.m Superstructure: Less than 0.1 sq.m

- RATING

(Y)	(Z)	Main Member	Secondary Member
Major	Major	4	3
	Minor	3	2
Minor	Major	3	2
	Minor	2	2

9. FREE LIME

It refers to the phenomena in which the lime contained in concrete oozes out through cracks, etc., by the action of rainwater which has soaked into the concrete. A similar substance also oozes out from alkali aggregate reactions and it is difficult to distinguish visually one from the other. For distinguishing between these two substances at the site, hydrochloric acid is put on to the substances, the substance oozed out by alkali aggregate reaction (silica) produces hydrogen and leaves a silica deposit on the surface. The grading by extension of damage is the same as that for the case of flaking and rebar exposure.



		Effects on load bearing capacity and durability	
		Major	Minor
Range (Z)	Grade	Damage on large area	Damage on small area
	e.g.	Substructure 1m ² or more Superstructure: 0.1m ² or more	Substructure: Less than 1m ² Superstructure: Less than 0.1m ²

- RATING

Z	Main Member	Secondary Member
Major	4	3
Minor	3	2

11. WEAR AND ABRASION

It refers to the condition of damage where the surface concrete of substructures are worn and abraded by water or acid water. The extent of damage, whether it is major or minor, is indicated by rebar exposure.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Rebar is exposed	Rebar is not exposed
	e.g		
Range (Z)	Grade	Damage on large area	Damage on small area
	e.g	Substructure: 1.0 sq.m or more Superstructure: 0.1 sq.m or more	Substructure: Less than 1 sq.m Superstructure: Less than 0.1 sq.m

- RATING

Y	Z	All Members
Major	Major	4
	Minor	3
Minor	Major	3
	Minor	2

12. SLIPPING OFF (CHIPPING)

It refers to the damage when a piece of concrete chips off the floor deck (including filling concrete) and which is accompanied by hexagonal cracks. The reason why it is graded 4 is because the necessity to perform emergency repairs depends on the inspector's judgment relative to the position of the chip and peripheral conditions in the same way as for the case of girder rupture.



		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Concrete mass chipping off	-
	e.g.	Type of damage which can be seen on concrete floor deck accompanied with hexagonal cracks.	-

- RATING

Y	All Members
Major	4

14. SLAB CRACKS

The importance is judged depending on whether the crack is running in one direction or two directions. The depth is graded depending on the pattern of damage, i.e. the effect of those accompanied with rust liquid is considered as major, those with a water leak as intermediate and those without any sign at water as minor. The width of crack is considered in the same way as that for Item 7 'Cracks' herein. Further, the interval between cracks is indicated here as the extent of damage and the criteria for judging whether it is major or minor depends on the spacing of crack (more than 50 cm is considered minor).

		Effects on load bearing capacity and durability		
		Major	Intermediate	Minor
Position or pattern (X)	Grade	2 directions		1 direction
	e.g.			
Depth (Y)	Grade	Cracks with rusty liquid or large width	Cracks with water leak or the width of gap is intermediate	Cracks without any sign at water or the width of gap is small
	e.g.	Presence of rusty liquid along the rebar, or the width is 0.3m or more	Presence of water leak and free lime along the cracks, or the width is 0.2 mm or more and less than 0.3mm	RC structure: 0.2 mm
Extension (Z)	Grade	Minimum gap small	-	Minimum gap large
	e.g.	Minimum width of gap is less than 50cm	-	Minimum width of gap is 50cm or more

- RATING

X	Y	Z	All Members
Major	Major	Major Minor	4 4
	Intermediate	Major Minor	4 3
	Minor	Major Minor	3 2
Minor	Major	Major Minor	3 3
	Intermediate	Major Minor	3 2
	Minor	Major Minor	2 2

15. ABNORMAL SPACING OF GAP (JOINT)

It refers to the condition where the spacing is abnormally wide or there is no opening left at all. An abnormal spacing condition is sometimes accompanied by damage to bearings and backwalls, it is necessary to check them at the same time.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Detected	-
		The spacing is so abnormally wide that the face plates are completely disconnected, or there is almost no spacing.	-

- RATING

Y	All Members
Major	4

16. DIFFERENCE IN LEVEL (BRIDGE APPROACH & JOINTS)

Shock produced by difference in level or corrugation cannot be ignored beyond a certain value. The value which is slightly more severe than the aimed value for ordinary roads is adopted, the value 15mm - 20mm is targeted for bridges in this criteria. (Relating to this, it has been proved by an experiment conducted by the Civil Research Institute Japan that shock greater than design value is produced when the difference in level reaches 20mm.)

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Considerably rough	Rough
		Unevenness of the direction bridge axis is 20mm or more	Unevenness of the direction of bridge axis is 10 - 20mm

- RATING

Y	All Members
Major	4
Minor	2

17. POT HOLE

Pot holes are bowl-shaped holes of various sizes in the surface course resulting from localized disintegration. As pot-holes, flaking and subsidence affect vehicles (especially two - wheeled vehicles) on the road and often cause problems to safety, particular care must be taken. Holes of less than 10mm - 50mm are considered as minor and those of 50mm or more as major. If the pot hole is 50mm or more damage to the floor deck is also possible, it is necessary therefore to carry out an inspection below the pavement.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Hole is deep	Hole is not so deep
	e.g	Hole is 50mm or more in depth	Hole is 10mm - 50mm in depth
Range	Grade	Diameter of hole is large	Diameter of hole is small
	e.g	Diameter of hole is 20cm or more	Diameter of hole is less than 20cm.

- RATING

Y	Z	All Members
Major	Major	4
	Minor	4
Minor	Major	4
	Minor	3

18. PAVEMENT CRACKS

It is unlikely that a crack on the bridge pavement would exceed 5mm in width, however, should such occur damage to the floor deck is possible. It then being necessary, therefore, to carry out an inspection below.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Crack width is large	Crack width is small
		Crack width is 5mm or more	Crack width on paving is less than 5mm

-RATING

Y	All Members
Major	4
Minor	2

19. RUTTING

Rutting is an unevenness on road pavement in a direction perpendicular to the bridge axis. As rutting causes accumulation of water from rainfall and produces problems such as splash and reduction of frictional resistance at high speed, it must be remedied. Unevenness of less than 20mm is not considered as damage, unevenness between 20mm to 30mm is considered as minor and that of 30mm or more as major.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Considerable uneven	Uneven
		Unevenness of direction perpendicular to bridge axis is 30mm or more	Unevenness of direction perpendicular to bridge axis is 20 to 30mm

- RATING

Y	All Members
Major	4
Minor	2

21. MATERIAL DETERIORATION

This covers material deterioration due to exhaust gases, salt air, etc on parts other than steel materials, such as on concrete, bearings, expansion joints, etc.

		Effects on load bearing capacity and durability	
		Major	Minor
Range (Z)	Grade	Widely	Locally
	e.g	Material deterioration extends all over the part. (Applicable to concrete, rubber, plastic, etc)	Material deterioration exist only locally on the part. (Applicable to concrete rubber, plastic, etc)

- RATING

Z	All Members
Major	4
Minor	3

22. WATER LEAK AND PONDING WATER

This includes water leakage from a damaged part of floor deck, expansion joint, drainage, etc. and ponding water in bearings, paving, etc.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Water leak and water accumulation detected.	-
	e.g	Water is leaking from below the floor deck, main girder, expansion joint, drainage basin jointing point, etc. Water is accumulating in the vicinity of bearings.	-

-RATING

Y	Main Members	Secondary Members
Major	4	2

23. ABNORMAL NOISE (POUNDING)

Abnormal noise produced by any structural defects shall be rectified, especially, in the case of loose bolts. In cases where the generation point cannot be determined, the presence of abnormal noises shall be noted.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Abnormal noise detected	-
	e.g	Abnormal noise is heard from stopper for shifting of movable bearings and girder	-

- RATING

Y	All Members
Major	4

24. ABNORMAL VIBRATION

It is difficult to check abnormal vibration accurately. The presence of abnormal vibration shall be checked by standing on the midspan of the superstructure and on the road in the vicinity of substructure when vehicles pass.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Abnormal vibration detected	-
	e.g	Abnormal vibration or shaking detected on main girder.	-

-RATING

Y	All Members
Major (Detected)	4

25. ABNORMAL DEFLECTION

It is difficult to check abnormal deflections accurately. The presence of abnormal deflections shall be checked by standing on the midspan of superstructure and on the road in the vicinity of substructure when vehicles pass.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Abnormal deflection detected	-
	e.g	Abnormal deflection detected on main girder etc.	-

- RATING

Y	All Members
Major (Detected)	4

26. DEFORMATION

This covers the deformation of steel parts of girders, railings, etc. caused by a traffic impact. As it is difficult to express quantitative affects on the load bearing capacity and durability, the grade of the affect is judged by whether or not deformation of the parts themselves is considerable.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Considerable deformation detected.	Deformation detected
	e.g	Girder, railings, etc. are considerably deformed by vehicles collision etc.	-

RATING

Y	All members
Major	4
Minor	2

27. SEDIMENT ACCUMULATION/VEGETATION

This refers to sediment accumulation with or without vegetation in catch basins and in the vicinity of bearings. Once catch basins become clogged with sediment, the drainage does not work properly causing leaking and accumulation of water. Besides, sediment accumulated in the vicinity of bearings not only accelerates corrosion and deterioration but also obstructs visual detection of serious defects. If sediment accumulation is reported, it shall be quickly cleaned.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Sediment accumulation and vegetation	Sediment accumulation only detected
	e.g	Sediment accumulated in catch basin and in the vicinity of bearing	-

- RATING

Y	All members
Major	3
Minor	2

28. SETTLEMENT

Foundations and bearings shall be subjected to checking. Settlement of the foundation is the easiest damage to check. As for grading of defect, settlement of 25mm or more is considered as major and that of less than 25mm as minor. In the case of a continuous girder, settlement at a point of $S = L/2000\text{mm}$ or more is considered as major and that of less than $L/2000\text{mm}$ as minor. As the settlement of bearings is difficult to detect it must be estimated based on the condition of anchor bolts and bearing mortar. If there is doubt about the settlement of the bearing, a detailed inspection shall be urgently carried out. (L is span length in meter)

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Settlement of bearing. Considerable settlement of foundation	There is doubt of settlement of bearing. Settlement of foundation.
e.g		Settlement of bearing is 25 mm or more for simple girder and $S = \text{greater than } L/2000\text{mm}$ for continuous girder in case of bridge approach difference in level $> 30\text{mm}$.	Settlement of bearing is; less than 25mm for simple girder and $S = \text{less than } L/2000\text{mm}$ for continuous girder. In case of bridge approach difference in level $< 30\text{mm}$

- RATING

Y	All members
Major	4
Minor	3

29. ABNORMAL MOVEMENT

Foundation and bearings shall be subjected to checking. For foundations, it means sideways movement. For bearings, it means abnormal displacement relative to girder or shoe due to abnormal lateral force, etc.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Abnormal movement of bearings Considerable movement of foundation	Suspected abnormal movement of bearing Movement of foundation.
	e.g	Substructure has: moved considerable due to sideways displacement of the foundation	Substructure has moved due to displacement of the foundation.

- RATING

Y	All members
Major	4
Minor	3

30. DIP

Foundations and bearings shall be subjected to checking. Regarding foundations, it covers the case of an abutment or pier becoming inclined due to displacement to the side or uneven settlement. Regarding bearings, it covers the case of the shoe become abnormally depressed due to an abnormal lateral force, etc.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth	Grade	Bearing has dipped Foundation has dipped considerably	Suspected dipping of bearing and foundation.
	e.g	Substructure has dropped considerably due to displacement	Substructure has dipped due to displacement of the side part.

- RATING

Y	All members
Major	4
Minor	3

31. SCOURING

This covers the case of the foundation and peripheral river bank being scoured or carried away by flowing water. In particular, for bridges located on upstream reaches of a river, special care must be taken, and checking is very important, especially, after typhoon, torrential rainfall, etc.

Further, in the case of direct foundations, the effect of scouring on the safety of the bridge is greater as compared with that of piled and caisson foundations. When scouring is considerable, in the case of direct foundations shifting of movable bearings is possible and emergency steps must be taken.

		Effects on load bearing capacity and durability	
		Major	Minor
Position or Pattern (X)	Grade	Direction foundation	Piled foundation Caisson foundation
	e.g	-	-
Depth	Grade	Considerable scouring is detected	Scouring is detected
	e.g	Foundation is considerably scoured by flowing water	Foundation is scouring by flowing water

- RATING

Y	Z	All Members
Major	Major	4
	Minor	4
Minor	Major	4
	Minor	3

32. DEFECT

This covers the case of a concrete girder, railings, rubber bearings, etc. having a partial deficiency caused by car crash or abnormal lateral force.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth	Grade	Considerable deficiency detected	Deficiency detected
	e.g	Girder, pedestrian railings, traffic etc. have considerable deficiency due to vehicle collision, etc.	Girder, pedestrian railings, traffic railings etc. have deficiency due to vehicle collision, etc.

- RATING

Y	All members
Major	4
Minor	2

33. EROSION

This covers the case of foundation and peripheral river banks being eroded or washed away by flowing water.


In particular for bridges which are located on river bends, special care must be taken.

		Effects on load bearing capacity and durability	
		Major	Minor
Depth (Y)	Grade	Considerable erosion detected	Erosion detected
	e.g	River bank up and down stream of abutment has been heavily eroded	Slightly eroded

- RATING

Y	All members
Major	4
Minor	3

FIG. F - 1 LOCATION & TYPE OF TYPICAL CRACKS
IN RC/PC STRUCTURE



**FIG. F - 2 LOCATION & TYPE OF TYPICAL CRACKS
IN PC SUPERSTRUCTURE**





FIG. F - 3 LOCATION & TYPE OF TYPICAL CRACKS
IN SUBSTRUCTURE



ANNEX - G
STRUCTURAL ASSESSMENT CRITERIA

TABLE OF CONTENTS

1.	General	G-1
2.	Geometric Design Standard	G-1
3.	Bridge Width	G-2
4.	Free Board	G-2
5.	Bridge Loading.....	G-3
6.	Design Method Applied	G-10
7.	Bridge Planning	G-10
8.	Superstructure Design	G-14
9.	Substructure Design	G-15
10.	Load Combination	G-20
11.	Material and Allowable Stress	G-22
12.	Design Standard	G-25

LIST OF FIGURES

Figure	G-1	Normal Bridge Cross-Section	G-2
Figure	G-2	Cross-Section of a Bridge with Side Walk ...	G-2
Figure	G-3	Application LTAL UDL and KEL Load	G-5
Figure	G-4	Applicable Types of Concrete Bridge	G-12
Figure	G-5	Applicable Types of Steel Bridge	G-12
Figure	G-6	Applicable Types of Pier	G-13
Figure	G-7	Applicable Types of Abutment	G-13
Figure	G-8	Applicable Types of Foundation	G-14
Figure	G-9	Chart For Calculating the Ultimate Bearing Capacity of the Ground at Pile Tip Per Unit Area	G-18
Figure	G-10	Coefficient of Bearing Capacity	G-20

LIST OF TABLES

Table G-1	Free Board For Bridge Over River	G-3
Table G-2	The Unit Weight of Bridge Construction Material	G-3
Table G-3	The Unit Weight of Ancillary Bridge Construction Material	G-4
Table G-4	LTAL Load For Various Loaded Length	G-4
Table G-5	Collision Load on Bridge Support	G-6
Table G-6	Collision Load on Bridge Parapet	G-7
Table G-7	Resistance Coefficient of Bridge Pier	G-8
Table G-8	Classification of Spread Footing and Caisson Foundation	G-15
Table G-9	Classification of Caisson and Pile Foundation	G-15
Table G-10	Allowable Bearing Pressure For Spread Footing	G-16
Table G-11	Angle of Internal Friction For Abroad Basic Soil Type	G-16
Table G-12	Pile Safety Factor	G-17
Table G-13	Skin Friction Force	G-19
Table G-14	Shape Factor of the Base of Caisson	G-20
Table G-15	Load Combination For Allowable Stress Design	G-21
Table G-16	Load Combination at ULS and Appropriate Partial Factor	G-22
Table G-17	The Allowable Compressive and Shear Stress of Concrete	G-23
Table G-18	The Permissible Stresses in Steel Reinforcement	G-23
Table G-19	The Permissible Stresses in Structural Steel	G-24

ABBREVIATION

(Alphabetical Order)

Bc	Concrete Bearing
Bs	Steel Bearing
Bt	Transversal Bearing
DFWL	Design Flood Water Level
DID	Drainage Irrigation Department
JKR	Jabatan Kerja Raya
KEL	Knife-Edge Load
LTAL	Long Term Axle Load
OECD	Organization for Economic Cooperation and Development
UDL	Uniformly Distributed Load

STRUCTURAL ASSESSMENT CRITERIA

1. General

Malaysia was once ruled by the British and as a result, bridges in Malaysia have traditionally been designed to British Standards. Throughout the years various revisions of the British Standard and modifications on the application of the standard to suit Malaysian conditions have been carried out resulting in bridges being designed to various loading and design specifications. Even today various standards have been used in bridge design, JKR Bridge Design Manual for example, adopted BS153 as its design standard while the current applicable British Standard is BS 5400 which is used by some bridge designers in Malaysia. For the purpose of this study the design criteria to be applied are based on JKR bridge design practice except where the specification is not clear then The Japanese Bridge Design Specification will suffice. The design criteria covers the following aspect of design:-

- Geometric design standard
- Bridge clearance
- Bridge width
- Bridge loading
- Design method
- Material and allowable stress
- Superstructure design
- Substructure design
- Applicable bridge design standard

2. Geometric Design Standard

The geometric design standard to be applied is based on the JKR "ARAHAN TEKNIK (JALAN) 8/86". The summary of the design standard is as follows:-

- | | |
|-------------------------------------|----------------|
| - Design speed..... | 70 - 100 Km/Hr |
| - Lane width for 2-lane..... | 3.5m |
| - Shoulder (general area) | 3.0m |
| (mountainous area)..... | 1.5m |
| - Sidewalk..... | 2.0m |
| - Vertical Clearance (over road) .. | 5.0m |
| (over rail) .. | 6.5m |
| - Crossfall..... | 2.5% |
| - Superelevation rates(max)..... | 0.10 m/m |
| - Horizontal radius (min.)..... | 465m |
| - Vertical Gradient..... | 6% |

3. Bridge Width

For the purpose of detailed assessment work, design standard of R5 road is applied in principle. However the width of the bridge depends on the availability of side walk. The difference between two types of bridge width requirements is shown in Figure G-1 and G-2 below;

Figure G-1 Normal Bridge Cross-Section





Figure G-2 Cross-Section of a Bridge With Sidewalk



4. Free Board

Hydraulic analysis shall be carried out based on DID Hydrological procedures (either Hp No.5, Hp No.11 or Hp No.4). The free board requirement is not clearly stated in the JKR bridge Design Manual, thus the recommendation given in the Japanese bridge design specification is adopted. The soffit of the bridge deck shall be designed such that it is above the designed flood level with a free board as tabulated in Table G-1.

Table G-1 Free Board For Bridge Over River

Free Board	Size of River	Design flood flow Q_f (cumec)
0.50m	Small river	$Q_f < 500$
1.00m	Medium river	$500 < Q_f \leq 2000$
1.50m	Big river	$Q_f > 2000$

5. Bridge Loading

Loads acting on the bridge structure include Dead Load, Live Load, Load due to centrifugal force, Tractive/Braking Force, collision load on bridge parapet, collision load on bridge support, Wind Load, Load due to creep, shrinkage and temperature; buoyancy or uplift force and Forces of Stream Current and Debris. In the detailed assessment the following type of bridge loadings shall be considered:

- + Dead Loads.
- + Primary Live Loads.
- + Tractive/Braking force.
- + Centrifugal force.
- + Collision load on bridge support.
- + Collision load on bridge parapet.
- + Pedestrian load (sidewalk loading).
- + Load due to temperature.
- + Forces due to stream current, debris and floating log.
- + Forces due to earth pressure.

(1) Dead Loads

The unit weight of bridge construction material as given in Table G-2 below may be used for calculation of the dead load:-

Table G-2 The Unit Weight of Bridge Construction Material

Material	Unit Weight (kN/cu.m)
Reinforced Concrete	25
Prestressed Concrete	25
Asphalt Pavement	23
Steel or Cast Steel	77
Cast Iron	71
Aluminium Alloys	28
Timber	8
Stone masonry	27
Bituminous water proofing material	11
Compacted sand, earth or gravel	19
Loose sand, earth or gravel	16

The unit weight of ancillary bridge construction material as given in Table G-3 below may be used for calculation of superimposed dead load:-

Table G-3 The Unit Weight of Ancillary Bridge Construction Material

Material	Unit Weight
100mm nom.dia. water main	0.24 (kN/m)
150mm nom.dia. water main	0.46 (kN/m)
200mm nom.dia. water main	0.73 (kN/m)
250mm nom.dia. water main	1.13 (kN/m)
300mm nom.dia. water main	1.47 (kN/m)
380mm nom.dia. water main	2.08 (kN/m)
10.0m high Lamp Post	1.31 (kN)
12.0m high Lamp Post	1.71 (kN)
RC Parapet + Handrail	7.32 (kN/m)
Std.Kerb + Handrail	4.21 (kN/m)
Std.Kerb Divider	1.80 (kN/m)

(2) Primary Live Loads

Live load to be applied shall be LTAL loading which is applied on each notional lane. Details of the application of the LTAL is as follows:-

- Notional Lanes

The width of each notional lane is fixed at 2.5m within the carriageway of the structure. Only integer numbers of the notional lanes shall be used. Areas of the carriageway not covered by the notional lanes shall be loaded with the minimum pedestrian loading of 5 kN/m².

- LTAL Loading

LTAL Loading consists of a uniformly distributed Load and a Knife-Edge Load combined, or a twin wheel load. The Nominal Uniformly Distributed Load (UDL) to be applied on a 2.5m lane width is as shown in Table G-4 below:-

Table G-4 LTAL Load For Various Loaded Length

Loaded Length L(m)	LTAL (kN/m/Lane)
$L \leq 20\text{m}$	$w = 176.8 \cdot L^{-0.6}$
$20\text{m} < L \leq 40\text{m}$	$w = (93.6 + 4.16 \cdot L) \cdot L^{-0.6}$
$40\text{m} < L \leq 50\text{m}$	$w = 260 \cdot L^{-0.6}$

where:

"L" is the Loaded length in meter and "w" is the load intensity in kN per meter of notional lane width.


The KEL per notional lane width shall be taken as 100 kN. No dispersal shall be assumed for UDL and KEL.

Twin nominal wheel load alternative to UDL and KEL consist of two 112 kN wheels spaced at 1.8m apart. Each of the wheel is uniformly distributed over a circular or square contact area with effective pressure of 1.1 N/mm^2 (i.e. 360 mm diameter and 320mm side effectively). The wheel load is dispersed at spread-to-depth ratio of 1 horizontal to 2 vertical through asphalt and 1 horizontal to 1 vertical through structural concrete.

- Application of LTAL Loading

The UDL and KEL loads shall be applied on two notional lanes so as to give the worst effects on the structure. The rest of the notional lanes shall be loaded with 0.6 times LTAL UDL and KEL as illustrated in Figure G-3 below. The carriageway width shall be taken as the width between raised Kerbs. In the absence of raised kerbs, it is the width between safety fences, less set back of 0.6m.

Figure G-3 Application LTAL UDL and KEL Load



NOTE: LANE LOADINGS ARE INTERCHANGEABLE FOR THE MOST SEVERE EFFECTS

(3) Load Due To Temperature

Load effect due to temperature difference can generally be ignored in the preliminary design. However the following data may be used if required :-

- The overall bridge temperature shall be taken as 20°C .
- Coefficient of thermal expansion for structural steel and for concrete shall be taken as 12×10^{-6} and 10×10^{-6} respectively.

(4) Centrifugal Load

Centrifugal load on curved bridges shall be applied on any two notional lanes at 50m centres acting radially at the surface of the road and parallel to it. The centrifugal force shall be determined as follows:-

$$F_c = \frac{30000}{(r+150)}$$

where F_c = Centrifugal force (kN)
 r = Radius of curvature of lane (m)

Each load F_c shall be either taken as a single load or subdivided into two parts of $\frac{1}{3} F_c$ and $\frac{2}{3} F_c$ at 5 m centres longitudinally, whichever gives the lesser effect. A vertical live load of 300 kN, distributed uniformly over the notional lane for a length of 5m shall be considered to be acting together with each F_c . Where the centrifugal load is subdivided, the vertical live load shall be subdivided in the same proportions.

(5) Collision Load on Bridge Support

The nominal collision loads on bridge support on bridges over the highways are given in Table G-5 below together with their direction and point of application.

Table G-5 Collision Load on Bridge Support

Type of load transmitted	Load normal to the carriageway below (kN)	Load parallel to the carriageway below (kN)	Point of application on bridge support.
Load transmitted from guard rail	150	50	Any one bracket attachment point or, for free standing fences, any one point 0.75m above carriageway level.
Residual load above guard rail	100	100	At the most severe point between 1m and 3m above carriageway level.

Bridge supports shall be capable of resisting the load transmitted from the guard rail applied simultaneously with the residual load above the guard rail. Loads normal to the carriageway are to be considered separately from loads parallel to the carriageway. No other primary live loads are required to be considered on the bridge.

(6) Collision Load on Bridge Parapet

Elements supporting bridge parapets shall be designed to resist loads due to vehicle collisions. The nominal load shall be as given in Table G-6 below:-

Table G-6 Collision Load on Bridge Parapet

Type of parapet	Collision load on parapet	
	High level containment	Normal level containment
Concrete	Moment 25 kNm/m	Moment 12.5 kNm/m
Metal	Force 50 kN	Force 25 kN

For concrete parapet the moment shall be applied uniformly at the parapet base. The transverse collision force on metal parapet shall be applied equally between the number of effective longitudinal members and acting at the centroid of the members. The associated primary live load to be applied shall be twin wheel load of 112 kN each spaced at 1.8m apart.

(7) Sidewalk Loading

Sidewalk loading shall be taken as 5 kN/m² for span length up to 50m.

(8) Tractive/Braking Force

The longitudinal load resulting from traction or braking of vehicles shall be applied at the road surface and parallel to it in one notional lane only. The nominal tractive/braking load shall be taken as follows:-

$$T = 8 \cdot L + 200 \text{ (kN)}; \text{ (but not more than 450 kN)}$$

where; L is Loaded length (m).

(9) Forces from Stream Current, Debris and Floating Log

- Force due to Stream Current

All piers and other parts of the structure which are subjected to the forces from flowing water, or debris shall be assessed accordingly. The force induced shall be calculated as follows:-




$$P = K \cdot V^2 \cdot A$$

[The forces induced by flowing water shall be taken to be acting at $0.6H$ from river bed]

where :

- P = Pressure (kN).
- V = Maximum current velocity (m/s).
- A = Vertically projected area of pier (m^2).
- H = Depth of water (m).
- K = Constant determined by the shape of the pier as shown in table G-7 below.

Table G-7 Resistance Coefficient of Bridge Pier

Shape of the end of bridge pier facing the stream	Constant
	0.07
	0.04
	0.02

- Force due to debris blockade

Where blockage by debris is likely to occur, allowance shall be made for hydrodynamic forces acting on the minimum depth of 1.2m of debris. The length of debris blockage affecting any pier shall be taken as half the sum of the adjacent spans. However, for minor bridges, the debris loadings need not be considered if the free board over the maximum flood level is more than 1.5m. The pressure P, induced by the debris on the pier shall be taken as follows;

$$P = 0.517 \cdot V^2 \quad (\text{kN/m}^2)$$

Where V is the approach flow velocity (m/s).

- Forces due to log impact

Where floating logs are likely, the force exerted by 10 tonne logs traveling at normal stream velocity shall be assessed. However the force due to log impact shall not be applied concurrently with debris force. The force due to log impact shall be calculated as follows;

$$F = 0.1 \cdot W \cdot V \quad (t)$$

Where :

W = Weight of log (10 Tonne).

V = Normal stream velocity (m/s).

(10) Forces due to Earth Pressure

Structures which retain earthfills shall be assessed to withstand pressure as given by Rankine's formula. In normal bridge design, because horizontal granular backfill is often used behind abutments, ground water conditions can be ignored. The earth pressure acting on the abutment depends on whether the abutment is movable type or not and also the type of soil. For preliminary design the following formula shall be used:-

- Earth pressure acting on movable walls;

(a) Sandy soil

$$P_a = K_a \cdot \Gamma \cdot h + K_a \cdot q$$

$$P_p = K_p \cdot \Gamma \cdot h + K_p \cdot q$$

(b) Cohesive soil

$$P_a = K_a \cdot \Gamma \cdot h - 2 \cdot c \cdot \sqrt{K_a} + K_a \cdot q$$

$$P_p = K_p \cdot \Gamma \cdot h + 2 \cdot c \cdot \sqrt{K_p} + K_p \cdot q$$

(2) Earth pressure acting on fixed wall;

$$P_a = K_s \cdot \Gamma \cdot h + K_s \cdot q$$

where;

Γ = Bulk density of earth (kN/m³).

P_a = Active earth pressure (kN/m²).

P_p = Passive earth pressure (kN/m²).

K_a = Coulomb's active earth pressure coefficient.

K_p = Coulomb's passive earth pressure coefficient.

K_s = Coefficient of earth pressure at rest.

h = Height of abutment (m).

c = Soil cohesion (kN/m²).

q = Surcharge (kN/m²).

The internal angle of friction of granular backfill material behind abutments shall be assumed to be 30° . Live Load surcharge for suitable material properly consolidated shall be taken as 20 kN/m^2 .

6. Design Method Applied

The assessment of existing bridges and rehabilitation work jointed directly to the existing bridges shall be in accordance with elastic design methods (allowable design stress method), while for an adding sidewalk which is not attached to the existing bridge or a completely new bridge for rehabilitation by total replacement, the design shall be carried out using ultimate limit design methods.

The reasons for adopting these two different design methods in the preliminary design are :

- Almost all old bridges in Malaysia were designed to BS153 which follows the elastic design principal.
- Quality of materials used in these bridges is often inconsistent (i.e. strength variation is very wide)

Thus, it is safe to apply elastic design method for the assessment and the rehabilitation design. However, quality of material and accuracy of design for an independent structure can be controlled properly within very low tolerance. Therefore, it is rational to apply ultimate limit design method only for an independent structure which will not be attached to the existing bridge.

The elastic design method shall be based on the guidelines given in JKR Bridge Design Manual, while for ultimate limit design the provisions prescribed in BS5400 shall be applied.

7. Bridge Planning

(Applicable to only total bridge replacement)


- **Determination of Bridge Length**

The clearances of a bridge controls the bridge's length as indicated in the following. From the intersection of ordinary water level and ground surface as shown in the sketch below, the proposed slopes of protection work follow the slope of the bank as close as possible, having in mind not to constrict the area of the water way required. Then the top of roadway elevation shall be determined based on the Design Flood Water Level (DFWL).

The distance between the intersections of the slopes of protection work and the top of roadway elevation represents the length of bridge required, which is the total distance between

the back of backwalls. Minor adjustments shall be made, if necessary, to suit the length of the superstructure is of standard type.

Free board under a bridge shall be determined taking into consideration the necessary space needed for river navigational ways and maintenance, etc. The river administrative clearance from the bottom of the bridge girder or beam to design flood water level will vary from 0.5m to 1.5m depending on the size of river.



The design elevation of the soffit of bridge girder shall not be lower than the highest water level plus the free board.

Free board (below the bridge) - For non navigable river; general clearance between D.F.W.L. and the bottom of the lowest member of superstructure shall comply with the requirement stated in Table G-1.

Vertical Clearance (Navigable river); The DID or Marine Department shall be consulted for determining the minimum horizontal and vertical clearances under a bridge before preparing the final design and plans of the proposed bridge.

- Applicable Bridge Types

To select the applicable types of superstructure, substructure and foundation, the basic and important factors to be taken into consideration shall include economical construction, stability and safety, construction period and ease of maintenance and operation.

Figure G-4 Applicable Types of Concrete Bridges




Figure G-5 Applicable Types of Steel Bridges




Figure G-4 and Figure G-5 show the relationship between the superstructure type and the span length based on the samples of bridges. The following items are fundamental in the selection of superstructure types :

- Reinforced concrete structures are usually selected because of maintenance is considered easy except where special cases require steel structures.
- Reinforced concrete beams and steel I-beam types are applicable for short spans (length 10m to 15m).
- Prestressed concrete girders, and steel plate girder types are applicable for medium spans (length 20m to 50m).

- Prestressed concrete box girder, steel through truss and ranger girder types are to be applied for long spans (length 60m to 150m).

Figure G-6 Applicable Types of Pier






TYPE		HEIGHT(m)					REMARKS
		0	10	20	30	40	
P-1	COLUMN TYPE	0	15				
P-2	RIGID FRAME TYPE (1 STOREY)	5	15				
P-3	RIGID FRAME TYPE (2 STOREY)		15	25			
P-4	WALL TYPE		10	30			
P-5	WALL TYPE (1 STOREY)			25	40		

Figure G-7 Applicable Types of Abutment








TYPE		HEIGHT(m)				REMARKS
		0	10	20	30	
A-1	CHAIR TYPE	5				
A-2	GRAVITY TYPE	4				
A-3	SEMI GRAVITY TYPE	4	6			
A-4	INVERSE T-TYPE	6	10			
A-5	BUTTRESSED TYPE		10	15		
A-6	BOX TYPE		10	20		
A-7	SUSTAINING WALL TYPE		10	15		

Figure G-6 and G-7 show the applicable substructure types in accordance with the required structural height of a bridge. The selection of substructure types is based not only on the specified figures but also on the following considerations :

- Reinforced concrete structures.
- The cross section of pier column in the river; circular or elliptical and rectangular shape with no restricted conditions.

- Non sliding of the back fill materials behind abutment structure is considered in the selection in the abutment type to avoid the approach settlement of the approach.

Figure G-8 Applicable Types of Foundation

TYPE	DEPTH	DEPTH (m.)											USABLE DIA. (m.)	SOIL CONDITION	
		0	10	20	30	40	50	60	70	80	90	100		CLAYEY	SANDY
F-1	SPREAD FOUNDATION	0	10										—	○	○
F-2	R.C. PILE	5	15	25									0.3 — 0.5	△	△
F-3	P.C. PILE	12	30	40									0.35 — 0.5	△	△
F-4	STEEL PIPE PILE		20	60									0.5 — 0.8	○	○
F-5	CAST IN PLACE W/CASING	10	30	40									1.0 — 1.2		△
F-6	EARTH AUGER	10	30										1.0 — 1.5	○	×
F-7	REVERSE CIRCULATION DRILL		25	60								90	1.0 — 1.2	○	×
F-8	SHINSO PILE	10	25										2.0 — 5.0	—	—
F-9	OPEN CAISSON	5					55	70					—	—	—
F-10	PNEUMATIC CAISSON	10	30										—	—	—

NOTE :
 ○ : APPLICABLE
 △ : CONSIDERABLE
 × : NOT APPLICABLE

Figure G-8 shows the applicable foundation types in accordance with the required effective depth to sustain the load from Super-structures. The following are considered in selecting the foundation type :

- Possible construction depth is studied in consideration of soil conditions.
- The advantageous type is considered for works above water e.g. reverse circulation drill pile.
- The prefabricated pile types are advantageous when the bearing stratum is within a shallow range.

8. Superstructure Design

In principal, JKR standard design of superstructure shall be applied if applicable.

The design method and manners of the superstructures such as Reinforced Concrete, Prestressed Concrete and Steel Structure shall be based on the provisions prescribed in BS5400.

9. Substructure Design

The present practices of substructure design in Malaysia is based on BS8004. Since foundation design is universal and for practical purpose, Standard Specification of Highway Bridges in Japan for substructure design is adopted in this manual. Thus, followings are presented for reference.

The substructures can be founded on spread footing, caisson or pile. In general the type of foundation could be classified accordance to Table G-8 and G-9 below.

Table G-8 Classification of Spread Footing and Caisson Foundation

Type of Foundation	Ratio of D_f/B
Spread footing	$D_f/B \leq 1/2$
Caisson	$D_f/B > 1/2$

D_f : Effective embedded depth

B : Shorter width of foundation

Table G-9 Classification of Caisson and Pile Foundation

Type of foundation	Pile or Caisson Characteristic
Caisson	$\beta.L \leq 1$
Short pile	$1 < \beta.L \leq 3$
Long pile	$\beta.L > 3$

where;

L = embedded length of caisson or pile (m).

β = characteristic value of caisson or pile $= \sqrt[4]{kD/4EI}$ (m^{-1}).

EI = flexural rigidity of caisson or pile (kNm^2).

D = Diameter of caisson or pile (m).

k = coefficient of horizontal subgrade reaction of caisson or pile (kN/m^3).

note:-

1. 'k' for caisson shall be taken as a mean value from ground surface to the point of $\frac{1}{2}$ depth.

2. 'k' for pile shall be taken as a mean value from ground surface to the point of $\frac{1}{6}$ depth.

In principle the foundation shall be designed so that it is stable against bearing, overturning and horizontal movement.

(1) Footing Foundation

The depth of footings shall be determined depending on the type and characteristic of the foundation material. In general, for footing not founded on rock, the base of footing should be founded at depth preferably not less than 1.2m below the stream bed for abutment and 1.8m for pier. This preferred minimum depth shall be increased depending on the site condition. For assessment and preliminary design purposes and where subsoil data is not available, the assumed bearing capacity and angle of internal friction for a broad basic soil type shall be as given in the Table G-10 and G-11 respectively.

Table G-10 Allowable Bearing Pressure For Spread Footing

Type of Bearing Material	Consistency	Allowable Bearing Pressure kN/m ²	
		Ordinary Range	Recommended for use
Alluvial Soil	Soft	0 - 80	50
	Medium	100 - 200	150
	Very stiff to hard	200 - 400	250
Homogeneous inorganic clay, sandy or silty clay	Soft	50 - 80	50
	Medium to stiff	100 - 300	200
	Very stiff to hard	300 - 500	300
Fine to Medium Sand	Loose	100 - 200	100
	Medium Dense	200 - 300	200
	Very Dense	300 - 400	300
Gravel, gravel-sand mixtures, boulder-gravel mixtures	Loose	200 - 300	200
	Medium Dense	400 - 600	400
	Very Dense	600 - 800	700

Table G-11 Angle of Internal Friction For A broad Basic Soil Type

Type of Bearing Material	Angle of friction
Alluvial Soil	25 - 30
Moist Sand	30 - 35
Submerged Sand	25 - 30
Gravel	35 - 40

In the preliminary design of footing, an appropriate safety factor has to be applied. The allowable bearing capacity of the footing shall not be more than 1/3 the ultimate bearing capacity of the ground. The horizontal reaction of the foundation shall not exceed 1/1.5 of the passive resistance of the ground. The spread footing shall have safety factors of 1.5 against sliding. The sliding resistance at the base of the footing shall be obtained as follows:-

$$H_u = C \cdot A + V \cdot \tan \phi$$

where;

- H_u = Maximum sliding resistance (t)
- C = cohesion of foundation and ground (t/m²)
- ϕ = friction angle between foundation and ground (°)
- A = effective loaded area (m²)
- V = vertical load (t), excluding buoyancy

(2) Pile Foundation

Generally the pile should penetrate not less than 3.0m into hard cohesive or dense granular material. In addition to that, for pile bents type pier, the pile should penetrate not less than 1/3 of the total length of pile. The bearing capacity of pile shall be estimated based on the following formula;

$$R_a = \{(R_u - W_s)/n\} + W_s - W$$

where;


- R_a = Allowable load carrying capacity of pile (t).
- n = Safety factor (refer to Table G-12).
- W_s = Eff. wt of soil replaced by the pile (t).
- W = Eff. wt of pile and earth in it (t).
- R_u = Ultimate bearing capacity of pile (t) = $q_d A + U \sum l_i f_i$
- A = Cross-sectional pile tip.
- q_d = Ultimate bearing capacity per unit area pile tip.
- U = Circumference of the pile.
- l_i = Penetration Length of pile/depth of stratum where skin friction is considered
- f_i = Maximum skin frictional resistance (t/m²).

Table G-12 Pile Safety Factor

Type of Pile	Safety Factor(n)
Load Bearing	3
Friction	4

In case of driven piles, the ultimate bearing capacity per unit area at the pile tip may be estimated from figure G-9 below;

Figure G-9 Chart For Calculating The Ultimate Bearing Capacity of The Ground at Pile Tip Per Unit Area



In Figure G-9 above ' q_d/N ' is given as a function of the ratio of the length of the pile embedded into the bearing stratum. The bearing capacity shall be taken as the sum of the end bearing capacity and skin friction capacity. In general, the bearing stratum could be considered to be 'good' when N -value for sand and gravel exceeds 30 and for cohesive soil N value is above 20 (ie q_u exceeds 0.4 N/mm^2). The following formula shall be used to calculate \bar{N} to be used for estimating the bearing capacity of a driven pile (ie. based on Figure G-9 above).

$$\bar{N} = \frac{(N_1 + N_2)}{2}$$

where;

\bar{N} = N value of the ground for design (but ≤ 40).

N_1 = N value of pile tip.

N_2 = Mean N value within the range of $4D$ upward from pile tip.

(If N value tend to decrease from pile tip downward, the mean value within the range of $2D$ from the pile tip shall be taken for N_2).

The equivalent penetration length shall be taken as the distance from the pile-tip to the point where the two equal areas surrounded by the N -value distribution curve and the line of \bar{N} .

The friction force depends on the type of pile and soil. The maximum friction force in Table G-13 below may be used for preliminary design.

Table G-13 Skin Friction Force

Soil Type	Skin friction force (t/m ²)	
	Cast in place	Cast in place driven
Sandy Soil	N/5 (≤ 10)	N/2 (≤ 12)
Cohesive Soil	C or N	c/2 or N/2

Note;

C = cohesion of the ground surrounding the pile and it may be assumed to be $\frac{1}{2}$ of the unconfined compressive strength of the undisturbed soil sample.

For preliminary design the N value need not be modified. The minimum distance between the centers of the piles in the outermost row and the edge of the footing may be 1.25 times the pile diameter in the case of driven piles and equal to the pile diameter in the case of cast-in-place concrete piles. The centre to centre spacing of both type of pile shall be 2.5 times the diameter of pile.

(3) Caisson Foundation.

In the preliminary design of caisson foundation, the vertical loads shall be supported at the base of the caisson only. The allowable bearing capacity may be obtained based on the following formula:-

$$q_a = 1/n \cdot (q_d - \Gamma_2 \cdot D_f) + \Gamma_2 \cdot D_f$$

$$q_d = \alpha \cdot C \cdot N_c + \frac{1}{2} \cdot \beta \cdot \Gamma_1 \cdot B \cdot N_r + \Gamma_2 \cdot D_f \cdot N_q$$

where;

- q_a = Allowable bearing capacity (t/m²)
- q_d = Ultimate bearing capacity (t/m²)
- n = Safety factor = 3
- c = Cohesion of the soil at base of caisson (t/m²)
- Γ_1 = bulk density of ground at base of caisson (t/cu.m)
- Γ_2 = bulk density of earth surrounding the caisson
- α, β = shape factor of the base of caisson as in Table G-14
- D_f = effective embedded length
- N_c, N_q, N_r = Coefficient of bearing capacity (Fig.G-10)

Figure G-10 Coefficient of Bearing Capacity




Table G-14 Shape Factor of the Base of Caisson

Shape factor	Shape factor of various shape of caisson			
	Strip	Square	Oval	Circular
α	1.0	1.3	$1 + 0.3B/L$	1.3
β	1.0	0.6	$1 - 0.4B/L$	0.6

where;

B = width of the total side Diameter of caisson (m)

L = width of front side of caisson (m)

note; If $B/L > 1$ than B/L shall be taken as unity.

The allowable horizontal bearing capacity of ground shall be similar to footing design.

10. Load Combination

- Allowable design method

Load combination for allowable stress design shall be as specified in BS 153-Part 3B and as summaries in the Table G-15 below:-

Table G-15 Load Combination For Allowable Stress Design

Load Combination	Loading	Incremental coefficient for allowable stresses
1	D + L	1.00
2	D+L+F+S	1.25
3	D+L+CS+S	1.25
4	D+L+CP+S	1.25
5	D+L+CL+S	1.25
6	D+L+BK+S	1.25

where;

D = Dead Load.
L = Live Load.
F = Centrifugal force.
CS = Collision load on bridge support.
CP = Collision load on bridge parapet.
CL = Collision load due to log impact.
BK = Tractive/Breaking force.
S = Stream current debris.

Based on engineering judgement, forces from load combination 2, 3 and 4 are not critical for all bridges in the study. Therefore for the purpose of preliminary design and assessment of bridges in the study, only load combination 1, 5 and 6 will be used.

- Ultimate Limit Design

For the purpose of design at Ultimate Limit State (ULS), the load combination given in Table G-16 below shall be considered:-

**Table G-16 Load Combination At ULS And Appropriate Partial
Factor, γ_{fl}**

No	Loading	Load Combination					
		1	2	3	4	5	6
1	D(Concrete) (Steel)	1.15 1.05	1.15 1.05	1.15 1.05	1.15 1.05	1.15 1.05	1.15 1.05
2	SIDL	1.75	1.75	1.75	1.75	1.75	1.75
3	S	1.10	1.10	-	1.10	1.10	1.10
4	L	1.50	1.50 ^{/1}	-	1.25 ^{/2}	1.25	1.25
5	F	-	1.50	-	-	-	-
6	CS	-	-	1.25	-	-	-
7	CP	-	-	-	1.25	-	-
8	CL	-	-	-	-	1.25	-
9	BK	-	-	-	-	-	1.25

Note;

/1: Live load to be applied shall be the appropriate live load as described in (4) above.

/2: Live load to be applied shall be the appropriate live load as described in (6) above.

SIDL : Superimposed Dead Load

11. Material And Allowable Stress

(1) Allowable Stress Design

The allowable stresses for reinforced concrete design shall be as specified in BE 1/73 and for steel design shall be as specified in BS 153 : Part 3B.

- Concrete

The allowable compressive stresses and allowable shear stress of concrete shall be as given in Table G-17 below.

Table G-17 The Allowable Compressive and Shear Stress of Concrete

Class of Concrete denoted by specified 28 days work cube strength	Permissible Stresses in Concrete				
	Compression		Shear	Bond	
	Direct	Bending		Average	Local
N/mm ²	N/mm ²	N/mm ²	N/mm ²	N/mm ²	N/mm ²
30	7.6	10	0.87	1.00	1.47
25	6.3	8.3	0.80	0.90	1.34
22.5	5.7	7.5	0.72	0.85	1.27
20	5.1	6.7	0.70	0.80	1.20

- Steel Reinforcement

The permissible stresses in steel reinforcement shall be as given in Table G-18 below;

Table G-18 The Permissible Stresses in Steel Reinforcement

Type of Stress	Permissible Stresses in rebar (N/mm ²)		
	Mild Steel Bars		All cold work & hot rolled high yield bar
	$\phi \leq 40\text{mm}$	$\phi > 40\text{mm}$	
Tensile stress other than in shear reinforcement	140	125	230
Tensile stress in shear reinforcement. That is stirrups and main bars, bent up to resist shear	140	125	175
Compressive stress	125	110	175
Range of stress	265	235	325

- Structural Steel

The permissible stresses in structural steel shall be as given BS 153:Part 3B which is summaries in Table F-19 below;

Table G-19 The Permissible Stresses in Structural Steel

Steel Grade	Yield Stress (N/mm ²)	Permissible Stresses (N/mm ²)				
		Bending			Direct/ Axial on effective X- Area.	Shear
		Plate & Hollow section	Rolled section	Plate Girder		
Grade 43	215	140	133	126	129	80
	230	150	142	135	138	85
	245	160	151	144	147	91
	280	183	173	165	168	107
Grade 50	325	212	201	191	191	120
	340	222	210	200	200	126
	355	232	219	209	209	131
Grade 55	400	261	247	235	235	148
	415	271	256	244	244	154
	430	281	265	253	253	159
	450	294	278	265	265	167

(2) Ultimate Limit State Design

- Concrete

The design strength of materials for ultimate limit state are expressed in terms of the 'characteristic strength' of the material multiplied by Γ_m , the partial safety factor for material.

- o Extreme fibre stress in compression, $f_c \dots 0.67f_{cu}/m$
- o (Γ_m shall be taken as 1.5)
- o Ultimate Bearing stress, $f_b \dots 0.4f_{cu}$
- o Ultimate shear stress, V_c shall be as follows;

$$V_c = \frac{0.27}{\Gamma_m} \left[\frac{100 \cdot A_s}{b_w \cdot d} \right]^{1/3} \cdot f_{cu}^{1/3}$$

where;

- A_s = Area of Longitudinal rebar.
- b_w = Breadth of web or rib of member.
- d = Effective depth of tension rebar.
- f_{cu} = Characteristic concrete cube strength.
- $\Gamma_m = 1.25$.

- Reinforcing Steel

- o The ultimate tensile strength, $f_s = 0.8f_y/m$
- o (Γ_m shall be taken as 1.15)
- o Characteristic strength of reinforcement, f_y is as follows;

Mild steel.....250 N/mm².
High Yield steel.....410 N/mm².

- Structural Steel

Nominal yield stress for steel complying with BS4360 is as follows:-

Steel Grade	Nominal Yield stress (N/sq.mm)	
	$t \leq 16\text{mm}$	$16\text{mm} < t < 40\text{mm}$
40	235	225
43	275	265
50	355	345
55	450	430

12. Design Standard

In deriving the design criteria, the JKR bridge Design Manual is referred. In addition, reference were also made to BS 153, BE 1/73, BS 5400 Part 1,2,3,and 4; and Specification for Highway Bridges published by Japan Road Association.

ANNEX - H
STANDARD REPORTING FORMS

Standard Reporting Form of Superficial Inspection Results

Key No.		State	Date	District
Bridge Type		Bridge Length (M)	Bridge Width	(M)
No's of Span		Max.Span (M)	Year Built	
Name of Inspector				
Date of Inspection				
Bridge Member		Rating	Major Damages	Maintenance Work Required
<input type="checkbox"/> Beam/ Girder	<input type="checkbox"/> Steel <input type="checkbox"/> Concrete			
<input type="checkbox"/> Deck Slab	<input type="checkbox"/> Steel <input type="checkbox"/> Concrete			
<input type="checkbox"/> Abutment	Concrete			
<input type="checkbox"/> Pier	<input type="checkbox"/> Steel <input type="checkbox"/> Concrete			
<input type="checkbox"/> Bearing	Steel			
<input type="checkbox"/> Drainage				
<input type="checkbox"/> Sidewalk <input type="checkbox"/> Kerb	Concrete			
<input type="checkbox"/> Railing	<input type="checkbox"/> Steel <input type="checkbox"/> Concrete			
<input type="checkbox"/> Pavement	<input type="checkbox"/> Asphalt <input type="checkbox"/> Concrete			
<input type="checkbox"/> Expansion Joint	<input type="checkbox"/> Steel <input type="checkbox"/> Rubber			
<input type="checkbox"/> River Bank				
Inspector's Comments ;				
Estimated Cost for Maintenance Works ;				
Detailed Inspection ;		<input type="checkbox"/> Required <input type="checkbox"/> Not Required		

Standard Reporting Form of Periodical Inspection Results

Key No.		State		Date	
Bridge Type		Bridge Length	(M)	Bridge Width	(M)
No's of Span		Max.Span Length	(M)	Year Built	
Name of Inspector					
Date of Inspection					
Bridge Member		Part Rating from Maintenance View Point	Part Rating from Bridge Safety View Point	Maintenance Work Required	
<input type="checkbox"/> Abutment	Concrete				
<input type="checkbox"/> Pier	<input type="checkbox"/> Steel <input type="checkbox"/> Concrete				
<input type="checkbox"/> Bearing	<input type="checkbox"/> Steel <input type="checkbox"/> Rubber				
<input type="checkbox"/> Beam/ Girder	<input type="checkbox"/> Steel <input type="checkbox"/> Concrete				
<input type="checkbox"/> Deck Slab	<input type="checkbox"/> Steel <input type="checkbox"/> Concrete				
<input type="checkbox"/> Pavement	<input type="checkbox"/> Asphalt <input type="checkbox"/> Concrete		-		
<input type="checkbox"/> Wing Wall	Concrete		-		
<input type="checkbox"/> Expansion Joint	<input type="checkbox"/> Steel <input type="checkbox"/> Rubber		-		
<input type="checkbox"/> Railing	<input type="checkbox"/> Steel <input type="checkbox"/> Concrete		-		
<input type="checkbox"/> Drainage			-		
<input type="checkbox"/> Bank Slope			-		
Overall Rating per the Bridge					
Traffic Capacity on the Bridge		<input type="checkbox"/> Adequate Capacity Year ; <input type="checkbox"/> Inadequate			
Pedestrian Flow Capacity		<input type="checkbox"/> Adequate <input type="checkbox"/> Inadequate			
Bridge Opening Capacity		<input type="checkbox"/> Adequate <input type="checkbox"/> Inadequate			
Inspector's Comments:					
Estimated Cost for Maintenance Works ;					
Detailed Inspection ; <input type="checkbox"/> Required <input type="checkbox"/> Not Required					

Standard Reporting Form of Detailed Inspection Results

			Date		
Key No.		State		District	
Bridge Type		Bridge Length	(M)	Bridge Width	(M)
No's of Span		Max.Span Length	(M)	Year Built	
Name of Chief Inspector			No's of Drawings		
Date of Inspection			Prepared		
Measurement Items		Measurement Results			
[] Steel Thickness (mm)	[] Beam/Girder	- Flang Min.;	Max.;	Average;	
		- Web Min.;	Max.;	Average;	
	[] Buckle Plate	Min.;	Max.;	Average;	
[] Concrete Cover (mm)	[] Beam/Girder	[] Abutment;			
	[] Deck Slab ;	[] Pier ;			
[] Pile Length (m)	Location;	Length;			
	Location;	Length;			
[] Steel Strength (N/mm2)	[] Beam/Girder;	[] Buckle Plate;			
	[] Reinforcing Bar;				
[] Concrete Strength (N/mm2)	[] Beam/Girder;	[] Abutment;			
	[] Deck Slab ;	[] Pier ;			
[] Carbonation Depth (mm)	[] Beam/Girder;	[] Abutment;			
	[] Deck Slab ;	[] Pier ;			
[] Chloride Content (%)	[] Beam/Girder;	[] Abutment;			
	[] Deck Slab ;	[] Pier ;			
[] Sulphate Content (%)	[] Beam/Girder;	[] Abutment;			
	[] Deck Slab ;	[] Pier ;			
Bridge Member		Major Damages	Rehabilitation Work	Estimated cost	
[] Abutment	[] Steel [] Concrete				
[] Pier	[] Steel [] Concrete				
[] Bearing	[] Steel [] Rubber				
[] Beam/ Girder	[] Steel [] Concrete				
[] Deck Slab	[] Steel [] Concrete				
[] Pavement	[] Asphalt [] Concrete				
[] Wing Wall	Concrete				
[] Expansion Joint	[] Steel [] Rubber				
[] Railing	[] Steel [] Concrete				
[] Drainage					
[] Bank Slope					
		Total Amount			
Name of Sr. Engineer in Charge ;					

Standard Reporting Form of Maintenance Works Carried out

				Date	
Key No.		State		District	
Bridge Type		Bridge Length	(M)	Bridge Width	(M)
No's of Span		Max.Span Length	(M)	Year Built	
Bridge Member		Outline of the Maintenance Works		Date	Cost
<input type="checkbox"/> Beam/ Girder	<input type="checkbox"/> Steel <input type="checkbox"/> Concrete				
<input type="checkbox"/> Deck Slab	<input type="checkbox"/> Steel <input type="checkbox"/> Concrete				
<input type="checkbox"/> Abutment	Concrete				
<input type="checkbox"/> Pier	<input type="checkbox"/> Steel <input type="checkbox"/> Concrete				
<input type="checkbox"/> Bearing	<input type="checkbox"/> Steel <input type="checkbox"/> Rubber				
<input type="checkbox"/> Drainage					
<input type="checkbox"/> Sidewalk <input type="checkbox"/> Kerb	Concrete				
<input type="checkbox"/> Railing	<input type="checkbox"/> Steel <input type="checkbox"/> Concrete				
<input type="checkbox"/> Pavement	<input type="checkbox"/> Asphalt <input type="checkbox"/> Concrete				
<input type="checkbox"/> Expansion Joint	<input type="checkbox"/> Steel <input type="checkbox"/> Rubber				
<input type="checkbox"/> River Bank					
Name of Engineer in Charge ;				Total Amount	

Standard Reporting Form of Rehabilitation Works Carried Out

				Date		
Key No.		State		District		
Bridge Type		Bridge Length	(M)	Bridge Width	(M)	
No's of Span		Max.Span Length	(M)	Year Built		
Name of contractor						
Construction Period						
Contract Amount						
Additional cost due to Variations						
Final Contract Amount						
Number of As Built Drawing						
Classification	Outline of Rehabilitation Works	Work Items	Quantities of Works	Unit	Unit Price	Amount
Structural Rehabilitation						
Functional Rehabilitation						
Hydraulic Rehabilitation						
Name of Sr. Engineer in Charge ;				Total Amount :		

ANNEX - I
ECONOMIC EVALUATION METHOD

ECONOMIC EVALUATION METHOD

1.1 Economic Evaluation Method


(1) General

The purpose of economic evaluation is to evaluate economic viability and to determine the priority of the proposed maintenance projects for bridges.

The following procedure shall be taken as shown in Fig. I-1.

- 1) Select a traffic count station corresponding to each bridge from the traffic census data.
- 2) Estimate the future traffic volume of each bridge using traffic growth rates included in the above.
- 3) List the possible benefits by bridge in the light of proposed rehabilitation works.
- 4) Formulate an evaluation model to quantify benefits included in the above.
- 5) Calculate economic benefits using future traffic volumes and vehicle operating costs.
- 6) Convert financial cost into economic cost.
- 7) Work out economic evaluation by benefit cost analysis.
- 8) Conduct sensitivity analysis to test evaluation stability.
- 9) Judge project feasibility considering related aspects.

Figure I-1 Flowchart of Economic Evaluation




(2) Traffic Projection

Future traffic volume on the bridge shall be estimated by "trends model" based on "Traffic Volume Malaysia". The following procedure shall be taken as shown in Fig. I-2.

- i) Identify a traffic count station corresponding to each bridge.
- ii) Determine traffic volume (16 hours) by vehicle type and growth rate for each bridge.
- iii) Convert 16-hour traffic volume to daily value (VPD).
- iv) Set growth rate at zero if it is calculated negative.
- v) Calculate future traffic volume using the growth rate.
- vi) Break down daily traffic volume into those by vehicle type using the present modal shares.

Figure I-2 Flowchart of Traffic Projection



(3) Economic Costs

The cost components to be considered in bridge rehabilitation project are:

- Rehabilitation Cost

Investment cost in order to improve bridge durability and to enhance bridge functions.

- Maintenance Cost

Continuously required cost in order to keep bridge serviceability after rehabilitation.

In economic evaluation, cost should be "economic cost", not "financial cost" in terms of market prices. "National Parameter for Project Appraisal" published by EPU in 1984 shows conversion factors from financial to economic cost by type of work. In this manual, a conversion factor of 0.80 is taken in accordance with the above.

Using the conversion factor, economic cost is derived according to the following formula:

$$\begin{array}{ccccc} \text{Economic Cost} & & \text{Conversion Factor} & & \text{Financial Cost} \\ (EC) & = & (CF) & \times & (FC) \end{array}$$

Annual maintenance cost is assumed to be 1 % of construction cost in this manual. In addition, standard construction cost of a bridge in Malaysia is about M\$2,500 per squaremeter of deck in 1991 market prices.

Maintenance cost after rehabilitation proposed in this manual is assumed as follows:

- i) Reconstruction and widening :
2.5 % of rehabilitation Cost for 5 years (0.5%/years)
- ii) Reinforcement :
5.0 % of rehabilitation Cost for 5 years (1.0%/years)
- iii) Protection :
10.0 % of rehabilitation Cost for 5 years (2.0%/years)

These maintenance costs are also subject to conversion.

(4) Benefit Measurement

Tangible benefits accrued from bridge rehabilitation are :

- i) Savings in vehicle operating cost due to a reduction of interruption to traffic flow.

Improvement of bridge durability reduces number of days of interruption (extends bridge life) and, therefore, saves vehicle operating cost due to detours.

- ii) Savings in vehicle operating cost due to an increase in vehicle speed

Bridge widening makes it possible for vehicles to keep at constant speed on and near the bridge.

- iii) Maintenance Cost Savings

The maintenance cost savings can be expected on the bridge administrator side. The benefit comes from the difference in maintenance cost between "with" and "without" project cases.

1) Probability Model For Bridges To Be Unusable

In order to quantify the benefit of reducing the interruption to traffic flow, a probabilistic model is introduced.

The "Unserviceability Probability Density" $f(t)$ is:


$$f(t) = \frac{1}{\sqrt{2\pi}\delta} e^{-\frac{(t-m)^2}{2\delta^2}} = N[m, \delta^2] = N[50, 16.7^2]$$

In this manual, bridge life is determined at 50 years.

In order to quantify the benefit of rehabilitation works, a function for the bridge unserviceability probability density after rehabilitation should be assumed.

Figure I-3 presents schematically the effects of maintenance works in terms of the probability for interruptions, for example bridges of an age of 30 years.

Figure I-3 Probability Density of Bridge Unserviceability After Rehabilitation



2) Vehicle Operating Costs

The National Axle Load Study (NALS) developed the evaluation model for vehicle operating cost in Malaysia after a detailed survey in 1987. In this manual, Econom V5.1 is adopted.

Table I-1 Vehicle Operating Costs by Vehicle Type

(M\$/km)

Vehicle Type	M'cycles	Cars & Taxies	Buses	S.Vans & Utilities	Medium Lorries	Heavy Lorries
Regular Route	0.046	0.184	1.517	0.498	0.785	1.059
Detour Route	0.055	0.220	1.859	0.632	0.911	1.147
Before Widening	0.066	0.266	2.761	0.867	1.248	1.579

3) Equivalent Age of Bridge

Residual life of a bridge differs by structure, traffic volume, geography, current damage and other factors even physical age. In order to assess the residual life of a bridge, a concept of "equivalent age of bridge" was introduced in relation to unserviceability probability based on the overall rating from a safety viewpoint, traffic volume and construction year. It can be defined as a normalized age on the unserviceability probability density function with an average age of 50.

Table I-2 Assumed Equivalent Age of Bridge

Overall Rating from Safety viewpoint (R)	Traffic Volume (AADT : Vehicle/day)	Year Built	
		Before 1945	After 1945
4.0 ≤ R	all	45	40
3.5 ≤ R < 4.0	AADT ≥ 9,000	45	40
	AADT < 9,000	40	30
R < 3.5	AADT ≥ 9,000	40	30
	AADT < 9,000	30	20

4) Interruption to Traffic Flow

In order to estimate the duration of bridge interrupts, the number of months required for bridge construction is assumed as a function of bridge length as follows:

$$\log (M) = 0.572 \log (L) + 0.043$$

where, M : Standard number of months required for
bridge construction
L : Bridge Length (m)

Using "M", number of days of interruptions is derived as follows:

$$d = f \times M \times (365/12)$$

where, f : probability for a bridge to be
unusable
d : number of days for a bridge to
be unusable

5) Equation for Benefit Calculation

The equations developed for calculating benefits are based on two options, 1) bridge rehabilitation (with project) and 2) do nothing (without project).

i) Protection

$$B1 = \sum_x \sum_i (fo(x) - fwp(x)) \text{ DBU AADTx}_i (\text{DLo VOCio} - \text{DLw VOCiw})$$

where, B1 : Benefit from Protection (\$)
fo(x): Probability for a bridge to be unusable
in year x without rehabilitation
fwp(x): Probability for a bridge to be unusable
in year x after protection
DBU : Duration of Bridge Unservice (day)
AADTx_i: Average Annual Daily Traffic of Vehicle
type i in year x (vehicles/day)
DLo : Length of detour route (km)
DLw : Length of regular route (km)
VOCio: Vehicle Operating Cost of Vehicle type i
in detour route (\$/km)
VOCiw: Vehicle Operating Cost of Vehicle type i
in regular route (\$/km)

ii) Reinforcement

$$B2 = \sum_x \sum_i (fo(x) - fwr(x)) \text{ DBU AADTx}_i (\text{DLo VOCio} - \text{DLw VOCiw})$$

where, B2 : Benefit from Reinforcement (\$)
 fwr(x): Probability for a bridge to be unusable
 in year x after reinforcement

iii) Reconstruction

$$B3 = \sum_x \sum_i (fo(x) - fwc(x)) \text{ DBU AADTx}_i (\text{DLo VOCio} - \text{DLw VOCiw})$$

where, B3 : Benefit from reconstruction (\$)
 fwc(x): Probability for a bridge to be unusable
 in year x after reconstruction

iv) Widening

$$B4 = \sum_x \sum_i (\text{AADTx}_i (\text{BL} + 200) / 1000 (\text{VOCio} - \text{VOCiw}))$$

where, B4 : Benefit from widening (\$)
 BL : Length of bridge (m)

v) Cost Saving in Maintenance

$$B5 = \sum_i (\text{BL} \quad \text{BW} \quad \text{UCC} \quad \text{Pm})$$

where, B5 : Benefit from cost saving in Maintenance (\$)
 BW : Width of bridge (m)
 UCC : Unit cost of bridge construction (\$/m²)
 Pm : Rate of annual maintenance cost against
 to initial construction cost (0.01)

(5) Economic Evaluation

Economic evaluation quantifies cost and benefit first and assesses both in comparison. This is usually called "Benefit Cost Analysis". In this analysis, the following three parameters are generally used for decision making and for determining priority:

i) Benefit Cost Ratio (BCR)

This ratio is calculated by dividing benefit by cost in terms of net present value:

$$BCR = \left(\sum_t Bt / (1+i)^t \right) / \left(\sum_t Ct / (1+i)^t \right)$$

where, Bt : Benefit in year t
Ct : Cost in year t
i : Discount rate

This quantifies the magnitude of net present benefit per net present cost.

ii) Net Present Value (NPV)

Unlike benefit cost ratio, this quantifies the magnitude of net present benefit less net present cost.

$$NPV = \left(\sum_t Bt / (1+i)^t \right) - \left(\sum_t Ct / (1+i)^t \right)$$

iii) Internal Rate of Return (IRR)

This rate is defined to be a discount rate or an interest rate where net present value of the project becomes zero. In other words, this is the highest interest rate that makes the project economically feasible.

$$\text{When } \sum_t (Bt - Ct) / (1+i)^t = 0$$

this "i" is called "Internal Rate of Return".

In order to calculate the net present value of benefit/cost or to determine project viability when IRR of the project is calculated, "discount rate" is needed as a criterion. In this manual, a discount rate of 11% per annum is used. Benefit/cost analysis shall be done over 20 years after the commencement of the project.

I.2 Calculation

A worksheet of Lotus 1-2-3 is attached in order for a bridge maintenance engineer to carry out automatically economic evaluation by only inputting necessary data.

(1) Input data

1) Bridge Data

No. : (arbitrary taken)
Key : (Code No. of bridge inventory)
State
District
Year Built
Length : (m)
Carriageway Width : (m)
Overall Rating from Safety Viewpoint
Length of Detour Route : Da (km)
Length of Regular Route : Db (km)

2) Traffic Census Data

State
District
Station Index
Year Conducted
16-Hours Traffic
Growth Rate : (%/year)
Vehicle Composition by Vehicle Type : (%)

3) Rehabilitation Data

Rehabilitation Method : Input "1" in the column
corresponding to rehabilitation method.
Rehabilitation Cost : (\$/bridge in market price)
Conversion Factor : "0.80" should be specified.
Standard Construction Cost of a Bridge : (\$/m2 in
market price)

4) Vehicle Operating Cost

Vehicle operating cost in 1991 prices are already
set on the worksheet.

Regular Route : (\$/km in economic price)
Detour Route : (\$/km in economic price)
Before Widening : (\$/km in economic price)

5) Calculation for Indicators

Discount Rate ; do

When a discount rate do is inputted, a corresponding NPVo is calculated and, at the same time, NPV1 is also calculated corresponding to a discount rate of $d1 = do + 2 (\%)$. Using these NPVo and NPV1, a discount rate d3 when NPV3=0 shall be calculated.

Value of do shall be gradually adjusted so that NPV3 approaches to 0.

As an initial value of do, $BCR \times 0.1$ is recommendable.

(2) Output

1) Indicators

BCR : Benefit Cost Ratio
NPV : Net Present Value
IRR : Internal Rate of Return (%)

2) Cost Benefit Flow

Cost benefit flow by vehicle type over the project period is calculated using the discount rate inputted.

3) Worksheet

An example of calculating economic indicators is shown in Table I-3.

Table I-3 Worksheet of Calculating Economic Indicators

< BRIDGE DATA >

No.	Key	State	District	Year Built	Length (m)	Carriageway Width (m)	Rating	Equivalent	Age	Detour Route (km)
32	237200	Pahang	Kuantan	1960	26.7	7.3	3.4	30	20.0	13.0

< TRAFFIC CENSUS DATA >

Traffic Census station				Year	16-Hours Traffic	Growth (%)	Vehicle Composition (%)					
State	District	Stn. Index					CARS & TAXIS	S. VANS & UTILITIES	MED. LORRIES	HEAVY LORRIES	BUSES	M/CYCLE
Pahang	Kuantan	022		1988	12593	7.4%	51.7%	11.3%	3.4%	3.6%	1.5%	28.4%

< REHABILITATION DATA >

Rehabilitation Method			
Protect.	Reinfor.	Reconst.	Widening
1	0	0	0
Rehabilitation Cost (\$)			
financial	375,724	2,500	
C/F	0.8	0.8	
economic	300,578	2,080	

< Vehicle Operation Cost (\$/km) >

	Cars & Taxi	S. Vans & Util.	Med. Lorry	Heavy Lorry	Buses	M/cycles
regular rt.	0.184	0.498	0.785	1.059	1.517	0.046
detour rt.	0.220	0.632	0.911	1.147	1.859	0.055
before wid.	0.268	0.867	1.248	1.579	2.761	0.066

< ECONOMIC EVALUATION >

Evaluation Period (20 years)	Discount Rate	IRR	NPV	BCR
from 1994	11.0%	21.21%	277,710	1.83

< PROBABILITY DENSITY OF BRIDGE UNSERVICEABILITY >

Year	EQUIVALENT AGE 20				EQUIVALENT AGE 30				EQUIVALENT AGE 40				EQUIVALENT AGE 45			
	WITHOUT	PROTECT	REINF.	RECONST.	WITHOUT	PROTECT	REINF.	RECONST.	WITHOUT	PROTECT	REINF.	RECONST.	WITHOUT	PROTECT	REINF.	RECONST.
1994	0.493%	0.483%	0.123%	0.032%	1.313%	1.234%	0.580%	0.027%	2.720%	2.400%	1.553%	0.021%	3.638%	3.086%	2.536%	0.027%
1995	0.508%	0.498%	0.123%	0.032%	1.407%	1.234%	0.580%	0.027%	2.815%	2.400%	1.553%	0.021%	3.687%	3.086%	2.536%	0.027%
1996	0.607%	0.482%	0.123%	0.032%	1.503%	1.234%	0.580%	0.027%	2.902%	2.400%	1.553%	0.021%	3.744%	3.086%	2.536%	0.027%
1997	0.670%	0.482%	0.123%	0.032%	1.601%	1.234%	0.580%	0.027%	2.981%	2.400%	1.553%	0.021%	3.778%	3.086%	2.536%	0.027%
1998	0.737%	0.482%	0.123%	0.032%	1.698%	1.234%	0.580%	0.027%	3.051%	2.400%	1.553%	0.021%	3.798%	3.086%	2.536%	0.027%
1999	0.807%	0.482%	0.123%	0.032%	1.795%	1.234%	0.580%	0.027%	3.112%	2.400%	1.553%	0.021%	3.805%	3.086%	2.536%	0.027%
2000	0.882%	0.538%	0.137%	0.074%	1.891%	1.323%	0.636%	0.074%	3.162%	2.433%	2.010%	0.074%	3.798%	3.137%	2.574%	0.074%
2001	0.958%	0.594%	0.151%	0.087%	1.985%	1.414%	0.684%	0.087%	3.202%	2.560%	2.085%	0.087%	3.778%	3.176%	2.607%	0.087%
2002	1.040%	0.655%	0.171%	0.101%	2.076%	1.505%	0.734%	0.101%	3.231%	2.630%	2.117%	0.101%	3.744%	3.205%	2.634%	0.101%
2003	1.123%	0.721%	0.190%	0.117%	2.163%	1.597%	0.785%	0.117%	3.249%	2.692%	2.164%	0.117%	3.697%	3.222%	2.655%	0.117%
2004	1.209%	0.790%	0.211%	0.136%	2.246%	1.688%	0.839%	0.136%	3.254%	2.746%	2.208%	0.136%	3.638%	3.228%	2.671%	0.136%
2005	1.296%	0.862%	0.234%	0.155%	2.324%	1.778%	0.894%	0.155%	3.249%	2.790%	2.247%	0.155%	3.567%	3.222%	2.680%	0.155%
2006	1.385%	0.938%	0.258%	0.174%	2.396%	1.857%	0.951%	0.174%	3.231%	2.826%	2.282%	0.174%	3.485%	3.205%	2.683%	0.174%
2007	1.475%	1.017%	0.285%	0.205%	2.461%	1.952%	1.008%	0.205%	3.202%	2.851%	2.312%	0.205%	3.393%	3.176%	2.680%	0.205%
2008	1.565%	1.098%	0.313%	0.234%	2.519%	2.034%	1.067%	0.234%	3.162%	2.866%	2.337%	0.234%	3.291%	3.137%	2.671%	0.234%
2009	1.654%	1.182%	0.344%	0.265%	2.569%	2.112%	1.127%	0.265%	3.112%	2.872%	2.357%	0.265%	3.180%	3.086%	2.656%	0.265%
2010	1.742%	1.267%	0.376%	0.301%	2.611%	2.185%	1.187%	0.301%	3.051%	2.866%	2.372%	0.301%	3.063%	3.026%	2.635%	0.301%
2011	1.829%	1.354%	0.411%	0.339%	2.644%	2.253%	1.248%	0.339%	2.981%	2.851%	2.381%	0.339%	2.939%	2.956%	2.608%	0.339%
2012	1.913%	1.442%	0.448%	0.381%	2.668%	2.315%	1.309%	0.381%	2.902%	2.826%	2.385%	0.381%	2.810%	2.878%	2.575%	0.381%
2013	1.993%	1.530%	0.487%	0.427%	2.682%	2.369%	1.370%	0.427%	2.815%	2.790%	2.384%	0.427%	2.678%	2.792%	2.537%	0.427%

< COST BENEFIT FLOW >

No.	YEAR	A.A.O.T. (VPD)	to-fw	REHABIL. COST (WITH)	MAINT. COST (WITH)	E.COST STREAM	BENEFIT FROM PROTECTION OR REINFORCEMENT OR RECONSTRUCTION				BENEFIT FR MAINT. COST		BENEFIT STREAM	
							CARS & TAXIES	S.VANS & UTILITIES	WED. LORRIES	HEAVY LORRIES	BUSES	M CYCLE	WIDENING	
				(WITH)	(WITH)								(WITHOUT)	
1	1994	20,003		300,578		300,578								3,898
2	1995	21,028	0.173%			0	8,311	5,578	2,182	2,644	2,097	1,141	0	3,898
3	1996	22,053	0.270%			0	13,572	9,109	3,563	4,317	3,424	1,864	0	3,898
4	1997	23,078	0.367%			0	19,331	12,974	5,074	6,149	4,876	2,655	0	3,898
5	1998	24,103	0.465%			0	25,556	17,152	6,708	8,129	6,447	3,510	0	3,898
6	1999	25,128	0.562%		30,058	30,058	32,208	21,617	8,455	10,246	8,125	4,423	0	3,898
7	2000	26,153	0.568%			0	33,909	22,758	8,901	10,786	8,554	4,657	0	3,898
8	2001	27,178	0.571%			0	35,427	23,777	9,300	11,269	8,937	4,865	0	3,898
9	2002	28,203	0.571%			0	36,727	24,650	9,641	11,683	9,255	5,044	0	3,898
10	2003	29,228	0.566%			0	37,771	25,351	9,915	12,015	9,528	5,187	0	3,898
11	2004	30,253	0.558%		30,058	30,058	38,525	25,656	10,113	12,255	9,718	5,291	0	3,898
12	2005	31,278	0.546%			0	38,955	26,145	10,226	12,391	9,827	5,350	0	3,898
13	2006	32,304	0.529%			0	39,031	26,196	10,246	12,416	9,846	5,360	0	3,898
14	2007	33,329	0.509%			0	38,729	25,993	10,166	12,320	9,770	5,319	0	3,898
15	2008	34,354	0.485%			0	38,027	25,523	9,982	12,096	9,593	5,222	0	3,898
16	2009	35,379	0.457%		30,058	30,058	36,911	24,774	9,689	11,741	9,311	5,069	0	3,898
17	2010	36,404	0.426%			0	35,372	23,741	9,285	11,252	8,923	4,858	0	3,898
18	2011	37,429	0.391%			0	33,408	22,422	8,769	10,627	8,428	4,588	0	3,898
19	2012	38,454	0.353%			0	31,022	20,821	8,143	9,868	7,826	4,260	0	3,898
20	2013	39,479	0.313%			0	28,228	18,946	7,410	8,979	7,121	3,877	0	3,898
TOTAL				300,578	90,174	390,753	601,072	403,383	157,768	191,183	151,617	82,539	0	77,964

< CALCULATION FOR INDICATORS >

		d0		d1		d2		d3		d4		d5		d6		d7		d8		d9		d10		d11		d12		d13		d14		d15		d16		d17		d18		d19		d20		d21		d22		d23		d24		d25		d26		d27		d28		d29		d30		d31		d32		d33		d34		d35		d36		d37		d38		d39		d40		d41		d42		d43		d44		d45		d46		d47		d48		d49		d50		d51		d52		d53		d54		d55		d56		d57		d58		d59		d60		d61		d62		d63		d64		d65		d66		d67		d68		d69		d70		d71		d72		d73		d74		d75		d76		d77		d78		d79		d80		d81		d82		d83		d84		d85		d86		d87		d88		d89		d90		d91		d92		d93		d94		d95		d96		d97		d98		d99		d100		d101		d102		d103		d104		d105		d106		d107		d108		d109		d110		d111		d112		d113		d114		d115		d116		d117		d118		d119		d120		d121		d122		d123		d124		d125		d126		d127		d128		d129		d130		d131		d132		d133		d134		d135		d136		d137		d138		d139		d140		d141		d142		d143		d144		d145		d146		d147		d148		d149		d150		d151		d152		d153		d154		d155		d156		d157		d158		d159		d160		d161		d162		d163		d164		d165		d166		d167		d168		d169		d170		d171		d172		d173		d174		d175		d176		d177		d178		d179		d180		d181		d182		d183		d184		d185		d186		d187		d188		d189		d190		d191		d192		d193		d194		d195		d196		d197		d198		d199		d200		d201		d202		d203		d204		d205		d206		d207		d208		d209		d210		d211		d212		d213		d214		d215		d216		d217		d218		d219		d220		d221		d222		d223		d224		d225		d226		d227		d228		d229		d230		d231		d232		d233		d234		d235		d236		d237		d238		d239		d240		d241		d242		d243		d244		d245		d246		d247		d248		d249		d250		d251		d252		d253		d254		d255		d256		d257		d258		d259		d260		d261		d262		d263		d264		d265		d266		d267		d268		d269		d270		d271		d272		d273		d274		d275		d276		d277		d278		d279		d280		d281		d282		d283		d284		d285		d286		d287		d288		d289		d290		d291		d292		d293		d294		d295		d296		d297		d298		d299		d300		d301		d302		d303		d304		d305		d306		d307		d308		d309		d310		d311		d312		d313		d314		d315		d316		d317		d318		d319		d320		d321		d322		d323		d324		d325		d326		d327		d328		d329		d330		d331		d332		d333		d334		d335		d336		d337		d338		d339		d340		d341		d342		d343		d344		d345		d346		d347		d348		d349		d350		d351		d352		d353		d354		d355		d356		d357		d358		d359		d360		d361		d362		d363		d364		d365		d366		d367		d368		d369		d370		d371		d372		d373		d374		d375		d376		d377		d378		d379		d380		d381		d382		d383		d384		d385		d386		d387		d388		d389		d390		d391		d392		d393		d394		d395		d396		d397		d398		d399		d400		d401		d402		d403		d404		d405		d406		d407		d408		d409		d410		d411		d412		d413		d414		d415		d416		d417		d418		d419		d420		d421		d422		d423		d424		d425		d426		d427		d428		d429		d430		d431		d432		d433		d434		d435		d436		d437		d438		d439		d440		d441		d442		d443		d444		d445		d446		d447		d448		d449		d450		d451		d452		d453		d454		d455		d456		d457		d458		d459		d460		d461		d462		d463		d464		d465		d466		d467		d468		d469		d470		d471		d472		d473		d474		d475		d476		d477		d478		d479		d480		d481		d482		d483		d484		d485		d486		d487		d488		d489		d490		d491		d492		d493		d494		d495		d496		d497		d498		d499		d500		d501		d502		d503		d504		d505		d506		d507		d508		d509		d510		d511		d512		d513		d514		d515		d516		d517		d518		d519		d520		d521		d522		d523		d524		d525		d526		d527		d528		d529		d530		d531		d532		d533		d534		d535		d536		d537		d538		d539		d540		d541		d542		d543		d544		d545		d546		d547		d548		d549		d550		d551		d552		d553		d554		d555		d556		d557		d558		d559		d560		d561		d562		d563		d564		d565		d566		d567		d568		d569		d570		d571		d572		d573		d574		d575		d576		d577		d578		d579		d580		d581		d582		d583		d584		d585		d586		d587		d588		d589		d590		d591		d592		d593		d594		d595		d596		d597		d598		d599		d600		d601		d602		d603		d604		d605		d606		d607		d608		d609		d610		d611		d612		d613		d614		d615		d616		d617		d618		d619		d620		d621		d622		d623		d624		d625		d626		d627		d628		d629		d630		d631		d632		d633		d634		d635		d636		d637		d638		d639		d640		d641		d642		d643		d644		d645		d646		d647		d648		d649		d650		d651		d652		d653		d654		d655		d656		d657		d658		d659		d660		d661		d662		d663		d664		d665		d666		d667		d668		d669		d670		d671		d672		d673		d674		d675		d676		d677		d678		d679		d680		d681		d682		d683		d684		d685		d686		d687		d688		d689		d690		d691		d692		d693		d694		d695		d696		d697		d698		d699		d700		d701		d702		d703		d704		d705		d706		d707		d708		d709		d710		d711		d712		d713		d714		d715		d716		d717		d718		d719		d720		d721		d722		d723		d724		d725		d726		d727		d728		d729		d730		d731		d732		d733		d734		d735		d736		d737		d738		d739		d740		d741		d742		d743		d744		d745		d746		d747		d748		d749		d750		d751		d752		d753		d754		d755		d756		d757		d758		d759		d760		d761		d762		d763		d764		d765		d766		d767		d768		d769		d770		d771		d772		d773		d774		d775		d776		d777		d778		d779		d780		d781		d782		d783		d784		d785		d786		d787		d788		d789		d790		d791		d792		d793		d794		d795		d796		d797		d798		d799		d800		d801		d802		d803		d804		d805		d806		d807		d808		d809		d810		d811		d812		d813		d814		d815		d816		d817		d818		d819		d820		d821		d822		d823		d824		d825		d826		d827		d828		d829		d830		d831		d832		d833		d834		d835		d836		d837		d838		d839		d840		d841		d842		d843		d844		d845		d846		d847		d848		d849		d850		d851		d852		d853		d854		d855		d856		d857		d858		d859		d860		d861		d862		d863		d864		d865		d866		d867		d868		d869		d870		d871		d872		d873		d874		d875		d876		d877		d878		d879		d880		d881		d882		d883		d884		d885		d886		d887		d888		d889		d890		d891		d892		d893		d894		d895		d896		d897		d898		d899		d900		d901		d902		d903		d904		d905		d906		d907		d908		d909		d910		d911		d912		d913		d914		d915		d916		d917		d918		d919		d920		d921		d922		d923		d924		d925		d926		d927		d928		d929		d930		d931		d932		d933		d934		d935		d936		d937		d938		d939		d940		d941		d942		d943		d944		d945		d946		d947		d948		d949		d950		d951		d952		d953		d954		d955		d956		d957		d958		d959		d960		d961		d962		d963		d964		d965		d966		d967		d968		d969		d970		d971		d972		d973		d974		d975		d976		d977		d978		d979		d980		d981		d982		d983		d984		d985		d986		d987		d988		d989		d990		d991		d992		d993		d994		d995		d996		d997		d998		d999		d1000		d1001		d1002		d1003		d1004		d1005		d1006		d1007		d1008		d1009		d1010		d1011		d1012		d1013		d1014		d1015		d1016		d1017		d1018		d1019		d1020		d1021		d1022		d1023		d1024		d1025		d1026		d1027		d1028		d1029		d1030		d1031		d1032		d1033		d1034		d1035		d1036	
--	--	----	--	----	--	----	--	----	--	----	--	----	--	----	--	----	--	----	--	----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	-----	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--	-------	--

