

**AN INTERIM REPORT ON
THE PRE-FEASIBILITY STUDY FOR THE DEVELOPMENT
IN
TSAV AREA, MONGOLIA
(PHASE II)**

MARCH 1994


**JAPAN INTERNATIONAL COOPERATION AGENCY
METAL MINING AGENCY OF JAPAN**

M P N
CR(3)
94-059

AN INTERIM REPORT ON
THE PRE-FEASIBILITY STUDY FOR THE DEVELOPMENT
IN
TSAV AREA, MONGOLIA
(PHASE II)

28070


JICA LIBRARY



1121077101

MARCH, 1994

JAPAN INTERNATIONAL COOPERATION AGENCY
METAL MINING AGENCY OF JAPAN



国際協力事業団

28070

Preface:

In response to a request from the Mongolian government the Japanese government initiated geological surveys for the purpose of regional development in Tsav, located in the eastern part of Mongolia's Dolnot prefecture. These surveys were entrusted to Japan International Cooperation Agency(JICA). As the scope of these surveys is included in the field of geological and mineralogical sciences, JICA further commissioned the actual undertaking of the surveys to Metal Mining Agency of Japan(MMAJ).

This survey for the second year was conducted in 1993 by the Metal Mining Agency of Japan. We dispatched a survey team comprising eleven members (four of whom were sent to continue tunnel prospecting) from July 1 to September 4, 1993 to complete preliminary operations for the survey.

The survey was based on the detailed survey rules and regulations established on July 30, 1992. Between August 10 and December 5, 1993, nine investigators were additionally sent to conduct tunnel prospecting.

Thanks to the cooperation of the relevant institutions of the Mongolian government, our surveys were completed as scheduled.

This report represents the results of the second year survey and will form a part of the final report.

In closing, we would like to extend our deep appreciation to the related institutions of the Mongolian government, as well as the Ministry of Foreign Affairs, the Ministry of International Trade and Industry, the local area Japanese Embassy, and to each of the many persons involved.

March 1994



Kensuke YANAGIYA

President


Japan International Cooperation Agency



Takashi ISHIKAWA

President

Metal Mining Agency of Japan



Location Tsav Deposit

Contents

Preface

Location Map of the survey area

Table of Contents

Appendices

Table of Contents

Part I. General Remarks

	Page
Chapter 1. Introduction	1
1.1 Purpose of the study	1
1.2 Scope of the study	1
Chapter 2. Topographical conditions of the designated area	2
2.1 Location and transportation	2
2.2 Topography	3
2.3 Vegetation and Climate	3
Chapter 3. Outline of the study in this year(1993)	4
Chapter 4. Progress Schedule	7

Part II. Results of Tunnel Prospecting

Chapter 1. Summary of the study	8
1.1 Purpose of the study	8
1.2 Study Site	8
1.3 Summary of each excavation work	8
1.4 Study Method	10

1.4.1	Length of Drift	-----	10
1.4.2	Specifications of Drift	-----	10
1.4.3	Main Equipment	-----	11
1.4.4	Form of Work	-----	12
1.4.5	Dormitory	-----	12
1.5	Organization of Study teams	-----	13

Appendices

1.	Progress Schdule	-----	15
2.	Tunnel Prospecting	-----	16
3.	Detail of required days for Tunneling	-----	17
4.	Each Work Progressive Efficiency	-----	18
5.	Item of Consumptive Materials in 1993	-----	19
6.	Photo	-----	20
7.	Figures	-----	the end of a book
7.1	General View of Mine Site		
7.2	Tunnel Project & Each Month Progress		

Part I GENERAL REMARKS

Part I. General Remarks

Chapter 1. Introduction

1.1 Purpose of the study

The purpose of the study is to carry out tunnel prospecting and drilling at upper parts from the level 180m (630m above sea level) of the Tsav deposits to explore the fourth vein where the investigation is most advanced, and to draw up a mine development plan through the exact recognition of the characteristics of the mentioned vein, as well as through mineral processing test to be conducted on the collected minerals. The tunnel prospecting comprises the excavation of a inclined shaft from the surface and a drift at -60m level (750m above sea level), while the drilling is carried out inside the tunnel as well as from the surface.

The study also aims to promote technology transfer pertaining to exavation, mining and machinery control by means of those works and training of counter parts in Japan.

1.2 Scope of the study

Mongolia possesses an exceptional potential for the production of virtually all types of metal ores producing, presently, copper, molybdenum, tin, and fluorite. Through tapping and development of its resources, it is expected that Mongolia will also become an important supplier to the world increasing demands for copper, lead, and zinc, etc in the future.

The reform of Mongolia's economic structure has steadily progressed since 1987. However, in recent years, the scale of its resource development efforts has scaled down considerably due to the diminished technological cooperation from the former Soviet Union and other Eastern European Countries. This decrease of Mongolia's mineral resource industry, an industry vital to the foreign currency earnings of the nation, has caused the industry to enter a period of stagnation.

Our concentrated studies in Tsav, an area in the northeastern section of Mongolia's Dolnot prefecture, indicate an exceptional potential for a commercially feasible mine. The Mongolian government has also expressed a strong interest in the development of the area, and in

February of 1992 made a request for Japanese the technical cooperation to detect the potential of polimetallic deposit (lead, zinc, copper, and silver) in the area.

The development of a new mine will have a significant effect on the economic growth of Mongolia while at the same time it we'll lead to the increase of additional stable supply source of metal ore resources for Japan. From these perspectives, Japan decided to positively support the development of this area making arrangements for new budget for the development program study and project implementation preparation.

Under these circumstances, Japan dispatched a preliminary study team and held a conference with the Mongolian government regarding the study to be conducted. And, in July 30, 1992, the rules and regulations for the escavation of study were established.

Under these formally established rules and regulations, a study team consisting of seven members was consigned to the designated area between August 31 and September 19 and the framing for the study was initiated.

Based on the frame were prepared from July 1 to December 5, 1993, 20 investigators in total were sent to conduct tunnel prospecting.

Chapter 2. Topographical conditions of the designated area.

2.1 Location and transportation

The Tsav mineral deposits are in the Somon area of the Choybalsan district of the Dolnot prefecture in the eastern region of Mongolia. It is located approximately 120 kilometers northeast of Choybalsan City (refer to map the location map). The first survey area, conducted in 1989, encompassed an area of approximately 45 km² and included the Tsav ore deposits. As indicated on the map, this area is located between a north latitude of 48° 50' to 49° 00' and an east longitude of 115° 15' to 115° 30'. The geographical coordinates at the heart of the Tsav ore deposits which includes an area of approximately 12 km² is at a north latitude of 48° 55' 40" and an east longitude of 115° 20' 33".

Approximately 5 kms west of the Tsav ore deposits is the main trunk line of the Siberian Railway which runs in a southerly direction from Siberian Railway's Bolsha Station across the border towards Choybalsan to Elentsav (Sorobefusuku), and then on to Choybalsan (Bayan Toumen).

The distance to the neighboring Habiika Station is approximately 17 kms.

An unpaved road which is manageable throughout the year runs between the Tsav ore deposits and Choybalsan. It takes approximately three hours by car. In July of 1992, a new customs house (the name in Chinese reads 35 Kokuzantou Customs) was established at the border of the autonomous Chinese Mongolian State located approximately 50 kms east-southeast of the Tsav ore deposits. For three months following July the customs house conducted business during the first half of each month. From the Tsav ore deposits the customs house can be reached by unpaved road in approximately ninety minutes.

2.2 Topography

The Tsav topography is a moderate one which includes a small but long, extinct volcano and a hilly terrain undulating intermittently with open plains. Its topography is characteristic of mountainous regions. The slope gradient of the Tsav ore deposit area does not exceed 5 to 10 degrees. It is a moderately hilly terrain with smooth slopes. The highest peak is 825 meters above sea level. The difference between the lowest mountain ridge and valley is 50 to 80 meters.

2.3 Vegetation and Climate

Vegetation of the Tsav ore deposit area is typical of steppe lands with a variety of grain plants and an absence of trees. The nearest wooded area is located towards the northwest and is approximately 150 kilometers away.

The climate reflects characteristics that are typical of a continental dry environment. The daily and annual changes in temperature and atmospheric pressure is striking. Winter consists of many windy days with little precipitation. On the average, annual snowfall does not exceed 80 to 150 millimeters. The daily temperature changes in spring are severe. Dry air, strong winds, and sand storms are characteristic of that season. Summer is short and mild. The temperature differences between day and night are severe. The primary wind direction is northwest with an average speed of three to five meters per second. The maximum wind speed is between 20 to 25 meters per second. The average temperature throughout the year is 0°C. The lowest recorded temperature is -37.5°C (1987). The highest recorded temperature is -37.5°C (1982).

According to the Choybalsan meteorological observatory, the average annual rainfall for the region is 244 millimeters. However, according to the Eldes Town (Maludai Mine) observatory, the average annual rainfall is 402 millimeters.

The table belows show the average temperature and rainfall on a monthly basis (source, the Eldes meteorological observatory).

Month	1	2	3	4	5	6	7	8	9	10	11	12
Temp. (°C)	-20	-18	-8	0	+11	+16	+18	+16	+9	+1	-10	-17
Rainfall (mm)	3	2	4	11	15	51	91	117	36	3	7	3

The depth of the frozen earth surface in winter is between 2.4 to 4.2 meters. By the end of June, it completely thaws. There are not permanently frozen surfaces in the designated area. There are no continuously flowing springs or watercourses in the vicinity of the Tsav ore deposits.

Chapter 3. Outline of the study in this year(1993)

Under the framework that were designed in 1992, the following tunnel prospecting was conducted

- (1)Name : regional development program study
- (2)Investigation area : Tsav area, Mongolia
- (3)Period : 1993, 06, 24~1994, 02, 25
- (4)Content of Study : Tunnel Prospecting and
Temporary Construction etc
- Mine mouth : construction of Portal
Width 8.0(m) x Height 6.0(m)x Thickness 0.8(m)
- Tunneling
Quantity
 - Inclined Shaft : 247.4m
 - Waste Pit : 30 (15x2 places)
 - Depository : 130m³ (65x2 places)
 - Transformer
Station : 15
 - Pump Station : 15
 - Project Section : 11.92m² (Width 4.0(m) x Height 3.4(m))

Project Gradient
of Inclined Shaft: 8° 30'
Project Direction
of Inclined Shaft: N68° 30' E

• Temporary Construction

Fuel Storage : setting Tanks (Gasoline, Light Oil, Kerosene) etc.
Electricity : setting Control Panel, Switch Board etc
Communication : Setting INMARSAT, Interphone 10 sets, etc
Power Station : setting Generator (750KVA X 2 units) Control Panels and Fuel Tank, etc
Air Supply : laying Pipe (4" x 30m)
Water Supply : (A) Drinking water supply
Drainage : setting Tank, Pump, Pipe (2" X 250m with heat insulator) etc
(B) Underground water supply setting pipe (2" X 250m with heat insulator) etc
(C) Deep-Well-Pump setting Pump, Pipe etc

Ventilation : setting Fan (Contrafan 75kw), FRV Air Duct (800m/m ϕ x 271m)

• Building & Repair

Dormitory

Building of Gel : 5 Geles of 10m ϕ , 3 Geles of 6m ϕ included a dining room, bathroom toilet, kitchen and laundry

Office

Building of Gel : 2 Geles of 10m ϕ included toilet

Workshop : (Width 12.0(m) x Length 20(m) x Height 7.75(m)) included 5t traveling crane, service pit

Garage : 6 Containeres

Improvement of

Power Station : setting Gate Doors, Windows

Improvement of
Magazine :setting Gate Doors

Chapter 4. Progress Schedule

Content of Study	Quantity	June	July	August	September	October	November	December	January	February	Note
1 Mobilization											
2 Transportation Procurement Temporary Construction Fuel storage Electric-Communication Power station Air Supply Water Supply Drainage Ventilation Building & Repairs Dormitories Office Workshop Garage Power Station Magazine											
3 Mine-Portal Tunneling Inclined Shaft Waste Pit Transformer Station Depository for Vehicle Pump Station Floor Concreting	247.4m 30 15m ³ 130 15										
4 Transportation											
5 Demobilization											
6 Report											

Part II Results of Tunnel Prospecting

Part II. Results of Tunnel Prospecting

Chapter I. Summary of the study

1.1 Purpose of the study

The purpose of this study was to analyze the conditions of the deposit and study the geography of the Tsav deposit in the Tsav region, Mongolia, and to draw up a mine development plan. The survey also aimed to transfer technologies to Mongolian institutions through the tunnel prospecting.

1.2. Study Site

Based on the location of the foot wall of the forth deposit (X coordinate: 77,989.0; Y coordinate: 22,386.9) and at an elevation of 790 meters in the Tsav deposit, we dug a canal at N68° 30'E and gradient 8° 30' to form a mine mouth.

1.3 Summary of each excavation work

1) Inclined shaft

Excavation was based on a blasting method which combined a hydraulic mobile jumbo (drilling machine) and LHD (an abbreviation for "load, haul, dump" and comprising a diesel-operated wheel loader for the mine interior), using the trackless method. We used the burn-cut method for blasting, while adopting the smooth blasting method to blast the outercircumference of the tunnel so as to leave the rock mass undamaged.

We used steel timbering or rockbolts for support, where necessitated according to the conditions of the rock after the excavation.

2) First Waste pit

We began excavating 15 meters along the horizontal pit in the direction of 30° from the inclined shaft direction at 126 meters from the beginning of the inclined shaft. We used the same method as that used in the inclined shaft excavation works.

3) Transformer Station

We extended the width of the left side at 134 meters from the beginning of the inclined shaft. We used virtually the same excavation method as that used in the inclined shaft excavation works.

(Because a free surface existed, we did not use the burn-cut method).

4) Pump Station

We extended the width of the left side at 142 meters from the beginning of the inclined shaft. We used the same excavation method as that used for the transformer station.

5) First Depository

We extended the width of the right side at 158 meters from the beginning of the inclined shaft. We used the same excavation method as that used for the transformer station.

6) Second Depository

We extended the width of the right side at 223 meters from the beginning of the inclined shaft. We used the same excavation method as that used for the transformer station.

7) Second Waste pit

We began excavating 15 meters along the horizontal pit in the direction of 30° from the inclined shaft direction at 243 meters from the beginning of the inclined shaft.

1.4 Study method

1.4.1 Length of drift

Work	Project	Result
Inclined Shaft	247.4m	247.4m
Type 1	20.7m	20.7m
Type 2	25.2m	25.2m
Type 3	21.0m	21.0m
Type 3-1		36.2m
Type 4	180.5m	144.3m
First Waste Pit	15.0m	16.5m
Second Waste Pit	15.0m	15.0m
First Depository	65.0m ³	65.0m ³
Second Depository	65.0m ³	65.0m ³
Transformer Station	15.0m ³	15.0m ³
Pump Station	15.0m ³	15.0m ³
Total	277.4m 160.0m³	278.9m 160.0m³

1.4.2 Specifications of drift

(1) Effective section for each drift

	Area(m ²)	Width(m) x Height(m)
Inclined shaft type 1	13.42	(4.3 x 3.55)
Inclined shaft type 2	13.67	(4.35x 3.575)
Inclined shaft type 3	11.96	(4.0 x 3.4)
Inclined shaft type 3-1	13.32	(4.0 x 3.4)
Inclined shaft type 4	11.96	(4.0 x 3.5)

(2) Gradient of inclined shaft

8° 30' (degree)

(3) Height of mine mouth

787.1m

(4) Direction of inclined shaft

N 68° 30' E

1. 4. 3 Main Equipment

Equipment	Specifications	Quantity	Note
Drill Jumbo	Hydraulic 2 Boom	1	use as rock-bolt
Mortal Charger Car	TOYOTA Hilux	1	Mortal Pump(MM151)
Load Haul Dump	3.8m ³ class	2	
Explosive Chager	TOYOTA Hilux	1	AN-FO charger(75Kg)
Compressor	21m ³ /min	1	
Mini-Back-Hoe	0.1m ³ class	1	with Breaker
Jack-hammer	30Kg class	2	
Track	2t, attached with crane	1	
Track	1t, Hilux, WCabin	1	
Wagon	Landeruser 80type	1	
Wagon	Landeruser 70type	1	
Generator	750KVA	2	
Generator	55KVA	1	
Generator	10KVA DCA-13SPK	2	
Submersible Pump	5.2KW BS-2102HT	3	
Submersible Pump	2.2KW BS-2066	2	
Deep-well Pump	3.7KW SP-5A-19type	2	
Fan	1,000mm ϕ , 300mmAq, 75Kw	1	
Car Washer	Pressure 65Kg/cm ²	1	
High-speed Cutter		2	
Baby-Compressor	3.7P-14V5, 230 Liter	1	
Electric Welder	BPZ-400-3	2	
Engine Welder	BLW-150SS	1	
Feed-Pump	25BISND5.4	1	
Fuel-Pump		2	for vehicles
Fuel-Pump		1	for generator
INMARSAT			
Communication		1	
Travelling Crane	5t electric crane	2	

1.4.4 Form of Work

① Working time

staff	9:00~18:00
first shift	9:00~17:00
second shift	17:00~ 1:00
third shift	1:00~ 9:00

② Number of Men

Member of Japanese study team

Engineer 20 persons (including 7 supervisors)

Member of Mongolian study team

Staff 12 persons (including 3 foremen)

Driller 6

Mechanic 3

Electrician 3

Operator of Generator 3

Surveyor 2

Kitchen worker for Japanese 3

Kitchen worker for Mongolian 4

Clerk 3

Lodge keeper 4

Driver 3

Laundry and sweeping worker 2

Assistnt worker for mongolian 5

Interpreter 4

1.4.5 Dormitory

For dormitory, the Japanese servey team built Gels (five buildings of ten meters in diameter and three buildings of six meters in diameter). Additional facilities included a dining room (one building of ten meters in diameter), four buildings serving as bathroom/toilet facilities (20 feet containers), a kitchen and a laundry (both 40 feet containers). Drinking water was carted from a tank at a well dug by the former Soviet Union and located six kilometers from Tsav. This was stored in a 50-cubic-meter tank. A septico tank with capacity to treat 21 persons processed polluted water.

The Mongolian side built a wooden prefabricated office which doubled as dormitory (52.5 meters x 12.5 meters).

Electricity was supplied to buildings for both parties using an

independent 750 KVA power generation system.

1.5 Organization of study teams

(1) Japanese team

Name	Duty	Company
Kunitoshi OE	General Manager	(MINDECO)
Mamoru OOSHITA	Chief Administrator	(")
Yoshio OONO	Chief Mecanical Engineer	(")
Michihiko HASEGAWA	Chief Electrical Engineer	(")
Hisayoshi FURUMORI	Chief Foreman for Tunneling	(")
Yukou TAKAHASHI	Chief Foreman for Tunneling	(")
Masanao WASHIYA	Chief Foreman for Tunneling	(")
Kazuo YOKOKAWA	Vice Foreman for Tunneling	(")
Hideo MIZUGUCHI	Vice Foreman for Tunneling	(")
Masaki SUMIYA	Vice Foreman for Tunneling	(")
Rikio OOE	Vice Foreman for Tunneling	(")
Minoru YAMAMOTO	Vice Foreman for Tunneling	(")
Hiroyuki HASHIMOTO	Vice Foreman for Tunneling	(")
Takeshi NAMIKI	Supervisor for Mecanical Engineer	(")
Yukikazu KAWAUCHI	Supervisor for Mecanical Engineer	(")
Iwao SASAHARA	Supervisor for Mecanical Engineer	(")
Yasuyuki KITAJIMA	Supervisor for Civil Engineer	(")
Kouji OOSHITA	Supervisor for Electrical Engineer	(")
Naoto OONOBORI	Supervisor for Electrical Engineer	(")
Hiroshi FUKAMI	Supervisor for Electrical Engineer	(")

MINDECO : MITSUI MINERAL DEVELOPMENT ENGINEERING CO., LTD.

(2) Mongolian team

Name	Duty	Company
Lodoin AYUR	General Project Manager Director of TSAV Company	(MGMR and TSAV Company)
R. BATBAYAR	Chief Engineer	(TSAV Company)
Y. LUTBAATAR	Tunnel Superintendent	(" ")
N. TSOLMON	Economist	(" ")
B. halzan	Administration Manager	(" ")
D. MUNHTSETSEG	Chief Accountant	(" ")
SH. NAMHAINYAMBUU	Electrical and mechanical Engineer	(" ")

TS. NOROVSAMBUU	Chief Geologist	(" ")
V. HURELTUMOR	Foreman for Tunneling	(" ")
L. HURELBAATAR	Foreman for Tunneling	(" ")
B. BAATARHUU	Foreman for Tunneling	(" ")
TS. DASHZEVGE	Foreman for Treasurer	(" ")

MGMR : THE MINISTRY OF GEOLOGY AND MINERAL RESOURCES OF MONGOLIA

Appendices

2. Tunnel Prospecting

Period	Starting Date		1993, 07, 01					
	Tunnel Starting Date		1993, 08, 26					
	Tunnel completing Date		1993, 12, 01					
	Completing Date		1993, 12, 05					
Required days			up-to-1993, 12, 01			up-to-1993, 12, 05		Note
			day	rate (%)		day	rate (%)	
	Tunnel	84	63.2	54.6	84	61.3	53.2	10days are double
	Construction	49	36.8	31.8	49	35.8	31.0	
	Others				4	2.9	2.5	
	Sub-total	133	100.0	86.4	137	100.0	86.7	
Day off	21		13.6	21		13.3		
Total	154		100.0	158		100.0		
Required men			Tunnel	Construction	Others	Note		
			Worker	Interior Exterior	580 1,755	1,569	124	
	Engineer	Interior Exterior	1,840	1,267	88			
	Total	Interior Exterior	2,420 1,755	2,836	212			
	Total		4,175	2,836	212			
Timbering Efficiency			up-to-1993, 12, 01		up-to-1993, 12, 05		Note	
			per working day		1.86			1.81
	per tunneling day		2.95		2.95			
	per required day		1.61		1.57			
	per required man		0.035		0.034			
	number of timbering		85		85			
length of timbering(%)		103.1m (41.7%)		103.1m (41.7%)				

3. Details of required days for Tunneling

Works	Period of tunneling				Breakdown			Additional construction				
	Construction day	tunnel day	Dismantle day	Total day	workings day	day off	Generator day	Dormitory day	Workshop day	Floor Concrete day	Total day	
Preparation	7/1~ 8/25 day 56			day 56	day 49	day 7	7/6~ 9/2 day 59	7/1~ 8/23 day 54	7/1~ 8/18 day 49		day day	
Inclined Shaft		8/26 ~ 11/29		92	78	14				11/12 11/17~20 11/27	6	
First Waste Pit		10/26 ~ 10/28		3	3							
Second Waste Pit		11/29 ~ 12/1		3	3							
Transformer Station		11/1 ~ 11/3		(3)	(3)							
Pump Station		11/1 ~ 11/3		(3)	(3)							
First Depository		11/4 ~ 11/6		(3)	(3)							
Second Depository		11/25 ~ 11/27		(3)	(3)							
Demobilization			12/2~ 12/5	4	4					12/1~3	3	
Total				98	158	21	59	54	49		9	


5. Item of Consumptive Materials in 1993

Article	Specifications	Quantity	Note
Bit		pieces	
	51m/m ϕ R32	66	
	89m/m ϕ R32	12	
	38m/m ϕ R28 insert	55 10	
Rod	38m/mHEX L=3,700	28	
	32m/mHEX L=2,365	15	
Shankrod	38m/m ϕ HD-150	20	
Sleeve	38m/m ϕ	31	
	38/32m/m ϕ	15	
Explosive			
Ammonita		7,524Kg	
Detonator		7,122 pieces	
Timberings	Inclined Shaft		
	Type 1	28 set	
	Type 2	21	
	Type 3	14	
	Type 3-1	27	
Rock-bolt	22m/m ϕ L=2.0m	1,244 pieces	
Pipe	2inch	1,060.5m	
	4inch	1,057.1	
Light Oil		181,428 liter	
Gasoline		2,279	
Kerosene		13,400	
Lubricant	Engine Oil 10#	800	
	Engine Oil 30#	800	
	Engine Oil 40#	3,800	
	Hydraulic		
	Oil 32#	1,200	
	Ger Oil 75#	400	

Photograph



General view of Tsav




Mine portal



Excavation of mine portal




Construction of mine portal (frame)




Construction of mine portal (base)




Construction of mine portal (assemble)



Drilling (hydraulic jumbo)




Charging explosive



Scaling




Excavation for timbering




Timbering




Timbering (steel board)




Rock-bolt (type 4)



Starting point of tunneling in 1993




Inclined shaft (type 1)




Inclined shaft (type 2)



Inclined shaft (type 3)




Inclined shaft (type 3-1)



Inclined shaft (type 4)



First waste pit



Transformer station



Pump station




First depository for heavy machines




Second depository for heavy machines



Second waste pit




Termination point of tunneling in 1993




Establishment of PC plate



Inspection by MMAJ




Establishment of TV-antena




Base for generator



Establishment of 750 KVA generator




Control panel for generator




Establishment of deep-well pump



Establishment of water tank



Establishment of fan




Establishment of ventilation tube




Establishment of ventilation tube (FRV)




Establishment of drainage tube




Establishment of drainage, feed tube




Establishment of septic tank




Constraction of drainage pond




Constraction of workshop



Construction of office




INMARSAT & TV antena



















22550

22500

22450



To Ereentsay 110km




50mm ϕ x 2

100mm ϕ x 2


50mm ϕ

100mm ϕ






Dining
& Kitchen(Mongolia)



Old inclined shaft
(natural refrigerator)



Dormitory
(Mongolia)




Sauna


22500


22450

22400

22350








Dormitory
(Mongolia)

Sauna



Power
station



Oil Pipe
100mm ϕ



Fuel oil (50m³x2)


Gasoline (50m³)

Gasoline station

Legend







Title	General View of Mine Site		
Scale	1/500	Date	1993. 8. 30
Drawing-No			