


THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY









Fig. 3.20
Proposed Channel Alignment and Cross Section of
Anilao River





**LONGITUDINAL PROFILE
ANILAO RIVER, ORMOC CITY**





THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 3.21
Longitudinal Profile of Anilao River






FIGURES IN PARENTHESES SHOW STATION NUMBERS OF RIVER IMPROVEMENT PLAN



THE STUDY ON THE FLOOD CONTROL FOR RIVERS IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 3.22
Proposed Channel Alignment and Cross Section of Malbasag River


LONGITUDINAL PROFILE
MALBASAG RIVER, ORMOG CITY



STATION No.	RIGHT BANK	LEFT BANK	DEEPEST RIVERBED	DESIGN RIVERBED	DESIGN HWL	DIKE CROWN	GRADIENT OF RIVERBED
1.000	20.46	22.54	17.41	4.000	17.000	17.000	1/100
1.100	18.40	18.80	13.30	3.500	16.500	17.300	1/200 with Dikes
1.200	15.01	16.26	13.95	3.000	15.000	16.800	
1.300	17.01	17.11	12.33	2.500	14.790	14.790	
1.400	12.99	14.00	11.42	2.000	13.480	14.290	
1.500	12.14	14.76	10.32	1.500	12.980	13.790	
1.600	12.70	12.80	9.90	1.000	11.780	11.780	
1.700	9.98	10.26	8.52	0.500	11.300	11.300	
1.800	8.84	9.15	7.54	0.050	10.850	10.850	
1.900	7.93	8.89	6.76	0.550	10.350	10.350	
2.000	12.34	6.41	5.77	1.050	9.875	9.875	
2.100	6.40	6.41	4.850	1.550	9.375	9.375	
2.200	6.40	6.40	4.70	2.050	8.875	8.875	
2.300	5.30	6.51	3.94	2.550	8.375	8.375	
2.400	4.66	6.29	3.36	3.050	7.875	7.875	
2.500	5.80	5.50	2.80	3.550	7.375	7.375	
2.600	5.30	5.05	4.87	4.050	6.875	6.875	
2.700	4.98	3.15	4.80	4.550	6.375	6.375	
2.800	3.77	1.39	2.04	5.050	5.875	5.875	
2.900	2.77	2.78	3.09	5.550	5.375	5.375	
3.000	4.30	4.30	0.97	6.050	4.875	4.875	
3.100	4.30	4.30	0.96	6.550	4.375	4.375	
3.200	4.30	4.30	0.95	7.050	3.875	3.875	
3.300	4.30	4.30	0.94	7.550	3.375	3.375	
3.400	4.30	4.30	0.93	8.050	2.875	2.875	
3.500	4.30	4.30	0.92	8.550	2.375	2.375	
3.600	4.30	4.30	0.91	9.050	1.875	1.875	
3.700	4.30	4.30	0.90	9.550	1.375	1.375	
3.800	4.30	4.30	0.89	10.050	0.875	0.875	
3.900	4.30	4.30	0.88	10.550	0.375	0.375	
4.000	4.30	4.30	0.87	11.050	-0.125	-0.125	
4.100	4.30	4.30	0.86	11.550	-0.625	-0.625	
4.200	4.30	4.30	0.85	12.050	-1.125	-1.125	
4.300	4.30	4.30	0.84	12.550	-1.625	-1.625	
4.400	4.30	4.30	0.83	13.050	-2.125	-2.125	
4.500	4.30	4.30	0.82	13.550	-2.625	-2.625	
4.600	4.30	4.30	0.81	14.050	-3.125	-3.125	
4.700	4.30	4.30	0.80	14.550	-3.625	-3.625	
4.800	4.30	4.30	0.79	15.050	-4.125	-4.125	
4.900	4.30	4.30	0.78	15.550	-4.625	-4.625	
5.000	4.30	4.30	0.77	16.050	-5.125	-5.125	
5.100	4.30	4.30	0.76	16.550	-5.625	-5.625	
5.200	4.30	4.30	0.75	17.050	-6.125	-6.125	
5.300	4.30	4.30	0.74	17.550	-6.625	-6.625	
5.400	4.30	4.30	0.73	18.050	-7.125	-7.125	
5.500	4.30	4.30	0.72	18.550	-7.625	-7.625	
5.600	4.30	4.30	0.71	19.050	-8.125	-8.125	
5.700	4.30	4.30	0.70	19.550	-8.625	-8.625	
5.800	4.30	4.30	0.69	20.050	-9.125	-9.125	
5.900	4.30	4.30	0.68	20.550	-9.625	-9.625	
6.000	4.30	4.30	0.67	21.050	-10.125	-10.125	
6.100	4.30	4.30	0.66	21.550	-10.625	-10.625	
6.200	4.30	4.30	0.65	22.050	-11.125	-11.125	
6.300	4.30	4.30	0.64	22.550	-11.625	-11.625	
6.400	4.30	4.30	0.63	23.050	-12.125	-12.125	
6.500	4.30	4.30	0.62	23.550	-12.625	-12.625	
6.600	4.30	4.30	0.61	24.050	-13.125	-13.125	
6.700	4.30	4.30	0.60	24.550	-13.625	-13.625	
6.800	4.30	4.30	0.59	25.050	-14.125	-14.125	
6.900	4.30	4.30	0.58	25.550	-14.625	-14.625	
7.000	4.30	4.30	0.57	26.050	-15.125	-15.125	


THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 3.23
Longitudinal Profile of Malbasag River




THE STUDY ON THE FLOOD CONTROL FOR RIVERS
 IN THE SELECTED URBAN CENTERS
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 3.24
 Alternatives of Diversion Point and Alignment of Jard
 Floodway



<p>THE STUDY ON THE FLOOD CONTROL FOR RIVERS IN THE SELECTED URBAN CENTERS</p>	<p>Fig. 3.25</p>
<p>JAPAN INTERNATIONAL COOPERATION AGENCY</p>	<p>Possible Dam Site of Guadalupe Flood Control Dam</p>


STAGE-CAPACITY RELATION CURVE OF GUADALUPE DAM




THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 3.26
Stage-Capacity Relation Curve of Guadalupe Flood
Control Dam

Cut-off Channel




Existing River Channel



THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY


Fig. 3.27
Channel Alignment of Alternatives for Anilao River



- Note: 1. Unit: m³/s
 2. The Figures show probable Flood Discharge of 50-Year Return Period
 3. () shows probable Flood Discharge of 20-Year Return Period

THE STUDY ON THE FLOOD CONTROL FOR RIVERS
 IN THE SELECTED URBAN CENTERS
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 4.1(1/2)
 Distribution of Design Discharge for Urgent Plan
 (Iloilo)






Legend	
	Improvement Limit
	Bridge

Note: 1. Unit: m³/s
 2. The Figures show probable Flood Discharge of 50-Year Return Period


THE STUDY ON THE FLOOD CONTROL FOR RIVERS
 IN THE SELECTED URBAN CENTERS
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 4.1(2/2)
 Distribution of Design Discharge for Urgent Plan
 (Ormoc)




THE STUDY ON THE FLOOD CONTROL FOR RIVERS
 IN THE SELECTED URBAN CENTERS
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 4.2
 Urgent Plan of Jaro River Improvement





THE STUDY ON THE FLOOD CONTROL FOR RIVERS
 IN THE SELECTED URBAN CENTERS
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 4.3
 Urgent Plan of Iloilo River Improvement




THE STUDY ON THE FLOOD CONTROL FOR RIVERS
 IN THE SELECTED URBAN CENTERS
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 4.4
 Cross Section for Master Plan and Urgent Plan (Anilao River)



<p>THE STUDY ON THE FLOOD CONTROL FOR RIVERS IN THE SELECTED URBAN CENTERS</p>	<p>Fig. 4.5 Cross Section for Master Plan and Urgent Plan (Malbasag River)</p>
<p>JAPAN INTERNATIONAL COOPERATION AGENCY</p>	

EARTH DIKE




DISTANCE (m ³ /s)	CREST WIDTH (m)	FREEBOARD (m)
less than 200	3.00	0.60
200 to 500	3.00	0.80
more than 500	4.00	1.00


THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 5.1
Typical Section of Earth Dike


CONCRETE DIKE



CONCRETE DIKE WITH SHEET PILE




REVTMENT : TYPE A



THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY


Fig. 5.3
Typical Section of Revetment Type A

REVETMENT : TYPE B



THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY


Fig. 5.4
Typical Section of Revetment Type B




RETAINING WALL

THE STUDY ON THE FLOOD CONTROL FOR RIVERS
 IN THE SELECTED URBAN CENTERS
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 5.5
 Typical Section of Retaining Wall



PLAN




DROP

THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY


Fig. 5.6
Standard Design of Drop

APPROACH STEPS TYPE A


PLAN



DETAIL B
(EDGE CONCRETE)




PROFILE



THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 5.7(1/2)
Standard Design of Approach Steps Type A


APPROACH STEPS TYPE B



THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY


Fig. 5.7(2/2)
Standard Design of Approach Steps Type B

M.F.C. PROTECTION
 TYPE A : BOULDER RIP-RAP





TYPE B : WOODEN PILE

SECTION



FRONT VIEW






	Area	Discharge	Type	Size	Remarks
Jaro R.	Sj-1		A	1 x 1	Fishpond
	Sj-2		A	1 x 1	Fishpond
	Sj-3	18	B	Type B-1.0 x 1	
	Sj-4	20	B	Type B-1.0 x 1	
	Sj-5	55	B	Type B-1.0 x 3	
	Sj-6	20	B	Type B-1.0 x 1	
	Sj-7	35	B	Type B-1.0 x 2	
	Sj-8	29	B	Type B-1.0 x 2	
	Sj-9	18	B	Type B-1.0 x 1	
	Sj-10	17	B	Type B-1.0 x 1	
	Sj-11	17	B	Type B-1.0 x 1	
	Sj-12	32	B	Type B-1.0 x 2	
Iloilo R.	Si-1	4	B	Type B-0.6	
	Si-2	93	A	Type A2	2 Fishpond
	Si-3	29	B	Type B-1.0 x 1	1 Fishpond
	Si-4	130	A	Type A3	Fishpond
	Si-5	6	B	Type B-0.6	
Mandurriao R.	Sm-1	25	B	Type B-1.0 x 2	
	Sm-2	42	A	Type A2	
	Sm-3	25	B	Type B-1.0 x 2	
	Sm-4	82	A	Type A3	


THE STUDY ON THE FLOOD CONTROL FOR RIVERS
 IN THE SELECTED URBAN CENTERS
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 5.9(1/2)
 Location of Sluices and Drainage Area (Iloilo)




THE STUDY ON THE FLOOD CONTROL FOR RIVERS
 IN THE SELECTED URBAN CENTERS
 JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 5.9(2/2)
 Location of Sluiques and Drainage Area (Ormoc)





PROFILE





PLAN



TYPE A1



TYPE A2




TYPE A3




THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY


Fig. 5.10
Standard Design of Sluice Type A



PROFILE






FRONT VIEW




PLAN

	DIAMETER
Type B0.6	600
Type B0.8	800
Type B1.0	1,000




THE STUDY ON THE FLOOD CONTROL FOR RIVERS IN THE SELECTED URBAN CENTERS
 JAPAN INTERNATIONAL COOPERATION AGENCY


Fig. 5.12
 Standard Design of Diversion Weirs for Jaro Floodway



PLAN S=1/2,000




PROFILE



FRONT VIEW

THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY




Fig. 5.13
Standard Design of Diversion Weir for La Paz
Floodway



GROUNDSILL FOR FLOODWAY

THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 5.14
Typical Section of Groundsill




DAM SITE	CREST ELEVATION (EL. m)	n (no.)	B1 (m)	B2 (m)	B3 (m)	B4 (m)
ANILAO 1	66.000	7	9.00	19.00	5.00	25.00
ANILAO 2	64.000	5	6.00	14.00	5.00	16.00
MALBASAG	135.500	8	5.00	21.50	16.50	23.00

THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY


Fig. 5.15
Location and Standard Design of Slit Dams

INVERT SIPHON


PROFILE





PLAN



TYPE A : SIDE SLOPE H=1:2.0
V=1:1.0



TYPE B : SIDE SLOPE 1:0.5 H=1:2.0
V=1:1.0




River	Name of Bridge/ Station No.	Length (m)	Width (m)	No. of Span	Type
Jaro	Ticud	60	7.00	3	TYPE A
	Ledesco	60	7.00	3	TYPE A
Jaro FW	STA. 0+300	70	7.00	4	TYPE A
	STA. 2+120	70	7.00	4	TYPE A
	STA. 4+090	70	7.00	4	TYPE A
La Paz FW	STA. 0+400	70	7.00	4	TYPE A
Iloilo	Molo	110	7.00	6	TYPE A
Mandurriao	Seminer	40	7.00	2	TYPE A
	Street	40	7.00	2	TYPE A
	Sant Rose	40	7.00	2	TYPE A
Bulacao	Inawayan	48	7.00	3	TYPE A
Kinalunsan	STA. 0+300	26	7.00	2	TYPE B
	STA. 0+450	26	7.00	2	TYPE B
	STA. 0+680	26	14.00	2	TYPE B
	STA. 1+200	26	7.00	2	TYPE B
	STA. 1+750	22	7.00	1	TYPE B
	STA. 3+970	22	3.50	1	TYPE B
Guadalupe	STA. 0+420	30	7.00	2	TYPE B
	STA. 0+920	30	7.00	2	TYPE B
	STA. 1+210	32	14.00	2	TYPE B
	STA. 4+000	41	7.00	2	TYPE B

River	Name of Bridge/ Station No.	Length (m)	Width (m)	No. of Span	Type
Lahug	STA. 0+000	21	14.00	1	TYPE B
	STA. 0+110	23	7.00	1	TYPE B
	STA. 0+300	23	14.00	1	TYPE B
	STA. 0+620	23	14.00	1	TYPE B
	STA. 1+040	23	7.00	1	TYPE B
	STA. 1+800	14	7.00	1	TYPE B
	STA. 2+400	14	7.00	1	TYPE B
	STA. 2+560	14	14.00	1	TYPE B
	STA. 2+730	14	14.00	1	TYPE B
	STA. 3+200	23	7.00	1	TYPE B
Subang Daku	STA. 0+150	30	14.00	2	TYPE B
	STA. 1+350	30	14.00	2	TYPE B
	STA. 2+640	32	3.50	2	TYPE B
	STA. 2+688	30	3.50	2	TYPE B
	STA. 3+750	30	3.50	2	TYPE B
	STA. 4+060	32	3.50	2	TYPE B
	STA. 4+720	32	3.50	2	TYPE B
	STA. 4+840	41	14.00	2	TYPE B
Anilao	Alegria	57	7.00	3	TYPE A
	Osmena Ext.	57	7.00	3	TYPE A
	Anilao	57	7.00	3	TYPE A
Malbasag	Malbasag	33	7.00	2	TYPE B
	Spillway	33	7.00	2	TYPE B


THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 5.17
Standard Design of Bridge


PLAN



PLOFILE




FRONT VIEW




THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 5.18
Bridge at Lahug River Mouth

PLAN



PROFILE



THE STUDY ON THE FLOOD CONTROL FOR RIVERS
IN THE SELECTED URBAN CENTERS
JAPAN INTERNATIONAL COOPERATION AGENCY

Fig. 5.19
Protection Works for Bridge Piers

SUPPORTING REPORT

ON

URBAN DRAINAGE PLAN

**SUPPORTING REPORT
ON
URBAN DRAINAGE PLAN**

Table of Contents

1. INTRODUCTION	UD-1
2. EXISTING DRAINAGE SYSTEM	UD-3
2.1 Iloilo City	UD-3
2.2 Cebu City	UD-4
2.3 Ormoc City	UD-5
2.4 Tacloban City	UD-7
3. DRAINAGE INUNDATION PROBLEMS	UD-9
3.1 Iloilo City	UD-9
3.2 Cebu City	UD-10
3.3 Ormoc City	UD-11
3.4 Tacloban City	UD-12
4. MASTER PLAN	UD-15
4.1 Project Area	UD-15
4.2 Project Scale	UD-15
4.3 Drainage Improvement Plan	UD-16
5. URGENT PLAN	UD-21
5.1 Project Area	UD-21
5.2 Planning Conditions	UD-21
5.3 Drainage Improvement Plan	UD-24
ANNEX: PREVIOUS STUDIES AND PROJECTS	A-1

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

LIST OF TABLES

Table 2.1	Hydraulic Features of Existing Drainage Channels in Iloilo City	T-1
Table 2.2	Hydraulic Features of Existing Drainage Channels in Cebu City	T-5
Table 2.3	Hydraulic Features of Existing Drainage Channels in Ormoc City	T-7
Table 2.4	Hydraulic Features of Existing Drainage Channels in Tacloban City	T-8
Table 3.1	Habitual Inundation Area and Condition	T-10
Table 4.1	Design Discharge of Urban Drainage Area	T-11
Table 4.2	Hydraulic Design of Channel Improvement	T-13
Table 5.1	Cost Comparison of Channel Improvement in Planning Scale	T-15
Table 5.2	Design Discharges for Alternatives of Drainage Improvement (Iloilo, Ormoc)	T-16
Table 5.3	Hydraulic Design for alternatives of Channel Improvement (Iloilo, Ormoc)	T-17
Table 5.4	Cost Comparison for Alternatives of Channel Improvement	T-18
Table 5.5	Cost Comparison of Channel Improvement in Discharge Ratio for Incore Diversion Channel	T-19
Table 5.6	Drainage Improvement Works for Urgent Plan, Iloilo and Ormoc	T-20

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

LIST OF FIGURES

Fig. 2.1	Delineated Drainage Basin and Subbasin, Iloilo	F-1
Fig. 2.2	Existing Urban Drainage System, Iloilo	F-2
Fig. 2.3(1/2)	Hydraulic Features of Existing Drains, Iloilo	F-3
Fig. 2.3(2/2)	Hydraulic Features of Existing Drains, Iloilo	F-4
Fig. 2.4	Delineated Drainage Basin and Subbasin, Cebu	F-5
Fig. 2.5	Existing Urban Drainage System, Cebu	F-6
Fig. 2.6	Hydraulic Features of Existing Drains, Cebu	F-7
Fig. 2.7	Delineated Drainage Basin and Subbasin, Ormoc	F-12
Fig. 2.8	Existing Urban Drainage System, Ormoc	F-13
Fig. 2.9	Hydraulic Features of Existing Drains, Ormoc	F-14
Fig. 2.10	Delineated Drainage Basin and Subbasin, Tacloban	F-15
Fig. 2.11	Existing Urban Drainage System, Tacloban	F-16
Fig. 2.12	Hydraulic Features of Existing Drains, Tacloban	F-17
Fig. 3.1	Habitual Inundation Area, Iloilo	F-21
Fig. 3.2	Habitual Inundation Area, Cebu	F-22
Fig. 3.3	Habitual Inundation Area, Ormoc	F-23
Fig. 3.4	Habitual Inundation Area, Tacloban	F-24
Fig. 4.1	Design discharge for channel improvement	F-25
Fig. 4.2	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Ingore Creek, Iloilo	F-27
Fig. 4.3	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Bo. Obrero Creek, Iloilo	F-28
Fig. 4.4	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Rizal Creek, Iloilo	F-29
Fig. 4.5	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Mabolo Creek, Cebu	F-30
Fig. 4.6	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Lahug Tributary, Cebu	F-31
Fig. 4.7	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Tinago Creek, Cebu	F-32
Fig. 4.8	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Pahina Central Kalunbihan DM, Cebu	F-33
Fig. 4.9	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Calamba DM, Cebu	F-34

Fig. 4.10	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Sta. Teresita Village DM, Cebu	F-35
Fig. 4.11	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Basak.San Nicolas DM, Cebu	F-36
Fig. 4.12	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Sto. Niño Creek, Cebu	F-37
Fig. 4.13	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Barangay Inayawan DC, Cebu	F-38
Fig. 4.14	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Lotao Creek, Ormoc	F-39
Fig. 4.15	Proposed Channel Alignment, Cross Section and Longitudinal Profile, City Proper Creek, Ormoc	F-40
Fig. 4.16	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Abucay River, Tacloban	F-41
Fig. 4.17	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Naga-Naga Creek, Tacloban	F-42
Fig. 4.18	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Mangonbangon River, Tacloban	F-43
Fig. 4.19	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Langhas-Lirang Creek, Tacloban	F-44
Fig. 4.20	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Sagkahan Creek, Tacloban	F-45
Fig. 4.21	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Pleasantville Creek, Tacloban	F-46
Fig. 4.22	Proposed Channel Alignment, Cross Section and Longitudinal Profile, Burayan River, Tacloban	F-47
Fig. 5.1	Objective Drainage Basin (Iloilo City)	F-48
Fig. 5.2	Objective Drainage Basin (Ormoc City)	F-49
Fig. 5.3	Basic Design of Drainage Channel Improvement	F-50
Fig. 5.4	Alternative Schemes of Drainage Channel Improvement (Ingore Creek)	F-51
Fig. 5.5	Alternative Profile of Drainage Channel Improvement (Ingore Creek)	F-52
Fig. 5.6	Alternative Width of Drainage Channel Improvement	F-53
Fig. 5.7	Alternative Schemes of Drainage Channel Improvement (Bo. Obrero Creek)	F-54
Fig. 5.8	Alternative Profile of Drainage Channel Improvement (Bo. Obrero Creek)	F-55
Fig. 5.9	Proposed Channel Alignment and Typical Cross Section, Ingore Creek	F-57
Fig. 5.10	Longitudinal Profile, Ingore Creek	F-59

Fig. 5.11	Proposed Channel Alignment and Typical Cross Section, Bo. Obrero Creek	F-60
Fig. 5.12	Longitudinal Profile, Bo. Obrero Creek	F-63
Fig. 5.13	Proposed Channel Alignment and Typical Cross Section, Rizal Creek	F-64
Fig. 5.14	Longitudinal Profile, Rizal Creek	F-65
Fig. 5.15	Proposed Channel Alignment and Typical Cross Section, Lotao Creek	F-66
Fig. 5.16	Longitudinal Profile, Lotao Creek	F-67

1. INTRODUCTION

This supporting report presents the results of the study on the drainage improvement in the study areas, with the aim of preparing the Master Plan for four cities: Iloilo, Cebu, Ormoc and Tacloban, and conducting the feasibility study on the urgent projects identified for two cities: Iloilo and Ormoc.

2. EXISTING DRAINAGE SYSTEM

2.1 Iloilo City

Urban areas of Iloilo composed of Iloilo City and the five municipalities of Lapaz, Jaro, Molo, Mandurriao and Arevalo are traversed by two main rivers and their tributaries. These watercourses constitute nine (9) drainage basins and subbasins delineated in Fig. 2.1, as follows:

No.	Drainage Basin	Area (km ²)
SB-1	Ingore Creek	8.02
SB-2	Jaro River Downstream	4.14
SB-3	Alangan Coastal	1.04
SB-4	Bo. Obrero Creek	3.89
SB-5	Rizal Creek	0.50
SB-6	Mandurriao Creek	5.81
SB-7	Iloilo River	12.21
SB-8	South City Proper	1.85
SB-9	Batiano River	3.43
Total		40.89

The stormwater collection and drainage systems have only been constructed in densely urbanized districts of the city proper at the right bank of the Iloilo river estuary, and Jaro-La Paz area between Mandurriao Creek and the Jaro main stream as shown in Fig. 2.2. Existing systems commonly use precast reinforced concrete pipes. The pipe sizes used are 400, 450, 600, 750, 900, 1,050 and 1,200 mm and the interval of manhole approximately ranges from 30 to 50 m. Open ditches are mostly unlined with various sizes and shapes. The following table gives a summary of the existing drainage length of the city core.

Primary Drainage Channel	Secondary Drainage				Total Length
	Ditch/Open Channel	RCP <900mm	RCP >1000mm	Box Culvert	
17,000	12,000	26,000	900	few	55,900

Since the drainage pipes have been installed several decades ago, functional damages are found in many places, even complete blockade due to sedimentation of soil or garbage and structural collapse. Consequently, a storm inundation frequently occurs even with normal rainfall. The drainage system, furthermore, performs the combined functions of sewage and stormwater collection.

Areas adjoining the city proper and Jaro-La Paz, which are Molo, Arevalo, Mandurriao, La Paz (coastal area) and Jaro (left bank area of Jaro River), have been considerably urbanized in recent years. However, the development of the drainage system has not coped with the urbanization. Although some villages and subdivisions have been provided with small scale drainage systems, they have been partially developed on a piecemeal basis without a comprehensive plan for the entire drainage area. Therefore, the stormwater in the areas drains to the nearest recipients depending on the ground surface runoff and/or are retained in depression ponds, etc.

In addition to the confined drainage system, the major drainage problem in the urban area is an inadequate drainage capacity of primary channels. The following table shows the flow capacities of three (3) primary channels lying in the serious inundation areas, and Table 2.1 and Fig. 2.3 show hydraulic features of the primary channels.

No.	Primary Channel	Drainage Area (km ²)	Drainage Capacity (m ³ /s)	
			Range	Average
1.	Ingore Creek	8.02	2 - 70	15
2.	Bo. Obrero Creek			
	- Downstream	3.89	10 - 90	30
	- Upstream	1.20	1 - 3	1
3.	Rizal Creek	0.50	4 - 230	4

2.2 Cebu City

The urban area of Cebu is traversed by five (5) rivers, several creeks and drainage mains. These waterways constitute the basis for the formation of some 20 hydrologically independent drainage basins and subbasins. The independent drainage basins are delineated in Fig. 2.4, as follows:

No.	Drainage Basin	Area (km ²)
SB-1	Subang Daku River	4.85
SB-2	Mabolo Creek	2.78
SB-3	Lahug Tributary	0.65
SB-4	Lahug River Downstream	4.06
SB-5	Tinago Creek	1.10
SB-6	Central Proper	0.34
SB-7	Pahina Central-Kalubihan	1.00
SB-8	Guadalupe River Downstream	3.34
SB-9	Calamba	0.79
SB-10	Sta. Teresita Village	3.80
SB-11	Buhisan River	1.70
SB-12	Kinalumsan River Downstream	4.82
SB-13	Barangay Mambaling	0.30
SB-14	Basak-San Nicolas	0.67
SB-15	Basak-Pardo	0.90
SB-16	Basak Coastal	0.43
SB-17	Sto. Niño Creek	5.11
SB-18	Kinasang-an Creek	0.36
SB-19	Barangay Inayawan	1.29
SB-20	Bulacao River	3.13
Total		41.42

The existing urban stormwater drainage systems including collection facilities of inlet and gutter are found only in densely populated districts of the city, which are bounded approximately on the north by Subang Daku River, on the south by Kinalumsan River and confined within 2 to 4 km wide from the coastline as shown in Fig. 2.5. The rest of the districts is defined as natural drainage areas where the storm runoff depends largely on overland flow to the nearest river and sea, natural detention in depression areas, ground

infiltration and/or evaporation, except in some subdivisions and villages where collection and drainage systems have been developed.

The existing collection and drainage systems serving the combined functions of sewage and stormwater collection were constructed on the basis of the Drainage Master Plan in 1950. Precast reinforced concrete pipe is commonly used for the facilities with the typical pipe sizes of 450, 600, 750, 900, and 1,800 mm. The interval of manhole ranges from 25 to 50 m. Lengths of the primary and secondary drainage including parts of the five rivers within the urban drainage area are estimated, as shown below.

Primary Drainage Channel	Secondary Drainage				(Unit: m)
	Ditch/Open Channel	RCP <900mm	RCP >1000mm	RC Box Culvert	Total Length
9,800	11,100	55,000	7,000	a few	82,900

Source: DPWH Region VII District Office

One of the significant causes to urban drainage problems is the inadequate drainage capacity of primary channel, as well as the confined service area of the drainage system. The drainage capacity of primary channels lying in the serious inundation areas are evaluated as shown below, and Table 2.2 and Fig. 2.6 show hydraulic features of the primary channels.

Item No.	Primary Channel/Drain	Drainage Area (km ²)	Drainage Capacity (m ³ /s)	
			Range	Average
1.	Mabolo	2.78	2 - 40	8
2.	Lahug Tributary	0.65	1 - 50	9
3.	Tinago	1.10	1 - 26	4
4.	Pahina Central - Kalunbihan	1.00	1 - 7	6
5.	Calamba	0.79	2 - 3	2
6.	Sta. Teresita Village	3.80	2 - 3	3
7.	Basak - San Nicolas	0.67	1 - 2	1
8.	Sto, Niño	5.11	1 - 10	2
9.	Barangay Inayawan	1.29	2 - 4	4

2.3 Ormoc City

The urban area of Ormoc is divided into two; the city proper of 0.93 km² surrounded by Anilao River, Malbasag River, Hermosila Drive Street and the coastal line, and the new residential area of 2.68 km² adjoining the city proper, as shown in Fig. 2.7.

The city proper is densely urbanized being the commercial and residential center of Ormoc City and the urban stormwater collection and drainage systems are well developed. The existing system is hydrologically divided into four drainage basins within the city proper, which drain independently to the sea or the rivers.

No.	Urban Drainage Basin	Area (km ²)
City Proper Area		
SB-1	South City Proper	0.21
SB-2	North City Proper	0.32
SB-3	Anilao River Downstream	0.19
SB-4	Malbasag River Downstream	0.21
New Residential Area		
SB-5	Anilao River Upstream	0.70
SB-6	Malbasag River Upstream	0.43
SB-7	Lotao Creek	1.03
SB-8	Barangay Punta	0.52
Total		3.61

Existing systems were constructed on the basis of the Drainage Improvement Plan prepared by the City Engineering Office. Various types of drainage facilities such as RC-U-type with cover, RC-pipe, open channel, RC-box culvert are adopted for the systems. The following table shows lengths of the existing drainage systems in the city proper, and Fig. 2.8 shows coverage of the systems.

(Unit: m)					
Primary Channel	Open Ditch	PC-Pipe	RC-U Type	RC-Box Culvert	Total
1,200	6,000	7,000	2,300	a few	16,500

During the flood caused by Typhoon Uring in November 1991, some drainage facilities were damaged and clogged due to sand and silt brought by the flood. Although some rehabilitation works were carried out, several places in the city core area will have stormwater inundation by downpour during the rainy season.

The new residential area is divided into four drainage areas which drain directly to Malbasag River, Anilao River, Lotao Creek and Ormoc Bay. These areas have been rapidly developing in recent years, however, the construction of the stormwater drainage system is not coping with the development and has not yet been completed. Even though unlined open drainage channels and ditches are provided along the district roads, these are frequently intermittent and lack of discharge capacity, especially at the culvert openings under the road. Furthermore, in Brgy. Punta located in the coastal drainage area, there is no proper drainage outlet.

To assess the existing drainage systems, the discharge capacities of the Lotao and City Proper creeks functioning as primary drainage channels in the urban area is calculated as shown below, and Table 2.3 and Fig. 2.9 show hydraulic features of the primary channels.

Item No.	Primary Drainage Channel	Drainage Area (km ²)	Drainage Capacity (m ³ /s)	
			Range	Average
1.	Lotao Creek			
	- Downstream	1.03	1 - 10	10
	- Upstream	0.44	0.5 - 1	1
2.	City Proper Creek	0.32	1 - 18	4

2.4 Tacloban City

The drainage area of Tacloban City covering 22.95 km² in total is divided into ten (10) hydrologically independent drainage areas where stormwaters are drained directly to the sea through traversing rivers, primary drainage channels, and mains. The independent drainage areas are delineated in Fig. 2.10 and indicated as follows:

No.	Drainage Basin	Area (km ²)
SB-1	Abucay River	2.38
SB-2	Naga-Naga Creek	1.21
SB-3	Naga-Naga Coastal	0.31
SB-4	Mangonbangon River	5.12
SB-5	City Proper	1.26
SB-6	Langhas-Lirang Creek	4.38
SB-7	Sagkahan Creek	0.14
SB-8	Pleasantville Creek	1.25
SB-9	Burayan Tributary	1.41
SB-10	Burayan River	5.49
Total		22.95

The existing urban stormwater collection and drainage system is found only in the most densely built-up area being the city commercial center which is bounded on the West by Mangonbangon river and on the south by the Langhas-Lirang Creek, as shown in Fig. 2.11. The rest of the urban area depends largely on natural overland drain to the nearest recipients of the watercourses and the sea.

The existing pipe drainage systems in the city proper were constructed in 1975 based on the drainage master plan in 1954 by the City Engineering Office. The total length of drainage pipe is nearly 5.3 km and open channel is 2.4 km. Reinforced concrete pipes ranging in size from 400 mm to 1,400 mm and open channels are commonly used as drainage systems.

Due to inadequate drainage capacity as well as the confined coverage of the drainage system, the urban area suffers from frequent inundation. As shown in the table below, the drainage capacities of primary channels, where five (5) major inundation areas are located, are obviously small compared to the expected design discharges. Table 2.4 and Fig. 2.12 show hydraulic features of the primary channels.

No.	Primary Drainage Channel	Drainage Area (km ²)	Drainage Capacity (m ³ /s)	
			Range	Average
1.	Naga-Naga Creek	1.21	1 - 4	2
2.	Langhas-Lirang Creek	4.38	1 - 9	3
3.	Pleasantville Creek	1.25	1 - 10	1
4.	Sagkahan Creek	0.14	0.4 - 10	1
5.	Burayan Tributary	1.41	0.1 - 2	2

To solve inundation problems, the Tacloban City Drainage Master Plan prepared in 1987 proposed the improvement of the watercourses and construction of drainage mains. Due to budgetary constraints, however, only some drainage pipe improvement works were implemented up to present.

3. DRAINAGE INUNDATION PROBLEMS

3.1 Iloilo City

The flood-prone areas in the urban area of Iloilo City experience regular inundation brought about by the inadequate drainage systems. The DPWH District Engineering Office has identified the habitual inundation areas at some 11 places with 100 ha in total area as shown in Table 3.1 and Fig. 3.1. The major inundation areas and conditions are listed as follows:

Location of Inundation	Inundation Condition			
	Area (ha)	Depth (m)	Duration (hours)	Frequency (times/yr)
(1) City Proper-Molo (5 places)	53.8	0.1 - 0.3	1 - 2	3 - 5
(2) Jaro-Lapaz (4 places)	18.6	0.2 - 0.3	2	5
(3) Ingore Creek Upstream (2 places)	42.4	0.3 - 1.0	2 - 12	2
Total	114.8	-	-	-

(1) City Proper Inundation Area

The area is fully urbanized, and has a well-developed stormwater collection and drainage system. However, frequent inundations still occur in various places, i.e., Gen. Hughes Street, J.M. Basa Street, Rizal Street, De Leon Street, Fuentes Street, Gen. Juan Luna Street, Timawa Avenue, etc. Major causes of these problems are various degrees of structural damage and clogging of underground facilities brought about by unconventional production and constructional practices. This was substantiated during site reconnaissance by inspecting the water levels in the manholes on a drainage line, i.e., completely clogged condition was evident from an upstream manhole filled with water while an adjacent downstream manhole had no water at all. In addition, tide effects reduce drainage capacity in many parts of the city proper.

(2) Jaro-La Paz Inundation Area

The area is situated between the Dugon Creek and Jaro main stream. Inundation is most severe at Samuel Area, Commission Civil Street and Huervana Street. The side channel flow along the streets is obstructed by heavy sedimentation and encroachment of private passages, especially at Lopez Jaena Street in Samuel Area, where open drainage channels are constructed.

Inundations along Commission Civil St. and Burgos St. are caused by the long outlet to Bo. Obrero Creek. The railway was closed in 1980's, and Bo. Obrero Creek was then connected to Burgos Street along the north side of the railway. At present, the upstream stretch of Bo. Obrero Creek between Arroyo and J. Avel streets are filled with soil and garbage and the stormwater is diverted by extending the drainage pipeline with a limited capacity through Arroyo Street to the creek.

In the inundation area along Huervana Street adjoining the La Paz Public Market, there are two primary drainage channels: Rizal Creek draining to Iloilo River and Bo. Obrero Creek to the Iloilo Strait. Due to the sedimentation and wastes, encroachment of squatter's shanties and private passages, frequent inundations