

4.4 Facility Requirement Establishment

Based on the air traffic demand forecasted in the Chapter 4.2, the planning requirements of each airport facility are determined in accordance with the procedure shown in Fig. 4.4 1. Summary of the facility requirements by airport and phase of development is given in Tables 4.4.18.




Fig. 4.4.1 Procedures of Facility Requirement Establishment

4.5 Master Plan for Long-Term Development of Priority Airports

4.5.1 General

Master planning of the priority airports will be made in the following sequence:

(1) Phasing of Development Plan

The target year of the master plan for each airport is 2020, and its development is planned to be implemented by the following 4 stages:

- **First Stage** **Present** - **2005**
- **Second Stage** **2006** - **2010**
- **Third Stage** **2011** - **2015**
- **Fourth Stage** **2016** - **2020**

(2) Priority Airports

The purpose of the Study is to prepare master plans of Class I and II airports for long-term development, and to select high priority projects for the subsequent Pre-Feasibility Study for short-term development.

Furthermore, recommendations on the modernization plan for long-term development of air transport system in Uzbekistan is another object of the Study. This is why master plan for Class III airports is also prepared in the Study.

(3) Coordination with Suspended Projects

There are several projects that were planned before and after the independence of Uzbekistan, and suspended thereafter.

These previous projects shall be incorporated into the master plan taking into account the facility requirements of the respective airports.

As to the modernization project for the three local airports, namely, Samarkand, Bukhara and Urgench, now progressing up to the development target year of 2005, the plans for these airports are to be included in the master plans, but their costs shall not be included in the cost estimate.

4.5.2 Development of Metropolitan Airport

(1) Facility Requirements of Metropolitan Airport

Runway extensions and domestic passenger terminal building will be required, in order to serve the large western-made aircraft such as the B-747, and to meet the air traffic demand of 2010, providing that the existing Tashkent airport will continue to operate after 2010.

However, continuous operation up to the year 2020 of the existing airport is expected to lead the following problems:

a) Impact of Aircraft Noise

The present approach and departure courses are crossing over the southern part of Tashkent city, therefore, the impact of aircraft noise will expand to a larger area of the

city in the future.

b) Interference of Development of Tashkent City

According to the long-term Tashkent city development plan up to 2015, the urban area is planned to expand largely to the east and south of the city. Consequently, the existing Tashkent airport will be surrounded by an urbanized area so that the existence of the airport is expected to hamper the regular development of the city.

c) Geographical Difficulty in Expansion of Tashkent Airport

On the east side of the runway, there is a river and the residential area extends to the banks of this river. The west side of the runway is also surrounded by a river and a residential area. Consequently, it is extremely difficult to extend the runway in both directions to meet the requirements for the operation of large aircraft such as B-747, from the economical and social aspects.

(2) Development Plan of Metropolitan Airport

Judging from the above circumstances, in the long-term development plan of airports for the Capital, construction of a new metropolitan airport is considered as an alternative solution.

Therefore, a long-term development plan for the metropolitan airport is studied in the following two cases:

Case 1: Development Plan of the Existing Airport

Case 2: Construction of New Airport

• Existing Tashkent Airport Development Plan (Case-1)

At a maximum degree, the existing airport facilities will be used with necessary rehabilitation and improvements, except runway extension. Maximum design aircraft is to be B767. Development of the existing airport is planned as shown in Table 4.5.8, and the general plan for 2020 is shown in Fig. 4.5.3.

Table 4.5.8 Development Plan of Existing Tashkent Airport

Item		Existing	1 st stage (-2005)	2 nd stage (2006-2010)	3 rd stage (2011-2015)	4 th stage (2016-2020)
Demand	Passenger ('000)	1,750	2,500	3,100	3,800	4,700
	Max. Aircraft	IL86(medium-Jet)	IL86/B767(Medium Jet)			
Development	Airfield	Runway	4000m	○ Full Parallel		
		Taxiway	Partial	○ TWY Improvement		○ RWY/TWY/APR overlay
	Pavement		○ Apron Improvement			
	Terminal	Pax. Bldg.		○ Rehabilitation (International passenger building) ○ Rehabilitation (Dom. Int.) ○ Expansion (Domestic passenger building)		
Air-Nav			○ VOR/DME, ASDE		○ Renewal	
Remark			○ Weather Radar		FANS ○	

• **New Tashkent Airport Development Plan (Case-2)**

As shown in Fig. 4.5.4, the location of the possible site, selected by NAC, for construction of the new airport is an area situated 40 km southwest of Tashkent city, near Almazar village in Chinaz, and between the state road M-39 and railway lines.

Development of the new airport is planned to be implemented in 2 phases. The First Phase will be to develop an airport serving international and CIS flights, and the Second Phase will include the facilities for domestic flights, as shown in Table 4.5.10. The general development plan for the year 2020 is shown in Fig. 4.5.5.

Fig.4.5.4 Location of New Tashkent Airport Site




Table 4.5.10 Development of New Tashkent Airport (Class I)

Item		1 st stage (-2005)	2 nd stage (2006-2010)	3 rd stage (2011-2015)	4 th stage (2016-2020)
Demand	Passenger ('000)		2,000	3,800	4,700
	Max. Aircraft		-> (Int'l/CIS) ->(Int'l/CIS/Dom.) ○ B747(Large-Jet)		
Development	Airfield	Runway	Phase I ○ 4,300m		
		Taxiway	Phase I ○ Full Parallel		
	Terminal	Apron	Phase I ○ International & CIS Apron ○ Domestic Apron		
		Pax. Bldg.	Phase I ○ Int. bldg. ○ Phase II Dom. Bldg		
Air-Nav		○ Cat-II ILS, VOR/DME, ASR/SSR ○ ATC, Met, Airfield Lighting FANS ○			





Fig. 4.5.3 Tashkent Airport Development Plan (2020)

Facilities	Existing Facilities	1 st stage (2006)	2 nd stage (2006-2016)	3 rd stage (2011-2015)	4 th stage (2016-2020)
Airfield	Runway Taxiway Perimeter	Full Perimeter			
Terminal		<input type="checkbox"/> TMY Improvement <input type="checkbox"/> Apron Improvement <input type="checkbox"/> Rehabilitation (In-terminal passenger building) <input type="checkbox"/> Expansion (Terminal passenger building)			
Air Navigation		<input type="checkbox"/> VOKZARI, ASIDE <input type="checkbox"/> Winter Kabin			PASS <input type="checkbox"/>

TERMINAL AREA	
1	Intl Passenger Terminal Building
2	Dom. Passenger Terminal Building
3	VIP Building
4	Control Tower and Operation
5	Car Park
6	Cargo Handling Area
7	Administration Area
8	Fuel Tank Farm
9	Fire Station
10	Aircraft Maintenance Area
11	Aircraft Maintenance Office

AIRPORT DATA	
Airport Name	Tashkent
Class	I
Province	Tashkent
Main City	Tashkent
Distance from city	6km south
Reference Point	N 41° 15' 24"
Coordinates	E 69° 07' 10" 24"
Airport Name	Tashkent
Elevation	431m
Reference Temperature	29°C
Runway	4000m x 60m
Direction (True north)	1800m x 60m
Instrument Runway	N 82° E
I.L.S. Category	08L/08R/26R
CAT-II	

The Republic of Uzbekistan	
National Air Company "Uzbekistan Havo Yullari"	
The Study for The Air Transportation Development in The Republic of Uzbekistan	
Airport	Tashkent Airport
Drawing Title	Airport Layout Plan (Year 2020)
Date	Scale



Item	Passenger (2040)	Passenger (2040)	Passenger (2040)	Passenger (2040)	Passenger (2040)
Passenger (2040)	1,000,000	1,000,000	1,000,000	1,000,000	1,000,000
Runway	3,000m x 60m	3,000m x 60m	3,000m x 60m	3,000m x 60m	3,000m x 60m
Taxiway	100m x 100m	100m x 100m	100m x 100m	100m x 100m	100m x 100m
Apron	100m x 100m	100m x 100m	100m x 100m	100m x 100m	100m x 100m
Terminal	100m x 100m	100m x 100m	100m x 100m	100m x 100m	100m x 100m
APN No.	100m x 100m	100m x 100m	100m x 100m	100m x 100m	100m x 100m

Fig. 4.5.5 New Tashkent Airport Development Plan (2020)

TERMINAL AREA		AIRPORT DATA	
1	International Passenger Terminal Bldg.	Airport Name	New Tashkent
2	Domestic Passenger Terminal Bldg.	Class	1
3	International Cargo Terminal Bldg.	Province	Tashkent
4	Domestic Cargo Terminal Bldg.	Min. City	Tashkent
5	Operation and Control Tower	Distance from city	40km southeast
6	Power Station	Reference Point	40km southeast
7	Fire and Rescue Station	Coordinates	43°00'N 66°00'E
8	Fuel Tank Farm	Elevation	(350m)
9	Hanger	Reference Temperature	-
10	International Car Park	Runway	4300m x 60m
11	Domestic Car Park	Direction (True north)	-
12	Access Road	Instrument Runway	-
13	Dormitory, Operation Center etc	U.S. Category	CA-T-11

The Republic of Uzbekistan
 National Air Company "Uzbekistan Havo Yullari"
 The Study for The Air Transportation Development
 in The Republic of Uzbekistan
 Airport: New Tashkent Airport
 Drawing Title: Airport Layout Plan (Year 2020)
 Scale: 1:1000

4.5.3 Local Airports Development Plan

The existing facilities of the other eleven (11) local airports need to be upgraded as follows.

(1) Extension or Relocation of Runway

Following airports require runway extension and bituminous overlay of the runway pavement in order to cater for larger aircraft:

- class II airports;
Namangan and Fergana,
- class III airports;
Andizhan, Kokand, Karshi and Navoi.

Runway should be widened at Termez and Karshi to meet international standard of ICAO.

(2) Taxiway Improvement

Taxiway should be widened and shoulder should be provided at the ten (10) airports in accordance with ICAO standards.

(3) Apron Extension and Improvement

Apron of the eleven (11) airports should be extended and pavement be strengthened to accommodate larger and more frequent aircraft operation.

(4) Passenger Terminal Building

Passenger terminal buildings of the eleven (11) airports should be expanded as necessary to accommodate future passenger demand.

(5) Other Facilities

Administration buildings and control tower, etc. should be expanded or constructed as necessary to cater for future demand.

(6) Air Navigation Aids

Air navigation aids should be installed or renewed in accordance with development criteria based on the classification of the airports.





Fig. 4.5.6 Namangan Airport Development Plan (2020)

Facilities	Existing Facilities	1 st stage (+2005)	2 nd stage (2006-2010) / (2011-2015)	3 rd stage (2016-2020)	4 th stage (2021-2025)
Runway	3,270m		○ New Runway 3300m		
Taxiway	Partial Parallel		○ Expansion		○ Full Parallel
Apron			○ Existing (TAV& Apron)		
Pavement			○ for (NAS)		○ Expansion (Den)
Terminal	Ins. Bldg.		○ for ILS, ANSAS, VOR/DME		
Air Navigation			○ ATC, Mts, Airfield Lighting		○ ILS

TERMINAL AREA	
1	Passenger Terminal Building
2	VIP building
3	Cargo Storage (under construction)
4	Control Tower
5	Administration Building
6	Storage and Garage Area
7	Fuel Farm
8	Car Park

AIRPORT DATA	
Airport Name	Namangan
Class	II
Province	Namangan
Main City	Namangan
Distance from city	8km south-west
Reference Point	N 40° 58' 05"
Coordinates	1071° 33' 27"
Elevation	515m
Reference Temperature	New Runway
New Runway	3300m
(Existing)	(3000m)
Direction (True north)	N 112° 33' E
Instrument Runway	28
U.S. Category	CAT-I

The Republic of Uzbekistan	
National Air Company "Uzbekistan Havo Yullari"	
The Study for The Air Transportation Development in The Republic of Uzbekistan	
Airport	Namangan Airport
Drawing Title	Airport Layout Plan (Year 2020)
Date	Scale



Facilities	Existing Facilities	1st Stage (2005)	2nd Stage (2011-2015)	3rd Stage (2016-2020)	4th Stage (2021-2025)
Runways	1, 2	3	4	5	6
Taxiways	1, 2	3	4	5	6
Terminal	1	2	3	4	5
Air Navigation	1	2	3	4	5

Fig. 4.5.9 Kokand Airport Development Plan (2020)

The Republic of Uzbekistan	
National Air Company "Uzbekistan Havoy Yullari"	
The Study for The Air Transportation Development in The Republic of Uzbekistan	
Airport	Kokand Airport
Drawing Title	Airport Layout Plan (Year 2020)
Date	Scale

AIRPORT DATA	
Airport Name	Kokand
Class	III
Province	Fergana
Main City	Kokand
Distance from city	4km south
Reference Point	N 40° 26'
Coordinates	E 007° 59'
Elevation	500m
Reference Temperature	20°C
Runway	2200m
(Existing)	(1600m)
Direction (True north)	N 73° 11'
Main Runway	25
I.I.S. Category	-

TERMINAL AREA	
1 Passenger Terminal Building	6 Boiler Building
2 VIP Building	9 Club House
3 Cargo Storage	10 Hangar
4 Administration Building	11 Fuel Farm
5 Fire Station	12 Dormitory
6 Garage	
7 Storage	




Fig. 4.5.10 Samarkand Airport Development Plan (2020)

Year	1st Stage (2005-2010)	2nd Stage (2011-2015)	3rd Stage (2016-2020)	4th Stage (2021-2025)
Planning
Design
Construction
Operation

AIRPORT DATA	
Airport Name	Samarkand
Class	II
Province	Samarkand
Main City	Samarkand
Distance from city	8 km north
Reference Point	N 39° 42' 06"
Coordinates	E 066° 59' 06"
Elevation	678m
Reference Temperature	36°C
Runway	31000m
(Existing)	(31000m)
Direction (True north)	N 99° 34' E
Instrument Runway	09
I.L.S. Category	CAT-3

The Republic of Uzbekistan	
National Air Company "Uzbekistan Havo Yullari"	
The Study for The Air Transportation Development in The Republic of Uzbekistan	
Airport	Samarkand Airport
Drawing Title	Airport Layout Plan (Year 2020)
Date	Scale





Fig. 4.5.11 Termez Airport Development Plan (2020)

Particular	1st Stage (2005)	2nd Stage (2005-2010)	3rd Stage (2011-2015)	4th Stage (2016-2020)
Runways				Shakhsay
Taxiways				Shakhsay
Aprons				Shakhsay
Terminal				Over the RW (2011)
Air Navigation				Expanding (2011)
Air Services				Expanding (2011)
Air Security				Expanding (2011)
Air Safety				Expanding (2011)
Air Quality				Expanding (2011)
Air Noise				Expanding (2011)
Air Pollution				Expanding (2011)
Air Climate				Expanding (2011)
Air Health				Expanding (2011)
Air Safety				Expanding (2011)
Air Security				Expanding (2011)
Air Services				Expanding (2011)
Air Navigation				Expanding (2011)
Air Quality				Expanding (2011)
Air Noise				Expanding (2011)
Air Pollution				Expanding (2011)
Air Climate				Expanding (2011)
Air Health				Expanding (2011)

AIRPORT DATA	
Airport Name	Termez
Class	II
Province	Sikhindirlik
Main City	Termez
Distance from city	9km
Reference Point	N 37° 17' 11" E
Coordinates	E066° 18' 33"
Elevation	313m
Runway	3000 (2000)
Direction (True north)	N 74° 09' E
Instrument Runway	25
I.L.S. Category	CA/I-I

TERMINAL AREA	
Passenger Terminal Building	7
Control Tower	Canteen
VIP Building	
Fire Station	
Garage	
Satrage	
Hanger	

The Republic of Uzbekistan	
National Air Company "Uzbekistan Havo Yullari"	
The Study for The Air Transportation Development in The Republic of Uzbekistan	
Airport	Termez Airport
Drawing Title	Airport Layout Plan (Year 2020)
Date	Scale




Country	Uzbekistan	2nd Stage	2025	4th Stage	2030
Region	Kashkadarya	1st Stage	2020	3rd Stage	2025
City	Karshi	2nd Stage	2025	4th Stage	2030
Coordinates	39° 48' N, 68° 48' E	3rd Stage	2025	5th Stage	2035
Area	1000 ha	4th Stage	2030	6th Stage	2035
Investment	100 million USD	5th Stage	2035	7th Stage	2040
AP Number	1000	6th Stage	2035	8th Stage	2040
AP Name	Karshi Airport	7th Stage	2035	9th Stage	2045
AP Code	KSI	8th Stage	2035	10th Stage	2050
AP Status	Active	9th Stage	2035	11th Stage	2055
AP Type	International	10th Stage	2035	12th Stage	2060
AP Category	Class C	11th Stage	2035	13th Stage	2065
AP Sub-category	Category 1	12th Stage	2035	14th Stage	2070
AP Sub-code	1000	13th Stage	2035	15th Stage	2075
AP Sub-name	Karshi Airport	14th Stage	2035	16th Stage	2080
AP Sub-code	1000	15th Stage	2035	17th Stage	2085
AP Sub-name	Karshi Airport	16th Stage	2035	18th Stage	2090
AP Sub-code	1000	17th Stage	2035	19th Stage	2095
AP Sub-name	Karshi Airport	18th Stage	2035	20th Stage	2100

Fig. 4.5.13 Karshi Airport Development Plan (2020)

The Republic of Uzbekistan	
National Air Company "Uzbekistan Havo Yullari"	
The Study for The Air Transportation Development in The Republic of Uzbekistan	
Airport	Karshi Airport
Drawing Title	Airport Layout Plan (Year 2020)
Date	Scale

AIRPORT DATA	
Airport Name	Karshi
Class	III
Province	Kashkadarya
Main City	Karshi
Distance from city	5 km north
Reference Point	N 39° 48'
Coordinates	106° 58' 46"
Elevation	374m
Reference Temperature	-
Runway	3000m x 50m
Direction (true north)	(2920m x 42m)
Miles Runway	N 167° 47' E
U.S. Category	16

TERMINAL AREA	
1	Passenger Terminal Building
2	VIP Building
3	Operation Administration Building and Control Tower
4	Storage
5	Fire Station
6	Garage
7	Fuel Farm
8	Hanger




Facilities	Existing Facilities	1st Stage (2006-2010)	2nd Stage (2011-2015)	3rd Stage (2016-2020)
Runway	1,000 m	<input checked="" type="checkbox"/> 3,160 m		
Taxiway	No Parallel	<input type="checkbox"/> Parallel	<input type="checkbox"/> Expansion	
Terminal		<input type="checkbox"/> Expansion	<input type="checkbox"/> Expansion	<input type="checkbox"/> Expansion
Air Navigation		<input type="checkbox"/> VOR/DME	<input type="checkbox"/> VOR/DME	<input type="checkbox"/> ILS

Fig. 4.5.15 Bukhara Airport Development Plan (2020)

AIRPORT DATA	
Airport Name	Bukhara
Country	Uzbekistan
Province	Bukhara
Main City	Bukhara
Distance from city	7 km
Reference Point	N 39° 46' 30"
Coordinates	E 66° 28' 48"
Elevation	229m
Reference Temperature	35°C
Runway	3000x60x5m
(Width)	(3000x60x5m)
Direction (True north)	N 15° E
Instrument Runway	01
I.S. Category	CAT-I

TERMINAL AREA	
1 Passenger Terminal Bldg.	0 Administration Building
2 Existing Passenger Terminal Bldg.	9 Car Park
3 Cargo Bldg.	
4 Control Tower and Operation	
5 Existing Control Tower and Operation	
6 Fire Station	
7 Refueling Station	

The Republic of Uzbekistan	
National Air Company "Uzbekistan Havo Yullari"	
The Study for The Air Transportation Development in The Republic of Uzbekistan	
Airport	Bukhara Airport
Drawing Title	Airport Layout Plan (Year 2020)
Date	Scale



Facilities	Existing Possibilities	1st Stage (2016-2018)	2nd Stage (2018-2020)	3rd Stage (2020-2025)	4th Stage (2025-2030)
Airfield	Runway	1,110 m	2,100 m	3,100 m	3,100 m
	Taxiway	Not Parallel	Not Parallel	Not Parallel	Not Parallel
	Terminal	Not Parallel	Not Parallel	Not Parallel	Not Parallel
	Passenger	Not Parallel	Not Parallel	Not Parallel	Not Parallel
	Ops. Bldg.	Not Parallel	Not Parallel	Not Parallel	Not Parallel
Terminal					
Air Navigation					

Fig. 4.5.16 Navoi Airport Development Plan (2020)

TERMINAL AREA		AIRPORT DATA	
1	Passenger Terminal Building	Airport Name	Navoi
2	Operation and Control Tower	Class	III
3	Administration Building	Province	Navoi
4	Fire Station	Main City	Navoi
5	Storage	Distance from city	25 km southwest
6	Fuel Farm	Reference Point	N 40° 07'
7	Utilities Farm	Coordinates	13665° 12'
		Runway	3100m x 45m
		Direction (True north)	N 82° 25' E
		Main Runway	25
		US Category	-
		Elevation	417m
		Reference Temperature	-

The Republic of Uzbekistan
 National Air Company "Uzbekistan Airways Yullari"
 The Study for The Air Transportation Development
 in The Republic of Uzbekistan
 Airport Navoi Airport
 Drawing Title Airport Layout Plan (Year 2020)
 Date _____ Scale _____




Fig. 4.5.17 Urgench Airport Development Plan (2020)

The Republic of Uzbekistan National Air Company "Uzbekistan Hayo Yullari"	
The Study for The Air Transportation Development in The Republic of Uzbekistan	
Airport	Urgench Airport
Drawing Title	Airport Layout Plan (Year 2020)
Date	Scale

AIRPORT DATA	
Airport Name	Urgench
Class	II
Province	Khorezm
Main City	Urgench
Distance from city	3km east
Reference Point	N 41° 34' 30"
Coordinates	50° 04' 30" E
Elevation	97m
Reference Temperature	3000mm±5m (1000mm±4m)
Runway (Existing)	N 143° 20' E
Instrument Runway	31
U.S. Category	CAT-I

Facilities	1st Stage (1-2005)	2nd Stage (2006-2010)	3rd Stage (2011-2015)	4th Stage (2016-2020)
Runway				
Taxiway				
Apron				
Terminal				
Pass. Bldg.				
Air Navigation				
Partial Parallel				
Expansion				
Renewal				
Partial Parallel				
Expansion				
Renewal				
Partial Parallel				
Expansion				
Renewal				




Fig. 4.5.18 Nukus Airport Development Plan (2020)

Facilities	Existing Facilities	1st Stage (2016-2018)	2nd Stage (2018-2020)	3rd Stage (2020-2025)	4th Stage (2025-2030)
Runway	1800x30 (1800x30)	2400x45 (2400x45)	3000x60 (3000x60)	3600x90 (3600x90)	4200x120 (4200x120)
Taxiway	100x30 (100x30)	150x45 (150x45)	200x60 (200x60)	250x75 (250x75)	300x90 (300x90)
Terminal	1000sqm	2000sqm	4000sqm	8000sqm	16000sqm
Air Navigation	100sqm	200sqm	400sqm	800sqm	1600sqm

TERMINAL AREA	
1	Passenger Terminal Building
2	VIP Building
3	Cargo Storage
4	Administration Building
5	Control Tower
6	Fire Station
7	Cargo Storage
8	Fuel Tank Farm
9	Aircraft Maintenance
10	Car Park

AIRPORT DATA	
Airport Name	Nukus II
Class	II
Province	Karakalpakstan
Main City	Nukus
Distance from city	7km southwest
Reference Point	N 42° 29' 18" E
Coordinates	49° 37' 24" E
Elevation	76m
Reference Temperature	3000hms/8h
Runway	(Existing) 3000hms/8h
Direction (True north)	N 159° 31' E
Instrument Runway	18
ILS Category	CAT-I

The Republic of Uzbekistan	
National Air Company "Uzbekistan Havo Yullari"	
The Study for The Air Transportation Development in The Republic of Uzbekistan	
Airport	Nukus Airport
Drawing Title	Airport Layout Plan (Year 2020)
Date	Scale

4.6 Development Plan for Air Navigation System

4.6.1 General

Air route structure in Uzbekistan mainly comprises four (4) VOR/DMEs and twenty (20) NDBs. ASR/SSRs are also installed at ten (10) local airports as well as Tashkent airport, for approach and en-route control.

A major part of these facilities were installed in the 1980s, and if their life is assumed to be about 15 years, they will reach the end of their useful life within the 1st Stage. Therefore, replacement of these facilities shall be taken into account for the development planning of the air navigation facilities.

On the other hand, Future Air Navigation System (FANS) discussed by ICAO and other countries, is expected to be realized in the future air navigation system, in place of the present system. During the long-term development of the air navigation systems, introduction of FANS shall be incorporated into the development plan.

4.6.2 Development Criteria

(1) Air Navigation Facilities by Category of Airports

Development of air navigation facilities is planned based on the criteria shown in Table 4.6.2.

Table 4.6.2 Air Navigation Facilities by Category of Airports

Airport	ILS	VOR/DME	ASR/SSR	NDB	AFTN	Control Tower	Airfield Lighting	Met. Facilities
Class I	Cat-II	Yes	Yes	Yes	Yes	Yes	Cat-II	Cat-II
Class II	Cat-I	Yes	Yes	Yes	Yes	Yes	Cat-I	Cat-I
Class III	No	Yes	No	Yes	Yes	Yes	Non-Precision (for night use)	Minimum

(2) Priority of Development

Priority for improvement and modernization of the air navigation system shall be based on the following factors:

- Replacement of existing facilities that are more than 15 years old
- Renewal and improvement by airport class from Class I and II
- Introduction of Medium and Large Jets

4.6.3 Facility Planning at Airports

Based on the above criteria, facility planning of air navigation systems at each airport is summarized as shown in Table 4.6.3.

Table 4.6.3 Development of Each Airport (1)

ITEM	Tashkent		New Tashkent		Nuratau		Andizhan		Fergana		Kokand	
	-2005' -2010'	-2015' -2020'	-2005' -2010'	-2015' -2020'	-2005' -2010'	-2015' -2020'	-2005' -2010'	-2015' -2020'	-2005' -2010'	-2015' -2020'	-2005' -2010'	-2015' -2020'
(1) Radio Nav aids												
a) ILS		○	●		○				●			
b) Locator		○	●		○		●		●			○
c) VOR/DME		○	●		●		●		●			●
(2) ATC System and Telecommunication												
a) Control Tower Facilities		○	●		○		●		●			○
b) ASR/SSR		○	●		○		○		●			
c) TRDPS		○	●		○		○		●			
d) AFTN		○	●		○		○		○			○
e) ASDE		○	●									
(3) Airfield Lighting System												
a) PALS		○	●		○				●			
b) SALS		○	●		○		●		●			●
c) PAPI		○	●		○		○		●			●
d) REDL		○	●		○		○		●			●
e) RTHL		○	●		○		○		●			●
f) TWEL		○	●		○		○		●			●
g) AFL		○	●		○		○		●			●
h) Aerodrome Beacon		○	●		○		○		●			●
i) Power supply system for Nav aids		○	●		○		○		●			●
(4) Meteorological Observation System												
a) Wind direction and speed sensor		○	●		○		○		○			○
b) Air temperature and humidity sensor		○	●		○		○		○			○
c) Barometer		○	●		○		○		○			○
d) RVR and Ceilometer		○	●		○		○		○			○
e) Data Collection and Processing System		○	●		○		○		○			○
f) Weather Data Monitor		○	●		○		○		○			○
g) Forecast equipment		○	●		○		○		○			○
h) Weather Radar		○	●		○		○		○			○
(5) FANS		○	●		○		○		○			○

○ Renewal of existing facilities (equipment)

● Installation of new facilities (equipment)

Table 4.6.3 Development of Each Airport (2)

ITEM	Sumar Kand/Bukhara		Urgench		Termez		Karehi		Navoi		Nukous	
	-2005	-2010	-2015	-2020	-2005	-2010	-2015	-2020	-2005	-2010	-2015	-2020
(1) Radio Nav aids												
a) ILS												
b) Locator												
c) VOR/DME	●											
(2) ATC System and Telecommunication												
a) Control Tower Facilities												
b) ASR/SSR												
c) TRDPS												
d) AFTN												
e) ASDE												
(3) Airfield Lighting System												
a) PALS												
b) SALS												
c) PAPI												
d) REDL												
e) RTHL												
f) TWEL												
g) AFL												
h) Aerodrome Beacon												
i) Power supply system for Nav aids												
(4) Meteorological Observation System												
a) Wind direction and speed sensor												
b) Air temperature and humidity sensor												
c) Barometer												
d) RVR and Ceilometer												
e) Data Collection and Processing System												
f) Weather Data Monitor												
g) Forecast equipment												
(5) FANS												

○ Renewal of existing facilities (equipment)

● Installation of new facilities (equipment)

4.6.4 Development Plan of Nationwide Air Navigation System

(1) Present Situation of Air Route System

Air routes in Uzbekistan mainly comprises of four (4) VOR/DMEs and twenty (20) NDBs, which are installed at the airports and other than airports, as shown in Fig. 4.6.1. Present air routes are concentrated at the areas of Tashkent, Samarkand and on the borders. Installation year of those equipment is shown in Table 4.6.4.

Functions of the en-route navigational aids importantly are summarized as follows:

Tamdybulak (VOR/DME), Karakhtay (NDB), Makhtaly (NDB), Toytepa (NDB), Dzhizak (NDB), Dalverzin (NDB), Syrdarya (NDB), Nurata (NDB), Bulungur (NDB), Nagornaya (NDB), Urgut (NDB), Guzar (NDB)

Table 4.6.4 Installation Year of En-route Navaids

Point	Year	Point	Year
VOR/DME		NDB	
Tamdybulak	1997	Syrdarya	1990
NDB		Nurata	1979
Karakhtay	1989	Bulungur	1988
Makhtaly	1993	Nagornaya	1982
Toytepa	1994	Urgut	1989
Dzhizak	1986	Guzar	1993
Dalverzin	1986		

(2) Development Plan

As abovementioned, en-route navaids in Uzbekistan mainly consist of NDBs. However, since NDB has disadvantages of radio wave interference, VOR/DME is commonly used as the en-route navaids precisely, and enable Region Navigation System(R-NAV).

Considering above situation, en-route navaids should be replaced by VOR/DME from the present NBD facilities. Development plan of en-route navaids is shown in Table 4.6.5 and location of en-route navaids and proposed air route network of 2020 is shown in Fig. 4.6.2.

Table 4.6.5 Development Plan of Nationwide Air Navigation System

Point	2005	2010	2015	2020
Tamdybulak			VOR/DME	
Karakhtay	VOR/DME			
Makhtaly		VOR/DME		
Toytepa		VOR/DME		
Dzhizak	VOR/DME			VOR/DME
Dalverzin	VOR/DME			VOR/DME
Syrdarya	VOR/DME			VOR/DME
Nurata	VOR/DME			VOR/DME
Bulungur	VOR/DME			VOR/DME
Nagornaya	VOR/DME			VOR/DME
Urgut	VOR/DME			VOR/DME
Guzar		VOR/DME		




Fig. 4.6.1 Air Route Network (1997)




Fig. 4.6.2 Air Route Network (2020)

4.6.5 Development of Future Air Navigation System (FANS)

(1) Global Navigation Satellite System (GNSS)

Future Air Navigation System (FANS), which is developed and proposed by ICAO, shall be incorporated into long-term development of the air navigation system.

The FANS concept, known as Communications, Navigation, Surveillance and Air Traffic Management (CNS/ATM), is based on the use of satellite technology for improved communications, point-to-point navigation, and surveillance in areas not to be covered with radar.

Main structure of the satellite concept is the Global Navigation Satellite System (GNSS). At this moment and for the immediate future, the only positioning constellations available as candidates for GNSS are the Global Positioning System (GPS), owned and managed by the United States of America, and the Global Orbiting Navigation Satellite System (GLONASS), owned by the Russian Federation Government.

(2) Proposed Function of FANS

a) Communication

Development target on communication function in FANS is to establish a data link between air and ground by using VHF and SSR mode S, and to provide Aeronautical mobile Satellite Service (AMSS). It is necessary to establish Aeronautical Telecommunication Network (ATN) using Satellite.

b) Navigation

Future navigation in the air route network is expected to be supported exclusively by GNSS in place of the present navigation using NDB and VOR/DME. Accordingly, aircraft will be able to select freely any flight courses and apply precision approach.

c) Surveillance

New system named Automatic Dependent Surveillance (ADS) is being studied. ADS is a new surveillance system in air space beyond radar coverage.

On the other hand, in air space within radar coverage, it will be possible to increase surveillance ability, and to improve communication method with aircraft using SSR mode S.

d) Air Traffic Management

In addition, the ultimate purpose of FANS is to achieve total management of air space and air traffic. This concept is called "Air Traffic Management (ATM)".

ATM consists of three procedures, namely, Air Traffic Control (ATC), Air Traffic Flow Management (ATFM), and Air Space Management (ASM), and its principal role is to manage and control air traffic in order to allow aircraft to operate safely and economically.

Table 4.6.6 Development of CNS System

Type of airspace	Current System			Proposed FANS		
	C	N	S	C	N	S
VHF voice HF voice	OMEGA/LORA N-C NDB VOR/DME Barometric altitude DMS/IRS	Primary radar/SSR Voice position reports	VHF voice/data AMSS data/voice HF over poles only (2)	RNAV/RNP/C, GNSS Barometric altitude High altitude GNSS altimeter (3) INS/TRS	ADS	
Continental airspace with high density traffic	VHF voice	OMEGA/LORAN-C NDB VOR/DME Barometric altitude DMS/IRS	Primary radar SSR mode A/C	VHF voice/data AMSS data/voice SSR mode S data link	RNAV/RNP/C GNSS Barometric altitude High altitude GNSS altimeter (3) VOR/DME (4) INS/TRS	SSR mode A/C or SSR mode S ADS
Oceanic airspace with high density traffic	HF voice	MNPS OMEGA/LORAN-C NDB VOR/DME Barometric altitude DMS/IRS	Voice position reports	AMSS data/voice	RNAV/RNP/C GNSS Barometric altitude High altitude GNSS altimeter (3) INS/TRS	ADS
Terminal areas with high density traffic	VHF voice	NDB VOR/DME ILS Barometric altitude DMS/IRS	Primary radar SSR mode A/C	VHF voice/data SSR mode S data link	RNAV/RNP/C GNSS MLS NDB (5) VOR/DME (4) Barometric altitude INS/TRS	SSR mode A/C or SSR mode S ADS (6)

Key:

- AMSS : aeronautical mobile-satellite service
- MNPS : minimum navigation performance specifications
- RNAV/RNP/C : area navigation/required navigation performance capability
- ADS : global navigation satellite system
- INS/TRS : internal navigation system/internal reference system

Notes:

- (1) : Include low-altitude, off-shore and remote areas.
- (2) : Until such time as satellite communication is available.
- (3) : To be used where barometric altimeter is not functional.
- (4) : VOR/DME will be progressively withdrawn.
- (5) : NDB will be progressively withdrawn.
- (6) : The need for primary radar is reduced.

4.7 Air Traffic Control Systems Development

4.7.1 General

The purpose of improvement of the ATC System is to enhance the safety and the capacity of air space use, so as to meet the expansion and variety of air traffic in the future, according to the airport development and the new establishment of air transportation network. It is important to cope with the modernized adjustment of Airport and Air Traffic System, on the basis of the adjustment of Air Transportation in the master plan, and the air traffic volume expected, and in particular to work towards an appropriate measure of compliance with the FANS of ICAO, by the ATC procedure and the information network and the appropriate establishment of Air Traffic Management(ATM).

4.7.2 Air Space Use Planning

(1) Planning Criteria

For this purpose, it is necessary to construct an integrated system of general control of air space use, instead of the current system, which is rather a priority for the military authority. This should be established in connection with the transfer to FANS and ATM. ATM is to be conducted generally for Air Traffic Control, Air Traffic Flow Management and Airspace Management and establishment of the appropriate system of conduct for it.

For the purpose of effective air space use, the coverage of surveillance of Radar on the ground shall be extended first. In the future, the usage of the whole air space shall be available technically as a result of the introduction of FANS. To be specific, an assessment of FIR and of the jurisdictional area of air space related to neighbouring countries, should be conducted and the establishment and promotion of a cooperative system of regional ATM should be examined.

(2) Development of Air Space Organization

- In the future, the appropriateness of controlled air space and the standardization of the ICAO for Obstacle Limitation Surfaces(OLS) and the flight procedures of instrument approach and departure, shall be conducted first as part of the short or medium term plan. Basically, the efficiency of air space shall be conducted gradually and the NDB Airways shall be changed to the VOR Airways by means of the replacement of significant NAVAIDS from NDB to VOR or VOR/DME.
- In the long term plan, the efficiency and effective usage of air space shall be assured with ICAO FANS/ATM. And the TMA(Terminal Control Areas) at some airports shall be combined and integrated to promote the efficiency of ATC services. The RNP(Required Navigation Performance) shall be introduced for Area(En-route) Control according to ICAO standards and be designated on the route of arrival and departure in the future.

(3) Upper Airspace and Airways

In the upper airspace, especially for international over-flights and the ATC provided, the practical service of FANS may take shape soon, and the efficient usage of air space shall be conducted according to the variety of flight routes by means of the R-NAV(Area Navigation). Corresponding to the introduction of FANS in the upper air space, the establishment of optional and efficient flight routes shall be possible. It is necessary to

adjust the system for providing efficient and flexible or dynamic routes according to weather and ATC conditions.

At present, the air space for civil air traffic is limited in the CTR(Control Zone), TMA(Terminal Control Area) and Airways, but it is necessary to ensure effective airspace control by the Area Control Services, except the restricted areas or the prohibited areas to be used for Radar Vector and others. In particular, it is important to provide for the efficient use of air space, given the coexistence of civil and military air traffic.

In the first stage, the R-NAV shall be conducted on the Area(En-route) control face by VOR/DME and in the future it shall be changed and conducted by the FANS, which are located around Tashkent airport(and new airport), the main airways of south – north(Termez VOR/DME – Tamdybulak VOR/DME), Samarkand airport, Bukhara airport and Nukus airport. The appropriateness of air traffic shall be planned at these locations which are the new territorial gateways of Uzbekistan for departure, arrival and over-flights. They connect to routes of Europe to South-east Asia, then the coordination should be necessary with the relevant authorities of other countries.

In particular, the establishment of a new international ATS route which connects the Fergana region and the eastern countries such as China shall be necessary soon. Also, a parallel south-north bound ATS route will be necessary, in relation to the efficiency of air transportation

(4) General Use of Air port space

For the airspace requirement of the 12 airports, it is first necessary to maintain the OLS appropriately. At the airport, all airfield obstacles should be removed as much as possible, except for some significant equipment for aircraft operating, especially the dispatch cabin(start control position) near the RWY end must be removed, which is found at some local airports, and the transmitter and receiver antenna and the apron flood lights, etc. shall be dealt with, without exception.

As for the controlled air space of an airport, it is proper that the CTR shall be designated and reconstructed on the basis of visual ATC. (Generally the shape of it appears cylindrical with a radius of 9.3km and about 900m in height.) The lower limit of the approach control area is about 200m in height above ground and also above the minimum safety height. And the lower limit of controlled air space out of the approach control area is generally 900m off above ground level.

In Uzbekistan, the CTR is designated as being 4500m in height above ground and an indefinite shape depending on the status of air traffic around the airport. Above this, the air space of Area control services is set within the FIR. The basic idea is the same as that of ICAO, but the altitude is so specific as to divide the air space vertically. As a result, there are some areas remaining out of the controlled air space and below 4500m in height.

It is proper that TRACON(Terminal Radar Approach Control) shall be established in the approach-controlled-areas of the airports Namangan, Andizhan, Fergana and Kokand, shall be combined over the Fergana area in the future. As for the approach procedures, the 3° GP of ILS approach shall be established instead of the current 2° 40' GP according to the standardization for ICAO. And the rule of OCA(H)(Obstacle

Clearance Altitude(Height)) for the ICAO precision segment shall be applied.

The precision approach is provided as Cat- I , with intermediate facilities of aeronautical lights at the majority of local airports, and the upper categories are not necessary to install, but only at important international airports such as Tashkent airport(new airport). The VOR/DME shall be installed at the airports in the future, comprising intermediate approach to assist for the ILS approach or, establish the VOR/DME approach(non-precision approach). In the future GNSS precision approach (Cat- I) might be established.

Proper noise abatement procedures for departure and approach(landing) must be established at all airports and adjusted according to the population density of the urban areas.

(5) Air Space Requirement at New Tashkent Airport

Air space condition of new Tashkent airport is better than existing Tashkent airport to be on plane area without terrain obstacle. Standard instrument departure procedure and instrument approach procedure will be proper to be established on any direction.

When both Tashkent airport and Tashkent new airport coexist, instrument flight procedures on either airport must be limited but keep efficiency with safe. It is proper that TRACON(Terminal Radar Approach Control) shall be established.

4.7.3 Air Traffic Control System Development

At the Air Traffic Control field, the improvements and functional advances of global operations systems shall be conducted, and since the adaptation to the integrated system on a world-wide scale is desirable, it is necessary to gradually adjust to this as ICAO develops in Uzbekistan, related to ATC, AIS, COM, SAR, MET, etc. shall be planned, being at the center of functional advance and performance of FANS/ATM.

Radar Data Processing System, Flight Data Processing System and RCAG(Remote Center Air-Ground Communication) or Control system of communication and data-link, etc. shall be introduced in a positive manner.

For the future, the total ATC center will most likely be established at the new Tashkent airport and it shall be the only facility using FANS and ATM(Air Traffic Control, Air Traffic Flow Management and Air Space Management) integration, including critical situation management for Air Traffic Services(ATS).

Finally, the regulation and practice procedures of ATC should be studied and applied to the ATS through adjustment of the technical conditions as SSR mode S, ACAS, VHS Data-link, ADS, MLS, GNSS, ILS(Cat-III) and R-NAV, etc..

4.7.4 Air Traffic Control Service Development

(1) Procedural Improvement

ATC Service Development shall be geared to the improvements of the airports. The increase in traffic volume and the global and regional trends at ICAO or other organizations, shall be taken into account. Especially cooperation with other CIS countries in the Central Asia region and the up-grade of ATC procedures corresponding to the enforcement of the ATC system should be necessary. It is also important to

conduct gradual improvements, on the basis of ATC operations and to establish the operational interface condition, between ATC equipment or system and controller's work.

- At the Aerodrome control, the ATC services, shall be established by visual control at the aircraft take-off or landing stage (Local control) and for local flight in the CTR, and the stage (Ground control) of maneuvering of aircraft or other vehicles on the ground.
- At the Approach Control and Area (En-route) Control, the provision of ATC services shall be conducted appropriately according to the improvements of the ATC equipment, Radar and Communication.
- Cooperation with the neighboring ATC authority to establish regional effective ATC procedure.

To meet the future increase in and variety of, air traffic volume, it is therefore appropriate to conduct these first improvement steps in the current ATC systems and it is wise in the long term, to introduce or make qualitative advances of ATC services, according to the development in new types of aircraft and the introduction of FANS, etc.. At first, it is necessary to establish the ATC procedures corresponding to the ADS (Automated Dependent Surveillance) which is expected to be introduced as well as R-NAV on the stage of Area (En-route) control level.

And the definite improvement or adjustment is considered necessary for practical reasons as follows:

- The system of conducting ATC services efficiently shall be established for introducing the appropriate shift-system.
- Visual ATC by flashing 'light-gun' signals should be established.
- The procedure of ATC without radar service should be established as ICAO standards.

(2) ATC Institution of Training

The training system for the modernized or advanced ATC such as FANS, should be established in the future. As the advanced western made ATC equipment is gradually introduced at the local airports, familiarity with or technical development of, Air Traffic Controller should be assured. Regarding the ATC of International over-flights, International arrivals or departures, controllers should communicate in English, and conduct the ATC of ICAO standards, and understand the performance of western made aircraft. So a proper organization of ATC services and the ATC training system should be established. In the future, the training center should be advanced and generalized with an integrated training system.

According to the development or improvement of ATC systems, the enforcement of the constitution of 'Uzaeronavigation' should be necessary with regard to the completion of the rating system of ATC services and controllers, the advance of air safety inspection related to the case of mistaken provision of ATC service, the appropriate management of personnel affairs, the efficient assignment of personnel, the effective technical transfer from Russian specialists to local (Uzbekistan) staff and the appointment of female staff, etc.

4.8 Cost and Implementation Plan of Projects

4.8.1 Preliminary Cost Estimates

The summary of cost estimates for the long-term development of the priority airports is shown in Table 4.8.1.

4.8.2 Implementation Plan

Table 4.8.3 presents a general schedule for implementing an airport project.

Project costs by stage is shown in Table 4.8.2. required amount for the 1st Stage up to 2005 is estimated roughly at US\$ 1,123 million, which is 40% of the total cost of the long-term development.

Table 4.8.2 Project Cost by Stages

(US\$ 1,000)					
Airport	I	II	III	IV	Total
[Airports]					
1. Tashkent	131,210	3,495	163,636	34,401	332,732
2. New Tashkent	156,593	439,650	172,818	21,980	791,041
3. Namangan	198,126	0	18,015	35,950	252,091
4. Andizhan (Extension)	83,708	6,206	30,019	16,223	136,156
5. Andizhan (New Runway)	125,028	6,206	30,300	16,223	177,757
6. Fergana	183,257	0	26,409	35,950	245,616
7. Kokand	3,128	0	28,512	966	32,606
8. Samarkand	1,934	61,532	33,050	2,900	99,416
9. Termez	89,622	15,830	36,036	35,852	177,340
10. Karshi	12,070	83,917	0	966	96,953
11. Bukhara	1,934	61,799	58,051	16,169	137,953
12. Navoi	40,365	0	77,952	966	119,283
13. Urgench	0	58,653	53,598	7,621	119,872
14. Nukus	96,665	22,459	9,212	49,620	177,956
[Nationwide Air Navigation System]	19,164	7,186	2,395	19,164	47,909
Total	1,142,804	766,933	740,003	294,951	2,944,681
	40%	27%	23%	10%	100%


Table 4.8.1 Preliminary Cost Estimates for Long-Term Development of Priority Airports

(USS 1,000)

Airport	1	2	3	4	5	6	7	8	9	10	11
	Airfield Facilities	Terminal Area Facilities	Air Navigation Facilities	Airport Special Equipment	Utilities	Project Administration Expenses	Compensation	Subtotal	Contingencies	Total	(%)
[Airports]											
1. Tashkent	48,118	104,451	96,477	7,580	30,212	45,894	0	332,732	33,273	366,005	11%
2. New Tashkent	285,615	259,868	42,491	5,264	78,406	80,597	38,800	791,041	79,104	870,145	27%
3. Namangan	93,185	46,125	61,149	647	13,283	34,302	3,400	252,091	25,209	277,300	9%
4. Andizhan (Extension)	24,960	46,849	27,144	832	17,591	18,780	0	136,156	13,616	149,772	5%
5. Andizhan (New Runway)	60,823	46,849	27,144	832	17,591	24,518	0	177,757	17,776	195,533	6%
6. Fergana	76,819	54,409	61,149	832	18,529	33,878	0	245,616	24,562	270,178	8%
7. Kokand	6,077	6,855	12,450	46	1,776	4,352	1,050	32,606	3,261	35,867	1%
8. Samarkand	11,886	29,865	32,658	601	10,694	13,712	0	99,416	9,942	109,358	3%
9. Termez	13,647	59,754	60,981	739	17,386	24,433	200	177,340	17,734	195,074	6%
10. Karshi	15,353	40,522	13,451	546	13,708	13,373	0	96,953	9,695	106,648	3%
11. Bukhara	21,554	49,334	52,658	739	14,640	19,028	0	137,953	13,795	151,748	5%
12. Navoi	33,389	33,626	25,151	508	10,156	16,453	0	119,283	11,928	131,211	4%
13. Urgench	17,715	38,917	30,991	785	14,930	16,534	0	119,872	11,987	131,859	4%
14. Nukus	25,910	48,903	60,981	739	16,877	24,546	0	177,956	17,796	195,752	6%
[Nationwide Air Navigations System]			41,660			6,249	0	47,909	4,791	52,700	2%
(%)	25%	29%	21%	1%	9%	13%	1%	(100%)			
Total	735,051	866,327	626,535	20,690	275,979	376,649	43,450	2,944,681	294,468	3,239,149	100%

Note: Total amount is the sum of the above all cases.

Table 4.8.3 Implementation Schedule of an Airport



4.9 Preliminary Economic Analysis

Purpose of the preliminary economic analysis is to make an evaluation of the economic worth brought about in the Republic of Uzbekistan by implementing development project of the study airport.

The economic evaluation is generally made in terms of the Economic Internal Rate of Return (EIRR) on the net present value (NPV) of the Project derived from the cost-benefit analysis made from the viewpoint of the national economy.

Table 4.9.1 Concept of Cost-Benefit Analysis

	The Base Case "with the project" (B)	The Project Case "without the project" (P)	Difference (D)=(B)-(P)	EIRR (Economic Internal Rate of Return) (E)
Costs	Cb	Cp	Cd = Cb - Cp	EIRR = E ; calculating from the following formula $\sum_t \frac{(Bd - Cd)}{(1 + E)^t} = 0$ where t = year (1, 2, ...)
Benefits	Bb	Bp	Bd = Bb - Bp	

4.10 Evaluation of Priority Projects

4.10.1 Priority Projects

(1) Air Transportation Facility Development Projects

Through the master planning for long-term development plan of airports and nationwide air navigation system, the following ten (10) projects are selected as the priority projects for modernization of the air transportation development in Uzbekistan.

- Project 1 (PJ-1) Development of Existing Tashkent Airport (Class I Airport)
- Project 2 (PJ-2) Development of New Tashkent Airport (Class I Airport)
- Project 3 (PJ-3) Development of Namangan Airport (Class II Airport)
- Project 4 (PJ-4) Development of Fergana Airport (Class II Airport)
- Project 5 (PJ-5) Development of Samarkand Airport (Class II Airport)
- Project 6 (PJ-6) Development of Termez Airport (Class II Airport)
- Project 7 (PJ-7) Development of Bukhara Airport (Class II Airport)
- Project 8 (PJ-8) Development of Urgench Airport (Class II Airport)
- Project 9 (PJ-9) Development of Nukus Airport (Class II Airport)
- Project 10 (PJ-10) Development of Nationwide Air Navigation System

(2) Management Development Projects

In addition to the above projects, through the review on the organization and

management procedure of NAC as stated in Chapters 6 and 7, the following four (4) projects related to the institutional and management modernization of NAC are selected.

Project 11 (PJ-11)	Program for Establishment of Department of Civil Aviation
Project 12 (PJ-12)	Improvement Program of Accounting and Management System of Airport Operation
Project 13 (PJ-13)	Program for Establishment of Corporate Planning Procedure for Airline Management
Project 14 (PJ-14)	Strengthening Program for Safety Operation in Aviation Sector

4.10.2 Evaluation Criteria of Priority Projects

(1) Evaluation Criteria of Air Transportation Facility Development Projects

Regarding the ten (10) Air Transportation Facility Development, evaluation was made from the viewpoints of the priority in national development plan, urgency of improvement, and efficiency of investment in order to select the high priority airports for subsequent pre-feasibility study. Evaluation was made at 3 grades, namely high (1), medium (2), and low (3). Evaluation criteria consist of the following items:

- a) Necessity of Urgent Improvement for Safety and Services
- b) National Development Priorities
- c) Importance in Air Transport Network of Uzbekistan
- d) Project Cost
- e) National Economic Cost and Benefit
- f) Environmental Impact by Airport Development

(2) Evaluation Criteria of Management Development Projects

Regarding the four (4) Management Development Projects, it is difficult to adopt the same criteria for evaluation of air transportation facility development projects. Therefore, those projects are evaluated through the review of the present situation of management procedures in NAC.

4.10.3 Selection of High Priority Projects

(1) Selection of Air Transportation Facility Development Projects

Results of evaluation are shown in **Table 4.10.5**. Based on the results of evaluation, among ten (10) projects of air transport facility development, the following four (4) airports are selected as the High Priority Airports for the Pre-Feasibility Study, except Samarkand, Bukhara and Urgench airports, of which the modernization projects are now being implemented, and Fergana airport being controlled by military.

- Tashkent (including New Airport)
- Namangan Airport
- Termez Airport
- Nukus Airport

- Nationwide Air Navigation System

(2) Selection of Management Development Projects


As shown in Table 4.10.5, the following projects are selected in order to make recommendation on organization, operation and management related to air transportation development in Uzbekistan.

- Program for Establishment of Department of Civil Aviation
- Improvement Program of Accounting and Management System of Airport Operation
- Program for Establishment of Corporate Planning Procedure for Airline Management
- Strengthening Program for Safety Operation in Aviation Sector

Table 4.10.5 Evaluation of Air Transportation Development Projects

Evaluation Items	Long-Term Development Projects for Air Transportation in Uzbekistan													
	PL1	PL2	PL3	PL4	PL5	PL6	PL7	PL8	PL9	PL10	PL11	PL12	PL13	PL14
	Master Plans for Air Transportation Facilities													
	Local Airports													
	Metropolitan Airport													
	Existing Terminal	New Terminal	Namangan	Fergana	Samarqand	Termez	Bukhara	Urgench	Nodus	Air Navigation System	Program for Establishment of Department of Civil Aviation	Improvement of Program of Airport Management	Training Program for Airline Management	Strengthening Program of Safety Operation
Outline of Projects	Improvement of Existing Facilities	New Airport	New Runway	Improvement of Existing Facilities	Improvement of Existing Facilities	Improvement of Existing Facilities	Improvement of Existing Facilities	Improvement of Existing Facilities	Improvement of Existing Facilities	Modernization of Nationwide Air Navigation Facilities	Establishment of New Department of Civil Aviation	Improvement of Airport Management	Improvement of Corporate Planning	Improvement of Training Program for Pilot and Mechanics
A. Urgency of Improvement	1	2	1	1	3	2	3	3	1	1	1	1	1	1
B. National Development Priority	1	1	3	2	2	2	2	2	3	1	1	1	1	1
D. Importance of Air Transport Network	1	1	2	2	2	2	2	2	2	1	3	1	1	1
E. Air Transport Demand (Passenger demand in 2020: thousand)	1	1	3	2	2	3	3	3	3	-	-	-	-	-
F. Project Cost (Cost/Passenger)	(4,470) (US\$5)	(4,470) (US\$15)	(760) (US\$25)	(1,220) (US\$11)	(940) (US\$7)	(650) (US\$20)	(750) (US\$13)	(870) (US\$10)	(570) (US\$22)					
G. National Economic Benefit (EIRR)	1	1	2	1	2	2	3	3	1	-	-	-	-	-
H. Environmental Impact	3	2	2	2	2	1	2	2	2	-	-	-	-	-
I. Total Point	9	10	16	12	14	15	17	16	15					
J. Overall Evaluation	High priority project due to international hub support	High priority project due to international hub support	High priority project due to regional core airport	High priority project due to regional core airport	Not a high priority project due to the ongoing project	High priority project due to regional core airport	Not a high priority project due to the ongoing project	Not a high priority project due to the ongoing project	High priority project due to regional core airport	High priority project due to the existing facilities	High priority project in order to modernize the present organization	High priority project in order to improve the present account system and management procedures	High priority project in order to improve the management procedures for airline business	High priority project in order to strengthen the safety operation.
K. (Order of Priority)	1	2	5	9	6	3	8	7	4					
L. Selection of High Priority Projects	●	●	●	●		●			●	●	●	●	●	●

CHAPTER 5
ENVIRONMENTAL STUDY



CHAPTER 5 ENVIRONMENTAL STUDY

5.1 Standard

5.1.1 Aircraft Noise Level

The standard method for evaluation of aircraft noise level used in Japan is WECPNL. Although the standards between Uzbekistan and other countries are different to simply compare, according to converted L_{Aeq} , the aircraft noise level standard of Uzbekistan seems to be the same as the standard of other countries.

5.1.2 Air Quality

The quality norms of ambient air of Uzbekistan are based on the norms prepared by specialist of Ministry of Health of the USSR in 1991.

5.1.3 Water Quality

The water quality standards in Uzbekistan are based on the water protection in USSR. Ministry of Health of the USSR established the water quality standard in 1988.

5.2 Issues at Present

5.2.1 Meteorology

(1) Uzbekistan

Uzbekistan has a warm, sharply continental and very arid climate same as the other Central Asia republics. Temperature of the air climbs to 40 - 45°C at noontime in the summer months. There is considerable difference between summer and winter temperature and sudden sharp changes in the weather.

(2) Tashkent City (Tashkent airport)

Tashkent Airport is influenced under two major climates, namely, severe continental and dryness. It is unstable and wet in winter that starts in December and ends in March, the date of snow-cover appearance is marked approximately from 15 December to 20 February.

The climatological data were measured at 430m height of sea level in Tashkent airport (41°15' 26" N, 69°16' 54" E). The monthly average wind speed is in the range of 1.5 to 2.2 m/sec, the prevailing wind throughout the year generally comes from northwest.

The monthly average, maximum and minimum temperatures are in the ranges of 0.8°C to 27.0°C, 6.4°C to 35.7°C and -3.6°C to 19.4°C, respectively.

(3) Sirdarya Town

The monthly average wind speed is in the range of 1.4 to 2.2 m/sec, dominant wind directions are north, north-west and west.

The monthly average, maximum and minimum temperatures are the range of -17.8°C to 26.7°C, 19°C to 45.0°C and -32°C to 9.0°C in 1936-1992.

5.2.2 Environmental Quality

(1) Air Quality

The air quality was measured near Tashkent loess valley once by UZGYdraMet for four air substances: inorganic dusts, nitrogen dioxide (NO₂), sulfur dioxide (SO₂), and carbon monoxide (CO). Air quality of all substances does not exceed the standard.

(2) Water Quality

Water quality of organic matters was monitored in Chirchik River, Boz-suy channel, Sirdarya River and Keles river for the period of 1988-1992. The range of BOD₅ was from 1.10mg/l to 3.87mg/l. BOD₅ of Chirchik River were highest comparing level with each other. The range of phenol concentration were 0.001mg/l to 0.008mg/l, each river concentration were same level.

5.3 Initial Environmental Evaluation (IEE)

5.3.1 Basic Concept

The purpose of Initial Environmental Evaluation (IEE) is to examine the environmental impact which might be caused by the airport development, and to select items for Environmental Impact Analysis, which is to be carried out in the 2nd field survey in Uzbekistan for Feasibility Study on selected priority projects.

5.3.2 Environmental Condition of the Project Site

Environmental condition of the 14 project sites was examined in terms of social and natural environment, and pollution.

5.3.3 Screening

Screening is a process to identify whether or not a project requires environmental impact assessment and the level of assessment. This process was performed by using a check list method.

5.3.4 Scoping

Scoping is a process to select the major environmental items, which may cause impact to surrounding area of the airport by the implementation of the project. This process was performed by using a check list method.


Table 5.4.1 Summary of Scoping of Priority Airports

Environmental Items	New Tashkent	Tashkent	Andizhan	Namangon	Fergana	Kokand	Samarqand	Termez	Karshi	Bulbarga	Navoi	Urgench	Nukus
[Social Environment]													
1	B	D	D	D	D	D	D	D	D	D	D	D	D
2	B	D	D	D	D	D	D	D	D	D	D	D	D
3	B	C	C	C	C	C	C	C	C	C	C	C	C
4	B	D	D	D	D	D	D	D	D	D	D	D	D
5	C	D	D	D	D	D	D	D	D	D	D	D	D
6	C	D	D	D	D	D	D	D	D	D	D	D	D
7	B	D	D	D	D	D	D	D	D	D	D	D	D
8	B	D	D	D	D	D	D	D	D	D	D	D	D
9	B	B	B	B	B	B	B	B	B	B	B	B	B
[Natural Environment]													
10	A	D	D	D	D	D	D	D	D	D	D	D	D
11	A	D	D	D	D	D	D	D	D	D	D	D	D
12	A	D	D	D	D	D	D	D	D	D	D	D	D
13	A	D	D	D	D	D	D	D	D	D	D	D	D
14	D	D	D	D	D	D	D	D	D	D	D	D	D
15	C	D	D	D	D	D	D	D	D	D	D	D	D
16	C	D	D	D	D	D	D	D	D	D	D	D	D
17	A	D	D	D	D	D	D	D	D	D	D	D	D
[Pollution]													
18	C	C	C	C	C	C	C	C	C	C	C	C	C
19	C	D	D	D	D	D	D	D	D	D	D	D	D
20	C	D	D	D	D	D	D	D	D	D	D	D	D
21	C	B	B	B	B	B	B	B	B	B	B	B	B
22	C	D	D	D	D	D	D	D	D	D	D	D	D
23	C	D	D	D	D	D	D	D	D	D	D	D	D

Note : Evaluation Category

- A: Serious impact is expected
- B: Some impact is expected.
- C: Extent of impact is unknown. (Examination is needed. Impacts may become clear as study progress)
- D: No impact is expected. IEE/EIA is not necessary.

CHAPTER 6
PRE-FEASIBILITY STUDIES FOR
HIGH PRIORITY PROJECTS



CHAPTER 6

PRE-FEASIBILITY STUDIES FOR HIGH PRIORITY PROJECTS

6.1 General

6.1.1 High Priority Projects

Selected High Priority Projects, which were agreed by NAC, are as follows:

- Development of the capital airport, i.e. development of the existing Tashkent Airport or New Tashkent Airport;
- Development of local airports including Namangan, Termez and Nukus Airports; and
- Development of Nationwide Air Navigation System.

6.1.2 Target Year for Development

Facility and land requirement analysis was made to provide adequate capacity to cope with the demand in;

- 5 years for facility;
- 10 years for land area;

After completion of the development, thus targeting the years 2010 for facility development, and 2015 for land acquisition.

However, regarding development of New Tashkent Airport, target year for development and implementation period have been shifted to 5 years later, taking into account the development of the existing international passenger terminal building at Tashkent airport financed by EBRD (European Bank for Rehabilitation and Development).

- Target Year for Development

<u>Facility</u>	Year 2010 (except New Tashkent) Year 2015 (New Tashkent)
<u>Area</u>	Year 2015 (except New Tashkent) Year 2020 (New Tashkent)
- Project Implementation Period

	Present – 2005 (except New Tashkent) Year 2000 – 2010 (New Tashkent)
--	---

6.1.3 Scope of Development

Based on the demand forecast and results of discussions with respective airport organization during the second field survey, scope of development was established as shown in Table 6.1.2.

Table 6.1.2

Summary of Development Plan

○ Rehabilitation ● Newly

Development Item	Tashkent	New Tashkent	Namangan	Termez	Nukus
1. Airfield facilities					
1.1 Runway		●			
1) Extension of length			○		
2) Expansion of width			○	○	
3) Overlay	○		○	○	○
4) Shoulder	○		○	○	○
5) Turning Pad	○		○		
1.2 Runway strip					
1) Overrun		●			
2) Earthwork (Expansion Area)			○		
3) Drainage(Expansion Area)			○		
4) Perimeter Road			○	○	
5) Perimeter Fence		●	○		
1.3 Taxiway					
1) Extension of Length				○	○
2) Expansion of Width	○			○	○
3) Overlay	○			○	○
4) Shoulder			○		○
1.4 Apron		●			
1) Expansion			○	○	○
2) Overlay	○ Dom.		○	○	○
3) Shoulder and Service Road	○ Dom.		○		
2. Terminal Facilities					
2.1 Passenger Terminal Building	○ Dom.	● Int'l	○ Int'l	○ Int'l	○ Int'l
2.2 Cargo Terminal Building	○	● Int'l			
2.3 Tower and Administration Bldg		●	○	○	○
2.4 Fire station		●	○	○	○
2.5 Power station		●	○	○	○
2.6 Road and car park		●	○	○	○
2.7 Aircraft hanger	○	● Int'l	○	○	○
2.8 Utilities		●			
2.9 Fuel supply system	○	●	○	○	○
3. Air Navigation System					
3.1 Radio Nav aids					
1) ILS, Locator		●	○	○	○
2) VOR/DME	○	●	●	●	●
3.2 ATC System and Telecom.					
1) Control Tower Facilities, TRDPS		●	●	●	●
2) ASR/SSR, AFTN		●	○	○	○
3) ASDE		●			
3.3 Airfield Lighting System	●				
1) PALS, SALS, PAPI		●	●	●	●
2) REDL, RTHL, TWEL, AFL		●	○	○	○
3) Aerodrome Beacon, Power Supply system for Nav aids		●	●	●	●
3.4 Meteorological Observation System					
1) Wind direction, and Speed Sensor, Air temperature and Humidity Sensor, Barometer		●	○	○	○
2) RVR and Ceilometer, Data Collection and Processing System, Weather data Monitor, Forecast Equipment		●	●	●	●
3) Weather Radar	●	●	●	●	●

Note Int'l: International Dom.: Domestic

6.2 Preliminary Design

6.2.1 Development of Existing Tashkent Airport

(1) Summary Development Plan

As the short-term development plan, the scope of the project has been set based on the forecast airport traffic of the target year 2010 taking into account the requirements mentioned above.

- airfield and air navigation facilities to satisfy international standards;
- provide comfortable facilities and qualified services suitable for the gateway to the Central Asia;
- achieve comfortable and speedy service grade for transfer (between International and CIS flights, between International and Domestic flights) passengers adequate for international hub airport;
- develop air cargo transportation center for CIS countries.

The scope of the project excludes the modernization of the international-related facilities being undertaken on the basis of EBRD finance.

Tables 6.2.2 shows summary development plan of this project of this project, and Fig.6.2.1 presents facility layout plan of the year 2010.

Table 6.2.2 Summary Development Plan of Existing Tashkent Airport

FACILITIES		CONTENTS
Planning Parameters		Passenger Int'l/CIS 2032thousand Dom. 1079 thousand Cargo 41.3thousand
Largest Aircraft		B767(Medium-Jet)
Airfield	Runway	
	Taxiway	(Widen taxiways 1 to 6,11 to 15 to 23m with 7.5m wide shoulders. Reinforce pavement by overlay.)
	Apron	(Int'l Apron :Improvement of apron under Planning) Domestic Apron : Improvement Area 8.6ha
Terminal	Passenger Bldg.	(Int'l/CIS :Improvement under construction and under planning) Domestic : Expansion of floor space to 8,400m ²
	Cargo Bldg.	Expansion of floor space to 8,000m ²
	Other Facilities	Rescue & Fire Fighting 1,460m ² (CAT.8) Car park 5.1ha (1460 spaces)
Air-Nav.	Airfield Lighting	-
	Radio-Nav. & Telecom.	Install ASDE. Renew VOR/DME.

Note: Items shown in () are to be implemented separately and are out of the scope of this project.

(2) Preliminary Design and Scope of this Project

a) Airfield Facilities

Rehabilitation of taxiways and international apron is to be carried out by EBRD financed project and, therefore, domestic apron improvement only is included in the scope of this project.

Existing apron capacity is adequate to cater for the demand of the target year 2010, however,

the existing pavement of the domestic aprons needs to be reinforced by phased demolition and reconstruction of cement concrete.

b) Passenger Terminal Building

The domestic passenger terminal building requires total floor area of 8,400 m² in order to cater for the forecast traffic of the target year 2010, 5,480 m² more compared to the existing floor area of 2,920 m².

The existing domestic passenger building lacks for arrival facilities, which need to be developed for passenger and greeter's convenience.

It is preferable to expand the existing domestic passenger building to southward (toward the airside).

One (1) level passenger-processing concept has been adopted considering the following:

- there is ample apron area and relocation of parking stands is acceptable,
- nose-in/push-out aircraft parking concept is not achievable and therefore aircraft embarkation/disembarkation by ramp bus is inevitable even in future.

Expansion of the domestic passenger building needs to be made in the manner shown in Table 6.2.4, in order to maintain operation of the building:

- construct the expansion area with adequate separation from the existing one to keep the existing building operable (Phase 1),
- after completion of the expansion, transfer the building function to the expanded area, and demolish a part of the existing one to build corridor connecting the expanded and existing buildings (Phase 2),
- convert the existing lobby to office, shop and restaurant (Phase 3),
- completion of expansion work (Phase 4).

Expansion plan of the domestic passenger terminal building is shown in Fig.6.2.2.

c) Other Terminal Facilities





Cargo terminal building and car park need to be expanded in order to cater for the forecast demand of the target year 2010 while the other facilities need not to be expanded.


(3) Air Navigation Aids

Following facilities should be installed or renewed:

- renewal of VOR/DME,
- installation of new Airport Surface Detection Equipment(ASDE),
- renewal of weather radar.

Table 6.2.4 Phasing Plan for Expansion of the Existing Domestic Passenger Terminal Building

Phase I	Phase II	Phase III	Phase IV
<p>Expansion Area</p>  <p>Existing Area</p>	<p>Expansion Area</p>  <p>Existing Area</p>	<p>Expansion Area</p>  <p>Conversion of lobby to office, shop and restaurant</p> <p>Existing Area</p>	<p>Expansion Area</p>  <p>Existing Area</p>
<p>Provide adequate separation between expansion and existing areas so as to maintain the existing one operable.</p>	<p>After completion of the expansion area, transfer the building function from existing building to expanded area to build corridor connecting the expanded and existing areas.</p>	<p>Convert the existing lobby to office, shop and restaurant.</p>	<p>Completion of expansion work.</p>



Development Plan (Case-1) Tashkent

FACILITIES	CONTENTS	
Air Traffic (Yr.2010)	Passenger Int'l: CIS 2032 thousand Dom. 1079 thousand Cargo 41.3 thousand	
Max. Aircraft	B767 (Medium-Jet)	
Air-field	Runway	RWY08R/26L Improvement: Shoulder 7.5m wide Both Runway Pavement overlay
	Taxiway	No 1-5, 11-15 Widen up to width 23m with 7.5m shoulder Pavement overlay
	Apron	Int'l Apron: Improvement of apron under Planning Domestic Apron: Improvement Area 8.6ha
Terminal	Passenger Bldg.	Int'l: CIS Improvement under Construction and under Planning Domestic: Expansion up to 8,400m ²
	Cargo Bldg.	8,000m ²
	Other Facilities	Rescue & Fire Fighting: 1,460m ² (CAT II) Car parking: 5.1ha (1,460 lots)
Air-Nav	Airfield Lighting	
	Radio-Nav. & Telecom.	New: ASDE Renewal: VOR/DME

Fig. 6.2.1 Tashkent Airport Development Plan (2010)

TERMINAL AREA			
1	Int'l Passenger Terminal Building	8	Fuel Tank Farm
2	Dom. Passenger Terminal Building	9	Fire Station
3	VIP Building	10	Aircraft Maintenance Area
4	Control Tower and Operation	11	Aircraft Maintenance Office
5	Car Park		
6	Cargo Handling Area		
7	Administration Area		

AIRPORT DATA			
Airport Name	Tashkent	Elevation	431m
Class	I	Reference Temperature	29°C
Province	Tashkent	Runway	4000mx60m
Main City	Tashkent		3900mx45m
Distance from city	6km south	Direction (True north)	N 82° E
Reference Point	N 41° 15' 24"	Instrument Runway	08L/08R/26R
Coordinates	E069° 16' 24"	ILS Category	CAT-II

The Republic of Uzbekistan National Air Company "Uzbekistan Havo Yullari"	
The Study for The Air Transportation Development in The Republic of Uzbekistan	
Airport	Tashkent Airport
Drawing Title	Airport Layout Plan (Year 2010)
Date	Scale




Fig. 6.2.2 Tashkent Airport Domestic Passenger Terminal Layout Plan (2010)

6.2.2 New Tashkent Airport

(1) Summary Development Plan of New Tashkent Airport

Development of the existing Tashkent Airport imply some problems shown below:

- increase of aircraft noise pollution on residential area;
- impediment of Tashkent City development due to occupation of large area by the airport; and
- difficulty in expanding the existing Tashkent Airport due to geographical constraint,

which may hinder the existing Tashkent Airport from playing the role as the hub airport of the Central Asia.

Construction of New Tashkent Airport has been discussed hereunder as an alternative solution to the development of the existing airport.

The new airport also needs to meet the same requirements as the hub airport specified for the existing Tashkent Airport. However, in order to minimize initial investment, one 4,300m long runway only is included in the scope of the project, securing future possibility of constructing a second close parallel runway.

Attention has also been paid to land use of the terminal area in order to provide adequate space for future relocation of aircraft maintenance facilities from the existing airport.

Development of the New Tashkent Airport is to be made in accordance with the functional distribution of capital airports shown in Table 4.5.9 of Chapter 4, and construction of the following facilities is included in the short-term development plan of this project:

- airfield facilities such as runway, taxiway and apron,
- international and CIS related passenger and cargo facilities,
- administration facilities.

Summary development plan of the New Tashkent Airport has been set as shown in Table 6.2.5, and airport layout plan is shown in Fig.6.2.4.

(2) Location and Orientation of Runway

Location and orientation of the runway has been determined as shown in Fig.6.2.5 considering the following:

- Environmental impact
- Economical development
- Adequate usability factor
- Location of site : Approx. Lat. N41° 01.5', Lon. E68° 53.5'
- Runway Orientation : Approx. N58.7° E

Table 6.2.5 Summary Development Plan of New Tashkent Airport

FACILITIES		CONTENTS
Air Traffic (Yr.2015)		Passenger 3,800 thousand (Int'l/CIS) Cargo 4.7 thousand (Int'l/CIS)
Largest Aircraft		B747(Large-Jet)
Airport Area		390ha
Airfield	Runway	Length 4300m Width 60m
	Taxiway	One full parallel and two apron taxiways plus four rapid exit and two exit taxiways
	Apron and aircraft parking	For Pax : L-Jet 7, M-Jet 21, S-Jet/MP 3, Total 31 For Cargo : M-Jet 3 Maintenance Apron
Terminal	Passenger Bldg.	International/CIS 27,400m ²
	Cargo Bldg.	International/CIS 8,700m ²
	Others	Operation & Control Tower 5,700m ² Aircraft Fuel Supply 6,820kl 14,300m ² Rescue & Fire Fighting 900m ² (CAT.8) Car park 7ha (2,020 spaces)
Navaids	Airfield Lighting	ALS, SFL, PAPI, RCL, RWL, TWL, AFL
	Radio-Nav. & Telecom.	ILS, VOR/DME, NDB, ASR/SSR, ASDE




Fig. 6.2.5 Location and Orientation of Runway (New Tashkent Airport)

(3) Site Conditions

a) Geography

The average ground elevation of the site is 340 m ranging from 325 m at the lowest to 355 m at the highest. The ground moderately declines from northwest (terminal side) to southeast (runway side) at an average slope of 1.2 % from height of 350 m to 300 m.

b) Geological Conditions

According to the results of soil investigation, the soil in the proposed site for construction of new airport consists of mainly of sand loam fairly well consolidated with N value of around 10, and CBR value of around 4%.

c) Land Use

Most of the site is cotton field. There are also cotton fields and farmer houses near the site.

(4) Land Preparation Plan

Site Area	: Approx. 390ha
Average Planned Elevation	: Approx. 340m
Volume of Earthwork	: Fill volume 7,500,00m ³ Cut volume 7,900,000 m ³
Average Height of Embankment and Excavation	: Approx. ±2m

(5) Airfield Facilities

a) Runway

The dimension of the runway will be 4300 m long and 60 m wide with 7.5 m wide shoulder on each side of the runway, so that B747 class aircraft will be able to operate without any operational restrictions.

b) Apron

Following number of aircraft parking stands should be provided in order to meet forecast traffic of the target year 2015:

- 7 stands for L-JET aircraft,
- 21 stands for M-JET aircraft,
- 3 stands for S-JET and MP aircraft,
- 3 stands for freighter aircraft.

In addition to the aircraft parking stands mentioned above, maintenance apron, which will also be utilized as the overnight apron, needs to be provided.

(6) Terminal Area Facilities

As specified in Chapter 4, international and CIS related passenger traffic only will be handled at New Tashkent Airport at opening day.

a) Passenger Terminal Concept

Selection of the terminal concept is made, taking into account land area available, number of passengers and aircraft parking stands, and among them, the linear terminal concept has been employed for New Tashkent Airport.

b) Floor Plan of Passenger Terminal Building

Fig.6.2.18 presents floor plan of the international passenger terminal building.

(7) Other Terminal Facilities

Following facilities will be developed to meet forecast traffic of the target year 2015:

- cargo terminal building,
- car park,
- administration building and control tower,
- electrical substation.

(8) Air Navigation Facilities

Following navigation aids are required to meet the requirement of the target year 2015.

- Radio Navigation Aids
- ATC System and Telecommunications
- Airfield Lighting System
- Meteorological Observation System

(9) Access Facilities

The main access route is R39 (high-grade two-lane road for each way) which is to be connected by 1.5 km long approach road to the new airport.

Visitors using R34 or rail will need to come to the airport via rural road connecting R34 or rail station to R39, and finally the approach road.

Provision of a ramp has been proposed to connect R39 and the approach road so that airport related traffic can smoothly be split from the other traffic.

(10) Other Facilities related to Airport Development

a) Diversion of Water Channels and Power Cable Lines

Water channels and power cable lines need to be diverted.

b) Utility

Following utility facilities need to be provided to the new airport:


- power supply ; 6700 to 7210 KVA (20000 KVA if power for related facilities

are to be supplied) will be supplied from neighboring high voltage (220 KV) power cable line via newly built substation and power line,

- water ; 1170 to 1230 m³ /day to be supplied from surrounding area,
- sewage ; 1170 to 1230 m³ /day to be treated in the new airport and discharged to surrounding rivers,
- Waste; 3.4 to 3.6 t/day to be incinerated in the new airport and/or surrounding area.

c) Others

Some of the employees of the existing airport will need to be relocated to the new airport area, and their housing should be developed in the neighboring area or airport-related facility area (approx. 10 ha) within the new airport.



FACILITY REQUIREMENTS

FACILITIES	CONTENTS
Air Traffic (Yr. 2015)	Passenger 3,800 thousand (Int'l/CIS) Cargo 4.7 thousand (Int'l/CIS)
Max. Aircraft	B747 (Large-Jet)
Airport Area	390ha
Air-field	Runway: Length 4300m Width 60m Taxiway: 1 Full Parallel, 2 Apron Taxiway, 4 Rapid Exit, 2 East Apron: Large-Jet 7, Medium-Jet 21, Small-Jet/Mini-Plane 3 Total 31 Passenger: Cargo Medium-Jet 3, Maintenance Apron Others
Terminal	Passenger Bldg.: International/CIS 27,400m ² Cargo Bldg.: International/CIS 8,700m ² Others: Operation & Control Tower 5,700m ² Aircraft Fuel Supply 6,820x14,300m ² Rescue & Fire Fighting 900m ² (CAT 8) Car parking 7ha (2,020 lots)
Air-Nav	Airfield Lighting: ALS, SFL, PAPI, RCL, RWL, TWL, AFL... Radio-Nav. & Telecom: H.S. VOR/DME, NDB, ASR/SSR, ASDE

Fig. 6.2.4 New Tashkent Airport Development Plan (2015)

TERMINAL AREA			
1	International Passenger Terminal Bldg	8	Fuel Tank Farm
2	(Domestic Passenger Terminal Bldg)	9	Hanger
3	International Cargo Terminal Bldg.	10	International Car Park
4	(Domestic Cargo Terminal Building)	11	(Domestic Car Park)
5	Operation and Control Tower	12	Access Road
6	Power Station	13	Dormitory, Operation Center etc.
7	Fire and Rescue Station		() constructed at 2nd stage

AIRPORT DATA			
Airport Name	New Tashkent	Elevation (Rwy Center)	338m
Airport Classification	I	Reference Temperature	(29°C)
Province	Tashkent	Runway	4300mx60m
Main City	Tashkent	Direction (True north)	N 58.7° E
Distance from city	45km south-west	Instrument Runway	06/24
Reference Point	N41° 02'	I.L.S. Category	CAT-II
Coordinates	E68° 54'		

The Republic of Uzbekistan National Air Company "Uzbekistan Havoyullari"	
The Study for The Air Transportation Development in The Republic of Uzbekistan	
Airport	New Tashkent Airport
Drawing Title	Airport Layout Plan (Year 2015)
Date	Scale




Fig. 6.2.19(1) New Tashkent Airport International Passenger Terminal Bldg. Layout Plan -1st Floor (2015)




Fig. 6.2.19(2) New Tashkent Airport International Passenger Terminal Bldg. Layout Plan -2nd Floor (2015)






Fig. 6.2.19(3) New Tashkent Airport International Passenger Terminal Bldg. Layout Plan -3rd Floor (2015)



New Tashkent Airport International Passenger Terminal Building Front Elevation



New Tashkent Airport International Passenger Terminal Building Side Elevation

Fig. 6.2.19(4) New Tashkent Airport International Passenger Terminal Building Elevation Plan (2015)

6.2.3 Namangan Airport

(1) Summary Development Plan

In the master plan, construction of a new runway has been proposed considering difficulty of correction of the longitudinal slope (1.6 %) of the existing runway to meet ICAO recommendation (no more than 1 %). However, based on the discussions with NAC and the administration office of Namangan Airport it has been decided that extension of the existing runway adequate to cater for B767 class aircraft without correction of the longitudinal slope is more preferable considering the following:

- There will be no significant problem such as restriction of allowable cabin load of aircraft even if the existing longitudinal slope is maintained ,
- Extension of the existing runway is more economical than construction of a new runway.

Table 6.2.8 shows summary development plan of Namangan Airport and Fig.6.2.20 presents airport development plan.

Table 6.2.8 Summary Development Plan of Namangan Airport

FACILITIES		CONTENTS
Air Traffic (Yr.2010)		Passenger : 485 thousand Cargo : 4400 t
Largest Aircraft		B767(Medium-Jet)
Extension Area		19.7 ha
Airfield	Runway	Extension 3270m→3500m ,Provision of a turnaround pad, Pavement overlay ,Shoulder improvement width 7.5m
	Taxiway	Widening 20m→23m ,Shoulder Improvement width 7.5m ,Pavement overlay
	Apron	Passenger : Medium-Jet 3 stands ,Small-Jet/Mini-Plane 3 stands Cargo : Medium -Jet 1 stand Expansion Area 13,800 m ² ,Overlay Area 36,500 m ²
Terminal	Passenger Bldg.	Int'l/CIS 8,400 m ² , Dom. 2,500m ²
	Cargo Bldg.	3,100m ²
	Other Facilities	New Operations & Control Tower Bldg 2,800m ² Rescue & Fire Fighting 600m ² (CAT.6) Car park 2.2ha (610 spaces)
Air-Nav	Airfield Lighting	New PALS, PAPI, SALS, etc. Renewal REDL, RTHL, TWEL, AFL etc.
	Radio-Nav.&Telecom.	New VOR/DME etc. Renewal ILS(Cat I), NDB, ASR/SSR etc.

(2) Preliminary Design and Scope of the Project

a) Airfield Facilities

• Existing Runway Improvement

The existing runway (3270 m long and 45 m wide) needs to be extended to the west by 230 m to the overall length of 3500 m.

The existing pavement of the runway should be reinforced by bituminous overlay.

• Existing Taxiway Improvement

The existing taxiways are 20 m wide, and should be widened to 23 m together with provision of 7.5 m wide shoulder on each side of the taxiways.

Pavement structure of widened portion should be the same as the extended portion of the runway, and pavement overlay on the existing portion should be undertaken for reinforcement.

• Existing Apron Improvement

The existing apron capacity is inadequate and expansion of the apron by 13,800 m² is required in order to cope with the demand of target year 2010.

The existing apron (36,500 m²) should be reinforced by bituminous overlay. Apron service road (20 m wide) should be provided along the edge of apron.

b) Terminal Area Facilities

• Passenger Terminal Building

The existing passenger terminal building should be expanded toward the apron. The expanded portion of the building should be two-story so that required floor space can be obtained in the limited land space. The second floor will be utilized for departure so that passenger boarding bridge can be provided in future. Floor plan of the passenger terminal building is shown in Fig.6.2.21.

• Other Terminal Facilities

Following facilities should be expanded to cater for requirements of the target year 2010:

- Cargo terminal building,
- Car park,
- Rescue & fire fighting facility.

The administration building, control tower and substation should be built in line with modernization of navigation aids.

6.2.4 Development of Termez Airport

(1) Summary Development Plan

Termez Airport has been selected as a High Priority Project in southern area of Uzbekistan for which development plan has been prepared based on the master plan presented in Chapter 4 of this report.

Summary development of Termez Airport is shown in Table 6.2.12, and airport layout plan of the year 2010 is presented in Fig.6.2.23.

Table 6.2.12 Summary Development Plan of Termez Airport

FACILITIES		CONTENTS
Air Traffic (Yr.2010)		Passenger : 440 thousand Cargo : 1.9thousand
Largest Aircraft		B767(Medium-Jet)
Expansion Area		3.6 ha
Airfield	Runway	Widen 42m to 45m with provision of 7.5 m wide shoulder. Provision of one Turnaround pad, Pavement overlay
	Taxiway	No.1-3 Widen 20m to 23m with provision of 7.5 m wide shoulder. No.4 Provision of 7.5 m wide shoulder Pavement overlay
	Apron	Medium-Jet 2 stands ,Small-Jet/Mini-Plane 3 stands Expansion : 18,700 m ² ,Overlay : 13,700 m ²
Terminal	Passenger Bldg.	CIS 4,200 m ² ,Dom. 2,500m ²
	Cargo Bldg.	1,700m ²
	Other Facilities	New Operations & Control Tower Bldg.2,800m ² Rescue & Fire Fighting 600m ² (CAT.6) Car park 1.4ha (390 spaces)
Air-Nav	Airfield Lighting	New PALS, PAPI, SALS etc. Renewal REDL, RTHL, TWEL, AFL etc.
	Radio-Nav. & Telecom.	Renewal ILS (Cat I), NDB, VOR/DME, ASR/SSR etc.

(2) Preliminary Design and Scope of this Project

a) Airfield Facilities

• Existing Runway Improvement

The existing runway is 3000 m long and 42 m wide, and is to be widened to 45 m with 7.5 m shoulder on each side of the runway in accordance with ICAO Annex 14. Reinforcement of the existing pavement should be made by bituminous overlay.

• Existing Taxiway Improvement

The existing taxiways are to be maintained for the future operation. Existing taxiways require the following:

- bituminous overlay on existing pavement,
- widen width of the taxiway from 20 m to 23 m,
- provision of 7.5 m wide shoulder on both sides of the taxiways.

• Existing Apron Improvement

The existing apron capacity is inadequate and should be expanded by 18,700 m² in order to cope with the forecast demand of the target year 2010. The existing apron (13,700m²) needs to be reinforced by bituminous overlay.

b) Terminal Area Facilities

Planning parameters, facility requirement and planning philosophy for terminal area facilities of Termez Airport are the same as those for Namangan Airport. Floor plan of the passenger terminal building is shown in Fig.6.2.24.

6.2.5 Development of Nukus Airport

(1) Summary Development Plan

Nukus Airport has been selected as a High Priority Project in northwestern area of Uzbekistan, and for the purpose of this pre-feasibility study the development plan for the year 2010 has been prepared based on the master plan presented in Chapter 4.

Table 6.2.13 shows summary development plan and Fig.6.2.26 presents facility layout plan respectively.

Table 6.2.13 Summary of Development Plan for Nukus Airport

FACILITIES		CONTENTS
Air Traffic (Yr.2010)		Passenger : 379 thousand Cargo :1.6 thousand
Largest Aircraft		B767(Medium-Jet)
Airfield	Runway	Widening of shoulder ,Provision of one turnaround pad, Pavement overlay
	Taxiway	Widen taxiways No.2, 3, 6 and 7 to 23m with 7.5m shoulder and provide 7.5 m wide shoulder. Pavement overlay
	Apron	Medium-Jet 3 stands ,Small-Jet/Mini-Plane 3 stands Expansion 8,400 m ² ,Overlay 33,400 m ²
Terminal	Passenger Bldg.	Int'l/CIS 8,400 m ² ,Dom. 2,500m ²
	Cargo Bldg.	2,100m ²
	Other Facilities	New Operations & Control Tower Bldg 2,800m ² Rescue & Fire Fighting 600m ² (CAT.6) Car park 2.2ha (610 spaces)
Air-Nav	Airfield Lighting	New PALS, PAPI, SALS etc. Renew REDL, RTHL, TWEL, AFL etc.
	Radio-Nav. & Telecom.	New VOR/DME Renew ILS (Cat I), NDB, ASR/SSR etc.

(2) Preliminary Design and Scope of this Project

a) Airfield Facilities

• Existing Runway Improvement

The existing runway is 3000 m long and 48 m wide and is sufficient to accommodate the medium class jets. However, 6 m wide shoulder should be provided on each side of the runway in accordance with ICAO Annex 14.

Pavement overlay work by bituminous concrete should be undertaken for reinforcement.

• Existing Taxiway Improvement


The existing taxiways are to be maintained for the future operation. Pavement overlay work by bituminous concrete should be undertaken for reinforcement.

- Existing Apron Improvement

The existing apron capacity is inadequate and needs to be expanded by 8,400 m² in order to cope with the demand of the target year 2010. Pavement of the existing apron (33,400 m²) should be reinforced by bituminous overlay. Apron service road (20 m wide) should be provided along the edge of apron.

- b) Terminal Area Facilities

Planning parameters, facility requirement and planning philosophy for terminal area facilities of Nukus Airport are the same as those for Namangan Airport. Floor plan of the passenger terminal building is shown in Fig.6.2.27 and terminal area layout plan is shown in Fig.6.2.28.



Development Plan (Case-1)		Namangan	
FACILITIES		CONTENTS	
Air Traffic (Yr.2010)		Passenger 485 thousand Cargo 4.4 thousand	
Max. Aircraft		B767(Medium-Jet)	
Air-field	Runway	Extension 3270m → 3500m, One turning Pad Pavement overlay, Shoulder improvement width 2.5m	
	Taxiway	Widening 20m → 23m, Shoulder improvement width 7.5m, Pavement overlay	
	Apron	Medium-Jet 3 stands, Small-Jet/Mini-Plane 3 stands Cargo Medium-Jet 1 stand Expansion Area 13,800 m ² , Overlay Area 36,500 m ²	
Terminal	Passenger Bldg.	Int'l CIS 8,400 m ² , Dom. 2,500m ²	
	Cargo Bldg.	3,100m ²	
	Other Facilities	New Operations & Control Tower Bldg 2,800m ² Rescue & Fire Fighting 600m ² (CAT.6) Car parking 2.2ha (610 lots)	
Air-Nav	Airfield Lighting	New PALS, PAPI, SALS etc. Renewal REDL, RTIL, TWEL, AFL etc.	
	Radio-Nav. & Telecom.	New VOR/DME etc. Renewal ILS(Cat I), NDB, ASR/SSR etc.	




Fig. 6.2.20 Namangan Airport Development Plan (2010)

TERMINAL AREA			
1	Passenger Terminal Building	8	Car Park
2	VIP building		
3	Cargo Storage(under construction)		
4	Control Tower		
5	Administration Building		
6	Storage and Garage Area		
7	Fuel Farm		

AIRPORT DATA			
Airport Name	Namangan	Elevation	515m
Class	II	Reference Temperature	35°C
Province	Namangan	New Runway	3500m
Main City	Namangan	(Existing)	(3270m)
Distance from city	8km south-west	Direction (True north)	N 112° 33' E
Reference Point	N 40° 59' 05"	Instrument Runway	29
Coordinates	E:071° 33' 27"	ILS Category	CAT-I

The Republic of Uzbekistan National Air Company "Uzbekistan Havoyullari"	
The Study for The Air Transportation Development in The Republic of Uzbekistan	
Airport	Namangan Airport
Drawing Title	Airport Layout Plan (Year 2010)
Date	Scale






Fig. 6.2.21(1) Namangan Airport Passenger Terminal Bldg. Layout Plan - 1st Floor (2010)



0 10 20 30M

Fig. 6.2.21(2) Namangan Airport Passenger Terminal Bldg. Layout Plan -2nd Floor (2010)



Development Plan		Termez
FACILITIES	CONTENTS	
Air Traffic (Yr.2010)	Passenger 440 thousand Cargo 1.9thousand	
Max. Aircraft	B767(Medium-Jet)	
Air-field	Runway	Widening width 42m→45m with 7.5m shoulder One Turning Pad, Pavement overlay
	Taxiway	No.1-3 Widening width 20m→23m with 7.5m shoulder No.4 Installation of Shoulder Pavement overlay
	Apron	Medium-Jet 2 stands ,Small-Jet/Mini-Plane 3 stands Expansion and renewal Area 18,700 m ² ,Overlay Area 13,700 m ²
Terminal	Passenger Bldg.	CIS 4,200 m ² ,Dom. 2,500m ²
	Cargo Bldg.	1,700m ²
	Other Facilities	New Operations & Control Tower Bldg 2,800m ² Rescue & Fire Fighting 600m ² (CAT.6) Car parking 1.4ha (390 lots)
Air-Nav	Airfield Lighting	New PALS ,PAPI ,SALS etc. Renewal REDL, RTHL, TWEL, AFI, etc.
	Radio-Nav.& Telecom.	Renewal ILS(Cat I), NDB, VOR/DME, ASR/SSR etc.

Fig. 6.2.23 Termez Airport Development Plan (2010)

TERMINAL AREA			
1	Passenger Terminal Building	7	Canteen
	Control Tower		
2	VIP Building		
3	Fire Station		
4	Garage		
5	Sotrage		
6	Hanger		

AIRPORT DATA			
Airport Name	Termez	Elevation	313m
Class	II	Reference Temperature	38°C
Province	Sukhandaria	Runway	3000
Main City	Termez	(Existing)	(3000)
Distance from city	9km	Direction (True north)	N 74° 09' E
Reference Point	N 37° 17' 11"	Instrument Runway	25
Coordinates	E067° 18' 33"	ILS Category	CAT-I

The Republic of Uzbekistan National Air Company "Uzbekistan Havoyullari"			
The Study for The Air Transportation Development in The Republic of Uzbekistan			
Airport	Termez Airport		
Drawing Title	Airport Layout Plan (Year 2010)		
Date		Scale	




Fig. 6.2.24(1) Termez Airport Passenger Terminal Bldg. Layout Plan -1st Floor (2010)





Fig. 6.2.24(2) Termez Airport Passenger Terminal Bldg. Layout Plan -2nd Floor (2010)



Development Plan		Nukus	
FACILITIES		CONTENTS	
Air Traffic (Yr.2010)		Passenger 370 thousand Cargo 1.6 thousand	
Max. Aircraft		B767(Medium-Jet)	
Air-field	Runway	Widen Shoulder, Improvement one Turning Pad Pavement overlay	
	Taxiway	No 2-3,6-7 Widening up to width 23m with 7.5m shoulder Pavement overlay	
	Apron	Medium-Jet 3 stands, Small-Jet/Mini-Plane 3 stands Expansion and renewal Area 8,400 m ² , Overlay Area 33,400 m ²	
Terminal	Passenger Bldg.	Int./CIS 8,400 m ² , Dom. 2,500m ²	
	Cargo Bldg.	2,500m ²	
	Other Facilities	New Operations & Control Tower Bldg 2,800m ² Rescue & Fire Fighting 600m ² (CAT 6) Car parking 2.2ha (610 lots)	
Air-Nav	Airfield Lighting	New PALS, PAPI, SALS etc Renewal REDL, RTIL, TWEL, AFL etc.	
	Radio-Nav. & Telecom.	New VOR/DME Renewal ILS(Cat I), NDB, ASR/SSR etc.	

Fig. 6.2.26 Nukus Airport Development Plan (2010)

TERMINAL AREA				AIRPORT DATA			
1	Passenger Terminal Building	8	Fuel Tank Farm	Airport Name	Nukus	Elevation	76m
2	VIP Building	9	Aircraft Maintenance	Class	II	Reference Temperature	(36°C)
3	Cargo Storage	10	Car Park	Province	Karakalpakstan	Runway	3000mx45m
4	Administration Building			Main City	Nukus	(Existing)	(3000mx48m)
5	Control Tower			Distance from city	7km north-west	Direction (True north)	N 159° 31' E
6	Fire Station			Reference Point	N 42° 29' 18"	Instrument Runway	33
7	Garage, Storage			Coordinates	E 059° 37' 24"	ILS Category	CAT-I

The Republic of Uzbekistan National Air Company "Uzbekistan Havoyullari"	
The Study for The Air Transportation Development in The Republic of Uzbekistan	
Airport	Nukus Airport
Drawing Title	Airport Layout Plan (Year 2010)
Date	Scale




Fig. 6.2.27(1) Nukus Airport Passenger Terminal Bldg. Layout Plan - 1st Floor (2010)




Fig. 6.2.27(1) Nukus Airport Passenger Terminal Bldg. Layout Plan -2nd Floor (2010)

6.2.6 Nationwide Air Navigation System

(1) Development Plan

Air routes in Uzbekistan are mainly comprised of four (4) sets of VOR/DME, and twenty (20) sets of NDB, which were installed on and off the airports. Present air routes are concentrated at the areas of Tashkent, Samarkand and on the borders.

However, regarding the worldwide en-route nav aids, since NDB has disadvantages of radio wave interference, VOR/DME is commonly used as the en-route nav aids in order to improve accuracy of air navigation on the air routes, with the following advantages;

- To avoid mutual radio wave interference between NDB;
- To install VOR/DME as basic facility enabling Regional Area Navigation System (RNAV);
- Ensure the alternative function of FANS routes.

Considering the above situations, it is recommendable that en-route nav aids should be replaced by VOR/DME from the present NDB facilities. Eight (8) sets of NDB are planned to be replaced by VOR/DME as a first phase up to 2005.

Table 6.2.14 Nationwide Air Navigation System

Point	Year of Installation of NDB
Karakhtay	1989
Dzhizak	1986
Dalverzin	1986
Syrdarya	1990
Nurata	1979
Bulungur	1988
Nagornaya	1982
Urgut	1989