

JAPAN INTERNATIONAL COOPERATION AGENCY (JICA)
MINISTRY OF COMMUNICATIONS (MOC)


FINAL REPORT

THE DEVELOPMENT STUDY ON THE NATIONWIDE FERRY SERVICE ROUTES(STAGE II) IN THE REPUBLIC OF INDONESIA

VOLUME 2

PART3: SHORT-TERM DEVELOPMENT PLAN

OCTOBER 1998



JICA LIBRARY



J 1147582 [9]

THE OVERSEAS COASTAL AREA DEVELOPMENT INSTITUTE OF JAPAN (OCDI)
PACIFIC CONSULTANTS INTERNATIONAL (PCI)

SSF
JR
98-123

EXCHANGE RATE

US\$ 1.00 =9,600 Rupiah =128 Yen

(Average exchange rate in the period from January to March 1998)


JAPAN INTERNATIONAL COOPERATION AGENCY (JICA)
MINISTRY OF COMMUNICATIONS (MOC)

FINAL REPORT
THE DEVELOPMENT STUDY ON
THE NATIONWIDE FERRY SERVICE
ROUTES (STAGE II)
IN THE REPUBLIC OF INDONESIA


VOLUME 2

PART 3: SHORT-TERM DEVELOPMENT PLAN


OCTOBER 1998




Location Map of Study Routes




Surabaya Ferry Terminal




Banjarmasin Ferry Terminal




Selayar Ferry-Terminal




Labuhan Bajo Ferry Terminal




Manokwari Ferry Terminal



Biak Ferry Terminal



Wahai Ferry Terminal



Babang Ferry Terminal

LIST OF ABBREVIATIONS

A

ADB	Asian Development Bank
AMDAL	Environmental Impact Analysis
ASDF	ASDP's antecedent project
ASDP	State-owned Ferry Terminal Company

B

BAPEDAL	Environmental Impact Management Agency
BAPENAS	National Development Planning Agency
BAPPEDA	Provincial Development and Planning Board
BKN	Province Treasurer
BM.	Bench Mark
BOT	Build Operate Transfer
BPS	Central Bureau of Statistics

C

CBR	California Bearing Ratio test
CFC	Conversion Factor for Consumption
CIF	Cost, Insurance of Freight
CONV	Conventional type boat

D

DIK	Activity of Filler List
DEPKEN	Ministry of Finance
DGAC	Directorate General of Air Communication
DGLT	Directorate General of Land Transportation and Island Waterways
DGSC	Directorate General of Sea Communication
DL	Datum Level
DUK	Activity of Proposal List
DWT	Dead Weight Tonnage

E

EIA	Environmental Impact Assessment
EIRR	Economic Internal Rate of Return

F

FOB	Free on Board
-----	---------------

G

GDP	Gross Domestic Product
GPS	Global Positioning System

	GRDP	Gross Regional Domestic Products
	GRT	Gross Registered Tonnage
H		
	HUWS	Highest High Water Spring
	HWS	High Water Spring
I		
	IBRD	International Bank for Reconstruction and Development
	IEE	Initial Environmental Examination
	ITCZ	Inter-tropical Convergence Zone
J		
	JICA	Japan International Cooperation Agency
K		
	KANWIL	Provincial Office
	KM	Decree of the Minister
	KVA	Kilo Volt Ampere
L		
	LCT	Landing Craft Transport
	LLAJ	Directorate of Highway Transportation
	LLAK	Directorate of City Transportation
	LLASDP	Directorate of River, Lake and Ferry Transportation
	LLJREL	Directorate of Railway Transportation
	LLWS	Lowest Low Water Spring
	LOA	Length over All
	LSL	Local Surface Level
	LWS	Low Water Spring
M		
	MOC	Ministry of Communications
	MOF	Ministry of Finance
	MSL	Mean Sea Level
N		
	NM	Nautical Mile (1852m)
	NPV	Net Present Value
O		
	OCC	Opportunity Cost of Capital
	OD	Origin and Destination
	OECP	Oversea Economic Cooperation Fund, Japan
P		
	PASS	Passenger vessel

	Pax.	Passenger
	P.C.	Precast Concrete
	PELINDO	Indonesian Sea Port Cooperation
	PELNI	Indonesian National Shipping Company
	PIANC	Permanent International Association of Navigation Congress
	PT.	Limited Company
R		
	RC	Reinforced Concrete
	REPELITA VI	Five Year National Development Plan in the Sixth
	Ro-Ro	Roll on Roll off type vessel
	Rp.	Rupiah
S		
	SCF	Standard Conversion Factor
	SMB	Srendrup Munk Bretschneider
T		
	T.A	Truk Air (non motor boat)
	TTM	Monthly Average Exchange Rate
U		
	UPT	Technical Implementation Unit
	USAID	United States Agency for International Development
	USD	US Dollar
V		
	VAT	Value Added Tax

CONTENTS

LIST OF ABBREVIATIONS

PART 1 PRESENT CONDITIONS

PART 2 LONG-TERM DEVELOPMENT PLAN

PART 3 SHORT-TERM DEVELOPMENT PLAN

Chapter 1	Selection of Ferry Routes for the Short-term Development Plan	1-1
1.1	Traffic Demand Forecast for the Short-term Development Plan	1-1
1.2	Evaluation of Ferry Routes for the Long-term Development Plan	1-1
1.2.1	Basic Premise for Selection of Ferry Routes	1-1
1.2.2	Evaluation Items of Ferry Routes	1-1
1.3	Selection of Ferry Routes for the Short-term Development Plan	1-3
1.3.1	Selection of Ferry Routes	1-3
1.3.2	Proposed Routes for the Short-term Development Plan	1-4
Chapter 2	Natural Conditions	2-1
2.1	Location	2-1
2.2	Topographic Conditions	2-1
2.2.1	Surabaya	2-2
2.2.2	Banjarmasin	2-3
2.2.3	Labuhan Bajo	2-3
2.2.4	Selayar (Patumbukan)	2-3
2.2.5	Wahai	2-4
2.2.6	Babang	2-4
2.2.7	Manokwari (Sowi)	2-4
2.2.8	Biak (Mokmer)	2-5
2.3	Tide	2-5
2.4	Current	2-6
2.5	Wave	2-7
2.6	Subsoil Conditions	2-13
Chapter 3	Ferry Terminal Development Plan	3-1
3.1	Factors Concerned with Ferry Terminal Planning	3-1
3.1.1	Required Ferry Terminal Facilities	3-1
3.2	Ferry Terminal Development Plan at Each Site	3-2
3.2.1	Basic Premises for Ferry Terminal Development Plan	3-2
3.2.2	Proposed Ferry Terminal Development Plan at Each Site	3-3

Chapter 4	Preliminary Design, Cost Estimation and Construction Schedule	4-1
4.1	Preliminary Design	4-1
4.1.1	Design Criteria	4-1
4.1.2	Mooring Facilities	4-7
4.1.3	On Land Facilities	4-48
4.1.4	Electricity and Water Supply	4-51
4.2	Cost Estimation	4-54
4.2.1	General	4-54
4.2.2	Current Prices of Construction-related Commodities	4-54
4.2.3	Current Situations of Construction Cost	4-55
4.2.4	Basic Cost of Construction Work	4-57
4.2.5	Estimation of Construction Cost of Planned Terminals	4-60
4.3	Construction Schedule	4-63
4.3.1	Construction Schedule and Construction Methods	4-63
4.3.2	Surabaya - Banjarmasin Route	4-63
4.3.3	Selayar - Labuhan Bajo Route	4-69
4.3.4	Wahai - Babang Route	4-73
4.3.5	Manokwari - Biak Route	4-77
4.3.6	Implementation Program	4-80
Chapter 5	Environmental Impact Assessment	5-1
5.1	General	5-1
5.2	Legal Aspect and Environmental Policy	5-1
5.3	Prediction and Evaluation of the Environmental Impact	5-1
5.4	Study Method	5-2
5.5	Surabaya	5-3
5.6	Banjarmasin	5-4
5.7	Selayar (Patumbukang)	5-5
5.8	Labuhan Bajo	5-7
5.9	Manokwari (Sowi)	5-8
5.10	Biak (Mokmer)	5-9
5.11	Wahai	5-10
5.12	Babang	5-11
5.13	Result of EIA	5-12
Chapter 6	Ferry Operation Planning	6-1
6.1	General Conditions on Ferry Operation	6-1
6.1.1	Transportation Volume	6-1
6.1.2	Boat Size and Capacity	6-1
6.1.3	Frequency and Time Schedule of Service	6-2

6.1.4	Setting of Operation Schedule	6-3
6.2	Operation Program of the Four Routes	6-4
6.2.1	Surabaya - Banjarmasin	6-4
6.2.2	Selayar - Labuhan Bajo	6-4
6.2.3	Manokwari - Biak	6-5
6.2.4	Wahai - Babang	6-6
6.2.5	Operation Capacity of Each Route	6-6
6.3	Navigation Safety	6-8
6.3.1	Ferry Boats Safety	6-8
6.3.2	Navigational Safety	6-8
6.3.3	Operation Safety	6-9
6.3.4	Maintenance of Ferry Boats	6-9
6.4	Recommendation on Ferry Operation	6-10
Chapter 7	Ferry System Management	7-1
7.1	Management and Operation of Ferry Transportation in the Short-term Development Plan	7-1
7.1.1	Enhancement of Profitability	7-1
7.1.2	Establishment of an Efficient PT. ASDP Organization	7-2
7.1.3	System of Ferry Service	7-3
7.2	Terminal Management and Operation in the Short-term Development Plan	7-4
7.2.1	Enhancement of Profitable Management and Subsidy System	7-4
7.2.2	Setting of Proper Terminal Tariff	7-5
7.2.3	Terminal Management Body	7-6
Chapter 8	Economic Analysis	8-1
8.1	Objectives and Methodology of the Economic Analysis	8-1
8.1.1	Objective	8-1
8.1.2	Methodology	8-1
8.2	Prerequisites of the Economic Analysis	8-2
8.2.1	Base Year	8-2
8.2.2	Implementation Schedule	8-3
8.2.3	Project Life	8-3
8.2.4	Foreign Exchange Rate	8-3
8.2.5	Residual Values	8-3
8.3	With Case and Without Case	8-3
8.3.1	With Case	8-3
8.3.2	Without Case	8-3
8.3.3	Traffic Demand of Projects	8-4

8.4	Benefits of the Projects	8-5
8.4.1	Benefit Items	8-5
8.4.2	Calculation of Benefits	8-5
8.5	Costs of the Projects	8-9
8.5.1	Cost Items	8-9
8.6	Economic Pricing	8-10
8.7	Economic Internal Rate of Return (EIRR)	8-11
8.7.1	Calculation of the EIRR	8-11
8.7.2	Sensitivity Analysis	8-12
8.8	Evaluation	8-13
Chapter 9	Financial Analysis	9-1
9.1	Presuppositions of the Financial Analysis	9-1
9.1.1	Scope of the Financial Analysis	9-1
9.1.2	Financial Conditions of Port Management Bodies	9-2
9.1.3	Financial Conditions of Shipping Management Bodies	9-4
9.2	Evaluation	9-6
9.2.1	Evaluation of Financial Soundness of Port Management Bodies	9-6
9.2.2	Evaluation of Financial Soundness of Shipping Management Bodies	9-10
9.3	Sensitivity Analysis	9-11
9.3.1	Sensitivity Analysis for Port Management Bodies	9-11
9.3.2	Sensitivity Analysis for Shipping Management Bodies	9-14
9.4	Conclusions	9-15
CONCLUSIONS AND RECOMMENDATIONS		1

Appendix

LIST OF TABLES

PART 3 SHORT-TEERM DEVELOPMENT PLAN

Table 1.1.1	Demand Forecast for the Short-term Development Plan	1-2
Table 1.3.1	Selection of Ferry Routes for the Short-term development Plan	1-5
Table 2.1.1	Terminal Location	2-1
Table 2.2.1	Benchmarks	2-2
Table 2.3.1	Tide Elevations in Each Terminal Site	2-5
Table 2.3.2	Tidal Constituents in Each Terminal Site	2-6
Table 2.3.3	Tidal Form Type	2-6
Table 2.4.1	Current Speed and Direction	2-7
Table 2.5.1(1)	Frequency of Occurrence of Wind (Hasanuddin)	2-9
Table 2.5.1(2)	Frequency of Occurrence of Wave (Patumbukan)	2-9
Table 2.5.2(1)	Frequency of Occurrence of Wind (Babullah)	2-10
Table 2.5.2(2)	Frequency of Occurrence of Wave (Babang)	2-10
Table 2.5.3(1)	Frequency of Occurrence of Wind (Manokwari)	2-11
Table 2.5.3(2)	Frequency of Occurrence of Wave (Manokwari)	2-11
Table 2.5.4	Possible Maximum Wave Height	2-12
Table 2.6.1	Summary of Soil Investigation	2-15
Table 3.1.1	Required Number of Berths at Each Terminal in the Short-term Development Plan	3-1
Table 4.1.1	Standard Dimensions and Capacity of Planned Ferry Boats	4-1
Table 4.1.2	Berthing Force and Mooring Post Capacity	4-2
Table 4.1.3	Tide Levels	4-2
Table 4.1.4	Current Velocity	4-2
Table 4.1.5	Design Waves	4-2
Table 4.1.6 (1)	Sub-soil condition of Surabaya Site	4-3
Table 4.1.6 (2)	Sub-soil condition of Banjarmasin Site	4-3
Table 4.1.6 (3)	Sub-soil condition of Selayar Site	4-4
Table 4.1.6 (4)	Sub-soil condition of Labuhan Bajo Site	4-4
Table 4.1.6 (5)	Sub-soil condition of Wahai Site	4-4
Table 4.1.6 (6)	Sub-soil condition of Babang Site	4-5
Table 4.1.6 (7)	Sub-soil condition of Manokwari Site	4-5
Table 4.1.6 (8)	Sub-soil condition of Biak Site	4-5
Table 4.1.7	Design Seismic Coefficient for Each Terminal	4-6
Table 4.1.8	Calculation of Length of Movable Bridge (MB) of Each Terminal	4-16

Table 4.1.9	Reclamation Volume for Land Preparation	4-48
Table 4.1.10	Required Area of Terminal Building of Each Terminal	4-49
Table 4.1.11	Required Area of Parking Lots of Each Terminal	4-50
Table 4.2.1	Combined Construction Cost and Their Changes between August 1997 and February 1998	4-59
Table 4.2.2	Summary of Construction Cost	4-62
Table 4.3.1(1)	Construction Schedule of Ferry Terminal (Surabaya – Banjarmasin Route)	4-67
Table 4.3.1(2)	Yearly Construction Cost of Ferry Terminal (Surabaya – Banjarmasin Route)	4-68
Table 4.3.2(1)	Construction Schedule of Ferry Terminal (Selayar – Labuhan Bajo Route)	4-71
Table 4.3.2(2)	Yearly Construction Cost of Ferry Terminal (Selayar – Labuhan bajo Route)	4-72
Table 4.3.3(1)	Construction Schedule of Ferry Terminal (Wahai – Babang Route)	4-75
Table 4.3.3(2)	Yearly Construction Cost of Ferry Terminal (Wahai – Babang Route)	4-76
Table 4.3.4(1)	Construction Schedule of Ferry Terminal (Manokwari – Biak Route)	4-78
Table 4.3.4(2)	Yearly Construction Cost of Ferry Terminal (Manokwari – Biak Route)	4-79
Table 4.3.5	Implementation Program	4-81
Table 5.13.1	Result of EIA	5-13
Table 6.1.1	Transportation Volume	6-1
Table 6.1.2	Ferry Boat Size and Capacity	6-2
Table 6.2.1	Operation Program of Surabaya - Banjarmasin Route	6-4
Table 6.2.2	Operation Program of Slayar - Labuhan Bajo Route.	6-5
Table 6.2.3	Operation Program of Manokwali - Biak Route.	6-5
Table 6.2.4	Operation Program of Wahai - Babang Route.	6-6
Table 6.2.5	Operation Capacities on Each Route	6-7
Table 6.2.6	Maximum Transportation Capacity of Route	6-7
Table 8.3.1	Size and Cruising Speed of Boat/Vessel in Both Cases	8-4
Table 8.4.1	Unit Passenger Time Value for Each Route	8-8
Table 8.7.1	Summary of Economic Analysis Results (Base Case)	8-11
Table 8.7.2	Results of EIRR (Pattern A)	8-13
Table 8.7.3	Results of EIRR (Pattern B)	8-13
Table 9.2.1	Required Operating Income in Surabaya-Banjarmasin Route	9-8

Table 9.2.2	Subsidy for Operating Cost in Selayar-Labuhan Bajo Route ····	9-8
Table 9.2.3	Subsidy for Operating Cost in Manokwari-Biak Route ······	9-9
Table 9.2.4	Subsidy for Operating Cost in Wahai-Babang Route ······	9-9
Table 9.2.5	The Assessment of the Financial Soundness to Each Route ····	9-10
Table 9.3.1	Required Operating Income on Sensitivity Analysis in Surabaya-Banjarmasin Route ······	9-12
Table 9.3.2	Subsidy for Operating Cost on Sensitivity Analysis in Selayar- Labuhan Bajo Route ······	9-12
Table 9.3.3	Subsidy for Operating Cost on Sensitivity Analysis in Manokwari-Biak Route ······	9-13
Table 9.3.4	Subsidy for Operating Cost on Sensitivity Analysis in Wahai- Babang Route ······	9-13
Table 9.3.5	The Assessment of the Financial Soundness to Each Route on Sensitivity Analysis ······	9-14

LIST OF FIGURES

PART 3 SHORT-TEERM DEVELOPMENT PLAN

Figure 1.3.1	Ferry Routes for the Short-term Development Plan	1-7
Figure 3.2.1	Layout Plan of Surabaya Ferry Terminal	3-8
Figure 3.2.2	Layout Plan of Banjarmasin Ferry Terminal	3-9
Figure 3.2.3	Layout Plan of Selayar Ferry Terminal	3-10
Figure 3.2.4	Layout Plan of Labuhan Bajo Ferry Terminal	3-11
Figure 3.2.5	Layout Plan of Manokwari Ferry Terminal	3-12
Figure 3.2.6	Layout Plan of Biak Ferry Terminal	3-13
Figure 3.2.7	Layout Plan of Wahai Ferry Terminal	3-14
Figure 3.2.8	Layout Plan of Babang Ferry Terminal	3-15
Figure 4.1.1(1)	Layout of Mooring Facilities of Surabaya Ferry Terminal	4-10
Figure 4.1.1(2)	Typical Cross Section of Detached Pier of Surabaya	4-11
Figure 4.1.1(3)	Unit Module of Detached Platform of Surabaya	4-12
Figure 4.1.1(4)	Plan and Cross Section of Access Bridge of Surabaya	4-13
Figure 4.1.1(5)	Typical Cross Section of Access Bridge of Surabaya	4-14
Figure 4.1.1(6)	Typical Cross Section of Causeway of Surabaya	4-15
Figure 4.1.2(1)	Layout of Mooring Facilities of Banjarmasin Ferry Terminal	4-20
Figure 4.1.2(2)	Typical Cross Section of Revetment of Banjarmasin	4-21
Figure 4.1.3(1)	Layout of Mooring Facilities and Harbor Basin of Selayar Ferry Terminal	4-25
Figure 4.1.3(2)	General Plan of Access Channel and Basin for Selayar Ferry Terminal	4-26
Figure 4.1.4	Layout of Mooring Facilities of Labuhan Bajo Ferry Terminal	4-30
Figure 4.1.5	Layout of Mooring Facilities of Wahai Ferry Terminal	4-31
Figure 4.1.6	Layout of Mooring Facilities of Babang Ferry Terminal	4-34
Figure 4.1.7	Layout of Mooring Facilities of Biak Ferry Terminal	4-38
Figure 4.1.8	Layout of Mooring Facilities of Manokwari Ferry Terminal	4-39
Figure 4.1.9	Typical Cross Section of Breasting Dolphin	4-40
Figure 4.1.10	Typical Cross Section of Mooring Dolphin	4-41
Figure 4.1.11	Plan and Typical Cross Section of Movable Bridge	4-42
Figure 4.1.12	Typical Cross Section of Bow Breasting Dolphin	4-43
Figure 4.1.13	Typical Cross Section of Causeway	4-44
Figure 4.1.14	Typical Cross Section of Trestle	4-45
Figure 4.1.15	Unit Module of Landing Staff	4-46
Figure 4.1.16	Typical Cross Section of Revetment	4-47

Figure 8.1.1	Flow Chart of Economic Analysis Procedure	8-2
Figure 8.7.1	Results of EIRR by the Fluctuation of Cost and Demand (Pattern B)	8-14

LIST OF TABLES IN APPENDICES

PART 3 SHORT-TERM DEVELOPMENT PLAN

Table A1.1.1	Passenger OD in 2004	A-1
Table A1.1.2	Cargo OD in 2004	A-1
Table A1.1.3	Ferry Passenger OD in 2004	A-3
Table A1.1.4	Ferry Cargo OD in 2004	A-3
Table A1.1.5	Four-wheel Vehicle OD carried by ferry in 2004	A-5
Table A1.3.1	Selection of Ferry Routes for the Short-term Development Plan	A-7
Table A4.1.1	Importance Coefficient, I	A-36
Table A4.1.2	Structural Type and Factor K	A-37
Table A4.2.1	Estimation of Construction Cost (Surabaya)	A-42
Table A4.2.2	Estimation of Construction Cost (Banjarmasin)	A-43
Table A4.2.3	Estimation of Construction Cost (Patumbukan / Selayar)	A-44
Table A4.2.4	Estimation of Construction Cost (Labuhan Bajo / Flores)	A-45
Table A4.2.5	Estimation of Construction Cost (Wahai / Seram)	A-46
Table A4.2.6	Estimation of Construction Cost (Babang / Bacan)	A-47
Table A4.2.7	Estimation of Construction Cost (Sowi / Manokwari)	A-48
Table A4.2.8	Estimation of Construction Cost (Mokmer / Biak)	A-49
Table A5.1.1	Data of Fishing Boats	A-51
Table A5.1.2	Number of Fishermen (1993-1996)	A-52
Table A5.1.3	Analysis of Ground Cover Ridge Rock Ecosystem	A-54
Table A5.1.4	Coral Colony Species	A-54
Table A5.1.5	Percent Cover of Benthic Life Form	A-56
Table A5.1.6	Percent Cover of Benthic Life Form	A-57
Table A5.1.7	Percent Cover of Benthic Life Form	A-59
Table A5.1.8	Percent Cover of Benthic Life Form	A-60
Table A5.1.9	List of Protected Fauna	A-61
Table A5.1.10	Analysis of Ground Cover Ridge Rock Ecosystem	A-62
Table A5.1.11	Coral Colony Species	A-63
Table A5.1.12	Summary of Chemical Test Results of Seawater Samples	A-64
Table A5.1.13	Summary of Chemical Test Results of Seabed Samples	A-66
Table A5.2.1	Environmental Assessment Summary Matrix : Surabaya	A-77
Table A5.2.2	Environmental Assessment Summary Matrix : Banjarmasin	A-79
Table A5.2.3	Environmental Assessment Summary Matrix : Selayar	A-81
Table A5.2.4	Environmental Assessment Summary Matrix : Labuhan Bajo	A-83
Table A5.2.5	Environmental Assessment Summary Matrix : Manokwari	A-85

Table A5.2.6	Environmental Assessment Summary Matrix : Biak	Λ-87
Table A5.2.7	Environmental Assessment Summary Matrix : Wahai	Λ-89
Table A5.2.8	Environmental Assessment Summary Matrix : Babang	Λ-91
Table A6.2.1	Projection of Operation Programs from 2004 to 2019 (Surabaya - Banjarmasin)	Λ-93
Table A6.2.2	Projection of Operation Programs from 2004 to 2019 (Selayar - Labuhan Bajo)	Λ-95
Table A6.2.3	Projection of Operation Programs from 2004 to 2019 (Manokwali - Biak)	Λ-97
Table A6.2.4	Projection of Operation Programs from 2004 to 2019 (Wahai - Babang)	Λ-99
Table A8.3.1(1)	Traffic Demand by Year	Λ-103
Table A8.3.1(2)	Traffic Demand by Year	Λ-104
Table A8.4.1	Estimation of Cargo Handling Cost by Year	Λ-105
Table A8.4.2	Estimation of Sea Transportation Cost by Year	Λ-106
Table A8.4.3	Economic Unit Vehicle Operating Cost	Λ-107
Table A8.4.4	Estimation of Land Transportation Cost	Λ-107
Table A8.4.5	Estimation of Unit Passenger Time Value	Λ-108
Table A8.4.6	Estimation of Unit Vehicle Time Value	Λ-109
Table A8.4.7	Estimation of Saving Of Travel Time Cost for Each Route	Λ-110
Table A8.6.1	Estimation of Standard Conversion Factor	Λ-112
Table A8.6.2	Estimation of Conversion Factor for Unskilled Labor	Λ-114
Table A8.6.3	Estimated Terminal Construction Cost at Economic Prices	Λ-114
Table A8.6.4	Estimated Terminal Operation and Maintenance Cost at Economic Prices	Λ-115
Table A8.6.5(1)	Estimated Operation and Maintenance Cost of New Ferry Boat at Economic Prices	Λ-116
Table A8.6.5(2)	Estimated Operation and Maintenance Cost of Used Ferry Boat at Economic Prices	Λ-117
Table A8.6.6	Estimation of Conversion Factor for Cargo Handling Cost	Λ-117
Table A8.7.1(1)	Economic Analysis for Surabaya-Banjarmasin Route (Pattern A)	Λ-119
Table A8.7.1(2)	Economic Analysis for Surabaya-Banjarmasin Route (Pattern B)	Λ-120
Table A8.7.2(1)	Economic Analysis for Selayar-Labuhan Bajo Route (Pattern A)	Λ-121
Table A8.7.2(2)	Economic Analysis for Selayar-Labuhan Bajo Route (Pattern B)	Λ-122

Table A8.7.3(1)	Economic Analysis for Manokwari-Biak Route (Pattern A) ····	A-123
Table A8.7.3(2)	Economic Analysis for Manokwari-Biak Route (Pattern B) ····	A-124
Table A8.7.4(1)	Economic Analysis for Wahai-Babang Route (Pattern A) ····	A-125
Table A8.7.4(2)	Economic Analysis for Wahai-Babang Route (Pattern B) ·····	A-126
Table A9.1.1	Port Terminal Tariff ·····	A-127
Table A9.1.2	Yearly Construction Cost of Each Route ·····	A-128
Table A9.1.3	Construction Cost Divided Local and Foreign Loan of Each Route ·····	A-128
Table A9.1.4	Service Life of Terminal Facilities ·····	A-129
Table A9.2.1	Subsidy for Investment Related in Surabaya-Banjarmasin Route	A-130
Table A9.2.2	Subsidy for Investment Related in Selayar-Labuhan Bajo Route	A-130
Table A9.2.3	Subsidy for Investment Related in Manokwari-Biak Route ····	A-131
Table A9.2.4	Subsidy for Investment Related in Wahai-Babang Route ·····	A-131
Table A9.2.5	Projected Financial Statement in Surabaya-Banjarmasin Route ·	A-133
Table A9.2.6	Projected Financial Statement in Selayar-Labuhan Bajo Route ·	A-135
Table A9.2.7	Projected Financial Statement in Manokwari-Biak Route ·····	A-137
Table A9.2.8	Projected Financial Statement in Wahai-Babang Route ·····	A-139
Table A9.2.9	Projected Profit and Loss Statement for Case 1 in Surabaya- Banjarmasin Route (Shpping Management Body) ·····	A-141
Table A9.2.10	Projected Profit and Loss Statement for Case 2 in Surabaya- Banjarmasin Route (Shpping Management Body) ·····	A-141
Table A9.2.11	Projected Profit and Loss Statement for Case 3 in Surabaya- Banjarmasin Route (Shpping Management Body) ·····	A-143
Table A9.2.12	Projected Profit and Loss Statement for Case 4 in Surabaya- Banjarmasin Route (Shpping Management Body) ·····	A-143
Table A9.2.13	Projected Profit and Loss Statement for Case 1 in Selayar- Labuhan Bajo Route (Shpping Management Body) ·····	A-145
Table A9.2.14	Projected Profit and Loss Statement for Case 2 in Selayar- Labuhan Bajo Route (Shpping Management Body) ·····	A-145
Table A9.2.15	Projected Profit and Loss Statement for Case 3 in Selayar- Labuhan Bajo Route (Shpping Management Body) ·····	A-147
Table A9.2.16	Projected Profit and Loss Statement for Case 4 in Selayar- Labuhan Bajo Route (Shpping Management Body) ·····	A-147
Table A9.2.17	Projected Profit and Loss Statement for Case 1 in Manokwari- Biak Route (Shpping Management Body) ·····	A-149
Table A9.2.18	Projected Profit and Loss Statement for Case 2 in Manokwari- Biak Route (Shpping Management Body) ·····	A-149
Table A9.2.19	Projected Profit and Loss Statement for Case 3 in Manokwari-	

	Biak Route (Shpping Management Body) ·····	A-151
Table A9.2.20	Projected Profit and Loss Statement for Case 4 in Manokwari-Biak Route (Shpping Management Body) ·····	A-151
Table A9.2.21	Projected Profit and Loss Statement for Case 1 in Wahai-Babang Route (Shpping Management Body) ·····	A-153
Table A9.2.22	Projected Profit and Loss Statement for Case 2 in Wahai-Babang Route (Shpping Management Body) ·····	A-153
Table A9.2.23	Projected Profit and Loss Statement for Case 3 in Wahai-Babang Route (Shpping Management Body) ·····	A-155
Table A9.2.24	Projected Profit and Loss Statement for Case 4 in Wahai-Babang Route (Shpping Management Body) ·····	A-155
Table A9.3.1	Subsidy for Investment Related on Sensitivity Analysis in Surabaya-Banjarmasin Route ·····	A-157
Table A9.3.2	Subsidy for Investment Related on Sensitivity Analysis in Selayar-Labuhan Bajo Route ·····	A-157
Table A9.3.3	Subsidy for Investment Related on Sensitivity Analysis in Manokwari-Biak Route ·····	A-158
Table A9.3.4	Subsidy for Investment Related on Sensitivity Analysis in Wahai-Babang Route ·····	A-158
Table A9.3.5	Projected Profit and Loss Statement for Case 1 on Sensitivity Analysis in Surabaya-Banjarmasin Route (Shpping Management Body) ·····	A-159
Table A9.3.6	Projected Profit and Loss Statement for Case 2 on Sensitivity Analysis in Surabaya-Banjarmasin Route (Shpping Management Body) ·····	A-159
Table A9.3.7	Projected Profit and Loss Statement for Case 3 on Sensitivity Analysis in Surabaya-Banjarmasin Route (Shpping Management Body) ·····	A-161
Table A9.3.8	Projected Profit and Loss Statement for Case 4 on Sensitivity Analysis in Surabaya-Banjarmasin Route (Shpping Management Body) ·····	A-161
Table A9.3.9	Projected Profit and Loss Statement for Case 1 on Sensitivity Analysis in Selayar-Labuhan Bajo Route (Shpping Management Body) ·····	A-163
Table A9.3.10	Projected Profit and Loss Statement for Case 2 on Sensitivity Analysis in Selayar-Labuhan Bajo Route (Shpping Management Body) ·····	A-163
Table A9.3.11	Projected Profit and Loss Statement for Case 3 on Sensitivity	

	Analysis in Selayar-Labuhan Bajo Route (Shpping Management Body)	A-165
Table A9.3.12	Projected Profit and Loss Statement for Case 4 on Sensitivity Analysis in Selayar-Labuhan Bajo Route (Shpping Management Body)	A-165
Table A9.3.13	Projected Profit and Loss Statement for Case 1 on Sensitivity Analysis in Manokwari-Biak Route (Shpping Management Body)	A-167
Table A9.3.14	Projected Profit and Loss Statement for Case 2 on Sensitivity Analysis in Manokwari-Biak Route (Shpping Management Body)	A-169
Table A9.3.15	Projected Profit and Loss Statement for Case 3 on Sensitivity Analysis in Manokwari-Biak Route (Shpping Management Body)	A-167
Table A9.3.16	Projected Profit and Loss Statement for Case 4 on Sensitivity Analysis in Manokwari-Biak Route (Shpping Management Body)	A-169
Table A9.3.17	Projected Profit and Loss Statement for Case 1 on Sensitivity Analysis in Wahai-Babang Route (Shpping Management Body)	A-171
Table A9.3.18	Projected Profit and Loss Statement for Case 2 on Sensitivity Analysis in Wahai-Babang Route (Shpping Management Body)	A-171
Table A9.3.19	Projected Profit and Loss Statement for Case 3 on Sensitivity Analysis in Wahai-Babang Route (Shpping Management Body)	A-173
Table A9.3.20	Projected Profit and Loss Statement for Case 4 on Sensitivity Analysis in Wahai-Babang Route (Shpping Management Body)	A-173

LIST OF FIGURES IN APPENDICES

PART 3 SHORT-TERM DEVELOPMENT PLAN

Figure A2.2.1	Survey Map of Lamong Bay Site (Surabaya)	A-11
Figure A2.2.2	Survey Map of Banjarmasin Site	A-15
Figure A2.2.3	Survey Map of Labuhan Bajo Site	A-17
Figure A2.2.4	Survey Map of Patumbukan Site (Selayar)	A-19
Figure A2.2.5	Survey Map of Wahai Site	A-23
Figure A2.2.6	Survey Map of Babang Site	A-25
Figure A2.2.7	Survey Map of South Sowi Site (Manokwari)	A-27
Figure A2.6.1	Soil Profile of Lamong Bay Site (Surabaya)	A-29
Figure A2.6.2	Soil Profile of Banjarmasin Site	A-30
Figure A2.6.3	Soil Profile of Labuhan Bajo Site	A-31
Figure A2.6.4	Soil Profile of Patumbukan Site (Selayar)	A-32
Figure A2.6.5	Soil Profile of Wahai Site	A-33
Figure A2.6.6	Soil Profile of Babang Site	A-34
Figure A2.6.7	Soil Profile of South Sowi Site (Manokwari)	A-35
Figure A4.1.1	Seismicity Zones and Regional Coefficient	A-38
Figure A6.2.1(1)	Transition of Demand and Capacity on Peak-day (Surabaya - Banjarmasin)	A-93
Figure A6.2.1(2)	An Example of Operation Schedule (Surabaya - Banjarmasin) ..	A-94
Figure A6.2.2(1)	Transition of Demand and Capacity on Peak-day (Selayar - Labuhan Bajo)	A-95
Figure A6.2.2(2)	An Example of Operation Schedule (Selayar - Labuhan Bajo) ..	A-96
Figure A6.2.3(1)	Transition of Demand and Capacity on Peak-day (Manokwali - Biak)	A-97
Figure A6.2.3(2)	An Example of Operation Schedule (Manokwali - Biak)	A-98
Figure A6.2.4(1)	Transition of Demand and Capacity on Peak-day (Wahai - Babang)	A-99
Figure A6.2.4(2)	An Example of Operation Schedule (Wahai - Babang)	A-100
Figure A8.3.1	Conceptual Route Map	A-101
Figure A9.1.1	Scope of Financial Analysis	A-128

PART 3

SHORT-TERM DEVELOPMENT PLAN

Chapter 1 Selection of Ferry Routes for the Short-term Development Plan

1.1 Traffic Demand Forecast for the Short-term Development Plan

1. Traffic demand for the short-term development plan is forecasted in the same manner as the traffic demand forecast for the long-term development plan.
2. The target year of the short-term development plan is 2004. In addition, the traffic demands in the years of 2008 and 2013 are forecasted as the midterm numerical values.
3. Ferry traffic demands of Category-1 and -2 ferry routes in the year of 2004 are estimated based on the passenger and cargo OD tables. The forecasts in the year of 2008 and 2013 are calculated based on the assumption that the demands increase every year from 2004 to 2019 at the same increase rate.
4. Traffic demands of Category-3 are forecasted using the same equation as that for the long-term development plan.
5. The projection of ferry passengers, cargoes, four-wheel vehicles and two-wheel vehicles for selection of the short-term development plan is shown in Table 1.1.1.

1.2 Evaluation of Ferry Routes for the Long-term Development Plan

1.2.1 Basic Premise for Selection of Ferry Routes

6. In order to select the ferry routes for the short-term development plan, the selected nine routes in the long-term development plan are categorized into the long distance routes and the middle and short distance routes.
7. The long distance routes are located on the trunk lines connecting main regions, which are regarded as the interregional routes. The middle and short distance routes connects the islands of eastern part of Indonesia, especially in Maluku and Irian Jaya.

1.2.2 Evaluation Items of Ferry Routes

8. In the selection of Ferry routes for short-term development plan, it is necessary to examine profitability and urgency of the ferry routes taking into consideration

Table 1.1.1 Demand Forecast for the Short-term Development Plan

	PASSENGER			CARGO			4 WHEEL-VEHICLE			2 WHEEL-VEHICLE						
	2004	2008	2013	2004	2008	2013	2004	2008	2013	2004	2008	2013				
	unit : ton						2004	2008	2013	2004	2008	2013				
Long Distance Route																
Surabaya	559,800	770,700	1,149,300	1,856,500	166,500	250,500	414,900	750,000	63,550	90,460	140,110	234,960	5,740	7,910	11,790	19,040
Jakarta	254,000	339,600	488,200	754,700	75,400	110,400	176,200	304,900	28,830	39,870	59,500	95,520	2,530	3,380	4,860	7,520
Surabaya	168,500	234,100	333,200	578,500	50,000	76,100	127,500	233,700	19,110	27,480	43,060	73,210	1,670	2,320	3,510	5,740
Kendari	126,000	182,200	289,100	502,900	37,400	59,200	104,400	203,200	14,300	21,380	35,250	63,660	1,260	1,830	2,900	5,040
Ambon	74,800	103,300	154,700	291,200	22,200	33,600	55,800	101,500	8,490	12,130	18,840	31,800	790	1,040	1,560	2,530
Middle and Short Distance Route																
Selayar	84,500	119,800	185,400	313,000	16,700	26,700	47,100	91,100	9,550	13,360	20,390	33,950	930	1,310	2,030	3,430
Manokwari	72,600	101,500	154,300	255,200	14,400	22,600	39,200	74,300	8,230	11,310	16,970	27,670	790	1,100	1,680	2,770
Wahai	47,700	71,900	120,000	222,100	9,400	16,000	30,500	64,600	5,370	8,010	13,200	24,090	510	760	1,270	2,350
Patani	44,600	68,100	115,400	217,500	8,800	15,200	29,300	63,300	5,030	7,610	12,680	23,590	470	720	1,230	2,310
TRUCK																
BUS																
SEDAN PICKUP																
LARGE TRUCK AND BUS																
Long Distance Route																
Surabaya	34,970	49,750	77,060	1,298,230	9,540	13,570	21,020	35,240	19,070	27,140	42,030	70,490	28,930	41,160	63,750	106,910
Jakarta	15,860	21,930	32,720	52,530	4,320	5,980	8,930	14,330	8,650	11,960	17,850	28,660	13,120	18,140	27,070	43,460
Surabaya	10,510	15,120	23,680	40,270	2,870	4,120	6,460	10,980	5,740	8,240	12,920	21,960	8,700	12,500	19,590	33,310
Kendari	7,860	11,760	19,380	35,010	2,150	3,210	5,290	9,550	4,290	6,410	10,580	19,100	6,510	9,730	16,040	28,970
Ambon	4,670	6,670	10,360	17,490	1,270	1,820	2,830	4,770	2,550	3,640	5,650	9,540	3,860	5,520	8,570	14,470
Middle and Short Distance Route																
Selayar	5,250	7,340	11,210	18,670	960	1,340	2,040	3,400	3,340	4,680	7,140	11,880	4,030	5,640	8,610	14,340
Manokwari	4,530	6,220	9,330	15,230	820	1,130	1,700	2,770	2,880	3,960	5,940	9,690	3,480	4,780	7,170	11,700
Wahai	2,950	4,410	6,970	13,240	540	800	1,320	2,410	1,880	2,800	4,620	8,420	2,270	3,380	5,580	10,170
Patani	2,770	4,190	6,980	12,970	500	760	1,270	2,360	1,760	2,660	4,440	8,260	2,130	3,220	5,360	9,970

Source : Study Team

investment cost, natural conditions and environmental influence.

9. The ferry demand volumes of passengers/ vehicles/ cargoes should be most important items for the evaluation of ferry service. Indonesian Government's policy to develop the economically less developed regions should also be taken into account. Accordingly the following items are selected for easy comparison and evaluation among the selected nine routes.

- 1) Ferry transport demand
 - Passenger volume in 2004 and 2019
 - Four-wheel vehicle volume in 2004 and 2019
(these volumes are subdivided into truck, bus and sedan & pickup)
 - Cargo volume in 2004 and 2019
- 2) Construction cost for ferry terminal on each route in 2019
 - Construction cost of the new ferry terminal including offshore and on shore facilities
- 3) Ferry boats operation cost for each route in 2004 and 2019
 - Procurement cost and operation costs of new or used ferry boats to be engaged on the routes
- 4) Demand efficiency
 - Tariff income potential of ferry transportation; total person-miles, vehicle numbers -miles, tons-miles
 - Ratio of ferry terminal construction cost per one passenger, vehicle and ton
 - Ratio of ferry boats operation cost per one passenger, vehicle and ton
- 5) Urgency of ferry route development
 - Necessity of urgent ferry route development considering the Indonesian Government's eastern region development plan

1.3 Selection of Ferry Routes for the Short-term Development Plan

1.3.1 Selection of Ferry Routes

10. Five long distance and four middle and short distance routes have been evaluated separately according to the above mentioned evaluation items.

11. The demand potential and ratio of ferry terminal construction cost and ferry boats operation cost are calculated by the following formulas.

- Tariff income potential = $\frac{\text{Ferry transport demand (passenger, vehicle and cargo)}}{\text{Ferry transport demand (Passenger, Vehicle and cargo)}} \times \text{Distance}$
- Ratio of ferry terminal construction cost = $\frac{\text{Ferry terminal construction cost}}{\text{Ferry transport demand (Passenger, Vehicle and cargo)}}$
- Ratio of ferry boats operation cost = $\frac{\text{Ferry boats operation cost}}{\text{Ferry transport demand (Passenger, vehicle and cargo)}}$

12. The results of selection are as follows.

13. Regarding the selection of the long distance routes, Surabaya - Banjarmasin route is most superior among the five routes from the point of view of the development efficiency.

14. Concerning the middle and short distance routes, Selayar - Labuhan Bajo route is most superior among the four routes from the point of view of the development efficiency, while, Patani - Sorong route is clearly inferior to the Manokwari - Biak and Wahai - Babang routes.

15. Comparing the routes of Manokwari - Biak and Wahai - Babang, both routes are evaluated highly, especially in the terms of ratio of ferry terminal construction cost.

16. Table 1.3.1 shows the selection of ferry routes for the short-term development plan including those which the Indonesian government suggested the study team to include. The evaluation ranks are shown in Appendices A1.3.1.

1.3.2 Proposed Routes for the Short-term Development Plan

17. According to the above mentioned evaluation items and evaluation, the proposed routes for the Feasibility Study are as follows.


Long distance route:	Surabaya - Banjarmasin
Middle and short distance route:	Selayar - Labuhan Bajo
	Manokwari - Biak
	Wahai - Babang

18. The ferry routes proposed for the short-term development plan are shown in Figure 1.3.1.

Table 1.3.1 Selection of Ferry Routes for the Short-term Development Plan

Route Selection for Short-term Development Plan	Evaluation Items and Evaluation														Urgency of Ferry Development	Study Team
	Demand Volume				Cost (Million Rp.)				Development Efficiency							
	2004		2019		Terminal Construction	Ferry boats Operation	2004		2019		2004		2019			
	Passenger Vehicle	Cargo	Passenger Vehicle	Cargo	(Rp.)	(Rp.)	Tariff/Passeng./Vehicle	Tariff/Cargo	Ratio of Terminal (Rp/4)	Ratio of Terminal (Rp/4)	Ratio of Ferry boats (000 Rp.)	Ratio of Ferry boats (000 Rp.)				
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)	(13)	(14)	(15)	(16)	
Long Distant Routes																
Route A																
Surabaya																
Banjarmasin																
Route B																
Jakarta																
Pontianak																
Route C																
Sumbawa																
Ujung Pandang																
Route D																
Kendari																
Ambon																
Route E																
Ambon																
Sorong																
Middle and Short Distant Routes																
Route a																
Selayar																
Labuhan Rajo																
Route b																
Manekwari																
Biak																
Route c																
Wahai																
Darubaung																
Route d																
Patani																
Sorong																

Note: ⊕ First priority, ⊙ Second priority, △ Third priority



- ① Surabaya - Banjarmasin
- ② Selayar - Labuhan Bajo
- ③ Manokwari - Biak
- ④ Wahai - Babang

- Legend
- Proposed Ferry Routes for the Short-term Development Plan
 -** Proposed Ferry Routes for the Long-term Development Plan
 - - - - -** Ferry Routes in Future
 - Existing Ferry Routes
 - - - - -** Ferry Routes under construction

Figure 1.3.1 Ferry Routes for the Short-term Development Plan

Chapter 2 Natural Conditions

2.1 Location

- The locations of each terminal of the study routes are shown below.

Table 2.1.1 Terminal Location

Route	Site	Coordinate	Regency	Province
Surabaya - Banjarmasin	Surabaya (Lamong Bay)	112° 42' 16" E 7° 13' 31" S	(Municipal) Surabaya	East Java
	Banjarmasin (Public Port)	114° 32' 38" E 3° 16' 0" S	(Municipal) Banjarmasin	South Kalimantan
Labuhan Bajo - Selayar	Labuhan Bajo	119° 52' 32" E 8° 29' 27" S	Manggarai	East Nusa Tenggara
	Selayar (Patumbukan)	120° 29' 32" E 6° 23' 34" S	Selayar	South Sulawesi
Wahai - Babang	Wahai	129° 29' 34" E 2° 47' 54" S	Central Maluku	Maluku
	Babang	127° 34' 38" E 0° 37' 20" S	North Maluku	Maluku
Manokwari - Biak	Manokwari (Sowi)	134° 02' 24" E 0° 54' 19" S	Manokwari	Irian Jaya
	Biak (Mokmer)	136° 18' 55" E 1° 11' 54" S	Biak	Irian Jaya

2.2 Topographic Conditions

- A series of topographic surveys was carried out for each terminal (except Biak – Mokmer site which was surveyed in the previous study) from January to March 1998 using the following criteria.

- Mapping Scale: 1:1,000 (Surabaya: 1:4,000)
- Contour Interval: 1m
- Datum Level: Lowest Low Water Spring (LLWS) was established by the result of tide observation at each terminal site and was used as datum level (DL) for mapping work.
- Survey Method: Traverse survey and height difference measurement.
- Bench Marks: At least two benchmarks were established for each terminal site. The location and elevation of each

benchmark is listed in the following table (See Table 2.2.1).

3. A series of hydrographic surveys was conducted simultaneously with the topographic surveys following the criteria below.

- 1) Mapping Scale: 1:1,000 (Surabaya: 1:4,000)
- 2) Contour Interval: 1m
- 3) Datum Level: LLWS
- 4) Survey Method: Measurement of water depth by echo sounder and positioning by GPS.

Table 2.2.1 Benchmarks

Site	Bench Mark	Local Coordinates		Elevation (DL, m)
		East	North	
Surabaya	BM I	10,000.000	10,000.000	+4.270
	BM II	9,973.599	10,195.222	+4.239
Banjarmasin	BM I	226,837.000	9,749,232.000	+3.076
	BM II	226,855,065	9,749,237.459	+3.909
Labuhan Bajo	BM I	816,525.613	9,060,312.302	+3.684
	BM II	816,557.902	9,060,146.645	+3.194
Selayar (Patumbukan)	BM IA	222,571.000	9,292,756.000	+2.704
	BM II	222,536.296	9,292,763.294	+4.735
	BM I	222,527.893	9,292,689.781	+3.695
	BM IIA	222,513.087	9,292,767.452	+6.363
Wahai	BM I	554,782.000	9,690,683.000	+2.143
	BM II	554,808.106	9,690,747.959	+2.414
Babang	BM I	341,677.000	9,929,362.000	+2.238
	BM II	341,623.370	9,929,311.759	+2.929
Manokwari (Sowi)	BM I	342,805.374	9,900,051.965	+4.427
	BM II	393,217.000	9,900,014.000	+2.609

4. The results of the topographic and hydrographic survey are shown in Figures A2.2.1 to A2.2.7 in Part 3 of the Appendices.

2.2.1 Surabaya

5. The survey site is located in the Lamong Bay between Surabaya City and Gresik

City, about 2.5km west of the commercial port Tanjung Perak. The slope of seabed in Lamong Bay is extremely gentle and six rivers flow into this bay area.

6. The proposed project site is actually on alluvial tidal flat with mud bottom and is about 3km from the shoreline of low water (LWS). The water area of water depth over 5m below LWS is obtained around 2 - 3km offshore.

2.2.2 Banjarmasin

7. The proposed site is located on the left bank of the Barito River approximately 30km upstream from the river mouth and belongs to tidal compartment of the river. The tidal range is observed about for 2.8m at the site. Waves will not pose a major problem to ferry services.

8. The site is separated from the public port of Banjarmasin (Trisakti Port) by a small creek of 15m width. The access roads to the site from the center of the Banjarmasin City do not have sufficient width and traffic capacity.

2.2.3 Labuhan Bajo

9. The proposed site is the existing ferry port with facilities of 500GRT ferry berthing jetty and movable bridge, which was constructed in 1995/96. The water depth at the end of the jetty is observed to be about DL-6m.

10. The topography of land in the vicinity of the port is rather flat. Some permanent buildings such as PT. ASDP office, staff housing, warehouses and so on are found around the port.

11. The water area in front of the existing port is surrounded by several islands and thus waves will not pose any problem to ferry operation.

2.2.4 Selayar (Patumbukan)

12. The proposed site is located at the head of an inlet about 42km south of Benteng City, the regional capital city of Selayar Island. The land topography is rather uneven, while seaside is characterized by mangrove in relatively shallow water.

13. The inlet is approximately 120m in width and 700m in length and both sides of

this inlet are steep slopes of the mountainous terrain. The influence of waves from the Flores Sea is negligibly small all through the year.

14. Access to the site from the main road, Benteng - Apatana, is through an unpaved road of 3m width, and some semi-permanent houses owned by new settlers are found at the site.

2.2.5 Wahai

15. The proposed site is situated on the seashore in a hidden bay and is located about 250m south of the Wahai Public Port. The branch office of DGSC, office building, staff houses, small shops and so on are found in the vicinity.

16. The seaside of the proposed area is covered by bush, coconut trees and mangrove. Wave are not considered to pose any problem to ferry services.

2.2.6 Babang

17. The proposed site is located on the East Coast of Bacan Island and is about 400m northwest from the Babang Public Port. Babang is about 16km from Labuha Town, the major port town of the island.

18. The proposed site, which is empty and covered by grass presently, is an abandoned reclaimed area.

19. The land side topography is flat, while sea side topography is rather steep and the contour of DL-5m is from only 10 - 20m from shoreline.

2.2.7 Manokwari (Sowi)

20. The proposed site is located on the bayside approximately 5km southwest of Manokwari Town. The access road is in fairly good condition, that is, a part of the road from Manokwari is asphalt paved though another part is still unpaved.

21. The vicinity of the proposed site is flat and is presently empty and covered by bush. Seaside topography is relatively steep and the contour of DL-5m is about 50 - 60m from shoreline.

2.2.8 Biak (Mokmer)

22. The proposed site is the ferry terminal now being constructed by DGLT and is located approximately 20 minutes from Biak Town by vehicle. The size of the ferry terminal area still under construction is approximately 100m x 60m and located at the center of Mokmer village. Fishponds are located on both sides of the ferry terminal now under construction.

23. The water depth at the end of the jetty is estimated to be approximately 5m below LWS. The site is open to SW waves. The maximum height of waves is assumed to be about two meters. The difference between HHWS and LWS is about 1.6m.

2.3 Tide

24. Tide observations were carried out continuously for 15 days and nights at each terminal site from January to February 1998. Based on the observed data, harmonic analysis was executed to determine the tidal constituents, amplitude and phases. The significant tide levels in each terminal site are as follows.

Table 2.3.1 Tide Elevations in Each Terminal Site

Terminal	HHWS (m)	MSL (m)	LLWS (m)	Remarks
Surabaya (Lamong Bay)	2.74	1.37	0.00	Existing Data
Banjarmasin (Port Site)	2.97	1.48	0.00	
Selayar (Patumbukan)	2.39	1.19	0.00	
Labuhan Bajo	2.70	1.35	0.00	
Wahai	1.92	0.96	0.00	
Babang	1.35	0.67	0.00	
Manokwari (Sowi)	2.22	1.11	0.00	
Biak (Mokmer)	1.55	0.92	0.00	Phase I Report

25. In the case of Lamong Bay (Surabaya), necessary data for sounding and topographic survey were obtained from existing tidal observation station of the Tanjung Perak Port. The tidal condition of Mokmer site (Biak) is quoted from the report of the Phase I Study.

26. Based on the observed data and harmonic analysis, the tidal constituents of each terminal site are as shown in Table 2.3.2.

Table 2.3.2 Tidal Constituents in Each Terminal Site

(Unit in meter)

Constituents	M ₂	S ₂	N ₂	K ₁	O ₁	M ₄	MS ₄	K ₂	P ₁
Surabaya	0.35	0.24	0.04	0.44	0.30	0.03	0.03	0.07	0.14
Banjarmasin	0.34	0.05	0.06	0.74	0.30	0.04	0.02	0.01	0.24
Patumbukan	0.43	0.15	0.12	0.34	0.15	0.03	0.01	0.04	0.11
Labuhan Bajo	0.43	0.17	0.28	0.20	0.29	0.00	0.01	0.05	0.09
Wahai	0.34	0.18	0.10	0.20	0.15	0.00	0.01	0.05	0.06
Babang	0.16	0.14	0.04	0.21	0.13	0.00	0.00	0.04	0.07
Manokwari	0.35	0.24	0.17	0.19	0.16	0.01	0.01	0.06	0.06
Biak *	0.42	0.11	0.05	0.21	0.13	0.00	0.01	0.03	0.07

* Source: Phase I Report, March 1993.

27. Tide is classified as diurnal, semi-diurnal and mixed semi-diurnal according to the number which is defined by the ratio: $(K_1 + O_1)/(M_2 + S_2)$.

Semi-diurnal type: Form Number < 0.25

Mixed Semi-diurnal type: $0.25 < \text{Form Number} < 1.25$

Diurnal type: Form Number > 1.25

The tidal types at each terminal site are described as follows.

Table 2.3.3 Tidal Form Type

Location	Form Number	Tidal Form Type
Surabaya	1.254	Diurnal
Banjarmasin	2.667	Diurnal
Patumbukan	0.845	Mixed Semi-diurnal
Labuhan Bajo	0.817	Mixed Semi-diurnal
Wahai	0.673	Mixed Semi-diurnal
Babang	1.133	Mixed Semi-diurnal
Manokwari	0.593	Mixed Semi-diurnal
Mokmer	0.642	Mixed Semi-diurnal

2.4 Current

28. The objective of current measurement is to obtain information of possible current speed and direction that will affect maneuvering of vessels in the vicinity of the proposed ferry terminal site. Observations of the current were executed at each terminal site according to the following criteria.

- 1) Point of Survey: One offshore point at each terminal site.
- 2) Layer: Two layers (surface layer and bottom layer) at each survey point.
- 3) Timing of Observation: Around the time of spring tide.
- 4) Period of Observation: 25 hours continuously.
- 5) Method of Observation: Self-recording current meter.
(Aanderra RCM7, Valeport BFM105)
Two minutes measurement at intervals of 10 minutes.

29. The maximum speeds of the observed current at each terminal site are presented in the table below. The results of observations verify that maneuverability of vessels at all the terminal sites is not adversely affected by the current.

Table 2.4.1 Current Speed and Direction

Location	Tide	Max. Speed (m/sec)	Direction
Surabaya (Lamong Bay)	Flood	0.27	W - WNW
	Ebb	0.25	E - ESE
Banjarmasin (Barito River)	Flood	0.68	NNE (upstream)
	Ebb	0.80	SSW (downstream)
Selayar (Patumbukan)	Flood	0.20	SE - E
	Ebb	0.18	W - WSW
Labuhan Bajo	Flood	0.44	SSW
	Ebb	0.23	N
Wahai	Flood	0.12	W - NW
	Ebb	0.14	SE - ESE
Babang	Flood	0.13	SE
	Ebb	0.36	NNW
Manokwari (Sowi)	Flood	0.23	N
	Ebb	0.10	S
Biak* (Mokmer)	Flood	0.65	ENE
	Ebb	0.50	WSW

* Source: Phase I Report, March 1993.

2.5 Wave

(1) Wave hindcast

30. The ferry operation in the following three proposed sites, among others, was

considered to be affected by waves, but there were no observed wave data available for each terminal site. Therefore wave hindcast in those sites was conducted using the latest wind data over a period of more than five years.

Patumbukan (Selayar Island, South Sulawesi)

Babang (Bacan Island, Halmahera, North Maluku)

Manokwari (Irian Jaya)

31. The applied method for wave hindcast was SMB (Sverdrup-Munk-Bretschneider) method, in which offshore waves (wave height, period, and direction of incidence) were calculated.

32. Summary tables of frequency of occurrence of wind (the combined distributions of frequency of wind direction and wind speed) and wave (the combined distributions of frequency of wave direction and wave height) for each of the three terminal sites are shown in the Tables 2.5.1 – 2.5.3.

(2) Selayar (Patumbukan)

33. The tables show the relatively calm characteristics of waves at the three terminal sites. According to Table 2.5.1(2), the directions of wave incidence to the Patumbukan (Selayar Island) site are limited to the range between NE – E – SE and the days with calm wave conditions (with wave height less than 0.3 meters) show a frequency of more than 95%. The frequency of occurrence of the waves with height 0.3 – 0.9 meters occupies 4.7% and the probability of the days with wave height greater than 1 meter is calculated as 0.7 days in a year (around once in 1.5 years).

(3) Babang

34. According to Table 2.5.2(2), the range of directions of wave incidence to the Babang (Bacan Island) site is rather wide. About 20% of waves come from N and NE and these waves are considered to be generated in the Molucca Sea area and to propagate to Halmahera, while about 18% of waves come from S and SE and those waves are seen to be generated in the Seram Sea area.

35. The days with calm wave conditions (with wave height less than 0.3 meters) show a frequency of more than 90%. The frequency of occurrence of the waves with height 0.3 – 0.9 meters occupies 9.7% and the probability of the days with wave height greater than 1 meter is calculated as 0.17 days in a year (around once in 6 years).

Table 2.5.1(1) Frequency of Occurrence of Wind (Hasanuddin)

Station: Hasanuddin - Ujung Pandang; 1987 - 1990 & 1994 - 1997

Speed (m/s)	Calm	1 - 3	3 - 5	5 - 7	7 - 9	9 - 11	11 -	Total
Direction	26,106 37.4%							26,106 37.38%
N		3,398 4.87%	1,122 1.61%	300 0.43%	37 0.05%	12 0.02%	13 0.02%	4,882 6.99%
NE		2,396 3.43%	515 0.74%	146 0.21%	19 0.03%	0	2 0.00%	3,078 4.41%
E		6,726 9.63%	688 0.99%	187 0.27%	30 0.04%	6 0.01%	2 0.00%	7,639 10.94%
SE		7,284 10.43%	507 0.73%	108 0.15%	17 0.02%	6 0.01%	0	7,922 11.34%
S		2,985 4.3%	574 0.8%	441 0.6%	127 0.2%	43 0.06%	9 0.01%	4,179 6.0%
SW		2,092 3.00%	300 0.43%	65 0.09%	8 0.01%	2 0.00%	1 0.00%	2,468 3.53%
W		4,096 5.87%	2,114 3.03%	603 0.86%	33 0.05%	9 0.01%	4 0.01%	6,859 9.82%
NW		4,219 6.04%	1,932 2.77%	501 0.72%	30 0.04%	15 0.02%	6 0.01%	6,703 9.60%
Total	26,106 37.38%	33,196 47.53%	7,752 11.10%	2,351 3.37%	301 0.43%	93 0.13%	37 0.05%	69,836 100.00%

Table 2.5.1(2) Frequency of Occurrence of Wave (Patumbukan)

Location: Patumbukan - Selayar Island; 1987 - 1990 & 1994 - 1997

Height (cm)	Calm	1 - 30	31 - 60	61 - 90	91 - 120	121 - 150	150 -	Total
Direction	47,018 67.3%							47,018 67.33%
N		0	0	0	0	0	0	0 0.00%
NE		2,396 3.43%	515 0.74%	146 0.21%	19 0.03%	0	2 0.00%	3,078 4.41%
E		6,726 9.63%	688 0.99%	187 0.27%	30 0.04%	6 0.01%	2 0.00%	7,639 10.94%
SE		7,284 10.43%	507 0.73%	108 0.15%	17 0.02%	6 0.01%	0	7,922 11.34%
S		2,985 4.27%	574 0.82%	568 0.81%	43 0.06%	9 0.01%	0	4,179 6.0%
SW		0	0	0	0	0	0	0
W		0	0	0	0	0	0	0
NW		0	0	0	0	0	0	0
Total	47,018 67.33%	19,391 27.77%	2,284 3.27%	1,009 1.44%	109 0.16%	21 0.03%	4 0.01%	69,836 100.00%

Table 2.5.2(1) Frequency of Occurrence of Wind (Babullah)

Station: Babullah - Ternate; 1989 - 1997 & 1992 - 1997

Speed (m/s)	Calm	1 - 3	3 - 5	5 - 7	7 - 9	9 - 11	11 -	Total
Direction	19,045 31.0%							19,045 30.96%
N		3,198 5.20%	4,435 7.21%	2,162 3.51%	424 0.69%	109 0.18%	309 0.50%	10,637 17.29%
NE		1,015 1.65%	723 1.18%	59 0.10%	9 0.01%	0	0	1,806 2.94%
E		1,888 3.07%	1,443 2.35%	145 0.24%	10 0.02%	1 0.00%	28 0.05%	3,515 5.71%
SE		1,864 3.03%	1,852 3.01%	426 0.69%	44 0.07%	14 0.02%	2 0.00%	4,202 6.83%
S		2,520 4.1%	2,085 3.4%	1,382 2.2%	391 0.6%	142 0.23%	88 0.1%	6,608 10.7%
SW		3,533 5.74%	245 0.40%	85 0.14%	16 0.03%	2 0.00%	3 0.00%	3,884 6.31%
W		1,977 3.21%	454 0.74%	130 0.21%	21 0.03%	2 0.00%	13 0.02%	2,597 4.22%
NW		2,584 4.20%	3,538 5.75%	2,304 3.75%	573 0.93%	145 0.24%	70 0.11%	9,214 14.98%
Total	19,045 30.96%	18,579 30.21%	14,775 24.02%	6,693 10.88%	1,488 2.42%	415 0.67%	513 0.83%	61,508 100.00%

Table 2.5.2(2) Frequency of Occurrence of Wave (Babang)

Location: Babang - Bacan Island; 1989 - 1990 & 1992 - 1997

Height (cm)	Calm	1 - 30	31 - 60	61 - 90	91 - 120	121 - 150	150 -	Total
Direction	34,740 56.5%							34,740 56.48%
N		7,633 12.41%	2,695 4.38%	309 0.50%	0	0	0	10,637 17.29%
NE		1,015 1.65%	782 1.27%	9 0.01%	0	0	0	1,806 2.94%
E		1,888 3.07%	1,443 2.35%	155 0.25%	1 0.00%	28 0.05%	0	3,515 5.71%
SE		3,716 6.04%	470 0.76%	16 0.03%	0	0	0	4,202 6.83%
S		6,520 10.6%	88 0.1%	0	0	0	0	6,608 10.7%
SW		0	0	0	0	0	0	0
W		0	0	0	0	0	0	0
NW		0	0	0	0	0	0	0
Total	34,740 56.48%	20,772 33.77%	5,478 8.91%	489 0.80%	1 0.00%	28 0.05%	0 0.00%	61,508 100.00%

Table 2.5.3(1) Frequency of Occurrence of Wind (Manokwari)

Station: Rendani - Manokwari; 1987 - 1997

Speed (m/s)	Calm	1 - 3	3 - 5	5 - 7	7 - 9	9 - 11	11 -	Total
Direction	22,229 69.2%							22,229 69.20%
N		812 2.53%	676 2.10%	225 0.70%	36 0.11%	34 0.11%	60 0.19%	1,843 5.74%
NE		168 0.52%	105 0.33%	16 0.05%	2 0.01%	0	4 0.01%	295 0.92%
E		493 1.53%	380 1.18%	104 0.32%	16 0.05%	12 0.04%	0	1,005 3.13%
SE		1,624 5.06%	1,106 3.44%	344 1.07%	62 0.19%	26 0.08%	5 0.02%	3,167 9.86%
S		421 1.3%	209 0.7%	47 0.1%	14 0.0%	2 0.01%	1 0.0%	694 2.2%
SW		151 0.47%	100 0.31%	23 0.07%	3 0.01%	2 0.01%	1 0.00%	280 0.87%
W		446 1.39%	272 0.85%	93 0.29%	24 0.07%	10 0.03%	3 0.01%	848 2.64%
NW		730 2.27%	611 1.90%	285 0.89%	75 0.23%	41 0.13%	19 0.06%	1,761 5.48%
Total	22,229 69.20%	4,845 15.08%	3,459 10.77%	1,137 3.54%	232 0.72%	127 0.40%	93 0.29%	32,122 100.00%

Table 2.5.3(2) Frequency of Occurrence of Wave (Manokwari)

Location: Sowi - Manokwari; 1987 - 1997

Height (cm)	Calm	1 - 30	31 - 60	61 - 90	91 - 120	121 - 150	150 -	Total
Direction	25,118 78.2%							25,118 78.20%
N		1,783 5.55%	60 0.19%	0	0	0	0	1,843 5.74%
NE		289 0.90%	6 0.02%	0	0	0	0	295 0.92%
E		493 1.53%	484 1.51%	16 0.05%	12 0.04%	0	0	1,005 3.13%
SE		1,624 5.06%	1,106 3.44%	344 1.07%	62 0.19%	26 0.08%	5 0.02%	3,167 9.86%
S		421 1.31%	256 0.80%	14 0.04%	3 0.01%	0	0	694 2.2%
SW		0	0	0	0	0	0	0
W		0	0	0	0	0	0	0
NW		0	0	0	0	0	0	0
Total	25,118 78.20%	4,610 14.35%	1,912 5.95%	374 1.16%	77 0.24%	26 0.08%	5 0.02%	32,122 100.00%

(4) Manokwari

36. According to Table 2.5.3(2), the directions of wave incidence to the Manokwari range between N – E – S, and about 7% of waves come from N and NE and these waves are considered to be generated in the Pacific Ocean and to propagate to Irian Jaya, while about 15% of waves come from S and E and those waves are seen to be generated in Cenderawasih Bay.

37. The days with calm wave conditions (with wave height less than 0.3 meters) show a frequency of more than 92.5%. The frequency of occurrence of the waves with height 0.3 – 0.9 meters occupies 7.1%, and the probability of the days with wave height greater than 1 meter is calculated as 1.2 days in a year (around once in 0.8 years).

(5) Summary and maximum wave height

38. From the above wave conditions, the proposed terminal sites can be considered to be calm enough to have operative and serviceable days over 90% of a year. And it is also considered that construction of breakwater is not necessary for these sites. The possible maximum waves hindcast from the wind conditions for the three sites are as follows.

Table 2.5.4 Possible Maximum Wave Height

Site	Wave Height $H_{1/3}$ (m)	Wave Period $T_{1/3}$ (s)	Direction
Selayar	2.3	6.6	E
Babang	1.8	5.6	E
Manokwari	2.3	6.6	SE

2.6 Subsoil Conditions

39. In order to survey and confirm the subsoil conditions of proposed terminal sites, one boring for the onshore development area and another boring for the offshore facility area were executed at each terminal site. The subsoil profiles acquired from the borings at each site are shown in Figures A2.6.1 -- A2.6.7 in Part 3 of the Appendices. The following is an outline of subsoil conditions at each survey site (Also see Table 2.6.1 for a summary of Soil Investigation results).

(1) Surabaya (Lamong Bay)

40. At BM.I, the upper layers up to -4m below local surface level (LSL) formed top soil in the form of organic matter with an N value of 0. The layers between -4m to -56m are loam layers with silt sand and shell fragments being inserted in the depth of -12m to 16m and 36m to 38m. At BM.II, the upper layers consist of silty clay or clay and the N values are relatively low. At about DL-59m there exists clayey stone layer.

(2) Banjarmasin (Near Public Port Site)

41. At BM.I, the upper layer is fine sandy clay and the lower layer is clayey to fine sand and the N values are relatively low. The layer between 4m – 22m below LSL formed silty loam layer with N values from 2 to 14. At BM.III, the upper layer is clayey silt and the lower layer is clayey fine sand and the N values are relatively low. The layer between 22m – 30m below LSL formed silty sand layer with N values from 8 to 32.

(3) Selayar (Patumbukan)

42. At BM.I, the upper layer is fine, gravelly and clayey sand and the lower layer is clayey sand. The N values are relatively low up to DL-17m (N=5 – 16). At BM.II, the upper layer is medium to fine sand and the middle layer is very soft mud and the lower layers are sandy clay or clay. The layer between DL-20 to -30m formed sandy loam and loam with N values of 4 – 6. At about DL-32.5m, there exists a gravel layer with N value over 50.

(4) Labuhan Bajo

43. Both BM.I and BM.II, the upper layers are medium to fine sand with shell fragments, characteristics of which are very loose to loose with N values between 1 – 12.

Meanwhile the layer of the depth 7 – 12m from local surface level generally consist of sand layer to gravel sand and gravel clay with N value around 9 – 31. At about DL-26m, there exists an Andesite Layer with N value over 60.

(5) Wahai

44. At BM.I, the upper layer consists of mainly silt, clay and fine sand and the N values are relatively low (N=4 – 7). The layer between 6m and 20m below LSL consists of silt, silt and sand with N values 6 – 31. The deeper layer between 22m and 28m below LSL consists of loam, silt and gravel sand with N values 3 – 6. Further the depth between 28m and 30m below LSL is the layer of sandy silt to gravel sand with N values from 6 to 56. At BM.II, the upper layer is fine sand and the lower layer is silt and the N values are relatively low.

(6) Babang

45. At BM.I, the upper layer consists of gravelly sand and shell fragments with N value over 50. The middle layers are clay or silt with shell fragments and N values are relatively low. The lower layer is gravelly coarse sand and the N values show over 50 again. At BM.II, the upper layers are silt or sandy silt with shell fragments and the N values are relatively low, while the lower layers are sand or silty sand with shell fragments.

(7) Manokwari (Sowi)

46. At BM.I, the upper layer consists of mainly silt and sand with average N value of about 30. A shell fragment of one meter thickness was found at about 6 – 8m below seabed. The lower layers below DL-16m commonly are silt and sand with N value over 50. At BM.II, the upper layer is gravelly sand with shell fragment and N value is over 50, while the middle layer is silt and sand with N values between 20 – 60. The layer below DL-14m is clay and shell fragments and is very hard with N value over 50.

Table 2.6.1 Summary of Soil Investigation

No	Site Location	Boring	Depth (DI, m)	Average N	Cohesive Soil	Non-cohesive Soil
1	Surabaya	BM. I	0-4	0	Soft	-
			4-60	33	Hard	-
		BM. II	0-11	1	Soft	-
			11-12	5	Medium	-
2	Banjarmasin	BM. I	12-60	35	Hard	-
			0-19	1	Soft	-
			19-22	14	Hard	-
			22-30	12	-	Medium
		BM. II	0-16	1	Soft	-
			16-19	5	Medium	-
			19-20	14	Hard	-
			0-14	2	Soft	-
		BM. III	14-24	7	Medium	-
			24-32	19	-	Medium
			0-3	3	Soft	-
			3-12	6	-	Soft
3	Selayar (Patumbukan)	BM. I	12-20	18	-	Medium
			20-22	60	-	Hard
			0-6	3	-	Soft
			6-20	0	Soft	-
		BM. II	20-27	5	Medium	-
			27-29	10	Hard	-
			29-30	50	-	Hard
			0-7	3	-	Soft
4	Labuhan Bajo	BM. I	7-19	12	-	Medium
			19-30	57	-	Hard
			0-5	4	-	Soft
		BM. II	5-11	16	-	Medium
			11-30	57	-	Hard
			0-10	6	-	Soft
5	Wahai	BM. I	10-14	12	-	Medium
			14-18	8	-	Soft
			18-20	31	-	Hard
			20-27	5	-	Soft
			27-30	50	-	Hard
		BM. II	0-6	4	-	Soft
			6-30	5	Medium	-
			0-3	60	-	Hard
			3-11	13	-	Medium
			11-14	12	Hard	-
6	Babang	BM. I	14-19	16	-	Medium
			19-22	56	-	Hard
			0-7	6	-	Soft
			7-13	12	Hard	-
		BM. II	13-27	18	-	Medium
			27-30	38	-	Hard
			0-5	6	-	Soft
		BM. III	5-14	21	-	Medium
			14-20	55	-	Hard
			0-7	30	-	Medium
7	Manokwari (Sowi)	BM. I	7-18	50	-	Hard
			0-16	50	-	Hard
		BM. II	6-14	35	-	Medium
			14-20	50	-	Hard

Notes	Cohesive Soil	Non-cohesive Soil	Remarks
N value	0-4	0-10	Soft
	4-8	10-30	Medium
	N > 8	N > 30	Hard

