

## 4.10 PROJECT EVALUATION

### 4.10.1 Economic Analysis

Economic feasibility of the proposed priority project was confirmed by deriving economic internal rate of return (EIRR), benefit-cost ratio (B/C) and net present value (NPV) for the standard case and alternative cases based on the assumptions same as those for the master plan. The following are the values specific to the priority project.

Economic Benefit in 2005

Item	Unit	Minimum Requirement	Commercial good
Value of water	Tg/m <sup>3</sup>	1,875	67
	\$/m <sup>3</sup>	2.11	0.08
Net water use in 2005			
Apartment	Lcd	10.6	139.4
Ger	Lcd	10.6	0
Population in 2005			
Apartment	No.	3,433	
Ger	No.	15,357	
Economic benefit in 2005 and thereafter			
Domestic water	10 <sup>3</sup> \$/year	153	13
Industrial and institutional water	10 <sup>3</sup> \$/year	112	

The following table summarizes the result.

Result of Economic Evaluation of Priority Project

Case	EIRR (%)	B/C	NPV (\$10 <sup>3</sup> )
Standard	16.3	1.38	532
Cost 10% up	14.3	1.25	391
Benefit 10% down	114.1	1.24	337
Cost 10% up plus benefit 10% down	12.3	1.13	196

The EIRR for the standard case was derived at 16.3% indicating high economic return of the priority project, compared with an opportunity cost of capital or cut-off EIRR at 10%. The same assumptions for the analysis on the master plan were also employed. The following are the used values and the estimated economic benefit.

#### 4.10.2 Financial Analysis

A financial analysis for the priority projected was carried out in the same way as for the master plan. The following are the derived water charges for the priority project.

- Ger : Tg 556/m<sup>3</sup>
- Apartment : Tg 64/m<sup>3</sup>
- Industry/Institution : Tg 900/m<sup>3</sup>

Under these water charges, operation and maintenance cost can be recovered as well as they are affordable for the residents. A financial internal rate of return (FIRR) is derived at 4.6%, indicating the possibility that the fund for implementing the priority project could be procured at an interest of less than 4.6% per year as shown in Table 4.2.

#### 4.10.3 Social Evaluation

Proposed project on water supply system mainly focused on the improvement of water supply in the ger area by increasing chances of water availability. Although the residents of ger area cited yard connection as a preferable choice, it is not technically feasible. As mentioned in social analysis, no negative impact on the proposed project is recognized in terms of religion and social custom, acquisition of land for the project, and water seller.

#### 4.10.4 Analysis for the Beneficiaries

While the higher income group of non-piped households approved 161% of increase, the lower income group of non-piped households approved 80% of increase to the current tariff level. As indicated in the result of the household survey, the lower income group of non-piped household consumes less volume of water per day per person than the higher income group. However even the volume used by the higher income group is insufficient for required volume of consumption. It is recommended that exemption system of water charge for lower income group - unemployed and single female headed households should be revised periodically in accordance with local poverty assessment.

The proposed program for water supply system, which plans the installation of kiosk type water delivery points in the ger area, will give the residents access to the water

whenever necessary for them. This also will lead to the increase of water consumption for non-piped households. The frequent supply of water is expected to reduce the habit of stock water and bring about less opportunity of contamination.

However, 20% of non-piped households will not gain the intended benefit of kiosk type of water supply since a fixed single kiosk is designed to cover a radius of 250m. Therefore the use of water carriers as proposed in the previous chapter will be especially important for these households.

#### 4.10.5 Environmental Impact Assessment (EIA)

##### (1) General Description

This section is written based mainly on the Environmental Impact Assessment report for the project conducted by an approved Mongolian EIA Company. The contents of the report is summarized in the following.

##### (2) Activities of the Project

###### Construction Phase

- ① Drilling of test wells
- ② Construction of production wells
- ③ Construction of distribution pipelines (about four kilometers) for Ger areas

###### Operation Phase

- ① Production of water from the production wells
- ② Chlorinating

##### (3) Environmental Impacts

###### Expected Impacts in the Construction Phase

- ① Impacts from drilling wells

Item	Judgement
Noise for human being (including livestock) and fauna (especially in breeding season).	small negative impact
Degradation of vegetation and subsoil, small area (10-30 m <sup>2</sup> )	small negative impact
Employment	small positive impact

② Impacts from the Construction of Water Supply Facilities

Item	Judgement
Degradation of vegetation and subsoil - distribution pipelines (30 m x 3.9 km, affected area 12 ha)	large negative impact
Employment	small impact
if construction workers are locally employed,	positive impact
if construction workers are employed from other places,	negative impact

③ Impacts in Operation Phase

Item	Judgement
Stable water supply, especially for Ger areas	large positive impact
Degradation of groundwater, wetland, vegetation and subsoil if overusing the groundwater	large negative impact
Employment (changing types of job)	small impact

(4) Mitigation of Impacts

Although there are not many serious impacts expected in this project, proper measures should be taken to minimize the impacts.

- 1) Informing for the construction detail before the construction
- 2) Preventing for the degradation of vegetation and subsoil from the construction work. The following steps should be taken:
  - ① to survey rare plant species and breeding sites of rare animal species in the affected area around the construction of facilities, and they take a protection action for these rare species if necessary;
  - ② to preserve subsoil from the affected area;
  - ③ to construct the facility;
  - ④ to return subsoil in the affected area; and
  - ⑤ to monitor fauna and flora in the affected area.
- 3) Prevention the degradation of groundwater from overusing  
The following measures should be taken :
  - ① to educate people on proper water use;
  - ② to reduce the leakage of water; and
  - ③ to monitor water level and quality of groundwater, vegetation and subsoil.

#### 4) Hygiene

① The following sanitary zonation scheme should be established to protect the sources of domestic water.

I - (100 m) strictly prohibited zone.

Prohibit to setting up of any sources of possible pollution in the I-zone.

II - (300 m) zone under protection.

III - (1,000 m) monitoring zone.

② Bacteriological and chemical analyses should be monitored in these zones.

#### (5) Monitoring and Management

##### 1) Construction Phase

After the construction of a facility, vegetation and subsoil in the affected area should be monitored, and if necessary, some measure should be taken to restore them.

##### 2) Operation Phase

Water level and quality of groundwater, vegetation, and subsoil should be monitored, and if necessary some measures should be taken to improve the situation.

**Table 4.1 Economic Evaluation of Priority Project**

(Unit : \$)

No.	Year	Cost				Benefit			Balance
		Investment	OM	Replacement	Total	Domestic	Industrial & institutional	Total	
1	2000	10,418	44,113	0	54,531	0	0	0	-54,531
2	2001	232,134	48,710	0	280,844	1,739	3,007	4,746	-276,098
3	2002	293,869	52,245	0	346,114	40,495	6,326	46,821	-299,293
4	2003	282,859	48,108	0	330,967	89,557	9,887	99,445	-231,522
5	2004	177,080	52,433	0	229,513	136,782	13,166	149,948	-79,565
6	2005	0	55,967	0	55,967	166,346	112,102	278,447	222,480
7	2006	0	55,967	0	55,967	166,346	112,102	278,447	222,480
8	2007	0	55,967	0	55,967	166,346	112,102	278,447	222,480
9	2008	0	55,967	0	55,967	166,346	112,102	278,447	222,480
10	2009	0	55,967	0	55,967	166,346	112,102	278,447	222,480
11	2010	0	55,967	0	55,967	166,346	112,102	278,447	222,480
12	2011	0	55,967	0	55,967	166,346	112,102	278,447	222,480
13	2012	0	55,967	0	55,967	166,346	112,102	278,447	222,480
14	2013	0	55,967	0	55,967	166,346	112,102	278,447	222,480
15	2014	0	55,967	0	55,967	166,346	112,102	278,447	222,480
16	2015	0	55,967	0	55,967	166,346	112,102	278,447	222,480
17	2016	0	55,967	0	55,967	166,346	112,102	278,447	222,480
18	2017	0	55,967	0	55,967	166,346	112,102	278,447	222,480
19	2018	0	55,967	0	55,967	166,346	112,102	278,447	222,480
20	2019	0	55,967	404,081	460,048	166,346	112,102	278,447	-181,601
21	2020	0	55,967	0	55,967	166,346	112,102	278,447	222,480
22	2021	0	55,967	0	55,967	166,346	112,102	278,447	222,480
23	2022	0	55,967	0	55,967	166,346	112,102	278,447	222,480
24	2023	0	55,967	0	55,967	166,346	112,102	278,447	222,480
25	2024	0	55,967	0	55,967	166,346	112,102	278,447	222,480
26	2025	0	55,967	0	55,967	166,346	112,102	278,447	222,480
27	2026	0	55,967	0	55,967	166,346	112,102	278,447	222,480
28	2027	0	55,967	0	55,967	166,346	112,102	278,447	222,480
29	2028	0	55,967	0	55,967	166,346	112,102	278,447	222,480
30	2029	0	55,967	0	55,967	166,346	112,102	278,447	222,480
	Total	996,360	1,644,784	404,081	3,045,225	4,427,220	2,834,926	7,262,146	4,216,921

**Sensitivity Analysis**

Case	EIRR (%)	B/C	B-C (\$)
Standard	16.3%	1.38	532,082
Cost 10% up	14.3%	1.25	390,646
Benefit 10% down	14.1%	1.24	337,438
Cost 10% up and benefit 10% dow	12.3%	1.13	196,001

**Table 4.2 Financial Internal Rate of Return of Priority Project**  
**(Under the revised water tariff for OM cost recovery)**

FIRR = 4.6%

(Unit : \$)

Year	Cost				Revenue			Balance
	Investment	OM	Replacement	Total	Domestic	Industrial & institutional	Total	
2000	10,418	44,113	0	54,531	0	0	0	-54,531
2001	232,134	48,710	0	280,844	536	977	1,513	-279,331
2002	293,869	52,245	0	346,114	12,489	22,741	35,230	-310,884
2003	282,859	48,108	0	330,967	27,620	50,294	77,914	-253,053
2004	177,080	52,433	0	229,513	42,184	76,815	118,999	-110,514
2005	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2006	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2007	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2008	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2009	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2010	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2011	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2012	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2013	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2014	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2015	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2016	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2017	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2018	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2019	0	55,967	404,081	460,048	51,302	93,418	144,720	-315,328
2020	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2021	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2022	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2023	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2024	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2025	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2026	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2027	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2028	0	55,967	0	55,967	51,302	93,418	144,720	88,753
2029	0	55,967	0	55,967	51,302	93,418	144,720	88,753
Total	996,360	1,644,784	404,081	3,045,225	1,365,381	2,486,273	3,851,654	806,429





Figure 4.1 Proposed Water Distribution Network in future ( by 2005 )

JICA The Study on Groundwater Development for Altai City



## **5 CONCLUSION AND RECOMMENDATION**



## 5. CONCLUSION AND RECOMMENDATION

### Conclusion

The project evaluation revealed that both the master plan and priority project were feasible, therefore worth promoting to the implementation stage. The project would contribute to the improvement of the living standard of Altai people and support economic development in the city. An appropriate financial arrangement would be needed considering the low financial return of the project. No adverse impacts are envisaged in the environmental and social aspects.

### Recommendation

- (1) At present ger dwellers have great disadvantage in that water wagons deliver water a couple of times a week for them, while apartment dwellers get water by taps any time. Ger dwellers cannot get water whenever they want. Therefore, improvement of water supply service for ger dwellers shall be given priority.
- (2) Disparity of water tariff between apartment dwellers and ger dwellers shall be revised. To start with, the fact should be opened to the public.
- (3) People have to change the awareness for water quality that high mineral concentrations in water affect their health. Actually, the chemical contents are below the Mongolian standards except magnesium. The problem is the total coliform in water, especially in the stored water in gers. Water in Altai City is not as bad as they claim, considering the water quality analysis result and especially when it is compared with water quality and standard of some other countries. Hygiene education for the public shall be conducted through radio, television, by the public health center and school with following objections:
  - increase of awareness on hygiene practice and water consumption,
  - proper management of stock water and water consumption, and
  - water and health.
- (4) Epidemiological survey, that started from 1998, shall be continued to clarify the cause of chronic diseases.
- (5) The drawdown in operation of wells should be kept around four to six meters to conserve the limited natural resources of groundwater.
- (6) The loss ratio of leakage should be improved step-wise. Water meters shall be installed at the pumping station, apartment buildings, public buildings, and in each apartment. APSD has to inspect meters and find the point of leakage in order to

improve the water supply facilities. Inspection staff in APSD should be strengthened.



- (7) All information shall be opened to the public to improve the people's awareness for saving water, preservation of the environment to spread the idea that groundwater is limited natural resources.



### Hydrogeological Description of Formations in the Study Area



Era / Period	System	Maximum thickness (m)	Explanation
CENOZOIC QUATERNARY	Upper Quaternary Recent river deposits	>20	Distributed in river and stream bed. Mainly sandy loam and loam. And sand, clay, gravel. A scattered and limited aquifer in Sukhin Khooloi.
	QIV		
	Middle and Upper Quaternary Fan and talus deposits	>100	Distributed widely in the area. Gravel, sandy gravel, sand. Most exploitable aquifer occurs in Olon Nuul, where the deposit is thick.
	QII-III		
TERTIARY	Neogene System	>100	Mainly covered by Quaternary sediments in the area. Unconsolidated generally. Very low productive aquifer in Sukhin Hooloi and Olon Nuul. Reddish clay with sand and gravel.
	N2at		
PALEOZOIC	Lower and Middle Devonian series	>1000	Distributed in the limited area. Sandstone and conglomerate. No aquifer in Study Area.
DEVONIAN			
D1-2			
CAMBRIAN	Tsagaan Olom Series	>1000	Distributed in the south end of Study Area. Mainly carbonate rocks.
Lower and Middle			
E1-2			
PRECAMBRIAN	Vend Series		Limited distribution in the mountain range on the south of Study Area.
PROTEROZOIC	Khantaishir Series		
Vht			
R1-3gb	Upper-Lower Rophean Series		Distributed in the southwest mountain range of Altai City. Mainly Dunite and Serpentine, Peridotite. Springs occur in places along faults.
PR1			
PR1am	Gobi Al Ulaantolgoi S	2950	Distributed widely in the northwest and central mountainous region in Study Area. Fractured aquifers occur in Kharzat and Sukhin Hooloi.
PROTEROZOIC	Intrusive Rock of Riphean Series		Limited distribution in the eastern area.
γ R2-3			




Hydrograph of Observation Wells from June 1997 to October 1998 with daily Rainfall and Maximum Ground Temperature measured at Altai



### Hydrogeological Description of Formations in the Study Area




Era / Period	System	Maximum thickness (m)	Explanation
CENOZOIC QUATERNARY	Upper Quaternary Recent river deposits. QIV	>20	Distributed in river and stream bed. Mainly sandy loam and loam. And sand clay, gravel. A scattered and limited aquifer in Sukhin Khoolor.
	Middle and Upper Quaternary Fan and talus deposits QII-III	>100	Distributed widely in the area. Gravel, sandy gravel, sand. Most exploitable aquifer occurs in Olon Nuul, where the deposit is thick.
	TERTIARY Neogene System N2at	>100	Mainly covered by Quaternary sediments in the area. Unconsolidated generally. Very low productive aquifer in Sukhin Hooloi and Olon Nuul. Reddish clay with sand and gravel.
PALEOZOIC DEVONIAN D1-2 CAMBRIAN	Lower and Middle Devonian series	>1000	Distributed in the limited area. Sandstone and conglomerate. No aquifer in Study Area.
	Lower and Middle Tsagaan Olom Series E1-2	>1000	Distributed in the south end of Study Area. Mainly carbonate rocks.
PRECAMBRIAN PROTEROZOIC	Vend Series Khantaishir Series Vht		Limited distribution in the mountain range on the south of Study Area.
	Upper-Lower Riphean Series R1-3gb		Distributed in the southwest mountain range of Altai City. Mainly Dunite and Serpentine, Peridotite. Springs occur in places along faults.
	PR1 PR1am Gobi Altai and Ulaantolgoi Series	29-50	Distributed widely in the northwest and central mountainous region in Study Area. Fractured aquifers occur in Kharzat and Sukhin Hooloi.
PROTEROZOIC γ R2-3	Intrusive Rock of Riphean Series		Limited distribution in the eastern area.












Rainfall (mm)











PALBOZOIC DEVONIAN D1-2 CAMBRIAN Lower and Middle	Lower and Middle Devonian series Tsagaan Olom Series	>1000 >1000	Distributed in the limited area. Sandstone and conglomerate. No aquifer in Study Area. Distributed in the south end of Study Area. Mainly carbonate rocks.
PRECAMBRIAN PROTEROZOIC Vht R1-3gb	Vend Series Khantaishir Series Upper-Lower Rephean Series		Limited distribution in the mountain range on the south of Study Area. Distributed in the southwest mountain range of Altai City. Mainly Dunite and Serpentine, Peridotite. Springs occur in places along faults.
PR1 PR1am	Gobi Al Ulaantolgoi S.	2950	Distributed widely in the northwest and central mountainous region in Study Area. Fractured aquifers occur in Kharzat and Sukhin Hooloi.
PROTEROZOIC γ R2-3	Intrusive Rock of Riphean Series		Limited distribution in the eastern area.



PALEOZOIC DEVONIAN D1-2 CAMBRIAN Lower and Middle Devonian series	>1000	Distributed in the limited area Sandstone and conglomerate. No aquifer in Study Area.
Middle E1-2 Tsagaan Olom Series	>1000	Distributed in the south end of Study Area. Mainly carbonate rocks
PRECAMBRIAN PROTEROZOIC Vht R1-3gb Vend Series Khantaishir Series		Limited distribution in the mountain range on the south of Study Area.
PR1 PR1am Upper-Lower Riphean Series	2-50	Distributed in the southwest mountain range of Altai City. Mainly Dunite and Serpentine. Springs occur in places along faults
PR1 PR1am Gobi Altai and Ulaantolgoi Series	2-50	Distributed widely in the northwest and central mountainous region in Study Area. Fractured aquifers occur in Kharzat and Sukhin Hooloi.
PROTEROZOIC γ R2-3 Intrusive Rock of Riphean Series		Limited distribution in the eastern area.





46° 30'


2000

B2	73	0.5
11.67	10.94	2100


B3	131	0.67
25.22	32.55	2800



A2	193	0.99
2.6	5	7600




A4	160	16.7
4.16	11.49	2400




46° 20'

2300

B5	80	6.7
3.22	19.23	400




B6	120	10.1
24.01	1.04	800




(m A. S. L.)

2100






A3	150	9.9
3.9	60.13	1200



A1	200	3.33
11.12	73.47	2000



B1	56	1.23
20.15	12.38	1400





Rainfall (mm)

Ground Max. Temp. (Cels.)

### LEGEND

- Electric conductivity of spring
- Electric conductivity of surface water
- Observation well (Water level measured monthly)
- Observation well for water sampling
- Observation well (automatic water level recorder installed)
- 7 < Pumping rate of well (litter/sec)



46° 30'

B2 73 0.5  
11.67 10.94 2100

B3 131 0.67  
25.22 32.55 2800

A2 193 0.99  
2.6 5 7600

A4 160 16.7  
4.16 11.49 2400

46° 20'

B5 80 6.7  
3.22 19.23 400

B6 120 10.1  
24.01 1.04 800

A3 150 9.9  
4.9 6.6 13 1200

A1 200 3.33  
11.12 73.47 2000

B1 56 1.23  
20.15 12.38 1400

2000

0

2250

2200

2150

2100

0


2300

2250

2200


2150

2100








**LEGEND**

- Electric conductivity of spring
- Electric conductivity of surface water
- Observation well (Water level measured monthly)
- Observation well for water sampling
- Observation well (automatic water level recorder installed)
- Pumping rate of well (liter/sec)



Rainfall (mm)  
 0  
 20  
 40  
 60  
 80  
 100  
 120  
 140  
 160  
 180  
 200  
 220  
 240  
 260  
 280  
 300  
 320  
 340  
 360  
 380  
 400  
 420  
 440  
 460  
 480  
 500  
 520  
 540  
 560  
 580  
 600  
 620  
 640  
 660  
 680  
 700  
 720  
 740  
 760  
 780  
 800  
 820  
 840  
 860  
 880  
 900  
 920  
 940  
 960  
 980  
 1000  
 1020  
 1040  
 1060  
 1080  
 1100  
 1120  
 1140  
 1160  
 1180  
 1200  
 1220  
 1240  
 1260  
 1280  
 1300  
 1320  
 1340  
 1360  
 1380  
 1400  
 1420  
 1440  
 1460  
 1480  
 1500  
 1520  
 1540  
 1560  
 1580  
 1600  
 1620  
 1640  
 1660  
 1680  
 1700  
 1720  
 1740  
 1760  
 1780  
 1800  
 1820  
 1840  
 1860  
 1880  
 1900  
 1920  
 1940  
 1960  
 1980  
 2000  
 2020  
 2040  
 2060  
 2080  
 2100  
 2120  
 2140  
 2160  
 2180  
 2200  
 2220  
 2240  
 2260  
 2280  
 2300  
 2320  
 2340  
 2360  
 2380  
 2400  
 2420  
 2440  
 2460  
 2480  
 2500  
 2520  
 2540  
 2560  
 2580  
 2600  
 2620  
 2640  
 2660  
 2680  
 2700  
 2720  
 2740  
 2760  
 2780  
 2800  
 2820  
 2840  
 2860  
 2880  
 2900  
 2920  
 2940  
 2960  
 2980  
 3000  
 3020  
 3040  
 3060  
 3080  
 3100  
 3120  
 3140  
 3160  
 3180  
 3200  
 3220  
 3240  
 3260  
 3280  
 3300  
 3320  
 3340  
 3360  
 3380  
 3400  
 3420  
 3440  
 3460  
 3480  
 3500  
 3520  
 3540  
 3560  
 3580  
 3600  
 3620  
 3640  
 3660  
 3680  
 3700  
 3720  
 3740  
 3760  
 3780  
 3800  
 3820  
 3840  
 3860  
 3880  
 3900  
 3920  
 3940  
 3960  
 3980  
 4000  
 4020  
 4040  
 4060  
 4080  
 4100  
 4120  
 4140  
 4160  
 4180  
 4200  
 4220  
 4240  
 4260  
 4280  
 4300  
 4320  
 4340  
 4360  
 4380  
 4400  
 4420  
 4440  
 4460  
 4480  
 4500  
 4520  
 4540  
 4560  
 4580  
 4600  
 4620  
 4640  
 4660  
 4680  
 4700  
 4720  
 4740  
 4760  
 4780  
 4800  
 4820  
 4840  
 4860  
 4880  
 4900  
 4920  
 4940  
 4960  
 4980  
 5000  
 5020  
 5040  
 5060  
 5080  
 5100  
 5120  
 5140  
 5160  
 5180  
 5200  
 5220  
 5240  
 5260  
 5280  
 5300  
 5320  
 5340  
 5360  
 5380  
 5400  
 5420  
 5440  
 5460  
 5480  
 5500  
 5520  
 5540  
 5560  
 5580  
 5600  
 5620  
 5640  
 5660  
 5680  
 5700  
 5720  
 5740  
 5760  
 5780  
 5800  
 5820  
 5840  
 5860  
 5880  
 5900  
 5920  
 5940  
 5960  
 5980  
 6000  
 6020  
 6040  
 6060  
 6080  
 6100  
 6120  
 6140  
 6160  
 6180  
 6200  
 6220  
 6240  
 6260  
 6280  
 6300  
 6320  
 6340  
 6360  
 6380  
 6400  
 6420  
 6440  
 6460  
 6480  
 6500  
 6520  
 6540  
 6560  
 6580  
 6600  
 6620  
 6640  
 6660  
 6680  
 6700  
 6720  
 6740  
 6760  
 6780  
 6800  
 6820  
 6840  
 6860  
 6880  
 6900  
 6920  
 6940  
 6960  
 6980  
 7000  
 7020  
 7040  
 7060  
 7080  
 7100  
 7120  
 7140  
 7160  
 7180  
 7200  
 7220  
 7240  
 7260  
 7280  
 7300  
 7320  
 7340  
 7360  
 7380  
 7400  
 7420  
 7440  
 7460  
 7480  
 7500  
 7520  
 7540  
 7560  
 7580  
 7600  
 7620  
 7640  
 7660  
 7680  
 7700  
 7720  
 7740  
 7760  
 7780  
 7800  
 7820  
 7840  
 7860  
 7880  
 7900  
 7920  
 7940  
 7960  
 7980  
 8000  
 8020  
 8040  
 8060  
 8080  
 8100  
 8120  
 8140  
 8160  
 8180  
 8200  
 8220  
 8240  
 8260  
 8280  
 8300  
 8320  
 8340  
 8360  
 8380  
 8400  
 8420  
 8440  
 8460  
 8480  
 8500  
 8520  
 8540  
 8560  
 8580  
 8600  
 8620  
 8640  
 8660  
 8680  
 8700  
 8720  
 8740  
 8760  
 8780  
 8800  
 8820  
 8840  
 8860  
 8880  
 8900  
 8920  
 8940  
 8960  
 8980  
 9000  
 9020  
 9040  
 9060  
 9080  
 9100  
 9120  
 9140  
 9160  
 9180  
 9200  
 9220  
 9240  
 9260  
 9280  
 9300  
 9320  
 9340  
 9360  
 9380  
 9400  
 9420  
 9440  
 9460  
 9480  
 9500  
 9520  
 9540  
 9560  
 9580  
 9600  
 9620  
 9640  
 9660  
 9680  
 9700  
 9720  
 9740  
 9760  
 9780  
 9800  
 9820  
 9840  
 9860  
 9880  
 9900  
 9920  
 9940  
 9960  
 9980  
 10000





46° 30'

12 23 0.5  
11.67 10.91 2100

13 131 0.67  
25.22 12.55 2800




A2 193 0.99  
2.6 5 7600

A4 169 16.7  
4.16 11.49 2400






46° 20'




15 80 6.7  
3.22 19.23 400

18 120 19.1  
24.01 1.04 800









**LEGEND**

- Electric conductivity of spring
- Electric conductivity of surface water
- Observation well (Water level measured monthly)
- Observation well for water sampling
- Observation well (automatic water level recorder installed)
- 7 < Pumping rate of well (litter/sec)
- 3 ≤ 7 Pumping rate of well (litter/sec)
- 1 ≤ 3 Pumping rate of well (litter/sec)
- JICA Test Well
- Photo lineament
- Inferred faults and fractured zone
- 2120 Water Table Contour (m ASL)
- 10 Isopach of Main Aquifer (m)
- Isoline of Transmissivity (m<sup>2</sup>/day)

Na+K Cl

Ca HCO3

Mg SO4

Cl type

0 20 40 60 80



Granular Aquifer		Fissured Aquifer	
	Highly productive aquifers Locally important aquifers		Productive aquifers (not extensive)
	Local and low productive aquifers		Insignificant Aquifer
			Minor aquifers with local and limited groundwater resources

Well No.	Depth	Q (l/s)
S.W.L	Drawdown (m)	TDS (mg/l)

1 : 100,000

B5	80	6.7
3.22	19.23	400

B6	120	10.1
24.01	1.04	800




18	80	6.7
3.22	19.23	400
18	120	19.1
24.01	1.64	800


**LEGEND**

- Electric conductivity of spring
- Electric conductivity of surface water
- Observation well (Water level measured monthly)
- Observation well for water sampling
- Observation well (automatic water level recorder installed)
- 7 ~ 10 Pumping rate of well (liter/sec)
- 3 ~ 7 Pumping rate of well (liter/sec)
- 1 ~ 3 Pumping rate of well (liter/sec)
- JICA Test Well
- Photo lineament
- Inferred faults and fractured zone
- Water Table Contour (m ASL)
- Isopach of Main Aquifer (m)
- Isoline of Transmissivity (m<sup>2</sup>/day)

Granular Aquifer		Fissured Aquifer	
	Highly productive aquifers		Productive aquifers (not extensive)
	Locally important aquifers		Insignificant Aquifer
	Local and low productive aquifers		Minor aquifers with local and limited groundwater resources

Well No.	Depth	Q (l/s)
S.W.L.	Drawdown (m)	TDS (mg/l)





B5	80	6.7
S.W.L	19.23	400

B6	120	10.1
S.W.L	24.01	800




**Fissured Aquifer**

Productive aquifers (not extensive)

**Insignificant Aquifer**

Minor aquifers with local and limited groundwater resources


Well No.	Depth	Q (l/s)
S.W.L	Drawdown (m)	TDS (mg/l)



January, 1999

# HYDROGEOLOGICAL MAP

**JICA**    The Study on Groundwater Development for Altai City



46° 20'

85 00 6.7  
322 19 23 400

86 120 10.1  
2401 104 800

**Fissured Aquifer**




Productive aquifers (not extensive)

**Insignificant Aquifer**

Minor aquifers with local and limited groundwater resources

Well No.	Depth	Q (l/s)
S.W.L.	Drawdown (m)	TDS (mg/l)

1 : 100,000




January, 1999

# HYDROGEOLOGICAL MAP

**JICA** The Study on Groundwater Development for Altai City











JICA