


GE2.

WATER PRESSURE TEST DATA



List of Borehole Water Tests (1)

| Depth (m) | Average Lugeon Value | | | | | | | |
|-----------|----------------------|-------|-------|-------|---|-------|-------|-------|
| | M98-1 | M98-2 | M98-3 | M98-4 | M98-5 | M98-6 | M98-7 | M98-8 |
| | | | | | $k = 5 \times 10^{-5}$ to 1×10^{-2} cm/sec | | | |
| 2 - 7 | 128 | 112 | 68 | 5 | | 8 | 41 | 38 |
| 5 - 10 | 110 | 65 | 13 | 0 | | 1 | 78 | 41 |
| 10 - 15 | 79 | 36 | 7 | 11 | 1 | 1 | 105 | 19 |
| 15 - 20 | 42 | 0 | 4 | 9 | 0 | 1 | 4 | 1 |
| 20 - 25 | 8 | 1 | 6 | 0 | 0 | 1 | 0 | 9 |
| 25 - 30 | 11 | 1 | 5 | 0 | 0 | 0 | 0 | 11 |
| 30 - 35 | 14 | 9 | 1 | 1 | | 1 | 0 | 32 |
| 35 - 40 | 12 | 1 | 1 | 1 | | 0 | 1 | 9 |
| 40 - 45 | 11 | 0 | 3 | 1 | | 0 | 1 | 4 |
| 45 - 50 | 9 | 2 | 0 | 2 | | 2 | 0 | 46 |
| 50 - 55 | 15 | 0 | 0 | 2 | | 2 | 0 | 2 |
| 55 - 60 | 18 | 0 | 0 | 1 | | 1 | 0 | 1 |
| 60 - 65 | 20 | 0 | 1 | 2 | | 1 | 0 | 0 |
| 65 - 70 | 0 | 0 | 0 | 1 | | 1 | 0 | 0 |
| 70 - 75 | | 0 | 1 | | | | 0 | |
| 75 - 80 | | 0 | 0 | | | | 0 | |
| 80 - 85 | | 0 | 0 | | | | 0 | |
| 85 - 90 | | 0 | 0 | | | | 0 | |
| 90 - 95 | | 0 | 0 | | | | 0 | |
| 95 - 100 | | 0 | 0 | | | | 0 | |

List of Borehole Water Tests (2)

| Depth (m) | Average Lugeon Value | | | | | | | |
|------------|----------------------|--------|--|--------|--------|--------|--------|--------|
| | M98-9 | M98-10 | M98-11 | M98-12 | M98-13 | M98-14 | M98-15 | M98-16 |
| | | | $k = 5 \times 10^{-2}$ to 6.2×10^{-2} cm/sec. | | | | | |
| 2 -- 7 | 20 | 20 | | 1 | 27 | 53 | 68 | 105 |
| 5 -- 10 | 9 | 54 | 241 | 1 | 24 | 1 | 75 | 35 |
| 10 -- 15 | 4 | 10 | 1 | 43 | 19 | 2 | 14 | 34 |
| 15 -- 20 | 0 | 5 | 2 | 1 | 24 | 1 | 5 | 13 |
| 20 -- 25 | 8 | 2 | 0 | 1 | 1 | 0 | 20 | 3 |
| 25 -- 30 | 5 | 4 | 0 | 3 | 2 | 0 | 24 | 13 |
| 30 -- 35 | | | | | | 0 | 0 | 28 |
| 35 -- 40 | | | | | | 0 | 0 | 1 |
| 40 -- 45 | | | | | | 0 | 0 | 1 |
| 45 -- 50 | | | | | | 0 | 5 | 2 |
| 50 -- 55 | | | | | | 0 | 0 | 1 |
| 55 -- 60 | | | | | | 1 | 0 | 1 |
| 60 -- 65 | | | | | | 1 | 0 | 0 |
| 65 -- 70 | | | | | | 1 | 0 | 0 |
| 70 -- 75 | | | | | | 0 | 0 | |
| 75 -- 80 | | | | | | 0 | 0 | |
| 80 -- 85 | | | | | | 0 | 0 | |
| 85 -- 90 | | | | | | 0 | 0 | |
| 90 -- 95 | | | | | | 0 | 0 | |
| 95 -- 100 | | | | | | 0 | 0 | |
| 100 -- 105 | | | | | | 0 | | |
| 105 -- 110 | | | | | | 0 | | |
| 110 -- 115 | | | | | | 0 | | |
| 115 -- 120 | | | | | | 0 | | |
| 120 -- 125 | | | | | | 0 | | |
| 125 -- 130 | | | | | | 0 | | |
| 130 -- 135 | | | | | | 0 | | |
| 135 -- 140 | | | | | | 0 | | |
| 140 -- 145 | | | | | | 0 | | |
| 145 -- 150 | | | | | | 0 | | |
| 150 -- 155 | | | | | | 0 | | |
| 155 -- 160 | | | | | | 0 | | |
| 160 -- 165 | | | | | | 0 | | |
| 165 -- 170 | | | | | | 0 | | |
| 170 -- 175 | | | | | | 0 | | |
| 175 -- 180 | | | | | | 0 | | |


List of Borehole Water Tests (3)

| Depth (m) | Average Lugeon Value | | | | | | |
|-----------|----------------------|--------|--------|--|------|------|--|
| | M98-17 | M98-18 | M98-19 | M98-20 | Qs-1 | Qs-2 | |
| | | | | $k = 2 \times 10^{-2}$ to 6×10^{-3} cm/sec. | | | |
| 2 -- 7 | 74 | 73 | 40 | | 84 | 8 | |
| 5 -- 10 | 22 | 49 | 9 | 5 | 68 | 33 | |
| 10 -- 15 | 23 | 18 | 5 | 1 | 33 | 0 | |
| 15 -- 20 | 23 | 4 | 8 | 12 | 29 | 2 | |
| 20 -- 25 | 25 | 0 | 214 | 11 | 3 | 2 | |
| 25 -- 30 | 6 | 1 | 14 | 0 | 36 | 1 | |
| 30 -- 35 | 7 | | 129 | | 43 | 3 | |
| 35 -- 40 | 1 | | 5 | | 35 | 1 | |
| 40 -- 45 | 0 | | 18 | | 32 | 1 | |
| 45 -- 50 | 3 | | 0 | | 7 | 1 | |
| 50 -- 55 | 2 | | 0 | | | 2 | |
| 55 -- 60 | 0 | | 1 | | | 1 | |
| 60 -- 65 | | | 0 | | | 2 | |
| 65 -- 70 | | | 0 | | | 2 | |
| 70 -- 75 | | | | | | 24 | |
| 75 -- 80 | | | | | | 3 | |
| 80 -- 85 | | | | | | 5 | |
| 85 -- 90 | | | | | | 4 | |
| 90 -- 95 | | | | | | 3 | |
| 95 -- 100 | | | | | | 12 | |

Water Pressure Test

Hole No.: M98-1 Stages: 1/14
 Location: Dam Axis (Right Bank, Dam Crest) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (P): $1 \times 10^{-4} \times Q^{1.71}$ Date: 3/December/1998

| Ground elevation: EL | | Groundwater level (L _g): Nil | | Gauge height (L _g): 0.73 m | | | |
|--|----------------|---|----------------|--|----------------|----------------|----------------|
| Pipe length from gauge to borehole mouth: (L _b) = 7.60 m | | Depth of test section: 2 m to (L _b) = 7 m | | Length of section (L _s): 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 13:16 | 13:29 | 13:41 | | | | |
| Q (m ³ /min) | 34,313 | 35,582 | 41,340 | | | | |
| 1 | 34,410 | 35,720 | 41,475 | | | | |
| 2 | 34,495 | 35,869 | 41,559 | | | | |
| 3 | 34,579 | 36,029 | 41,646 | | | | |
| 4 | 34,667 | 36,193 | 41,732 | | | | |
| 5 | 34,750 | 36,365 | 41,820 | | | | |
| 6 | 34,838 | 36,548 | 41,907 | | | | |
| 7 | 34,923 | 36,713 | 42,000 | | | | |
| 8 | 35,007 | 36,886 | 42,083 | | | | |
| 9 | 35,090 | 37,059 | 42,168 | | | | |
| 10 | 35,176 | 37,239 | 42,258 | | | | |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 863 | 1,687 | 918 | Q=1 | Q=2 | Q=3 | Q=4 |
| Average lit./min | 57.5 | 111.8 | 61.2 | Q=1 | Q=2 | Q=3 | Q=4 |
| Friction loss (P) | 0.63 | 2.31 | 0.71 | Q=5 | Q=6 | Q=7 | Q=7 |



Water Injection Ratio (q : lit./min/m)

Lugeon value : (128) Lu'
 Critical Pressure: >2.2 kg/cm²


Remarks: Pressure could not built at 7 kg/cm² and 10 kg/cm² due to at 4 kg/cm² water take more than 150 lit./min.

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute
 Prepared by: Azhar Ms. & A. Gill (Inspected by: M. Supa)

Water Pressure Test

Hole No.: M98-1 Stages: 2/14
 Location: Dam Axis (Right Bank, Dam Crest) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (P): $1 \times 10^{-4} \times Q^{1.71}$ Date: 4/December/1998

| Ground elevation: EL | | Groundwater level (L _g): Nil | | Gauge height (L _g): 0.73 m | | | |
|---|----------------|--|----------------|--|----------------|----------------|----------------|
| Pipe length from pressure gauge to borehole mouth: (L _b) = 7.76 m | | Depth of test section: 5 m to (L _b) = 10 m | | Length of section (L _s): 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 10:04 | 10:35 | 12:00 | 12:11 | 12:22 | | |
| Q (m ³ /min) | 49,372 | 51,421 | 55,757 | 57,644 | 59,248 | | |
| 1 | 49,464 | 51,570 | 55,927 | 57,792 | 59,330 | | |
| 2 | 49,540 | 51,734 | 56,100 | 57,959 | 59,412 | | |
| 3 | 49,619 | 51,869 | 56,270 | 58,087 | 59,496 | | |
| 4 | 49,697 | 52,019 | 56,445 | 58,233 | 59,578 | | |
| 5 | 49,775 | 52,166 | 56,621 | 58,386 | 59,663 | | |
| 6 | 49,853 | 52,318 | 56,799 | 58,532 | 59,756 | | |
| 7 | 49,931 | 52,459 | 56,979 | 58,688 | 59,833 | | |
| 8 | 50,013 | 52,605 | 57,138 | 58,844 | 59,922 | | |
| 9 | 50,091 | 52,750 | 57,314 | 59,003 | 60,016 | | |
| 10 | 50,168 | 52,900 | 57,485 | 59,160 | 60,109 | | |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 796 | 1,479 | 1,728 | 1,516 | 861 | Q=5 | Q=6 |
| Average lit./min | 79.6 | 147.9 | 172.8 | 151.6 | 86.1 | Q=5 | Q=6 |
| Friction loss (P) | 0.71 | 2.42 | 3.29 | 2.54 | 0.83 | Q=7 | Q=7 |



Water Injection Ratio (q : lit./min/m)

Lugeon value : (110) Lu'
 Critical Pressure: >2.8 kg/cm²


Remarks: At 7 and 10 kg/cm², pressure could not built.

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute
 Prepared by: Azhar (Inspected by: A. Gill)

Water Pressure Test

Hole No.: M98-1 Stages: 3/14
 Location: Dam Axis (Right Bank, Dam Crest) Dia. of Hole: 76 m/m
 Hole Inclination (α): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁻⁶ x Q² m Date: 8/December/1998

| Ground elevation: EL. m | | Groundwater level (L _g): Nil | | Gauge height (L _g): 0.73 m | | | |
|---|-----------------|---|-----------------|--|-----------------|-----------------|-----------------|
| Pipe length from pressure gauge to borehole mouth: (L _g) = 7.20 m | | Depth of test section: 10 m to (L _g) = 15 m | | Length of section (L _s): 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge # (kg/cm ²) | P ₀₁ | P ₀₂ | P ₀₃ | P ₀₄ | P ₀₅ | P ₀₆ | P ₀₇ |
| Start time | 14:51 | 15:14 | 15:36 | 15:50 | 16:05 | | |
| Q (mm) | 77,259 | 78,226 | 79,620 | 81,226 | 82,492 | | |
| 1 | 77,215 | 78,351 | 79,770 | 81,359 | 82,544 | | |
| 2 | 77,366 | 78,466 | 79,926 | 81,469 | 82,593 | | |
| 3 | 77,425 | 78,579 | 80,075 | 81,586 | 82,639 | | |
| 4 | 77,479 | 78,695 | 80,225 | 81,700 | 82,687 | | |
| 5 | 77,537 | 78,809 | 80,375 | 81,815 | 82,747 | | |
| 6 | 77,589 | 78,923 | 80,526 | 81,928 | 82,803 | | |
| 7 | 77,642 | 79,038 | 80,676 | 82,036 | 82,862 | | |
| 8 | 77,690 | 79,149 | 80,827 | 82,138 | 82,912 | | |
| 9 | 77,734 | 79,264 | 80,976 | 82,231 | 82,949 | | |
| 10 | 77,781 | 79,378 | 81,131 | 82,327 | 82,989 | | |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 572 | 1,142 | 1,511 | 1,091 | 497 | | |
| Average lit./min | 57.2 | 114.2 | 151.1 | 109.1 | 49.7 | | |
| Finish time | 15:31 | 15:24 | 15:36 | 16:03 | 16:15 | | |
| (P ₀) | 0.62 | 1.96 | 3.41 | 1.79 | 0.38 | | |
| Friction Loss (P _f) = p _f (L _g + L _s) [kg/cm ²] | | | | | | | |




Water Injection Ratio (q : lit./min/m)
 Lu_g value: (80)
 Critical Pressure: >4.9 kg/cm²

Remarks: Due to very high loss of water, pressure did not developed beyond 7 kg/cm².
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the last previous one minute.
 Prepared by: A. Hamid & Azhar Inspected by: A. Gill

Water Pressure Test

Hole No.: M98-1 Stages: 4/14
 Location: Dam Axis (Right Bank, Dam Crest) Dia. of Hole: 76 m/m
 Hole Inclination (α): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁻⁶ x Q² m Date: 17/December/1998

| Ground elevation: EL. m | | Groundwater level (L _g): Nil | | Gauge height (L _g): 0.73 m | | | |
|---|-----------------|---|-----------------|--|-----------------|-----------------|-----------------|
| Pipe length from pressure gauge to borehole mouth: (L _g) = 9.34 m | | Depth of test section: 14.5 m to (L _g) = 20 m | | Length of section (L _s): 5.5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge # (kg/cm ²) | P ₀₁ | P ₀₂ | P ₀₃ | P ₀₄ | P ₀₅ | P ₀₆ | P ₀₇ |
| Start time | 15:15 | 15:30 | 15:45 | 16:00 | 16:15 | 16:30 | 16:50 |
| Q (mm) | 98,290 | 99,000 | 200 | 2,000 | 3,660 | 5,100 | 6,250 |
| 1 | 98,359 | 99,092 | 327 | 2,141 | 3,792 | 5,206 | 6,321 |
| 2 | 98,416 | 99,192 | 454 | 2,298 | 3,923 | 5,312 | 6,393 |
| 3 | 98,473 | 99,297 | 583 | 2,448 | 4,057 | 5,418 | 6,464 |
| 4 | 98,528 | 99,383 | 713 | 2,601 | 4,186 | 5,524 | 6,535 |
| 5 | 98,584 | 99,479 | 839 | 2,746 | 4,320 | 5,629 | 6,606 |
| 6 | 98,638 | 99,575 | 969 | 2,896 | 4,452 | 5,735 | 6,678 |
| 7 | 98,694 | 99,671 | 1,099 | 3,045 | 4,584 | 5,841 | 6,749 |
| 8 | 98,750 | 99,767 | 1,228 | 3,194 | 4,716 | 5,947 | 6,822 |
| 9 | 98,805 | 99,863 | 1,356 | 3,345 | 4,846 | 6,053 | 6,894 |
| 10 | 98,862 | 99,959 | 1,485 | 3,493 | 4,979 | 6,159 | 6,966 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 572 | 959 | 1,285 | 1,493 | 1,319 | 1,059 | 716 |
| Average lit./min | 57.2 | 95.9 | 128.5 | 149.3 | 131.9 | 105.9 | 71.6 |
| Finish time | 15:25 | 15:40 | 15:55 | 16:10 | 16:25 | 16:40 | 17:00 |
| (P ₀) | 0.70 | 1.93 | 3.43 | 4.61 | 3.61 | 2.34 | 1.08 |
| Friction Loss (P _f) = p _f (L _g + L _s) [kg/cm ²] | | | | | | | |



Water Injection Ratio (q : lit./min/m)
 Lu_g value: (42)
 Critical Pressure: >7.2 kg/cm²

Remarks:
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the last previous one minute.
 Prepared by: Farhat M. Shah Inspected by: M. Suga

Water Pressure Test


Hole No.: M98-1 Stage: 5/14
 Location: Dam Axis (Right Bank, Dam Crest) Dia. of Hole: 101 m/m
 Hole Inclination (α): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁻⁶ x Q^{1.75} m Date: 1/January/1998

| Ground elevation: EL | | Groundwater level (L _g): | | NII | | Gauge height (L _g): | | 0.73 m | |
|---|--------|---|--------|-----------------------------|--------|---|--------|--------|-----|
| Pipe length from pressure gauge to borehole mouth: (L _g) = 9.30 m | | Depth of test section: (L _s) = 20 m | | to (L _g) = 25 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | | | |
| Gauge P. | Pa1 | Pa2 | Pa3 | Pa4 | Pa5 | Pa6 | Pa7 | Pa8 | Pa9 |
| 1 | 11:35 | 11:48 | 12:06 | 12:13 | 12:35 | 12:47 | 13:00 | | |
| Q (m ³ /min) | 37.970 | 38.120 | 38.410 | 38.910 | 39.610 | 40.130 | 40.500 | | |
| 1 | 37.981 | 38.149 | 38.450 | 38.970 | 39.657 | 40.164 | 40.518 | | |
| 2 | 37.994 | 38.167 | 38.490 | 39.028 | 39.705 | 40.198 | 40.536 | | |
| 3 | 38.006 | 38.191 | 38.530 | 39.087 | 39.753 | 40.232 | 40.554 | | |
| 4 | 38.017 | 38.213 | 38.570 | 39.146 | 39.801 | 40.266 | 40.578 | | |
| 5 | 38.028 | 38.236 | 38.611 | 39.205 | 39.847 | 40.301 | 40.591 | | |
| 6 | 38.039 | 38.260 | 38.651 | 39.265 | 39.894 | 40.335 | 40.610 | | |
| 7 | 38.049 | 38.282 | 38.691 | 39.325 | 39.942 | 40.370 | 40.630 | | |
| 8 | 38.059 | 38.305 | 38.731 | 39.386 | 39.990 | 40.404 | 40.650 | | |
| 9 | 38.070 | 38.328 | 38.771 | 39.447 | 40.037 | 40.438 | 40.669 | | |
| 10 | 38.080 | 38.351 | 38.812 | 39.500 | 40.084 | 40.473 | 40.689 | | |
| 11 | | | | | | | | | |
| 12 | | | | | | | | | |
| 13 | | | | | | | | | |
| 14 | | | | | | | | | |
| 15 | | | | | | | | | |
| Total | Q=1 | Q=2 | Q=3 | Q=4 | Q=5 | Q=6 | Q=7 | | |
| Ill. | 237 | 362 | 344 | 710 | 602 | 454 | 290 | | |
| Average | Q=1 | Q=2 | Q=3 | Q=4 | Q=5 | Q=6 | Q=7 | | |
| Ill./min | 23.7 | 36.2 | 34.4 | 71.0 | 60.2 | 45.4 | 29.0 | | |
| Remarks | 11:35 | 11:38 | 12:10 | 12:22 | 12:43 | 12:57 | 13:10 | | |
| Friction Loss (P _f) = p(L _g + L _s) [kg/cm ²] | 0.03 | 0.14 | 0.43 | 0.91 | 0.59 | 0.31 | 0.10 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.3 | 4.6 | 4.6 | 8.0 | 8.0 | 11.8 | 9.5 | 6.9 | 3.8 |
| Water Pressure in kg/cm ² | 11 | 10 | 10 | 10 | 10 | 10 | 10 | 10 | 10 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m) | 3.6 | 6.4 | 8.9 | 11.3 | 8.7 | 6.2 | 3.6 | | |
| Water Pressure in kg/cm ² | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 |
| Water Injection Ratio (q: ill/min/m | | | | | | | | | |

Water Pressure Test

Hole No.: M98-1 Stage: 7/14
 Location: Dam Axis (Right Bank, Dam Crest) Dia. of Hole: 101 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁴ x Q^{1.75} Date: 3/January/1998

| Ground elevation: EL. m | | Groundwater level (L _g): | | NIL | | Gauge height (L _g): 0.73 m | |
|---|----------------|--|----------------|----------------------------|----------------|--|----------------|
| Pipe length from pressure gauge to borehole mouth: (L _p)= 7.50 m | | Depth of test section to (L _s)= 30 m | | to (L _g)= 35 m | | Length of section (L _s)= 5 m | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 12:30 | 12:43 | 12:55 | 13:08 | 13:20 | 13:33 | 13:45 |
| Q (m ³ /min) | 54.440 | 54.660 | 55.220 | 55.950 | 56.960 | 57.900 | 58.610 |
| 1 | 54.454 | 54.703 | 55.281 | 56.031 | 57.034 | 57.966 | 58.644 |
| 2 | 54.477 | 54.784 | 55.342 | 56.117 | 57.120 | 58.032 | 58.688 |
| 3 | 54.496 | 54.832 | 55.404 | 56.207 | 57.205 | 58.100 | 58.727 |
| 4 | 54.514 | 54.875 | 55.465 | 56.298 | 57.293 | 58.167 | 58.767 |
| 5 | 54.533 | 54.917 | 55.526 | 56.390 | 57.380 | 58.235 | 58.807 |
| 6 | 54.552 | 54.917 | 55.587 | 56.487 | 57.468 | 58.303 | 58.847 |
| 7 | 54.570 | 54.954 | 55.648 | 56.585 | 57.556 | 58.370 | 58.886 |
| 8 | 54.588 | 55.003 | 55.710 | 56.685 | 57.644 | 58.439 | 58.926 |
| 9 | 54.607 | 55.045 | 55.771 | 56.787 | 57.731 | 58.507 | 58.966 |
| 10 | 54.625 | 55.087 | 55.833 | 56.890 | 57.814 | 58.575 | 59.005 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 185 | 427 | 613 | 940 | 1254 | 1675 | 2095 |
| Average lit./min | 18.5 | 42.7 | 61.3 | 94.0 | 125.4 | 167.5 | 209.5 |
| Flow time | 12:40 | 12:53 | 13:05 | 13:18 | 13:30 | 13:43 | 13:55 |
| (P ₁) | 0.12 | 0.61 | 1.25 | 2.91 | 2.41 | 1.52 | 0.53 |
| Friction Loss (P _f) = p(L _p + L _s) (kg/cm ²) | | | | | | | |
| Remarks: | | | | | | | |




Water Injection Rate (q) : lit/min/m
 Lugeon value : (14)
 Critical Pressure : 9.1 kg/cm²

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.
 Prepared by: A. Hamid & Azhor
 Inspected by: A. Gill

Water Pressure Test

Hole No.: M98-1 Stage: 8/14
 Location: Dam Axis (Right Bank, Dam Crest) Dia. of Hole: 101 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁴ x Q^{1.75} Date: 4/January/1999

| Ground elevation: EL. m | | Groundwater level (L _g): | | NIL | | Gauge height (L _g): 0.73 m | |
|---|----------------|--|----------------|----------------------------|----------------|--|----------------|
| Pipe length from pressure gauge to borehole mouth: (L _p)= 7.50 m | | Depth of test section to (L _s)= 35 m | | to (L _g)= 40 m | | Length of section (L _s)= 5 m | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 12:00 | 12:12 | 12:25 | 12:38 | 12:50 | 13:03 | 13:15 |
| Q (m ³ /min) | 66.300 | 66.600 | 67.100 | 67.800 | 68.600 | 69.300 | 69.800 |
| 1 | 66.323 | 66.641 | 67.158 | 67.875 | 68.691 | 69.374 | 69.854 |
| 2 | 66.350 | 66.682 | 67.217 | 67.951 | 68.752 | 69.418 | 69.889 |
| 3 | 66.375 | 66.723 | 67.275 | 68.027 | 68.813 | 69.463 | 69.905 |
| 4 | 66.398 | 66.763 | 67.334 | 68.103 | 68.874 | 69.507 | 69.950 |
| 5 | 66.423 | 66.804 | 67.392 | 68.179 | 68.938 | 69.551 | 69.956 |
| 6 | 66.448 | 66.845 | 67.450 | 68.255 | 68.997 | 69.595 | 69.981 |
| 7 | 66.472 | 66.886 | 67.508 | 68.331 | 69.058 | 69.639 | 70.006 |
| 8 | 66.497 | 66.926 | 67.567 | 68.409 | 69.120 | 69.683 | 70.032 |
| 9 | 66.520 | 66.967 | 67.625 | 68.485 | 69.181 | 69.727 | 70.057 |
| 10 | 66.545 | 67.008 | 67.683 | 68.561 | 69.242 | 69.772 | 70.082 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 245 | 408 | 583 | 761 | 945 | 1127 | 1307 |
| Average lit./min | 24.5 | 40.8 | 58.3 | 76.1 | 94.5 | 112.7 | 130.7 |
| Flow time | 12:10 | 12:22 | 12:35 | 12:48 | 13:00 | 13:13 | 13:25 |
| (P ₁) | 0.23 | 0.64 | 1.29 | 2.18 | 1.82 | 0.75 | 0.25 |
| Friction Loss (P _f) = p(L _p + L _s) (kg/cm ²) | | | | | | | |
| Remarks: | | | | | | | |




Water Injection Rate (q) : lit/min/m
 Lugeon value : 12
 Critical Pressure : >12 kg/cm²

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.
 Prepared by: Azhor
 Inspected by: A. Gill

Water Pressure Test

Hole No.: M98-1 Stage: 9/14
 Location: Dam Axis (Right Bank, Dam Crest) Dia. of Hole: 101 m/m
 Hole Inclination (α): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁶ kg/cm²/m Date: 5/January/1999

| Ground elevation: EL | | Groundwater level (L _g): Nil | | Gauge height (L _g): 0.73 m | | | |
|---|-----------------|---|-----------------|---|-----------------|-----------------|-----------------|
| Pipe length from pressure gauge to borehole mouth: (L _b) = 7.50 m | | Depth of test section to (L _t) = 45 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P _{a1} | P _{a2} | P _{a3} | P _{a4} | P _{a5} | P _{a6} | P _{a7} |
| Start time | 13:10 | 13:25 | 13:40 | 13:55 | 14:10 | 14:25 | 14:40 |
| U (min) | 85.430 | 85.655 | 86.050 | 86.620 | 87.430 | 88.021 | 88.655 |
| 1 | 85.432 | 85.693 | 86.104 | 86.691 | 87.487 | 88.062 | 88.677 |
| 2 | 85.474 | 85.732 | 86.157 | 86.764 | 87.544 | 88.105 | 88.698 |
| 3 | 85.497 | 85.769 | 86.212 | 86.838 | 87.602 | 88.145 | 88.721 |
| 4 | 85.518 | 85.807 | 86.265 | 86.910 | 87.662 | 88.188 | 88.743 |
| 5 | 85.539 | 85.846 | 86.319 | 86.983 | 87.721 | 88.230 | 88.767 |
| 6 | 85.562 | 85.886 | 86.374 | 87.057 | 87.778 | 88.271 | 88.792 |
| 7 | 85.584 | 85.923 | 86.428 | 87.128 | 87.834 | 88.313 | 88.813 |
| 8 | 85.602 | 85.961 | 86.481 | 87.201 | 87.893 | 88.355 | 88.836 |
| 9 | 85.626 | 86.000 | 86.534 | 87.276 | 87.951 | 88.398 | 88.858 |
| 10 | 85.647 | 86.037 | 86.590 | 87.349 | 88.011 | 88.440 | 88.882 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total | Q _{a1} | Q _{a2} | Q _{a3} | Q _{a4} | Q _{a5} | Q _{a6} | Q _{a7} |
| lit. | 217 | 362 | 540 | 779 | 581 | 419 | 227 |
| Average | Q _{a1} | Q _{a2} | Q _{a3} | Q _{a4} | Q _{a5} | Q _{a6} | Q _{a7} |
| lit./min. | 21.7 | 38.2 | 54 | 72.9 | 58.1 | 41.9 | 22.7 |
| Flow time | 13:20 | 13:35 | 13:50 | 14:05 | 14:20 | 14:35 | 14:50 |
| (P) | 0.21 | 0.63 | 1.24 | 2.24 | 1.33 | 0.75 | 0.22 |
| Friction Loss (P _f) = p(L _b + L _t) [kg/cm ²] | | Lugeon value: 11 Lu | | Critical Pressure: >12 kg/cm ² | | Remarks: | |




Water Injection Ratio (q : lit./min/m)
 Lugeon value: 11 Lu
 Critical Pressure: >12 kg/cm²

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.
 Prepared by: Azhor / Hamid Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-1 Stage: 10/14
 Location: Dam Axis (Right Bank, Dam Crest) Dia. of Hole: 101 m/m
 Hole Inclination (α): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁶ kg/cm²/m Date: 10/January/1999

| Ground elevation: EL | | Groundwater level (L _g): Nil | | Gauge height (L _g): 0.73 m | | | |
|---|-----------------|---|-----------------|---|-----------------|-----------------|-----------------|
| Pipe length from pressure gauge to borehole mouth: (L _b) = 7.50 m | | Depth of test section to (L _t) = 45 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P _{a1} | P _{a2} | P _{a3} | P _{a4} | P _{a5} | P _{a6} | P _{a7} |
| Start time | 13:00 | 13:12 | 13:25 | 13:38 | 13:50 | 14:03 | 14:15 |
| U (min) | 13.590 | 13.965 | 14.459 | 15.018 | 15.630 | 16.190 | 16.845 |
| 1 | 13.618 | 14.005 | 14.499 | 15.071 | 15.678 | 16.233 | 16.723 |
| 2 | 13.646 | 14.045 | 14.547 | 15.121 | 15.726 | 16.276 | 16.760 |
| 3 | 13.674 | 14.085 | 14.594 | 15.174 | 15.773 | 16.319 | 16.798 |
| 4 | 13.701 | 14.126 | 14.642 | 15.225 | 15.820 | 16.362 | 16.835 |
| 5 | 13.728 | 14.166 | 14.690 | 15.280 | 15.868 | 16.403 | 16.872 |
| 6 | 13.756 | 14.207 | 14.737 | 15.332 | 15.916 | 16.445 | 16.910 |
| 7 | 13.784 | 14.248 | 14.786 | 15.386 | 15.963 | 16.487 | 16.946 |
| 8 | 13.811 | 14.288 | 14.833 | 15.437 | 16.010 | 16.527 | 16.981 |
| 9 | 13.839 | 14.328 | 14.881 | 15.492 | 16.058 | 16.570 | 17.019 |
| 10 | 13.867 | 14.369 | 14.929 | 15.545 | 16.106 | 16.612 | 17.056 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total | Q _{a1} | Q _{a2} | Q _{a3} | Q _{a4} | Q _{a5} | Q _{a6} | Q _{a7} |
| lit. | 377 | 404 | 479 | 527 | 476 | 422 | 371 |
| Average | Q _{a1} | Q _{a2} | Q _{a3} | Q _{a4} | Q _{a5} | Q _{a6} | Q _{a7} |
| lit./min. | 27.7 | 40.4 | 47.9 | 52.7 | 47.6 | 42.2 | 37.1 |
| Flow time | 13:10 | 13:22 | 13:35 | 13:48 | 14:00 | 14:13 | 14:25 |
| (P) | 0.37 | 0.77 | 1.08 | 1.30 | 1.07 | 0.94 | 0.65 |
| Friction Loss (P _f) = p(L _b + L _t) [kg/cm ²] | | Lugeon value: 9.2 Lu | | Critical Pressure: >14 kg/cm ² | | Remarks: | |



Water Injection Ratio (q : lit./min/m)
 Lugeon value: 9.2 Lu
 Critical Pressure: >14 kg/cm²

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.
 Prepared by: Azhor / Hamid Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-1 Stage: 11/14
 Location: Dam Axis (Right Bank, Dam Crest) Dia. of Hole: 101 m/m
 Hole Inclination (α): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁻⁴ x Q^{1.75} Date: 13/January/1999

| Ground elevation: EL | | Groundwater level (L _g): GL = 50.30 m | | Gauge height (L _g): 0.73 m | | |
|---|-----------------|---|-----------------|---|-----------------|-----------------|
| Pipe length from pressure gauge to borehole mouth: (L _b) = 7.00 m | | Depth of test section: GL - (L _b) = 55 m to (L _g) = 5 m | | Length of section (L _s) = 5 m | | |
| Reading of flow meter | | | | | | |
| Gauge P. (kg/cm ²) | P _{a1} | P _{a2} | P _{a3} | P _{a4} | P _{a5} | P _{a7} |
| Start time | 11:00 | 11:12 | 11:25 | 11:38 | 11:53 | 12:18 |
| Q (lit/min) | 31.000 | 31.520 | 32.170 | 33.030 | 34.280 | 34.860 |
| 1 | 31.046 | 31.577 | 32.240 | 33.120 | 34.362 | 35.257 |
| 2 | 31.093 | 31.634 | 32.312 | 33.210 | 34.444 | 35.323 |
| 3 | 31.137 | 31.691 | 32.383 | 33.304 | 34.527 | 35.390 |
| 4 | 31.180 | 31.747 | 32.454 | 33.398 | 34.608 | 35.456 |
| 5 | 31.222 | 31.804 | 32.525 | 33.494 | 34.690 | 35.523 |
| 6 | 31.264 | 31.862 | 32.596 | 33.591 | 34.774 | 35.590 |
| 7 | 31.305 | 31.918 | 32.666 | 33.692 | 34.855 | 35.656 |
| 8 | 31.346 | 31.975 | 32.737 | 33.797 | 34.937 | 35.723 |
| 9 | 31.387 | 32.032 | 32.810 | 33.907 | 35.019 | 35.789 |
| 10 | 31.428 | 32.088 | 32.884 | 34.020 | 35.102 | 35.856 |
| 11 | | | | | | |
| 12 | | | | | | |
| 13 | | | | | | |
| 14 | | | | | | |
| 15 | | | | | | |
| Total lit. | 428 | 568 | 714 | 890 | 1122 | 1228 |
| Average lit./min | 42.8 | 56.8 | 71.4 | 89.0 | 112.2 | 122.8 |
| Final time | 11:10 | 11:22 | 11:35 | 11:48 | 12:03 | 12:28 |
| (P _f) | 0.94 | 1.64 | 2.38 | 4.91 | 3.40 | 2.25 |
| Friction Loss (P _f) = p(L _b + L _s) [kg/cm ²] | | | | | | |
| Remarks: | | | | | | |

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute
 Prepared by: Azhor / Hamid Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-1 Stage: 12/14
 Location: Dam Axis (Right Bank, Dam Crest) Dia. of Hole: 76 m/m
 Hole Inclination (α): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁻⁴ x Q^{1.75} Date: 28/January/1999

| Ground elevation: EL | | Groundwater level (L _g): GL = 50.30 m | | Gauge height (L _g): 0.73 m | | |
|---|-----------------|--|-----------------|---|-----------------|-----------------|
| Pipe length from pressure gauge to borehole mouth: (L _b) = 7.00 m | | Depth of test section: GL - (L _b) = 55 m to (L _g) = 60 m | | Length of section (L _s) = 5 m | | |
| Reading of flow meter | | | | | | |
| Gauge P. (kg/cm ²) | P _{a1} | P _{a2} | P _{a3} | P _{a4} | P _{a5} | P _{a7} |
| Start time | 15:00 | 15:13 | 15:25 | 15:40 | 15:54 | 16:20 |
| Q (lit/min) | 73.030 | 73.100 | 73.930 | 74.910 | 76.010 | 76.820 |
| 1 | 73.051 | 73.284 | 74.009 | 75.005 | 76.092 | 76.884 |
| 2 | 73.075 | 73.295 | 74.086 | 75.100 | 76.171 | 76.948 |
| 3 | 73.092 | 73.444 | 74.164 | 75.195 | 76.250 | 77.010 |
| 4 | 73.112 | 73.495 | 74.240 | 75.289 | 76.330 | 77.074 |
| 5 | 73.132 | 73.550 | 74.317 | 75.385 | 76.411 | 77.137 |
| 6 | 73.151 | 73.605 | 74.396 | 75.480 | 76.491 | 77.197 |
| 7 | 73.170 | 73.662 | 74.474 | 75.574 | 76.570 | 77.256 |
| 8 | 73.190 | 73.715 | 74.552 | 75.667 | 76.652 | 77.297 |
| 9 | 73.211 | 73.773 | 74.630 | 75.760 | 76.733 | 77.345 |
| 10 | 73.234 | 73.830 | 74.708 | 75.853 | 76.811 | 77.446 |
| 11 | | | | | | |
| 12 | | | | | | |
| 13 | | | | | | |
| 14 | | | | | | |
| 15 | | | | | | |
| Total lit. | 204 | 530 | 778 | 945 | 801 | 626 |
| Average lit./min | 20.4 | 53.0 | 77.8 | 94.5 | 80.1 | 62.6 |
| Final time | 15:10 | 15:23 | 15:35 | 15:50 | 16:04 | 16:30 |
| (P _f) | 0.24 | 1.56 | 3.32 | 4.87 | 3.51 | 2.16 |
| Friction Loss (P _f) = p(L _b + L _s) [kg/cm ²] | | | | | | |
| Remarks: | | | | | | |

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute
 Prepared by: Azhor / Hamid Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-1 Stage: 13/14
 Location: Dam Axis (Right Bank, Dam Crest) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁶ x Q^{1.75} Date: 30/January/1999

| Ground elevation: EL. m | | Groundwater level (L _g): GL. m | | Gauge height (L _g): 0.73 m | | |
|--|--------|---|--------|---|--------|--------|
| Pipe length from pressure gauge to borehole mouth: (L _p) = 7.00 m | | Depth of test section: GL. - (L _g) = 65 m | | Length of section (L _s) = 5 m | | |
| Reading of flow meter | | | | | | |
| Gauge P. (kg/cm ²) | P1 | P2 | P3 | P4 | P5 | P6 |
| Start time | 15:15 | 15:27 | 15:40 | 15:52 | 16:05 | 16:17 |
| Q (m ³ /min) | 11.270 | 11.828 | 12.670 | 13.738 | 14.890 | 16.270 |
| 1 | 11.313 | 11.894 | 12.764 | 13.838 | 14.972 | 16.410 |
| 2 | 11.356 | 11.938 | 12.846 | 13.933 | 15.054 | 16.648 |
| 3 | 11.398 | 12.022 | 12.930 | 14.030 | 15.136 | 16.942 |
| 4 | 11.441 | 12.087 | 13.013 | 14.126 | 15.219 | 17.288 |
| 5 | 11.484 | 12.153 | 13.098 | 14.221 | 15.300 | 17.683 |
| 6 | 11.526 | 12.219 | 13.184 | 14.318 | 15.382 | 18.128 |
| 7 | 11.568 | 12.283 | 13.268 | 14.414 | 15.465 | 18.623 |
| 8 | 11.612 | 12.348 | 13.351 | 14.512 | 15.545 | 19.168 |
| 9 | 11.655 | 12.413 | 13.434 | 14.609 | 15.628 | 19.763 |
| 10 | 11.698 | 12.479 | 13.518 | 14.706 | 15.710 | 20.408 |
| 11 | | | | | | |
| 12 | | | | | | |
| 13 | | | | | | |
| 14 | | | | | | |
| 15 | | | | | | |
| Calculation of Lupegon value | | | | | | |
| $P = P_0 + 0.1(\sin(\theta)L_p + L_s) \cdot Pr$ [kg/cm ²], $q = Q_p/L_s$ [lit/min/m] | | | | | | |
| | P1= | 5.0 | 6.6 | 8.6 | 13.0 | 17.0 |
| | P2= | 6.6 | 7.9 | 9.9 | 14.4 | 19.4 |
| | P3= | 7.9 | 9.6 | 12.4 | 16.4 | 22.8 |
| | P4= | 9.6 | 11.3 | 14.4 | 19.4 | 26.8 |
| | P5= | 11.3 | 13.0 | 16.4 | 22.8 | 31.3 |
| | P6= | 13.0 | 14.8 | 19.4 | 26.8 | 36.3 |
| | P7= | 14.8 | 16.6 | 22.8 | 31.3 | 41.8 |
| | | | | | | |
| Total | | Q=1 | Q=2 | Q=3 | Q=4 | Q=5 |
| Lit. | | 428 | 651 | 848 | 968 | 1070 |
| Average | | Q=1 | Q=2 | Q=3 | Q=4 | Q=5 |
| Lit./Area | | 42.8 | 65.1 | 84.8 | 96.8 | 107.0 |
| Friction Loss | | 15:25 | 15:37 | 15:50 | 16:02 | 16:15 |
| (P) | | 3.10 | 2.52 | 2.25 | 2.08 | 1.94 |
| Friction Loss (P) = p(L _p + L _s) [kg/cm ²] | | | | | | |
| Lupegon value: (20) Lu | | | | | | |
| Critical Pressure: | | >9.6 kg/cm ² | | | | |
| Remarks: | | | | | | |

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute
 Prepared by: Azhor / Humid Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-1 Stage: 14/14
 Location: Dam Axis (Right Bank, Dam Crest) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁶ x Q^{1.75} Date: 02/February/1999


| Ground elevation: EL. m | | Groundwater level (L _g): GL. m | | Gauge height (L _g): 0.73 m | | |
|--|-------|---|-------|---|-------|-------|
| Pipe length from pressure gauge to borehole mouth: (L _p) = 7.00 m | | Depth of test section: GL. - (L _g) = 65 m | | Length of section (L _s) = 5 m | | |
| Reading of flow meter | | | | | | |
| Gauge P. (kg/cm ²) | P1 | P2 | P3 | P4 | P5 | P6 |
| Start time | 11:45 | 11:57 | 12:10 | 12:22 | 12:34 | 12:46 |
| Q (m ³ /min) | 7.974 | 7.980 | 7.981 | 7.981 | 7.981 | 7.981 |
| 1 | 7.974 | 7.980 | 7.981 | 7.981 | 7.981 | 7.981 |
| 2 | 7.974 | 7.980 | 7.981 | 7.981 | 7.981 | 7.981 |
| 3 | 7.974 | 7.980 | 7.981 | 7.981 | 7.981 | 7.981 |
| 4 | 7.974 | 7.980 | 7.981 | 7.981 | 7.981 | 7.981 |
| 5 | 7.974 | 7.980 | 7.981 | 7.981 | 7.981 | 7.981 |
| 6 | 7.974 | 7.980 | 7.981 | 7.981 | 7.981 | 7.981 |
| 7 | 7.974 | 7.980 | 7.981 | 7.981 | 7.981 | 7.981 |
| 8 | 7.974 | 7.980 | 7.981 | 7.981 | 7.981 | 7.981 |
| 9 | 7.974 | 7.980 | 7.981 | 7.981 | 7.981 | 7.981 |
| 10 | 7.974 | 7.980 | 7.981 | 7.981 | 7.981 | 7.981 |
| 11 | | | | | | |
| 12 | | | | | | |
| 13 | | | | | | |
| 14 | | | | | | |
| 15 | | | | | | |
| Calculation of Lupegon value | | | | | | |
| $P = P_0 + 0.1(\sin(\theta)L_p + L_s) \cdot Pr$ [kg/cm ²], $q = Q_p/L_s$ [lit/min/m] | | | | | | |
| | P1= | 6.1 | 9.1 | 12.1 | 15.1 | 18.1 |
| | P2= | 9.1 | 12.1 | 15.1 | 18.1 | 21.1 |
| | P3= | 12.1 | 15.1 | 18.1 | 21.1 | 24.1 |
| | P4= | 15.1 | 18.1 | 21.1 | 24.1 | 27.1 |
| | P5= | 18.1 | 21.1 | 24.1 | 27.1 | 30.1 |
| | P6= | 21.1 | 24.1 | 27.1 | 30.1 | 33.1 |
| | P7= | 24.1 | 27.1 | 30.1 | 33.1 | 36.1 |
| | | | | | | |
| Total | | Q=1 | Q=2 | Q=3 | Q=4 | Q=5 |
| Lit. | | 0.0 | 0.1 | 0.2 | 0.3 | 0.4 |
| Average | | Q=1 | Q=2 | Q=3 | Q=4 | Q=5 |
| Lit./Area | | 0.00 | 0.01 | 0.02 | 0.03 | 0.04 |
| Friction Loss | | 11:55 | 12:07 | 12:20 | 12:32 | 12:44 |
| (P) | | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Friction Loss (P) = p(L _p + L _s) [kg/cm ²] | | | | | | |
| Lupegon value: (20) Lu | | 0.0 | | | | |
| Critical Pressure: | | 1.5 kg/cm ² | | | | |
| Remarks: | | | | | | |

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute
 Prepared by: Azhor / Humid Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-2 Stage: 1/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁶ m/m Date: 17/December/1998

| Ground elevation : EL. m | | Groundwater level (L _g): Nil | | Gauge height (L _g): 0.86 m | | | |
|--|----------------|---|----------------|--|----------------|----------------|----------------|
| Pipe length from pressure gauges to borehole mouth: (L _b)= 7.50 m | | Depth of test section m to (L _b)= 7 m | | Length of section (L _s)= 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 13:37 | 13:40 | | | | | |
| Q (l/min) | 11,320 | 12,040 | | | | | |
| 1 | 11,380 | 12,197 | | | | | |
| 2 | 11,445 | 12,332 | | | | | |
| 3 | 11,506 | 12,480 | | | | | |
| 4 | 11,568 | 12,630 | | | | | |
| 5 | 11,629 | | | | | | |
| 6 | 11,690 | | | | | | |
| 7 | 11,751 | | | | | | |
| 8 | 11,810 | | | | | | |
| 9 | 11,870 | | | | | | |
| 10 | 11,929 | | | | | | |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 609 | 590 | | | | | |
| Average lit./min | 60.9 | 147.5 | | | | | |
| Friction loss (Pa) | 0.31 | 1.79 | | | | | |
| Friction Loss (Pr) = p(L _s + L _b) [kg/cm ²] | | | | | | | |




Calculation of Lugeon value
 $P = P_0 + 0.1(\sin(\theta))L_s + L_b \cdot Pr$ [kg/cm²], $q = Q/L_s$ [lit/min/m]
 P₁= 1.2 q₁= 12.2
 P₂= 2.7 q₂= 29.5
 P₃= ... q₃= ...
 P₄= ... q₄= ...
 P₅= ... q₅= ...
 P₆= ... q₆= ...
 P₇= ... q₇= ...
 Lugeon value : (112) Lu' kg/cm²
 Critical Pressure: >2.7 kg/cm²

Remarks : Packer leaked at 1kg/cm² and 2 kg/cm².
 Note : Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.
 Prepared by : Farhat M. Shah Inspected by : M. Suga

Water Pressure Test

Hole No.: M98-2 Stage: 2/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁶ m/m Date: 18/December/1998

| Ground elevation : EL. m | | Groundwater level (L _g): Nil | | Gauge height (L _g): 0.86 m | | | |
|--|----------------|--|----------------|--|----------------|----------------|----------------|
| Pipe length from pressure gauges to borehole mouth: (L _b)= 6.89 m | | Depth of test section m to (L _b)= 10 m | | Length of section (L _s)= 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 12:05 | 12:30 | 12:35 | 13:10 | | | |
| Q (l/min) | 18,930 | 20,100 | 20,200 | 24,300 | | | |
| 1 | 19,002 | 20,238 | 20,300 | 24,367 | | | |
| 2 | 19,073 | 20,357 | 20,398 | 24,436 | | | |
| 3 | 19,143 | 20,477 | 20,494 | 24,502 | | | |
| 4 | 19,212 | 20,601 | | 24,568 | | | |
| 5 | 19,279 | 20,727 | | 24,633 | | | |
| 6 | 19,346 | 20,855 | | 24,699 | | | |
| 7 | 19,413 | 20,982 | | 24,766 | | | |
| 8 | 19,480 | 21,106 | | 24,831 | | | |
| 9 | 19,547 | 21,223 | | 24,898 | | | |
| 10 | 19,614 | 21,345 | | 24,963 | | | |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 684 | 1,245 | 294 | 663 | | | |
| Average lit./min | 68.4 | 124.5 | 98.0 | 66.3 | | | |
| Friction loss (Pa) | 0.49 | 1.01 | 1.80 | 0.46 | | | |
| Friction Loss (Pr) = p(L _s + L _b) [kg/cm ²] | | | | | | | |




Calculation of Lugeon value
 $P = P_0 + 0.1(\sin(\theta))L_s + L_b \cdot Pr$ [kg/cm²], $q = Q/L_s$ [lit/min/m]
 P₁= 1.3 q₁= 13.7
 P₂= 3.2 q₂= 24.9
 P₃= 2.3 q₃= 19.6
 P₄= 1.4 q₄= 13.3
 P₅= ... q₅= ...
 P₆= ... q₆= ...
 P₇= ... q₇= ...
 Lugeon value : (65) Lu' kg/cm²
 Critical Pressure: >3.2 kg/cm²

Remarks : Due to high water loss all stages could not be completed. Equipment condition unsatisfactory. Test had to be stopped three times due to puncture of delivery hose.
 Note : Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.
 Prepared by : Farhat M. Shah Inspected by : M. Suga

Water Pressure Test

Hole No.: M98-2 Stage: 3/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1 x 10⁻³ kg/cm²/m Date: 20/December/1998

| Ground elevation: EL. m | | Groundwater level (L _g): Nil | | Gauge height (L _g): 0.86 m | | | |
|--|----------------|---|----------------|---|----------------|----------------|----------------|
| Pipe length from pressure gauge to borehole mouth: (L _g) = 6.81 m | | Depth of test section m to (L _g) = 15 m | | Length of section (L _g) = 5 m | | | |
| Group P _i (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 12:30 | 13:04 | 13:16 | 13:30 | 13:45 | | |
| Q (m ³ /min) | 35.561 | 36.220 | 34.000 | 39.370 | 40.130 | | |
| 1 | 35.608 | 36.311 | 38.125 | 39.436 | 40.167 | | |
| 2 | 35.655 | 36.391 | 38.258 | 39.504 | 40.207 | | |
| 3 | 35.702 | 36.473 | 38.374 | 39.575 | 40.250 | | |
| 4 | 35.752 | 36.558 | 38.497 | 39.647 | 40.294 | | |
| 5 | 35.802 | 36.642 | 38.516 | 39.720 | 40.338 | | |
| 6 | 35.852 | 36.726 | 38.790 | 39.792 | 40.382 | | |
| 7 | 35.902 | 36.811 | 38.858 | 39.867 | 40.425 | | |
| 8 | 35.952 | 36.899 | 38.980 | 39.937 | 40.465 | | |
| 9 | 36.003 | 36.983 | 39.085 | 40.004 | 40.498 | | |
| 10 | 36.056 | 37.072 | 39.186 | 40.073 | 40.529 | | |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 496 | 842 | 1,186 | 703 | 399 | | |
| Average lit./min | 49.6 | 84.2 | 118.6 | 70.3 | 39.9 | | |
| Friction Loss (Pr) = p(L _g + L _g) [kg/cm ²] | 0.37 | 1.05 | 2.07 | 0.74 | 0.24 | | |




Water Pressure in kg/cm²
 Water Injection Ratio (q : lit./min/m)
 Lugeon value: (36) Lu'
 Critical Pressure: >6.3 kg/cm²

Remarks: 10 kg/cm² pressure could not built, due to more than maximum discharge of pump.
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the last previous one minute
 Prepared by: A. Humid & Azhor Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-2 Stage: 4/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1 x 10⁻³ kg/cm²/m Date: 22/December/1998

| Ground elevation: EL. m | | Groundwater level (L _g): Nil | | Gauge height (L _g): 0.86 m | | | |
|--|----------------|---|----------------|---|----------------|----------------|----------------|
| Pipe length from pressure gauge to borehole mouth: (L _g) = 6.75 m | | Depth of test section m to (L _g) = 20 m | | Length of section (L _g) = 5 m | | | |
| Group P _i (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 12:30 | 12:45 | 12:57 | 13:10 | 13:22 | 13:35 | 13:50 |
| Q (m ³ /min) | 5.784.9 | 5.798.0 | 5.813.5 | 5.838.0 | 5.862.0 | 5.879.0 | 5.888.9 |
| 1 | 5.785.5 | 5.799.2 | 5.815.3 | 5.840.2 | 5.863.4 | 5.880.0 | 5.889.3 |
| 2 | 5.786.1 | 5.800.5 | 5.817.1 | 5.842.5 | 5.864.9 | 5.880.9 | 5.889.8 |
| 3 | 5.786.7 | 5.801.7 | 5.818.9 | 5.844.6 | 5.866.3 | 5.881.8 | 5.890.3 |
| 4 | 5.787.3 | 5.802.9 | 5.820.7 | 5.846.8 | 5.867.7 | 5.882.8 | 5.890.8 |
| 5 | 5.787.9 | 5.804.1 | 5.822.4 | 5.848.8 | 5.869.5 | 5.883.7 | 5.891.2 |
| 6 | 5.788.5 | 5.805.3 | 5.824.2 | 5.850.9 | 5.870.6 | 5.884.7 | 5.891.7 |
| 7 | 5.789.1 | 5.806.4 | 5.825.9 | 5.853.0 | 5.872.0 | 5.885.6 | 5.892.1 |
| 8 | 5.789.7 | 5.807.6 | 5.827.6 | 5.855.1 | 5.873.4 | 5.886.5 | 5.892.6 |
| 9 | 5.790.2 | 5.808.7 | 5.829.3 | 5.857.1 | 5.874.8 | 5.887.5 | 5.893.1 |
| 10 | 5.790.8 | 5.809.9 | 5.831.0 | 5.859.1 | 5.876.2 | 5.888.4 | 5.893.5 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 5.9 | 11.9 | 17.5 | 21.1 | 14.2 | 9.4 | 4.6 |
| Average lit./min | 0.59 | 1.19 | 1.75 | 2.1 | 1.42 | 0.94 | 0.46 |
| Friction Loss (Pr) = p(L _g + L _g) [kg/cm ²] | 0.09 | 0.09 | 0.09 | 0.09 | 0.09 | 0.09 | 0.09 |



Water Pressure in kg/cm²
 Water Injection Ratio (q : lit./min/m)
 Lugeon value: 0.4 Lu
 Critical Pressure: >12 kg/cm²

Remarks:
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the last previous one minute
 Prepared by: Falhat M. Shah Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-2 Stage: S/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (α): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁻⁴ kg/cm²/m Date: 24/December/1998

| Ground elevation: EL | | Groundwater level (L _g): | | Nil | | Gauge height (L _g): | | 0.86 m | |
|--|----------------|---|----------------|----------------|----------------|--------------------------------------|----------------|----------------|----------------|
| Pipe length from pressure gauge to borehole mouth: (L _g) = 7.50 m | | Depth of test section: 20 m to (L _g) = 25 m | | | | Length of section (L _s): | | 5 m | |
| Reading of flow meter | | | | | | | | | |
| Group P _i (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ | P ₈ | P ₉ |
| Start time | 10:55 | 11:10 | 11:25 | 11:40 | 11:55 | 12:10 | 12:20 | 12:30 | 12:40 |
| Q (m ³ /min) | 49.350 | 49.373 | 49.440 | 49.501 | 49.563 | 49.636 | 49.667 | | |
| 1 | 49.351 | 49.378 | 49.446 | 49.508 | 49.588 | 49.638 | 49.668 | | |
| 2 | 49.351 | 49.383 | 49.451 | 49.515 | 49.592 | 49.641 | 49.670 | | |
| 3 | 49.352 | 49.387 | 49.457 | 49.522 | 49.597 | 49.644 | 49.673 | | |
| 4 | 49.353 | 49.392 | 49.462 | 49.529 | 49.601 | 49.647 | 49.674 | | |
| 5 | 49.353 | 49.396 | 49.468 | 49.536 | 49.606 | 49.649 | 49.674 | | |
| 6 | 49.354 | 49.400 | 49.473 | 49.544 | 49.610 | 49.652 | 49.676 | | |
| 7 | 49.355 | 49.404 | 49.478 | 49.549 | 49.615 | 49.655 | 49.677 | | |
| 8 | 49.355 | 49.408 | 49.483 | 49.556 | 49.619 | 49.658 | 49.678 | | |
| 9 | 49.356 | 49.412 | 49.488 | 49.563 | 49.623 | 49.661 | 49.680 | | |
| 10 | 49.356 | 49.416 | 49.493 | 49.570 | 49.628 | 49.664 | 49.682 | | |
| 11 | | | | | | | | | |
| 12 | | | | | | | | | |
| 13 | | | | | | | | | |
| 14 | | | | | | | | | |
| 15 | | | | | | | | | |
| Total lit. | 6 | 43 | 53 | 69 | 85 | 98 | 15 | | |
| Average lit./min | 0.6 | 4.3 | 5.3 | 6.9 | 8.5 | 7.8 | 1.5 | | |
| Friction loss | 11:55 | 11:50 | 11:55 | 11:50 | 12:05 | 12:20 | 12:30 | | |
| (P _f) | 0.00 | 0.00 | 0.01 | 0.01 | 0.01 | 0.00 | 0.00 | | |
| Calculation of Lugeon value | | | | | | | | | |
| $P = P_0 + 0.1(\sin \alpha)L_s + L_s P_f$ (kg/cm ²), $q = Q_w/L_s$ (lit/min/m) | | | | | | | | | |
| | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ | P ₈ | P ₉ |
| | 3.3 | 6.3 | 9.3 | 12.3 | 15.3 | 18.3 | 21.3 | 24.3 | 27.3 |
| | q ₁ | q ₂ | q ₃ | q ₄ | q ₅ | q ₆ | q ₇ | q ₈ | q ₉ |
| | 0.1 | 0.9 | 1.1 | 1.4 | 0.9 | 0.6 | 0.3 | | |

Water Pressure in kg/cm² vs. Lugeon value (lit/min/m)

Lugeon value: 1.1 Lu
Critical Pressure: >12 kg/cm²

Remarks: " " " "

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.

Prepared by: A. Hamid & Azhor Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-2 Stage: 6/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (α): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁻⁴ kg/cm²/m Date: 24/December/1998

| Ground elevation: EL | | Groundwater level (L _g): | | 27.80 m | | Gauge height (L _g): | | 0.86 m | |
|--|----------------|---|----------------|----------------|----------------|--------------------------------------|----------------|----------------|----------------|
| Pipe length from pressure gauge to borehole mouth: (L _g) = 6.80 m | | Depth of test section: 25 m to (L _g) = 30 m | | | | Length of section (L _s): | | 5 m | |
| Reading of flow meter | | | | | | | | | |
| Group P _i (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ | P ₈ | P ₉ |
| Start time | 16:10 | 16:22 | 16:34 | 16:45 | 16:56 | 17:08 | 17:20 | | |
| Q (m ³ /min) | 51.403 | 51.454 | 51.479 | 51.528 | 51.584 | 51.619 | 51.638 | | |
| 1 | 51.404 | 51.456 | 51.482 | 51.533 | 51.587 | 51.621 | 51.638 | | |
| 2 | 51.405 | 51.458 | 51.486 | 51.538 | 51.590 | 51.623 | 51.639 | | |
| 3 | 51.406 | 51.460 | 51.489 | 51.543 | 51.594 | 51.625 | 51.639 | | |
| 4 | 51.407 | 51.462 | 51.493 | 51.549 | 51.597 | 51.626 | 51.640 | | |
| 5 | 51.407 | 51.464 | 51.496 | 51.554 | 51.600 | 51.628 | 51.641 | | |
| 6 | 51.408 | 51.466 | 51.500 | 51.559 | 51.602 | 51.630 | 51.641 | | |
| 7 | 51.409 | 51.468 | 51.503 | 51.563 | 51.606 | 51.632 | 51.642 | | |
| 8 | 51.409 | 51.470 | 51.506 | 51.570 | 51.609 | 51.633 | 51.642 | | |
| 9 | 51.410 | 51.472 | 51.509 | 51.576 | 51.613 | 51.635 | 51.643 | | |
| 10 | 51.411 | 51.474 | 51.513 | 51.581 | 51.617 | 51.637 | 51.644 | | |
| 11 | | | | | | | | | |
| 12 | | | | | | | | | |
| 13 | | | | | | | | | |
| 14 | | | | | | | | | |
| 15 | | | | | | | | | |
| Total lit. | 8 | 20 | 34 | 51 | 63 | 78 | 6 | | |
| Average lit./min | 0.8 | 2.0 | 3.4 | 5.3 | 3.3 | 1.8 | 0.6 | | |
| Friction loss | 16:20 | 16:32 | 16:44 | 16:55 | 17:06 | 17:18 | 17:30 | | |
| (P _f) | 0.00 | 0.00 | 0.00 | 0.01 | 0.00 | 0.00 | 0.00 | | |
| Calculation of Lugeon value | | | | | | | | | |
| $P = P_0 + 0.1(\sin \alpha)L_s + L_s P_f$ (kg/cm ²), $q = Q_w/L_s$ (lit/min/m) | | | | | | | | | |
| | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ | P ₈ | P ₉ |
| | 3.9 | 6.9 | 9.9 | 12.9 | 15.9 | 18.9 | 21.9 | 24.9 | 27.9 |
| | q ₁ | q ₂ | q ₃ | q ₄ | q ₅ | q ₆ | q ₇ | q ₈ | q ₉ |
| | 0.2 | 0.4 | 0.7 | 1.1 | 0.7 | 0.4 | 0.1 | | |

Water Pressure in kg/cm² vs. Lugeon value (lit/min/m)

Lugeon value: 0.7 Lu
Critical Pressure: >13 kg/cm²

Remarks: " " " "


Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.

Prepared by: A. Hamid & Azhor Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-2 Stage: 7/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (pr): 1x10⁻³ kg/cm²/m Date: 25/December/1998

| Ground elevation: EL | | Groundwater level (L _g): GL = 27.80 m | | Gauge height (L _g): 0.86 m | | | |
|---|--------|--|--------|---|--------|--------|--------|
| Pipe length from pressure gauge to borehole mouth: (L _g) = 6.70 m | | Depth of test section: GL - (L _g) = 30 m to (L _g) = 35 m | | Length of section (L _g) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P-1 | P-2 | P-3 | P-4 | P-5 | P-6 | P-7 |
| Start time | 13:55 | 14:10 | 14:25 | 14:40 | 14:55 | 15:10 | 15:25 |
| Q (lit/min) | 54.004 | 54.051 | 54.262 | 54.747 | 55.343 | 55.693 | 55.861 |
| 1 | 54.005 | 54.068 | 54.302 | 54.807 | 55.378 | 55.709 | 55.866 |
| 2 | 54.006 | 54.088 | 54.343 | 54.865 | 55.412 | 55.727 | 55.871 |
| 3 | 54.007 | 54.108 | 54.383 | 54.923 | 55.447 | 55.745 | 55.877 |
| 4 | 54.008 | 54.128 | 54.421 | 54.980 | 55.481 | 55.762 | 55.882 |
| 5 | 54.009 | 54.148 | 54.460 | 55.039 | 55.516 | 55.780 | 55.888 |
| 6 | 54.010 | 54.166 | 54.496 | 55.095 | 55.549 | 55.797 | 55.895 |
| 7 | 54.012 | 54.182 | 54.533 | 55.149 | 55.581 | 55.815 | 55.901 |
| 8 | 54.013 | 54.196 | 54.569 | 55.204 | 55.613 | 55.833 | 55.908 |
| 9 | 54.014 | 54.212 | 54.605 | 55.260 | 55.645 | 55.850 | 55.915 |
| 10 | 54.015 | 54.226 | 54.641 | 55.314 | 55.677 | 55.868 | 55.921 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | Q-1 | Q-2 | Q-3 | Q-4 | Q-5 | Q-6 | Q-7 |
| Average lit./min | Q-1 | Q-2 | Q-3 | Q-4 | Q-5 | Q-6 | Q-7 |
| Friction Loss (Pr) = pr(L _g + L _g) [kg/cm ²] | 14:03 | 14:20 | 14:35 | 14:50 | 15:05 | 15:20 | 15:35 |
| (Pr) | 0.00 | 0.10 | 0.48 | 1.05 | 0.37 | 0.10 | 0.01 |




Water Injection Ratio (q : lit/min/m)
 Lu = 8.5 kg/cm²
 Critical Pressure: >12 kg/cm²

Remarks: Reverse flow for 50 seconds by decreasing from 4 to 1 kg/cm².
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the last previous one minute.
 Prepared by: A. Hamid & Azhor Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-2 Stage: 8/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (pr): 1x10⁻³ kg/cm²/m Date: 27/December/1998

| Ground elevation: EL | | Groundwater level (L _g): GL = 27.80 m | | Gauge height (L _g): 0.86 m | | | |
|---|---------|--|--------|---|--------|--------|--------|
| Pipe length from pressure gauge to borehole mouth: (L _g) = 6.73 m | | Depth of test section: GL - (L _g) = 35 m to (L _g) = 40 m | | Length of section (L _g) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P-1 | P-2 | P-3 | P-4 | P-5 | P-6 | P-7 |
| Start time | 10:18 | 10:12 | 10:25 | 10:38 | 10:50 | 11:02 | 11:15 |
| Q (lit/min) | 2.842.0 | 62.856 | 62.902 | 63.163 | 63.700 | 64.026 | 64.161 |
| 1 | 2.842.8 | 62.860 | 62.923 | 63.214 | 63.732 | 64.037 | 64.163 |
| 2 | 2.843.9 | 62.864 | 62.946 | 63.266 | 63.765 | 64.050 | 64.166 |
| 3 | 2.844.9 | 62.868 | 62.968 | 63.318 | 63.798 | 64.063 | 64.170 |
| 4 | 2.845.7 | 62.872 | 62.990 | 63.370 | 63.831 | 64.076 | 64.173 |
| 5 | 2.846.7 | 62.875 | 63.013 | 63.421 | 63.863 | 64.090 | 64.177 |
| 6 | 2.847.7 | 62.879 | 63.035 | 63.471 | 63.895 | 64.103 | 64.181 |
| 7 | 2.848.7 | 62.882 | 63.058 | 63.520 | 63.927 | 64.116 | 64.186 |
| 8 | 2.849.6 | 62.886 | 63.081 | 63.571 | 63.958 | 64.130 | 64.190 |
| 9 | 2.850.5 | 62.890 | 63.103 | 63.623 | 63.990 | 64.143 | 64.195 |
| 10 | 2.851.4 | 62.896 | 63.126 | 63.675 | 64.018 | 64.157 | 64.199 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | Q-1 | Q-2 | Q-3 | Q-4 | Q-5 | Q-6 | Q-7 |
| Average lit./min | Q-1 | Q-2 | Q-3 | Q-4 | Q-5 | Q-6 | Q-7 |
| Friction Loss (Pr) = pr(L _g + L _g) [kg/cm ²] | 10:10 | 10:22 | 10:35 | 10:48 | 11:00 | 11:12 | 11:25 |
| (Pr) | 0.00 | 0.01 | 0.19 | 0.98 | 0.38 | 0.07 | 0.01 |




Water Injection Ratio (q : lit/min/m)
 Lu = 8.4 kg/cm²
 Critical Pressure: 8.4 kg/cm²

Remarks:
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the last previous one minute.
 Prepared by: A. Hamid & Azhor Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-2 Stage: 9/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (P_f): 1x10⁻⁴ kg/cm²/m Date: 28/December/1998

| Ground elevation: EL. m | | Groundwater level (L _g): GL. m | | Gauge height (L _g): 0.86 m | | |
|--|-----------------|---|-----------------|---|-----------------|-----------------|
| Pipe length from pressure gauge to borehole mouth: (L _p) = 6.85 m | | Depth of test section: GL. - (L _g) = 45 m | | Length of section (L _s) = 5 m | | |
| Reading of flow meter | | | | | | |
| Gauge Pt. (kg/cm ²) | P _{o1} | P _{o2} | P _{o3} | P _{o4} | P _{o5} | P _{o6} |
| 1 | 11.22 | 11.35 | 11.47 | 12.00 | 12.15 | 12.27 |
| 2 | 9.700.7 | 9.702.8 | 9.703.5 | 9.704.4 | 9.712.0 | 9.722.6 |
| 3 | 9.700.7 | 9.702.8 | 9.703.5 | 9.706.6 | 9.718.0 | 9.724.9 |
| 4 | 9.700.7 | 9.702.8 | 9.703.5 | 9.707.7 | 9.718.7 | 9.724.9 |
| 5 | 9.700.7 | 9.702.8 | 9.703.5 | 9.708.8 | 9.719.2 | 9.724.9 |
| 6 | 9.700.7 | 9.702.8 | 9.703.5 | 9.709.9 | 9.719.8 | 9.724.9 |
| 7 | 9.700.7 | 9.702.8 | 9.703.5 | 9.711.1 | 9.720.4 | 9.724.9 |
| 8 | 9.700.7 | 9.702.8 | 9.703.5 | 9.712.2 | 9.721.0 | 9.724.9 |
| 9 | 9.700.7 | 9.702.8 | 9.703.5 | 9.713.3 | 9.721.6 | 9.724.9 |
| 10 | 9.700.7 | 9.702.8 | 9.703.5 | 9.714.4 | 9.722.2 | 9.724.9 |
| 11 | 9.700.7 | 9.702.8 | 9.703.5 | 9.715.5 | 9.722.8 | 9.724.9 |
| 12 | | | | | | |
| 13 | | | | | | |
| 14 | | | | | | |
| 15 | | | | | | |
| Total | 0.0 | 0.0 | 0.0 | 11.1 | 5.8 | 2.6 |
| Average | 0.00 | 0.00 | 0.00 | 1.11 | 0.58 | 0.26 |
| Remarks | 11.20 | 11.32 | 11.45 | 11.57 | 12.10 | 12.25 |
| (P _f) | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Friction Loss (P _f) = p(L _s + L _p) [kg/cm ²] | | | | | | |
| Remarks: Reverse flow for 7 seconds by decreasing from 7 to 4 kg/cm ² and for 1 minutes to 1 kg/cm ² . | | | | | | |




Water Injection Ratio (q): lit/min/m
 Lu_g value: (0.0)
 Critical Pressure: 9.9 kg/cm²

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.
 Prepared by: Azhor Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-2 Stage: 10/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (P_f): 1x10⁻⁴ kg/cm²/m Date: 29/December/1998

| Ground elevation: EL. m | | Groundwater level (L _g): GL. m | | Gauge height (L _g): 0.86 m | | |
|--|-----------------|---|-----------------|---|-----------------|-----------------|
| Pipe length from pressure gauge to borehole mouth: (L _p) = 6.60 m | | Depth of test section: GL. - (L _g) = 45 m | | Length of section (L _s) = 5 m | | |
| Reading of flow meter | | | | | | |
| Gauge Pt. (kg/cm ²) | P _{o1} | P _{o2} | P _{o3} | P _{o4} | P _{o5} | P _{o6} |
| 1 | 15.30 | 15.42 | 15.54 | 16.08 | 16.35 | 16.45 |
| 2 | 7.477.0 | 7.488.8 | 7.555 | 7.592 | 7.6293 | 7.6733 |
| 3 | 7.477.0 | 7.488.8 | 7.555 | 7.592 | 7.6293 | 7.6733 |
| 4 | 7.477.0 | 7.488.8 | 7.555 | 7.592 | 7.6293 | 7.6733 |
| 5 | 7.477.0 | 7.488.8 | 7.555 | 7.592 | 7.6293 | 7.6733 |
| 6 | 7.477.0 | 7.488.8 | 7.555 | 7.592 | 7.6293 | 7.6733 |
| 7 | 7.477.0 | 7.488.8 | 7.555 | 7.592 | 7.6293 | 7.6733 |
| 8 | 7.477.0 | 7.488.8 | 7.555 | 7.592 | 7.6293 | 7.6733 |
| 9 | 7.477.0 | 7.488.8 | 7.555 | 7.592 | 7.6293 | 7.6733 |
| 10 | 7.477.0 | 7.488.8 | 7.555 | 7.592 | 7.6293 | 7.6733 |
| 11 | | | | | | |
| 12 | | | | | | |
| 13 | | | | | | |
| 14 | | | | | | |
| 15 | | | | | | |
| Total | 8.4 | 63 | 272 | 376 | 221 | 103 |
| Average | 0.8 | 6.3 | 27.2 | 37.6 | 22.1 | 10.3 |
| Remarks | 15.40 | 15.52 | 16.04 | 16.18 | 16.30 | 16.45 |
| (P _f) | 0.00 | 0.02 | 0.33 | 0.66 | 0.23 | 0.03 |
| Friction Loss (P _f) = p(L _s + L _p) [kg/cm ²] | | | | | | |
| Remarks: Reverse flow for 7 seconds by decreasing from 7 to 4 kg/cm ² and for 1 minutes to 1 kg/cm ² . | | | | | | |



Water Injection Ratio (q): lit/min/m
 Lu_g value: (2.4)
 Critical Pressure: 6.8 kg/cm²


Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.
 Prepared by: A. Hamid & Azhor Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-2 Stage: 11/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (θ): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁻⁶ kg/cm²/m Date: 30/December/1998

Ground elevation: EL. m Groundwater level (L_g): GL - 27.80 m Gauge height (L_g): 0.86 m
 Pipe length from pressure gauge to borehole mouth: (L_p) = 7.70 m Depth of test section: 55 m Length of section (L_s): 5 m
 GL - (L_g) = 55 m to (L_s) = 5 m

| Reading of flow meter | | | | | | | | | | Calculation of Lugeon value | | | | | | | | | | |
|---|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|
| Gauge P. (kg/cm ²) | P _{o1} | P _{o2} | P _{o3} | P _{o4} | P _{o5} | P _{o6} | P _{o7} | P _{o8} | P _{o9} | P _{o10} | P _{o11} | P _{o12} | P _{o13} | P _{o14} | P _{o15} | P _{o16} | P _{o17} | P _{o18} | P _{o19} | P _{o20} |
| Start time | 12:58 | 13:10 | 13:25 | 13:40 | 13:55 | 14:10 | 14:25 | 14:40 | 14:55 | 15:10 | 15:25 | 15:40 | 15:55 | 16:10 | 16:25 | 16:40 | 16:55 | 17:10 | 17:25 | 17:40 |
| Q (min) | 2.224.4 | 2.226.5 | 2.231.5 | 2.235.6 | 2.240.9 | 2.244.2 | 2.246.5 | 2.248.8 | 2.251.1 | 2.253.4 | 2.255.7 | 2.258.0 | 2.260.3 | 2.262.6 | 2.264.9 | 2.267.2 | 2.269.5 | 2.271.8 | 2.274.1 | 2.276.4 |
| 1 | 2.224.4 | 2.226.5 | 2.231.5 | 2.235.6 | 2.240.9 | 2.244.2 | 2.246.5 | 2.248.8 | 2.251.1 | 2.253.4 | 2.255.7 | 2.258.0 | 2.260.3 | 2.262.6 | 2.264.9 | 2.267.2 | 2.269.5 | 2.271.8 | 2.274.1 | 2.276.4 |
| 2 | 2.224.5 | 2.226.6 | 2.231.6 | 2.235.7 | 2.241.0 | 2.244.3 | 2.246.6 | 2.248.9 | 2.251.2 | 2.253.5 | 2.255.8 | 2.258.1 | 2.260.4 | 2.262.7 | 2.265.0 | 2.267.3 | 2.269.6 | 2.271.9 | 2.274.2 | 2.276.5 |
| 3 | 2.224.5 | 2.227.1 | 2.233.4 | 2.236.9 | 2.241.9 | 2.244.8 | 2.246.5 | 2.248.8 | 2.251.1 | 2.253.4 | 2.255.7 | 2.258.0 | 2.260.3 | 2.262.6 | 2.264.9 | 2.267.2 | 2.269.5 | 2.271.8 | 2.274.1 | 2.276.4 |
| 4 | 2.224.6 | 2.227.3 | 2.233.7 | 2.237.3 | 2.242.5 | 2.245.2 | 2.246.6 | 2.248.9 | 2.251.2 | 2.253.5 | 2.255.8 | 2.258.1 | 2.260.4 | 2.262.7 | 2.265.0 | 2.267.3 | 2.269.6 | 2.271.9 | 2.274.2 | 2.276.5 |
| 5 | 2.224.6 | 2.227.5 | 2.234.0 | 2.237.8 | 2.243.2 | 2.245.7 | 2.246.6 | 2.248.9 | 2.251.2 | 2.253.5 | 2.255.8 | 2.258.1 | 2.260.4 | 2.262.7 | 2.265.0 | 2.267.3 | 2.269.6 | 2.271.9 | 2.274.2 | 2.276.5 |
| 6 | 2.224.6 | 2.227.7 | 2.234.3 | 2.238.2 | 2.243.8 | 2.245.4 | 2.246.6 | 2.248.9 | 2.251.2 | 2.253.5 | 2.255.8 | 2.258.1 | 2.260.4 | 2.262.7 | 2.265.0 | 2.267.3 | 2.269.6 | 2.271.9 | 2.274.2 | 2.276.5 |
| 7 | 2.224.7 | 2.227.9 | 2.234.6 | 2.238.7 | 2.243.1 | 2.245.6 | 2.246.6 | 2.248.9 | 2.251.2 | 2.253.5 | 2.255.8 | 2.258.1 | 2.260.4 | 2.262.7 | 2.265.0 | 2.267.3 | 2.269.6 | 2.271.9 | 2.274.2 | 2.276.5 |
| 8 | 2.224.7 | 2.228.1 | 2.234.9 | 2.239.1 | 2.243.3 | 2.245.8 | 2.246.6 | 2.248.9 | 2.251.2 | 2.253.5 | 2.255.8 | 2.258.1 | 2.260.4 | 2.262.7 | 2.265.0 | 2.267.3 | 2.269.6 | 2.271.9 | 2.274.2 | 2.276.5 |
| 9 | 2.224.7 | 2.228.3 | 2.235.2 | 2.239.7 | 2.243.6 | 2.246.0 | 2.246.6 | 2.248.9 | 2.251.2 | 2.253.5 | 2.255.8 | 2.258.1 | 2.260.4 | 2.262.7 | 2.265.0 | 2.267.3 | 2.269.6 | 2.271.9 | 2.274.2 | 2.276.5 |
| 10 | 2.224.8 | 2.228.6 | 2.235.5 | 2.240.2 | 2.243.8 | 2.246.2 | 2.246.6 | 2.248.9 | 2.251.2 | 2.253.5 | 2.255.8 | 2.258.1 | 2.260.4 | 2.262.7 | 2.265.0 | 2.267.3 | 2.269.6 | 2.271.9 | 2.274.2 | 2.276.5 |
| 11 | | | | | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | | | | | |
| 13 | | | | | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | | | | | |
| 15 | | | | | | | | | | | | | | | | | | | | |
| Total lit. | 0.5 | 2.1 | 4.0 | 4.6 | 4.6 | 2.9 | 2.0 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 | 0.1 |
| Average lit./min | 0.05 | 0.21 | 0.40 | 0.46 | 0.46 | 0.29 | 0.20 | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 |
| Friction loss (P _f) | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Friction Loss (P _f) = p(L _o + L _s) [kg/cm ²] | | | | | | | | | | | | | | | | | | | | |



Water Injection Ratio (q; lit./min/m)
 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0
 Lugeon value: 0.1 Lu
 Critical Pressure: >13 kg/cm²


Remarks:
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 50% to 110% of the injection rate in the last previous one minute.
 Prepared by: A. Hamid & Azhar Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-2 Stage: 12/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (θ): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁻⁶ kg/cm²/m Date: 21/December/1998

Ground elevation: EL. m Groundwater level (L_g): GL - 27.80 m Gauge height (L_g): 0.86 m
 Pipe length from pressure gauge to borehole mouth: (L_p) = 7.60 m Depth of test section: 55 m Length of section (L_s): 5 m
 GL - (L_g) = 55 m to (L_s) = 5 m

| Reading of flow meter | | | | | | | | | | Calculation of Lugeon value | | | | | | | | | | |
|---|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|------------------|
| Gauge P. (kg/cm ²) | P _{o1} | P _{o2} | P _{o3} | P _{o4} | P _{o5} | P _{o6} | P _{o7} | P _{o8} | P _{o9} | P _{o10} | P _{o11} | P _{o12} | P _{o13} | P _{o14} | P _{o15} | P _{o16} | P _{o17} | P _{o18} | P _{o19} | P _{o20} |
| Start time | 14:00 | 14:12 | 14:25 | 14:38 | 14:50 | 15:02 | 15:15 | 15:28 | 15:40 | 15:53 | 16:05 | 16:18 | 16:30 | 16:43 | 16:55 | 17:08 | 17:20 | 17:33 | 17:45 | 17:58 |
| Q (min) | 7.953.6 | 7.955.3 | 7.955.9 | 7.956.0 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 |
| 1 | 7.953.6 | 7.955.3 | 7.955.9 | 7.956.0 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 |
| 2 | 7.953.6 | 7.955.3 | 7.955.9 | 7.956.0 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 |
| 3 | 7.953.6 | 7.955.3 | 7.955.9 | 7.956.0 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 |
| 4 | 7.953.6 | 7.955.3 | 7.955.9 | 7.956.0 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 |
| 5 | 7.953.6 | 7.955.3 | 7.955.9 | 7.956.0 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 |
| 6 | 7.953.6 | 7.955.3 | 7.955.9 | 7.956.0 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 |
| 7 | 7.953.6 | 7.955.3 | 7.955.9 | 7.956.0 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 |
| 8 | 7.953.6 | 7.955.3 | 7.955.9 | 7.956.0 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 |
| 9 | 7.953.6 | 7.955.3 | 7.955.9 | 7.956.0 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 |
| 10 | 7.953.6 | 7.955.3 | 7.955.9 | 7.956.0 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 | 7.956.8 |
| 11 | | | | | | | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | | | | | | | |
| 13 | | | | | | | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | | | | | | | |
| 15 | | | | | | | | | | | | | | | | | | | | |
| Total lit. | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Average lit./min | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| Friction loss (P _f) | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Friction Loss (P _f) = p(L _o + L _s) [kg/cm ²] | | | | | | | | | | | | | | | | | | | | |




Water Injection Ratio (q; lit./min/m)
 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0
 Lugeon value: 0.0 Lu
 Critical Pressure: >13 kg/cm²

Remarks:
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the last previous one minute.
 Prepared by: A. Hamid & Azhar Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-2 Stage: 13/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (α): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1 x 10⁻⁶ x Q^{1.75} Date: 2/January/1999

| Ground elevation: EL | | m | | Groundwater level (L _g): GL = 27.80 m | | Gauge height (L _g): 0.86 m | |
|---|---------|---|---------|---|---------|---|---------|
| Pipe length from pressure gauge to borehole mouth: (L _p) = 6.60 m | | GL - (L _p) = 65 m to (L _g) = 60 m | | Depth of test section | | Length of section (L _s) = 5 m | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P1 | P2 | P3 | P4 | P5 | P6 | P7 |
| Start time (h:m:s) | 09:40 | 09:55 | 10:10 | 10:25 | 10:40 | 10:55 | 11:10 |
| Q (m ³ /min) | 3.930.8 | 3.933.7 | 3.937.7 | 3.938.5 | 3.939.5 | 3.939.5 | 3.939.5 |
| 1 | 3.930.9 | 3.933.8 | 3.937.8 | 3.938.5 | 3.939.5 | 3.939.5 | 3.939.5 |
| 2 | 3.931.0 | 3.934.0 | 3.937.9 | 3.938.5 | 3.939.5 | 3.939.5 | 3.939.5 |
| 3 | 3.931.0 | 3.934.1 | 3.938.0 | 3.938.5 | 3.939.5 | 3.939.5 | 3.939.5 |
| 4 | 3.931.0 | 3.934.1 | 3.938.1 | 3.938.6 | 3.939.5 | 3.939.5 | 3.939.5 |
| 5 | 3.931.0 | 3.934.1 | 3.938.2 | 3.938.9 | 3.939.5 | 3.939.5 | 3.939.5 |
| 6 | 3.931.0 | 3.934.2 | 3.938.2 | 3.939.2 | 3.939.5 | 3.939.5 | 3.939.5 |
| 7 | 3.931.0 | 3.934.2 | 3.938.3 | 3.939.4 | 3.939.5 | 3.939.5 | 3.939.5 |
| 8 | 3.931.0 | 3.934.3 | 3.938.3 | 3.939.5 | 3.939.5 | 3.939.5 | 3.939.5 |
| 9 | 3.931.0 | 3.934.3 | 3.938.4 | 3.939.6 | 3.939.5 | 3.939.5 | 3.939.5 |
| 10 | 3.931.0 | 3.934.3 | 3.938.5 | 3.939.7 | 3.939.5 | 3.939.5 | 3.939.5 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 0.2 | 0.6 | 0.8 | 1.2 | 0.0 | 0.0 | 0.0 |
| Average lit./min | 0.02 | 0.06 | 0.08 | 0.12 | 0.00 | 0.00 | 0.00 |
| Remarks | 09:50 | 10:05 | 10:13 | 10:30 | 10:42 | 10:55 | 11:10 |
| Friction Loss (P ₇) = p(L _p + L _g) [kg/cm ²] | | | | | | | |
| | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |



Calculation of Luqcon value
 $P = P_0 + 0.1(\sin \alpha) L_p + L_g - P_r$ [kg/cm²], $q = Q_w / L_s$ [lit./min/m]
 P1 = 3.9, q1 = 0.004
 P2 = 6.9, q2 = 0.012
 P3 = 9.9, q3 = 0.016
 P4 = 12.9, q4 = 0.024
 P5 = 9.9, q5 = 0.000
 P6 = 6.9, q6 = 0.000
 P7 = 3.9, q7 = 0.000

Luqcon value: 0.0 Lu
 Critical Pressure: >13 kg/cm²


Remarks: -

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute
 Prepared by: A. Hamid & Azhor
 Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-2 Stage: 14/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (α): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1 x 10⁻⁶ x Q^{1.75} Date: 3/January/1999

| Ground elevation: EL | | m | | Groundwater level (L _g): GL = 27.80 m | | Gauge height (L _g): 0.86 m | |
|---|---------|---|---------|---|---------|---|---------|
| Pipe length from pressure gauge to borehole mouth: (L _p) = 6.70 m | | GL - (L _p) = 65 m to (L _g) = 70 m | | Depth of test section | | Length of section (L _s) = 5 m | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P1 | P2 | P3 | P4 | P5 | P6 | P7 |
| Start time (h:m:s) | 09:55 | 09:58 | 10:10 | 10:23 | 10:35 | 10:50 | 11:05 |
| Q (m ³ /min) | 7.743.5 | 7.746.7 | 7.748.4 | 7.751.0 | 7.756.0 | 7.756.6 | 7.756.6 |
| 1 | 7.743.6 | 7.746.9 | 7.748.6 | 7.751.4 | 7.756.2 | 7.756.6 | 7.756.6 |
| 2 | 7.743.6 | 7.747.0 | 7.748.8 | 7.751.9 | 7.756.3 | 7.756.6 | 7.756.6 |
| 3 | 7.743.7 | 7.747.1 | 7.748.9 | 7.752.3 | 7.756.4 | 7.756.6 | 7.756.6 |
| 4 | 7.743.7 | 7.747.2 | 7.749.1 | 7.752.8 | 7.756.4 | 7.756.6 | 7.756.6 |
| 5 | 7.743.8 | 7.747.2 | 7.749.3 | 7.753.2 | 7.756.5 | 7.756.6 | 7.756.6 |
| 6 | 7.743.8 | 7.747.3 | 7.749.5 | 7.753.7 | 7.756.6 | 7.756.6 | 7.756.6 |
| 7 | 7.743.8 | 7.747.3 | 7.749.7 | 7.754.2 | 7.756.6 | 7.756.6 | 7.756.6 |
| 8 | 7.743.9 | 7.747.4 | 7.749.8 | 7.754.7 | 7.756.7 | 7.756.6 | 7.756.6 |
| 9 | 7.743.9 | 7.747.5 | 7.750.1 | 7.755.2 | 7.756.7 | 7.756.6 | 7.756.6 |
| 10 | 7.744.0 | 7.747.6 | 7.750.3 | 7.755.8 | 7.756.8 | 7.756.6 | 7.756.6 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 0.5 | 0.9 | 1.9 | 4.8 | 0.8 | 0.0 | 0.0 |
| Average lit./min | 0.05 | 0.09 | 0.19 | 0.48 | 0.08 | 0.00 | 0.00 |
| Remarks | 09:55 | 10:08 | 10:20 | 10:33 | 10:45 | 11:00 | 11:15 |
| Friction Loss (P ₇) = p(L _p + L _g) [kg/cm ²] | | | | | | | |
| | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |



Calculation of Luqcon value
 $P = P_0 + 0.1(\sin \alpha) L_p + L_g - P_r$ [kg/cm²], $q = Q_w / L_s$ [lit./min/m]
 P1 = 3.9, q1 = 0.01
 P2 = 6.9, q2 = 0.02
 P3 = 9.9, q3 = 0.04
 P4 = 12.9, q4 = 0.10
 P5 = 9.9, q5 = 0.02
 P6 = 6.9, q6 = 0.00
 P7 = 3.9, q7 = 0.00

Luqcon value: 0.0 Lu
 Critical Pressure: >13 kg/cm²


Remarks: -

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute
 Prepared by: A. Hamid & Azhor
 Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-2 Stage: 15/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁶ x Q² m Date: 5/January/1999

| Ground elevation: EL. m | | Groundwater level (L _g): GL- 27.80 m | | Gauge height (L _g): 0.86 m | | | |
|---|---------|---|---------|---|---------|------------------------|---------|
| Pipe length from pressure gauge to borehole mouth: (L _p) = 6.70 m | | Depth of test section GL - (L _g) = 75 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Q (mm) | P1 | P2 | P3 | P4 | P5 | P6 | P7 |
| 1 | 11:55 | 12:08 | 12:20 | 12:35 | 12:48 | 13:00 | 13:13 |
| 2 | 7:662.4 | 7:667.2 | 7:670.5 | 7:675.0 | 7:683.5 | 7:688.1 | 7:691.0 |
| 3 | 7:662.6 | 7:667.4 | 7:671.1 | 7:676.3 | 7:684.2 | 7:688.8 | 7:691.2 |
| 4 | 7:662.8 | 7:667.6 | 7:671.4 | 7:677.1 | 7:684.6 | 7:689.0 | 7:691.5 |
| 5 | 7:662.9 | 7:667.8 | 7:672.0 | 7:678.7 | 7:685.4 | 7:689.4 | 7:691.5 |
| 6 | 7:663.0 | 7:667.9 | 7:672.3 | 7:679.5 | 7:686.8 | 7:689.6 | 7:691.6 |
| 7 | 7:663.1 | 7:668.0 | 7:672.6 | 7:680.3 | 7:686.1 | 7:689.8 | 7:691.7 |
| 8 | 7:663.2 | 7:668.1 | 7:672.9 | 7:681.1 | 7:686.5 | 7:690.1 | 7:691.8 |
| 9 | 7:663.3 | 7:668.3 | 7:673.3 | 7:681.8 | 7:686.9 | 7:690.3 | 7:691.9 |
| 10 | 7:663.4 | 7:668.4 | 7:673.6 | 7:682.6 | 7:687.2 | 7:690.5 | 7:692.0 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total | Q-1 | Q-2 | Q-3 | Q-4 | Q-5 | Q-6 | Q-7 |
| lit. | 1.0 | 1.2 | 3.1 | 7.6 | 3.7 | 2.4 | 1.0 |
| Average | Q-1 | Q-2 | Q-3 | Q-4 | Q-5 | Q-6 | Q-7 |
| lit./min | 0.10 | 0.12 | 0.31 | 0.76 | 0.37 | 0.24 | 0.10 |
| Friction loss | 12:05 | 12:18 | 12:30 | 12:45 | 12:58 | 13:10 | 13:23 |
| (P) | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Friction Loss (P) = p(L _s + L _p) [kg/cm ²] | | | | | | Lu' kg/cm ² | |
| | | | | | | 0.0 | |




Water Injection Ratio (q : lit/min/m)
 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0
 Lu' kg/cm² (0.0)
 Critical Pressure: 8.7 kg/cm²

Remarks: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute
 Prepared by : A. Hamid & Azhar Inspected by : Farhat M. Shah

Water Pressure Test

Hole No.: M98-2 Stage: 16/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁶ x Q² m Date: 7/January/1999

| Ground elevation: EL. m | | Groundwater level (L _g): GL- 27.80 m | | Gauge height (L _g): 0.86 m | | | |
|---|---------|---|---------|---|---------|------------------------|---------|
| Pipe length from pressure gauge to borehole mouth: (L _p) = 6.75 m | | Depth of test section GL - (L _g) = 80 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Q (mm) | P1 | P2 | P3 | P4 | P5 | P6 | P7 |
| 1 | 10:30 | 10:42 | 10:55 | 11:10 | 11:23 | 11:35 | 11:48 |
| 2 | 8:135.9 | 8:138.0 | 8:139.9 | 8:142.2 | 8:147.0 | 8:149.6 | 8:149.7 |
| 3 | 8:136.0 | 8:138.2 | 8:140.1 | 8:142.6 | 8:147.2 | 8:149.7 | 8:149.7 |
| 4 | 8:136.1 | 8:138.3 | 8:140.3 | 8:143.0 | 8:147.5 | 8:149.8 | 8:149.7 |
| 5 | 8:136.2 | 8:138.4 | 8:140.5 | 8:143.4 | 8:147.7 | 8:149.9 | 8:149.8 |
| 6 | 8:136.3 | 8:138.6 | 8:140.7 | 8:143.8 | 8:148.0 | 8:150.0 | 8:149.8 |
| 7 | 8:136.5 | 8:138.7 | 8:140.9 | 8:144.3 | 8:148.3 | 8:150.1 | 8:149.8 |
| 8 | 8:136.6 | 8:138.8 | 8:141.0 | 8:144.7 | 8:148.5 | 8:150.2 | 8:149.9 |
| 9 | 8:136.7 | 8:139.0 | 8:141.2 | 8:145.3 | 8:148.8 | 8:150.3 | 8:149.9 |
| 10 | 8:136.8 | 8:139.2 | 8:141.5 | 8:145.7 | 8:149.1 | 8:150.4 | 8:149.9 |
| 11 | 8:136.9 | 8:139.3 | 8:141.7 | 8:146.2 | 8:149.4 | 8:150.5 | 8:149.9 |
| 12 | 8:137.0 | 8:139.4 | 8:141.9 | 8:146.7 | 8:149.6 | 8:150.6 | 8:150.0 |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total | Q-1 | Q-2 | Q-3 | Q-4 | Q-5 | Q-6 | Q-7 |
| lit. | 1.1 | 1.4 | 2.0 | 4.5 | 2.6 | 1.0 | 0.3 |
| Average | Q-1 | Q-2 | Q-3 | Q-4 | Q-5 | Q-6 | Q-7 |
| lit./min | 0.11 | 0.14 | 0.20 | 0.45 | 0.26 | 0.10 | 0.03 |
| Friction loss | 10:40 | 10:52 | 11:05 | 11:20 | 11:33 | 11:45 | 11:58 |
| (P) | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Friction Loss (P) = p(L _s + L _p) [kg/cm ²] | | | | | | Lu' kg/cm ² | |
| | | | | | | 0.0 | |




Water Injection Ratio (q : lit/min/m)
 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0
 Lu' kg/cm² (0.0)
 Critical Pressure: 9.5 kg/cm²

Remarks: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute
 Prepared by : A. Hamid & Azhar Inspected by : Farhat M. Shah

Water Pressure Test

Hole No.: M98-2 Stage: 17/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁴ x Q² m Date: 14/January/1999

| Ground elevation: EL. m | | Groundwater level (L _g): GL = 27.80 m | | Gauge height (L _g): 0.86 m | | | |
|---|----------------|--|----------------|--|----------------|----------------|----------------|
| Pipe length from pressure gauge to borehole mouth: (L _p) = 3.90 m | | Depth of test section: GL - (L _p) = 85 m to (L _g) = 80 m | | Length of section (L _s): 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 10:20 | 10:42 | 10:55 | 11:10 | 11:23 | 11:35 | 11:48 |
| Q (min) | 1,160.1 | 1,163.6 | 1,167.5 | 1,175.3 | 1,188.0 | 1,195.8 | 1,199.3 |
| 1 | 1,160.2 | 1,164.2 | 1,168.1 | 1,176.5 | 1,188.7 | 1,196.2 | 1,199.5 |
| 2 | 1,160.3 | 1,164.6 | 1,169.1 | 1,177.8 | 1,189.3 | 1,196.6 | 1,199.8 |
| 3 | 1,160.3 | 1,164.9 | 1,169.7 | 1,179.0 | 1,190.1 | 1,197.0 | 1,200.0 |
| 4 | 1,160.3 | 1,165.2 | 1,170.3 | 1,181.5 | 1,191.6 | 1,197.8 | 1,200.3 |
| 5 | 1,160.8 | 1,165.5 | 1,170.8 | 1,182.7 | 1,192.3 | 1,198.1 | 1,200.8 |
| 6 | 1,161.1 | 1,165.7 | 1,171.3 | 1,184.0 | 1,193.1 | 1,198.5 | 1,201.0 |
| 7 | 1,161.5 | 1,166.0 | 1,171.9 | 1,185.2 | 1,193.9 | 1,198.9 | 1,201.2 |
| 8 | 1,161.9 | 1,166.3 | 1,172.5 | 1,186.5 | 1,194.6 | 1,199.3 | 1,201.5 |
| 9 | 1,162.2 | 1,166.5 | 1,173.1 | 1,187.8 | 1,195.5 | 1,199.7 | 1,201.8 |
| 10 | | | | | | | |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 2.1 | 2.9 | 5.6 | 12.5 | 7.5 | 3.9 | 2.5 |
| Average lit./min | 0.21 | 0.29 | 0.56 | 1.25 | 0.75 | 0.39 | 0.25 |
| Friction Loss (P _f) = p(L _p + L _s) [kg/cm ²] | 10:40 | 10:52 | 11:05 | 11:20 | 11:33 | 11:45 | 11:58 |
| (P _f) | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |




Calculation of Lugeon value
 $P = P_0 + 0.1(\sin(a)(L_p + L_s) + Pr)$ [kg/cm²], $q = Q_0/L_s$ [lit/min/m]
 P₁ = 3.9, q₁ = 0.04
 P₂ = 6.9, q₂ = 0.06
 P₃ = 9.9, q₃ = 0.11
 P₄ = 12.9, q₄ = 0.25
 P₅ = 9.9, q₅ = 0.15
 P₆ = 6.9, q₆ = 0.08
 P₇ = 3.9, q₇ = 0.05
 Lugeon value: (0.1) Lu' = 8.9 kgf/cm²
 Critical Pressure: >10

Remarks: -
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the last previous one minute.
 Prepared by: A. Hamid & Azhor Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-2 Stage: 18/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁴ x Q² m Date: 27/January/1999

| Ground elevation: EL. m | | Groundwater level (L _g): GL = 32.40 m | | Gauge height (L _g): 0.86 m | | | |
|---|----------------|--|----------------|--|----------------|----------------|----------------|
| Pipe length from pressure gauge to borehole mouth: (L _p) = 4.10 m | | Depth of test section: GL - (L _p) = 85 m to (L _g) = 90 m | | Length of section (L _s): 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 14:45 | 14:58 | 15:10 | 15:23 | 15:35 | 15:48 | 16:00 |
| Q (min) | 8,316.0 | 8,324.0 | 8,332.0 | 8,339.0 | 8,348.0 | 8,352.0 | 8,356.0 |
| 1 | 8,316.3 | 8,324.3 | 8,333.1 | 8,339.9 | 8,348.5 | 8,352.3 | 8,356.2 |
| 2 | 8,316.8 | 8,325.0 | 8,333.5 | 8,340.6 | 8,348.9 | 8,352.7 | 8,356.5 |
| 3 | 8,317.5 | 8,325.5 | 8,334.0 | 8,341.5 | 8,349.5 | 8,353.0 | 8,356.7 |
| 4 | 8,317.9 | 8,326.1 | 8,334.6 | 8,342.3 | 8,349.9 | 8,353.5 | 8,357.1 |
| 5 | 8,318.3 | 8,326.5 | 8,335.0 | 8,343.0 | 8,350.4 | 8,353.8 | 8,357.4 |
| 6 | 8,318.7 | 8,327.0 | 8,335.7 | 8,343.9 | 8,350.8 | 8,354.1 | 8,357.8 |
| 7 | 8,319.0 | 8,327.6 | 8,336.1 | 8,344.9 | 8,351.3 | 8,354.5 | 8,358.1 |
| 8 | 8,319.4 | 8,328.0 | 8,336.6 | 8,345.8 | 8,351.8 | 8,354.8 | 8,358.4 |
| 9 | 8,319.8 | 8,328.4 | 8,337.2 | 8,346.6 | 8,352.4 | 8,355.3 | 8,358.8 |
| 10 | 8,320.1 | 8,328.9 | 8,337.6 | 8,347.3 | 8,352.8 | 8,355.6 | 8,359.1 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 4.1 | 4.9 | 5.6 | 8.3 | 4.8 | 3.6 | 3.1 |
| Average lit./min | 0.41 | 0.49 | 0.56 | 0.83 | 0.48 | 0.36 | 0.31 |
| Friction Loss (P _f) = p(L _p + L _s) [kg/cm ²] | 14:55 | 15:08 | 15:20 | 15:32 | 15:45 | 15:58 | 16:10 |
| (P _f) | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |




Calculation of Lugeon value
 $P = P_0 + 0.1(\sin(a)(L_p + L_s) + Pr)$ [kg/cm²], $q = Q_0/L_s$ [lit/min/m]
 P₁ = 4.3, q₁ = 0.08
 P₂ = 7.3, q₂ = 0.10
 P₃ = 10.3, q₃ = 0.11
 P₄ = 13.3, q₄ = 0.17
 P₅ = 10.3, q₅ = 0.10
 P₆ = 7.3, q₆ = 0.07
 P₇ = 4.3, q₇ = 0.06
 Lugeon value: 0.1 Lu = 2.1 kgf/cm²
 Critical Pressure: >10

Remarks: -
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the last previous one minute.
 Prepared by: A. Hamid & Azhor Inspected by: M. Suza

Water Pressure Test

Hole No.: M98-3 Stage: 1/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 mm/m
 Hole Inclination (α): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁻⁴ kg/cm²/m Date: 28/November/1998

| Ground elevation: EL. m | | Groundwater level (L _g): NIL | | Gauge height (L _g): 0.96 m | | | |
|---|-----------------|---|-----------------|--|-----------------|-----------------|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _g)= 3.97 m | | Depth of test section to (L _g)= 2 m | | Length of section (L _g)= 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P _{g1} | P _{g2} | P _{g3} | P _{g4} | P _{g5} | P _{g6} | P _{g7} |
| 1 | 10.57 | 11.10 | | | | | |
| 2 | 58.483 | 58.710 | | | | | |
| 3 | 58.494 | 58.805 | | | | | |
| 4 | 58.504 | 58.915 | | | | | |
| 5 | 58.516 | | | | | | |
| 6 | 58.527 | | | | | | |
| 7 | 58.537 | | | | | | |
| 8 | 58.556 | | | | | | |
| 9 | 58.566 | | | | | | |
| 10 | 58.576 | | | | | | |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 106 | 315 | | | | | |
| Average lit./min | 10.6 | 105.0 | | | | | |
| Friction loss (p _f) | 11.07 | 11.14 | | | | | |
| (p _f) | 0.01 | 0.58 | | | | | |
| Friction Loss (P _f) = p _f (L _g + L _g) [kg/cm ²] | | | | | | | |
| Lugeon value: (6x) | | Lu' | | kg/cm ² | | | |
| Critical Pressure: >=4.0 | | | | | | | |



Remarks: Water table at 2 kg/cm² was more than 100 lit./min. And due to surficial leach 3.0m distance from borehole, pressure test was stopped. At 4kg/cm², pressure could not build.


Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 1.10% of the injection rate in the just previous one minute.

Prepared by: A. Hamid Inspected by: Raja Bashir

Water Pressure Test

Hole No.: M98-3 Stage: 2/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 mm/m
 Hole Inclination (α): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁻⁴ kg/cm²/m Date: 30/November/1998

| Ground elevation: EL. m | | Groundwater level (L _g): NIL | | Gauge height (L _g): 1.00 m | | | |
|---|-----------------|---|-----------------|---|-----------------|-----------------|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _g)= 3.80 m | | Depth of test section to (L _g)= 5 m | | Length of section (L _g)= 10 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P _{g1} | P _{g2} | P _{g3} | P _{g4} | P _{g5} | P _{g6} | P _{g7} |
| 1 | 11.53 | 12.07 | 12.53 | 12.98 | 13.44 | 13.90 | 14.36 |
| 2 | 65.406 | 65.558 | 66.189 | 66.990 | 68.085 | 68.833 | 69.225 |
| 3 | 65.416 | 65.589 | 66.236 | 67.038 | 68.134 | 68.873 | 69.241 |
| 4 | 65.425 | 65.619 | 66.310 | 67.130 | 68.222 | 68.912 | 69.256 |
| 5 | 65.434 | 65.649 | 66.370 | 67.239 | 68.290 | 68.950 | 69.272 |
| 6 | 65.443 | 65.677 | 66.430 | 67.310 | 68.360 | 68.988 | 69.287 |
| 7 | 65.452 | 65.704 | 66.487 | 67.405 | 68.428 | 69.027 | 69.303 |
| 8 | 65.460 | 65.736 | 66.545 | 67.500 | 68.496 | 69.065 | 69.318 |
| 9 | 65.469 | 65.765 | 66.600 | 67.588 | 68.563 | 69.099 | 69.334 |
| 10 | 65.477 | 65.795 | 66.663 | 67.684 | 68.628 | 69.141 | 69.349 |
| 11 | 65.486 | 65.823 | 66.722 | 67.780 | 68.680 | 69.177 | 69.365 |
| 12 | 65.494 | 65.852 | 66.779 | 67.874 | 68.733 | 69.212 | 69.379 |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 88 | 294 | 590 | 924 | 668 | 379 | 154 |
| Average lit./min | 8.8 | 29.4 | 59 | 92.4 | 66.8 | 37.9 | 15.4 |
| Friction loss (p _f) | 12.05 | 12.17 | 12.33 | 12.45 | 12.58 | 13.10 | 13.22 |
| (p _f) | 0.01 | 0.107 | 0.27 | 0.46 | 0.35 | 0.11 | 0.02 |
| Friction Loss (P _f) = p _f (L _g + L _g) [kg/cm ²] | | | | | | | |
| Lugeon value: (13) | | Lu' | | kg/cm ² | | | |
| Critical Pressure: 5.8 | | | | | | | |



Remarks: Water table is Nil.

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 1.10% of the injection rate in the just previous one minute.

Prepared by: A. Hamid Inspected by: Raja Bashir & Azumi Gill

Water Pressure Test

Hole No.: M98-3 Stages: 3/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁻⁴ kg/cm²/m Date: 2/December/1998

| Ground elevation: EL. _____ m | | Groundwater level (L _g): Nil | | Gauge height (L _g): 1.00 m | | | |
|---|--------------------|---|--------|---|--------|---|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _g) = 3.80 m | | Depth of test section to (L _g) = 10 m | | Length of section (L _g) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P1 | P2 | P3 | P4 | P5 | P6 | P7 |
| Start time | 14:00 | 14:12 | 14:23 | 14:35 | 14:46 | 14:57 | 15:08 |
| Q (m ³ /min) | 50.896 | 51.013 | 51.227 | 51.678 | 52.334 | 52.786 | 53.044 |
| 1 | 50.895 | 51.031 | 51.261 | 51.738 | 52.378 | 52.811 | 53.053 |
| 2 | 50.905 | 51.059 | 51.295 | 51.799 | 52.420 | 52.837 | 53.081 |
| 3 | 50.914 | 51.068 | 51.330 | 51.860 | 52.463 | 52.862 | 53.069 |
| 4 | 50.923 | 51.086 | 51.364 | 51.921 | 52.505 | 52.888 | 53.078 |
| 5 | 50.932 | 51.104 | 51.397 | 51.982 | 52.548 | 52.913 | 53.087 |
| 6 | 50.941 | 51.123 | 51.429 | 52.043 | 52.591 | 52.940 | 53.097 |
| 7 | 50.950 | 51.141 | 51.463 | 52.105 | 52.634 | 52.965 | 53.106 |
| 8 | 50.958 | 51.160 | 51.496 | 52.165 | 52.675 | 52.990 | 53.115 |
| 9 | 50.967 | 51.177 | 51.529 | 52.227 | 52.716 | 53.014 | 53.123 |
| 10 | 50.975 | 51.195 | 51.561 | 52.289 | 52.760 | 53.039 | 53.132 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total | Q=1 | Q=2 | Q=3 | Q=4 | Q=5 | Q=6 | Q=7 |
| lit. | 89 | 182 | 334 | 611 | 426 | 253 | 88 |
| Average | Q=1 | Q=2 | Q=3 | Q=4 | Q=5 | Q=6 | Q=7 |
| lit./min | 8.9 | 18.2 | 33.4 | 61.1 | 42.6 | 25.3 | 8.8 |
| Friction loss | 14:10 | 14:22 | 14:33 | 14:45 | 14:56 | 15:07 | 15:18 |
| (P _f) | 0.01 | 0.04 | 0.14 | 0.46 | 0.23 | 0.08 | 0.01 |
| Friction Loss (P _f) = p(L _g + L) | kg/cm ² | | | | | | 1 st |
| Friction Loss (P _f) = p(L _g + L) | kg/cm ² | | | | | | 2 nd |
| Calculation of Lugeon value | | | | | | Lugeon value: (6.6) | |
| Lugeon value: (6.6) | | | | | | Critical Pressure: 7.4 | |
| Water Pressure in kg/cm ² | | | | | | Water Injection Ratio (q : lit./min/m) | |
| | | | | | | Pa = P _{atm} + 0.1 (sin(a) L _g + L) P _f [kg/cm ²], q = Q _g / L _g [lit./min/m] P1 = 2.3 q1 = 1.8 P2 = 5.3 q2 = 3.6 P3 = 8.2 q3 = 6.7 P4 = 10.9 q4 = 12.2 P5 = 8.1 q5 = 8.5 P6 = 5.3 q6 = 5.1 P7 = 2.3 q7 = 1.8 | |

Remarks: _____
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 4% to 110% of the injection rate in the last previous one minute.
 Prepared by: A. Hamid Inspected by: A. Gil

Water Pressure Test

Hole No.: M98-3 Stages: 4/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁻⁴ kg/cm²/m Date: 3/December/1998


| Ground elevation: EL. _____ m | | Groundwater level (L _g): Nil | | Gauge height (L _g): 1.00 m | | | |
|---|--------------------|---|--------|---|--------|--|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _g) = 3.80 m | | Depth of test section to (L _g) = 15 m | | Length of section (L _g) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P1 | P2 | P3 | P4 | P5 | P6 | P7 |
| Start time | 16:17 | 16:28 | 16:39 | 16:50 | 17:02 | 17:13 | 17:24 |
| Q (m ³ /min) | 59.521 | 59.566 | 59.701 | 59.908 | 60.280 | 60.543 | 60.714 |
| 1 | 59.525 | 59.580 | 59.719 | 59.937 | 60.306 | 60.561 | 60.719 |
| 2 | 59.529 | 59.592 | 59.736 | 59.967 | 60.331 | 60.578 | 60.736 |
| 3 | 59.531 | 59.601 | 59.754 | 59.997 | 60.356 | 60.594 | 60.732 |
| 4 | 59.533 | 59.614 | 59.771 | 60.028 | 60.380 | 60.610 | 60.739 |
| 5 | 59.535 | 59.626 | 59.788 | 60.062 | 60.405 | 60.626 | 60.745 |
| 6 | 59.537 | 59.637 | 59.806 | 60.100 | 60.430 | 60.645 | 60.750 |
| 7 | 59.538 | 59.649 | 59.823 | 60.129 | 60.456 | 60.661 | 60.754 |
| 8 | 59.539 | 59.660 | 59.840 | 60.164 | 60.481 | 60.679 | 60.759 |
| 9 | 59.540 | 59.671 | 59.860 | 60.197 | 60.506 | 60.695 | 60.764 |
| 10 | 59.541 | 59.683 | 59.884 | 60.228 | 60.531 | 60.712 | 60.768 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total | Q=1 | Q=2 | Q=3 | Q=4 | Q=5 | Q=6 | Q=7 |
| lit. | 20 | 117 | 183 | 320 | 251 | 167 | 54 |
| Average | Q=1 | Q=2 | Q=3 | Q=4 | Q=5 | Q=6 | Q=7 |
| lit./min | 2.0 | 11.7 | 18.3 | 32.0 | 25.1 | 16.7 | 5.4 |
| Friction loss | 16:27 | 16:38 | 16:49 | 17:00 | 17:12 | 17:23 | 17:34 |
| (P _f) | 0.00 | 0.02 | 0.06 | 0.17 | 0.11 | 0.05 | 0.01 |
| Friction Loss (P _f) = p(L _g + L) | kg/cm ² | | | | | | 1 st |
| Friction Loss (P _f) = p(L _g + L) | kg/cm ² | | | | | | 2 nd |
| Calculation of Lugeon value | | | | | | Lugeon value: (4.3) | |
| Lugeon value: (4.3) | | | | | | Critical Pressure: 8.8 | |
| Water Pressure in kg/cm ² | | | | | | Water Injection Ratio (q : lit./min/m) | |
| | | | | | | Pa = P _{atm} + 0.1 (sin(a) L _g + L) P _f [kg/cm ²], q = Q _g / L _g [lit./min/m] P1 = 2.8 q1 = 0.4 P2 = 5.8 q2 = 2.3 P3 = 8.8 q3 = 3.7 P4 = 11.7 q4 = 6.4 P5 = 8.7 q5 = 5.0 P6 = 5.8 q6 = 3.3 P7 = 2.8 q7 = 1.1 | |

Remarks: _____
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 4% to 110% of the injection rate in the last previous one minute.
 Prepared by: A. Hamid & A. Gil Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-3 Stage: 5/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁶ x Q^{1.75} Date: 5/December/1998

| Ground elevation: EL. m | | Groundwater level (L _g): | | Nill | | Gauge height (L _g): | |
|---|----------------|--|----------------|----------------------------|----------------|--|----------------|
| Pipe length from pressure gauge to hole mouth: (L _p)= 3.80 m | | Depth of test section GL - (L _g)= 20 m | | to (L _g)= 25 m | | Length of section (L _s)= 5 m | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 11:22 | 11:34 | 11:45 | 11:56 | 12:08 | 12:19 | 12:30 |
| Q (lit/min) | 65.411 | 65.456 | 65.630 | 65.930 | 66.516 | 66.911 | 67.162 |
| 1 | 65.414 | 65.469 | 65.656 | 65.977 | 66.554 | 66.931 | 67.164 |
| 2 | 65.417 | 65.484 | 65.680 | 65.028 | 66.590 | 66.956 | 67.166 |
| 3 | 65.418 | 65.500 | 65.706 | 66.080 | 66.628 | 66.981 | 67.176 |
| 4 | 65.419 | 65.515 | 65.731 | 66.132 | 66.665 | 67.007 | 67.190 |
| 5 | 65.421 | 65.531 | 65.757 | 66.184 | 66.703 | 67.031 | 67.206 |
| 6 | 65.423 | 65.546 | 65.783 | 66.237 | 66.741 | 67.069 | 67.220 |
| 7 | 65.424 | 65.561 | 65.809 | 66.288 | 66.778 | 67.097 | 67.234 |
| 8 | 65.426 | 65.576 | 65.835 | 66.340 | 66.816 | 67.113 | 67.240 |
| 9 | 65.428 | 65.591 | 65.860 | 66.392 | 66.853 | 67.140 | 67.263 |
| 10 | 65.430 | 65.606 | 65.887 | 66.443 | 66.891 | 67.166 | 67.279 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 19 | 150 | 257 | 513 | 375 | 255 | 117 |
| Average lit./min | 1.9 | 15 | 25.7 | 51.3 | 37.5 | 25.5 | 11.7 |
| Friction Loss (P ₇) = p(L _p + L _s) [kg/cm ²] | 11.32 | 11.44 | 11.53 | 12.43 | 12.18 | 12.29 | 12.40 |
| (P ₅) | 0.60 | 0.95 | 0.14 | 0.36 | 0.30 | 0.18 | 0.05 |




Water Injection Ratio (q) : lit/min/m
 Lu' value : (5.8)
 Critical Pressure: 9.2 kg/cm²

Remarks: For 3 minutes reverse running at final 1 kg/cm² pressure.
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the just previous one minute.
 Prepared by: A. Hamid & A. Gill Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-3 Stage: 6/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁶ x Q^{1.75} Date: 7/December/1998

| Ground elevation: EL. m | | Groundwater level (L _g): | | Nill | | Gauge height (L _g): | |
|---|----------------|--|----------------|----------------------------|----------------|--|----------------|
| Pipe length from pressure gauge to hole mouth: (L _p)= 3.80 m | | Depth of test section GL - (L _g)= 25 m | | to (L _g)= 30 m | | Length of section (L _s)= 5 m | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 15:44 | 15:59 | 16:10 | 16:22 | 16:32 | 16:45 | 16:53 |
| Q (lit/min) | 80.088 | 80.279 | 80.531 | 81.008 | 81.776 | 82.271 | 82.508 |
| 1 | 80.107 | 80.302 | 80.570 | 81.071 | 81.818 | 82.293 | 82.516 |
| 2 | 80.125 | 80.324 | 80.611 | 81.141 | 81.862 | 82.318 | 82.527 |
| 3 | 80.141 | 80.346 | 80.650 | 81.215 | 81.907 | 82.345 | 82.539 |
| 4 | 80.159 | 80.368 | 80.689 | 81.288 | 81.956 | 82.373 | 82.552 |
| 5 | 80.176 | 80.389 | 80.728 | 81.361 | 82.004 | 82.399 | 82.566 |
| 6 | 80.192 | 80.410 | 80.767 | 81.435 | 82.053 | 82.427 | 82.581 |
| 7 | 80.208 | 80.431 | 80.807 | 81.510 | 82.101 | 82.454 | 82.596 |
| 8 | 80.223 | 80.452 | 80.845 | 81.579 | 82.150 | 82.482 | 82.611 |
| 9 | 80.238 | 80.473 | 80.885 | 81.654 | 82.199 | 82.510 | 82.626 |
| 10 | 80.252 | 80.493 | 80.924 | 81.727 | 82.246 | 82.538 | 82.643 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 164 | 214 | 303 | 721 | 470 | 267 | 135 |
| Average lit./min | 16.4 | 21.4 | 30.3 | 72.1 | 47.0 | 26.7 | 13.5 |
| Friction Loss (P ₇) = p(L _p + L _s) [kg/cm ²] | 15.534 | 16.09 | 16.20 | 16.32 | 16.42 | 16.55 | 17.04 |
| (P ₅) | 0.07 | 0.12 | 0.40 | 1.37 | 0.80 | 0.20 | 0.08 |




Water Injection Ratio (q) : lit/min/m
 Lu' value : (5.4)
 Critical Pressure: 8.6 kg/cm²

Remarks: For 3 minutes reverse running at final 1 kg/cm² pressure.
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the just previous one minute.
 Prepared by: A. Hamid Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-3 Stage: 7/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁴ kg/cm²/m Date: 11/December/1998


| Ground elevation: EL. m | | Groundwater level (L _g): Nil | | Gauge height (L _g): 1.00 m | | | |
|--|-----------------|---|-----------------|---|-----------------|--|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _p) = 3.80 m | | Depth of test section to (L _s) = 30 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P _{o1} | P _{o2} | P _{o3} | P _{o4} | P _{o5} | P _{o6} | P _{o7} |
| Start time | 11:00 | 11:14 | 11:25 | 11:36 | 11:48 | 12:00 | 12:22 |
| Q (m ³ /min) | 92.745 | 92.751 | 92.795 | 93.088 | 93.932 | 94.386 | 94.556 |
| 1 | 92.745 | 92.753 | 92.818 | 93.168 | 93.987 | 94.400 | 94.561 |
| 2 | 92.745 | 92.754 | 92.841 | 93.226 | 94.025 | 94.417 | 94.567 |
| 3 | 92.745 | 92.756 | 92.862 | 93.298 | 94.074 | 94.431 | 94.572 |
| 4 | 92.745 | 92.760 | 92.885 | 93.379 | 94.123 | 94.448 | 94.574 |
| 5 | 92.745 | 92.761 | 92.907 | 93.445 | 94.171 | 94.466 | 94.584 |
| 6 | 92.745 | 92.763 | 92.930 | 93.523 | 94.220 | 94.483 | 94.590 |
| 7 | 92.745 | 92.765 | 92.952 | 93.602 | 94.267 | 94.501 | 94.596 |
| 8 | 92.745 | 92.767 | 92.980 | 93.680 | 94.315 | 94.519 | 94.602 |
| 9 | 92.745 | 92.770 | 93.018 | 93.769 | 94.360 | 94.536 | 94.609 |
| 10 | 92.745 | 92.771 | 93.055 | 93.857 | 94.400 | 94.553 | 94.616 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 0.2 | 20.8 | 240 | 749 | 468 | 169 | 60 |
| Average lit./min | 0.02 | 2.08 | 24.0 | 74.9 | 46.8 | 17.8 | 6.4 |
| Friction loss (P _f) | 0.02 | 0.00 | 0.18 | 1.68 | 0.64 | 0.10 | 0.01 |
| Friction Loss (P _f) = p(L _p + L _s) [kg/cm ²] | | | | | | Lugeon value: (0.8) Lu' kg/cm ² | |
| Remarks: At reversal pressure 1 kg/cm ² , the flow meter started reverse for 4 minutes. | | | | | | Critical Pressure: 9.6 kg/cm ² | |



Water Pressure Test

Hole No.: M98-3 Stage: 8/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁴ kg/cm²/m Date: 12/December/1998

| Ground elevation: EL. m | | Groundwater level (L _g): Nil | | Gauge height (L _g): 1.90 m | | | |
|---|-----------------|---|-----------------|---|-----------------|--|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _p) = 3.98 m | | Depth of test section to (L _s) = 35 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P _{o1} | P _{o2} | P _{o3} | P _{o4} | P _{o5} | P _{o6} | P _{o7} |
| Start time | 12:00 | 12:20 | 12:36 | 13:00 | 13:15 | 13:40 | 14:00 |
| Q (m ³ /min) | 91.292 | 91.376 | 91.952 | 9.270 | 10.210 | 10.581 | 664.7 |
| 1 | 91.292 | 91.390 | 91.977 | 9.326 | 10.255 | 10.588 | 664.7 |
| 2 | 91.293 | 91.400 | 91.402 | 9.404 | 10.300 | 10.596 | 664.7 |
| 3 | 91.294 | 91.410 | 91.412 | 9.498 | 10.343 | 10.605 | 664.7 |
| 4 | 91.295 | 91.425 | 91.428 | 9.572 | 10.386 | 10.614 | 664.7 |
| 5 | 91.296 | 91.440 | 91.449 | 9.657 | 10.428 | 10.623 | 664.7 |
| 6 | 91.297 | 91.453 | 91.474 | 9.740 | 10.466 | 10.632 | 664.7 |
| 7 | 91.298 | 91.465 | 91.500 | 9.824 | 10.504 | 10.641 | 664.7 |
| 8 | 91.299 | 91.465 | 91.530 | 9.906 | 10.542 | 10.651 | 664.7 |
| 9 | 91.301 | 91.470 | 91.564 | 10.087 | 10.580 | 10.660 | 664.7 |
| 10 | 91.302 | 91.476 | 91.585 | 10.178 | 10.615 | 10.668 | 664.8 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 1.0 | 10.0 | 19.3 | 908 | 405 | 87.0 | 0.1 |
| Average lit./min | 0.1 | 1.0 | 2.7 | 90.8 | 37.4 | 9 | 0.02 |
| Friction loss (P _f) | 12:10 | 12:30 | 12:46 | 13:10 | 13:25 | 13:50 | 14:10 |
| (P _f) | 0.00 | 0.00 | 0.00 | 2.83 | 0.49 | 0.03 | 0.00 |
| Friction Loss (P _f) = p(L _p + L _s) [kg/cm ²] | | | | | | Lugeon value: 0.5 Lu kg/cm ² | |
| Remarks: By decreasing the pressure to 4 kg/cm ² , the flow started reverse for 3 minutes and to 1 kg/cm ² for 7 minutes. | | | | | | Critical Pressure: 11 kg/cm ² | |




Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.
 Prepared by: A. Hamid & Azhor Inspected by: Farhat M. Shah

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.
 Prepared by: A. Hamid Inspected by: M. Syaq

Water Pressure Test

Hole No.: M98-3 Stage: 9/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁴ kg/cm²/m Date: 15/December/1998


| Ground elevation : EL | | m | | Groundwater level (L _g): | | Nil | | Gauge height (L _g): | | 1.00 m | |
|---|----------------|----------------|----------------|---|----------------|----------------|----------------|--------------------------------------|----------------|-----------------|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _g)= | | 3.97 m | | Depth of test section to (L _g)= | | 45 m | | Length of section (L _g)= | | 5 m | |
| Reading of flow meter | | | | | | | | | | | |
| Gauge P. (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ | P ₈ | P ₉ | P ₁₀ | P ₁₁ |
| Start time | 15:50 | 16:05 | 16:20 | 16:35 | 16:50 | 17:05 | 17:20 | 17:35 | 17:50 | 18:05 | 18:20 |
| Q (mm) | 16,180 | 16,220 | 16,250 | 16,280 | 16,310 | 16,340 | 16,370 | 16,400 | 16,430 | 16,460 | 16,490 |
| 1 | 16,182 | 16,233 | 16,280 | 16,320 | 16,360 | 16,400 | 16,440 | 16,480 | 16,520 | 16,560 | 16,600 |
| 2 | 16,183 | 16,248 | 16,413 | 16,430 | 16,450 | 16,470 | 16,490 | 16,510 | 16,530 | 16,550 | 16,570 |
| 3 | 16,185 | 16,262 | 16,444 | 16,460 | 16,480 | 16,500 | 16,520 | 16,540 | 16,560 | 16,580 | 16,600 |
| 4 | 16,187 | 16,272 | 16,475 | 16,490 | 16,510 | 16,530 | 16,550 | 16,570 | 16,590 | 16,610 | 16,630 |
| 5 | 16,189 | 16,282 | 16,507 | 16,520 | 16,540 | 16,560 | 16,580 | 16,600 | 16,620 | 16,640 | 16,660 |
| 6 | 16,191 | 16,292 | 16,538 | 16,550 | 16,570 | 16,590 | 16,610 | 16,630 | 16,650 | 16,670 | 16,690 |
| 7 | 16,193 | 16,302 | 16,568 | 16,580 | 16,600 | 16,620 | 16,640 | 16,660 | 16,680 | 16,700 | 16,720 |
| 8 | 16,195 | 16,311 | 16,601 | 16,610 | 16,630 | 16,650 | 16,670 | 16,690 | 16,710 | 16,730 | 16,750 |
| 9 | 16,197 | 16,320 | 16,633 | 16,640 | 16,660 | 16,680 | 16,700 | 16,720 | 16,740 | 16,760 | 16,780 |
| 10 | 16,199 | 16,329 | 16,664 | 16,670 | 16,690 | 16,710 | 16,730 | 16,750 | 16,770 | 16,790 | 16,810 |
| 11 | | | | | | | | | | | |
| 12 | | | | | | | | | | | |
| 13 | | | | | | | | | | | |
| 14 | | | | | | | | | | | |
| 15 | | | | | | | | | | | |
| Total lit. | 19 | 109 | 314 | 512 | 714 | 917 | 1120 | 1323 | 1526 | 1729 | 1932 |
| Average lit./min | 1.9 | 9.6 | 31.4 | 51.2 | 71.4 | 91.7 | 112.0 | 132.3 | 152.6 | 172.9 | 193.2 |
| Remarks | 16:00 | 16:15 | 16:30 | 16:45 | 16:55 | 17:05 | 17:15 | 17:25 | 17:35 | 17:45 | 17:55 |
| (P ₁) | 0.00 | 0.04 | 0.39 | 1.16 | 0.30 | 0.60 | 0.90 | 0.00 | 0.00 | 0.00 | 0.00 |
| Friction Loss (Pr) = p(L _g + L) [kg/cm ²] | | | | | | | | | | | |
| Remarks : By decreasing pressure to 4 kg/cm ² , the flowmeter started reverse reading a minutes and to 1 kg/cm ² for 5 minutes. | | | | | | | | | | | |
| Note : Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute. | | | | | | | | | | | |
| Prepared by : A. Hamid & Azhor Inspected by : M. Suga | | | | | | | | | | | |



Water Pressure Test

Hole No.: M98-3 Stage: 10/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁴ kg/cm²/m Date: 20/December/1998

| Ground elevation : EL | | m | | Groundwater level (L _g): | | Nil | | Gauge height (L _g): | | 1.00 m | |
|---|----------------|----------------|----------------|---|----------------|----------------|----------------|--------------------------------------|----------------|-----------------|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _g)= | | 4.40 m | | Depth of test section to (L _g)= | | 45 m | | Length of section (L _g)= | | 5 m | |
| Reading of flow meter | | | | | | | | | | | |
| Gauge P. (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ | P ₈ | P ₉ | P ₁₀ | P ₁₁ |
| Start time | 10:12 | 10:23 | 10:34 | 10:45 | 10:57 | 11:10 | 11:22 | 11:34 | 11:46 | 11:58 | 12:10 |
| Q (mm) | 32,737 | 32,750 | 32,759 | 32,772 | 32,793 | 32,802 | 32,804 | 32,797 | 32,788 | 32,781 | 32,797 |
| 1 | 32,738 | 32,751 | 32,761 | 32,776 | 32,795 | 32,802 | 32,804 | 32,796 | 32,786 | 32,776 | 32,797 |
| 2 | 32,738 | 32,751 | 32,761 | 32,776 | 32,795 | 32,802 | 32,804 | 32,796 | 32,786 | 32,776 | 32,797 |
| 3 | 32,738 | 32,751 | 32,761 | 32,776 | 32,795 | 32,802 | 32,804 | 32,796 | 32,786 | 32,776 | 32,797 |
| 4 | 32,739 | 32,753 | 32,763 | 32,781 | 32,797 | 32,802 | 32,804 | 32,796 | 32,786 | 32,776 | 32,797 |
| 5 | 32,740 | 32,754 | 32,764 | 32,783 | 32,798 | 32,803 | 32,804 | 32,796 | 32,786 | 32,776 | 32,797 |
| 6 | 32,740 | 32,754 | 32,764 | 32,783 | 32,798 | 32,803 | 32,804 | 32,796 | 32,786 | 32,776 | 32,797 |
| 7 | 32,740 | 32,754 | 32,764 | 32,783 | 32,798 | 32,803 | 32,804 | 32,796 | 32,786 | 32,776 | 32,797 |
| 8 | 32,741 | 32,756 | 32,766 | 32,785 | 32,799 | 32,804 | 32,805 | 32,797 | 32,787 | 32,777 | 32,798 |
| 9 | 32,742 | 32,757 | 32,767 | 32,786 | 32,800 | 32,805 | 32,806 | 32,798 | 32,788 | 32,778 | 32,799 |
| 10 | 32,742 | 32,758 | 32,770 | 32,793 | 32,803 | 32,804 | 32,805 | 32,797 | 32,787 | 32,777 | 32,798 |
| 11 | | | | | | | | | | | |
| 12 | | | | | | | | | | | |
| 13 | | | | | | | | | | | |
| 14 | | | | | | | | | | | |
| 15 | | | | | | | | | | | |
| Total lit. | 5 | 8 | 11 | 21 | 10 | 2 | 1 | 0 | 0 | 0 | 0 |
| Average lit./min | 0.5 | 0.8 | 1.1 | 2.1 | 1.0 | 0.2 | 0.1 | 0.0 | 0.0 | 0.0 | 0.0 |
| Remarks | 10:22 | 10:33 | 10:44 | 10:55 | 11:07 | 11:20 | 11:32 | 11:44 | 11:55 | 12:07 | 12:19 |
| (P ₁) | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Friction Loss (Pr) = p(L _g + L) [kg/cm ²] | | | | | | | | | | | |
| Remarks : From 10 kg/cm ² to 7 kg/cm ² , reverse flow for 2 minutes. | | | | | | | | | | | |
| Note : Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute. | | | | | | | | | | | |
| Prepared by : A. Hamid Inspected by : M. Suga | | | | | | | | | | | |



Water Pressure Test

Hole No.: M98-3 Stage: 11/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^{-6} \text{ kg/cm}^2$ Date: 24/December/1998

| Ground elevation: EL | | Groundwater level (L _g): GL = 53.50 m | | Gauge height (L _g): 1.00 m | | | |
|---|-----------------|--|-----------------|---|-----------------|-----------------|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _h) = 2.80 m | | Depth of test section: GL - (L _h) = 55 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P _{o1} | P _{o2} | P _{o3} | P _{o4} | P _{o5} | P _{o6} | P _{o7} |
| Start time | 09:30 | 09:50 | 10:05 | 10:20 | 10:35 | 10:50 | 11:05 |
| U (mm) | 8.521.0 | 8.523.0 | 8.525.2 | 8.530.8 | 8.537.4 | 8.565.0 | 8.570.5 |
| 1 | 8.521.0 | 8.523.0 | 8.525.2 | 8.533.2 | 8.537.4 | 8.565.0 | 8.570.5 |
| 2 | 8.521.0 | 8.523.6 | 8.526.0 | 8.536.1 | 8.538.2 | 8.565.8 | 8.570.5 |
| 3 | 8.521.0 | 8.523.8 | 8.526.4 | 8.538.3 | 8.538.5 | 8.566.5 | 8.570.5 |
| 4 | 8.521.0 | 8.524.0 | 8.526.8 | 8.540.0 | 8.539.4 | 8.566.9 | 8.570.5 |
| 5 | 8.521.0 | 8.524.1 | 8.527.2 | 8.543.0 | 8.540.8 | 8.567.4 | 8.570.5 |
| 6 | 8.521.0 | 8.524.1 | 8.527.6 | 8.545.0 | 8.545.0 | 8.567.3 | 8.570.5 |
| 7 | 8.521.0 | 8.524.2 | 8.528.0 | 8.547.0 | 8.547.0 | 8.568.5 | 8.570.5 |
| 8 | 8.521.0 | 8.524.2 | 8.528.4 | 8.550.0 | 8.562.0 | 8.569.0 | 8.570.5 |
| 9 | 8.521.0 | 8.524.4 | 8.528.8 | 8.553.0 | 8.562.8 | 8.569.5 | 8.570.5 |
| 10 | 8.521.0 | 8.524.5 | 8.529.2 | 8.555.0 | 8.563.4 | 8.569.7 | 8.570.5 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 0.0 | 1.5 | 4.0 | 24.2 | 6.0 | 4.7 | 0.0 |
| Average lit./min | 0.00 | 0.15 | 0.40 | 2.42 | 0.60 | 0.47 | 0.00 |
| Friction Loss (P _f) = p(L _h + L _s) [kg/cm ²] | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |

Water Pressure in kg/cm²

Water Injection Ratio (q : lit./min/m)

Lugeon value: 0.0 Lu
Critical Pressure: 12 kg/cm²

Remarks: From 4 kg/cm² to 1 kg/cm² reverse flow 4 minutes.

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.

Prepared by: A. Hamid & Farhat Inspected by: M. Suja

Water Pressure Test

Hole No.: M98-3 Stage: 12/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^{-6} \text{ kg/cm}^2$ Date: 25/December/1998

| Ground elevation: EL | | Groundwater level (L _g): GL = 53.50 m | | Gauge height (L _g): 1.00 m | | | |
|---|-----------------|--|-----------------|---|-----------------|-----------------|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _h) = 3.80 m | | Depth of test section: GL - (L _h) = 60 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P _{o1} | P _{o2} | P _{o3} | P _{o4} | P _{o5} | P _{o6} | P _{o7} |
| Start time | 11:10 | 11:25 | 11:40 | 12:00 | 12:15 | 12:30 | 12:45 |
| U (mm) | 3.890.4 | 43.903 | 43.923 | 43.960 | 44.020 | 44.057 | 4.006.6 |
| 1 | 3.890.4 | 43.903 | 43.926 | 43.965 | 44.023 | 44.058 | 4.006.6 |
| 2 | 3.890.8 | 43.905 | 43.929 | 43.969 | 44.026 | 44.059 | 4.006.6 |
| 3 | 3.891.0 | 43.907 | 43.932 | 43.977 | 44.030 | 44.060 | 4.006.6 |
| 4 | 3.891.8 | 43.909 | 43.935 | 43.983 | 44.034 | 44.063 | 4.007.0 |
| 5 | 3.891.8 | 43.911 | 43.938 | 43.989 | 44.038 | 44.064 | 4.007.0 |
| 6 | 3.892.5 | 43.912 | 43.942 | 43.995 | 44.042 | 44.064 | 4.007.0 |
| 7 | 3.893.3 | 43.914 | 43.944 | 43.999 | 44.046 | 44.066 | 4.007.0 |
| 8 | 3.894.0 | 43.916 | 43.948 | 44.007 | 44.050 | 44.067 | 4.007.5 |
| 9 | 3.894.7 | 43.917 | 43.951 | 44.012 | 44.054 | 44.069 | 4.007.5 |
| 10 | 3.895.4 | 43.919 | 43.953 | 44.018 | 44.057 | 44.071 | 4.008.0 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 5.0 | 18 | 30 | 58 | 37 | 14 | 1.4 |
| Average lit./min | 0.5 | 1.8 | 3.0 | 5.8 | 3.7 | 1.4 | 0.1 |
| Friction Loss (P _f) = p(L _h + L _s) [kg/cm ²] | 0.00 | 0.00 | 0.01 | 0.02 | 0.01 | 0.00 | 0.00 |

Water Pressure in kg/cm²

Water Injection Ratio (q : lit./min/m)

Lugeon value: 0.4 Lu
Critical Pressure: 13 kg/cm²

Remarks: From 4 kg/cm² to 1 kg/cm² reverse flow 4 minutes.


Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.

Prepared by: A. Hamid & Farhat Inspected by: M. Suja

Water Pressure Test

Hole No.: M98-3 Stage: 13/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁶ kg/cm²/m Date: 27/December/1998

| Ground elevation: EL | | Groundwater level (L _g): G.L. = 53.50 m | | Gauge height (L _g): 1.00 m | | | |
|---|----------------|--|----------------|---|----------------|----------------|----------------|
| Pipe length from pressure gauge to hole mouth: (L _p) = 4.30 m | | Depth of test section: G.L. - (L _g) = 65 m to (L _h) = 65 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| (kg/cm ²) | 1 | 4 | 7 | 10 | 7 | 4 | 1 |
| Start time | 13:00 | 13:11 | 13:22 | 13:34 | 13:46 | 14:00 | 14:15 |
| Q (min) | 54.837 | 54.857 | 54.892 | 54.952 | 55.016 | 55.044 | 55.051.3 |
| 1 | 54.838 | 54.861 | 54.896 | 54.958 | 55.018 | 55.044 | 55.051.3 |
| 2 | 54.839 | 54.865 | 54.902 | 54.966 | 55.021 | 55.045 | 55.051.4 |
| 3 | 54.839 | 54.868 | 54.907 | 54.972 | 55.024 | 55.045 | 55.051.4 |
| 4 | 54.839 | 54.871 | 54.914 | 54.978 | 55.027 | 55.046 | 55.051.5 |
| 5 | 54.839 | 54.874 | 54.919 | 54.984 | 55.029 | 55.047 | 55.051.5 |
| 6 | 54.840 | 54.877 | 54.925 | 54.990 | 55.032 | 55.047 | 55.051.5 |
| 7 | 54.841 | 54.880 | 54.931 | 54.997 | 55.035 | 55.048 | 55.051.6 |
| 8 | 54.842 | 54.882 | 54.936 | 55.003 | 55.038 | 55.049 | 55.051.6 |
| 9 | 54.842 | 54.885 | 54.942 | 55.009 | 55.040 | 55.050 | 55.051.7 |
| 10 | 54.843 | 54.887 | 54.946 | 55.014 | 55.043 | 55.051 | 55.051.7 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ |
| Average lit./min | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ |
| Friction loss (Pa) | 0.00 | 0.00 | 0.02 | 0.02 | 0.00 | 0.00 | 0.00 |
| Friction Loss (P _r) = p(L _w + L _s) [kg/cm ²] | | | | | | | |
| Lugeon value: 0.6 Lu | | | | | | | |
| Critical Pressure: >15 kg/cm ² | | | | | | | |




Remarks: From 4 to 1 kg/cm², for 3 minutes in reverse flowing.
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the last previous one minute.
 Prepared by: A. Humid
 Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-3 Stage: 14/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁶ kg/cm²/m Date: 28/December/1998

| Ground elevation: EL | | Groundwater level (L _g): G.L. = 53.30 m | | Gauge height (L _g): 1.00 m | | | |
|---|----------------|--|----------------|---|----------------|----------------|----------------|
| Pipe length from pressure gauge to hole mouth: (L _p) = 3.80 m | | Depth of test section: G.L. - (L _g) = 65 m to (L _h) = 70 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| (kg/cm ²) | 1 | 4 | 7 | 10 | 7 | 4 | 1 |
| Start time | 15:30 | 15:42 | 15:54 | 16:10 | 16:26 | 16:40 | 17:00 |
| Q (min) | 61.628 | 61.641 | 61.662 | 66.692 | 66.730 | 66.740 | 66.745 |
| 1 | 61.629 | 61.642 | 61.664 | 66.695 | 66.731 | 66.741 | 66.745 |
| 2 | 61.630 | 61.644 | 61.667 | 66.699 | 66.733 | 66.741 | 66.745 |
| 3 | 61.631 | 61.646 | 61.670 | 66.702 | 66.734 | 66.742 | 66.745 |
| 4 | 61.632 | 61.648 | 61.672 | 66.706 | 66.736 | 66.742 | 66.746 |
| 5 | 61.632 | 61.649 | 61.674 | 66.709 | 66.738 | 66.742 | 66.746 |
| 6 | 61.633 | 61.651 | 61.676 | 66.712 | 66.737 | 66.743 | 66.746 |
| 7 | 61.634 | 61.652 | 61.679 | 66.716 | 66.737 | 66.743 | 66.747 |
| 8 | 61.635 | 61.654 | 61.681 | 66.719 | 66.738 | 66.743 | 66.747 |
| 9 | 61.636 | 61.656 | 61.683 | 66.722 | 66.738 | 66.744 | 66.747 |
| 10 | 61.637 | 61.658 | 61.686 | 66.726 | 66.739 | 66.744 | 66.747 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ |
| Average lit./min | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ |
| Friction loss (Pa) | 0.00 | 0.00 | 0.00 | 0.01 | 0.00 | 0.00 | 0.00 |
| Friction Loss (P _r) = p(L _w + L _s) [kg/cm ²] | | | | | | | |
| Lugeon value: 0.4 Lu | | | | | | | |
| Critical Pressure: >15 kg/cm ² | | | | | | | |




Remarks: From 4 to 1 kg/cm², for 4 minutes in reverse flowing.
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the last previous one minute.
 Prepared by: A. Humid & Mathboob
 Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-3 Stage: 15/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁶ m/m Date: 29/December/1998

| Ground elevation: EL | | Groundwater level (L): GL | | Gauge height (L _g): | | | |
|---|--|------------------------------|----------------|---|----------------|----------------|----------------|
| Pipe length from pressure gauge to hole mouth: (L _m) = 3.94 m | | Depth of test section: 75 m | | Length of section (L _s): 1.00 m | | | |
| Reading of flow meter | | Calculation of Luggeon value | | | | | |
| Gauge P. | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 15:10 | 15:25 | 15:40 | 16:00 | 16:15 | 16:30 | 16:45 |
| Q (min) | 68.466 | 68.489 | 68.521 | 68.503 | 68.619 | 68.611 | 68.665 |
| 1 | 68.468 | 68.492 | 68.525 | 68.509 | 68.623 | 68.612 | 68.665 |
| 2 | 68.470 | 68.496 | 68.529 | 68.575 | 68.626 | 68.613 | 68.666 |
| 3 | 68.471 | 68.499 | 68.534 | 68.580 | 68.629 | 68.614 | 68.666 |
| 4 | 68.473 | 68.503 | 68.538 | 68.585 | 68.632 | 68.616 | 68.667 |
| 5 | 68.474 | 68.506 | 68.542 | 68.591 | 68.635 | 68.617 | 68.667 |
| 6 | 68.475 | 68.508 | 68.546 | 68.596 | 68.638 | 68.618 | 68.667 |
| 7 | 68.477 | 68.510 | 68.550 | 68.601 | 68.641 | 68.620 | 68.668 |
| 8 | 68.478 | 68.513 | 68.554 | 68.606 | 68.644 | 68.621 | 68.668 |
| 9 | 68.479 | 68.515 | 68.558 | 68.611 | 68.647 | 68.622 | 68.668 |
| 10 | 68.480 | 68.517 | 68.562 | 68.616 | 68.650 | 68.624 | 68.669 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ |
| Lit. | 1.4 | 2.8 | 4.1 | 5.3 | 3.1 | 1.3 | 4 |
| Average | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ |
| lit./min | 1.4 | 2.8 | 4.1 | 5.3 | 3.1 | 1.3 | 0.4 |
| Flow rate | 15:20 | 15:35 | 15:50 | 16:10 | 16:25 | 16:40 | 16:55 |
| (P) | 0.00 | 0.01 | 0.01 | 0.02 | 0.01 | 0.00 | 0.00 |
| Friction Loss (P) = p(L _m + L _s) [kg/cm ²] | | | | | | | |
| Remarks: | From 7 to 4 kg/cm ² , for 3 minutes in reverse flowing. | | | | | | |




Water Injection Ratio (q) : lit./min/m
 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0
 Luggeon value : 0.6 Lu
 Critical Pressure: >15 kg/cm²

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the just previous one minute.
 Prepared by: A. Hamid & Gil
 Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-3 Stage: 16/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): 1x10⁻⁶ m/m Date: 30/December/1998

| Ground elevation: EL | | Groundwater level (L): GL | | Gauge height (L _g): | | | |
|---|--|------------------------------|----------------|---|----------------|----------------|----------------|
| Pipe length from pressure gauge to hole mouth: (L _m) = 3.93 m | | Depth of test section: 75 m | | Length of section (L _s): 1.00 m | | | |
| Reading of flow meter | | Calculation of Luggeon value | | | | | |
| Gauge P. | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 15:00 | 15:15 | 15:30 | 15:45 | 16:00 | 16:15 | 16:30 |
| Q (min) | 73.700 | 73.701 | 73.702 | 73.715 | 73.733 | 73.742 | 73.749 |
| 1 | 73.700 | 73.701 | 73.704 | 73.717 | 73.733 | 73.742 | 73.749 |
| 2 | 73.700 | 73.701 | 73.704 | 73.720 | 73.734 | 73.743 | 73.749 |
| 3 | 73.700 | 73.701 | 73.705 | 73.722 | 73.735 | 73.743 | 73.749 |
| 4 | 73.700 | 73.701 | 73.706 | 73.724 | 73.736 | 73.744 | 73.749 |
| 5 | 73.700 | 73.701 | 73.708 | 73.727 | 73.737 | 73.744 | 73.749 |
| 6 | 73.700 | 73.701 | 73.709 | 73.729 | 73.738 | 73.745 | 73.749 |
| 7 | 73.700 | 73.701 | 73.710 | 73.732 | 73.739 | 73.746 | 73.749 |
| 8 | 73.700 | 73.701 | 73.712 | 73.734 | 73.740 | 73.746 | 73.749 |
| 9 | 73.700 | 73.701 | 73.713 | 73.736 | 73.741 | 73.747 | 73.749 |
| 10 | 73.700 | 73.701 | 73.714 | 73.738 | 73.742 | 73.747 | 73.749 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ |
| Lit. | 0 | 0 | 12 | 23 | 9 | 5 | 0 |
| Average | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ |
| lit./min | 0.0 | 0.0 | 1.2 | 2.3 | 0.9 | 0.5 | 0.0 |
| Flow rate | 15:10 | 15:25 | 15:40 | 15:55 | 16:10 | 16:25 | 16:40 |
| (P) | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Friction Loss (P) = p(L _m + L _s) [kg/cm ²] | | | | | | | |
| Remarks: | From 7 to 4 kg/cm ² , for 3 minutes in reverse flowing. | | | | | | |




Water Injection Ratio (q) : lit./min/m
 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0
 Luggeon value : (0.0) Lu
 Critical Pressure: 8.7 kg/cm²

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the just previous one minute.
 Prepared by: A. Hamid & Mahboob
 Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-3 Stage: 17/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^4 \text{ kg/cm}^2$ Date: 1/January/1999

| Ground elevation : EL | | Groundwater level (L _g): GL= 42.50 m | | Gauge height (L _g): 1.00 m | | | |
|---|----------------|---|----------------|---|----------------|---|----------------|
| Pipe length from pressure gauge to hole mouth: (L _p)= 2.80 m | | Depth of test section GL - (L _g) = 85 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 09:30 | 09:42 | 09:56 | 10:10 | 10:25 | 10:40 | 10:51 |
| U (min) | 79,912 | 79,920 | 79,931 | 79,965 | 80,018 | 80,052 | 80,057 |
| 1 | 79,912 | 79,921 | 79,934 | 79,970 | 80,021 | 80,054 | 80,057 |
| 2 | 79,913 | 79,922 | 79,937 | 79,974 | 80,024 | 80,055 | 80,057 |
| 3 | 79,914 | 79,924 | 79,940 | 79,979 | 80,026 | 80,057 | 80,058 |
| 4 | 79,914 | 79,924 | 79,942 | 79,984 | 80,029 | 80,059 | 80,058 |
| 5 | 79,914 | 79,925 | 79,945 | 79,988 | 80,033 | 80,061 | 80,058 |
| 6 | 79,915 | 79,926 | 79,948 | 79,993 | 80,036 | 80,062 | 80,058 |
| 7 | 79,915 | 79,927 | 79,950 | 79,998 | 80,039 | 80,064 | 80,059 |
| 8 | 79,916 | 79,928 | 79,953 | 80,002 | 80,043 | 80,066 | 80,059 |
| 9 | 79,916 | 79,929 | 79,956 | 80,007 | 80,047 | 80,067 | 80,059 |
| 10 | 79,917 | 79,930 | 79,958 | 80,012 | 80,050 | 80,069 | 80,059 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 5 | 10 | 27 | 47 | 32 | 17 | 2 |
| Average lit./min | 0.5 | 1 | 2.7 | 4.7 | 3.2 | 1.7 | 0.2 |
| Friction loss (P _f) | 0.040 | 0.052 | 0.066 | 0.10 | 0.20 | 0.35 | 0.59 |
| (P _f) | 0.04 | 0.04 | 0.04 | 0.02 | 0.03 | 0.04 | 0.04 |
| Friction Loss (P _f) = p(L _p + L _s) [kg/cm ²] | | | | | | Lugeon value : (0.2) Lu' | |
| | | | | | | Critical Pressure: 9.0 kg/cm ² | |




Remarks :
 Note : Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the just previous one minute.
 Prepared by : A. Humid
 Inspected by : Farhat M. Shah

Water Pressure Test

Hole No.: M98-3 Stage: 18/20
 Location: Dam Axis (Right Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^4 \text{ kg/cm}^2$ Date: 3/January/1999

| Ground elevation : EL | | Groundwater level (L _g): GL= 36.50 m | | Gauge height (L _g): 1.00 m | | | |
|---|----------------|---|----------------|---|----------------|---|----------------|
| Pipe length from pressure gauge to hole mouth: (L _p)= 3.95 m | | Depth of test section GL - (L _g) = 85 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 12:10 | 12:25 | 12:40 | 12:55 | 13:10 | 13:15 | 13:30 |
| U (min) | 86,000 | 86,007 | 86,020 | 86,051 | 86,102 | 86,131 | 86,138 |
| 1 | 86,001 | 86,008 | 86,023 | 86,056 | 86,105 | 86,133 | 86,138 |
| 2 | 86,001 | 86,009 | 86,026 | 86,061 | 86,108 | 86,134 | 86,139 |
| 3 | 86,002 | 86,010 | 86,029 | 86,067 | 86,111 | 86,136 | 86,141 |
| 4 | 86,002 | 86,011 | 86,032 | 86,072 | 86,114 | 86,137 | 86,141 |
| 5 | 86,002 | 86,011 | 86,034 | 86,077 | 86,118 | 86,139 | 86,142 |
| 6 | 86,003 | 86,012 | 86,037 | 86,081 | 86,121 | 86,140 | 86,142 |
| 7 | 86,004 | 86,013 | 86,040 | 86,084 | 86,124 | 86,142 | 86,143 |
| 8 | 86,004 | 86,014 | 86,042 | 86,088 | 86,126 | 86,143 | 86,143 |
| 9 | 86,004 | 86,015 | 86,045 | 86,092 | 86,129 | 86,145 | 86,144 |
| 10 | 86,005 | 86,016 | 86,047 | 86,097 | 86,131 | 86,146 | 86,144 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 5 | 9 | 27 | 46 | 29 | 15 | 6 |
| Average lit./min | 0.5 | 0.9 | 2.7 | 4.6 | 2.9 | 1.5 | 0.6 |
| Friction loss (P _f) | 0.040 | 0.052 | 0.066 | 0.10 | 0.20 | 0.35 | 0.59 |
| (P _f) | 0.04 | 0.04 | 0.04 | 0.02 | 0.03 | 0.04 | 0.04 |
| Friction Loss (P _f) = p(L _p + L _s) [kg/cm ²] | | | | | | Lugeon value : (0.2) Lu' | |
| | | | | | | Critical Pressure: 7.7 kg/cm ² | |




Remarks :
 Note : Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the just previous one minute.
 Prepared by : A. Humid
 Inspected by : Farhat M. Shah

Water Pressure Test

Hole No.: M98-3
 Location: Dam Axis (Right Bank)
 Hole Inclination (α): 90 degrees
 Stage: 19/20
 Dia. of Hole: 76 m/m
 Packer Type: Mechanical
 Date: 4/January/1999

| | | | | | | | |
|---|-----------|----------------------|----------------------|---|----------------------|--|----------------------|
| Ground elevation: EL | | m | | Groundwater level (L _g): GL = 35.50 m | | Gauge height (L _g): 1.00 m | |
| Pipe length from pressure gauge to hole mouth: (L _g) = 3.95 m | | m | | Depth of test section: 95 m | | Length of section (L _s): 5 m | |
| Friction Loss per meter (P _f): 1x10 ⁻³ kg/cm ² /m | | | | | | | |
| Calculation of Lugeon value | | | | | | | |
| Start time | Q (l/min) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ |
| 1 | 91.240 | 13.90 | 13.11 | 13.23 | 13.35 | 13.50 | 14.05 |
| 2 | 91.240 | 91.249 | 91.260 | 91.290 | 91.340 | 91.360 | 91.375 |
| 3 | 91.241 | 91.250 | 91.265 | 91.299 | 91.345 | 91.367 | 91.374 |
| 4 | 91.242 | 91.251 | 91.269 | 91.304 | 91.347 | 91.368 | 91.374 |
| 5 | 91.242 | 91.251 | 91.272 | 91.313 | 91.352 | 91.369 | 91.375 |
| 6 | 91.243 | 91.254 | 91.275 | 91.317 | 91.355 | 91.370 | 91.376 |
| 7 | 91.244 | 91.254 | 91.277 | 91.322 | 91.358 | 91.371 | 91.376 |
| 8 | 91.244 | 91.255 | 91.279 | 91.326 | 91.360 | 91.371 | 91.377 |
| 9 | 91.245 | 91.256 | 91.282 | 91.331 | 91.363 | 91.372 | 91.377 |
| 10 | 91.246 | 91.257 | 91.284 | 91.336 | 91.365 | 91.373 | 91.378 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 6 | Q ₁ = 6 | Q ₂ = 6 | Q ₃ = 6 | Q ₄ = 6 | Q ₅ = 6 | Q ₆ = 6 |
| Average lit./min | 0.6 | Q ₁ = 0.6 | Q ₂ = 0.6 | Q ₃ = 0.6 | Q ₄ = 0.6 | Q ₅ = 0.6 | Q ₆ = 0.6 |
| Friction loss (P _f) | 0.00 | 0.00 | 0.01 | 0.02 | 0.01 | 0.00 | 0.00 |
| Friction Loss (P _f) = p _f (L _g + L _s) [kg/cm ²] | | | | | | | |
| Remarks: | | | | | | | |
| Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the last previous one minute | | | | | | | |
| Prepared by: A. Hamid | | | | | | | |
| Inspected by: A. Gill | | | | | | | |




Water Injection Ratio (q : lit./min/m)
 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0

Lugeon value: (0.2)
 Critical Pressure: 8.8 kg/cm²

Water Pressure Test

Hole No.: M98-3
 Location: Dam Axis (Right Bank)
 Hole Inclination (α): 90 degrees
 Stage: 20/20
 Dia. of Hole: 76 m/m
 Packer Type: Mechanical
 Date: 5/January/1999

| | | | | | | | |
|---|-----------|----------------------|----------------------|---|----------------------|--|----------------------|
| Ground elevation: EL | | m | | Groundwater level (L _g): GL = 33.40 m | | Gauge height (L _g): 1.00 m | |
| Pipe length from pressure gauge to hole mouth: (L _g) = 3.95 m | | m | | Depth of test section: 95 m | | Length of section (L _s): 5 m | |
| Friction Loss per meter (P _f): 1x10 ⁻³ kg/cm ² /m | | | | | | | |
| Calculation of Lugeon value | | | | | | | |
| Start time | Q (l/min) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ |
| 1 | 10.587 | 08.10 | 08.22 | 08.35 | 08.50 | 09.03 | 09.15 |
| 2 | 10.588 | 10.594 | 10.604 | 10.626 | 10.652 | 10.671 | 10.675 |
| 3 | 10.588 | 10.594 | 10.605 | 10.628 | 10.654 | 10.672 | 10.675 |
| 4 | 10.589 | 10.595 | 10.607 | 10.631 | 10.659 | 10.672 | 10.676 |
| 5 | 10.590 | 10.596 | 10.609 | 10.634 | 10.658 | 10.673 | 10.676 |
| 6 | 10.590 | 10.597 | 10.611 | 10.638 | 10.659 | 10.673 | 10.676 |
| 7 | 10.590 | 10.597 | 10.612 | 10.640 | 10.662 | 10.674 | 10.677 |
| 8 | 10.591 | 10.598 | 10.614 | 10.643 | 10.664 | 10.674 | 10.677 |
| 9 | 10.591 | 10.599 | 10.615 | 10.646 | 10.666 | 10.675 | 10.678 |
| 10 | 10.591 | 10.600 | 10.617 | 10.648 | 10.668 | 10.675 | 10.678 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 4 | Q ₁ = 4 | Q ₂ = 4 | Q ₃ = 4 | Q ₄ = 4 | Q ₅ = 4 | Q ₆ = 4 |
| Average lit./min | 0.4 | Q ₁ = 0.4 | Q ₂ = 0.4 | Q ₃ = 0.4 | Q ₄ = 0.4 | Q ₅ = 0.4 | Q ₆ = 0.4 |
| Friction loss (P _f) | 0.00 | 0.00 | 0.00 | 0.01 | 0.01 | 0.00 | 0.00 |
| Friction Loss (P _f) = p _f (L _g + L _s) [kg/cm ²] | | | | | | | |
| Remarks: | | | | | | | |
| Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the last previous one minute | | | | | | | |
| Prepared by: A. Hamid & Azhor | | | | | | | |
| Inspected by: Farhat M. Shah | | | | | | | |




Water Injection Ratio (q : lit./min/m)
 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0

Lugeon value: (0.2)
 Critical Pressure: 8.3 kg/cm²

Water Pressure Test

Hole No.: M98-4 Stage: 1/14
 Location: Dam Axis (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (α): 60 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁻⁴ x Q^{1.75} Date: 11/January/1999

| Ground elevation: EL. m | | Groundwater level (L _g): GL. m | | Gauge height (L _g): 0.70 m | | | |
|---|-----------------|--|-----------------|---|-----------------|-----------------|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _g) = 4.50 m | | Depth of test section to (L _g) = 2 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P _f (kg/cm ²) | P _{h1} | P _{h2} | P _{h3} | P _{h4} | P _{h5} | P _{h6} | P _{h7} |
| Start time | 10:30 | 10:42 | 10:54 | 11:06 | 11:18 | 11:30 | 11:42 |
| U (min) | 57.546 | 57.488 | 57.664 | 58.020 | 58.450 | 58.763 | 58.966 |
| 1 | 57.558 | 57.496 | 57.682 | 58.059 | 58.481 | 58.783 | 58.979 |
| 2 | 57.570 | 57.513 | 57.704 | 58.100 | 58.511 | 58.803 | 58.990 |
| 3 | 57.582 | 57.528 | 57.726 | 58.141 | 58.542 | 58.823 | 59.001 |
| 4 | 57.593 | 57.544 | 57.749 | 58.182 | 58.572 | 58.843 | 59.011 |
| 5 | 57.604 | 57.558 | 57.771 | 58.223 | 58.601 | 58.863 | 59.022 |
| 6 | 57.614 | 57.573 | 57.792 | 58.263 | 58.631 | 58.883 | 59.033 |
| 7 | 57.624 | 57.583 | 57.814 | 58.304 | 58.661 | 58.903 | 59.043 |
| 8 | 57.635 | 57.601 | 57.836 | 58.344 | 58.690 | 58.921 | 59.054 |
| 9 | 57.645 | 57.615 | 57.857 | 58.385 | 58.719 | 58.942 | 59.064 |
| 10 | 57.655 | 57.629 | 57.878 | 58.425 | 58.747 | 58.961 | 59.075 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | Q=1 | Q=2 | Q=3 | Q=4 | Q=5 | Q=6 | Q=7 |
| Average lit./min | 10.9 | 14.9 | 21.8 | 40.5 | 29.7 | 198 | 107 |
| Remarks | 10.9 | 14.9 | 21.8 | 40.5 | 29.7 | 19.8 | 10.7 |
| (P _f) | 0.01 | 0.01 | 0.03 | 0.10 | 0.05 | 0.02 | 0.01 |




Lugeon value: (4.5) L_u'
 Critical Pressure: 6.9 kg/cm²

Remarks: COS60=0.868
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute
 Prepared by: A. Hamid & Azhor Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-4 Stage: 2/14
 Location: Dam Axis (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (α): 60 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁻⁴ x Q^{1.75} Date: 11/January/1999

| Ground elevation: EL. m | | Groundwater level (L _g): GL. m | | Gauge height (L _g): 0.70 m | | | |
|---|-----------------|--|-----------------|---|-----------------|-----------------|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _g) = 4.50 m | | Depth of test section to (L _g) = 5 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P _f (kg/cm ²) | P _{h1} | P _{h2} | P _{h3} | P _{h4} | P _{h5} | P _{h6} | P _{h7} |
| Start time | 16:00 | 16:12 | 16:23 | 16:34 | 16:46 | 16:56 | 17:10 |
| U (min) | 63.021 | 63.022 | 63.023 | 63.043 | 63.066 | 63.084 | 63.092 |
| 1 | 63.021 | 63.023 | 63.030 | 63.043 | 63.067 | 63.085 | 63.092 |
| 2 | 63.021 | 63.024 | 63.031 | 63.047 | 63.069 | 63.086 | 63.092 |
| 3 | 63.021 | 63.025 | 63.033 | 63.049 | 63.071 | 63.086 | 63.092 |
| 4 | 63.022 | 63.026 | 63.034 | 63.051 | 63.073 | 63.087 | 63.092 |
| 5 | 63.022 | 63.026 | 63.035 | 63.053 | 63.075 | 63.088 | 63.092 |
| 6 | 63.022 | 63.026 | 63.036 | 63.056 | 63.076 | 63.089 | 63.092 |
| 7 | 63.022 | 63.027 | 63.038 | 63.058 | 63.078 | 63.090 | 63.093 |
| 8 | 63.022 | 63.027 | 63.039 | 63.060 | 63.080 | 63.091 | 63.093 |
| 9 | 63.022 | 63.027 | 63.040 | 63.062 | 63.082 | 63.092 | 63.093 |
| 10 | 63.022 | 63.028 | 63.042 | 63.064 | 63.083 | 63.093 | 63.093 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | Q=1 | Q=2 | Q=3 | Q=4 | Q=5 | Q=6 | Q=7 |
| Average lit./min | 0.1 | 0.2 | 0.3 | 0.4 | 0.5 | 0.6 | 0.7 |
| Remarks | 16.10 | 16.22 | 16.33 | 16.44 | 16.56 | 17.08 | 17.20 |
| (P _f) | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |



Lugeon value: (0.3) L_u'
 Critical Pressure: 5.7 kg/cm²


Remarks: COS60=0.868
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute
 Prepared by: A. Hamid & Azhor Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-4 Stage: 3/14
 Location: Dam Axis (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 60 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^{-4} \times Q^{1.911}$ Date: 12/January/1999

Ground elevation: EL. m Groundwater level (L₁): CL. 12.50 m Gauge height (L₂): 0.70 m
 Pipe length from pressure gauge to hole mouth: (L₃) = 4.50 m CL. (L₄) = 15 m to (L₅) = 10 m Depth of test section Length of section (L₆) = 5 m

| Reading of flow meter | | | | | | | | | | | | | | |
|---|----------------|----------------|----------------|----------------|----------------|----------------|----------------|--|--|--|--|--|--|--|
| Gauge P. | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ | | | | | | | |
| (kg/cm ²) | 1 | 4 | 7 | 10 | 7 | 4 | 1 | | | | | | | |
| Start time | 08:00 | 08:12 | 08:24 | 08:35 | 08:47 | 08:58 | 09:10 | | | | | | | |
| Q (min) | 70.800 | 71.020 | 71.420 | 72.180 | 73.250 | 74.060 | 74.620 | | | | | | | |
| 1 | 70.800 | 71.053 | 71.483 | 72.280 | 73.328 | 74.114 | 74.652 | | | | | | | |
| 2 | 70.339 | 71.086 | 71.548 | 72.380 | 73.405 | 74.167 | 74.684 | | | | | | | |
| 3 | 70.858 | 71.118 | 71.613 | 72.480 | 73.488 | 74.220 | 74.717 | | | | | | | |
| 4 | 70.877 | 71.150 | 71.679 | 72.581 | 73.558 | 74.373 | 74.751 | | | | | | | |
| 5 | 70.896 | 71.182 | 71.748 | 72.681 | 73.635 | 74.375 | 74.784 | | | | | | | |
| 6 | 70.915 | 71.213 | 71.819 | 72.782 | 73.712 | 74.379 | 74.817 | | | | | | | |
| 7 | 70.934 | 71.246 | 71.891 | 72.884 | 73.792 | 74.483 | 74.850 | | | | | | | |
| 8 | 70.953 | 71.278 | 71.979 | 72.986 | 73.865 | 74.486 | 74.883 | | | | | | | |
| 9 | 70.971 | 71.310 | 72.060 | 73.087 | 73.940 | 74.539 | 74.916 | | | | | | | |
| 10 | 70.990 | 71.342 | 72.142 | 73.188 | 74.016 | 74.592 | 74.949 | | | | | | | |
| 11 | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | |
| 13 | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | |
| 15 | | | | | | | | | | | | | | |
| Total | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ | | | | | | | |
| Hr. | 190 | 322 | 722 | 1,008 | 766 | 532 | 329 | | | | | | | |
| Average | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ | | | | | | | |
| lit/min | 19.0 | 32.2 | 72.2 | 100.8 | 76.6 | 53.2 | 32.9 | | | | | | | |
| Remarks | 08:10 | 08:22 | 08:34 | 08:45 | 08:57 | 09:08 | 09:20 | | | | | | | |
| Friction Loss (P ₂) = p(L ₂ × L ₃) (kg/cm ²) | 0.05 | 0.14 | 0.67 | 1.29 | 0.75 | 0.37 | 0.14 | | | | | | | |



Lugeon value : (11) Lu'
 Critical Pressure: 5.0 kg/cm²


Remarks : COS60=0.868
 Note : Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.
 Prepared by : A. Hamid & Azhar Inspected by : Farhat M. Shah

Water Pressure Test

Hole No.: M98-4 Stage: 4/14
 Location: Dam Axis (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 60 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^{-4} \times Q^{1.911}$ Date: 12/January/1999

Ground elevation: EL. m Groundwater level (L₁): CL. 14.50 m Gauge height (L₂): 0.70 m
 Pipe length from pressure gauge to hole mouth: (L₃) = 4.50 m CL. (L₄) = 20 m to (L₅) = 15 m Depth of test section Length of section (L₆) = 5 m

| Reading of flow meter | | | | | | | | | | | | | | |
|---|----------------|----------------|----------------|----------------|----------------|----------------|----------------|--|--|--|--|--|--|--|
| Gauge P. | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ | | | | | | | |
| (kg/cm ²) | 1 | 4 | 7 | 10 | 7 | 4 | 1 | | | | | | | |
| Start time | 16:30 | 16:42 | 16:54 | 17:10 | 17:21 | 17:32 | 17:44 | | | | | | | |
| Q (min) | 83.323 | 83.510 | 83.800 | 85.000 | 86.200 | 87.360 | 88.250 | | | | | | | |
| 1 | 83.323 | 83.536 | 83.857 | 85.089 | 86.320 | 87.417 | 88.294 | | | | | | | |
| 2 | 83.343 | 83.555 | 83.920 | 85.184 | 86.432 | 87.487 | 88.348 | | | | | | | |
| 3 | 83.352 | 83.583 | 83.986 | 85.289 | 86.542 | 87.563 | 88.410 | | | | | | | |
| 4 | 83.362 | 83.606 | 84.057 | 85.395 | 86.647 | 87.644 | 88.474 | | | | | | | |
| 5 | 83.372 | 83.650 | 84.160 | 85.509 | 86.757 | 87.721 | 88.537 | | | | | | | |
| 6 | 83.382 | 83.650 | 84.248 | 85.625 | 86.869 | 86.811 | 88.602 | | | | | | | |
| 7 | 83.392 | 83.674 | 84.333 | 85.745 | 86.976 | 86.897 | 88.668 | | | | | | | |
| 8 | 83.403 | 83.697 | 84.428 | 85.867 | 87.092 | 86.984 | 88.736 | | | | | | | |
| 9 | 83.413 | 83.720 | 84.536 | 85.999 | 87.212 | 86.071 | 88.803 | | | | | | | |
| 10 | 83.423 | 83.749 | 84.626 | 86.130 | 87.324 | 88.159 | 88.871 | | | | | | | |
| 11 | | | | | | | | | | | | | | |
| 12 | | | | | | | | | | | | | | |
| 13 | | | | | | | | | | | | | | |
| 14 | | | | | | | | | | | | | | |
| 15 | | | | | | | | | | | | | | |
| Total | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ | | | | | | | |
| Hr. | 100 | 239 | 826 | 1,170 | 1,126 | 799 | 621 | | | | | | | |
| Average | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ | | | | | | | |
| lit/min | 10.0 | 23.9 | 82.6 | 117.0 | 112.6 | 79.9 | 62.1 | | | | | | | |
| Remarks | 16:40 | 16:52 | 17:04 | 17:10 | 17:31 | 17:42 | 17:54 | | | | | | | |
| Friction Loss (P ₂) = p(L ₂ × L ₃) (kg/cm ²) | 0.02 | 0.10 | 1.17 | 2.18 | 2.16 | 1.10 | 0.67 | | | | | | | |



Lugeon value : (9.3) Lu'
 Critical Pressure: 5.2 kg/cm²

Remarks : COS60=0.868
 Note : Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.
 Prepared by : A. Hamid & Azhar Inspected by : Farhat M. Shah

Water Pressure Test

Hole No.: M98-4 Stage: 5/14
 Location: Dam Axis (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 60 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^{-4} \times Q^{1.711}$ Date: 13/January/1999

| Ground elevation: EL | | Groundwater level (L _g): GL = 14.70 m | | Gauge height (L _g): 0.70 m | | | |
|---|-----------------|--|-----------------|---|-----------------|-----------------|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _h) = 4.50 m | | Depth of test section GL - (L _h) = 2.5 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P _{h1} | P _{h2} | P _{h3} | P _{h4} | P _{h5} | P _{h6} | P _{h7} |
| Start time | 07:30 | 07:42 | 07:54 | 08:05 | 08:17 | 08:29 | 08:42 |
| Q (lit/min) | 95.472 | 95.473 | 95.473 | 95.473 | 95.476 | 95.476 | 95.476 |
| 1 | 95.472 | 95.473 | 95.473 | 95.474 | 95.476 | 95.476 | 95.476 |
| 2 | 95.472 | 95.473 | 95.473 | 95.474 | 95.476 | 95.476 | 95.476 |
| 3 | 95.472 | 95.473 | 95.473 | 95.475 | 95.476 | 95.476 | 95.476 |
| 4 | 95.472 | 95.473 | 95.473 | 95.475 | 95.476 | 95.476 | 95.476 |
| 5 | 95.472 | 95.473 | 95.473 | 95.475 | 95.477 | 95.476 | 95.476 |
| 6 | 95.472 | 95.473 | 95.473 | 95.476 | 95.477 | 95.476 | 95.476 |
| 7 | 95.472 | 95.473 | 95.473 | 95.476 | 95.477 | 95.476 | 95.476 |
| 8 | 95.472 | 95.473 | 95.473 | 95.476 | 95.477 | 95.476 | 95.476 |
| 9 | 95.472 | 95.473 | 95.473 | 95.477 | 95.478 | 95.476 | 95.476 |
| 10 | 95.472 | 95.473 | 95.473 | 95.477 | 95.478 | 95.476 | 95.476 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Average lit./min | 0.0 | 0.0 | 0.0 | 0.4 | 0.2 | 0.0 | 0.0 |
| Final time | 07:40 | 07:52 | 08:04 | 08:15 | 08:27 | 08:39 | 08:52 |
| (P) | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Friction Loss (P _f) = p(L _h + L _s) (kg/cm ²) | | | | | | | |

Remarks: COS60=0.868

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 1.10 % of the injection rate in the last previous one minute

Prepared by: A. Hamid & Azhor Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-4 Stage: 6/14
 Location: Dam Axis (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 60 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^{-4} \times Q^{1.711}$ Date: 13/January/1999

| Ground elevation: EL | | Groundwater level (L _g): GL = 14.20 m | | Gauge height (L _g): 0.70 m | | | |
|---|-----------------|--|-----------------|---|-----------------|-----------------|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _h) = 4.50 m | | Depth of test section GL - (L _h) = 3.0 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P _{h1} | P _{h2} | P _{h3} | P _{h4} | P _{h5} | P _{h6} | P _{h7} |
| Start time | 16:45 | 16:57 | 17:09 | 17:20 | 17:32 | 17:44 | 17:55 |
| Q (lit/min) | 10.629 | 10.630 | 10.635 | 10.647 | 10.666 | 10.676 | 10.676 |
| 1 | 10.629 | 10.630 | 10.635 | 10.647 | 10.666 | 10.676 | 10.676 |
| 2 | 10.629 | 10.630 | 10.636 | 10.649 | 10.667 | 10.676 | 10.676 |
| 3 | 10.629 | 10.630 | 10.637 | 10.650 | 10.668 | 10.676 | 10.676 |
| 4 | 10.629 | 10.630 | 10.638 | 10.652 | 10.669 | 10.676 | 10.676 |
| 5 | 10.629 | 10.630 | 10.638 | 10.654 | 10.670 | 10.676 | 10.676 |
| 6 | 10.629 | 10.631 | 10.639 | 10.655 | 10.671 | 10.676 | 10.676 |
| 7 | 10.629 | 10.631 | 10.640 | 10.657 | 10.673 | 10.676 | 10.676 |
| 8 | 10.629 | 10.631 | 10.640 | 10.659 | 10.674 | 10.676 | 10.676 |
| 9 | 10.629 | 10.631 | 10.641 | 10.661 | 10.675 | 10.676 | 10.676 |
| 10 | 10.629 | 10.632 | 10.642 | 10.663 | 10.676 | 10.677 | 10.676 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 0 | 2 | 8 | 18 | 12 | 1 | 0 |
| Average lit./min | 0.0 | 0.2 | 0.8 | 1.8 | 1.2 | 0.1 | 0.0 |
| Final time | 16:55 | 17:07 | 17:19 | 17:30 | 17:42 | 17:54 | 18:05 |
| (P) | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Friction Loss (P _f) = p(L _h + L _s) (kg/cm ²) | | | | | | | |

Remarks: COS60=0.868

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 1.10 % of the injection rate in the last previous one minute

Prepared by: A. Hamid & Azhor Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-4 Stage: 7/14
 Location: Dam Axis (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 60 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^{-4} \times Q^{1.75}$ Date: 14/January/1999

| Ground elevation: EL. m | | Groundwater level (L _g): GL. 14.10 m | | Gauge height (L _g): 0.70 m | | | |
|---|----------------|--|----------------|---|----------------|----------------|----------------|
| Pipe length from pressure gauge to hole mouth: (L _p) = 4.50 m | | Depth of test section: GL. - (L _g) = 35 m to (L _g) = 5 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 07:30 | 07:42 | 07:54 | 08:06 | 08:17 | 08:29 | 08:42 |
| Q (m ³ /min) | 19.631 | 19.660 | 19.688 | 19.722 | 19.761 | 19.770 | 19.771 |
| 1 | 19.633 | 19.662 | 19.691 | 19.726 | 19.762 | 19.770 | 19.771 |
| 2 | 19.635 | 19.664 | 19.693 | 19.730 | 19.763 | 19.771 | 19.771 |
| 3 | 19.637 | 19.666 | 19.695 | 19.733 | 19.764 | 19.771 | 19.772 |
| 4 | 19.639 | 19.669 | 19.698 | 19.737 | 19.765 | 19.772 | 19.773 |
| 5 | 19.641 | 19.672 | 19.701 | 19.741 | 19.766 | 19.772 | 19.773 |
| 6 | 19.642 | 19.674 | 19.704 | 19.744 | 19.767 | 19.773 | 19.773 |
| 7 | 19.644 | 19.676 | 19.707 | 19.748 | 19.768 | 19.774 | 19.774 |
| 8 | 19.646 | 19.678 | 19.709 | 19.752 | 19.769 | 19.774 | 19.774 |
| 9 | 19.647 | 19.680 | 19.712 | 19.756 | 19.770 | 19.775 | 19.775 |
| 10 | 19.649 | 19.682 | 19.715 | 19.759 | 19.771 | 19.776 | 19.776 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 18 | 22 | 27 | 37 | 10 | 6 | 5 |
| Average lit./min | 1.8 | 2.2 | 2.7 | 3.7 | 1.0 | 0.6 | 0.5 |
| Friction loss (Pr) | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Friction Loss (Pr) = p(L _p + L _s) [kgf/cm ²] | | | | | | | |
| Calculation of Lugeon value | | | | | | | |
| $P_1 = P_2 + 0.1 \sin(\alpha) (L_p + L_s) \cdot Pr$ [kgf/cm ²]; $q = Q/L_s$ [lit/min/m] | | | | | | | |
| $P_1 = 2.3$ $q_1 = 0.4$ $P_2 = 5.3$ $q_2 = 0.4$ $P_3 = 8.3$ $q_3 = 0.5$ $P_4 = 11.3$ $q_4 = 0.7$ $P_5 = 8.3$ $q_5 = 0.2$ $P_6 = 5.3$ $q_6 = 0.1$ $P_7 = 2.3$ $q_7 = 0.1$ | | | | | | | |
| | | | | | | | |
| Lugeon value: 0.7 Lu kgf/cm ² Critical Pressure: >11 | | | | | | | |
| Remarks: From 7kgf to 4kgf and from 4kgf to 1kgf for few second reversed run | | | | | | | |
| COS60=0.868 | | | | | | | |
| Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the last previous one minute | | | | | | | |
| Prepared by: A. Hamid & Azhor Inspected by: Farhat M. Shah | | | | | | | |

Water Pressure Test


Hole No.: M98-4 Stage: 8/14
 Location: Dam Axis (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 60 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^{-4} \times Q^{1.75}$ Date: 14/January/1999

| Ground elevation: EL. m | | Groundwater level (L _g): GL. 13.70 m | | Gauge height (L _g): 0.70 m | | | |
|---|----------------|--|----------------|---|----------------|----------------|----------------|
| Pipe length from pressure gauge to hole mouth: (L _p) = 4.50 m | | Depth of test section: GL. - (L _g) = 35 m to (L _g) = 5 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 18:10 | 18:12 | 18:24 | 18:36 | 18:48 | 19:00 | 19:12 |
| Q (m ³ /min) | 31.298 | 31.331 | 31.367 | 31.410 | 31.455 | 31.460 | 31.467 |
| 1 | 31.300 | 31.334 | 31.371 | 31.415 | 31.456 | 31.461 | 31.468 |
| 2 | 31.302 | 31.337 | 31.374 | 31.420 | 31.457 | 31.463 | 31.469 |
| 3 | 31.305 | 31.339 | 31.377 | 31.425 | 31.459 | 31.465 | 31.470 |
| 4 | 31.307 | 31.342 | 31.381 | 31.427 | 31.461 | 31.466 | 31.471 |
| 5 | 31.309 | 31.345 | 31.384 | 31.432 | 31.461 | 31.466 | 31.472 |
| 6 | 31.312 | 31.348 | 31.388 | 31.436 | 31.462 | 31.467 | 31.472 |
| 7 | 31.314 | 31.350 | 31.391 | 31.441 | 31.463 | 31.468 | 31.473 |
| 8 | 31.316 | 31.353 | 31.394 | 31.446 | 31.465 | 31.470 | 31.474 |
| 9 | 31.319 | 31.356 | 31.397 | 31.449 | 31.466 | 31.471 | 31.475 |
| 10 | 31.321 | 31.358 | 31.400 | 31.454 | 31.467 | 31.472 | 31.476 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 23 | 27 | 33 | 44 | 12 | 12 | 9 |
| Average lit./min | 2.3 | 2.7 | 3.3 | 4.4 | 1.2 | 1.2 | 0.9 |
| Friction loss (Pr) | 0.00 | 0.00 | 0.00 | 0.01 | 0.00 | 0.00 | 0.00 |
| Friction Loss (Pr) = p(L _p + L _s) [kgf/cm ²] | | | | | | | |
| Calculation of Lugeon value | | | | | | | |
| $P_1 = P_2 + 0.1 \sin(\alpha) (L_p + L_s) \cdot Pr$ [kgf/cm ²]; $q = Q/L_s$ [lit/min/m] | | | | | | | |
| $P_1 = 2.3$ $q_1 = 0.5$ $P_2 = 5.3$ $q_2 = 0.5$ $P_3 = 8.3$ $q_3 = 0.7$ $P_4 = 11.2$ $q_4 = 0.9$ $P_5 = 8.3$ $q_5 = 0.2$ $P_6 = 5.3$ $q_6 = 0.2$ $P_7 = 2.3$ $q_7 = 0.2$ | | | | | | | |
| | | | | | | | |
| Lugeon value: 0.8 Lu kgf/cm ² Critical Pressure: >11 | | | | | | | |
| Remarks: Reverse reading for few seconds by decreasing to 4 & 1 kgf/cm2 | | | | | | | |
| COS60=0.868 | | | | | | | |
| Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the last previous one minute | | | | | | | |
| Prepared by: A. Hamid & Azhor Inspected by: Farhat M. Shah | | | | | | | |

Water Pressure Test

Hole No.: M98-4 Stage: 9/14
 Location: Dam Axis (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 60 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^{-4} \times Q^{1.75}$ Date: 15/January/1999

| Ground elevation: EL | | Groundwater level (L _g): GL = 13.50 m | | Gauge height (L _g): 0.70 m | | | |
|--|-----------------|--|-----------------|---|-----------------|-----------------|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _g) = 4.50 m | | Depth of test section: GL - (L _g) = 45 m | | Length of section (L _g) = 5 m | | | |
| Calculation of Lugeon value | | | | | | | |
| Gauge P. (kg/cm ²) | P _{o1} | P _{o2} | P _{o3} | P _{o4} | P _{o5} | P _{o6} | P _{o7} |
| Start time | 07:00 | 07:12 | 07:24 | 07:36 | 07:48 | 08:00 | 08:12 |
| U (mm) | 41,489 | 41,512 | 41,547 | 41,590 | 41,634 | 41,640 | 41,647 |
| 1 | 41,491 | 41,515 | 41,551 | 41,595 | 41,636 | 41,641 | 41,648 |
| 2 | 41,493 | 41,518 | 41,555 | 41,599 | 41,638 | 41,642 | 41,649 |
| 3 | 41,495 | 41,520 | 41,559 | 41,603 | 41,643 | 41,645 | 41,650 |
| 4 | 41,496 | 41,522 | 41,562 | 41,608 | 41,640 | 41,645 | 41,651 |
| 5 | 41,498 | 41,525 | 41,565 | 41,612 | 41,641 | 41,646 | 41,652 |
| 6 | 41,499 | 41,528 | 41,568 | 41,615 | 41,642 | 41,648 | 41,653 |
| 7 | 41,500 | 41,531 | 41,571 | 41,619 | 41,643 | 41,649 | 41,653 |
| 8 | 41,502 | 41,534 | 41,575 | 41,623 | 41,645 | 41,650 | 41,654 |
| 9 | 41,504 | 41,537 | 41,578 | 41,627 | 41,646 | 41,651 | 41,654 |
| 10 | 41,506 | 41,540 | 41,582 | 41,632 | 41,647 | 41,652 | 41,655 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 17 | 28 | 35 | 42 | 23 | 12 | 8 |
| Average lit./min | 1.7 | 2.8 | 3.5 | 4.2 | 2.3 | 1.2 | 0.8 |
| March time | 07:10 | 07:22 | 07:34 | 07:46 | 07:58 | 08:10 | 08:22 |
| Friction Loss (Pr) = p(L _g + L _g) (kg/cm ²) | 0.00 | 0.00 | 0.01 | 0.01 | 0.00 | 0.00 | 0.00 |
| Friction Loss (Pr) = p(L _g + L _g) (kg/cm ²) | | | | | | | |




Remarks: From 7kgf to 4kgf and from 4kgf to 1kgf for few second reversed run
 COS60=0.868
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the just previous one minute
 Prepared by: A. Hamid & Azhor Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-4 Stage: 10/14
 Location: Dam Axis (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 60 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^{-4} \times Q^{1.75}$ Date: 15/January/1999

| Ground elevation: EL | | Groundwater level (L _g): GL = 13.80 m | | Gauge height (L _g): 0.70 m | | | |
|--|-----------------|--|-----------------|---|-----------------|-----------------|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _g) = 4.50 m | | Depth of test section: GL - (L _g) = 50 m | | Length of section (L _g) = 5 m | | | |
| Calculation of Lugeon value | | | | | | | |
| Gauge P. (kg/cm ²) | P _{o1} | P _{o2} | P _{o3} | P _{o4} | P _{o5} | P _{o6} | P _{o7} |
| Start time | 17:00 | 17:12 | 17:24 | 17:36 | 17:48 | 18:00 | 18:12 |
| U (mm) | 49,618 | 49,642 | 49,691 | 49,760 | 49,850 | 49,915 | 49,951 |
| 1 | 49,628 | 49,647 | 49,698 | 49,769 | 49,855 | 49,918 | 49,953 |
| 2 | 49,622 | 49,652 | 49,705 | 49,778 | 49,861 | 49,921 | 49,955 |
| 3 | 49,624 | 49,656 | 49,711 | 49,787 | 49,867 | 49,924 | 49,958 |
| 4 | 49,627 | 49,660 | 49,718 | 49,795 | 49,873 | 49,928 | 49,960 |
| 5 | 49,629 | 49,663 | 49,725 | 49,804 | 49,880 | 49,931 | 49,962 |
| 6 | 49,631 | 49,667 | 49,731 | 49,812 | 49,886 | 49,934 | 49,964 |
| 7 | 49,633 | 49,671 | 49,737 | 49,821 | 49,893 | 49,937 | 49,967 |
| 8 | 49,635 | 49,676 | 49,746 | 49,829 | 49,900 | 49,941 | 49,969 |
| 9 | 49,638 | 49,680 | 49,750 | 49,838 | 49,906 | 49,944 | 49,971 |
| 10 | 49,640 | 49,684 | 49,757 | 49,846 | 49,911 | 49,948 | 49,973 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 22 | 42 | 66 | 86 | 61 | 33 | 22 |
| Average lit./min | 2.2 | 4.2 | 6.6 | 8.6 | 6.1 | 3.3 | 2.2 |
| March time | 17:10 | 17:22 | 17:34 | 17:46 | 17:58 | 18:10 | 18:22 |
| Friction Loss (Pr) = p(L _g + L _g) (kg/cm ²) | 0.00 | 0.01 | 0.02 | 0.03 | 0.02 | 0.01 | 0.00 |
| Friction Loss (Pr) = p(L _g + L _g) (kg/cm ²) | | | | | | | |




Remarks: COS60=0.868
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the just previous one minute
 Prepared by: A. Hamid & Azhor Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-4 Stage: 11/14
 Location: Dam Axis (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 60 degrees Packer Type: Mechanical
 Friction Loss per meter (p) : $1 \times 10^{-4} \times Q^{1.75}$ Date: 16/January/1999

| Ground elevation: EL | | Groundwater level (L _g): G.L. = 13.40 m | | Gauge height (L _g): 0.70 m | | | |
|---|------------------|--|------------------|--|------------------|------------------|------------------|
| Pipe length from pressure gauge to hole mouth: (L _p) = 4.50 m | | Depth of test section: 55 m to (L _s) = 5 m | | Length of section (L _s): 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 17:00 | 17:12 | 17:24 | 17:36 | 17:48 | 18:00 | 18:12 |
| Q (mm) | 54.282 | 54.300 | 54.354 | 54.452 | 54.550 | 54.601 | 54.625 |
| 1 | 54.282 | 54.306 | 54.362 | 54.462 | 54.555 | 54.603 | 54.625 |
| 2 | 54.282 | 54.310 | 54.370 | 54.472 | 54.561 | 54.606 | 54.625 |
| 3 | 54.282 | 54.314 | 54.377 | 54.481 | 54.567 | 54.609 | 54.626 |
| 4 | 54.283 | 54.317 | 54.384 | 54.490 | 54.573 | 54.613 | 54.626 |
| 5 | 54.283 | 54.321 | 54.392 | 54.499 | 54.579 | 54.615 | 54.626 |
| 6 | 54.283 | 54.325 | 54.400 | 54.508 | 54.584 | 54.618 | 54.627 |
| 7 | 54.283 | 54.328 | 54.408 | 54.518 | 54.589 | 54.620 | 54.627 |
| 8 | 54.283 | 54.332 | 54.415 | 54.528 | 54.595 | 54.622 | 54.627 |
| 9 | 54.283 | 54.336 | 54.422 | 54.537 | 54.601 | 54.625 | 54.628 |
| 10 | 54.284 | 54.340 | 54.430 | 54.546 | 54.607 | 54.628 | 54.628 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ |
| lit. | 2 | 40 | 76 | 94 | 57 | 27 | 3 |
| Average | Q _{av1} | Q _{av2} | Q _{av3} | Q _{av4} | Q _{av5} | Q _{av6} | Q _{av7} |
| lit/min | 0.2 | 4.0 | 7.6 | 9.4 | 5.7 | 2.7 | 0.3 |
| lit/min | 17:10 | 17:22 | 17:34 | 17:46 | 17:58 | 18:10 | 18:22 |
| Friction Loss (P _p) = p(L _s + L _p) [kg/cm ²] | 0.00 | 0.01 | 0.03 | 0.05 | 0.02 | 0.01 | 0.00 |



Calculation of Lupegnon value
 $P = P_0 + 0.1(\sin \theta) L_p + P_p$
 $q = Q/L_s$ [lit/min/m]
 $q_1 = 0.0$
 $q_2 = 0.8$
 $q_3 = 1.5$
 $q_4 = 1.9$
 $q_5 = 1.1$
 $q_6 = 0.5$
 $q_7 = 0.1$

Lupegnon value: 2.0 Lu
 Critical Pressure: >11 kg/cm²

Remarks: Reverse reading for few seconds by decreasing to 4 & 1 kg/cm²
 COS60=0.868


Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the last previous one minute

Prepared by: A. Hamid & Azhor Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-4 Stage: 12/14
 Location: Dam Axis (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 60 degrees Packer Type: Mechanical
 Friction Loss per meter (p) : $1 \times 10^{-4} \times Q^{1.75}$ Date: 16/January/1999

| Ground elevation: EL | | Groundwater level (L _g): G.L. = 13.40 m | | Gauge height (L _g): 0.70 m | | | |
|---|------------------|---|------------------|--|------------------|------------------|------------------|
| Pipe length from pressure gauge to hole mouth: (L _p) = 4.50 m | | Depth of test section: 55 m to (L _s) = 60 m | | Length of section (L _s): 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 16:00 | 16:12 | 16:24 | 16:36 | 16:48 | 17:00 | 17:12 |
| Q (mm) | 60.028 | 60.068 | 60.118 | 60.202 | 60.273 | 60.329 | 60.362 |
| 1 | 60.031 | 60.071 | 60.125 | 60.209 | 60.278 | 60.333 | 60.369 |
| 2 | 60.034 | 60.074 | 60.127 | 60.216 | 60.283 | 60.337 | 60.366 |
| 3 | 60.037 | 60.078 | 60.139 | 60.222 | 60.289 | 60.340 | 60.368 |
| 4 | 60.040 | 60.081 | 60.146 | 60.224 | 60.293 | 60.343 | 60.370 |
| 5 | 60.043 | 60.084 | 60.153 | 60.235 | 60.299 | 60.346 | 60.372 |
| 6 | 60.045 | 60.088 | 60.159 | 60.242 | 60.304 | 60.349 | 60.375 |
| 7 | 60.048 | 60.091 | 60.166 | 60.249 | 60.310 | 60.352 | 60.377 |
| 8 | 60.050 | 60.094 | 60.172 | 60.255 | 60.315 | 60.355 | 60.379 |
| 9 | 60.053 | 60.097 | 60.178 | 60.262 | 60.320 | 60.358 | 60.382 |
| 10 | 60.055 | 60.101 | 60.184 | 60.269 | 60.326 | 60.361 | 60.384 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ |
| lit. | 27 | 33 | 66 | 67 | 53 | 32 | 22 |
| Average | Q _{av1} | Q _{av2} | Q _{av3} | Q _{av4} | Q _{av5} | Q _{av6} | Q _{av7} |
| lit/min | 2.7 | 3.3 | 6.6 | 6.7 | 5.3 | 3.2 | 2.2 |
| lit/min | 16:10 | 16:22 | 16:34 | 16:46 | 16:58 | 17:10 | 17:22 |
| Friction Loss (P _p) = p(L _s + L _p) [kg/cm ²] | 0.00 | 0.01 | 0.02 | 0.03 | 0.02 | 0.01 | 0.00 |



Calculation of Lupegnon value
 $P = P_0 + 0.1(\sin \theta) L_p + P_p$
 $q = Q/L_s$ [lit/min/m]
 $q_1 = 0.5$
 $q_2 = 0.7$
 $q_3 = 1.3$
 $q_4 = 1.5$
 $q_5 = 1.1$
 $q_6 = 0.6$
 $q_7 = 0.4$

Lupegnon value: 1.2 Lu
 Critical Pressure: >11 kg/cm²

Remarks: COS60=0.868


Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90% to 110% of the injection rate in the last previous one minute

Prepared by: A. Hamid & Azhor Inspected by: Farhat M. Shah

Water Pressure Test

Hole No.: M98-4 Stage: 13/14
 Location: Dam Axis (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 60 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^{-4} \times Q^{1.711}$ Date: 17/January/1999

| Ground elevation : EL | | m | | Groundwater level (L _g): GL- 13.50 m | | Gauge height (L _g): 0.70 m | |
|---|----------------|---|----------------|--|----------------|--|----------------|
| Pipe length from pressure gauge to hole mouth: (L _g)= 4.50 m | | GL - (L _g)= 60 m to (L _g)= 65 m | | Depth of test section | | Length of section (L _g)= 5 m | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| 1 | 16.307 | 16.42 | 16.55 | 17.07 | 17.20 | 17.32 | 17.45 |
| Start time | 08:00 | 08:12 | 08:24 | 08:36 | 08:48 | 09:00 | 09:12 |
| Q (m ³ /min) | 65.869 | 65.942 | 65.953 | 66.018 | 66.135 | 66.187 | 66.200 |
| 1 | 65.870 | 65.905 | 65.959 | 66.029 | 66.140 | 66.188 | 66.201 |
| 2 | 65.872 | 65.908 | 65.964 | 66.040 | 66.145 | 66.190 | 66.203 |
| 3 | 65.873 | 65.911 | 65.968 | 66.050 | 66.151 | 66.192 | 66.204 |
| 4 | 65.875 | 65.914 | 65.973 | 66.060 | 66.156 | 66.194 | 66.205 |
| 5 | 65.876 | 65.916 | 65.978 | 66.071 | 66.161 | 66.196 | 66.206 |
| 6 | 65.877 | 65.919 | 65.984 | 66.082 | 66.167 | 66.197 | 66.207 |
| 7 | 65.878 | 65.922 | 65.988 | 66.093 | 66.172 | 66.199 | 66.209 |
| 8 | 65.879 | 65.924 | 65.993 | 66.103 | 66.178 | 66.201 | 66.210 |
| 9 | 65.880 | 65.927 | 65.998 | 66.114 | 66.183 | 66.202 | 66.211 |
| 10 | 65.881 | 65.933 | 66.004 | 66.124 | 66.188 | 66.204 | 66.212 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 12 | 31 | 51 | 106 | 53 | 17 | 12 |
| Average lit./min | 0.7 | 1.7 | 4.0 | 9.0 | 5.0 | 1.8 | 0.7 |
| Final time | 08:10 | 08:22 | 08:34 | 08:46 | 08:58 | 09:10 | 09:22 |
| (P) | 0.00 | 0.01 | 0.02 | 0.07 | 0.02 | 0.00 | 0.00 |
| Friction Loss (P) = p(L _g + L _g) [kg/cm ²] | | | | | | | |
| Lu _g value : (1.7) | | | | | | | |
| Critical Pressure: 8.2 | | | | | | | |




COS60=0.868

Remarks :
 Note : Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute
 Prepared by : A. Hamid & Azhar Inspected by : Azim Gill

Water Pressure Test

Hole No.: M98-4 Stage: 14/14
 Location: Dam Axis (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 60 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^{-4} \times Q^{1.711}$ Date: 17/January/1999

| Ground elevation : EL | | m | | Groundwater level (L _g): GL- 12.70 m | | Gauge height (L _g): 0.70 m | |
|---|----------------|---|----------------|--|----------------|--|----------------|
| Pipe length from pressure gauge to hole mouth: (L _g)= 4.50 m | | GL - (L _g)= 65 m to (L _g)= 70 m | | Depth of test section | | Length of section (L _g)= 5 m | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| 1 | 16.307 | 16.42 | 16.55 | 17.07 | 17.20 | 17.32 | 17.45 |
| Start time | 08:00 | 08:12 | 08:24 | 08:36 | 08:48 | 09:00 | 09:12 |
| Q (m ³ /min) | 74.107 | 74.116 | 74.135 | 74.178 | 74.270 | 74.323 | 74.343 |
| 1 | 74.108 | 74.118 | 74.139 | 74.186 | 74.275 | 74.325 | 74.344 |
| 2 | 74.108 | 74.120 | 74.144 | 74.195 | 74.280 | 74.327 | 74.344 |
| 3 | 74.109 | 74.121 | 74.148 | 74.205 | 74.284 | 74.329 | 74.345 |
| 4 | 74.110 | 74.123 | 74.151 | 74.214 | 74.289 | 74.330 | 74.346 |
| 5 | 74.111 | 74.125 | 74.155 | 74.222 | 74.295 | 74.332 | 74.356 |
| 6 | 74.111 | 74.126 | 74.160 | 74.231 | 74.300 | 74.334 | 74.347 |
| 7 | 74.112 | 74.128 | 74.164 | 74.241 | 74.304 | 74.336 | 74.348 |
| 8 | 74.113 | 74.129 | 74.168 | 74.250 | 74.310 | 74.337 | 74.349 |
| 9 | 74.113 | 74.131 | 74.171 | 74.260 | 74.315 | 74.339 | 74.349 |
| 10 | 74.114 | 74.133 | 74.175 | 74.268 | 74.320 | 74.341 | 74.350 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 7 | 17 | 40 | 90 | 50 | 18 | 7 |
| Average lit./min | 0.7 | 1.7 | 4.0 | 9.0 | 5.0 | 1.8 | 0.7 |
| Final time | 08:40 | 08:52 | 09:05 | 09:17 | 09:30 | 09:42 | 09:55 |
| (P) | 0.00 | 0.00 | 0.01 | 0.05 | 0.02 | 0.00 | 0.00 |
| Friction Loss (P) = p(L _g + L _g) [kg/cm ²] | | | | | | | |
| Lu _g value : (0.7) | | | | | | | |
| Critical Pressure: 7.2 | | | | | | | |



COS60=0.868

Remarks :
 Note : Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute
 Prepared by : A. Hamid & Azhar Inspected by : Azim Gill

Permeability Test (Open End Constant Head Method)

Hole No.: M98-5 Stage: 1/5
 Location: Dam axis (river) Dia. of Hole (2r): 430 mm
 Bottom of Hole (GL- h1): 1.50 m Bottom of Casing: 1.50 m
 Groundwater Level (GL- h2): 0.00 m Constant Head Level (GL + h3): 4.47 m

Test Record

Start Time: (16:30) Date: 23 /February/1999

| Time Elapsed (min.) | Reading of Flow Meter | | Calculation |
|---------------------|-----------------------------------|-----------------------------------|--|
| | Reading (liter) | Volume of Flow (cm ³) | |
| 0 | 4,524.0 | 0 | Calculation Formula $k = \frac{q}{5.5rH}$ k : Coefficient of Permeability (cm/sec) r : Radius of Hole (cm) H: Water Head (cm); when groundwater is Nil H=h1+h3 when water found in the hole H=h2+h3 q : Constant Injection Rate into Hole (cm ³ /sec) |
| 1 | 4,525.2 | 1,200 | |
| 2 | 4,525.9 | 700 | |
| 3 | 4,525.9 | 0 | |
| 4 | 4,526.0 | 100 | |
| 5 | 4,526.5 | 500 | |
| 6 | 4,526.5 | 0 | |
| 7 | 4,526.9 | 400 | |
| 8 | 4,527.5 | 600 | |
| 9 | 4,527.8 | 300 | |
| 10 | 4,528.0 | 200 | |
| 11 | 4,528.6 | 600 | |
| 12 | 4,528.9 | 300 | |
| 13 | 4,529.5 | 600 | |
| 14 | 4,529.9 | 400 | |
| 15 | 4,530.3 | 400 | |
| 16 | 4,530.8 | 500 | |
| 17 | 4,531.1 | 300 | |
| 18 | 4,531.5 | 400 | |
| 19 | 4,531.8 | 300 | |
| 20 | 4,532.1 | 300 | |
| Total | Q = 8,100 cm³ | | Permeability (k) = |
| Average | q = 405 cm³/min | | 9.56E-05 cm/sec |
| | | = 7 cm³/sec | |

Finish Time: (16:50)

Tested by: A. Hameed
 Prepared by: A. Hameed
 Inspected by: K. Yano

Permeability Test (Open End Constant Head Method)

Hole No.: M98-5 Stage: 2/5
 Location: Dam axis (river) Dia. of Hole (2r): 430 mm
 Bottom of Hole (GL- h1): 2.50 m Bottom of Casing: 2.50 m
 Groundwater Level (GL- h2): 0.00 m Constant Head Level (GL + h3): 4.47 m

Test Record

Start Time: (18:10) Date: 23 /February/1999

| Time Elapsed (min.) | Reading of Flow Meter | | Calculation |
|---------------------|-----------------------------------|-----------------------------------|--|
| | Reading (liter) | Volume of Flow (cm ³) | |
| 0 | 3,096.6 | 0 | Calculation Formula $k = \frac{q}{5.5rH}$ k : Coefficient of Permeability (cm/sec) r : Radius of Hole (cm) H: Water Head (cm); when groundwater is Nil H=h1+h3 when water found in the hole H=h2+h3 q : Constant Injection Rate into Hole (cm ³ /sec) |
| 1 | 3,096.8 | 200 | |
| 2 | 3,097.0 | 200 | |
| 3 | 3,097.3 | 300 | |
| 4 | 3,097.5 | 200 | |
| 5 | 3,097.8 | 300 | |
| 6 | 3,098.1 | 300 | |
| 7 | 3,098.3 | 200 | |
| 8 | 3,098.5 | 200 | |
| 9 | 3,098.9 | 400 | |
| 10 | 3,099.1 | 200 | |
| 11 | 3,099.4 | 300 | |
| 12 | 3,099.7 | 300 | |
| 13 | 3,100.0 | 300 | |
| 14 | 3,100.3 | 300 | |
| 15 | 3,100.7 | 400 | |
| 16 | 3,101.0 | 300 | |
| 17 | 3,101.2 | 200 | |
| 18 | 3,101.4 | 200 | |
| 19 | 3,101.7 | 300 | |
| 20 | 3,101.9 | 200 | |
| Total | Q = 5,300 cm³ | | Permeability (k) = |
| Average | q = 265 cm³/min | | 5.36E-05 cm/sec |
| | | = 4 cm³/sec | |

Finish Time: (18:30)

Tested by: A. Hameed
 Prepared by: A. Hameed
 Inspected by: K. Yano

Permeability Test (Open End Constant Head Method)

Hole No.: M98-5 Stage: 3/5
 Location: Dam axis (river) Dia. of Hole (2r): 490 mm
 Bottom of Hole (GL- h1): 3.50 m Bottom of Casing: 3.50 m
 Groundwater Level (GL- h2): 0.00 m Constant Head Level (GL + h3): 5.61 m

Test Record

| Start Time: (9:10) | | Date: 24 /February/1999 | |
|----------------------|--------------------------------|-----------------------------------|---|
| Time Elapsed (min.) | Reading of Flow Meter | | Calculation |
| | Reading (liter) | Volume of Flow (cm ³) | |
| 0 | 3,970.0 | 0 | Calculation Formula $k = \frac{q}{5.5rH}$ k : Coefficient of Permeability (cm/sec) r : Radius of Hole (cm) H: Water Head (cm) : when groundwater is Nill H=h1+h3 when water found in the hole H=h2+h3 q : Constant Injection Rate into Hole (cm ³ /sec) |
| 1 | 3,975.4 | 5,400 | |
| 2 | 3,980.0 | 4,600 | |
| 3 | 3,984.2 | 4,200 | |
| 4 | 3,988.3 | 4,100 | |
| 5 | 3,990.5 | 2,200 | |
| 6 | 3,992.7 | 2,200 | |
| 7 | 3,995.4 | 2,700 | |
| 8 | 3,995.7 | 300 | |
| 9 | 3,998.2 | 2,500 | |
| 10 | 4,000.7 | 2,500 | |
| 11 | 4,004.9 | 4,200 | |
| 12 | 4,007.2 | 2,300 | |
| 13 | 4,010.9 | 3,700 | |
| 14 | 4,013.2 | 2,300 | |
| 15 | 4,014.4 | 1,200 | |
| 16 | 4,017.2 | 2,800 | |
| 17 | 4,020.7 | 3,500 | |
| 18 | 4,024.2 | 3,500 | |
| 19 | 4,026.9 | 2,700 | |
| 20 | 4,029.3 | 2,400 | |
| Total | Q = 59,300 cm ³ | | Permeability (k) = |
| Average | q = 2,965 cm ³ /min | | 4.59E-04 cm/sec |
| | | = 49 cm ³ /sec | |

Finish Time: (9:30)

Tested by: A. Hameed
 Prepared by: A. Hameed
 Inspected by: K. Yano

Permeability Test (Open End Constant Head Method)

Hole No.: M98-5 Stage: 4/5
 Location: Dam axis (river) Dia. of Hole (2r): 430 mm
 Bottom of Hole (GL- h1): 4.50 m Bottom of Casing: 4.50 m
 Groundwater Level (GL- h2): 0.00 m Constant Head Level (GL + h3): 4.53 m

Test Record

| Start Time: (11:00) | | Date: 24 /February/1999 | |
|-----------------------|---------------------------------|-----------------------------------|---|
| Time Elapsed (min.) | Reading of Flow Meter | | Calculation |
| | Reading (liter) | Volume of Flow (cm ³) | |
| 0 | 7,037.0 | 0 | Calculation Formula $k = \frac{q}{5.5rH}$ k : Coefficient of Permeability (cm/sec) r : Radius of Hole (cm) H: Water Head (cm) : when groundwater is Nill H=h1+h3 when water found in the hole H=h2+h3 q : Constant Injection Rate into Hole (cm ³ /sec) |
| 1 | 7,054.6 | 17,600 | |
| 2 | 7,072.7 | 18,100 | |
| 3 | 7,090.6 | 17,900 | |
| 4 | 7,108.7 | 18,100 | |
| 5 | 7,126.2 | 17,500 | |
| 6 | 7,144.0 | 17,800 | |
| 7 | 7,162.0 | 18,000 | |
| 8 | 7,180.0 | 18,000 | |
| 9 | 7,197.7 | 17,700 | |
| 10 | 7,215.4 | 17,700 | |
| 11 | 7,233.5 | 18,100 | |
| 12 | 7,250.9 | 17,400 | |
| 13 | 7,256.3 | 5,400 | |
| 14 | 7,271.5 | 15,200 | |
| 15 | 7,294.2 | 22,700 | |
| 16 | 7,309.3 | 15,100 | |
| 17 | 7,324.5 | 15,200 | |
| 18 | 7,340.0 | 15,500 | |
| 19 | 7,354.7 | 14,700 | |
| 20 | 7,370.5 | 15,800 | |
| Total | Q = 333,500 cm ³ | | Permeability (k) = |
| Average | q = 16,675 cm ³ /min | | 2.60E-03 cm/sec |
| | | = 278 cm ³ /sec | |

Finish Time: (11:20)

Tested by: A. Hameed
 Prepared by: A. Hameed
 Inspected by: K. Yano

Permeability Test (Open End Constant Head Method)

Hole No.: M98-S Stage: S/S
 Location: Dam axis (river) Dia. of Hole (2r): 430 mm
 Bottom of Hole (GL- h1): 7.50 m Bottom of Casing: 7.50 m
 Groundwater Level (GL- h2): 0.00 m Constant Head Level (GL + h3): 4.63 m

Test Record

| Start Time: (11:30) | | Date: 25/February/1999 | |
|---------------------|-----------------|---|------------------------------------|
| Time Elapsed (min.) | Reading (liter) | Volume of Flow (cm ³) | Calculation |
| 0 | 5,231.0 | 0 | |
| 1 | 5,233.0 | 2,000 | |
| 2 | 5,235.0 | 2,000 | |
| 3 | 5,238.0 | 3,000 | |
| 4 | 5,240.0 | 2,000 | |
| 5 | 5,242.0 | 2,000 | |
| 6 | 5,245.0 | 3,000 | |
| 7 | 5,247.0 | 2,000 | |
| 8 | 5,250.0 | 3,000 | |
| 9 | 5,252.0 | 2,000 | |
| 10 | 5,253.0 | 1,000 | |
| 11 | 5,255.0 | 2,000 | |
| 12 | 5,257.0 | 2,000 | |
| 13 | 5,260.0 | 3,000 | |
| 14 | 5,262.0 | 2,000 | |
| 15 | 5,265.0 | 3,000 | |
| 16 | 5,267.0 | 2,000 | |
| 17 | 5,269.0 | 2,000 | |
| 18 | 5,272.0 | 3,000 | |
| 19 | 5,274.0 | 2,000 | |
| 20 | 5,276.0 | 2,000 | |
| Total | | Q = 45,000 cm ³ | |
| Average | | q = 2,250 cm ³ /min = 38 cm ³ /sec | Permeability (k) = 2.61E-04 cm/sec |

Finish Time: (11:50)

Tested by: A. Hameed
 Prepared by: A. Hameed
 Inspected by: K. Yano

Water Pressure Test

Hole No.: M98-S Stage: 1/4
 Location: Dam axis (River) Dia. of Hole: 76 mm
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (P_f): 1x10⁻⁴ x Q^{1.75} Date: 25/February/1999

| Ground elevation: EL. m | | Groundwater level (L _g): GL- 0.00 m | | Gauge height (L _g): 0.82 m | | | |
|---|-----------------|---|-----------------|--|-----------------|-----------------|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _g) = 4.60 m | | Depth of test section: 10 m to (L _g) = 15 m | | Length of section (L _g): 5 m | | | |
| Calculation of Lugeon value | | | | | | | |
| Group P _i (kg/cm ²) | P _{i1} | P _{i2} | P _{i3} | P _{i4} | P _{i5} | P _{i6} | P _{i7} |
| 1 | 10.00 | 10.12 | 10.25 | 10.36 | 10.44 | 11.00 | 11.12 |
| 2 | 86.004 | 86.038 | 86.076 | 86.123 | 86.160 | 86.184 | 86.197 |
| 3 | 86.008 | 86.044 | 86.082 | 86.129 | 86.164 | 86.186 | 86.197 |
| 4 | 86.010 | 86.047 | 86.085 | 86.133 | 86.166 | 86.188 | 86.197 |
| 5 | 86.012 | 86.049 | 86.089 | 86.136 | 86.168 | 86.189 | 86.197 |
| 6 | 86.014 | 86.052 | 86.092 | 86.140 | 86.170 | 86.190 | 86.198 |
| 7 | 86.016 | 86.055 | 86.095 | 86.144 | 86.172 | 86.192 | 86.198 |
| 8 | 86.018 | 86.057 | 86.099 | 86.147 | 86.174 | 86.193 | 86.198 |
| 9 | 86.023 | 86.059 | 86.102 | 86.150 | 86.176 | 86.194 | 86.198 |
| 10 | 86.026 | 86.062 | 86.105 | 86.154 | 86.178 | 86.196 | 86.198 |
| 11 | 86.026 | 86.065 | 86.108 | 86.157 | 86.180 | 86.197 | 86.199 |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | Q=1 | Q=2 | Q=3 | Q=4 | Q=5 | Q=6 | Q=7 |
| Average lit/min | 2.2 | 2.7 | 3.2 | 3.4 | 2.0 | 1.3 | 0.2 |
| Friction loss (P _f) | 0.00 | 0.01 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |

Water Pressure in kg/cm² vs Water Injection Ratio (q : lit./min/m)


Lu = 0.7 kg/cm²
 Critical Pressure: >10 kg/cm²

Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.
 Prepared by: Fahad M. Shah Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-5 Stage: 2/4
 Location: Dam axis (River) Dia. of Hole: 76 mm
 Hole Inclination (α): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁻⁴ x Q^{1.75} Date: 26/February/1999

| Ground elevation: EL | | Groundwater level (L _g): GL = 0.00 m | | Gauge height (L _g): 0.82 m | | | |
|---|----------------|---|----------------|---|----------------|----------------|----------------|
| Pipe length from pressure gauge to hole mouth: (L _p) = 4.60 m | | Depth of test section GL - (L _p) = 20 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 11:50 | 11:22 | 11:34 | 11:50 | 12:12 | 12:30 | 12:42 |
| Q (min) | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 |
| 1 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 |
| 2 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 |
| 3 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 |
| 4 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 |
| 5 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 |
| 6 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 |
| 7 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 |
| 8 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 |
| 9 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 |
| 10 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 | 297.002 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Average lit./min | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Friction loss (P _f) | 11:10 | 11:32 | 11:44 | 12:00 | 12:22 | 12:40 | 12:52 |
| Friction Loss (P _f) = p(L _w + L _s) [kg/cm ²] | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |




Water Injection Ratio (q : lit/min/m)
 Lugeon value : 0.0 Lu
 Critical Pressure: >10 kg/cm²

Remarks:
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.
 Prepared by: A. Hamid & Azhor Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-5 Stage: 3/4
 Location: Dam axis (River) Dia. of Hole: 76 mm
 Hole Inclination (α): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁻⁴ x Q^{1.75} Date: 26/February/1999

| Ground elevation: EL | | Groundwater level (L _g): GL = 0.00 m | | Gauge height (L _g): 0.82 m | | | |
|---|----------------|---|----------------|---|----------------|----------------|----------------|
| Pipe length from pressure gauge to hole mouth: (L _p) = 4.60 m | | Depth of test section GL - (L _p) = 20 m | | Length of section (L _s) = 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P. (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 18:00 | 18:12 | 18:24 | 18:36 | 18:48 | 19:00 | 19:13 |
| Q (min) | 301.123 | 301.124 | 301.124 | 301.125 | 301.125 | 301.126 | 301.127 |
| 1 | 301.123 | 301.124 | 301.124 | 301.125 | 301.125 | 301.126 | 301.127 |
| 2 | 301.123 | 301.124 | 301.124 | 301.125 | 301.125 | 301.126 | 301.127 |
| 3 | 301.123 | 301.124 | 301.124 | 301.125 | 301.125 | 301.126 | 301.127 |
| 4 | 301.123 | 301.124 | 301.124 | 301.125 | 301.125 | 301.126 | 301.127 |
| 5 | 301.123 | 301.124 | 301.124 | 301.125 | 301.125 | 301.126 | 301.127 |
| 6 | 301.123 | 301.124 | 301.124 | 301.125 | 301.125 | 301.126 | 301.127 |
| 7 | 301.123 | 301.124 | 301.124 | 301.125 | 301.125 | 301.126 | 301.127 |
| 8 | 301.123 | 301.124 | 301.124 | 301.125 | 301.125 | 301.126 | 301.127 |
| 9 | 301.123 | 301.124 | 301.124 | 301.125 | 301.125 | 301.126 | 301.127 |
| 10 | 301.123 | 301.124 | 301.124 | 301.125 | 301.125 | 301.126 | 301.127 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Average lit./min | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Friction loss (P _f) | 18:10 | 18:22 | 18:34 | 18:46 | 18:58 | 19:10 | 19:22 |
| Friction Loss (P _f) = p(L _w + L _s) [kg/cm ²] | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |




Water Injection Ratio (q : lit/min/m)
 Lugeon value : 0.0 Lu
 Critical Pressure: >10 kg/cm²

Remarks:
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.
 Prepared by: A. Hamid & Azhor Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-5 Stage: 4/4
 Location: Dam axis (River) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^{-4} \times Q^{1.911}$ Date: 27/February/1999


| Ground elevation: EL | | m | | Groundwater level (L _g): GL = 0.00 m | | Gauge height (L _g): 0.82 m | |
|---|-----------------|-----------------|-----------------|--|-----------------|---|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _h) = 4.60 m | | m | | GL = (L _g) = 30 m | | Length of section (L _s) = 5 m | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P _{o1} | P _{o2} | P _{o3} | P _{o4} | P _{o5} | P _{o6} | P _{o7} |
| Start time | 08:00 | 08:12 | 08:23 | 08:35 | 08:46 | 08:58 | 09:10 |
| Q (m ³ /min) | 64.072 | 64.077 | 64.080 | 64.083 | 64.082 | 64.081 | 64.079 |
| 1 | 64.072 | 64.077 | 64.080 | 64.083 | 64.082 | 64.081 | 64.079 |
| 2 | 64.072 | 64.077 | 64.080 | 64.083 | 64.082 | 64.081 | 64.079 |
| 3 | 64.072 | 64.077 | 64.080 | 64.083 | 64.082 | 64.081 | 64.079 |
| 4 | 64.072 | 64.077 | 64.080 | 64.083 | 64.082 | 64.081 | 64.079 |
| 5 | 64.072 | 64.077 | 64.080 | 64.083 | 64.082 | 64.081 | 64.079 |
| 6 | 64.072 | 64.077 | 64.080 | 64.083 | 64.082 | 64.081 | 64.079 |
| 7 | 64.072 | 64.077 | 64.080 | 64.083 | 64.082 | 64.081 | 64.079 |
| 8 | 64.072 | 64.077 | 64.080 | 64.083 | 64.082 | 64.081 | 64.079 |
| 9 | 64.072 | 64.077 | 64.080 | 64.083 | 64.082 | 64.081 | 64.079 |
| 10 | 64.072 | 64.077 | 64.080 | 64.083 | 64.082 | 64.081 | 64.079 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total | Q _{o1} | Q _{o2} | Q _{o3} | Q _{o4} | Q _{o5} | Q _{o6} | Q _{o7} |
| lit. | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Average | Q _{o1} | Q _{o2} | Q _{o3} | Q _{o4} | Q _{o5} | Q _{o6} | Q _{o7} |
| lit./min | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Friction loss | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| (Pa) | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| Friction Loss (P _r) = p(L _h + L _s) [kg/cm ²] | | | | | | | |
| Lugeon value: 0.0 Lu | | | | | | | |
| Critical Pressure: >10 kg/cm ² | | | | | | | |
| Remarks: | | | | | | | |
| Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 40 % to 110 % of the injection rate in the last previous one minute | | | | | | | |
| Prepared by: A. Hamid & Azhor | | | | | | | |
| Inspected by: M. Suga | | | | | | | |



Water Pressure Test

Hole No.: M98-6 Stage: 1/14
 Location: Upstream Cofferdam (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^{-4} \times Q^{1.911}$ Date: 30/January/1999


| Ground elevation: EL | | m | | Groundwater level (L _g): Nil | | Gauge height (L _g): 0.73 m | |
|---|-----------------|-----------------|-----------------|--|-----------------|---|-----------------|
| Pipe length from pressure gauge to hole mouth: (L _h) = 4.36 m | | m | | GL = (L _g) = 7 m | | Length of section (L _s) = 5 m | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P _{o1} | P _{o2} | P _{o3} | P _{o4} | P _{o5} | P _{o6} | P _{o7} |
| Start time | 10:10 | 10:12 | 10:25 | 10:30 | 10:45 | 11:00 | 11:12 |
| Q (m ³ /min) | 69.992 | 69.098 | 69.333 | 70.660 | 71.650 | 72.463 | 72.832 |
| 1 | 69.003 | 69.117 | 69.410 | 70.210 | 71.732 | 72.500 | 72.849 |
| 2 | 69.016 | 69.131 | 69.472 | 70.383 | 71.812 | 72.537 | 72.865 |
| 3 | 69.026 | 69.152 | 69.523 | 70.546 | 71.891 | 72.575 | 72.882 |
| 4 | 69.034 | 69.173 | 69.598 | 70.700 | 71.972 | 72.611 | 72.900 |
| 5 | 69.043 | 69.193 | 69.657 | 70.856 | 72.050 | 72.645 | 72.917 |
| 6 | 69.050 | 69.212 | 69.741 | 71.008 | 72.129 | 72.681 | 72.933 |
| 7 | 69.057 | 69.232 | 69.814 | 71.164 | 72.210 | 72.716 | 72.948 |
| 8 | 69.064 | 69.252 | 69.889 | 71.322 | 72.292 | 72.750 | 72.965 |
| 9 | 69.071 | 69.272 | 69.966 | 71.483 | 72.371 | 72.785 | 72.982 |
| 10 | 69.076 | 69.292 | 70.043 | 71.642 | 72.452 | 72.821 | 72.998 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total | Q _{o1} | Q _{o2} | Q _{o3} | Q _{o4} | Q _{o5} | Q _{o6} | Q _{o7} |
| lit. | 84 | 144 | 710 | 1,592 | 802 | 356 | 166 |
| Average | Q _{o1} | Q _{o2} | Q _{o3} | Q _{o4} | Q _{o5} | Q _{o6} | Q _{o7} |
| lit./min | 8.4 | 14.4 | 71 | 159.2 | 80.2 | 35.6 | 16.6 |
| Friction loss | 10.10 | 10.22 | 10.35 | 10.46 | 10.58 | 11.10 | 11.22 |
| (Pa) | 0.00 | 0.02 | 0.28 | 1.38 | 0.36 | 0.07 | 0.02 |
| Friction Loss (P _r) = p(L _h + L _s) [kg/cm ²] | | | | | | | |
| Lugeon value: (7.9) Lu | | | | | | | |
| Critical Pressure: 6.3 kg/cm ² | | | | | | | |
| Remarks: | | | | | | | |
| Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute | | | | | | | |
| Prepared by: Fatmat M. Shah | | | | | | | |
| Inspected by: M. Suga | | | | | | | |



Water Pressure Test

Hole No.: M98-6 Stages: 2/14
 Location: Upstream Cofferdam (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (α): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^{-4} \times Q^{1.71}$ Date: 31/January/1999

| Ground elevation: EL | | Groundwater level (L _g): | | Depth of test section | | Gauge height (L _g): | |
|---|----------------|--------------------------------------|----------------|---------------------------|----------------|--|----------------|
| Pipe length from pressure gauge to hole mouth: (L _g)= 4.40 m | | GL - (L _g)= 10 m | | to (L _g)= 5 m | | Length of section (L _s)= 5 m | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 11:00 | 11:22 | 11:34 | 11:50 | 12:12 | 12:30 | 12:42 |
| Q (m ³ /min) | 74.494 | 74.510 | 74.570 | 75.146 | 75.710 | 76.007 | 76.120 |
| 1 | 74.496 | 74.520 | 74.597 | 75.187 | 75.739 | 76.023 | 76.127 |
| 2 | 74.497 | 74.524 | 74.624 | 75.228 | 75.764 | 76.032 | 76.134 |
| 3 | 74.499 | 74.527 | 74.652 | 75.270 | 75.796 | 76.045 | 76.141 |
| 4 | 74.500 | 74.530 | 74.678 | 75.314 | 75.826 | 76.055 | 76.146 |
| 5 | 74.501 | 74.533 | 74.706 | 75.357 | 75.854 | 76.064 | 76.155 |
| 6 | 74.502 | 74.536 | 74.734 | 75.402 | 75.882 | 76.074 | 76.162 |
| 7 | 74.504 | 74.539 | 74.760 | 75.448 | 75.910 | 76.083 | 76.169 |
| 8 | 74.505 | 74.542 | 74.786 | 75.497 | 75.937 | 76.092 | 76.175 |
| 9 | 74.506 | 74.545 | 74.811 | 75.548 | 75.965 | 76.103 | 76.182 |
| 10 | 74.507 | 74.548 | 74.838 | 75.598 | 75.993 | 76.113 | 76.189 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ |
| lit. | 13 | 32 | 268 | 452 | 283 | 106 | 69 |
| Average | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ |
| lit./min | 1.3 | 3.2 | 26.8 | 45.2 | 28.3 | 10.6 | 6.9 |
| Remarks | 11:10 | 11:32 | 11:34 | 12:00 | 12:22 | 12:40 | 12:52 |
| (P ₁) | 0.00 | 0.00 | 0.06 | 0.17 | 0.07 | 0.01 | 0.00 |
| Friction Loss (P _f) = p(L _s + L _g) (kg/cm ²) | | | | | | | |
| Friction Loss (P _f) = p(L _s + L _g) (kg/cm ²) | | | | | | | |



Water Pressure in kg/cm²
 Water Injection Ratio (q: lit./min/m)

Lugeon value: (1.3) Lu'
 Critical Pressure: 4.8 kg/cm²

Remarks: * * * * *


Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute

Prepared by: A. Hamid & Azhor Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-6 Stages: 3/14
 Location: Upstream Cofferdam (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (α): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^{-4} \times Q^{1.71}$ Date: 31/January/1999

| Ground elevation: EL | | Groundwater level (L _g): | | Depth of test section | | Gauge height (L _g): | |
|---|----------------|--------------------------------------|----------------|----------------------------|----------------|--|----------------|
| Pipe length from pressure gauge to hole mouth: (L _g)= 4.43 m | | GL - (L _g)= 10 m | | to (L _g)= 15 m | | Length of section (L _s)= 5 m | |
| Reading of flow meter | | | | | | | |
| Gauge P. | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 18:00 | 18:12 | 18:24 | 18:36 | 18:48 | 19:00 | 19:13 |
| Q (m ³ /min) | 81.139 | 81.172 | 81.222 | 81.294 | 81.430 | 81.507 | 81.560 |
| 1 | 81.138 | 81.176 | 81.227 | 81.305 | 81.437 | 81.512 | 81.562 |
| 2 | 81.141 | 81.179 | 81.232 | 81.323 | 81.443 | 81.517 | 81.565 |
| 3 | 81.143 | 81.184 | 81.237 | 81.334 | 81.449 | 81.523 | 81.567 |
| 4 | 81.145 | 81.187 | 81.241 | 81.345 | 81.456 | 81.527 | 81.569 |
| 5 | 81.147 | 81.190 | 81.246 | 81.357 | 81.462 | 81.532 | 81.571 |
| 6 | 81.150 | 81.193 | 81.251 | 81.368 | 81.469 | 81.536 | 81.574 |
| 7 | 81.152 | 81.197 | 81.255 | 81.381 | 81.476 | 81.541 | 81.577 |
| 8 | 81.155 | 81.201 | 81.260 | 81.392 | 81.482 | 81.545 | 81.579 |
| 9 | 81.158 | 81.204 | 81.264 | 81.404 | 81.488 | 81.549 | 81.581 |
| 10 | 81.160 | 81.208 | 81.269 | 81.415 | 81.495 | 81.554 | 81.584 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ |
| lit. | 24 | 36 | 47 | 121 | 65 | 47 | 24 |
| Average | Q ₁ | Q ₂ | Q ₃ | Q ₄ | Q ₅ | Q ₆ | Q ₇ |
| lit./min | 2.4 | 3.6 | 4.7 | 12.1 | 6.5 | 4.7 | 2.4 |
| Remarks | 18:10 | 18:22 | 18:34 | 18:46 | 18:58 | 19:10 | 19:23 |
| (P ₁) | 0.00 | 0.00 | 0.00 | 0.02 | 0.01 | 0.00 | 0.00 |
| Friction Loss (P _f) = p(L _s + L _g) (kg/cm ²) | | | | | | | |
| Friction Loss (P _f) = p(L _s + L _g) (kg/cm ²) | | | | | | | |



Water Pressure in kg/cm²
 Water Injection Ratio (q: lit./min/m)

Lugeon value: (1.1) Lu'
 Critical Pressure: 8.3 kg/cm²

Remarks: * * * * *


Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute

Prepared by: A. Hamid & Azhor Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-6 Stages: 4/14
 Location: Upstream Colfer Dam (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (θ): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁴ x Q^{1.87} Date: 01/February/1999

| Ground elevation: EL. m | | Groundwater level (L _g): GL. 13.40 m | | Gauge height (L _g): 0.73 m | | | |
|---|----------------|---|----------------|--|----------------|----------------------|----------------|
| Pipe length from pressure gauge to hole mouth: (L _g) = 5.48 m | | Depth of test section: 15 m to (L _g) = 20 m | | Length of section (L _s): 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P _i (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 09:00 | 09:12 | 09:24 | 09:36 | 09:50 | 10:02 | 10:10 |
| Q (m ³ /min) | 86.995 | 87.005 | 87.030 | 87.108 | 87.210 | 87.283 | 87.337 |
| 1 | 86.995 | 87.006 | 87.037 | 87.117 | 87.217 | 87.293 | 87.339 |
| 2 | 86.996 | 87.010 | 87.049 | 87.138 | 87.230 | 87.299 | 87.342 |
| 3 | 86.996 | 87.011 | 87.056 | 87.148 | 87.237 | 87.304 | 87.347 |
| 4 | 86.997 | 87.013 | 87.063 | 87.158 | 87.244 | 87.309 | 87.350 |
| 5 | 86.997 | 87.014 | 87.070 | 87.167 | 87.251 | 87.314 | 87.352 |
| 6 | 86.998 | 87.016 | 87.076 | 87.176 | 87.258 | 87.318 | 87.355 |
| 7 | 86.998 | 87.018 | 87.083 | 87.185 | 87.264 | 87.323 | 87.358 |
| 8 | 86.999 | 87.019 | 87.090 | 87.193 | 87.271 | 87.328 | 87.360 |
| 9 | 87.000 | 87.021 | 87.097 | 87.202 | 87.277 | 87.333 | 87.363 |
| 10 | | | | | | | |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 5 | 16 | 67 | 94 | 67 | 48 | 26 |
| Average lit./min | 0.5 | 1.6 | 6.7 | 9.4 | 6.7 | 4.8 | 2.6 |
| Franch time (P _f) | 0:01 | 0:02 | 0:03 | 0:04 | 0:05 | 0:06 | 0:07 |
| Friction Loss (P _f) = p _f (L _g + L _s) [kg/cm ²] | 0.01 | 0.01 | 0.01 | 0.01 | 0.01 | 0.00 | 0.00 |
| Calculation of Lugeon value | | | | | | Lugeon value: (0.7) | |
| P = P _g + 0.1(sin θ)(L _g + L _s)P _f [kg/cm ²] | | | | | | Lu' [lit/min/m] | |
| P ₁ = 2.4 | | | | | | q ₁ = 0.1 | |
| P ₂ = 5.4 | | | | | | q ₂ = 0.3 | |
| P ₃ = 8.4 | | | | | | q ₃ = 1.3 | |
| P ₄ = 11.4 | | | | | | q ₄ = 1.9 | |
| P ₅ = 8.4 | | | | | | q ₅ = 1.3 | |
| P ₆ = 5.4 | | | | | | q ₆ = 1.0 | |
| P ₇ = 2.4 | | | | | | q ₇ = 0.5 | |



Remarks: Lugeon value: (0.7) Lu' Critical Pressure: 5.4 kg/cm²


Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the just previous one minute

Prepared by: A. Hamid & Azhor Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-6 Stages: 5/14
 Location: Upstream Colfer Dam (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (θ): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p_f): 1x10⁴ x Q^{1.87} Date: 01/February/1999

| Ground elevation: EL. m | | Groundwater level (L _g): GL. 13.40 m | | Gauge height (L _g): 0.73 m | | | |
|---|----------------|---|----------------|--|----------------|---------------------------|----------------|
| Pipe length from pressure gauge to hole mouth: (L _g) = 4.44 m | | Depth of test section: 20 m to (L _g) = 25 m | | Length of section (L _s): 5 m | | | |
| Reading of flow meter | | | | | | | |
| Gauge P _i (kg/cm ²) | P ₁ | P ₂ | P ₃ | P ₄ | P ₅ | P ₆ | P ₇ |
| Start time | 15:00 | 15:12 | 15:25 | 15:37 | 15:50 | 16:02 | 16:14 |
| Q (m ³ /min) | 91.711 | 91.724 | 91.751 | 91.802 | 91.908 | 92.045 | 92.064 |
| 1 | 91.712 | 91.724 | 91.755 | 91.811 | 91.916 | 92.011 | 92.067 |
| 2 | 91.712 | 91.726 | 91.760 | 91.821 | 91.924 | 92.016 | 92.070 |
| 3 | 91.713 | 91.729 | 91.764 | 91.830 | 91.932 | 92.022 | 92.073 |
| 4 | 91.713 | 91.731 | 91.768 | 91.840 | 91.940 | 92.027 | 92.077 |
| 5 | 91.714 | 91.734 | 91.773 | 91.849 | 91.947 | 92.033 | 92.080 |
| 6 | 91.714 | 91.736 | 91.777 | 91.859 | 91.956 | 92.039 | 92.083 |
| 7 | 91.715 | 91.739 | 91.781 | 91.869 | 91.964 | 92.044 | 92.087 |
| 8 | 91.715 | 91.741 | 91.785 | 91.878 | 91.972 | 92.050 | 92.090 |
| 9 | 91.716 | 91.744 | 91.789 | 91.889 | 91.980 | 92.055 | 92.093 |
| 10 | 91.716 | 91.746 | 91.794 | 91.894 | 91.987 | 92.061 | 92.096 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | 5 | 25 | 43 | 97 | 79 | 56 | 32 |
| Average lit./min | 0.5 | 2.5 | 4.3 | 9.7 | 7.9 | 5.6 | 3.2 |
| Franch time (P _f) | 15:10 | 15:22 | 15:35 | 15:47 | 16:00 | 16:12 | 16:24 |
| Friction Loss (P _f) = p _f (L _g + L _s) [kg/cm ²] | 0.01 | 0.01 | 0.00 | 0.02 | 0.01 | 0.01 | 0.00 |
| Calculation of Lugeon value | | | | | | Lugeon value: (1.1) | |
| P = P _g + 0.1(sin θ)(L _g + L _s)P _f [kg/cm ²] | | | | | | Lu' [kg/cm ²] | |
| P ₁ = 2.4 | | | | | | q ₁ = 0.1 | |
| P ₂ = 5.4 | | | | | | q ₂ = 0.5 | |
| P ₃ = 8.4 | | | | | | q ₃ = 0.9 | |
| P ₄ = 11.4 | | | | | | q ₄ = 1.9 | |
| P ₅ = 8.4 | | | | | | q ₅ = 1.6 | |
| P ₆ = 5.4 | | | | | | q ₆ = 1.1 | |
| P ₇ = 2.4 | | | | | | q ₇ = 0.6 | |



Remarks: Lugeon value: (1.1) Lu' Critical Pressure: 8.4 kg/cm²


Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the just previous one minute

Prepared by: A. Hamid & Azhor Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-6 Stage: 6/14
 Location: Upstream Coffier Dam (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^4 \times Q^{1.711}$ Date: 2/February/1999

| | | | | | | | |
|--|-----------------|-----------------|-----------------|---|-----------------|--|-----------------|
| Ground elevation: EL | | m | | Groundwater level (L _g): GL- 13.40 m | | Gauge height (L _g): 0.73 m | |
| Pipe length from pressure gauge to hole mouth: (L _p)= 4.70 m | | m | | Depth of test section GL - (L _g)= 30 m to (L _g)= 30 m | | Length of section (L _s)= 5 m | |
| Calculation of Lugeon value | | | | | | | |
| Gauge P. (kg/cm ²) | P _{o1} | P _{o2} | P _{o3} | P _{o4} | P _{o5} | P _{o6} | P _{o7} |
| Start time | 10:10 | 10:22 | 10:33 | 10:45 | 10:57 | 11:10 | 11:23 |
| Q (min) | 98.460 | 98.470 | 98.477 | 98.487 | 98.502 | 98.508 | 98.511 |
| 1 | 98.460 | 98.470 | 98.477 | 98.488 | 98.502 | 98.508 | 98.511 |
| 2 | 98.461 | 98.472 | 98.478 | 98.491 | 98.503 | 98.508 | 98.511 |
| 3 | 98.461 | 98.473 | 98.480 | 98.493 | 98.504 | 98.509 | 98.511 |
| 4 | 98.461 | 98.473 | 98.481 | 98.494 | 98.504 | 98.509 | 98.511 |
| 5 | 98.462 | 98.474 | 98.482 | 98.496 | 98.505 | 98.509 | 98.511 |
| 6 | 98.462 | 98.474 | 98.483 | 98.497 | 98.505 | 98.510 | 98.512 |
| 7 | 98.462 | 98.475 | 98.484 | 98.498 | 98.506 | 98.510 | 98.512 |
| 8 | 98.463 | 98.475 | 98.485 | 98.499 | 98.506 | 98.510 | 98.512 |
| 9 | 98.463 | 98.476 | 98.486 | 98.501 | 98.507 | 98.511 | 98.512 |
| 10 | 98.464 | 98.476 | 98.487 | 98.502 | 98.508 | 98.511 | 98.513 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | Q _{o1} | Q _{o2} | Q _{o3} | Q _{o4} | Q _{o5} | Q _{o6} | Q _{o7} |
| Average lit./min | Q _{a1} | Q _{a2} | Q _{a3} | Q _{a4} | Q _{a5} | Q _{a6} | Q _{a7} |
| Friction loss (Pr) | P _{r1} | P _{r2} | P _{r3} | P _{r4} | P _{r5} | P _{r6} | P _{r7} |
| Friction Loss (Pr) = p(L _w + L _s) [kg/cm ²] | | | | | | | |




Water Injection Ratio (q : lit./min/m)
 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0
 Lugeon value : 0.3 Lu
 Critical Pressure: >11 kg/cm²

Remarks:
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.
 Prepared by: A. Hamid & Azhor Inspected by: M. Suga

Water Pressure Test

Hole No.: M98-6 Stage: 7/14
 Location: Upstream Coffier Dam (Left Bank) Dia. of Hole: 76 m/m
 Hole Inclination (a): 90 degrees Packer Type: Mechanical
 Friction Loss per meter (p): $1 \times 10^4 \times Q^{1.711}$ Date: 02/February/1999

| | | | | | | | |
|--|-----------------|-----------------|-----------------|---|-----------------|--|-----------------|
| Ground elevation: EL | | m | | Groundwater level (L _g): GL- 13.40 m | | Gauge height (L _g): 0.75 m | |
| Pipe length from pressure gauge to hole mouth: (L _p)= 4.70 m | | m | | Depth of test section GL - (L _g)= 30 m to (L _g)= 35 m | | Length of section (L _s)= 5 m | |
| Calculation of Lugeon value | | | | | | | |
| Gauge P. (kg/cm ²) | P _{o1} | P _{o2} | P _{o3} | P _{o4} | P _{o5} | P _{o6} | P _{o7} |
| Start time | 16:45 | 16:57 | 17:08 | 17:20 | 17:32 | 17:43 | 17:54 |
| Q (min) | 11.850 | 11.871 | 11.883 | 11.912 | 11.972 | 11.998 | 12.008 |
| 1 | 11.850 | 11.872 | 11.885 | 11.917 | 11.975 | 11.999 | 12.008 |
| 2 | 11.851 | 11.873 | 11.886 | 11.923 | 11.978 | 12.000 | 12.009 |
| 3 | 11.852 | 11.874 | 11.888 | 11.929 | 11.980 | 12.001 | 12.009 |
| 4 | 11.853 | 11.874 | 11.892 | 11.935 | 11.982 | 12.003 | 12.010 |
| 5 | 11.853 | 11.875 | 11.894 | 11.940 | 11.985 | 12.004 | 12.010 |
| 6 | 11.854 | 11.876 | 11.896 | 11.946 | 11.987 | 12.005 | 12.011 |
| 7 | 11.855 | 11.877 | 11.898 | 11.951 | 11.989 | 12.006 | 12.012 |
| 8 | 11.855 | 11.878 | 11.899 | 11.958 | 11.992 | 12.006 | 12.012 |
| 9 | 11.856 | 11.879 | 11.902 | 11.964 | 11.995 | 12.007 | 12.012 |
| 10 | 11.857 | 11.879 | 11.904 | 11.970 | 11.997 | 12.008 | 12.013 |
| 11 | | | | | | | |
| 12 | | | | | | | |
| 13 | | | | | | | |
| 14 | | | | | | | |
| 15 | | | | | | | |
| Total lit. | Q _{o1} | Q _{o2} | Q _{o3} | Q _{o4} | Q _{o5} | Q _{o6} | Q _{o7} |
| Average lit./min | Q _{a1} | Q _{a2} | Q _{a3} | Q _{a4} | Q _{a5} | Q _{a6} | Q _{a7} |
| Friction loss (Pr) | P _{r1} | P _{r2} | P _{r3} | P _{r4} | P _{r5} | P _{r6} | P _{r7} |
| Friction Loss (Pr) = p(L _w + L _s) [kg/cm ²] | | | | | | | |



Water Injection Ratio (q : lit./min/m)
 0.0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0
 Lugeon value : 0.8 Lu
 Critical Pressure: >11 kg/cm²

Remarks:
 Note: Injection of water should be continued for at least 10 minutes under the specified pressure, after the injection rate per minute settles within 90 % to 110 % of the injection rate in the last previous one minute.
 Prepared by: A. Hamid & Azhor Inspected by: M. Suga