

Sagala Line-N2750

Curr.Elect C1	Curr.Elect C2	Pot.Elect P1	Pot.Elect P2	n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
-1000	-950	-900	-850	1	770	97.53	119.38	6.61
-1000	-950	-850	-800	2	770	42.68	208.96	6.53
-1000	-950	-800	-750	3	770	30.44	372.58	6.77
-1000	-950	-750	-700	4	770	24.09	589.72	7.06
-1000	-950	-700	-650	5	770	7.58	324.73	5.73
-950	-900	-850	-800	1	500	70.57	133.02	6.03
-950	-900	-800	-750	2	500	48.31	364.25	6.97
-950	-900	-750	-700	3	500	40.53	763.97	7.67
-950	-900	-700	-650	4	500	10.06	379.25	6.88
-950	-900	-650	-600	5	500	4.50	296.88	5.18
-900	-850	-800	-750	1	460	91.85	188.19	6.28
-900	-850	-750	-700	2	460	64.88	531.72	7.45
-900	-850	-700	-650	3	460	15.29	313.27	6.65
-900	-850	-650	-600	4	460	6.25	256.11	5.04
-900	-850	-600	-550	5	460	10.63	762.28	6.14
-850	-800	-750	-700	1	550	145.07	248.59	7.26
-850	-800	-700	-650	2	550	27.53	188.70	6.61
-850	-800	-650	-600	3	550	9.64	165.19	4.53
-850	-800	-600	-550	4	550	15.77	540.47	6.16
-850	-800	-550	-500	5	550	11.52	690.92	6.43
-800	-750	-700	-650	1	100	27.54	259.56	5.85
-800	-750	-650	-600	2	100	4.77	179.82	2.74
-800	-750	-600	-550	3	100	6.11	575.85	5.72
-800	-750	-550	-500	4	100	3.90	735.13	3.63
-800	-750	-500	-450	5	100	2.82	930.23	6.54
-750	-700	-650	-600	1	120	15.59	122.44	3.28
-750	-700	-600	-550	2	120	15.03	472.18	4.12
-750	-700	-550	-500	3	120	8.44	662.88	4.03
-750	-700	-500	-450	4	120	5.59	878.08	6.05
-750	-700	-450	-400	5	120	2.28	626.75	3.39
-700	-650	-600	-550	1	210	28.73	128.94	4.78
-700	-650	-550	-500	2	210	13.33	239.30	4.81
-700	-650	-500	-450	3	210	7.87	353.20	7.10
-700	-650	-450	-400	4	210	3.08	276.46	3.97
-700	-650	-400	-350	5	210	1.53	240.33	4.22
-650	-600	-550	-500	1	180	34.25	179.33	4.36
-650	-600	-500	-450	2	180	14.54	304.53	6.20
-650	-600	-450	-400	3	180	4.10	214.68	5.27
-650	-600	-400	-350	4	180	1.66	173.83	4.03
-650	-600	-350	-300	5	180	1.07	196.09	5.27
-600	-550	-500	-450	1	100	51.25	483.02	6.27
-600	-550	-450	-400	2	100	10.04	378.50	5.32
-600	-550	-400	-350	3	100	3.31	311.96	5.06
-600	-550	-350	-300	4	100	2.12	399.61	5.09
-600	-550	-300	-250	5	100	1.58	521.19	3.16
-550	-500	-450	-400	1	120	28.85	226.59	4.88
-550	-500	-400	-350	2	120	5.98	187.87	4.18
-550	-500	-350	-300	3	120	3.17	248.97	4.54
-550	-500	-300	-250	4	120	2.18	342.43	2.55
-550	-500	-250	-200	5	120	1.87	514.04	4.06
-500	-450	-400	-350	1	270	51.97	181.41	8.88
-500	-450	-350	-300	2	270	16.93	236.39	7.03
-500	-450	-300	-250	3	270	9.45	329.87	6.60
-500	-450	-250	-200	4	270	8.00	558.51	6.57
-500	-450	-200	-150	5	270	4.89	597.43	6.80

Sagala Line-N2750

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-450	-400	-350	-300	1	350	38.17	102.78	7.87
-450	-400	-300	-250	2	350	14.92	160.71	5.51
-450	-400	-250	-200	3	350	11.40	306.98	5.71
-450	-400	-200	-150	4	350	6.71	361.37	5.76
-450	-400	-150	-100	5	350	3.05	287.46	4.99
-400	-350	-300	-250	1	500	37.98	71.59	5.61
-400	-350	-250	-200	2	500	23.46	176.88	5.70
-400	-350	-200	-150	3	500	12.65	238.45	6.53
-400	-350	-150	-100	4	500	5.47	206.21	5.25
-400	-350	-100	-50	5	500	3.13	206.50	4.53
-350	-300	-250	-200	1	590	54.38	86.87	5.04
-350	-300	-200	-150	2	590	25.05	160.06	5.64
-350	-300	-150	-100	3	590	10.13	161.82	5.75
-350	-300	-100	-50	4	590	5.57	177.95	5.00
-350	-300	-50	0	5	590	4.62	258.30	5.28
-300	-250	-200	-150	1	450	42.44	88.89	5.69
-300	-250	-150	-100	2	450	13.65	114.35	5.20
-300	-250	-100	-50	3	450	6.17	129.22	4.42
-300	-250	-50	0	4	450	4.86	203.58	5.13
-300	-250	0	50	5	450	3.24	237.50	5.54
-250	-200	-150	-100	1	350	29.78	80.19	4.71
-250	-200	-100	-50	2	350	9.05	97.48	4.71
-250	-200	-50	0	3	350	6.35	170.99	5.76
-250	-200	0	50	4	350	3.88	208.96	3.34
-250	-200	50	100	5	350	3.75	353.43	4.99
-200	-150	-100	-50	1	280	13.10	44.09	5.74
-200	-150	-50	0	2	280	7.65	103.00	4.50
-200	-150	0	50	3	280	4.38	147.43	4.99
-200	-150	50	100	4	280	4.17	280.72	3.20
-200	-150	100	150	5	280	3.13	368.74	5.94
-150	-100	-50	0	1	440	18.76	40.18	4.52
-150	-100	0	50	2	440	8.41	72.06	3.53
-150	-100	50	100	3	440	6.75	144.58	6.72
-150	-100	100	150	4	440	4.83	206.92	4.22
-150	-100	150	200	5	440	2.86	214.41	4.27
-100	-50	0	50	1	310	17.12	52.05	4.00
-100	-50	50	100	2	310	8.98	109.21	4.61
-100	-50	100	150	3	310	5.88	178.77	5.26
-100	-50	150	200	4	310	3.24	197.01	4.14
-100	-50	200	250	5	310	3.48	370.30	3.78
-50	0	50	100	1	130	8.58	62.20	4.11
-50	0	100	150	2	130	4.00	116.00	2.78
-50	0	150	200	3	130	1.87	135.57	2.81
-50	0	200	250	4	130	1.83	265.34	1.37
-50	0	250	300	5	130	0.96	243.59	1.50
0	50	100	150	1	150	14.99	94.18	5.10
0	50	150	200	2	150	4.39	110.33	3.18
0	50	200	250	3	150	3.38	212.37	2.26
0	50	250	300	4	150	1.60	201.06	4.61
0	50	300	350	5	150	0.91	200.12	3.75
50	100	150	200	1	220	29.49	126.33	6.15
50	100	200	250	2	220	15.53	266.12	5.67
50	100	250	300	3	220	5.92	253.61	5.20
50	100	300	350	4	220	2.85	244.19	6.70
50	100	350	400	5	220	2.47	370.35	6.74

Sagala Line-N2750

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
100	150	200	250	1	200	45.33	213.61	5.86
100	150	250	300	2	200	14.28	269.17	5.61
100	150	300	350	3	200	4.90	230.91	4.99
100	150	350	400	4	200	3.76	354.37	6.81
100	150	400	450	5	200	1.84	303.48	4.03
150	200	250	300	1	300	57.56	180.83	5.12
150	200	300	350	2	300	13.94	175.18	5.06
150	200	350	400	3	300	8.80	276.46	5.52
150	200	400	450	4	300	3.50	219.91	2.04
150	200	450	500	5	300	4.74	521.19	4.81
200	250	300	350	1	460	99.59	204.05	5.83
200	250	350	400	2	460	41.32	338.64	6.08
200	250	400	450	3	460	12.84	263.07	4.26
200	250	450	500	4	460	16.08	658.91	4.05
200	250	500	550	5	460	21.52	1543.20	4.01
250	300	350	400	1	420	60.89	136.64	7.01
250	300	400	450	2	420	14.54	130.51	4.00
250	300	450	500	3	420	15.81	354.78	4.44
250	300	500	550	4	420	20.40	915.55	4.24
250	300	550	600	5	420	7.08	556.06	6.20
300	350	400	450	1	120	6.79	53.33	1.13
300	350	450	500	2	120	5.57	174.99	2.23
300	350	500	550	3	120	7.42	582.77	1.92
300	350	550	600	4	120	2.32	364.42	4.53
300	350	600	650	5	120	1.08	296.88	6.03
350	400	450	500	1	125	16.03	120.86	3.21
350	400	500	550	2	125	16.02	483.15	2.62
350	400	550	600	3	125	4.49	338.54	5.67
350	400	600	650	4	125	1.95	294.05	5.79
350	400	650	700	5	125	0.94	248.06	8.44
400	450	500	550	1	230	60.40	247.50	2.59
400	450	550	600	2	230	13.74	225.21	5.35
400	450	600	650	3	230	5.35	219.23	6.75
400	450	650	700	4	230	2.22	181.94	4.60
400	450	700	750	5	230	2.52	361.42	8.27
450	500	550	600	1	240	65.74	258.16	5.14
450	500	600	650	2	240	18.78	295.00	6.03
450	500	650	700	3	240	7.66	300.81	3.67
450	500	700	750	4	240	7.57	594.55	5.83
450	500	750	800	5	240	5.38	739.45	5.73
500	550	600	650	1	290	61.59	200.16	5.43
500	550	650	700	2	290	20.83	270.78	3.84
500	550	700	750	3	290	18.73	608.71	4.68
500	550	750	800	4	290	12.57	817.03	5.29
500	550	800	850	5	290	5.61	638.12	5.16
550	600	650	700	1	190	19.85	98.46	5.97
550	600	700	750	2	190	11.24	223.02	6.01
550	600	750	800	3	190	6.70	332.35	6.25
550	600	800	850	4	190	2.74	271.83	4.07
550	600	850	900	5	190	1.30	225.70	9.14
600	650	700	750	1	140	21.52	144.87	8.09
600	650	750	800	2	140	7.58	204.11	5.06
600	650	800	850	3	140	2.73	183.78	3.65
600	650	850	900	4	140	1.09	146.76	1.61
600	650	900	950	5	140	1.03	242.69	3.71

Sagala Line-N2750

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
650	700	750	800	1	75	10.41	130.82	3.96
650	700	800	850	2	75	2.67	134.21	31.32
650	700	850	900	3	75	0.89	111.84	-90.25
650	700	900	950	4	75	0.71	178.44	5.06
650	700	950	1000	5	75	0.50	219.91	-2.92
700	750	800	850	1	45	6.09	127.55	1.90
700	750	850	900	2	45	1.49	124.83	-2.54
700	750	900	950	3	45	0.83	173.83	-101.85
700	750	950	1000	4	45	0.58	242.95	146.58
700	750	1000	1050	5	45	0.38	278.55	-5.62
750	800	850	900	1	55	6.20	106.24	3.61
750	800	900	950	2	55	2.40	164.51	2.77
750	800	950	1000	3	55	1.37	234.76	-2.88
750	800	1000	1050	4	55	0.83	284.46	0.75
750	800	1050	1100	5	55	0.53	317.87	10.15
800	850	900	950	1	80	6.78	79.87	2.56
800	850	950	1000	2	80	2.68	126.29	-1.93
800	850	1000	1050	3	80	1.39	163.76	3.17
800	850	1050	1100	4	80	0.75	176.71	-0.63
800	850	1100	1150	5	80	0.64	263.89	0.69
850	900	950	1000	1	50	5.12	96.51	3.32
850	900	1000	1050	2	50	1.81	136.47	-1.56
850	900	1050	1100	3	50	0.78	147.03	-5.41
850	900	1100	1150	4	50	0.60	226.19	2.17
850	900	1150	1200	5	50	0.36	237.50	-3.32
900	950	1000	1050	1	40	3.41	80.35	-2.42
900	950	1050	1100	2	40	1.15	108.38	-7.38
900	950	1100	1150	3	40	0.77	181.43	-7.78
900	950	1150	1200	4	40	0.45	212.06	-0.39
900	950	1200	1250	5	40	0.32	263.89	485.76
950	1000	1050	1100	1	50	4.18	78.79	-0.59
950	1000	1100	1150	2	50	1.99	150.04	-2.22
950	1000	1150	1200	3	50	1.01	190.38	-0.08
950	1000	1200	1250	4	50	0.43	162.11	-12.15
950	1000	1250	1300	5	50	0.39	257.30	10.33
1000	1050	1100	1150	1	200	35.79	168.66	13.99
1000	1050	1150	1200	2	200	12.39	233.55	7.50
1000	1050	1200	1250	3	200	4.08	192.27	2.36
1000	1050	1250	1300	4	200	3.26	307.25	6.96
1000	1050	1300	1350	5	200	2.54	418.93	6.78
1050	1100	1150	1200	1	220	36.52	156.45	13.45
1050	1100	1200	1250	2	220	7.73	132.46	3.52
1050	1100	1250	1300	3	220	5.39	230.91	4.03
1050	1100	1300	1350	4	220	4.01	343.58	4.02
1050	1100	1350	1400	5	220	2.54	380.85	5.60
1100	1150	1200	1250	1	370	47.66	121.40	7.24
1100	1150	1250	1300	2	370	22.59	230.17	6.26
1100	1150	1300	1350	3	370	13.68	348.46	6.85
1100	1150	1350	1400	4	370	7.81	397.88	6.38
1100	1150	1400	1450	5	370	4.62	411.89	5.03
1150	1200	1250	1300	1	320	36.78	108.33	4.97
1150	1200	1300	1350	2	320	18.05	212.65	5.77
1150	1200	1350	1400	3	320	9.27	273.02	2.97
1150	1200	1400	1450	4	320	5.08	299.24	8.52
1150	1200	1450	1500	5	320	2.83	291.73	6.75

Sagala Line-N2750

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
1200	1250	1300	1350	1	180	21.59	113.04	4.36
1200	1250	1350	1400	2	180	8.36	175.09	4.33
1200	1250	1400	1450	3	180	3.88	203.16	7.77
1200	1250	1450	1500	4	180	2.07	216.77	0.38
1200	1250	1500	1550	5	180	1.33	243.74	6.36
1250	1300	1350	1400	1	190	27.98	138.79	4.22
1250	1300	1400	1450	2	190	9.95	197.42	4.40
1250	1300	1450	1500	3	190	4.24	210.32	2.96
1250	1300	1500	1550	4	190	2.52	250.00	3.03
1250	1300	1550	1600	5	190	1.79	310.77	2.55
1300	1350	1400	1450	1	450	65.17	136.49	6.54
1300	1350	1450	1500	2	450	19.59	164.12	5.61
1300	1350	1500	1550	3	450	9.78	204.83	4.84
1300	1350	1550	1600	4	450	6.19	259.29	4.16
1300	1350	1600	1650	5	450	6.54	479.41	3.77
1350	1400	1450	1500	1	220	21.77	93.26	4.29
1350	1400	1500	1550	2	220	7.95	136.23	3.85
1350	1400	1550	1600	3	220	4.35	186.35	2.89
1350	1400	1600	1650	4	220	4.10	351.29	3.10
1350	1400	1650	1700	5	220	2.93	439.32	4.50
1400	1450	1500	1550	1	130	11.43	82.87	3.03
1400	1450	1550	1600	2	130	4.61	133.69	2.52
1400	1450	1600	1650	3	130	3.75	271.87	5.60
1400	1450	1650	1700	4	130	2.40	347.99	-0.70
1400	1450	1700	1750	5	130	1.26	319.72	7.41
1450	1500	1550	1600	1	175	12.57	67.70	2.00
1450	1500	1600	1650	2	175	7.82	168.46	3.16
1450	1500	1650	1700	3	175	4.38	235.89	1.89
1450	1500	1700	1750	4	175	2.09	225.12	5.17
1450	1500	1750	1800	5	175	1.49	280.86	5.70
1500	1550	1600	1650	1	370	46.69	118.93	2.47
1500	1550	1650	1700	2	370	18.71	190.64	5.28
1500	1550	1700	1750	3	370	7.45	189.77	3.12
1500	1550	1750	1800	4	370	4.57	232.82	5.17
1500	1550	1800	1850	5	370	2.26	201.49	6.83
1550	1600	1650	1700	1	350	55.09	148.35	3.45
1550	1600	1700	1750	2	350	15.01	161.68	3.63
1550	1600	1750	1800	3	350	7.41	199.54	5.13
1550	1600	1800	1850	4	350	3.17	170.72	4.41
1550	1600	1850	1900	5	350	2.48	233.73	3.94
1600	1650	1700	1750	1	230	42.04	172.27	2.46
1600	1650	1750	1800	2	230	14.15	231.93	3.65
1600	1650	1800	1850	3	230	4.78	195.87	3.11
1600	1650	1850	1900	4	230	3.18	260.62	3.89
1600	1650	1900	1950	5	230	2.29	328.43	6.16
1650	1700	1750	1800	1	220	32.51	139.27	3.21
1650	1700	1800	1850	2	220	7.56	129.55	2.83
1650	1700	1850	1900	3	220	3.94	168.79	4.04
1650	1700	1900	1950	4	220	2.73	233.91	2.92
1650	1700	1950	2000	5	220	2.22	332.87	5.66
1700	1750	1800	1850	1	350	24.88	67.00	5.88
1700	1750	1850	1900	2	350	9.12	98.23	3.30
1700	1750	1900	1950	3	350	5.65	152.14	3.63
1700	1750	1950	2000	4	350	4.30	231.58	5.47
1750	1800	1850	1900	1	420	30.81	69.14	5.60

Sagala Line-N2750

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
1750	1800	1900	1950	2	420	13.54	121.53	4.60
1750	1800	1950	2000	3	420	8.93	200.39	6.17
1800	1850	1900	1950	1	290	23.92	77.74	10.03
1800	1850	1950	2000	2	290	9.70	126.10	5.78
1850	1900	1950	2000	1	320	184.62	543.75	35.82

Sagala Line-N2500

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-1000	-950	-900	-850	1	390	18.81	45.46	4.03
-1000	-950	-850	-800	2	390	5.86	56.65	4.67
-1000	-950	-800	-750	3	390	3.62	87.48	3.82
-1000	-950	-750	-700	4	390	2.17	104.88	4.03
-1000	-950	-700	-650	5	390	2.00	169.16	3.69
-950	-900	-850	-800	1	350	20.07	54.04	6.52
-950	-900	-800	-750	2	350	8.35	89.94	5.23
-950	-900	-750	-700	3	350	4.03	108.52	4.97
-950	-900	-700	-650	4	350	3.20	172.34	5.07
-950	-900	-650	-600	5	350	2.04	192.27	4.87
-900	-850	-800	-750	1	170	7.61	42.19	3.09
-900	-850	-750	-700	2	170	2.55	56.55	4.50
-900	-850	-700	-650	3	170	1.68	93.14	3.52
-900	-850	-650	-600	4	170	0.98	108.66	2.63
-900	-850	-600	-550	5	170	0.72	139.71	5.36
-850	-800	-750	-700	1	100	3.39	31.95	3.31
-850	-800	-700	-650	2	100	1.51	56.93	2.38
-850	-800	-650	-600	3	100	0.75	70.69	2.18
-850	-800	-600	-550	4	100	0.50	94.25	5.42
-850	-800	-550	-500	5	100	0.49	161.63	-9.42
-800	-750	-700	-650	1	125	4.87	36.72	2.42
-800	-750	-650	-600	2	125	1.84	55.49	1.99
-800	-750	-600	-550	3	125	1.04	78.41	3.64
-800	-750	-550	-500	4	125	1.01	152.30	1.71
-800	-750	-500	-450	5	125	0.63	166.25	6.36
-750	-700	-650	-600	1	220	10.92	46.78	2.75
-750	-700	-600	-550	2	220	4.07	69.74	3.09
-750	-700	-550	-500	3	220	3.23	138.37	2.99
-750	-700	-500	-450	4	220	1.71	146.51	2.44
-750	-700	-450	-400	5	220	1.53	229.41	1.48
-700	-650	-600	-550	1	380	25.87	64.16	4.07
-700	-650	-550	-500	2	380	11.18	110.91	3.79
-700	-650	-500	-450	3	380	5.17	128.23	2.74
-700	-650	-450	-400	4	380	4.23	209.83	3.99
-700	-650	-400	-350	5	380	3.20	277.78	4.24
-650	-600	-550	-500	1	1100	62.51	53.56	3.08
-650	-600	-500	-450	2	1100	22.86	78.35	2.59
-650	-600	-450	-400	3	1100	15.39	131.86	4.19
-650	-600	-400	-350	4	1100	9.85	168.79	4.55
-650	-600	-350	-300	5	1100	6.54	196.12	3.94
-600	-550	-500	-450	1	220	13.37	57.28	5.53
-600	-550	-450	-400	2	220	6.17	105.73	4.69
-600	-550	-400	-350	3	220	3.15	134.95	5.10
-600	-550	-350	-300	4	220	1.78	152.51	3.41
-600	-550	-300	-250	5	220	1.37	205.42	3.91
-550	-500	-450	-400	1	200	19.65	92.60	10.50
-550	-500	-400	-350	2	200	7.19	135.53	6.99
-550	-500	-350	-300	3	200	3.10	146.08	6.47
-550	-500	-300	-250	4	200	1.94	182.84	5.96
-550	-500	-250	-200	5	200	0.95	156.69	5.34
-500	-450	-400	-350	1	250	21.98	82.86	6.38
-500	-450	-350	-300	2	250	6.83	102.99	5.10
-500	-450	-300	-250	3	250	3.35	126.29	4.49
-500	-450	-250	-200	4	250	1.36	102.54	4.33
-500	-450	-200	-150	5	250	1.05	138.54	6.28

Sagala Line-N2500

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-450	-400	-350	-300	1	150	22.36	140.49	7.58
-450	-400	-300	-250	2	150	9.02	226.70	6.92
-450	-400	-250	-200	3	150	3.07	192.89	5.80
-450	-400	-200	-150	4	150	1.80	226.19	6.00
-450	-400	-150	-100	5	150	1.25	274.89	6.33
-400	-350	-300	-250	1	180	35.12	183.89	7.10
-400	-350	-250	-200	2	180	9.76	204.41	6.56
-400	-350	-200	-150	3	180	4.58	239.81	6.20
-400	-350	-150	-100	4	180	2.90	303.69	6.78
-400	-350	-100	-50	5	180	1.62	296.88	3.18
-350	-300	-250	-200	1	220	35.00	149.94	7.63
-350	-300	-200	-150	2	220	10.76	184.38	6.92
-350	-300	-150	-100	3	220	5.72	245.04	6.85
-350	-300	-100	-50	4	220	2.60	222.77	5.28
-350	-300	-50	0	5	220	1.68	251.90	4.18
-300	-250	-200	-150	1	250	29.06	109.55	5.37
-300	-250	-150	-100	2	250	12.46	187.89	6.00
-300	-250	-100	-50	3	250	5.39	203.20	4.83
-300	-250	-50	0	4	250	3.01	226.95	4.40
-300	-250	0	50	5	250	1.71	225.63	5.50
-250	-200	-150	-100	1	300	27.82	87.40	5.83
-250	-200	-100	-50	2	300	8.77	110.21	4.22
-250	-200	-50	0	3	300	4.15	130.38	3.10
-250	-200	0	50	4	300	2.08	130.69	6.20
-250	-200	50	100	5	300	1.52	167.13	6.29
-200	-150	-100	-50	1	270	28.59	99.80	5.54
-200	-150	-50	0	2	270	10.24	142.98	5.90
-200	-150	0	50	3	270	4.40	153.59	5.05
-200	-150	50	100	4	270	2.67	186.40	6.26
-200	-150	100	150	5	270	1.96	239.46	4.43
-150	-100	-50	0	1	280	28.97	97.51	6.45
-150	-100	0	50	2	280	9.24	124.41	5.38
-150	-100	50	100	3	280	4.72	158.87	6.26
-150	-100	100	150	4	280	3.22	216.77	5.22
-150	-100	150	200	5	280	2.50	294.52	3.51
-100	-50	0	50	1	300	21.11	66.32	4.53
-100	-50	50	100	2	300	8.01	100.66	4.75
-100	-50	100	150	3	300	4.67	146.71	3.74
-100	-50	150	200	4	300	3.35	210.49	3.01
-100	-50	200	250	5	300	2.26	248.50	2.68
-50	0	50	100	1	280	18.59	62.57	5.97
-50	0	100	150	2	280	8.20	110.40	5.04
-50	0	150	200	3	280	4.90	164.93	5.76
-50	0	200	250	4	280	3.12	210.04	5.22
-50	0	250	300	5	280	2.82	332.22	3.55
0	50	100	150	1	280	22.56	75.94	5.27
0	50	150	200	2	280	9.67	130.20	5.66
0	50	200	250	3	280	5.56	187.15	5.81
0	50	250	300	4	280	4.45	299.57	5.60
0	50	300	350	5	280	3.94	464.17	5.81
50	100	150	200	1	470	68.87	138.10	9.61
50	100	200	250	2	470	25.02	200.69	8.76
50	100	250	300	3	470	18.21	365.16	8.48
50	100	300	350	4	470	15.22	610.40	9.03
50	100	350	400	5	470	7.68	539.02	8.53

Sagala Line-N2500

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
100	150	200	250	1	980	140.58	135.20	8.21
100	150	250	300	2	980	83.08	319.60	7.93
100	150	300	350	3	980	65.43	629.25	8.62
100	150	350	400	4	980	30.80	592.41	8.50
100	150	400	450	5	980	10.20	343.33	6.30
150	200	250	300	1	450	83.40	174.67	8.33
150	200	300	350	2	450	58.48	489.92	9.37
150	200	350	400	3	450	25.47	533.44	9.44
150	200	400	450	4	450	8.00	335.10	7.81
150	200	450	500	5	450	6.64	486.74	7.85
200	250	300	350	1	200	42.93	202.30	7.90
200	250	350	400	2	200	14.61	275.39	8.06
200	250	400	450	3	200	4.19	197.45	6.80
200	250	450	500	4	200	3.23	304.42	7.22
200	250	500	550	5	200	1.41	232.56	5.35
250	300	350	400	1	200	45.61	214.93	7.56
250	300	400	450	2	200	10.19	192.08	5.57
250	300	450	500	3	200	5.73	270.02	5.89
250	300	500	550	4	200	2.32	218.65	3.55
250	300	550	600	5	200	2.21	364.50	5.53
300	350	400	450	1	340	64.21	177.99	6.82
300	350	450	500	2	340	26.56	294.50	6.69
300	350	500	550	3	340	9.30	257.80	4.45
300	350	550	600	4	340	8.05	446.29	6.03
300	350	600	650	5	340	8.15	790.71	5.46
350	400	450	500	1	750	128.67	161.69	9.68
350	400	500	550	2	750	29.80	149.79	5.91
350	400	550	600	3	750	21.12	265.40	7.06
350	400	600	650	4	750	18.74	470.99	7.10
350	400	650	700	5	750	12.21	537.02	6.34
400	450	500	550	1	470	50.87	102.01	6.10
400	450	550	600	2	470	22.36	179.35	6.15
400	450	600	650	3	470	17.71	355.13	6.49
400	450	650	700	4	470	9.42	377.79	5.52
400	450	700	750	5	470	4.20	294.77	5.81
450	500	550	600	1	270	47.22	164.83	6.73
450	500	600	650	2	270	31.66	442.06	7.52
450	500	650	700	3	270	14.36	501.26	6.82
450	500	700	750	4	270	5.60	390.95	7.19
450	500	750	800	5	270	2.70	329.87	5.98
500	550	600	650	1	400	81.17	191.25	6.34
500	550	650	700	2	400	25.87	243.82	5.87
500	550	700	750	3	400	10.61	249.99	6.35
500	550	750	800	4	400	3.92	184.73	3.49
500	550	800	850	5	400	2.23	183.90	1.74
550	600	650	700	1	400	131.40	309.60	9.35
550	600	700	750	2	400	33.80	318.56	9.45
550	600	750	800	3	400	11.98	282.27	7.81
550	600	800	850	4	400	6.41	302.06	6.38
550	600	850	900	5	400	3.97	327.39	7.13
600	650	700	750	1	300	96.77	304.01	8.22
600	650	750	800	2	300	26.04	327.23	6.53
600	650	800	850	3	300	12.32	387.04	5.17
600	650	850	900	4	300	7.15	449.25	4.91
600	650	900	950	5	300	3.73	410.13	5.14

Sagala Line-N2500

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
650	700	750	800	1	170	26.34	146.03	5.85
650	700	800	850	2	170	7.76	172.09	3.59
650	700	850	900	3	170	3.83	212.33	3.86
650	700	900	950	4	170	2.39	265.00	4.18
650	700	950	1000	5	170	2.60	504.50	5.17
700	750	800	850	1	100	8.68	81.81	2.50
700	750	850	900	2	100	3.44	129.68	2.86
700	750	900	950	3	100	1.48	139.49	1.89
700	750	950	1000	4	100	1.53	288.40	2.33
700	750	1000	1050	5	100	0.86	283.69	1.34
750	800	850	900	1	90	4.82	50.47	0.26
750	800	900	950	2	90	1.57	65.76	1.43
750	800	950	1000	3	90	1.36	142.42	1.64
750	800	1000	1050	4	90	0.77	161.27	2.62
750	800	1050	1100	5	90	0.49	179.59	1.44
800	850	900	950	1	160	9.67	56.96	2.20
800	850	950	1000	2	160	5.99	141.14	2.15
800	850	1000	1050	3	160	2.82	166.11	2.60
800	850	1050	1100	4	160	1.78	209.70	1.80
800	850	1100	1150	5	160	0.83	171.12	1.38
850	900	950	1000	1	350	33.47	90.13	6.75
850	900	1000	1050	2	350	12.06	129.90	5.62
850	900	1050	1100	3	350	7.36	198.19	5.57
850	900	1100	1150	4	350	3.13	168.57	3.95
850	900	1150	1200	5	350	2.36	222.42	7.41
900	950	1000	1050	1	270	28.51	99.52	13.50
900	950	1050	1100	2	270	12.23	170.76	6.59
900	950	1100	1150	3	270	4.55	158.82	5.70
900	950	1150	1200	4	270	3.05	212.93	5.45
900	950	1200	1250	5	270	2.23	272.45	5.51
950	1000	1050	1100	1	350	56.83	153.03	10.34
950	1000	1100	1150	2	350	16.08	173.20	6.90
950	1000	1150	1200	3	350	9.51	256.08	7.27
950	1000	1200	1250	4	350	6.63	357.06	7.48
950	1000	1250	1300	5	350	3.67	345.89	5.50
1000	1050	1100	1150	1	320	30.14	88.77	7.06
1000	1050	1150	1200	2	320	10.86	127.94	6.63
1000	1050	1200	1250	3	320	6.27	184.67	5.73
1000	1050	1250	1300	4	320	3.31	194.98	4.64
1000	1050	1300	1350	5	320	2.37	244.31	5.18
1050	1100	1150	1200	1	200	20.39	96.09	6.01
1050	1100	1200	1250	2	200	8.14	153.44	5.77
1050	1100	1250	1300	3	200	3.50	164.93	5.03
1050	1100	1300	1350	4	200	2.14	201.69	2.97
1050	1100	1350	1400	5	200	1.28	211.12	7.89
1100	1150	1200	1250	1	125	9.55	72.01	2.50
1100	1150	1250	1300	2	125	2.83	85.35	1.24
1100	1150	1300	1350	3	125	1.36	102.54	0.06
1100	1150	1350	1400	4	125	0.70	105.56	3.37
1100	1150	1400	1450	5	125	1.15	303.48	2.79
1150	1200	1250	1300	1	100	8.43	79.45	2.26
1150	1200	1300	1350	2	100	2.75	103.67	1.92
1150	1200	1350	1400	3	100	1.17	110.27	1.03
1150	1200	1400	1450	4	100	1.43	269.55	2.91
1150	1200	1450	1500	5	100	0.81	267.19	1.66

Sagala Line-N2500

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
1200	1250	1300	1350	1	80	6.89	81.17	0.42
1200	1250	1350	1400	2	80	2.09	98.49	-1.05
1200	1250	1400	1450	3	80	2.26	266.25	0.32
1200	1250	1450	1500	4	80	1.20	282.74	-1.85
1200	1250	1500	1550	5	80	0.47	193.80	-0.24
1250	1300	1350	1400	1	150	10.58	66.48	2.77
1250	1300	1400	1450	2	150	7.60	191.01	3.76
1250	1300	1450	1500	3	150	3.26	204.83	5.14
1250	1300	1500	1550	4	150	1.29	162.11	2.47
1250	1300	1550	1600	5	150	0.79	173.73	-18.58
1300	1350	1400	1450	1	120	17.09	134.22	4.07
1300	1350	1450	1500	2	120	5.69	178.76	1.82
1300	1350	1500	1550	3	120	1.82	142.94	-1.10
1300	1350	1550	1600	4	120	0.97	152.37	8.91
1300	1350	1600	1650	5	120	1.11	305.13	1.59
1350	1400	1450	1500	1	90	14.67	153.62	0.65
1350	1400	1500	1550	2	90	3.64	152.47	1.39
1350	1400	1550	1600	3	90	1.60	167.55	1.30
1350	1400	1600	1650	4	90	1.56	326.73	-1.55
1350	1400	1650	1700	5	90	0.98	359.19	-0.41
1400	1450	1500	1550	1	120	24.35	191.24	4.13
1400	1450	1550	1600	2	120	8.82	277.09	4.83
1400	1450	1600	1650	3	120	7.47	586.69	2.46
1400	1450	1650	1700	4	120	4.05	636.17	3.67
1400	1450	1700	1750	5	120	3.60	989.60	2.18
1450	1500	1550	1600	1	150	21.67	136.16	5.07
1450	1500	1600	1650	2	150	14.36	360.91	2.78
1450	1500	1650	1700	3	150	6.65	417.83	3.76
1450	1500	1700	1750	4	150	5.75	722.57	2.43
1450	1500	1750	1800	5	150	2.70	593.76	3.44
1500	1550	1600	1650	1	320	71.07	209.32	8.04
1500	1550	1650	1700	2	320	20.08	236.56	5.24
1500	1550	1700	1750	3	320	16.19	476.83	4.12
1500	1550	1750	1800	4	320	7.20	424.11	7.16
1500	1550	1800	1850	5	320	2.58	265.96	1.52
1550	1600	1650	1700	1	500	174.44	328.81	10.57
1550	1600	1700	1750	2	500	88.28	665.62	6.41
1550	1600	1750	1800	3	500	35.60	671.04	9.00
1550	1600	1800	1850	4	500	11.33	427.13	6.86
1550	1600	1850	1900	5	500	6.51	429.49	6.10
1600	1650	1700	1750	1	300	195.08	612.86	12.60
1600	1650	1750	1800	2	300	61.37	771.20	6.64
1600	1650	1800	1850	3	300	18.75	589.05	3.92
1600	1650	1850	1900	4	300	10.04	630.83	3.02
1600	1650	1900	1950	5	300	3.49	383.75	1.38
1650	1700	1750	1800	1	250	192.97	727.48	20.28
1650	1700	1800	1850	2	250	34.60	521.76	9.09
1650	1700	1850	1900	3	250	15.43	581.70	5.64
1650	1700	1900	1950	4	250	4.80	361.91	4.71
1650	1700	1950	2000	5	250	4.20	554.18	6.21
1700	1750	1800	1850	1	200	120.25	566.66	24.44
1700	1750	1850	1900	2	200	28.79	542.68	6.52
1700	1750	1900	1950	3	200	7.84	369.45	3.89
1700	1750	1950	2000	4	200	6.16	580.57	5.53
1750	1800	1850	1900	1	220	151.47	648.90	29.32

Sagala Line-N2500

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
1750	1800	1900	1950	2	220	13.64	233.73	9.70
1750	1800	1950	2000	3	220	8.28	354.71	7.36
1800	1850	1900	1950	1	250	130.88	493.41	32.99
1800	1850	1950	2000	2	250	19.94	300.69	15.18
1850	1900	1950	2000	1	220	286.56	1227.62	34.07

Sagala Line-N2250

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-1000	-950	-900	-850	1	300	35.19	110.55	4.43
-1000	-950	-850	-800	2	300	26.49	332.88	6.52
-1000	-950	-800	-750	3	300	11.56	363.17	6.61
-1000	-950	-750	-700	4	300	4.19	263.27	4.30
-1000	-950	-700	-650	5	300	2.28	250.70	4.12
-950	-900	-850	-800	1	790	170.88	203.86	6.46
-950	-900	-800	-750	2	790	61.80	294.91	6.50
-950	-900	-750	-700	3	790	20.24	241.47	3.56
-950	-900	-700	-650	4	790	10.40	248.15	2.83
-950	-900	-650	-600	5	790	5.90	246.36	4.05
-900	-850	-800	-750	1	500	147.24	277.54	6.78
-900	-850	-750	-700	2	500	33.76	254.54	3.68
-900	-850	-700	-650	3	500	13.67	257.67	2.62
-900	-850	-650	-600	4	500	7.57	285.38	3.95
-900	-850	-600	-550	5	500	6.42	423.55	6.10
-850	-800	-750	-700	1	220	75.66	324.13	5.72
-850	-800	-700	-650	2	220	21.66	371.16	4.25
-850	-800	-650	-600	3	220	10.39	445.11	5.30
-850	-800	-600	-550	4	220	8.08	692.29	6.92
-850	-800	-550	-500	5	220	3.75	562.27	6.99
-800	-750	-700	-650	1	190	45.18	224.11	4.98
-800	-750	-650	-600	2	190	16.51	327.59	6.16
-800	-750	-600	-550	3	190	11.29	560.03	7.89
-800	-750	-550	-500	4	190	4.80	476.20	6.10
-800	-750	-500	-450	5	190	2.59	449.66	4.80
-750	-700	-650	-600	1	330	52.23	149.17	4.39
-750	-700	-600	-550	2	330	27.41	313.13	5.83
-750	-700	-550	-500	3	330	10.17	290.45	4.57
-750	-700	-500	-450	4	330	4.97	283.89	3.20
-750	-700	-450	-400	5	330	3.54	353.86	2.65
-700	-650	-600	-550	1	490	88.68	170.57	6.53
-700	-650	-550	-500	2	490	26.80	206.19	5.28
-700	-650	-500	-450	3	490	11.93	229.46	3.29
-700	-650	-450	-400	4	490	7.82	300.82	3.32
-700	-650	-400	-350	5	490	3.85	259.18	2.28
-650	-600	-550	-500	1	550	84.89	145.47	7.89
-650	-600	-500	-450	2	550	25.92	177.67	5.72
-650	-600	-450	-400	3	550	14.37	246.24	5.39
-650	-600	-400	-350	4	550	6.26	214.54	5.58
-650	-600	-350	-300	5	550	4.35	260.89	4.71
-600	-550	-500	-450	1	920	136.64	139.98	7.50
-600	-550	-450	-400	2	920	58.28	238.82	7.66
-600	-550	-400	-350	3	920	22.15	226.91	7.19
-600	-550	-350	-300	4	920	13.80	282.74	6.72
-600	-550	-300	-250	5	920	9.63	345.28	6.21
-550	-500	-450	-400	1	350	44.74	120.48	6.27
-550	-500	-400	-350	2	350	13.04	140.46	6.02
-550	-500	-350	-300	3	350	6.86	184.73	5.83
-550	-500	-300	-250	4	350	4.53	243.97	5.52
-550	-500	-250	-200	5	350	3.04	286.51	5.39
-500	-450	-400	-350	1	270	21.57	75.29	4.45
-500	-450	-350	-300	2	270	7.82	109.19	4.32
-500	-450	-300	-250	3	270	4.67	163.01	3.93
-500	-450	-250	-200	4	270	2.98	208.04	3.43
-500	-450	-200	-150	5	270	2.78	339.64	2.91

Sagala Line-N2250

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-450	-400	-350	-300	1	390	25.21	60.92	4.55
-450	-400	-300	-250	2	390	11.71	113.19	4.11
-450	-400	-250	-200	3	390	6.74	162.88	4.54
-450	-400	-200	-150	4	390	5.95	287.58	4.27
-450	-400	-150	-100	5	390	3.86	326.48	4.07
-400	-350	-300	-250	1	400	19.87	46.82	3.81
-400	-350	-250	-200	2	400	8.75	82.47	4.10
-400	-350	-200	-150	3	400	6.94	163.52	3.92
-400	-350	-150	-100	4	400	4.30	202.63	3.18
-400	-350	-100	-50	5	400	2.80	230.91	5.47
-350	-300	-250	-200	1	530	29.78	52.96	8.66
-350	-300	-200	-150	2	530	15.48	110.11	3.99
-350	-300	-150	-100	3	530	8.71	154.89	3.41
-350	-300	-100	-50	4	530	5.25	186.72	4.88
-350	-300	-50	0	5	530	3.85	239.62	4.55
-300	-250	-200	-150	1	750	48.73	61.24	3.83
-300	-250	-150	-100	2	750	21.75	109.33	3.14
-300	-250	-100	-50	3	750	11.02	138.48	5.05
-300	-250	-50	0	4	750	7.66	192.52	4.35
-300	-250	0	50	5	750	3.64	160.10	4.14
-250	-200	-150	-100	1	310	27.99	85.10	2.70
-250	-200	-100	-50	2	310	10.05	122.22	4.44
-250	-200	-50	0	3	310	5.63	171.17	4.07
-250	-200	0	50	4	310	2.45	148.97	3.58
-250	-200	50	100	5	310	1.53	162.81	4.19
-200	-150	-100	-50	1	250	23.19	87.42	4.02
-200	-150	-50	0	2	250	9.92	149.59	2.92
-200	-150	0	50	3	250	3.98	150.04	4.13
-200	-150	50	100	4	250	2.27	171.15	3.52
-200	-150	100	150	5	250	2.02	266.53	3.34
-150	-100	-50	0	1	390	31.16	75.30	2.99
-150	-100	0	50	2	390	10.02	96.86	2.60
-150	-100	50	100	3	390	4.92	118.90	3.12
-150	-100	100	150	4	390	4.00	193.33	2.78
-150	-100	150	200	5	390	3.31	279.96	3.10
-100	-50	0	50	1	650	49.11	71.21	3.26
-100	-50	50	100	2	650	17.40	100.92	4.14
-100	-50	100	150	3	650	11.66	169.07	4.45
-100	-50	150	200	4	650	8.49	246.20	3.69
-100	-50	200	250	5	650	7.42	376.56	4.54
-50	0	50	100	1	990	65.81	62.65	3.61
-50	0	100	150	2	990	31.76	120.94	3.69
-50	0	150	200	3	990	20.09	191.26	2.96
-50	0	200	250	4	990	16.38	311.87	3.26
-50	0	250	300	5	990	8.32	277.22	3.70
0	50	100	150	1	1450	81.59	53.03	3.40
0	50	150	200	2	1450	38.49	100.07	2.87
0	50	200	250	3	1450	26.59	172.83	2.86
0	50	250	300	4	1450	13.03	169.39	3.26
0	50	300	350	5	1450	9.86	224.31	3.33
50	100	150	200	1	820	60.30	69.31	3.03
50	100	200	250	2	820	29.95	137.69	3.08
50	100	250	300	3	820	13.08	150.34	3.48
50	100	300	350	4	820	8.60	197.69	3.45
50	100	350	400	5	820	5.50	221.25	3.68

Sagala Line-N2250

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
100	150	200	250	1	620	67.23	102.20	3.14
100	150	250	300	2	620	20.41	124.10	3.54
100	150	300	350	3	620	11.85	180.13	3.29
100	150	350	400	4	620	6.83	207.65	3.95
100	150	400	450	5	620	5.04	268.15	3.85
150	200	250	300	1	500	49.05	92.46	2.81
150	200	300	350	2	500	19.57	147.55	2.74
150	200	350	400	3	500	10.69	201.50	2.93
150	200	400	450	4	500	6.45	243.16	3.85
150	200	450	500	5	500	4.92	324.59	3.43
200	250	300	350	1	340	29.27	81.14	2.34
200	250	350	400	2	340	12.32	136.60	2.44
200	250	400	450	3	340	6.20	171.86	2.78
200	250	450	500	4	340	4.38	242.83	2.78
200	250	500	550	5	340	4.60	446.29	3.11
250	300	350	400	1	400	25.30	59.61	2.69
250	300	400	450	2	400	9.37	88.31	2.90
250	300	450	500	3	400	5.52	130.06	2.74
250	300	500	550	4	400	5.09	239.86	2.99
250	300	550	600	5	400	3.20	263.89	3.28
300	350	400	450	1	850	52.67	58.40	3.09
300	350	450	500	2	850	23.65	104.89	3.13
300	350	500	550	3	850	18.59	206.13	2.92
300	350	550	600	4	850	10.47	232.18	3.18
300	350	600	650	5	850	9.83	381.48	3.03
350	400	450	500	1	1400	81.13	54.62	3.38
350	400	500	550	2	1400	54.35	146.35	3.23
350	400	550	600	3	1400	22.85	153.83	3.30
350	400	600	650	4	1400	21.21	285.57	3.58
350	400	650	700	5	1400	13.69	322.56	3.87
400	450	500	550	1	1200	108.81	85.46	2.86
400	450	550	600	2	1200	35.90	112.78	2.80
400	450	600	650	3	1200	26.26	206.25	3.01
400	450	650	700	4	1200	15.24	239.39	3.37
400	450	700	750	5	1200	6.28	172.63	3.93
450	500	550	600	1	1200	118.19	92.83	2.77
450	500	600	650	2	1200	52.19	163.96	2.68
450	500	650	700	3	1200	24.76	194.46	2.96
450	500	700	750	4	1200	9.29	145.93	3.91
450	500	750	800	5	1200	9.09	249.87	4.49
500	550	600	650	1	900	173.29	181.47	2.63
500	550	650	700	2	900	60.58	253.76	2.54
500	550	700	750	3	900	18.79	196.77	3.12
500	550	750	800	4	900	17.28	361.91	4.62
500	550	800	850	5	900	11.28	413.43	4.22
550	600	650	700	1	930	194.60	197.21	2.71
550	600	700	750	2	930	40.56	164.42	3.41
550	600	750	800	3	930	25.03	253.66	3.98
550	600	800	850	4	930	13.59	275.45	3.74
550	600	850	900	5	930	10.03	355.76	4.22
600	650	700	750	1	1200	188.42	147.98	3.28
600	650	750	800	2	1200	86.69	272.34	3.93
600	650	800	850	3	1200	39.92	313.53	3.76
600	650	850	900	4	1200	27.12	426.00	4.09
600	650	900	950	5	1200	30.46	837.31	4.04

Sagala Line-N2250

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
650	700	750	800	1	1300	183.54	133.06	3.87
650	700	800	850	2	1300	60.68	175.97	3.46
650	700	850	900	3	1300	36.56	265.05	3.81
650	700	900	950	4	1300	39.68	575.35	3.62
650	700	950	1000	5	1300	25.68	651.61	3.18
700	750	800	850	1	800	75.10	88.48	3.42
700	750	850	900	2	800	31.56	148.72	3.55
700	750	900	950	3	800	28.09	330.93	3.27
700	750	950	1000	4	800	15.32	360.97	3.84
700	750	1000	1050	5	800	10.25	422.64	3.59
750	800	850	900	1	650	93.88	136.12	4.50
750	800	900	950	2	650	61.95	359.30	3.85
750	800	950	1000	3	650	28.80	417.59	3.93
750	800	1000	1050	4	650	17.94	520.25	3.63
750	800	1050	1100	5	650	6.76	343.06	4.93
800	850	900	950	1	750	183.60	230.72	4.12
800	850	950	1000	2	750	56.66	284.80	3.69
800	850	1000	1050	3	750	29.61	372.09	3.35
800	850	1050	1100	4	750	10.30	258.87	4.89
800	850	1100	1150	5	750	5.71	251.14	4.76
850	900	950	1000	1	1000	229.03	215.86	3.98
850	900	1000	1050	2	1000	88.11	332.17	3.60
850	900	1050	1100	3	1000	25.88	243.91	5.29
850	900	1100	1150	4	1000	12.28	231.47	5.68
850	900	1150	1200	5	1000	9.91	326.90	4.69
900	950	1000	1050	1	1850	1275.55	649.83	3.61
900	950	1050	1100	2	1850	261.98	533.86	4.94
900	950	1100	1150	3	1850	86.91	442.76	5.15
900	950	1150	1200	4	1850	73.02	744.00	3.82
900	950	1200	1250	5	1850	37.26	664.37	4.24
950	1000	1050	1100	1	1200	318.39	250.06	4.25
950	1000	1100	1150	2	1200	90.80	285.26	4.52
950	1000	1150	1200	3	1200	66.91	525.51	3.38
950	1000	1200	1250	4	1200	33.25	522.29	3.68
950	1000	1250	1300	5	1200	15.72	432.13	3.42
1000	1050	1100	1150	1	660	91.91	131.25	4.30
1000	1050	1150	1200	2	660	59.88	342.03	2.96
1000	1050	1200	1250	3	660	26.65	380.56	3.25
1000	1050	1250	1300	4	660	11.66	333.01	2.86
1000	1050	1300	1350	5	660	6.63	331.37	3.95
1050	1100	1150	1200	1	960	108.24	106.26	4.53
1050	1100	1200	1250	2	960	37.84	148.60	4.90
1050	1100	1250	1300	3	960	14.29	140.29	4.34
1050	1100	1300	1350	4	960	6.96	136.66	5.72
1050	1100	1350	1400	5	960	7.69	264.24	6.00
1100	1150	1200	1250	1	1900	229.87	114.02	4.20
1100	1150	1250	1300	2	1900	66.58	132.11	3.63
1100	1150	1300	1350	3	1900	29.94	148.51	4.52
1100	1150	1350	1400	4	1900	27.92	276.99	4.65
1100	1150	1400	1450	5	1900	29.98	520.50	5.74
1150	1200	1250	1300	1	300	28.47	89.44	1.90
1150	1200	1300	1350	2	300	9.32	117.12	2.39
1150	1200	1350	1400	3	300	8.44	265.15	2.82
1150	1200	1400	1450	4	300	8.49	533.44	4.03
1150	1200	1450	1500	5	300	4.71	517.89	3.95

Sagala Line-N2250

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
1200	1250	1300	1350	1	210	11.20	50.27	3.45
1200	1250	1350	1400	2	210	7.69	138.05	3.36
1200	1250	1400	1450	3	210	7.01	314.61	4.53
1200	1250	1450	1500	4	210	3.75	336.60	4.65
1200	1250	1500	1550	5	210	2.34	367.57	5.12
1250	1300	1350	1400	1	300	18.43	57.90	3.44
1250	1300	1400	1450	2	300	13.02	163.61	4.67
1250	1300	1450	1500	3	300	6.15	193.21	4.77
1250	1300	1500	1550	4	300	3.61	226.82	5.12
1250	1300	1550	1600	5	300	1.83	201.22	2.81
1300	1350	1400	1450	1	270	32.51	113.48	5.70
1300	1350	1450	1500	2	270	10.08	140.74	5.14
1300	1350	1500	1550	3	270	4.94	172.44	5.21
1300	1350	1550	1600	4	270	2.28	159.17	2.83
1300	1350	1600	1650	5	270	2.53	309.10	4.35
1350	1400	1450	1500	1	220	32.99	141.33	7.21
1350	1400	1500	1550	2	220	11.07	189.70	6.57
1350	1400	1550	1600	3	220	4.33	185.50	4.57
1350	1400	1600	1650	4	220	4.24	363.28	5.13
1350	1400	1650	1700	5	220	3.40	509.79	4.75
1400	1450	1500	1550	1	270	52.63	183.71	8.31
1400	1450	1550	1600	2	270	13.06	182.35	5.64
1400	1450	1600	1650	3	270	11.31	394.79	6.14
1400	1450	1650	1700	4	270	8.31	580.15	6.31
1400	1450	1700	1750	5	270	4.04	493.58	5.58
1450	1500	1550	1600	1	370	34.92	88.95	6.91
1450	1500	1600	1650	2	370	20.09	204.70	6.99
1450	1500	1650	1700	3	370	14.00	356.61	7.61
1450	1500	1700	1750	4	370	5.83	297.01	4.80
1450	1500	1750	1800	5	370	5.20	463.60	6.86
1500	1550	1600	1650	1	300	31.68	99.53	7.62
1500	1550	1650	1700	2	300	16.56	208.10	7.56
1500	1550	1700	1750	3	300	6.07	190.69	4.01
1500	1550	1750	1800	4	300	5.06	317.93	6.48
1500	1550	1800	1850	5	300	3.62	398.04	5.28
1550	1600	1650	1700	1	380	66.66	165.33	14.93
1550	1600	1700	1750	2	380	12.88	127.78	4.14
1550	1600	1750	1800	3	380	9.02	223.71	6.71
1550	1600	1800	1850	4	380	6.01	298.12	5.72
1550	1600	1850	1900	5	380	6.79	589.42	6.83
1600	1650	1700	1750	1	550	82.22	140.89	12.15
1600	1650	1750	1800	2	550	34.59	237.09	8.11
1600	1650	1800	1850	3	550	20.98	359.51	7.66
1600	1650	1850	1900	4	550	21.67	742.67	7.85
1600	1650	1900	1950	5	550	8.79	527.19	8.23
1650	1700	1750	1800	1	850	101.46	112.50	9.66
1650	1700	1800	1850	2	850	42.12	186.81	7.20
1650	1700	1850	1900	3	850	38.48	426.67	7.74
1650	1700	1900	1950	4	850	14.54	322.44	7.21
1650	1700	1950	2000	5	850	9.06	351.60	7.48
1700	1750	1800	1850	1	1200	173.54	136.30	7.29
1700	1750	1850	1900	2	1200	97.38	305.93	7.48
1700	1750	1900	1950	3	1200	31.26	245.52	6.91
1700	1750	1950	2000	4	1200	18.22	286.20	7.87
1750	1800	1850	1900	1	850	229.42	254.38	9.24

Sagala Line-N2250

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
1750	1800	1900	1950	2	850	60.29	267.40	9.06
1750	1800	1950	2000	3	850	24.91	276.20	9.37
1800	1850	1900	1950	1	500	119.54	225.33	8.73
1800	1850	1950	2000	2	500	28.59	215.56	6.32
1850	1900	1950	2000	1	300	49.59	155.79	6.11

Sagala Line-N2000

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-1000	-950	-900	-850	1	990	212.47	202.27	7.05
-1000	-950	-850	-800	2	990	106.56	405.78	7.26
-1000	-950	-800	-750	3	990	75.27	716.57	8.71
-1000	-950	-750	-700	4	990	32.47	618.23	6.76
-1000	-950	-700	-650	5	990	14.08	469.14	5.24
-950	-900	-850	-800	1	850	231.91	257.14	8.10
-950	-900	-800	-750	2	850	118.20	524.24	9.36
-950	-900	-750	-700	3	850	42.64	472.79	7.06
-950	-900	-700	-650	4	850	16.36	362.80	4.56
-950	-900	-650	-600	5	850	16.72	648.87	6.70
-900	-850	-800	-750	1	500	118.72	223.78	8.01
-900	-850	-750	-700	2	500	32.92	248.21	5.80
-900	-850	-700	-650	3	500	10.80	203.58	3.63
-900	-850	-650	-600	4	500	10.48	395.09	5.48
-900	-850	-600	-550	5	500	4.43	292.26	5.83
-850	-800	-750	-700	1	420	82.59	185.33	5.86
-850	-800	-700	-650	2	420	20.14	180.78	3.86
-850	-800	-650	-600	3	420	16.67	374.07	5.56
-850	-800	-600	-550	4	420	6.45	289.48	5.29
-850	-800	-550	-500	5	420	5.23	410.76	4.89
-800	-750	-700	-650	1	350	49.76	133.99	5.26
-800	-750	-650	-600	2	350	37.06	399.18	7.53
-800	-750	-600	-550	3	350	11.26	303.21	7.73
-800	-750	-550	-500	4	350	7.58	408.23	6.22
-800	-750	-500	-450	5	350	9.41	886.87	7.08
-750	-700	-650	-600	1	320	58.60	172.59	6.42
-750	-700	-600	-550	2	320	13.90	163.76	7.14
-750	-700	-550	-500	3	320	7.61	224.13	5.31
-750	-700	-500	-450	4	320	9.29	547.23	6.10
-750	-700	-450	-400	5	320	6.79	699.94	5.18
-700	-650	-600	-550	1	300	27.19	85.42	5.26
-700	-650	-550	-500	2	300	9.49	119.25	3.95
-700	-650	-500	-450	3	300	8.69	273.00	4.63
-700	-650	-450	-400	4	300	6.14	385.79	4.06
-700	-650	-400	-350	5	300	5.21	572.87	4.15
-650	-600	-550	-500	1	350	41.21	110.97	5.59
-650	-600	-500	-450	2	350	25.78	277.68	5.82
-650	-600	-450	-400	3	350	15.99	430.58	4.99
-650	-600	-400	-350	4	350	12.98	699.05	5.38
-650	-600	-350	-300	5	350	4.40	414.69	5.56
-600	-550	-500	-450	1	530	72.28	128.53	5.93
-600	-550	-450	-400	2	530	30.57	217.45	5.17
-600	-550	-400	-350	3	530	22.48	399.75	5.55
-600	-550	-350	-300	4	530	6.85	243.62	5.80
-600	-550	-300	-250	5	530	4.04	251.45	7.60
-550	-500	-450	-400	1	660	122.18	174.47	4.24
-550	-500	-400	-350	2	660	75.22	429.66	4.26
-550	-500	-350	-300	3	660	20.93	298.88	4.55
-550	-500	-300	-250	4	660	10.61	303.02	5.85
-550	-500	-250	-200	5	660	5.36	267.89	7.02
-500	-450	-400	-350	1	890	305.53	323.55	4.96
-500	-450	-350	-300	2	890	76.32	323.28	5.26
-500	-450	-300	-250	3	890	35.27	373.50	7.14
-500	-450	-250	-200	4	890	16.48	349.03	3.68
-500	-450	-200	-150	5	890	11.79	436.98	4.88

Sagala Line-N2000

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-450	-400	-350	-300	1	680	122.13	169.27	5.47
-450	-400	-300	-250	2	680	35.91	199.08	6.80
-450	-400	-250	-200	3	680	14.96	207.35	4.76
-450	-400	-200	-150	4	680	10.22	283.30	4.58
-450	-400	-150	-100	5	680	15.00	727.65	5.57
-400	-350	-300	-250	1	300	58.34	183.28	5.95
-400	-350	-250	-200	2	300	14.57	183.09	3.59
-400	-350	-200	-150	3	300	8.22	258.24	3.69
-400	-350	-150	-100	4	300	11.39	715.65	4.72
-400	-350	-100	-50	5	300	5.42	595.96	5.59
-350	-300	-250	-200	1	240	19.68	77.28	3.73
-350	-300	-200	-150	2	240	6.49	101.94	3.42
-350	-300	-150	-100	3	240	7.79	305.91	4.90
-350	-300	-100	-50	4	240	3.55	278.82	4.16
-350	-300	-50	0	5	240	1.60	219.91	7.64
-300	-250	-200	-150	1	180	14.97	78.38	5.26
-300	-250	-150	-100	2	180	12.52	262.22	6.32
-300	-250	-100	-50	3	180	5.07	265.46	6.50
-300	-250	-50	0	4	180	1.99	208.39	4.64
-300	-250	0	50	5	180	1.21	221.74	3.40
-250	-200	-150	-100	1	130	14.56	105.56	4.32
-250	-200	-100	-50	2	130	4.78	138.62	4.62
-250	-200	-50	0	3	130	1.60	116.00	3.57
-250	-200	0	50	4	130	0.90	130.50	2.99
-250	-200	50	100	5	130	1.15	291.81	7.57
-200	-150	-100	-50	1	170	20.61	114.26	5.47
-200	-150	-50	0	2	170	4.39	97.35	3.43
-200	-150	0	50	3	170	2.15	119.20	3.95
-200	-150	50	100	4	170	2.64	292.72	4.38
-200	-150	100	150	5	170	2.10	407.48	5.50
-150	-100	-50	0	1	250	26.07	98.28	5.07
-150	-100	0	50	2	250	9.90	149.29	4.70
-150	-100	50	100	3	250	11.78	444.10	7.03
-150	-100	100	150	4	250	8.84	666.52	7.74
-150	-100	150	200	5	250	5.54	730.99	5.84
-100	-50	0	50	1	260	12.78	46.33	4.55
-100	-50	50	100	2	260	11.62	168.49	4.64
-100	-50	100	150	3	260	8.06	292.17	10.29
-100	-50	150	200	4	260	4.84	350.89	6.21
-100	-50	200	250	5	260	2.38	301.96	6.73
-50	0	50	100	1	280	21.31	71.73	6.76
-50	0	100	150	2	280	11.81	159.01	5.91
-50	0	150	200	3	280	6.30	212.06	3.60
-50	0	200	250	4	280	2.88	193.88	5.71
-50	0	250	300	5	280	3.67	432.36	4.89
0	50	100	150	1	190	17.84	88.49	6.04
0	50	150	200	2	190	6.95	137.90	4.94
0	50	200	250	3	190	2.75	136.41	3.14
0	50	250	300	4	190	3.40	337.31	5.77
0	50	300	350	5	190	1.60	277.78	7.30
50	100	150	200	1	150	24.17	151.86	7.54
50	100	200	250	2	150	5.89	148.03	4.17
50	100	250	300	3	150	7.05	442.96	6.24
50	100	300	350	4	150	3.33	418.46	6.88
50	100	350	400	5	150	1.33	292.48	5.82

Sagala Line-N2000

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
100	150	200	250	1	150	14.10	88.59	4.19
100	150	250	300	2	150	13.64	342.81	6.60
100	150	300	350	3	150	6.18	388.30	8.35
100	150	350	400	4	150	2.12	266.41	4.82
100	150	400	450	5	150	1.32	290.28	5.37
150	200	250	300	1	200	38.16	179.82	5.51
150	200	300	350	2	200	13.78	259.75	6.69
150	200	350	400	3	200	4.19	197.45	3.71
150	200	400	450	4	200	2.38	224.31	3.66
150	200	450	500	5	200	2.15	354.61	3.99
200	250	300	350	1	250	38.63	145.63	6.04
200	250	350	400	2	250	8.77	132.25	2.51
200	250	400	450	3	250	4.18	157.58	2.32
200	250	450	500	4	250	2.92	220.16	1.15
200	250	500	550	5	250	2.70	356.26	-1.15
250	300	350	400	1	200	36.76	173.23	6.72
250	300	400	450	2	200	14.40	271.43	5.98
250	300	450	500	3	200	8.08	380.76	4.94
250	300	500	550	4	200	6.97	656.91	5.30
250	300	550	600	5	200	5.12	844.46	5.86
300	350	400	450	1	170	17.41	96.52	5.75
300	350	450	500	2	170	7.55	167.43	5.29
300	350	500	550	3	170	5.99	332.08	6.05
300	350	550	600	4	170	4.22	467.91	6.27
300	350	600	650	5	170	2.50	485.10	2.53
350	400	450	500	1	120	8.84	69.43	2.45
350	400	500	550	2	120	5.39	169.33	2.78
350	400	550	600	3	120	3.43	269.39	2.74
350	400	600	650	4	120	1.78	279.60	2.84
350	400	650	700	5	120	1.64	450.82	-0.10
400	450	500	550	1	130	15.58	112.95	1.71
400	450	550	600	2	130	7.57	219.52	3.14
400	450	600	650	3	130	3.72	269.69	9.54
400	450	650	700	4	130	3.11	450.94	-4.03
400	450	700	750	5	130	1.94	492.26	0.47
450	500	550	600	1	330	74.62	213.11	6.15
450	500	600	650	2	330	32.39	370.02	6.67
450	500	650	700	3	330	21.21	605.76	6.51
450	500	700	750	4	330	11.81	674.59	4.67
450	500	750	800	5	330	4.60	459.81	4.26
500	550	600	650	1	300	64.30	202.00	7.02
500	550	650	700	2	300	33.89	425.87	6.85
500	550	700	750	3	300	17.52	550.41	5.11
500	550	750	800	4	300	6.45	405.27	4.91
500	550	800	850	5	300	3.84	422.23	4.32
550	600	650	700	1	280	77.16	259.72	6.87
550	600	700	750	2	280	31.05	418.06	4.98
550	600	750	800	3	280	10.61	357.13	5.16
550	600	800	850	4	280	5.51	370.93	6.16
550	600	850	900	5	280	4.72	556.06	6.58
600	650	700	750	1	380	106.06	263.05	7.38
600	650	750	800	2	380	23.74	235.52	7.19
600	650	800	850	3	380	9.65	239.34	8.47
600	650	850	900	4	380	7.41	367.57	8.68
600	650	900	950	5	380	3.81	330.74	6.41

Sagala Line-N2000

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
650	700	750	800	1	840	277.56	311.42	6.38
650	700	800	850	2	840	75.75	339.97	8.08
650	700	850	900	3	840	48.30	541.92	8.27
650	700	900	950	4	840	21.27	477.30	6.30
650	700	950	1000	5	840	12.89	506.19	5.18
700	750	800	850	1	420	91.79	205.98	6.99
700	750	850	900	2	420	43.53	390.72	7.17
700	750	900	950	3	420	14.34	321.79	4.84
700	750	950	1000	4	420	7.75	347.82	3.31
700	750	1000	1050	5	420	7.60	596.90	4.14
750	800	850	900	1	300	50.87	159.81	7.39
750	800	900	950	2	300	12.04	151.30	4.62
750	800	950	1000	3	300	5.46	171.53	3.82
750	800	1000	1050	4	300	4.76	299.08	3.80
750	800	1050	1100	5	300	3.73	410.13	5.18
800	850	900	950	1	250	30.31	114.27	6.79
800	850	950	1000	2	250	8.82	133.00	4.49
800	850	1000	1050	3	250	6.53	246.18	5.06
800	850	1050	1100	4	250	4.31	324.97	4.98
800	850	1100	1150	5	250	1.21	159.66	4.15
850	900	950	1000	1	210	24.21	108.65	5.34
850	900	1000	1050	2	210	12.05	216.32	6.07
850	900	1050	1100	3	210	7.02	315.06	5.81
850	900	1100	1150	4	210	1.76	157.98	5.81
850	900	1150	1200	5	210	2.34	367.57	5.81
900	950	1000	1050	1	320	47.81	140.81	4.79
900	950	1050	1100	2	320	22.71	267.55	4.21
900	950	1100	1150	3	320	4.55	134.01	3.04
900	950	1150	1200	4	320	4.84	285.10	1.27
900	950	1200	1250	5	320	3.66	377.29	3.34
950	1000	1050	1100	1	500	99.06	186.72	5.55
950	1000	1100	1150	2	500	16.46	124.11	4.19
950	1000	1150	1200	3	500	17.41	328.17	3.55
950	1000	1200	1250	4	500	9.15	344.95	5.69
950	1000	1250	1300	5	500	3.63	239.48	2.35
1000	1050	1100	1150	1	530	79.12	140.70	4.46
1000	1050	1150	1200	2	530	44.01	313.04	4.04
1000	1050	1200	1250	3	530	24.79	440.83	6.12
1000	1050	1250	1300	4	530	10.90	387.66	5.00
1000	1050	1300	1350	5	530	5.52	343.56	3.82
1050	1100	1150	1200	1	820	145.71	167.47	5.09
1050	1100	1200	1250	2	820	71.05	326.65	6.79
1050	1100	1250	1300	3	820	29.44	338.37	5.27
1050	1100	1300	1350	4	820	14.06	323.20	4.86
1050	1100	1350	1400	5	820	7.45	299.70	7.03
1100	1150	1200	1250	1	460	81.63	167.25	7.23
1100	1150	1250	1300	2	460	21.08	172.76	5.87
1100	1150	1300	1350	3	460	8.07	165.34	5.63
1100	1150	1350	1400	4	460	3.64	149.16	4.99
1100	1150	1400	1450	5	460	3.03	217.28	5.34
1150	1200	1250	1300	1	320	83.58	246.16	6.09
1150	1200	1300	1350	2	320	20.96	246.93	4.74
1150	1200	1350	1400	3	320	7.51	221.19	3.65
1150	1200	1400	1450	4	320	5.22	307.48	4.00
1150	1200	1450	1500	5	320	3.50	360.79	4.73

Sagala Line-N2000

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
1200	1250	1300	1350	1	180	27.48	143.88	5.03
1200	1250	1350	1400	2	180	7.14	149.54	3.90
1200	1250	1400	1450	3	180	4.09	214.15	3.89
1200	1250	1450	1500	4	180	2.54	265.99	4.56
1200	1250	1500	1550	5	180	1.87	342.70	3.98
1250	1300	1350	1400	1	120	9.57	75.16	2.91
1250	1300	1400	1450	2	120	3.51	110.27	2.47
1250	1300	1450	1500	3	120	1.82	142.94	2.72
1250	1300	1500	1550	4	120	1.21	190.07	3.00
1250	1300	1550	1600	5	120	0.81	222.66	1.54
1300	1350	1400	1450	1	70	3.11	41.87	-0.75
1300	1350	1450	1500	2	70	1.11	59.78	-0.05
1300	1350	1500	1550	3	70	0.60	80.78	0.31
1300	1350	1550	1600	4	70	0.38	102.33	1.47
1300	1350	1600	1650	5	70	0.28	131.95	8.44
1350	1400	1450	1500	1	90	3.83	40.11	1.64
1350	1400	1500	1550	2	90	1.50	62.83	2.41
1350	1400	1550	1600	3	90	0.84	87.96	3.25
1350	1400	1600	1650	4	90	0.57	119.38	3.86
1350	1400	1650	1700	5	90	0.40	146.61	7.22
1400	1450	1500	1550	1	500	23.27	43.86	4.21
1400	1450	1550	1600	2	500	10.49	79.09	3.71
1400	1450	1600	1650	3	500	6.46	121.77	3.40
1400	1450	1650	1700	4	500	4.28	161.35	3.24
1400	1450	1700	1750	5	500	2.88	190.00	3.79
1450	1500	1550	1600	1	930	36.57	37.06	4.08
1450	1500	1600	1650	2	930	18.02	73.05	3.87
1450	1500	1650	1700	3	930	10.86	110.06	4.01
1450	1500	1700	1750	4	930	6.87	139.24	4.55
1450	1500	1750	1800	5	930	4.63	164.22	2.66
1500	1550	1600	1650	1	1200	52.54	41.26	3.97
1500	1550	1650	1700	2	1200	24.39	76.62	3.98
1500	1550	1700	1750	3	1200	13.13	103.12	4.20
1500	1550	1750	1800	4	1200	8.63	135.56	4.08
1500	1550	1800	1850	5	1200	7.31	200.94	3.78
1550	1600	1650	1700	1	1700	70.46	39.06	3.87
1550	1600	1700	1750	2	1700	29.81	66.11	3.72
1550	1600	1750	1800	3	1700	17.95	99.51	3.68
1550	1600	1800	1850	4	1700	14.21	157.56	3.96
1550	1600	1850	1900	5	1700	9.60	186.28	5.38
1600	1650	1700	1750	1	1500	52.48	32.97	3.61
1600	1650	1750	1800	2	1500	25.20	63.33	3.57
1600	1650	1800	1850	3	1500	17.55	110.27	3.77
1600	1650	1850	1900	4	1500	10.70	134.46	4.65
1600	1650	1900	1950	5	1500	8.54	187.80	5.23
1650	1700	1750	1800	1	1200	51.28	40.28	3.96
1650	1700	1800	1850	2	1200	25.17	79.07	3.38
1650	1700	1850	1900	3	1200	13.03	102.34	4.89
1650	1700	1900	1950	4	1200	9.55	150.01	4.80
1650	1700	1950	2000	5	1200	7.75	213.04	4.60
1700	1750	1800	1850	1	1500	76.57	48.11	3.85
1700	1750	1850	1900	2	1500	27.37	68.79	4.69
1700	1750	1900	1950	3	1500	17.55	110.27	4.90
1700	1750	1950	2000	4	1500	13.18	165.62	4.47
1750	1800	1850	1900	1	2100	105.11	47.17	4.47

Sagala Line-N2000

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
1750	1800	1900	1950	2	2100	46.48	83.44	4.77
1750	1800	1950	2000	3	2100	31.39	140.88	4.47
1800	1850	1900	1950	1	400	25.87	60.95	4.26
1800	1850	1950	2000	2	400	13.27	125.07	4.10
1850	1900	1950	2000	1	150	11.78	74.02	3.82

Sagala Line-N1750

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-1000	-950	-900	-850	1	300	47.93	150.58	5.89
-1000	-950	-850	-800	2	300	26.16	328.74	6.92
-1000	-950	-800	-750	3	300	11.27	354.06	6.33
-1000	-950	-750	-700	4	300	6.30	395.84	7.15
-1000	-950	-700	-650	5	300	3.00	329.87	4.74
-950	-900	-850	-800	1	460	146.08	299.30	7.35
-950	-900	-800	-750	2	460	34.21	280.37	5.11
-950	-900	-750	-700	3	460	16.26	333.15	5.94
-950	-900	-700	-650	4	460	7.62	312.25	4.98
-950	-900	-650	-600	5	460	10.08	722.84	4.71
-900	-850	-800	-750	1	500	132.99	250.68	3.95
-900	-850	-750	-700	2	500	40.04	301.89	4.67
-900	-850	-700	-650	3	500	16.21	305.55	4.50
-900	-850	-650	-600	4	500	20.06	756.24	3.14
-900	-850	-600	-550	5	500	9.87	651.16	6.21
-850	-800	-750	-700	1	270	47.68	166.43	4.98
-850	-800	-700	-650	2	270	15.91	222.15	3.82
-850	-800	-650	-600	3	270	17.20	600.39	3.83
-850	-800	-600	-550	4	270	7.96	555.71	5.62
-850	-800	-550	-500	5	270	4.21	514.35	4.92
-800	-750	-700	-650	1	220	45.87	196.51	3.95
-800	-750	-650	-600	2	220	26.28	450.33	4.13
-800	-750	-600	-550	3	220	9.56	409.55	4.94
-800	-750	-550	-500	4	220	5.12	438.68	5.38
-800	-750	-500	-450	5	220	6.27	940.12	4.80
-750	-700	-650	-600	1	350	108.40	291.90	3.99
-750	-700	-600	-550	2	350	27.86	300.08	5.56
-750	-700	-550	-500	3	350	10.24	275.74	5.18
-750	-700	-500	-450	4	350	10.74	578.41	4.28
-750	-700	-450	-400	5	350	6.49	611.67	3.76
-700	-650	-600	-550	1	650	150.18	217.76	4.05
-700	-650	-550	-500	2	650	35.33	204.91	3.50
-700	-650	-500	-450	3	650	29.40	426.29	2.65
-700	-650	-450	-400	4	650	17.65	511.84	3.11
-700	-650	-400	-350	5	650	5.84	296.37	4.68
-650	-600	-550	-500	1	250	67.81	255.64	2.43
-650	-600	-500	-450	2	250	39.53	596.10	2.57
-650	-600	-450	-400	3	250	15.47	583.21	2.83
-650	-600	-400	-350	4	250	6.14	462.95	4.52
-650	-600	-350	-300	5	250	3.69	486.88	5.51
-600	-550	-500	-450	1	170	35.51	196.87	2.38
-600	-550	-450	-400	2	170	14.25	316.01	2.56
-600	-550	-400	-350	3	170	4.17	231.18	4.89
-600	-550	-350	-300	4	170	2.80	310.46	5.32
-600	-550	-300	-250	5	170	1.46	283.30	1.88
-550	-500	-450	-400	1	270	61.24	213.77	2.69
-550	-500	-400	-350	2	270	13.41	187.24	5.29
-550	-500	-350	-300	3	270	6.62	231.08	5.20
-550	-500	-300	-250	4	270	3.18	222.01	3.71
-550	-500	-250	-200	5	270	4.50	549.78	5.66
-500	-450	-400	-350	1	360	118.97	311.46	3.70
-500	-450	-350	-300	2	360	32.30	338.24	3.95
-500	-450	-300	-250	3	360	14.48	379.09	2.59
-500	-450	-250	-200	4	360	15.49	811.05	4.39
-500	-450	-200	-150	5	360	9.20	842.99	3.12

Sagala Line-N1750

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-450	-400	-350	-300	1	400	60.51	142.57	3.71
-450	-400	-300	-250	2	400	21.57	203.29	2.34
-450	-400	-250	-200	3	400	20.50	483.02	4.09
-450	-400	-200	-150	4	400	11.43	538.63	2.74
-450	-400	-150	-100	5	400	9.24	761.99	1.98
-400	-350	-300	-250	1	300	25.32	79.55	3.32
-400	-350	-250	-200	2	300	20.37	255.98	5.78
-400	-350	-200	-150	3	300	7.67	240.96	4.44
-400	-350	-150	-100	4	300	5.70	358.14	3.51
-400	-350	-100	-50	5	300	4.54	499.20	6.57
-350	-300	-250	-200	1	260	47.66	172.76	6.25
-350	-300	-200	-150	2	260	12.31	178.49	5.35
-350	-300	-150	-100	3	260	7.80	282.74	4.38
-350	-300	-100	-50	4	260	5.93	429.91	6.18
-350	-300	-50	0	5	260	4.05	513.83	2.81
-300	-250	-200	-150	1	200	23.95	112.86	4.92
-300	-250	-150	-100	2	200	9.59	180.77	3.29
-300	-250	-100	-50	3	200	6.42	302.54	4.78
-300	-250	-50	0	4	200	4.02	378.88	3.87
-300	-250	0	50	5	200	3.76	620.15	1.87
-250	-200	-150	-100	1	170	34.88	193.37	4.79
-250	-200	-100	-50	2	170	19.24	426.67	6.46
-250	-200	-50	0	3	170	11.06	613.16	5.27
-250	-200	0	50	4	170	9.71	1076.64	4.07
-250	-200	50	100	5	170	5.29	1026.47	4.01
-200	-150	-100	-50	1	250	35.63	134.32	6.45
-200	-150	-50	0	2	250	17.38	262.08	5.02
-200	-150	0	50	3	250	14.49	546.26	3.48
-200	-150	50	100	4	250	7.19	542.11	3.64
-200	-150	100	150	5	250	2.59	341.74	4.33
-150	-100	-50	0	1	280	39.91	134.34	5.01
-150	-100	0	50	2	280	25.82	347.64	3.03
-150	-100	50	100	3	280	11.90	400.55	3.19
-150	-100	100	150	4	280	3.87	260.53	3.71
-150	-100	150	200	5	280	2.44	287.46	2.94
-100	-50	0	50	1	300	66.81	209.89	5.00
-100	-50	50	100	2	300	27.03	339.67	4.97
-100	-50	100	150	3	300	7.67	240.96	5.81
-100	-50	150	200	4	300	4.39	275.83	4.27
-100	-50	200	250	5	300	3.38	371.65	4.84
-50	0	50	100	1	500	110.49	208.27	3.86
-50	0	100	150	2	500	24.14	182.01	4.43
-50	0	150	200	3	500	11.36	214.13	3.93
-50	0	200	250	4	500	7.77	292.92	4.10
-50	0	250	300	5	500	4.76	314.03	3.65
0	50	100	150	1	280	59.95	201.79	4.38
0	50	150	200	2	280	18.97	255.41	3.69
0	50	200	250	3	280	10.19	342.99	3.43
0	50	250	300	4	280	5.56	374.30	4.38
0	50	300	350	5	280	4.26	501.87	2.37
50	100	150	200	1	220	26.78	114.73	3.06
50	100	200	250	2	220	9.64	165.19	3.17
50	100	250	300	3	220	4.19	179.50	3.90
50	100	300	350	4	220	3.02	258.75	3.47
50	100	350	400	5	220	2.66	398.84	4.95

Sagala Line-N1750

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
100	150	200	250	1	330	35.33	100.90	4.36
100	150	250	300	2	330	9.00	102.82	5.11
100	150	300	350	3	330	5.50	157.08	4.57
100	150	350	400	4	330	4.75	271.32	5.20
100	150	400	450	5	330	2.65	264.89	3.61
150	200	250	300	1	370	37.97	96.72	11.75
150	200	300	350	2	370	11.09	113.00	4.69
150	200	350	400	3	370	7.53	191.81	4.90
150	200	400	450	4	370	4.29	218.55	4.15
150	200	450	500	5	370	4.38	390.49	6.87
200	250	300	350	1	320	21.36	62.91	4.20
200	250	350	400	2	320	10.91	128.53	4.59
200	250	400	450	3	320	5.57	164.05	3.94
200	250	450	500	4	320	5.42	319.26	6.07
200	250	500	550	5	320	4.22	435.01	6.80
250	300	350	400	1	320	20.08	59.14	5.15
250	300	400	450	2	320	7.10	83.64	4.25
250	300	450	500	3	320	5.91	174.06	6.61
250	300	500	550	4	320	4.48	263.89	7.37
250	300	550	600	5	320	5.24	540.16	6.10
300	350	400	450	1	250	13.89	52.36	3.08
300	350	450	500	2	250	8.02	120.94	4.95
300	350	500	550	3	250	5.73	216.02	6.69
300	350	550	600	4	250	6.06	456.91	4.56
300	350	600	650	5	250	3.61	476.33	4.58
350	400	450	500	1	280	26.16	88.05	12.06
350	400	500	550	2	280	10.26	138.14	6.39
350	400	550	600	3	280	8.89	299.24	4.59
350	400	600	650	4	280	4.87	327.85	2.91
350	400	650	700	5	280	3.82	450.03	4.80
400	450	500	550	1	400	179.49	422.91	37.30
400	450	550	600	2	400	30.36	286.14	6.94
400	450	600	650	3	400	11.93	281.09	2.93
400	450	650	700	4	400	7.72	363.80	4.75
400	450	700	750	5	400	4.52	372.75	3.13
450	500	550	600	1	220	114.22	489.32	22.09
450	500	600	650	2	220	19.04	326.27	5.21
450	500	650	700	3	220	7.76	332.44	5.23
450	500	700	750	4	220	4.09	350.43	4.04
450	500	750	800	5	220	2.42	362.85	4.80
500	550	600	650	1	110	52.54	450.16	17.07
500	550	650	700	2	110	9.21	315.64	5.52
500	550	700	750	3	110	3.57	305.88	3.45
500	550	750	800	4	110	1.98	339.29	4.91
500	550	800	850	5	110	1.08	323.87	2.03
550	600	650	700	1	120	58.43	458.91	8.06
550	600	700	750	2	120	13.04	409.66	1.45
550	600	750	800	3	120	7.18	563.92	2.72
550	600	800	850	4	120	3.32	521.50	3.11
550	600	850	900	5	120	3.11	854.91	2.45
600	650	700	750	1	260	50.15	181.79	0.64
600	650	750	800	2	260	19.50	282.74	1.87
600	650	800	850	3	260	8.31	301.23	2.40
600	650	850	900	4	260	6.86	497.34	2.20
600	650	900	950	5	260	3.33	422.48	4.19

Sagala Line-N1750

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
650	700	750	800	1	300	65.56	205.96	3.83
650	700	800	850	2	300	20.88	262.39	4.12
650	700	850	900	3	300	13.82	434.17	4.10
650	700	900	950	4	300	6.24	392.07	4.61
650	700	950	1000	5	300	6.58	723.51	3.32
700	750	800	850	1	400	43.54	102.59	2.88
700	750	850	900	2	400	17.91	168.80	3.00
700	750	900	950	3	400	7.29	171.77	4.57
700	750	950	1000	4	400	7.35	346.36	2.60
700	750	1000	1050	5	400	6.66	549.23	1.11
750	800	850	900	1	440	49.58	106.20	3.61
750	800	900	950	2	440	13.53	115.92	4.37
750	800	950	1000	3	440	11.41	244.40	3.10
750	800	1000	1050	4	440	9.67	414.26	3.04
750	800	1050	1100	5	440	4.25	318.62	3.53
800	850	900	950	1	520	38.08	69.02	3.79
800	850	950	1000	2	520	21.86	158.48	2.31
800	850	1000	1050	3	520	16.81	304.67	2.80
800	850	1050	1100	4	520	6.48	234.89	2.93
800	850	1100	1150	5	520	7.72	489.73	3.89
850	900	950	1000	1	540	63.52	110.86	2.06
850	900	1000	1050	2	540	40.99	286.16	2.29
850	900	1050	1100	3	540	13.95	243.47	2.77
850	900	1100	1150	4	540	15.35	535.82	2.85
850	900	1150	1200	5	540	5.65	345.14	2.91
900	950	1000	1050	1	560	81.00	136.32	1.74
900	950	1050	1100	2	560	21.39	144.00	2.60
900	950	1100	1150	3	560	20.25	340.81	2.87
900	950	1150	1200	4	560	6.92	232.93	2.94
900	950	1200	1250	5	560	4.05	238.56	3.55
950	1000	1050	1100	1	720	80.52	105.40	1.87
950	1000	1100	1150	2	720	57.55	301.33	1.90
950	1000	1150	1200	3	720	17.63	230.78	1.84
950	1000	1200	1250	4	720	9.90	259.18	2.43
950	1000	1250	1300	5	720	8.04	368.35	3.31
1000	1050	1100	1150	1	660	140.82	201.09	1.98
1000	1050	1150	1200	2	660	33.95	193.92	1.80
1000	1050	1200	1250	3	660	16.06	229.34	2.68
1000	1050	1250	1300	4	660	12.13	346.43	3.01
1000	1050	1300	1350	5	660	7.96	397.84	2.57
1050	1100	1150	1200	1	660	76.19	108.80	2.37
1050	1100	1200	1250	2	660	24.64	140.74	3.16
1050	1100	1250	1300	3	660	16.07	229.48	3.53
1050	1100	1300	1350	4	660	9.92	283.31	3.71
1050	1100	1350	1400	5	660	9.98	498.80	5.21
1100	1150	1200	1250	1	470	56.80	113.90	4.38
1100	1150	1250	1300	2	470	27.71	222.26	4.51
1100	1150	1300	1350	3	470	15.53	311.42	4.43
1100	1150	1350	1400	4	470	14.31	573.91	5.60
1100	1150	1400	1450	5	470	9.93	696.93	4.22
1150	1200	1250	1300	1	440	30.25	64.80	4.23
1150	1200	1300	1350	2	440	11.81	101.19	4.42
1150	1200	1350	1400	3	440	9.62	206.06	5.33
1150	1200	1400	1450	4	440	6.44	275.89	4.90
1150	1200	1450	1500	5	440	6.14	460.31	4.71

Sagala Line-N1750

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
1200	1250	1300	1350	1	430	31.71	69.50	4.94
1200	1250	1350	1400	2	430	15.06	132.03	6.51
1200	1250	1400	1450	3	430	8.75	191.78	4.73
1200	1250	1450	1500	4	430	8.04	352.44	4.71
1200	1250	1500	1550	5	430	4.25	326.03	3.94
1250	1300	1350	1400	1	500	40.43	76.21	5.84
1250	1300	1400	1450	2	500	17.37	130.97	4.88
1250	1300	1450	1500	3	500	14.73	277.65	5.02
1250	1300	1500	1550	4	500	7.65	288.40	4.86
1250	1300	1550	1600	5	500	5.03	331.85	6.86
1300	1350	1400	1450	1	320	24.11	71.01	5.04
1300	1350	1450	1500	2	320	16.82	198.16	5.03
1300	1350	1500	1550	3	320	7.71	227.08	4.46
1300	1350	1550	1600	4	320	4.77	280.98	7.41
1300	1350	1600	1650	5	320	2.72	280.39	4.65
1350	1400	1450	1500	1	330	42.35	120.95	5.30
1350	1400	1500	1550	2	330	16.86	192.61	4.74
1350	1400	1550	1600	3	330	9.46	270.18	7.46
1350	1400	1600	1650	4	330	5.12	292.45	4.80
1350	1400	1650	1700	5	330	2.95	294.88	5.03
1400	1450	1500	1550	1	1400	116.89	78.69	4.18
1400	1450	1550	1600	2	1400	52.20	140.56	6.58
1400	1450	1600	1650	3	1400	25.79	173.62	3.71
1400	1450	1650	1700	4	1400	13.86	186.61	4.84
1400	1450	1700	1750	5	1400	12.41	292.40	4.44
1450	1500	1550	1600	1	860	83.74	91.77	6.65
1450	1500	1600	1650	2	860	28.32	124.14	3.00
1450	1500	1650	1700	3	860	13.75	150.69	4.27
1450	1500	1700	1750	4	860	11.75	257.54	4.01
1450	1500	1750	1800	5	860	6.09	233.59	3.17
1500	1550	1600	1650	1	710	52.28	69.40	3.37
1500	1550	1650	1700	2	710	17.68	93.88	3.69
1500	1550	1700	1750	3	710	12.99	172.43	3.90
1500	1550	1750	1800	4	710	6.41	170.18	3.29
1500	1550	1800	1850	5	710	3.74	173.76	3.77
1550	1600	1650	1700	1	1200	83.35	65.46	6.82
1550	1600	1700	1750	2	1200	43.60	136.97	6.62
1550	1600	1750	1800	3	1200	19.50	153.15	5.94
1550	1600	1800	1850	4	1200	9.90	155.51	6.47
1550	1600	1850	1900	5	1200	7.45	204.79	6.06
1600	1650	1700	1750	1	1400	98.33	66.20	5.60
1600	1650	1750	1800	2	1400	30.97	83.40	3.79
1600	1650	1800	1850	3	1400	13.97	94.05	4.44
1600	1650	1850	1900	4	1400	9.57	128.85	4.17
1600	1650	1900	1950	5	1400	5.42	127.71	4.31
1650	1700	1750	1800	1	1300	141.58	102.64	7.04
1650	1700	1800	1850	2	1300	45.21	131.11	7.47
1650	1700	1850	1900	3	1300	22.06	159.93	7.32
1650	1700	1900	1950	4	1300	11.27	163.41	6.61
1650	1700	1950	2000	5	1300	10.14	257.30	6.15
1700	1750	1800	1850	1	1700	157.99	87.59	6.03
1700	1750	1850	1900	2	1700	56.95	126.29	6.41
1700	1750	1900	1950	3	1700	27.24	151.02	5.85
1700	1750	1950	2000	4	1700	22.61	250.70	5.55
1750	1800	1850	1900	1	2000	112.24	52.89	5.88

Sagala Line-N1750

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
1750	1800	1900	1950	2	2000	41.11	77.49	5.18
1750	1800	1950	2000	3	2000	29.07	136.99	4.84
1800	1850	1900	1950	1	1600	103.27	60.83	6.76
1800	1850	1950	2000	2	1600	47.64	112.25	5.89
1850	1900	1950	2000	1	1100	100.15	85.81	6.51

Sagala Line-N1500

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-1000	-950	-900	-850	1	380	90.76	225.10	9.62
-1000	-950	-850	-800	2	380	24.14	239.49	7.70
-1000	-950	-800	-750	3	380	10.84	268.85	6.06
-1000	-950	-750	-700	4	380	6.75	334.83	3.90
-1000	-950	-700	-650	5	380	3.95	342.89	5.76
-950	-900	-850	-800	1	300	72.05	226.35	9.55
-950	-900	-800	-750	2	300	24.50	307.88	6.77
-950	-900	-750	-700	3	300	13.57	426.31	4.63
-950	-900	-700	-650	4	300	7.35	461.81	6.64
-950	-900	-650	-600	5	300	5.54	609.15	7.46
-900	-850	-800	-750	1	820	157.56	181.09	7.06
-900	-850	-750	-700	2	820	68.87	316.63	4.56
-900	-850	-700	-650	3	820	32.67	375.50	6.09
-900	-850	-650	-600	4	820	21.77	500.43	5.98
-900	-850	-600	-550	5	820	17.18	691.11	7.00
-850	-800	-750	-700	1	1200	226.16	177.63	6.20
-850	-800	-700	-650	2	1200	80.62	253.28	6.53
-850	-800	-650	-600	3	1200	50.80	398.98	6.55
-850	-800	-600	-550	4	1200	34.36	539.73	6.57
-850	-800	-550	-500	5	1200	20.10	552.53	5.44
-800	-750	-700	-650	1	1700	326.53	181.03	7.36
-800	-750	-650	-600	2	1700	131.79	292.26	6.68
-800	-750	-600	-550	3	1700	85.95	476.51	6.71
-800	-750	-550	-500	4	1700	42.87	475.34	6.29
-800	-750	-500	-450	5	1700	44.38	861.15	5.01
-750	-700	-650	-600	1	630	70.80	105.92	3.55
-750	-700	-600	-550	2	630	43.45	260.00	3.75
-750	-700	-550	-500	3	630	17.52	262.10	3.40
-750	-700	-500	-450	4	630	18.18	543.94	1.95
-750	-700	-450	-400	5	630	8.15	426.73	3.40
-700	-650	-600	-550	1	370	56.87	144.86	5.51
-700	-650	-550	-500	2	370	17.56	178.92	5.16
-700	-650	-500	-450	3	370	16.27	414.44	4.47
-700	-650	-450	-400	4	370	6.81	346.93	6.29
-700	-650	-400	-350	5	370	4.97	443.09	7.55
-650	-600	-550	-500	1	370	48.96	124.71	5.32
-650	-600	-500	-450	2	370	27.46	279.79	4.35
-650	-600	-450	-400	3	370	10.27	261.60	4.93
-650	-600	-400	-350	4	370	7.12	362.73	5.14
-650	-600	-350	-300	5	370	6.34	565.23	4.62
-600	-550	-500	-450	1	400	83.21	196.06	5.80
-600	-550	-450	-400	2	400	22.09	208.19	5.87
-600	-550	-400	-350	3	400	11.82	278.50	5.36
-600	-550	-350	-300	4	400	9.66	455.22	5.14
-600	-550	-300	-250	5	400	5.57	459.34	4.78
-550	-500	-450	-400	1	340	62.64	173.64	8.79
-550	-500	-400	-350	2	340	20.37	225.86	6.26
-550	-500	-350	-300	3	340	11.73	325.15	5.77
-550	-500	-300	-250	4	340	7.45	413.03	5.14
-550	-500	-250	-200	5	340	4.46	432.71	4.30
-500	-450	-400	-350	1	370	155.14	395.18	15.58
-500	-450	-350	-300	2	370	48.53	494.47	4.59
-500	-450	-300	-250	3	370	26.65	678.84	3.90
-500	-450	-250	-200	4	370	14.75	751.43	4.25
-500	-450	-200	-150	5	370	12.91	1150.97	3.73

Sagala Line-N1500

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-450	-400	-350	-300	1	160	37.89	223.19	8.52
-450	-400	-300	-250	2	160	14.78	348.25	3.41
-450	-400	-250	-200	3	160	6.70	394.66	3.71
-450	-400	-200	-150	4	160	6.00	706.86	4.22
-450	-400	-150	-100	5	160	3.65	752.51	3.59
-400	-350	-300	-250	1	100	35.19	331.66	10.26
-400	-350	-250	-200	2	100	10.08	380.01	3.76
-400	-350	-200	-150	3	100	8.79	828.44	4.20
-400	-350	-150	-100	4	100	4.95	933.05	4.68
-400	-350	-100	-50	5	100	1.63	537.68	5.51
-350	-300	-250	-200	1	180	39.46	206.61	8.14
-350	-300	-200	-150	2	180	27.00	565.49	4.80
-350	-300	-150	-100	3	180	13.73	718.90	3.91
-350	-300	-100	-50	4	180	4.25	445.06	1.35
-350	-300	-50	0	5	180	3.27	599.26	2.62
-300	-250	-200	-150	1	460	126.95	260.10	8.44
-300	-250	-150	-100	2	460	45.56	373.39	4.80
-300	-250	-100	-50	3	460	12.42	254.47	2.91
-300	-250	-50	0	4	460	8.87	363.47	3.68
-300	-250	0	50	5	460	6.03	432.41	2.86
-250	-200	-150	-100	1	480	146.41	287.48	7.07
-250	-200	-100	-50	2	480	23.74	186.45	3.15
-250	-200	-50	0	3	480	15.52	304.73	4.33
-250	-200	0	50	4	480	9.43	370.32	3.61
-250	-200	50	100	5	480	7.69	528.47	3.23
-200	-150	-100	-50	1	360	88.62	232.01	4.38
-200	-150	-50	0	2	360	35.99	376.89	4.49
-200	-150	0	50	3	360	18.11	474.12	4.01
-200	-150	50	100	4	360	13.40	701.62	3.12
-200	-150	100	150	5	360	8.82	808.17	4.57
-150	-100	-50	0	1	340	72.21	200.17	4.58
-150	-100	0	50	2	340	26.03	288.62	3.89
-150	-100	50	100	3	340	17.33	480.39	2.39
-150	-100	100	150	4	340	10.44	578.79	3.23
-150	-100	150	200	5	340	13.25	1285.51	4.01
-100	-50	0	50	1	400	58.85	138.66	6.88
-100	-50	50	100	2	400	23.29	219.50	3.49
-100	-50	100	150	3	400	12.32	290.28	3.78
-100	-50	150	200	4	400	13.31	627.22	6.01
-100	-50	200	250	5	400	16.79	1384.62	6.95
-50	0	50	100	1	340	59.33	164.46	2.50
-50	0	100	150	2	340	23.97	265.78	3.48
-50	0	150	200	3	340	20.23	560.77	3.92
-50	0	200	250	4	340	24.30	1347.19	5.54
-50	0	250	300	5	340	6.45	625.78	4.38
0	50	100	150	1	480	100.38	197.10	1.65
0	50	150	200	2	480	51.82	406.99	2.65
0	50	200	250	3	480	56.81	1115.46	4.35
0	50	250	300	4	480	14.89	584.73	3.38
0	50	300	350	5	480	7.73	531.22	2.80
50	100	150	200	1	900	238.77	250.04	3.46
50	100	200	250	2	900	220.62	924.13	5.22
50	100	250	300	3	900	54.83	574.18	4.20
50	100	300	350	4	900	27.02	565.91	3.79
50	100	350	400	5	900	19.68	721.31	2.36

Sagala Line-N1500

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
100	150	200	250	1	230	137.52	563.52	5.16
100	150	250	300	2	230	28.59	468.62	4.30
100	150	300	350	3	230	12.71	520.82	4.14
100	150	350	400	4	230	8.77	718.74	3.82
100	150	400	450	5	230	5.25	752.96	2.99
150	200	250	300	1	250	127.00	478.78	6.08
150	200	300	350	2	250	46.98	708.44	5.59
150	200	350	400	3	250	29.76	1121.93	5.18
150	200	400	450	4	250	16.84	1269.71	3.90
150	200	450	500	5	250	10.53	1389.40	4.89
200	250	300	350	1	950	408.71	405.47	7.00
200	250	350	400	2	950	225.13	893.39	6.71
200	250	400	450	3	950	120.90	1199.43	5.67
200	250	450	500	4	950	73.07	1449.83	6.85
200	250	500	550	5	950	33.11	1149.67	5.74
250	300	350	400	1	620	217.95	331.31	6.49
250	300	400	450	2	620	72.67	441.87	4.90
250	300	450	500	3	620	43.37	659.28	5.95
250	300	500	550	4	620	15.12	459.69	4.38
250	300	550	600	5	620	8.85	470.86	6.01
300	350	400	450	1	550	173.09	296.61	6.06
300	350	450	500	2	550	83.46	572.07	6.71
300	350	500	550	3	550	23.20	397.55	4.63
300	350	550	600	4	550	11.76	403.04	6.13
300	350	600	650	5	550	7.53	451.62	6.72
350	400	450	500	1	790	395.63	471.99	6.64
350	400	500	550	2	790	73.37	350.12	4.71
350	400	550	600	3	790	33.78	403.00	5.57
350	400	600	650	4	790	21.47	512.28	5.76
350	400	650	700	5	790	11.04	460.98	4.67
400	450	500	550	1	850	559.42	620.28	4.73
400	450	550	600	2	850	108.74	482.28	6.03
400	450	600	650	3	850	33.17	367.79	5.38
400	450	650	700	4	850	20.20	447.95	4.66
400	450	700	750	5	850	17.63	684.18	5.87
450	500	550	600	1	680	207.26	287.26	5.33
450	500	600	650	2	680	41.94	232.51	5.83
450	500	650	700	3	680	23.98	332.36	4.41
450	500	700	750	4	680	19.27	534.16	6.42
450	500	750	800	5	680	9.93	481.70	6.08
500	550	600	650	1	750	132.75	166.82	5.79
500	550	650	700	2	750	53.45	268.67	4.57
500	550	700	750	3	750	32.18	404.39	5.37
500	550	750	800	4	750	15.34	385.54	4.16
500	550	800	850	5	750	7.46	328.11	4.20
550	600	650	700	1	680	76.45	105.96	5.67
550	600	700	750	2	680	41.93	232.46	6.58
550	600	750	800	3	680	15.40	213.44	5.78
550	600	800	850	4	680	7.64	211.78	4.92
550	600	850	900	5	680	8.05	390.50	5.13
600	650	700	750	1	420	47.16	105.83	6.19
600	650	750	800	2	420	12.07	108.34	5.37
600	650	800	850	3	420	4.91	110.18	4.14
600	650	850	900	4	420	4.82	216.32	5.12
600	650	900	950	5	420	6.79	533.29	4.67

Sagala Line-N1500

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
650	700	750	800	1	330	30.88	88.19	4.85
650	700	800	850	2	330	6.58	75.17	3.15
650	700	850	900	3	330	6.06	173.07	2.94
650	700	900	950	4	330	7.67	438.11	3.65
650	700	950	1000	5	330	1.86	185.93	5.95
700	750	800	850	1	400	26.41	62.23	4.24
700	750	850	900	2	400	19.60	184.73	4.19
700	750	900	950	3	400	21.12	497.63	4.53
700	750	950	1000	4	400	3.62	170.59	3.39
700	750	1000	1050	5	400	5.18	427.18	3.81
750	800	850	900	1	370	27.28	69.49	3.61
750	800	900	950	2	370	24.80	252.69	4.15
750	800	950	1000	3	370	4.35	110.80	4.25
750	800	1000	1050	4	370	4.72	240.46	3.90
750	800	1050	1100	5	370	6.96	620.51	3.99
800	850	900	950	1	270	46.42	162.04	3.45
800	850	950	1000	2	270	6.33	88.38	4.23
800	850	1000	1050	3	270	4.66	162.66	3.43
800	850	1050	1100	4	270	6.09	425.16	2.53
800	850	1100	1150	5	270	2.08	254.12	1.60
850	900	950	1000	1	300	36.69	115.27	3.34
850	900	1000	1050	2	300	15.29	192.14	2.71
850	900	1050	1100	3	300	15.45	485.38	1.73
850	900	1100	1150	4	300	5.45	342.43	2.72
850	900	1150	1200	5	300	3.86	424.43	4.02
900	950	1000	1050	1	500	110.11	207.55	3.19
900	950	1050	1100	2	500	102.82	775.24	2.32
900	950	1100	1150	3	500	25.02	471.62	2.75
900	950	1150	1200	4	500	11.72	441.83	4.54
900	950	1200	1250	5	500	10.23	674.91	3.98
950	1000	1050	1100	1	370	125.79	320.42	2.47
950	1000	1100	1150	2	370	21.84	222.53	2.95
950	1000	1150	1200	3	370	8.09	206.07	5.20
950	1000	1200	1250	4	370	6.62	337.25	4.95
950	1000	1250	1300	5	370	3.75	334.32	4.11
1000	1050	1100	1150	1	190	91.11	451.94	1.60
1000	1050	1150	1200	2	190	22.52	446.83	4.34
1000	1050	1200	1250	3	190	17.06	846.25	4.03
1000	1050	1250	1300	4	190	9.02	894.86	3.83
1000	1050	1300	1350	5	190	3.73	647.58	4.60
1050	1100	1150	1200	1	210	65.35	293.29	2.89
1050	1100	1200	1250	2	210	44.72	802.81	2.69
1050	1100	1250	1300	3	210	22.45	1007.55	2.23
1050	1100	1300	1350	4	210	9.18	823.99	2.43
1050	1100	1350	1400	5	210	3.13	491.66	3.64
1100	1150	1200	1250	1	460	104.87	214.86	3.86
1100	1150	1250	1300	2	460	44.10	361.42	3.24
1100	1150	1300	1350	3	460	17.50	358.55	3.28
1100	1150	1350	1400	4	460	5.59	229.06	4.15
1100	1150	1400	1450	5	460	5.94	425.96	4.85
1150	1200	1250	1300	1	700	113.36	152.63	4.12
1150	1200	1300	1350	2	700	36.95	199.00	4.29
1150	1200	1350	1400	3	700	9.89	133.16	3.86
1150	1200	1400	1450	4	700	11.21	301.86	6.30
1150	1200	1450	1500	5	700	15.32	721.94	3.51

Sagala Line-N1500

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
1200	1250	1300	1350	1	920	156.26	160.08	4.22
1200	1250	1350	1400	2	920	25.37	103.96	5.05
1200	1250	1400	1450	3	920	21.28	218.00	5.52
1200	1250	1450	1500	4	920	31.38	642.93	3.34
1200	1250	1500	1550	5	920	18.76	672.64	3.53
1250	1300	1350	1400	1	950	92.30	91.57	4.34
1250	1300	1400	1450	2	950	48.71	193.30	5.37
1250	1300	1450	1500	3	950	60.77	602.89	3.15
1250	1300	1500	1550	4	950	34.14	677.39	3.31
1250	1300	1550	1600	5	950	12.70	440.98	4.84
1300	1350	1400	1450	1	1300	79.17	57.40	4.78
1300	1350	1450	1500	2	1300	78.21	226.80	2.62
1300	1350	1500	1550	3	1300	41.54	301.16	2.72
1300	1350	1550	1600	4	1300	14.99	217.35	3.92
1300	1350	1600	1650	5	1300	10.43	264.66	6.84
1350	1400	1450	1500	1	1400	135.82	91.43	2.31
1350	1400	1500	1550	2	1400	57.77	155.56	2.28
1350	1400	1550	1600	3	1400	19.07	128.38	3.64
1350	1400	1600	1650	4	1400	11.08	149.18	6.12
1350	1400	1650	1700	5	1400	6.61	155.74	7.15
1400	1450	1500	1550	1	1500	424.42	266.67	2.29
1400	1450	1550	1600	2	1500	88.76	223.08	3.68
1400	1450	1600	1650	3	1500	45.72	287.27	6.33
1400	1450	1650	1700	4	1500	24.00	301.59	7.29
1400	1450	1700	1750	5	1500	15.79	347.24	7.01
1450	1500	1550	1600	1	1300	282.08	204.50	1.95
1450	1500	1600	1650	2	1300	121.72	352.98	4.23
1450	1500	1650	1700	3	1300	57.89	419.69	5.05
1450	1500	1700	1750	4	1300	36.76	533.01	4.52
1450	1500	1750	1800	5	1300	21.85	554.43	3.41
1500	1550	1600	1650	1	1300	186.51	135.22	4.53
1500	1550	1650	1700	2	1300	68.09	197.46	5.25
1500	1550	1700	1750	3	1300	40.35	292.53	4.69
1500	1550	1750	1800	4	1300	22.95	332.77	3.71
1500	1550	1800	1850	5	1300	12.71	322.51	4.13
1550	1600	1650	1700	1	1300	81.56	59.13	6.76
1550	1600	1700	1750	2	1300	34.34	99.58	5.39
1550	1600	1750	1800	3	1300	17.79	128.97	3.78
1550	1600	1800	1850	4	1300	9.73	141.08	4.34
1550	1600	1850	1900	5	1300	7.39	187.52	4.79
1600	1650	1700	1750	1	1000	117.13	110.39	13.81
1600	1650	1750	1800	2	1000	35.17	132.59	7.53
1600	1650	1800	1850	3	1000	16.71	157.49	7.71
1600	1650	1850	1900	4	1000	12.31	232.04	7.59
1600	1650	1900	1950	5	1000	15.35	506.35	5.22
1650	1700	1750	1800	1	1200	92.44	72.60	11.03
1650	1700	1800	1850	2	1200	27.27	85.67	8.17
1650	1700	1850	1900	3	1200	17.93	140.82	7.71
1650	1700	1900	1950	4	1200	19.75	310.23	6.42
1650	1700	1950	2000	5	1200	16.75	460.44	6.07
1700	1750	1800	1850	1	1100	53.16	45.55	6.56
1700	1750	1850	1900	2	1100	25.81	88.46	6.28
1700	1750	1900	1950	3	1100	22.91	196.29	5.06
1700	1750	1950	2000	4	1100	18.02	308.79	4.88
1750	1800	1850	1900	1	1050	65.97	59.21	4.97

Sagala Line-N1500

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
1750	1800	1900	1950	2	1050	42.83	153.78	3.99
1750	1800	1950	2000	3	1050	29.23	262.37	4.05
1800	1850	1900	1950	1	1200	133.68	104.99	4.79
1800	1850	1950	2000	2	1200	67.24	211.24	4.64
1850	1900	1950	2000	1	940	245.52	246.17	3.34

Sagala Line-N1250

Curr. Elect C1	Curr. Elect C2	Pot. Elect P1	Pot. Elect P2	n	Current (mA)	Potential (mV)	Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
-1000	-950	-900	-850	1	50	3.29	62.02	0.65
-1000	-950	-850	-800	2	50	2.05	154.57	-0.33
-1000	-950	-800	-750	3	50	0.87	163.99	0.40
-1000	-950	-750	-700	4	50	0.74	278.97	1.35
-1000	-950	-700	-650	5	50	0.48	316.67	1.93
-950	-900	-850	-800	1	40	8.42	198.39	5.72
-950	-900	-800	-750	2	40	1.12	105.56	-8.07
-950	-900	-750	-700	3	40	0.66	155.51	0.16
-950	-900	-700	-650	4	40	0.42	197.92	-16.90
-950	-900	-650	-600	5	40	0.30	247.40	-22.93
-900	-850	-800	-750	1	40	3.54	83.41	-5.19
-900	-850	-750	-700	2	40	1.05	98.96	-9.97
-900	-850	-700	-650	3	40	0.59	139.02	-3.61
-900	-850	-650	-600	4	40	0.44	207.35	-29.22
-900	-850	-600	-550	5	40	0.35	288.63	24.35
-850	-800	-750	-700	1	60	12.59	197.76	-0.75
-850	-800	-700	-650	2	60	3.92	246.30	-4.85
-850	-800	-650	-600	3	60	2.60	408.41	-6.62
-850	-800	-600	-550	4	60	1.86	584.34	-7.93
-850	-800	-550	-500	5	60	0.92	505.80	-9.41
-800	-750	-700	-650	1	300	83.41	262.04	10.06
-800	-750	-650	-600	2	300	39.65	498.26	4.65
-800	-750	-600	-550	3	300	24.04	755.24	4.27
-800	-750	-550	-500	4	300	11.25	706.86	6.00
-800	-750	-500	-450	5	300	6.05	665.23	5.93
-750	-700	-650	-600	1	250	80.65	304.04	6.31
-750	-700	-600	-550	2	250	38.07	574.08	4.43
-750	-700	-550	-500	3	250	16.49	621.66	6.22
-750	-700	-500	-450	4	250	7.61	573.78	6.25
-750	-700	-450	-400	5	250	5.16	680.85	5.26
-700	-650	-600	-550	1	200	76.78	361.82	5.18
-700	-650	-550	-500	2	200	22.51	424.30	4.74
-700	-650	-500	-450	3	200	9.36	441.08	5.24
-700	-650	-450	-400	4	200	5.02	473.12	3.37
-700	-650	-400	-350	5	200	2.36	389.24	4.15
-650	-600	-550	-500	1	150	66.11	415.38	3.30
-650	-600	-500	-450	2	150	19.15	481.29	3.45
-650	-600	-450	-400	3	150	10.29	646.54	1.41
-650	-600	-400	-350	4	150	3.73	468.73	1.49
-650	-600	-350	-300	5	150	1.84	404.64	2.89
-600	-550	-500	-450	1	170	49.49	274.37	4.74
-600	-550	-450	-400	2	170	25.16	557.95	3.77
-600	-550	-400	-350	3	170	6.98	386.97	3.82
-600	-550	-350	-300	4	170	3.75	415.80	4.15
-600	-550	-300	-250	5	170	2.43	471.52	2.52
-550	-500	-450	-400	1	200	68.93	324.82	5.79
-550	-500	-400	-350	2	200	11.88	223.93	4.92
-550	-500	-350	-300	3	200	6.89	324.68	5.48
-550	-500	-300	-250	4	200	2.76	260.12	4.74
-550	-500	-250	-200	5	200	3.18	524.49	4.48
-500	-450	-400	-350	1	50	11.74	221.29	1.63
-500	-450	-350	-300	2	50	2.03	153.06	-3.10
-500	-450	-300	-250	3	50	1.33	250.70	0.75
-500	-450	-250	-200	4	50	0.70	263.89	3.02
-500	-450	-200	-150	5	50	0.49	323.27	-4.76

Sagala Line-N1250

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-450	-400	-350	-300	1	45	8.66	181.37	1.58
-450	-400	-300	-250	2	45	2.57	215.30	-1.27
-450	-400	-250	-200	3	45	1.19	249.23	2.48
-450	-400	-200	-150	4	45	0.66	276.46	5.28
-450	-400	-150	-100	5	45	0.37	271.22	7.39
-400	-350	-300	-250	1	90	21.83	228.60	11.26
-400	-350	-250	-200	2	90	4.81	201.48	4.58
-400	-350	-200	-150	3	90	2.23	233.53	5.85
-400	-350	-150	-100	4	90	1.03	215.72	4.09
-400	-350	-100	-50	5	90	0.70	256.56	3.04
-350	-300	-250	-200	1	70	11.00	148.10	2.65
-350	-300	-200	-150	2	70	2.60	140.03	-2.53
-350	-300	-150	-100	3	70	1.01	135.99	-3.44
-350	-300	-100	-50	4	70	0.60	161.57	8.81
-350	-300	-50	0	5	70	0.94	442.96	-0.98
-300	-250	-200	-150	1	60	6.63	104.14	0.52
-300	-250	-150	-100	2	60	1.45	91.11	-2.45
-300	-250	-100	-50	3	60	0.78	122.52	-4.32
-300	-250	-50	0	4	60	1.15	361.28	-3.36
-300	-250	0	50	5	60	0.91	500.30	-1.34
-250	-200	-150	-100	1	75	7.67	96.38	-0.64
-250	-200	-100	-50	2	75	2.21	111.09	0.44
-250	-200	-50	0	3	75	2.80	351.86	0.32
-250	-200	0	50	4	75	2.15	540.35	1.88
-250	-200	50	100	5	75	1.69	743.30	1.74
-200	-150	-100	-50	1	120	7.84	61.58	2.37
-200	-150	-50	0	2	120	7.48	234.99	2.69
-200	-150	0	50	3	120	5.41	424.90	1.92
-200	-150	50	100	4	120	4.11	645.60	1.67
-200	-150	100	150	5	120	1.97	541.53	4.04
-150	-100	-50	0	1	100	8.91	83.97	0.84
-150	-100	0	50	2	100	4.75	179.07	-1.60
-150	-100	50	100	3	100	3.28	309.13	-2.17
-150	-100	100	150	4	100	1.46	275.20	-0.78
-150	-100	150	200	5	100	1.25	412.33	1.64
-100	-50	0	50	1	100	15.88	149.67	-1.54
-100	-50	50	100	2	100	9.52	358.90	-1.65
-100	-50	100	150	3	100	3.80	358.14	-0.22
-100	-50	150	200	4	100	3.26	614.50	1.08
-100	-50	200	250	5	100	0.99	326.57	0.57
-50	0	50	100	1	220	57.64	246.93	3.63
-50	0	100	150	2	220	17.85	305.88	4.22
-50	0	150	200	3	220	14.62	626.32	5.78
-50	0	200	250	4	220	4.23	362.43	3.57
-50	0	250	300	5	220	2.58	386.84	4.94
0	50	100	150	1	500	116.57	219.73	5.15
0	50	150	200	2	500	51.36	387.25	5.93
0	50	200	250	3	500	12.46	234.87	4.07
0	50	250	300	4	500	7.12	268.42	3.56
0	50	300	350	5	500	10.55	696.02	4.37
50	100	150	200	1	500	184.17	347.15	7.14
50	100	200	250	2	500	40.64	306.42	5.08
50	100	250	300	3	500	14.17	267.10	3.61
50	100	300	350	4	500	20.56	775.09	4.19
50	100	350	400	5	500	20.30	1339.26	3.39

Sagala Line-N1250

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
100	150	200	250	1	350	63.12	169.97	6.84
100	150	250	300	2	350	16.22	174.71	5.80
100	150	300	350	3	350	18.87	508.13	6.25
100	150	350	400	4	350	17.30	931.71	5.27
100	150	400	450	5	350	4.76	448.62	7.51
150	200	250	300	1	300	27.33	85.86	5.48
150	200	300	350	2	300	21.81	274.07	5.79
150	200	350	400	3	300	17.89	562.03	5.01
150	200	400	450	4	300	4.73	297.19	6.44
150	200	450	500	5	300	5.14	565.17	5.82
200	250	300	350	1	320	35.16	103.55	4.62
200	250	350	400	2	320	21.79	256.71	3.84
200	250	400	450	3	320	4.44	130.77	4.94
200	250	450	500	4	320	4.12	242.69	3.55
200	250	500	550	5	320	1.88	193.80	3.52
250	300	350	400	1	550	143.02	245.08	4.44
250	300	400	450	2	550	20.62	141.34	5.84
250	300	450	500	3	550	13.78	236.13	4.24
250	300	500	550	4	550	5.40	185.07	4.58
250	300	550	600	5	550	3.99	239.30	5.37
300	350	400	450	1	650	182.38	264.44	5.42
300	350	450	500	2	650	61.54	356.92	5.05
300	350	500	550	3	650	22.84	331.17	5.44
300	350	550	600	4	650	16.55	479.94	4.10
300	350	600	650	5	650	12.10	614.06	4.69
350	400	450	500	1	300	87.38	274.51	4.39
350	400	500	550	2	300	23.37	293.68	4.55
350	400	550	600	3	300	14.15	444.54	3.55
350	400	600	650	4	300	9.85	618.89	4.08
350	400	650	700	5	300	9.75	1072.07	3.05
400	450	500	550	1	300	45.16	141.87	4.71
400	450	550	600	2	300	19.92	250.32	4.05
400	450	600	650	3	300	11.77	369.77	4.24
400	450	650	700	4	300	10.42	654.71	2.09
400	450	700	750	5	300	3.32	365.05	4.63
450	500	550	600	1	650	129.17	187.29	5.28
450	500	600	650	2	650	63.40	367.71	5.59
450	500	650	700	3	650	52.82	765.87	3.22
450	500	700	750	4	650	16.05	465.44	5.98
450	500	750	800	5	650	7.44	377.57	4.35
500	550	600	650	1	800	128.07	150.88	5.85
500	550	650	700	2	800	82.17	387.22	3.48
500	550	700	750	3	800	22.23	261.89	6.00
500	550	750	800	4	800	8.96	211.12	6.30
500	550	800	850	5	800	7.85	323.68	6.33
550	600	650	700	1	300	126.54	397.54	3.83
550	600	700	750	2	300	27.00	339.29	6.28
550	600	750	800	3	300	8.41	264.21	6.70
550	600	800	850	4	300	6.54	410.92	6.59
550	600	850	900	5	300	3.57	392.54	4.65
600	650	700	750	1	300	63.61	199.84	5.83
600	650	750	800	2	300	13.53	170.02	6.64
600	650	800	850	3	300	9.29	291.85	6.88
600	650	850	900	4	300	4.76	299.08	6.17
600	650	900	950	5	300	2.11	232.01	5.13

Sagala Line-N1250

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
650	700	750	800	1	500	82.53	155.57	3.71
650	700	800	850	2	500	42.30	318.93	4.28
650	700	850	900	3	500	18.91	356.45	3.75
650	700	900	950	4	500	7.32	275.96	2.60
650	700	950	1000	5	500	7.55	498.10	2.85
700	750	800	850	1	600	65.23	102.46	6.73
700	750	850	900	2	600	23.29	146.34	5.71
700	750	900	950	3	600	7.57	118.91	4.76
700	750	950	1000	4	600	7.23	227.14	5.56
750	800	850	900	1	700	79.42	106.93	5.52
750	800	900	950	2	700	16.44	88.54	4.30
750	800	950	1000	3	700	13.10	176.38	5.11
800	850	900	950	1	650	35.27	51.14	4.74
800	850	950	1000	2	650	20.22	117.27	5.27
850	900	950	1000	1	450	31.55	66.08	4.42

Sagala Line-N1000

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-1000	-950	-900	-850	1	150	18.68	117.37	8.96
-1000	-950	-850	-800	2	150	5.62	141.25	3.51
-1000	-950	-800	-750	3	150	3.53	221.80	5.26
-1000	-950	-750	-700	4	150	2.99	375.73	4.02
-1000	-950	-700	-650	5	150	2.77	609.15	3.97
-950	-900	-850	-800	1	350	53.60	144.33	10.07
-950	-900	-800	-750	2	350	21.41	230.61	6.61
-950	-900	-750	-700	3	350	14.48	389.92	6.30
-950	-900	-700	-650	4	350	13.82	744.29	5.49
-950	-900	-650	-600	5	350	7.89	743.61	4.99
-900	-850	-800	-750	1	200	37.61	177.23	10.29
-900	-850	-750	-700	2	200	17.50	329.87	6.16
-900	-850	-700	-650	3	200	12.94	609.78	5.45
-900	-850	-650	-600	4	200	7.16	674.81	5.49
-900	-850	-600	-550	5	200	4.03	664.68	7.78
-850	-800	-750	-700	1	120	22.42	176.09	9.02
-850	-800	-700	-650	2	120	9.67	303.79	3.54
-850	-800	-650	-600	3	120	4.92	386.42	3.62
-850	-800	-600	-550	4	120	2.57	403.69	4.61
-850	-800	-550	-500	5	120	1.79	492.05	0.82
-800	-750	-700	-650	1	150	38.64	242.78	10.89
-800	-750	-650	-600	2	150	10.92	274.45	3.68
-800	-750	-600	-550	3	150	5.21	327.35	4.47
-800	-750	-550	-500	4	150	3.15	395.84	2.54
-800	-750	-500	-450	5	150	2.42	532.19	7.20
-750	-700	-650	-600	1	170	47.28	262.12	9.87
-750	-700	-600	-550	2	170	14.18	314.45	5.95
-750	-700	-550	-500	3	170	6.03	334.30	4.00
-750	-700	-500	-450	4	170	4.49	497.85	4.34
-750	-700	-450	-400	5	170	1.27	246.43	0.60
-700	-650	-600	-550	1	150	58.85	369.77	10.52
-700	-650	-550	-500	2	150	15.02	377.49	4.04
-700	-650	-500	-450	3	150	10.10	634.60	4.90
-700	-650	-450	-400	4	150	2.42	304.11	2.78
-700	-650	-400	-350	5	150	0.99	217.71	2.65
-650	-600	-550	-500	1	270	53.27	185.95	8.88
-650	-600	-500	-450	2	270	26.16	365.26	6.79
-650	-600	-450	-400	3	270	5.57	194.43	5.66
-650	-600	-400	-350	4	270	1.91	133.34	2.92
-650	-600	-350	-300	5	270	3.72	454.48	5.43
-600	-550	-500	-450	1	470	119.23	239.09	8.89
-600	-550	-450	-400	2	470	15.54	124.65	6.41
-600	-550	-400	-350	3	470	4.69	94.05	3.04
-600	-550	-350	-300	4	470	7.12	285.55	6.52
-600	-550	-300	-250	5	470	5.17	362.85	5.73
-550	-500	-450	-400	1	70	6.69	90.07	5.75
-550	-500	-400	-350	2	70	1.09	58.70	1.03
-550	-500	-350	-300	3	70	1.10	148.10	0.77
-550	-500	-300	-250	4	70	0.79	212.73	2.40
-550	-500	-250	-200	5	70	0.28	131.95	3.93
-500	-450	-400	-350	1	130	2.90	21.02	0.40
-500	-450	-350	-300	2	130	0.61	17.69	1.17
-500	-450	-300	-250	3	130	0.53	38.42	0.13
-500	-450	-250	-200	4	130	0.20	29.00	-1.92
-500	-450	-200	-150	5	130	0.27	68.51	-1.09

Sagala Line-N1000

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-450	-400	-350	-300	1	30	1.62	50.89	1.02
-450	-400	-300	-250	2	30	0.25	31.42	-3.15
-450	-400	-250	-200	3	30	0.08	25.13	1.13
-450	-400	-200	-150	4	30	0.05	31.42	33.13
-450	-400	-150	-100	5	30	0.07	76.97	48.69
-400	-350	-300	-250	1	35	2.79	75.13	-0.90
-400	-350	-250	-200	2	35	0.36	38.78	1.77
-400	-350	-200	-150	3	35	0.15	40.39	1.93
-400	-350	-150	-100	4	35	0.17	91.55	18.71
-400	-350	-100	-50	5	35	0.25	235.62	77.10
-350	-300	-250	-200	1	70	8.70	117.14	3.90
-350	-300	-200	-150	2	70	1.40	75.40	1.53
-350	-300	-150	-100	3	70	1.23	165.61	1.51
-350	-300	-100	-50	4	70	1.63	438.93	4.49
-350	-300	-50	0	5	70	1.24	584.34	4.98
-300	-250	-200	-150	1	120	8.46	66.44	3.05
-300	-250	-150	-100	2	120	5.04	158.34	1.76
-300	-250	-100	-50	3	120	5.92	464.96	4.15
-300	-250	-50	0	4	120	4.03	633.03	4.76
-300	-250	0	50	5	120	1.77	486.55	3.15
-250	-200	-150	-100	1	200	18.20	85.77	2.66
-250	-200	-100	-50	2	200	16.57	312.34	4.47
-250	-200	-50	0	3	200	9.52	448.62	5.58
-250	-200	0	50	4	200	4.03	379.82	4.68
-250	-200	50	100	5	200	3.01	496.45	2.92
-200	-150	-100	-50	1	280	65.38	220.07	6.13
-200	-150	-50	0	2	280	30.72	413.61	6.96
-200	-150	0	50	3	280	12.34	415.36	6.55
-200	-150	50	100	4	280	9.05	609.24	5.05
-200	-150	100	150	5	280	3.80	447.68	4.51
-150	-100	-50	0	1	150	66.64	418.71	8.01
-150	-100	0	50	2	150	22.31	560.71	7.75
-150	-100	50	100	3	150	14.76	927.40	6.89
-150	-100	100	150	4	150	5.90	741.42	6.00
-150	-100	150	200	5	150	2.70	593.76	5.68
-100	-50	0	50	1	55	22.32	382.47	5.80
-100	-50	50	100	2	55	11.22	769.06	5.13
-100	-50	100	150	3	55	4.37	748.84	4.26
-100	-50	150	200	4	55	1.91	654.59	3.68
-100	-50	200	250	5	55	1.14	683.72	0.61
-50	0	50	100	1	60	16.12	253.21	5.15
-50	0	100	150	2	60	5.78	363.17	4.13
-50	0	150	200	3	60	2.34	367.57	3.64
-50	0	200	250	4	60	1.36	427.26	3.38
-50	0	250	300	5	60	1.48	813.67	2.42
0	50	100	150	1	250	38.90	146.65	6.75
0	50	150	200	2	250	11.42	172.21	4.90
0	50	200	250	3	250	6.23	234.87	4.57
0	50	250	300	4	250	6.86	517.23	5.11
0	50	300	350	5	250	5.00	659.73	5.83
50	100	150	200	1	620	82.29	125.09	6.03
50	100	200	250	2	620	34.29	208.50	5.01
50	100	250	300	3	620	38.48	584.94	6.07
50	100	300	350	4	620	21.11	641.80	5.77
50	100	350	400	5	620	8.26	439.47	5.23

Sagala Line-N1000

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
100	150	200	250	1	490	34.84	67.01	4.39
100	150	250	300	2	490	31.44	241.89	5.38
100	150	300	350	3	490	17.10	328.91	5.01
100	150	350	400	4	490	6.35	244.27	5.19
100	150	400	450	5	490	5.91	397.86	5.89
150	200	250	300	1	350	43.02	115.84	4.96
150	200	300	350	2	350	19.15	206.27	4.87
150	200	350	400	3	350	6.53	175.84	4.78
150	200	400	450	4	350	5.05	271.97	6.40
150	200	450	500	5	350	4.27	402.44	5.19
200	250	300	350	1	280	43.26	145.61	4.97
200	250	350	400	2	280	10.42	140.29	5.12
200	250	400	450	3	280	5.98	201.29	4.99
200	250	450	500	4	280	4.66	313.71	4.18
200	250	500	550	5	280	1.83	215.59	3.14
250	300	350	400	1	270	42.24	147.45	6.42
250	300	400	450	2	270	16.63	232.20	5.87
250	300	450	500	3	270	11.24	392.35	5.00
250	300	500	550	4	270	4.17	291.12	3.93
250	300	550	600	5	270	2.30	281.00	2.28
300	350	400	450	1	230	45.68	187.18	7.92
300	350	450	500	2	230	23.42	383.88	6.97
300	350	500	550	3	230	7.42	304.05	5.79
300	350	550	600	4	230	3.58	293.40	5.61
300	350	600	650	5	230	2.47	354.25	4.92
350	400	450	500	1	250	41.56	156.68	7.04
350	400	500	550	2	250	10.34	155.92	5.80
350	400	550	600	3	250	4.16	156.83	5.75
350	400	600	650	4	250	2.36	177.94	4.99
350	400	650	700	5	250	1.88	248.06	4.11
400	450	500	550	1	400	89.69	211.33	7.46
400	450	550	600	2	400	27.96	263.52	8.31
400	450	600	650	3	400	11.94	281.33	6.70
400	450	650	700	4	400	9.07	427.41	6.24
400	450	700	750	5	400	8.40	692.72	6.15
450	500	550	600	1	630	101.84	152.35	7.04
450	500	600	650	2	630	33.63	201.24	5.41
450	500	650	700	3	630	23.09	345.43	5.05
450	500	700	750	4	630	20.58	615.75	5.45
450	500	750	800	5	630	10.45	547.16	4.53
500	550	600	650	1	300	29.72	93.37	6.69
500	550	650	700	2	300	15.45	194.15	6.40
500	550	700	750	3	300	11.53	362.23	6.58
500	550	750	800	4	300	5.37	337.41	5.95
500	550	800	850	5	300	2.58	283.69	4.75
550	600	650	700	1	310	28.46	86.53	5.37
550	600	700	750	2	310	16.11	195.91	5.71
550	600	750	800	3	310	6.65	202.18	4.84
550	600	800	850	4	310	2.88	175.12	5.50
550	600	850	900	5	310	1.93	205.37	6.36
600	650	700	750	1	860	115.54	126.62	5.45
600	650	750	800	2	860	34.02	149.13	4.22
600	650	800	850	3	860	12.33	135.13	5.12
600	650	850	900	4	860	7.76	170.08	5.00
600	650	900	950	5	860	8.67	332.55	5.66

Sagala Line-N1000

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
650	700	750	800	1	750	89.30	112.22	4.35
650	700	800	850	2	750	18.90	95.00	4.50
650	700	850	900	3	750	10.67	134.08	4.29
650	700	900	950	4	750	11.02	276.96	5.07
650	700	950	1000	5	750	6.75	296.88	4.49
700	750	800	850	1	400	26.81	63.17	3.98
700	750	850	900	2	400	11.19	105.46	4.51
700	750	900	950	3	400	10.06	237.03	5.11
700	750	950	1000	4	400	6.07	286.04	4.76
750	800	850	900	1	350	14.67	39.50	3.23
750	800	900	950	2	350	8.91	95.97	3.73
750	800	950	1000	3	350	5.13	138.14	3.49
800	850	900	950	1	400	13.73	32.35	3.69
800	850	950	1000	2	400	6.38	60.13	3.26
850	900	950	1000	1	260	11.52	41.76	2.85

Sagala Line-N750

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-1000	-950	-900	-850	1	100	34.82	328.17	16.95
-1000	-950	-850	-800	2	100	13.65	514.59	5.64
-1000	-950	-800	-750	3	100	6.45	607.90	6.19
-1000	-950	-750	-700	4	100	5.77	1087.62	5.46
-1000	-950	-700	-650	5	100	5.19	1712.01	5.42
-950	-900	-850	-800	1	120	50.30	395.06	15.57
-950	-900	-800	-750	2	120	13.27	416.89	5.17
-950	-900	-750	-700	3	120	10.50	824.67	4.65
-950	-900	-700	-650	4	120	8.57	1346.17	5.43
-950	-900	-650	-600	5	120	4.67	1283.73	6.41
-900	-850	-800	-750	1	120	30.63	240.57	7.15
-900	-850	-750	-700	2	120	17.81	559.52	4.04
-900	-850	-700	-650	3	120	11.38	893.78	5.30
-900	-850	-650	-600	4	120	6.49	1019.45	5.97
-900	-850	-600	-550	5	120	2.15	591.01	6.97
-850	-800	-750	-700	1	380	157.26	390.04	8.30
-850	-800	-700	-650	2	380	67.32	667.87	6.57
-850	-800	-650	-600	3	380	35.40	877.99	7.41
-850	-800	-600	-550	4	380	10.62	526.80	7.54
-850	-800	-550	-500	5	380	6.73	584.21	6.09
-800	-750	-700	-650	1	550	369.19	632.64	12.83
-800	-750	-650	-600	2	550	117.55	805.73	8.99
-800	-750	-600	-550	3	550	28.64	490.77	9.55
-800	-750	-550	-500	4	550	15.52	531.90	6.94
-800	-750	-500	-450	5	550	7.19	431.23	6.44
-750	-700	-650	-600	1	460	411.44	842.98	10.21
-750	-700	-600	-550	2	460	80.20	657.28	8.93
-750	-700	-550	-500	3	460	32.20	659.73	6.45
-750	-700	-500	-450	4	460	14.17	580.65	5.59
-750	-700	-450	-400	5	460	9.70	695.59	5.90
-700	-650	-600	-550	1	290	167.29	543.68	17.41
-700	-650	-550	-500	2	290	35.44	460.71	6.79
-700	-650	-500	-450	3	290	14.39	467.66	5.72
-700	-650	-450	-400	4	290	9.22	599.29	6.01
-700	-650	-400	-350	5	290	9.96	1132.92	6.28
-650	-600	-550	-500	1	150	42.62	267.79	14.19
-650	-600	-500	-450	2	150	9.44	237.25	4.04
-650	-600	-450	-400	3	150	5.04	316.67	3.85
-650	-600	-400	-350	4	150	5.05	634.60	4.95
-650	-600	-350	-300	5	150	2.90	637.74	2.35
-600	-550	-500	-450	1	180	48.92	256.14	22.95
-600	-550	-450	-400	2	180	5.89	123.36	4.77
-600	-550	-400	-350	3	180	4.39	229.86	4.72
-600	-550	-350	-300	4	180	2.22	232.48	4.66
-600	-550	-300	-250	5	180	1.99	364.69	3.77
-550	-500	-450	-400	1	300	61.98	194.72	15.51
-550	-500	-400	-350	2	300	21.32	267.92	7.35
-550	-500	-350	-300	3	300	9.53	299.39	6.38
-550	-500	-300	-250	4	300	7.69	483.18	4.98
-550	-500	-250	-200	5	300	5.31	583.86	5.38
-500	-450	-400	-350	1	300	65.32	205.21	16.16
-500	-450	-350	-300	2	300	9.83	123.53	4.30
-500	-450	-300	-250	3	300	7.01	220.23	3.46
-500	-450	-250	-200	4	300	4.43	278.35	4.39
-500	-450	-200	-150	5	300	2.12	233.11	2.51

Sagala Line-N750

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-450	-400	-350	-300	1	300	49.07	154.16	9.81
-450	-400	-300	-250	2	300	21.36	268.42	5.35
-450	-400	-250	-200	3	300	13.53	425.06	6.64
-450	-400	-200	-150	4	300	6.30	395.84	6.31
-450	-400	-150	-100	5	300	5.96	655.34	7.24
-400	-350	-300	-250	1	180	31.08	162.73	5.68
-400	-350	-250	-200	2	180	17.48	366.10	6.49
-400	-350	-200	-150	3	180	7.64	400.03	5.39
-400	-350	-150	-100	4	180	6.49	679.63	7.63
-400	-350	-100	-50	5	180	3.40	623.08	5.69
-350	-300	-250	-200	1	200	43.13	203.25	7.22
-350	-300	-200	-150	2	200	14.09	265.59	5.81
-350	-300	-150	-100	3	200	10.30	485.38	7.19
-350	-300	-100	-50	4	200	4.88	459.93	5.73
-350	-300	-50	0	5	200	2.20	362.85	4.66
-300	-250	-200	-150	1	150	39.50	248.19	5.48
-300	-250	-150	-100	2	150	22.74	571.52	7.06
-300	-250	-100	-50	3	150	9.51	597.53	5.31
-300	-250	-50	0	4	150	4.03	506.42	5.01
-300	-250	0	50	5	150	2.21	486.00	4.98
-250	-200	-150	-100	1	90	27.66	289.65	6.14
-250	-200	-100	-50	2	90	9.06	379.50	4.51
-250	-200	-50	0	3	90	3.60	376.99	4.78
-250	-200	0	50	4	90	1.84	385.37	4.67
-250	-200	50	100	5	90	1.42	520.46	5.72
-200	-150	-100	-50	1	120	35.37	277.80	7.17
-200	-150	-50	0	2	120	8.76	275.20	6.10
-200	-150	0	50	3	120	3.98	312.59	4.26
-200	-150	50	100	4	120	2.83	444.54	5.71
-200	-150	100	150	5	120	2.80	769.69	3.82
-150	-100	-50	0	1	340	97.81	271.13	18.35
-150	-100	0	50	2	340	28.64	317.56	9.05
-150	-100	50	100	3	340	18.22	505.06	8.03
-150	-100	100	150	4	340	17.27	957.45	8.40
-150	-100	150	200	5	340	9.19	891.61	7.52
-100	-50	0	50	1	720	116.99	153.14	13.37
-100	-50	50	100	2	720	46.32	242.53	5.92
-100	-50	100	150	3	720	39.90	522.29	5.98
-100	-50	150	200	4	720	19.92	521.50	5.95
-100	-50	200	250	5	720	9.36	428.83	5.69
-50	0	50	100	1	1300	122.29	88.66	9.67
-50	0	100	150	2	1300	75.04	217.61	5.10
-50	0	150	200	3	1300	33.41	242.22	4.93
-50	0	200	250	4	1300	14.72	213.43	4.85
-50	0	250	300	5	1300	11.59	294.09	5.94
0	50	100	150	1	1200	113.95	89.50	7.23
0	50	150	200	2	1200	34.01	106.85	3.05
0	50	200	250	3	1200	12.55	98.57	2.97
0	50	250	300	4	1200	8.65	135.87	3.40
0	50	300	350	5	1200	9.24	254.00	4.29
50	100	150	200	1	900	94.50	98.96	4.35
50	100	200	250	2	900	24.74	103.63	3.60
50	100	250	300	3	900	11.93	124.93	3.16
50	100	300	350	4	900	11.30	236.67	3.92
50	100	350	400	5	900	5.38	197.19	3.43

Sagala Line-N750

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
100	150	200	250	1	750	69.25	87.02	3.82
100	150	250	300	2	750	22.25	111.84	3.33
100	150	300	350	3	750	17.98	225.94	4.17
100	150	350	400	4	750	8.43	211.87	3.65
100	150	400	450	5	750	3.49	153.50	3.38
150	200	250	300	1	860	45.72	50.10	3.44
150	200	300	350	2	860	24.90	109.15	3.87
150	200	350	400	3	860	11.03	120.88	3.42
150	200	400	450	4	860	3.98	87.23	2.55
150	200	450	500	5	860	4.84	185.65	2.04
200	250	300	350	1	1100	75.52	64.71	4.83
200	250	350	400	2	1100	22.72	77.87	3.74
200	250	400	450	3	1100	7.49	64.17	3.24
200	250	450	500	4	1100	8.40	143.94	2.96
200	250	500	550	5	1100	8.86	265.69	3.41
250	300	350	400	1	1100	61.17	52.41	4.79
250	300	400	450	2	1100	15.37	52.68	3.81
250	300	450	500	3	1100	14.69	125.86	3.55
250	300	500	550	4	1100	14.27	244.53	4.03
250	300	550	600	5	1100	12.45	373.35	4.46
300	350	400	450	1	1100	38.42	32.92	4.15
300	350	450	500	2	1100	27.69	94.90	3.58
300	350	500	550	3	1100	24.20	207.35	3.99
300	350	550	600	4	1100	20.31	348.03	4.72
300	350	600	650	5	1100	14.23	426.73	4.66
350	400	450	500	1	1200	47.98	37.68	3.60
350	400	500	550	2	1200	29.10	91.42	3.38
350	400	550	600	3	1200	20.80	163.36	3.87
350	400	600	650	4	1200	13.09	205.62	3.77
350	400	650	700	5	1200	8.35	229.53	4.42
400	450	500	550	1	1200	52.70	41.39	3.23
400	450	550	600	2	1200	27.59	86.68	3.57
400	450	600	650	3	1200	14.51	113.96	3.33
400	450	650	700	4	1200	7.96	125.04	4.16
400	450	700	750	5	1200	4.88	134.15	3.53
450	500	550	600	1	950	102.57	101.76	3.28
450	500	600	650	2	950	39.51	156.79	3.17
450	500	650	700	3	950	19.73	195.74	3.44
450	500	700	750	4	950	11.18	221.83	2.91
450	500	750	800	5	950	7.24	251.39	3.27
500	550	600	650	1	1400	193.09	129.99	3.56
500	550	650	700	2	1400	82.60	222.42	3.87
500	550	700	750	3	1400	41.66	280.45	3.41
500	550	750	800	4	1400	25.21	339.43	4.48
500	550	800	850	5	1400	17.64	415.63	5.51
550	600	650	700	1	1800	244.40	127.97	3.96
550	600	700	750	2	1800	97.91	205.06	3.48
550	600	750	800	3	1800	51.94	271.96	4.37
550	600	800	850	4	1800	34.64	362.75	5.14
550	600	850	900	5	1800	22.51	412.52	4.62
600	650	700	750	1	1500	204.56	128.53	3.27
600	650	750	800	2	1500	75.03	188.57	3.71
600	650	800	850	3	1500	44.19	277.65	4.48
600	650	850	900	4	1500	25.40	319.19	4.03
600	650	900	950	5	1500	12.19	268.07	4.05

Sagala Line-N750

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
650	700	750	800	1	1200	111.74	87.76	4.28
650	700	800	850	2	1200	51.81	162.77	4.98
650	700	850	900	3	1200	25.80	202.63	4.68
650	700	900	950	4	1200	11.17	175.46	4.61
650	700	950	1000	5	1200	7.96	218.81	5.22
700	750	800	850	1	1000	89.68	84.52	4.53
700	750	850	900	2	1000	33.66	126.90	4.24
700	750	900	950	3	1000	13.11	123.56	4.24
700	750	950	1000	4	1000	8.68	163.61	4.89
750	800	850	900	1	1300	139.52	101.15	4.77
750	800	900	950	2	1300	41.07	119.10	4.76
750	800	950	1000	3	1300	21.98	159.35	5.17
800	850	900	950	1	1700	122.64	67.99	4.92
800	850	950	1000	2	1700	47.23	104.74	5.08
850	900	950	1000	1	1100	123.63	105.93	4.18

Sagala Line-N500

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-1000	-950	-900	-850	1	130	16.16	117.16	10.18
-1000	-950	-850	-800	2	130	13.31	385.98	4.65
-1000	-950	-800	-750	3	130	8.76	635.09	6.29
-1000	-950	-750	-700	4	130	5.89	854.03	4.09
-1000	-950	-700	-650	5	130	2.48	629.29	5.75
-950	-900	-850	-800	1	300	39.04	122.65	4.84
-950	-900	-800	-750	2	300	21.62	271.68	4.53
-950	-900	-750	-700	3	300	16.00	502.65	4.58
-950	-900	-700	-650	4	300	6.01	377.62	4.69
-950	-900	-650	-600	5	300	4.12	453.02	4.97
-900	-850	-800	-750	1	140	60.98	410.52	4.73
-900	-850	-750	-700	2	140	31.82	856.85	3.54
-900	-850	-700	-650	3	140	10.00	673.20	4.84
-900	-850	-650	-600	4	140	4.73	636.85	1.87
-900	-850	-600	-550	5	140	3.90	918.92	5.47
-850	-800	-750	-700	1	160	157.94	930.34	5.48
-850	-800	-700	-650	2	160	33.60	791.68	5.39
-850	-800	-650	-600	3	160	12.68	746.91	2.06
-850	-800	-600	-550	4	160	8.96	1055.58	4.13
-850	-800	-550	-500	5	160	1.83	377.29	4.03
-800	-750	-700	-650	1	230	225.68	924.78	11.78
-800	-750	-650	-600	2	230	51.16	838.56	6.10
-800	-750	-600	-550	3	230	31.44	1288.33	7.94
-800	-750	-550	-500	4	230	5.90	483.53	5.08
-800	-750	-500	-450	5	230	3.38	484.76	2.03
-750	-700	-650	-600	1	280	170.06	572.42	8.33
-750	-700	-600	-550	2	280	74.41	1001.85	6.72
-750	-700	-550	-500	3	280	13.04	438.93	4.18
-750	-700	-500	-450	4	280	5.95	400.55	2.84
-750	-700	-450	-400	5	280	12.12	1427.85	4.61
-700	-650	-600	-550	1	400	506.64	1193.74	21.46
-700	-650	-550	-500	2	400	35.97	339.01	7.34
-700	-650	-500	-450	3	400	11.74	276.62	5.24
-700	-650	-450	-400	4	400	19.13	901.48	6.86
-700	-650	-400	-350	5	400	13.65	1125.67	7.46
-650	-600	-550	-500	1	550	116.84	200.22	6.74
-650	-600	-500	-450	2	550	28.41	194.73	3.21
-650	-600	-450	-400	3	550	38.19	654.42	4.74
-650	-600	-400	-350	4	550	24.78	849.26	5.03
-650	-600	-350	-300	5	550	12.63	757.50	3.65
-600	-550	-500	-450	1	560	77.29	130.08	9.69
-600	-550	-450	-400	2	560	57.63	387.96	6.16
-600	-550	-400	-350	3	560	38.28	644.25	7.10
-600	-550	-350	-300	4	560	17.86	601.17	5.38
-600	-550	-300	-250	5	560	6.72	395.84	6.40
-550	-500	-450	-400	1	520	85.09	154.22	6.09
-550	-500	-400	-350	2	520	34.93	253.24	5.01
-550	-500	-350	-300	3	520	13.01	235.80	3.27
-550	-500	-300	-250	4	520	4.15	150.43	3.17
-550	-500	-250	-200	5	520	1.79	113.55	1.49
-500	-450	-400	-350	1	600	147.32	231.41	6.41
-500	-450	-350	-300	2	600	35.77	224.75	3.22
-500	-450	-300	-250	3	600	9.59	150.64	2.96
-500	-450	-250	-200	4	600	4.22	132.58	1.62
-500	-450	-200	-150	5	600	8.38	460.71	4.94

Sagala Line-N500

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-450	-400	-350	-300	1	580	247.73	402.55	5.89
-450	-400	-300	-250	2	580	53.38	346.96	5.83
-450	-400	-250	-200	3	580	22.86	371.47	4.89
-450	-400	-200	-150	4	580	35.11	1141.05	7.03
-450	-400	-150	-100	5	580	29.76	1692.56	7.97
-400	-350	-300	-250	1	460	82.21	168.44	5.89
-400	-350	-250	-200	2	460	24.41	200.05	4.83
-400	-350	-200	-150	3	460	32.18	659.32	6.99
-400	-350	-150	-100	4	460	26.02	1066.23	7.73
-400	-350	-100	-50	5	460	17.76	1273.57	8.14
-350	-300	-250	-200	1	500	53.26	100.39	4.36
-350	-300	-200	-150	2	500	47.23	356.11	6.17
-350	-300	-150	-100	3	500	35.11	661.81	6.99
-350	-300	-100	-50	4	500	22.66	854.26	7.98
-350	-300	-50	0	5	500	13.38	882.72	8.23
-300	-250	-200	-150	1	540	61.55	107.43	5.47
-300	-250	-150	-100	2	540	34.83	243.16	6.37
-300	-250	-100	-50	3	540	18.63	325.15	7.22
-300	-250	-50	0	4	540	10.57	368.96	6.96
-300	-250	0	50	5	540	4.48	273.67	5.06
-250	-200	-150	-100	1	360	57.96	151.74	4.44
-250	-200	-100	-50	2	360	21.38	223.89	5.32
-250	-200	-50	0	3	360	10.64	278.55	5.39
-250	-200	0	50	4	360	3.83	200.54	2.96
-250	-200	50	100	5	360	2.00	183.26	0.45
-200	-150	-100	-50	1	250	97.19	366.40	9.23
-200	-150	-50	0	2	250	41.28	622.49	9.42
-200	-150	0	50	3	250	11.63	438.44	6.95
-200	-150	50	100	4	250	6.47	487.83	6.01
-200	-150	100	150	5	250	4.61	608.28	7.58
-150	-100	-50	0	1	300	79.05	248.34	9.47
-150	-100	0	50	2	300	24.34	305.87	7.57
-150	-100	50	100	3	300	10.24	321.70	6.08
-150	-100	100	150	4	300	6.99	439.19	6.73
-150	-100	150	200	5	300	6.01	660.83	6.74
-100	-50	0	50	1	100	11.84	111.59	4.80
-100	-50	50	100	2	100	5.11	192.64	3.95
-100	-50	100	150	3	100	2.97	279.92	5.65
-100	-50	150	200	4	100	2.22	418.46	3.88
-100	-50	200	250	5	100	1.77	583.86	2.41
-50	0	50	100	1	75	7.24	90.98	1.55
-50	0	100	150	2	75	3.31	166.38	2.98
-50	0	150	200	3	75	2.33	292.80	2.76
-50	0	200	250	4	75	1.82	457.42	3.94
-50	0	250	300	5	75	0.65	285.88	2.37
0	50	100	150	1	160	15.55	91.60	4.61
0	50	150	200	2	160	7.38	173.89	3.95
0	50	200	250	3	160	4.79	282.15	5.18
0	50	250	300	4	160	1.77	208.52	3.68
0	50	300	350	5	160	1.47	303.07	5.15
50	100	150	200	1	380	35.67	88.47	4.79
50	100	200	250	2	380	17.69	175.50	5.51
50	100	250	300	3	380	5.42	134.43	4.95
50	100	300	350	4	380	4.48	222.23	5.54
50	100	350	400	5	380	2.81	243.93	5.54

Sagala Line-N500

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
100	150	200	250	1	550	92.00	157.65	8.05
100	150	250	300	2	550	21.24	145.59	5.09
100	150	300	350	3	550	12.87	220.54	4.94
100	150	350	400	4	550	7.71	264.24	5.12
100	150	400	450	5	550	3.30	197.92	2.57
150	200	250	300	1	500	104.36	196.71	10.33
150	200	300	350	2	500	34.29	258.54	5.96
150	200	350	400	3	500	18.56	349.85	6.40
150	200	400	450	4	500	7.25	273.32	5.13
150	200	450	500	5	500	3.69	243.44	4.14
200	250	300	350	1	540	113.40	197.92	8.59
200	250	350	400	2	540	48.30	337.20	8.14
200	250	400	450	3	540	16.86	294.26	6.71
200	250	450	500	4	540	7.54	263.20	6.08
200	250	500	550	5	540	4.95	302.38	6.08
250	300	350	400	1	600	123.50	193.99	13.37
250	300	400	450	2	600	26.75	168.08	6.85
250	300	450	500	3	600	9.76	153.31	5.66
250	300	500	550	4	600	5.39	169.33	4.90
250	300	550	600	5	600	3.50	192.42	4.55
300	350	400	450	1	500	131.08	247.08	13.84
300	350	450	500	2	500	29.21	220.24	8.64
300	350	500	550	3	500	12.32	232.23	7.80
300	350	550	600	4	500	6.82	257.11	6.46
300	350	600	650	5	500	6.03	397.82	8.57
350	400	450	500	1	700	124.68	167.87	14.08
350	400	500	550	2	700	30.72	165.45	7.62
350	400	550	600	3	700	14.23	191.59	6.60
350	400	600	650	4	700	11.80	317.75	8.28
350	400	650	700	5	700	10.16	478.78	8.37
400	450	500	550	1	900	91.81	96.14	10.25
400	450	550	600	2	900	24.59	103.00	6.23
400	450	600	650	3	900	16.86	176.56	7.56
400	450	650	700	4	900	13.35	279.60	7.14
400	450	700	750	5	900	9.27	339.76	7.86
450	500	550	600	1	950	107.58	106.73	16.19
450	500	600	650	2	950	32.37	128.45	8.98
450	500	650	700	3	950	21.58	214.09	6.97
450	500	700	750	4	950	13.72	272.23	7.41
450	500	750	800	5	950	7.03	244.10	5.33
500	550	600	650	1	1100	238.08	203.99	29.13
500	550	650	700	2	1100	40.71	139.52	7.06
500	550	700	750	3	1100	22.73	194.75	7.06
500	550	750	800	4	1100	10.93	187.30	5.34
500	550	800	850	5	1100	7.80	233.91	5.60
550	600	650	700	1	760	63.21	78.39	8.40
550	600	700	750	2	760	21.91	108.68	5.87
550	600	750	800	3	760	9.59	118.93	4.38
550	600	800	850	4	760	6.12	151.79	4.61
550	600	850	900	5	760	4.01	174.05	3.84
600	650	700	750	1	270	33.11	115.58	9.94
600	650	750	800	2	270	8.88	123.99	6.87
600	650	800	850	3	270	3.93	137.18	5.64
600	650	850	900	4	270	2.22	154.99	5.20
600	650	900	950	5	270	1.85	226.02	7.16

Sagala Line-N500

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
650	700	750	800	1	220	30.39	130.19	9.96
650	700	800	850	2	220	8.10	138.80	5.62
650	700	850	900	3	220	3.56	152.51	4.65
650	700	900	950	4	220	2.67	228.77	6.26
650	700	950	1000	5	220	2.78	416.83	5.32
700	750	800	850	1	450	48.78	102.16	8.16
700	750	850	900	2	450	15.09	126.42	6.73
700	750	900	950	3	450	9.56	200.22	8.45
700	750	950	1000	4	450	8.86	371.13	8.94
750	800	850	900	1	800	51.66	60.86	6.07
750	800	900	950	2	800	24.97	117.67	7.54
750	800	950	1000	3	800	19.73	232.44	7.83
800	850	900	950	1	700	49.16	66.19	7.33
800	850	950	1000	2	700	26.83	144.50	7.50
850	900	950	1000	1	550	49.11	84.15	6.81

Sagala Line-N250

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-1000	-950	-900	-850	1	100	103.75	977.82	13.68
-1000	-950	-850	-800	2	100	11.54	435.05	3.99
-1000	-950	-800	-750	3	100	3.55	334.58	3.66
-1000	-950	-750	-700	4	100	2.66	501.40	4.09
-1000	-950	-700	-650	5	100	2.08	686.12	4.66
-950	-900	-850	-800	1	100	37.77	355.97	10.61
-950	-900	-800	-750	2	100	6.29	237.13	3.04
-950	-900	-750	-700	3	100	3.64	343.06	3.08
-950	-900	-700	-650	4	100	2.65	499.51	3.40
-950	-900	-650	-600	5	100	1.79	590.46	3.81
-900	-850	-800	-750	1	130	28.82	208.94	9.23
-900	-850	-750	-700	2	130	6.24	180.96	2.89
-900	-850	-700	-650	3	130	3.77	273.32	3.11
-900	-850	-650	-600	4	130	2.33	337.84	1.65
-900	-850	-600	-550	5	130	1.45	367.93	3.08
-850	-800	-750	-700	1	150	23.74	149.16	4.66
-850	-800	-700	-650	2	150	9.16	230.22	3.59
-850	-800	-650	-600	3	150	4.85	304.73	2.83
-850	-800	-600	-550	4	150	2.73	343.06	1.03
-850	-800	-550	-500	5	150	2.49	547.58	5.38
-800	-750	-700	-650	1	190	37.12	184.13	8.64
-800	-750	-650	-600	2	190	9.88	196.04	3.85
-800	-750	-600	-550	3	190	4.43	219.75	3.44
-800	-750	-550	-500	4	190	3.31	328.38	4.20
-800	-750	-500	-450	5	190	5.77	1001.75	6.50
-750	-700	-650	-600	1	200	38.90	183.31	6.93
-750	-700	-600	-550	2	200	8.45	159.28	3.76
-750	-700	-550	-500	3	200	5.44	256.35	4.74
-750	-700	-500	-450	4	200	8.78	827.50	5.51
-750	-700	-450	-400	5	200	5.16	851.06	4.44
-700	-650	-600	-550	1	230	44.50	182.35	6.18
-700	-650	-550	-500	2	230	11.09	181.78	4.89
-700	-650	-500	-450	3	230	14.94	612.20	5.05
-700	-650	-450	-400	4	230	8.29	679.40	3.95
-700	-650	-400	-350	5	230	2.71	388.67	2.62
-650	-600	-550	-500	1	220	25.74	110.27	5.29
-650	-600	-500	-450	2	220	19.74	338.26	3.93
-650	-600	-450	-400	3	220	9.85	421.97	1.81
-650	-600	-400	-350	4	220	3.12	267.32	5.90
-650	-600	-350	-300	5	220	2.55	382.35	3.70
-600	-550	-500	-450	1	300	87.71	275.55	8.19
-600	-550	-450	-400	2	300	30.13	378.62	3.76
-600	-550	-400	-350	3	300	8.44	265.15	2.79
-600	-550	-350	-300	4	300	6.45	405.27	4.31
-600	-550	-300	-250	5	300	4.38	481.61	4.82
-550	-500	-450	-400	1	440	143.04	306.39	11.55
-550	-500	-400	-350	2	440	26.09	223.54	4.73
-550	-500	-350	-300	3	440	18.81	402.91	6.36
-550	-500	-300	-250	4	440	12.21	523.08	6.12
-550	-500	-250	-200	5	440	6.61	495.55	5.56
-500	-450	-400	-350	1	450	161.02	337.24	7.21
-500	-450	-350	-300	2	450	83.25	697.43	6.84
-500	-450	-300	-250	3	450	48.70	1019.97	6.91
-500	-450	-250	-200	4	450	24.67	1033.37	6.22
-500	-450	-200	-150	5	450	15.74	1153.80	8.23

Sagala Line-N250

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-450	-400	-350	-300	1	370	122.31	311.55	6.88
-450	-400	-300	-250	2	370	56.36	574.25	6.11
-450	-400	-250	-200	3	370	25.84	658.21	5.43
-450	-400	-200	-150	4	370	15.49	789.13	7.24
-450	-400	-150	-100	5	370	9.34	832.69	7.31
-400	-350	-300	-250	1	400	97.20	229.02	6.13
-400	-350	-250	-200	2	400	30.63	288.68	5.13
-400	-350	-200	-150	3	400	15.27	359.79	7.09
-400	-350	-150	-100	4	400	7.58	357.20	6.82
-400	-350	-100	-50	5	400	4.27	352.13	4.29
-350	-300	-250	-200	1	500	171.05	322.42	7.52
-350	-300	-200	-150	2	500	61.58	464.30	9.28
-350	-300	-150	-100	3	500	25.75	485.38	8.85
-350	-300	-100	-50	4	500	14.02	528.54	8.27
-350	-300	-50	0	5	500	6.70	442.02	7.35
-300	-250	-200	-150	1	650	227.75	330.23	13.26
-300	-250	-150	-100	2	650	63.46	368.06	9.51
-300	-250	-100	-50	3	650	29.70	430.64	8.64
-300	-250	-50	0	4	650	13.30	385.69	7.57
-300	-250	0	50	5	650	11.57	587.16	8.23
-250	-200	-150	-100	1	580	107.49	174.67	15.14
-250	-200	-100	-50	2	580	32.15	208.97	7.25
-250	-200	-50	0	3	580	12.85	208.81	5.74
-250	-200	0	50	4	580	10.65	346.12	6.89
-250	-200	50	100	5	580	6.72	382.19	5.25
-200	-150	-100	-50	1	480	84.81	166.52	20.21
-200	-150	-50	0	2	480	13.81	108.46	6.49
-200	-150	0	50	3	480	10.33	202.83	7.94
-200	-150	50	100	4	480	6.17	242.30	6.56
-200	-150	100	150	5	480	4.73	325.06	6.49
-150	-100	-50	0	1	760	52.65	65.29	7.87
-150	-100	0	50	2	760	27.37	135.77	7.80
-150	-100	50	100	3	760	14.25	176.71	6.71
-150	-100	100	150	4	760	9.98	247.52	6.94
-150	-100	150	200	5	760	14.91	647.15	6.85
-100	-50	0	50	1	800	61.24	72.15	10.46
-100	-50	50	100	2	800	19.83	93.45	5.30
-100	-50	100	150	3	800	11.52	135.72	5.35
-100	-50	150	200	4	800	15.91	374.87	6.55
-100	-50	200	250	5	800	10.39	428.42	7.06
-50	0	50	100	1	480	41.49	81.47	14.94
-50	0	100	150	2	480	9.73	76.42	5.59
-50	0	150	200	3	480	10.62	208.52	6.18
-50	0	200	250	4	480	6.48	254.47	6.50
-50	0	250	300	5	480	3.71	254.96	5.46
0	50	100	150	1	300	49.92	156.83	17.54
0	50	150	200	2	300	12.01	150.92	7.14
0	50	200	250	3	300	6.25	196.35	7.07
0	50	250	300	4	300	3.20	201.06	4.97
0	50	300	350	5	300	2.37	260.60	5.12
50	100	150	200	1	200	49.84	234.87	14.17
50	100	200	250	2	200	7.57	142.69	5.87
50	100	250	300	3	200	2.99	140.90	4.31
50	100	300	350	4	200	2.12	199.81	4.86
50	100	350	400	5	200	1.99	328.22	8.53

Sagala Line-N250

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
100	150	200	250	1	140	51.16	344.41	14.12
100	150	250	300	2	140	4.67	125.75	5.04
100	150	300	350	3	140	2.74	184.46	4.76
100	150	350	400	4	140	2.23	300.25	7.39
100	150	400	450	5	140	1.49	351.07	7.69
150	200	250	300	1	130	28.05	203.36	7.90
150	200	300	350	2	130	10.10	292.89	6.02
150	200	350	400	3	130	6.90	500.24	6.23
150	200	400	450	4	130	4.16	603.19	8.04
150	200	450	500	5	130	3.44	872.88	9.15
200	250	300	350	1	200	37.40	176.24	8.10
200	250	350	400	2	200	15.99	301.40	6.37
200	250	400	450	3	200	8.33	392.54	7.02
200	250	450	500	4	200	6.13	577.74	7.69
200	250	500	550	5	200	5.99	987.95	5.79
250	300	350	400	1	350	115.79	311.80	10.98
250	300	400	450	2	350	29.85	321.52	8.42
250	300	450	500	3	350	18.39	495.20	9.38
250	300	500	550	4	350	15.97	860.08	8.03
250	300	550	600	5	350	9.00	848.23	5.46
300	350	400	450	1	600	141.60	222.42	9.23
300	350	450	500	2	600	66.72	419.21	9.97
300	350	500	550	3	600	51.17	803.78	7.86
300	350	550	600	4	600	28.16	884.67	5.62
300	350	600	650	5	600	16.49	906.59	5.94
350	400	450	500	1	330	154.63	441.62	14.10
350	400	500	550	2	330	76.13	869.71	10.02
350	400	550	600	3	330	37.28	1064.71	8.02
350	400	600	650	4	330	20.41	1165.82	8.08
350	400	650	700	5	330	8.74	873.65	8.09
400	450	500	550	1	270	113.22	395.21	9.71
400	450	550	600	2	270	45.78	639.21	7.24
400	450	600	650	3	270	24.16	843.34	7.55
400	450	650	700	4	270	10.10	705.11	7.46
400	450	700	750	5	270	7.82	955.39	8.64
450	500	550	600	1	400	204.62	482.12	9.44
450	500	600	650	2	400	85.98	810.34	9.63
450	500	650	700	3	400	31.45	741.02	9.45
450	500	700	750	4	400	23.65	1114.48	10.38
450	500	750	800	5	400	10.09	832.09	11.40
500	550	600	650	1	420	291.45	654.01	8.12
500	550	650	700	2	420	84.43	757.84	8.10
500	550	700	750	3	420	59.17	1327.77	9.04
500	550	750	800	4	420	23.82	1069.04	9.40
500	550	800	850	5	420	15.96	1253.50	8.60
550	600	650	700	1	640	233.55	343.93	6.10
550	600	700	750	2	640	122.56	721.94	6.73
550	600	750	800	3	640	35.89	528.52	6.39
550	600	800	850	4	640	21.52	633.82	5.40
550	600	850	900	5	640	14.16	729.83	5.11
600	650	700	750	1	420	187.44	420.61	6.48
600	650	750	800	2	420	41.31	370.80	6.94
600	650	800	850	3	420	20.59	462.04	6.07
600	650	850	900	4	420	12.68	569.08	4.53
600	650	900	950	5	420	6.98	548.21	6.95

Sagala Line-N250

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
650	700	750	800	1	440	132.68	284.20	7.40
650	700	800	850	2	440	41.52	355.74	5.80
650	700	850	900	3	440	23.96	513.22	5.71
650	700	900	950	4	440	11.53	493.94	7.46
650	700	950	1000	5	440	6.46	484.31	7.05
700	750	800	850	1	440	99.27	212.64	6.14
700	750	850	900	2	440	47.18	404.24	5.47
700	750	900	950	3	440	20.92	448.11	7.16
700	750	950	1000	4	440	10.73	459.67	6.54
750	800	850	900	1	350	64.27	173.07	5.53
750	800	900	950	2	350	23.00	247.74	7.02
750	800	950	1000	3	350	10.03	270.09	6.04
800	850	900	950	1	440	68.77	147.30	7.09
800	850	950	1000	2	440	23.84	204.26	6.07
850	900	950	1000	1	800	84.77	99.87	6.53