

Apc. 9 Liste des valeurs mesurées au terrain

Kekoro Line-N1500

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
400	350	300	250	1	250	138.58	522.43	15.89
400	350	250	200	2	250	10.85	163.61	10.47
400	350	200	150	3	250	4.89	184.35	8.62
400	350	150	100	4	250	3.64	274.45	11.27
400	950	100	50	5	250	1.94	255.98	11.18
350	300	250	200	1	200	104.16	490.84	16.07
350	300	200	150	2	200	5.43	102.35	3.56
350	300	150	100	3	200	3.49	164.46	7.50
350	300	100	50	4	200	1.75	164.93	7.45
350	300	50	0	5	200	0.94	155.04	5.83
300	250	200	150	1	330	31.92	91.16	3.24
300	250	150	100	2	330	15.89	181.53	5.23
300	250	100	50	3	330	6.84	195.35	5.09
300	250	50	0	4	330	3.31	189.07	5.17
300	250	0	-50	5	330	1.75	174.93	4.81
250	200	150	100	1	1020	137.38	126.94	2.80
250	200	100	50	2	1020	46.72	172.68	3.10
250	200	50	0	3	1020	20.40	188.50	4.30
250	200	0	-50	4	1020	10.20	188.50	4.06
250	200	-50	-100	5	1020	9.79	316.61	4.85
200	150	100	50	1	1300	120.67	87.48	2.47
200	150	50	0	2	1300	38.47	111.56	2.94
200	150	0	-50	3	1300	16.38	118.75	3.57
200	150	-50	-100	4	1300	14.64	212.28	3.52
200	150	-100	-150	5	1300	9.70	246.13	4.01
150	100	50	0	1	1500	169.32	106.39	3.92
150	100	0	-50	2	1500	49.89	125.39	4.10
150	100	-50	-100	3	1500	38.46	241.65	4.38
150	100	-100	-150	4	1500	22.69	285.13	3.66
150	100	-150	-200	5	1500	14.04	308.76	2.96
100	50	0	-50	1	1900	115.03	57.06	2.91
100	50	550	-100	2	1900	63.78	126.55	3.51
100	50	-100	-150	3	1900	33.00	163.69	3.03
100	50	-150	-200	4	1900	18.68	185.32	1.74
100	50	-200	-250	5	1900	18.69	324.49	1.53
50	0	-50	-100	1	3000	226.64	71.20	2.76
50	0	-100	-150	2	3000	85.61	107.58	2.41
50	0	-150	-200	3	3000	40.50	127.23	1.37
50	0	-200	-250	4	3000	36.86	231.60	0.77
50	0	-250	-300	5	3000	26.07	286.65	0.95
0	-50	-100	-150	1	3200	180.23	53.08	1.87
0	-50	-150	-200	2	3200	63.51	74.82	0.68
0	-50	-200	-250	3	3200	50.72	149.38	-0.16
0	-50	-250	-300	4	3200	33.48	197.21	-0.16
0	-50	-300	-350	5	3200	24.70	254.62	0.40
-50	-100	-150	-200	1	3200	174.09	51.27	2.03
-50	-100	-200	-250	2	3200	106.23	125.15	1.02
-50	-100	-250	-300	3	3200	61.93	182.40	0.90
-50	-100	-300	-350	4	3200	42.44	249.99	1.36
-50	-100	-350	-400	5	3200	48.17	496.55	2.36
-100	-150	-200	-250	1	3300	245.94	70.24	1.41
-100	-150	-250	-300	2	3300	114.42	130.71	1.18
-100	-150	-300	-350	3	3300	67.70	193.35	1.39
-100	-150	-350	-400	4	3300	70.76	404.18	2.30
-100	-150	-400	-450	5	3300	56.55	565.27	1.17

Kekoro Line-N1500

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-150	-200	-250	-300	1	4300	302.22	66.24	1.16
-150	-200	-300	-350	2	4300	130.57	114.47	1.50
-150	-200	-350	-400	3	4300	121.61	266.55	2.25
-150	-200	-400	-450	4	4300	92.98	407.59	1.14
-150	-200	-450	-500	5	4300	58.69	450.23	1.10
-200	-250	-300	-350	1	3800	326.59	81.00	1.70
-200	-250	-350	-400	2	3800	225.41	223.63	2.41
-200	-250	-400	-450	3	3800	156.99	389.37	1.21
-200	-250	-450	-500	4	3800	95.32	472.83	1.17
-200	-250	-500	-550	5	3800	68.12	591.33	0.99
-250	-300	-350	-400	1	2600	334.26	121.17	2.95
-250	-300	-400	-450	2	2600	168.58	244.44	1.84
-250	-300	-450	-500	3	2600	94.58	342.84	1.83
-250	-300	-500	-550	4	2600	65.81	477.11	1.91
-250	-300	-550	-600	5	2600	40.36	512.06	1.09
-300	-350	-400	-450	1	2600	545.85	197.87	3.33
-300	-350	-450	-500	2	2600	225.42	326.85	3.13
-300	-350	-500	-550	3	2600	126.20	457.46	3.11
-300	-350	-550	-600	4	2600	68.33	495.38	2.29
-300	-350	-600	-650	5	2600	44.73	567.50	2.22
-350	-400	-450	-500	1	2800	951.69	320.34	3.32
-350	-400	-500	-550	2	2800	413.16	556.28	4.01
-350	-400	-550	-600	3	2800	192.55	648.12	3.35
-350	-400	-600	-650	4	2800	111.31	749.34	3.24
-350	-400	-650	-700	5	2800	22.08	260.12	1.29
-400	-450	-500	-550	1	2000	753.83	355.23	2.00
-400	-450	-550	-600	2	2000	273.00	514.59	1.77
-400	-450	-600	-650	3	2000	134.11	631.98	1.92
-400	-450	-650	-700	4	2000	24.70	232.79	0.23
-400	-450	-700	-750	5	2000	25.23	416.13	-0.18
-450	-500	-550	-600	1	2400	698.63	274.35	1.58
-450	-500	-600	-650	2	2400	255.79	401.79	1.82
-450	-500	-650	-700	3	2400	41.71	163.79	0.60
-450	-500	-700	-750	4	2400	35.86	281.64	0.25
-450	-500	-750	-800	5	2400	37.24	511.84	-0.55
-500	-550	-600	-650	1	2300	792.55	324.77	1.73
-500	-550	-650	-700	2	2300	100.70	165.06	0.93
-500	-550	-700	-750	3	2300	67.64	277.17	0.81
-500	-550	-750	-800	4	2300	53.46	438.13	-0.69
-500	-550	-800	-850	5	2300	39.86	571.67	0.62
-550	-600	-650	-700	1	1600	241.12	142.03	0.70
-550	-600	-700	-750	2	1600	114.12	268.89	0.81
-550	-600	-750	-800	3	1600	68.14	401.38	-0.28
-550	-600	-800	-850	4	1600	44.09	519.42	0.62
-550	-600	-850	-900	5	1600	26.33	542.84	3.26
-600	-650	-700	-750	1	1300	196.96	142.79	1.11
-600	-650	-750	-800	2	1300	90.40	262.15	0.40
-600	-650	-800	-850	3	1300	49.76	360.75	1.00
-600	-650	-850	-900	4	1300	25.10	363.94	3.05
-600	-650	-900	-950	5	1300	12.69	322.00	4.47
-650	-700	-750	-800	1	1600	158.70	93.48	0.95
-650	-700	-800	-850	2	1600	60.50	142.55	1.53
-650	-700	-850	-900	3	1600	21.38	125.94	3.36
-650	-700	-900	-950	4	1600	9.42	110.98	5.02
-650	-700	-950	-1000	5	1600	7.52	155.04	6.00

Kekoro Line-N1500

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-700	-750	-800	-850	1	1800	263.96	138.21	2.10
-700	-750	-850	-900	2	1800	62.65	131.21	3.52
-700	-750	-900	-950	3	1800	23.34	122.21	5.22
-700	-750	-950	-1000	4	1800	16.62	174.04	5.82
-700	-750	-1000	-1050	5	1800	11.12	203.78	6.57
-750	-800	-850	-900	1	1100	116.82	100.09	4.45
-750	-800	-900	-950	2	1100	34.97	119.85	6.91
-750	-800	-950	-1000	3	1100	22.58	193.46	8.06
-750	-800	-1000	-1050	4	1100	14.18	242.99	8.88
-750	-800	-1050	-1100	5	1100	9.55	286.38	9.15
-800	-850	-900	-950	1	700	39.09	52.63	4.76
-800	-850	-950	-1000	2	700	18.81	101.30	6.21
-800	-850	-1000	-1050	3	700	10.79	145.28	8.24
-800	-850	-1050	-1100	4	700	6.83	183.92	8.74
-800	-850	-1100	-1150	5	700	3.20	150.80	8.22
-850	-900	-950	-1000	1	830	51.26	58.21	0.58
-850	-900	-1000	-1050	2	830	20.53	93.25	2.70
-850	-900	-1050	-1100	3	830	10.95	124.34	3.46
-850	-900	-1100	-1150	4	830	4.68	106.28	3.44
-850	-900	-1150	-1200	5	830	6.11	242.83	4.21
-900	-950	-1000	-1050	1	1300	67.62	49.02	1.21
-900	-950	-1050	-1100	2	1300	26.02	75.46	1.75
-900	-950	-1100	-1150	3	1300	9.34	67.71	1.30
-900	-950	-1150	-1200	4	1300	10.72	155.44	1.53
-900	-950	-1200	-1250	5	1300	9.50	241.06	2.82
-950	-1000	-1050	-1100	1	1400	68.32	45.99	1.61
-950	-1000	-1100	-1150	2	1400	18.67	50.27	1.54
-950	-1000	-1150	-1200	3	1400	18.22	122.66	1.96
-950	-1000	-1200	-1250	4	1400	14.65	197.25	3.49
-950	-1000	-1250	-1300	5	1400	9.98	235.15	4.17
-1000	-1050	-1100	-1150	1	750	28.79	36.18	0.29
-1000	-1050	-1150	-1200	2	750	18.76	94.30	0.58
-1000	-1050	-1200	-1250	3	750	11.92	149.79	2.30
-1000	-1050	-1250	-1300	4	750	7.66	192.52	3.13
-1000	-1050	-1300	-1350	5	750	6.97	306.56	4.89
-1050	-1100	-1150	-1200	1	600	34.05	53.49	0.32
-1050	-1100	-1200	-1250	2	600	14.26	89.60	1.39
-1050	-1100	-1250	-1300	3	600	8.00	125.66	2.20
-1050	-1100	-1300	-1350	4	600	6.68	209.86	3.17
-1050	-1100	-1350	-1400	5	600	3.90	214.41	6.33
-1100	-1150	-1200	-1250	1	600	22.83	35.86	1.30
-1100	-1150	-1250	-1300	2	600	9.69	60.88	3.06
-1100	-1150	-1300	-1350	3	600	7.03	110.43	4.07
-1100	-1150	-1350	-1400	4	600	3.73	117.18	7.75
-1150	-1200	-1250	-1300	1	740	53.61	68.28	2.19
-1150	-1200	-1300	-1350	2	740	28.76	146.52	4.30
-1150	-1200	-1350	-1400	3	740	12.61	160.60	7.91
-1200	-1250	-1300	-1350	1	1600	185.10	109.03	3.17
-1200	-1250	-1350	-1400	2	1600	61.88	145.80	7.67
-1250	-1300	-1350	-1400	1	1100	97.59	83.61	5.74

Kekoro Line-N1250

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
1000	950	900	850	1	1400	63.17	42.53	8.96
1000	950	850	800	2	1400	21.96	59.13	10.24
1000	950	800	750	3	1400	10.13	68.19	13.12
1000	950	750	700	4	1400	7.09	95.46	12.07
1000	950	700	650	5	1400	6.03	142.08	17.47
950	900	850	800	1	3200	123.80	36.46	6.63
950	900	800	750	2	3200	39.88	46.98	9.53
950	900	750	700	3	3200	23.93	70.48	10.55
950	900	700	650	4	3200	19.59	115.39	14.76
950	900	650	600	5	3200	13.60	140.19	14.07
900	850	800	750	1	4600	180.92	37.07	5.69
900	850	750	700	2	4600	76.65	62.82	6.75
900	850	700	650	3	4600	56.43	115.62	11.02
900	850	650	600	4	4600	36.50	149.57	11.19
900	850	600	550	5	4600	19.93	142.92	12.28
850	800	750	700	1	3000	131.13	41.20	3.83
850	800	700	650	2	3000	69.44	87.26	8.26
850	800	650	600	3	3000	38.41	120.67	9.70
850	800	600	550	4	3000	19.68	123.65	11.17
850	800	550	500	5	3000	15.03	165.26	13.89
800	750	700	650	1	2900	145.70	47.35	4.59
800	750	650	600	2	2900	57.64	74.93	6.87
800	750	600	550	3	2900	25.64	83.33	7.91
800	750	550	500	4	2900	18.53	120.44	11.34
800	750	500	450	5	2900	12.98	147.64	10.08
750	700	650	600	1	700	47.12	63.44	5.62
750	700	600	550	2	700	12.70	68.40	6.58
750	700	550	500	3	700	8.04	108.25	10.28
750	700	500	450	4	700	4.77	128.45	11.40
750	700	450	400	5	700	3.28	154.57	17.19
700	650	600	550	1	140	10.35	69.68	8.10
700	650	550	500	2	140	4.76	128.18	11.66
700	650	500	450	3	140	2.35	158.20	12.94
700	650	450	400	4	140	1.44	193.88	19.84
700	650	400	350	5	140	1.19	280.39	24.59
650	600	550	500	1	150	12.48	78.41	6.96
650	600	500	450	2	150	4.49	112.85	11.03
650	600	450	400	3	150	2.28	143.26	15.01
650	600	400	350	4	150	1.94	243.79	19.36
650	600	350	300	5	150	0.97	213.31	17.02
600	550	500	450	1	270	24.14	84.26	9.76
600	550	450	400	2	270	6.82	95.23	15.64
600	550	400	350	3	270	4.77	166.50	18.01
600	550	350	300	4	270	2.19	152.89	16.64
600	550	300	250	5	270	1.20	146.61	10.01
550	500	450	400	1	210	24.37	109.37	12.92
550	500	400	350	2	210	7.65	137.33	17.45
550	500	350	300	3	210	2.79	125.21	17.93
550	500	300	250	4	210	1.28	114.89	13.14
550	500	250	200	5	210	1.22	191.64	12.50
500	450	400	350	1	180	121.89	638.21	12.80
500	450	350	300	2	180	11.39	238.55	14.64
500	450	300	250	3	180	2.06	107.86	17.55
500	450	250	200	4	180	1.45	151.84	19.07
500	450	200	150	5	180	0.89	163.10	15.54

Kekoro Line-N1250

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
450	400	350	300	1	180	170.17	891.01	17.51
450	400	300	250	2	180	11.96	250.49	16.24
450	400	250	200	3	180	3.07	160.74	16.98
450	400	200	150	4	180	1.48	154.99	12.51
450	400	150	100	5	180	1.10	201.59	14.00
400	350	300	250	1	100	144.25	1359.52	19.32
400	350	250	200	2	100	7.15	269.55	20.15
400	350	200	150	3	100	1.60	150.80	15.63
400	350	150	100	4	100	1.09	205.46	18.99
400	350	100	50	5	100	0.53	174.83	24.23
350	300	250	200	1	90	90.26	945.20	20.28
350	300	200	150	2	90	3.26	136.55	9.16
350	300	150	100	3	90	1.36	142.42	5.19
350	300	100	50	4	90	0.63	131.95	7.63
350	300	50	0	5	90	0.35	128.28	11.54
300	250	200	150	1	80	47.35	557.83	13.70
300	250	150	100	2	80	4.15	195.56	4.29
300	250	100	50	3	80	1.50	176.71	4.32
300	250	50	0	4	80	0.71	167.29	6.24
300	250	0	-50	5	80	0.56	230.91	4.45
250	200	150	100	1	100	36.34	342.50	12.63
250	200	100	50	2	100	6.43	242.41	6.52
250	200	50	0	3	100	2.50	235.62	7.53
250	200	0	-50	4	100	1.80	339.29	6.31
250	200	-50	-100	5	100	0.72	237.50	5.53
200	150	100	50	1	580	67.39	109.51	4.91
200	150	50	0	2	580	17.99	116.93	7.49
200	150	0	-50	3	580	11.10	180.37	6.97
200	150	-50	-100	4	580	4.11	133.57	6.76
200	150	-100	-150	5	580	3.20	182.00	7.19
150	100	50	0	1	450	40.46	84.74	5.54
150	100	0	-50	2	450	16.95	142.00	6.50
150	100	-50	-100	3	450	5.25	109.96	6.60
150	100	-100	-150	4	450	3.67	153.73	7.81
150	100	-150	-200	5	450	4.30	315.21	8.82
100	50	0	-50	1	630	38.75	57.97	3.66
100	50	-50	-100	2	630	8.86	53.02	3.95
100	50	-100	-150	3	630	5.24	78.39	5.90
100	50	-150	-200	4	630	5.71	170.84	7.23
100	50	-200	-250	5	630	3.89	203.68	7.23
50	0	-50	-100	1	610	28.49	44.02	0.54
50	0	-100	-150	2	610	10.87	67.18	1.03
50	0	-150	-200	3	610	9.85	152.19	2.19
50	0	-200	-250	4	610	6.00	185.41	1.43
50	0	-250	-300	5	610	4.59	248.21	3.23
0	-50	-100	-150	1	750	42.08	52.88	0.35
0	-50	-150	-200	2	750	27.27	137.07	1.48
0	-50	-200	-250	3	750	14.33	180.08	1.22
0	-50	-250	-300	4	750	10.14	254.85	2.46
0	-50	-300	-350	5	750	7.60	334.27	2.45
-50	-100	-150	-200	1	3100	141.97	43.16	0.43
-50	-100	-200	-250	2	3100	53.56	65.13	0.08
-50	-100	-250	-300	3	3100	33.00	100.33	1.11
-50	-100	-300	-350	4	3100	22.49	136.75	1.13
-50	-100	-350	-400	5	3100	14.73	156.74	1.68

Kekoro Line-N1250

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-100	-150	-200	-250	1	3200	165.48	48.74	0.04
-100	-150	-250	-300	2	3200	72.90	85.88	0.53
-100	-150	-300	-350	3	3200	42.91	126.38	0.40
-100	-150	-350	-400	4	3200	25.98	153.03	0.95
-100	-150	-400	-450	5	3200	27.85	287.09	1.77
-150	-200	-250	-300	1	2600	206.42	74.83	0.57
-150	-200	-300	-350	2	2600	88.70	128.61	0.51
-150	-200	-350	-400	3	2600	45.82	166.09	0.94
-150	-200	-400	-450	4	2600	44.95	325.88	1.61
-150	-200	-450	-500	5	2600	26.27	333.29	1.11
-200	-250	-300	-350	1	3050	221.16	68.34	0.33
-200	-250	-350	-400	2	3050	85.52	105.71	0.68
-200	-250	-400	-450	3	3050	72.74	224.77	1.23
-200	-250	-450	-500	4	3050	39.79	245.91	0.85
-200	-250	-500	-550	5	3050	32.00	346.09	0.77
-250	-300	-350	-400	1	2500	174.21	65.68	0.50
-250	-300	-400	-450	2	2500	112.76	170.04	0.97
-250	-300	-450	-500	3	2500	55.16	207.95	0.62
-250	-300	-500	-550	4	2500	41.74	314.71	0.54
-250	-300	-550	-600	5	2500	32.33	426.58	0.60
-300	-350	-400	-450	1	2500	212.70	80.19	0.93
-300	-350	-450	-500	2	2500	84.19	126.96	0.54
-300	-350	-500	-550	3	2500	58.95	222.24	0.51
-300	-350	-550	-600	4	2500	43.97	331.53	0.59
-300	-350	-600	-650	5	2500	23.29	307.30	0.72
-350	-400	-450	-500	1	3100	196.38	59.70	0.68
-350	-400	-500	-550	2	3100	104.44	127.01	0.45
-350	-400	-550	-600	3	3100	70.40	214.03	0.59
-350	-400	-600	-650	4	3100	35.39	215.19	0.70
-350	-400	-650	-700	5	3100	36.11	384.24	0.36
-400	-450	-500	-550	1	2600	251.93	91.32	0.57
-400	-450	-550	-600	2	2600	125.24	181.59	0.62
-400	-450	-600	-650	3	2600	58.32	211.41	0.81
-400	-450	-650	-700	4	2600	53.05	384.60	0.50
-400	-450	-700	-750	5	2600	29.39	372.88	2.34
-450	-500	-550	-600	1	2000	181.15	85.36	0.33
-450	-500	-600	-650	2	2000	65.92	124.26	0.19
-450	-500	-650	-700	3	2000	48.21	227.18	-0.16
-450	-500	-700	-750	4	2000	24.01	226.29	1.54
-450	-500	-750	-800	5	2000	24.03	396.34	2.92
-500	-550	-600	-650	1	1900	165.15	81.92	0.41
-500	-550	-650	-700	2	1900	86.01	170.66	-0.28
-500	-550	-700	-750	3	1900	36.66	181.85	1.16
-500	-550	-750	-800	4	1900	32.92	326.59	2.50
-500	-550	-800	-850	5	1900	33.04	573.62	4.25
-550	-600	-650	-700	1	2000	224.50	105.79	0.45
-550	-600	-700	-750	2	2000	73.81	139.13	1.54
-550	-600	-750	-800	3	2000	56.63	266.86	2.83
-550	-600	-800	-850	4	2000	52.07	490.75	4.67
-550	-600	-850	-900	5	2000	30.70	506.35	6.52
-600	-650	-700	-750	1	2200	155.85	66.77	1.18
-600	-650	-750	-800	2	2200	84.20	144.28	1.87
-600	-650	-800	-850	3	2200	65.69	281.42	3.29
-600	-650	-850	-900	4	2200	36.34	311.36	4.85
-600	-650	-900	-950	5	2200	14.33	214.86	5.17

Kekoro Line-N1250

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-650	-700	-750	-800	1	1650	244.14	139.45	2.79
-650	-700	-800	-850	2	1650	138.84	317.22	3.88
-650	-700	-850	-900	3	1650	67.69	386.64	5.49
-650	-700	-900	-950	4	1650	24.35	278.17	5.80
-650	-700	-950	-1000	5	1650	13.93	278.49	7.26
-700	-750	-800	-850	1	2100	321.44	144.26	2.90
-700	-750	-850	-900	2	2100	122.27	219.50	5.02
-700	-750	-900	-950	3	2100	38.63	173.37	5.51
-700	-750	-950	-1000	4	2100	19.74	177.19	7.28
-700	-750	-1000	-1050	5	2100	11.82	185.67	6.25
-750	-800	-850	-900	1	860	170.25	186.58	4.03
-750	-800	-900	-950	2	860	43.46	190.51	4.12
-750	-800	-950	-1000	3	860	19.02	208.44	5.85
-750	-800	-1000	-1050	4	860	10.52	230.58	4.94
-750	-800	-1050	-1100	5	860	6.37	244.33	4.71
-800	-850	-900	-950	1	880	162.13	173.64	3.93
-800	-850	-950	-1000	2	880	51.29	219.73	6.24
-800	-850	-1000	-1050	3	880	23.73	254.15	5.13
-800	-850	-1050	-1100	4	880	13.03	279.10	5.03
-800	-850	-1100	-1150	5	880	9.63	360.98	5.38
-850	-900	-950	-1000	1	2600	356.27	129.14	4.26
-850	-900	-1000	-1050	2	2600	114.09	165.43	3.98
-850	-900	-1050	-1100	3	2600	51.02	184.94	3.79
-850	-900	-1100	-1150	4	2600	34.47	249.90	4.50
-850	-900	-1150	-1200	5	2600	34.26	434.66	5.09
-900	-950	-1000	-1050	1	2100	194.35	87.22	1.76
-900	-950	-1050	-1100	2	2100	58.02	104.16	1.56
-900	-950	-1100	-1150	3	2100	32.42	145.50	2.04
-900	-950	-1150	-1200	4	2100	29.12	261.38	2.43
-900	-950	-1200	-1250	5	2100	20.30	318.87	2.54
-950	-1000	-1050	-1100	1	1250	78.21	58.97	0.85
-950	-1000	-1100	-1150	2	1250	33.24	100.25	1.30
-950	-1000	-1150	-1200	3	1250	26.26	198.00	1.79
-950	-1000	-1200	-1250	4	1250	17.02	256.66	1.60
-950	-1000	-1250	-1300	5	1250	6.87	181.30	2.20
-1000	-1050	-1100	-1150	1	1200	59.68	46.87	1.22
-1000	-1050	-1150	-1200	2	1200	36.64	115.11	1.80
-1000	-1050	-1200	-1250	3	1200	20.97	164.70	1.60
-1000	-1050	-1250	-1300	4	1200	7.38	115.92	1.15
-1000	-1050	-1300	-1350	5	1200	4.13	113.53	0.60
-1050	-1100	-1150	-1200	1	1000	76.08	71.70	1.63
-1050	-1100	-1200	-1250	2	1000	31.15	117.43	1.66
-1050	-1100	-1250	-1300	3	1000	9.36	88.22	1.40
-1050	-1100	-1300	-1350	4	1000	4.74	89.35	0.80
-1050	-1100	-1350	-1400	5	1000	4.36	143.82	1.58
-1100	-1150	-1200	-1250	1	800	71.96	84.78	1.17
-1100	-1150	-1250	-1300	2	800	15.95	75.16	1.31
-1100	-1150	-1300	-1350	3	800	7.07	83.29	1.04
-1100	-1150	-1350	-1400	4	800	5.69	134.07	1.19
-1150	-1200	-1250	-1300	1	1000	70.39	66.34	1.42
-1150	-1200	-1300	-1350	2	1000	23.11	87.12	1.26
-1150	-1200	-1350	-1400	3	1000	16.01	150.89	0.95
-1200	-1250	-1300	-1350	1	950	52.23	51.82	1.74
-1200	-1250	-1350	-1400	2	950	26.34	104.53	1.73
-1250	-1300	-1350	-1400	1	550	28.88	49.49	0.76

Kekoro Line-N1000

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
1000	950	900	850	1	50	25.97	489.52	15.05
1000	950	850	800	2	50	2.39	180.20	10.07
1000	950	800	750	3	50	0.85	160.22	4.68
1000	950	750	700	4	50	0.66	248.81	6.53
1000	950	700	650	5	50	0.30	197.92	3.82
950	900	850	800	1	35	23.94	644.65	18.43
950	900	800	750	2	35	1.31	141.10	10.90
950	900	750	700	3	35	0.64	172.34	8.28
950	900	700	650	4	35	0.26	140.03	8.68
950	900	650	600	5	35	0.22	207.35	10.98
900	850	800	750	1	50	27.62	520.62	19.61
900	850	750	700	2	50	1.98	149.29	8.43
900	850	700	650	3	50	0.62	116.87	3.40
900	850	650	600	4	50	0.49	184.73	7.23
900	850	600	550	5	50	0.33	217.71	7.14
850	800	750	700	1	180	55.27	289.39	21.44
850	800	700	650	2	180	3.91	81.89	8.22
850	800	650	600	3	180	2.64	138.23	9.84
850	800	600	550	4	180	1.65	172.79	11.33
850	800	550	500	5	180	0.98	179.59	10.75
800	750	700	650	1	300	25.48	80.05	19.03
800	750	650	600	2	300	6.47	81.30	10.19
800	750	600	550	3	300	3.53	110.90	9.69
800	750	550	500	4	300	1.93	121.27	9.34
800	750	500	450	5	300	1.10	120.95	9.81
750	700	650	600	1	600	63.99	100.52	10.69
750	700	600	550	2	600	21.14	132.83	10.79
750	700	550	500	3	600	9.78	153.62	10.41
750	700	500	450	4	600	4.99	156.77	10.47
750	700	450	400	5	600	2.68	147.34	9.80
700	650	600	550	1	1350	83.82	58.52	7.58
700	650	550	500	2	1350	28.37	79.22	8.18
700	650	500	450	3	1350	12.40	86.57	8.26
700	650	450	400	4	1350	6.20	86.57	7.33
700	650	400	350	5	1350	5.12	125.11	7.78
650	600	550	500	1	2450	163.61	62.94	6.36
650	600	500	450	2	2450	51.70	79.55	7.72
650	600	450	400	3	2450	21.90	84.25	7.18
650	600	400	350	4	2450	16.93	130.25	7.93
650	600	350	300	5	2450	12.33	166.01	9.42
600	550	500	450	1	2200	113.28	48.53	5.85
600	550	450	400	2	2200	33.33	57.11	5.43
600	550	400	350	3	2200	23.39	100.20	6.35
600	550	350	300	4	2200	14.84	127.15	8.53
600	550	300	250	5	2200	17.55	263.14	10.97
550	500	450	400	1	1700	59.45	32.96	3.67
550	500	400	350	2	1700	30.03	66.59	4.46
550	500	350	300	3	1700	15.60	86.49	7.07
550	500	300	250	4	1700	17.25	191.27	9.68
550	500	250	200	5	1700	10.52	204.13	9.19
500	450	400	350	1	1800	71.79	37.59	1.76
500	450	350	300	2	1800	24.51	51.33	4.62
500	450	300	250	3	1800	22.48	117.71	6.96
500	450	250	200	4	1800	12.89	134.98	5.47
500	450	200	150	5	1800	10.15	186.01	7.32

Kekoro Line-N1000

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
450	400	350	300	1	2000	73.54	34.65	4.52
450	400	300	250	2	2000	46.99	88.57	7.07
450	400	250	200	3	2000	22.49	105.98	5.40
450	400	200	150	4	2000	15.52	146.27	5.77
450	400	150	100	5	2000	12.32	203.20	9.26
400	350	300	250	1	1100	86.33	73.97	7.42
400	350	250	200	2	1100	27.53	94.35	3.95
400	350	200	150	3	1100	16.15	138.37	4.53
400	350	150	100	4	1100	12.28	210.43	6.94
400	350	100	50	5	1100	8.92	267.49	13.28
350	300	250	200	1	830	89.39	101.50	10.25
350	300	200	150	2	830	31.16	141.53	2.91
350	300	150	100	3	830	20.04	227.56	4.83
350	300	100	50	4	830	13.70	311.13	10.23
350	300	50	0	5	830	8.14	323.51	20.28
300	250	200	150	1	400	85.22	200.79	18.00
300	250	150	100	2	400	21.45	202.16	9.39
300	250	100	50	3	400	12.65	298.06	12.79
300	250	50	0	4	400	7.35	346.36	23.38
300	250	0	-50	5	400	3.59	296.06	20.83
250	200	150	100	1	200	274.78	1294.87	18.23
250	200	100	50	2	200	17.54	330.62	15.71
250	200	50	0	3	200	7.93	373.69	24.12
250	200	0	-50	4	200	3.45	325.15	22.61
250	200	-50	-100	5	200	2.00	329.87	23.14
200	150	100	50	1	120	113.80	893.78	20.61
200	150	50	0	2	120	15.26	479.41	21.73
200	150	0	-50	3	120	5.23	410.76	18.95
200	150	-50	-100	4	120	2.31	362.85	20.26
200	150	-100	-150	5	120	1.47	404.09	15.01
150	100	50	0	1	90	121.29	1270.15	21.99
150	100	0	-50	2	90	12.89	539.94	20.82
150	100	-50	-100	3	90	3.88	406.31	23.05
150	100	-100	-150	4	90	2.00	418.88	18.34
150	100	-150	-200	5	90	1.31	480.14	20.80
100	50	0	-50	1	70	93.05	1252.82	17.75
100	50	-50	-100	2	70	8.71	469.08	19.48
100	50	-100	-150	3	70	2.76	371.61	13.42
100	50	-150	-200	4	70	1.44	387.76	17.06
100	50	-200	-250	5	70	0.72	339.29	10.95
50	0	-50	-100	1	80	135.15	1592.20	26.04
50	0	-100	-150	2	80	8.20	386.42	3.61
50	0	-150	-200	3	80	3.85	453.57	7.64
50	0	-200	-250	4	80	1.34	315.73	10.52
50	0	-250	-300	5	80	0.64	263.89	10.44
0	-50	-100	-150	1	180	30.88	161.69	3.18
0	-50	-150	-200	2	180	11.32	237.09	6.70
0	-50	-200	-250	3	180	3.49	182.74	11.22
0	-50	-250	-300	4	180	1.58	165.46	11.64
0	-50	-300	-350	5	180	0.81	148.44	13.48
-50	-100	-150	-200	1	310	73.12	222.30	4.31
-50	-100	-200	-250	2	310	15.34	186.55	8.88
-50	-100	-250	-300	3	310	6.02	183.02	9.71
-50	-100	-300	-350	4	310	2.76	167.82	9.18
-50	-100	-350	-400	5	310	2.77	294.75	10.99

Kekoro Line-N1000

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-100	-150	-200	-250	1	540	103.41	180.48	4.07
-100	-150	-250	-300	2	540	27.92	194.92	4.98
-100	-150	-300	-350	3	540	11.41	199.14	3.60
-100	-150	-350	-400	4	540	10.88	379.78	4.32
-100	-150	-400	-450	5	540	7.70	470.37	6.37
-150	-200	-250	-300	1	1100	144.30	123.64	4.00
-150	-200	-300	-350	2	1100	44.01	150.83	2.91
-150	-200	-350	-400	3	1100	35.69	305.79	3.60
-150	-200	-400	-450	4	1100	24.59	421.37	6.12
-150	-200	-450	-500	5	1100	13.47	403.94	8.66
-200	-250	-300	-350	1	1700	135.50	75.12	1.15
-200	-250	-350	-400	2	1700	77.65	172.20	0.74
-200	-250	-400	-450	3	1700	47.57	263.73	2.70
-200	-250	-450	-500	4	1700	24.10	267.22	4.88
-200	-250	-500	-550	5	1700	14.38	279.03	8.02
-250	-300	-350	-400	1	2700	215.05	75.07	0.07
-250	-300	-400	-450	2	2700	105.19	146.87	1.78
-250	-300	-450	-500	3	2700	47.11	164.44	4.09
-250	-300	-500	-550	4	2700	25.95	181.17	7.52
-250	-300	-550	-600	5	2700	15.33	187.29	10.47
-300	-350	-400	-450	1	3400	279.61	77.51	1.28
-300	-350	-450	-500	2	3400	97.92	108.57	4.03
-300	-350	-500	-550	3	3400	47.79	132.47	7.67
-300	-350	-550	-600	4	3400	26.22	145.36	10.84
-300	-350	-600	-650	5	3400	27.20	263.89	8.88
-350	-400	-450	-500	1	2300	244.22	100.07	3.26
-350	-400	-500	-550	2	2300	93.38	153.06	6.79
-350	-400	-550	-600	3	2300	43.82	179.56	10.98
-350	-400	-600	-650	4	2300	41.20	337.65	9.81
-350	-400	-650	-700	5	2300	20.12	288.56	7.53
-400	-450	-500	-550	1	3000	337.13	105.91	5.61
-400	-450	-550	-600	2	3000	114.34	143.68	10.72
-400	-450	-600	-650	3	3000	87.89	276.11	11.55
-400	-450	-650	-700	4	3000	44.35	278.66	8.42
-400	-450	-700	-750	5	3000	19.17	210.79	12.25
-450	-500	-550	-600	1	2000	166.97	78.68	8.89
-450	-500	-600	-650	2	2000	91.81	173.06	9.94
-450	-500	-650	-700	3	2000	37.67	177.52	7.89
-450	-500	-700	-750	4	2000	15.63	147.31	11.69
-450	-500	-750	-800	5	2000	14.79	243.94	14.19
-500	-550	-600	-650	1	1400	158.30	106.57	13.02
-500	-550	-650	-700	2	1400	44.78	120.58	12.33
-500	-550	-700	-750	3	1400	17.35	116.80	14.67
-500	-550	-750	-800	4	1400	14.12	190.11	17.54
-500	-550	-800	-850	5	1400	12.73	299.94	16.28
-550	-600	-650	-700	1	1400	137.42	92.51	7.51
-550	-600	-700	-750	2	1400	36.58	98.50	10.29
-550	-600	-750	-800	3	1400	23.97	161.37	14.65
-550	-600	-800	-850	4	1400	19.85	267.26	14.14
-550	-600	-850	-900	5	1400	13.04	307.25	14.25
-600	-650	-700	-750	1	1200	153.55	120.60	2.75
-600	-650	-750	-800	2	1200	72.83	228.80	8.00
-600	-650	-800	-850	3	1200	51.24	402.44	8.22
-600	-650	-850	-900	4	1200	31.01	487.10	8.42
-600	-650	-900	-950	5	1200	17.30	475.56	7.95

Kekoro Line-N1000

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-650	-700	-750	-800	1	400	44.79	105.53	5.81
-650	-700	-800	-850	2	400	23.28	219.41	6.94
-650	-700	-850	-900	3	400	12.33	290.52	7.32
-650	-700	-900	-950	4	400	6.40	301.59	6.74
-650	-700	-950	-1000	5	400	3.44	283.69	6.79
-700	-750	-800	-850	1	310	50.32	152.99	5.14
-700	-750	-850	-900	2	310	19.44	236.41	5.89
-700	-750	-900	-950	3	310	8.75	266.02	5.61
-700	-750	-950	-1000	4	310	4.20	255.38	5.06
-700	-750	-1000	-1050	5	310	3.41	362.85	5.76
-750	-800	-850	-900	1	450	116.36	243.70	3.44
-750	-800	-900	-950	2	450	38.57	323.12	3.59
-750	-800	-950	-1000	3	450	16.14	338.04	3.53
-750	-800	-1000	-1050	4	450	11.85	496.37	3.85
-750	-800	-1050	-1100	5	450	5.89	431.76	3.94
-800	-850	-900	-950	1	850	219.88	243.80	1.96
-800	-850	-950	-1000	2	850	74.39	329.93	2.24
-800	-850	-1000	-1050	3	850	47.91	531.22	2.51
-800	-850	-1050	-1100	4	850	22.06	489.20	3.17
-800	-850	-1100	-1150	5	850	13.11	508.77	3.36
-850	-900	-950	-1000	1	1950	292.07	141.16	2.20
-850	-900	-1000	-1050	2	1950	157.40	304.30	2.68
-850	-900	-1050	-1100	3	1950	63.37	306.28	3.27
-850	-900	-1100	-1150	4	1950	35.84	346.45	3.34
-850	-900	-1150	-1200	5	1950	26.86	454.37	7.49
-900	-950	-1000	-1050	1	2350	293.68	117.78	2.04
-900	-950	-1050	-1100	2	2350	88.23	141.54	2.50
-900	-950	-1100	-1150	3	2350	44.92	180.15	2.34
-900	-950	-1150	-1200	4	2350	31.49	252.58	6.25
-900	-950	-1200	-1250	5	2350	18.89	265.16	9.26
-950	-1000	-1050	-1100	1	2450	221.15	85.07	2.11
-950	-1000	-1100	-1150	2	2450	81.24	125.01	2.02
-950	-1000	-1150	-1200	3	2450	48.41	186.23	5.88
-950	-1000	-1200	-1250	4	2450	26.16	201.27	9.36
-950	-1000	-1250	-1300	5	2450	17.20	231.58	13.71
-1000	-1050	-1100	-1150	1	3150	321.97	96.33	1.18
-1000	-1050	-1150	-1200	2	3150	147.81	176.90	4.84
-1000	-1050	-1200	-1250	3	3150	67.96	203.34	9.55
-1000	-1050	-1250	-1300	4	3150	41.13	246.12	13.96
-1000	-1050	-1300	-1350	5	3150	15.85	165.98	12.40
-1050	-1100	-1150	-1200	1	1500	126.74	79.63	3.08
-1050	-1100	-1200	-1250	2	1500	44.38	111.54	8.91
-1050	-1100	-1250	-1300	3	1500	23.80	149.54	13.46
-1050	-1100	-1300	-1350	4	1500	8.36	105.05	12.11
-1050	-1100	-1350	-1400	5	1500	4.74	104.24	11.36
-1100	-1150	-1200	-1250	1	600	44.64	70.12	7.69
-1100	-1150	-1250	-1300	2	600	18.08	113.60	13.37
-1100	-1150	-1300	-1350	3	600	5.28	82.94	12.84
-1100	-1150	-1350	-1400	4	600	2.83	88.91	11.98
-1150	-1200	-1250	-1300	1	680	86.87	120.40	8.47
-1150	-1200	-1300	-1350	2	680	17.64	97.80	12.14
-1150	-1200	-1350	-1400	3	680	8.11	112.40	12.47
-1200	-1250	-1300	-1350	1	350	22.60	60.86	6.48
-1200	-1250	-1350	-1400	2	350	8.02	86.38	8.97
-1250	-1300	-1350	-1400	1	300	25.57	80.33	4.17

Kekoro Line-N750

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
1000	950	900	850	1	350	34.98	94.19	7.35
1000	950	850	800	2	350	12.56	135.29	12.94
1000	950	800	750	3	350	6.62	178.26	10.90
1000	950	750	700	4	350	4.21	226.73	12.52
1000	950	700	650	5	350	2.67	251.64	14.65
950	900	850	800	1	430	53.83	117.99	16.10
950	900	800	750	2	430	17.46	153.08	9.40
950	900	750	700	3	430	9.74	213.48	10.01
950	900	700	650	4	430	5.78	253.37	11.40
950	900	650	600	5	430	4.03	309.15	11.28
900	850	800	750	1	170	89.99	498.90	25.88
900	850	750	700	2	170	8.77	194.48	19.63
900	850	700	650	3	170	3.31	183.51	11.96
900	850	650	600	4	170	2.15	238.39	10.07
900	850	600	550	5	170	1.49	289.12	9.90
850	800	750	700	1	80	81.81	963.80	21.57
850	800	700	650	2	80	4.81	226.67	19.28
850	800	650	600	3	80	1.57	184.96	15.53
850	800	600	550	4	80	0.97	228.55	8.08
850	800	550	500	5	80	0.62	255.65	8.28
800	750	700	650	1	55	35.78	613.12	16.94
800	750	650	600	2	55	2.13	146.00	15.90
800	750	600	550	3	55	0.86	147.37	6.28
800	750	550	500	4	55	0.51	174.79	7.02
800	750	500	450	5	55	0.31	185.93	4.68
750	700	650	600	1	60	30.12	473.12	16.51
750	700	600	550	2	60	1.72	108.07	8.26
750	700	550	500	3	60	0.79	124.09	4.13
750	700	500	450	4	60	0.44	138.23	1.24
750	700	450	400	5	60	0.22	120.95	-4.59
700	650	600	550	1	80	19.93	234.79	19.37
700	650	550	500	2	80	2.66	125.35	8.70
700	650	500	450	3	80	1.29	151.97	5.79
700	650	450	400	4	80	0.60	141.37	5.15
700	650	400	350	5	80	0.35	144.32	6.77
650	600	550	500	1	290	33.90	110.17	13.67
650	600	500	450	2	290	8.59	111.67	6.66
650	600	450	400	3	290	3.56	115.70	6.04
650	600	400	350	4	290	1.98	128.70	7.73
650	600	350	300	5	290	1.09	123.98	8.70
600	550	500	450	1	300	23.88	75.02	2.64
600	550	450	400	2	300	6.78	85.20	1.26
600	550	400	350	3	300	3.25	102.10	2.61
600	550	350	300	4	300	1.68	105.56	4.27
600	550	300	250	5	300	1.72	189.12	4.53
550	500	450	400	1	300	16.30	51.21	1.28
550	500	400	350	2	300	6.03	75.78	1.67
550	500	350	300	3	300	2.63	82.62	3.23
550	500	300	250	4	300	2.45	153.94	4.71
550	500	250	200	5	300	1.42	156.14	3.96
500	450	400	350	1	1250	64.93	48.96	3.19
500	450	350	300	2	1250	20.28	61.16	2.64
500	450	300	250	3	1250	15.88	119.73	4.74
500	450	250	200	4	1250	8.41	126.82	5.06
500	450	200	150	5	1250	7.73	203.99	9.94

Kekoro Line-N750

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
450	400	350	300	1	2400	107.82	42.34	3.40
450	400	300	250	2	2400	53.80	84.51	4.82
450	400	250	200	3	2400	23.25	91.30	4.37
450	400	200	150	4	2400	19.98	156.92	9.03
450	400	150	100	5	2400	13.92	191.32	13.14
400	350	300	250	1	2250	170.82	71.55	4.88
400	350	250	200	2	2250	52.57	88.08	3.66
400	350	200	150	3	2250	38.75	162.32	8.12
400	350	150	100	4	2250	24.31	203.66	11.39
400	350	100	50	5	2250	21.22	311.10	13.14
350	300	250	200	1	950	51.48	51.07	3.79
350	300	200	150	2	950	29.34	116.43	6.93
350	300	150	100	3	950	16.43	163.00	11.31
350	300	100	50	4	950	13.53	268.46	12.81
350	300	50	0	5	950	10.44	362.51	13.08
300	250	200	150	1	350	30.80	82.94	9.64
300	250	150	100	2	350	12.25	131.95	11.54
300	250	100	50	3	350	9.37	252.31	13.42
300	250	50	0	4	350	6.96	374.84	15.81
300	250	0	-50	5	350	2.98	280.86	11.62
250	200	150	100	1	110	15.17	129.98	14.01
250	200	100	50	2	110	4.45	152.51	9.48
250	200	50	0	3	110	2.81	240.76	11.66
250	200	0	-50	4	110	1.11	190.21	7.98
250	200	-50	-100	5	110	1.29	386.84	15.36
200	150	100	50	1	90	63.37	663.61	18.76
200	150	50	0	2	90	8.30	347.67	9.74
200	150	0	-50	3	90	2.36	247.14	7.37
200	150	-50	-100	4	90	2.35	492.18	9.65
200	150	-100	-150	5	90	0.78	285.88	10.41
150	100	50	0	1	90	116.71	1222.18	21.27
150	100	0	-50	2	90	7.94	332.59	11.66
150	100	-50	-100	3	90	5.60	586.43	10.60
150	100	-100	-150	4	90	1.61	337.20	12.08
150	100	-150	-200	5	90	0.66	241.90	14.91
100	50	0	-50	1	90	69.21	724.77	18.41
100	50	-50	-100	2	90	16.51	691.57	12.60
100	50	-100	-150	3	90	3.26	341.39	7.49
100	50	-150	-200	4	90	1.20	251.33	7.13
100	50	-200	-250	5	90	0.73	267.56	18.93
50	0	-50	-100	1	100	298.12	2809.71	21.75
50	0	-100	-150	2	100	8.49	320.07	6.96
50	0	-150	-200	3	100	2.68	252.58	8.57
50	0	-200	-250	4	100	1.46	275.20	12.01
50	0	-250	-300	5	100	1.17	385.94	13.56
0	-50	-100	-150	1	130	13.52	98.02	2.53
0	-50	-150	-200	2	130	3.39	98.31	4.24
0	-50	-200	-250	3	130	1.62	117.45	6.87
0	-50	-250	-300	4	130	1.23	178.35	8.81
0	-50	-300	-350	5	130	0.75	190.31	8.32
-50	-100	-150	-200	1	180	28.65	150.01	4.78
-50	-100	-200	-250	2	180	9.04	189.33	9.07
-50	-100	-250	-300	3	180	6.03	315.73	11.30
-50	-100	-300	-350	4	180	3.34	349.76	11.92
-50	-100	-350	-400	5	180	1.89	346.36	15.72

Kekoro Line-N750

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-100	-150	-200	-250	1	320	21.31	62.76	3.50
-100	-150	-250	-300	2	320	10.72	126.29	6.60
-100	-150	-300	-350	3	320	5.27	155.21	6.87
-100	-150	-350	-400	4	320	2.81	165.52	10.19
-100	-150	-400	-450	5	320	1.72	177.30	9.29
-150	-200	-250	-300	1	700	47.15	63.48	5.77
-150	-200	-300	-350	2	700	16.44	88.54	7.37
-150	-200	-350	-400	3	700	7.54	101.52	10.25
-150	-200	-400	-450	4	700	4.29	115.52	9.31
-150	-200	-450	-500	5	700	2.40	113.10	11.09
-200	-250	-300	-350	1	470	43.41	87.05	6.91
-200	-250	-350	-400	2	470	13.10	105.08	10.13
-200	-250	-400	-450	3	470	6.25	125.33	9.78
-200	-250	-450	-500	4	470	3.13	125.53	12.06
-200	-250	-500	-550	5	470	1.95	136.86	16.19
-250	-300	-350	-400	1	520	46.04	83.45	7.42
-250	-300	-400	-450	2	520	16.06	116.43	8.30
-250	-300	-450	-500	3	520	6.95	125.97	9.68
-250	-300	-500	-550	4	520	3.97	143.91	15.87
-250	-300	-550	-600	5	520	2.31	146.54	17.60
-300	-350	-400	-450	1	350	24.54	66.08	7.30
-300	-350	-450	-500	2	350	7.58	81.65	9.73
-300	-350	-500	-550	3	350	3.55	95.59	15.35
-300	-350	-550	-600	4	350	2.13	114.71	18.61
-300	-350	-600	-650	5	350	1.65	155.51	19.29
-350	-400	-450	-500	1	270	16.05	56.03	7.18
-350	-400	-500	-550	2	270	5.26	73.44	15.73
-350	-400	-550	-600	3	270	2.52	87.96	19.54
-350	-400	-600	-650	4	270	1.73	120.78	22.99
-350	-400	-650	-700	5	270	1.15	140.50	18.11
-400	-450	-500	-550	1	500	27.30	51.46	11.37
-400	-450	-550	-600	2	500	9.25	69.74	17.81
-400	-450	-600	-650	3	500	5.25	98.96	19.77
-400	-450	-650	-700	4	500	3.07	115.74	17.50
-400	-450	-700	-750	5	500	3.07	202.54	16.75
-450	-500	-550	-600	1	1900	105.13	52.15	10.06
-450	-500	-600	-650	2	1900	42.14	83.61	13.92
-450	-500	-650	-700	3	1900	19.06	94.55	13.28
-450	-500	-700	-750	4	1900	17.26	171.23	13.49
-450	-500	-750	-800	5	1900	16.33	283.51	13.76
-500	-550	-600	-650	1	1900	155.76	77.26	5.48
-500	-550	-650	-700	2	1900	50.66	100.52	6.40
-500	-550	-700	-750	3	1900	38.67	191.82	7.28
-500	-550	-750	-800	4	1900	33.62	333.54	8.19
-500	-550	-800	-850	5	1900	17.52	304.17	8.73
-550	-600	-650	-700	1	1700	163.90	90.87	2.57
-550	-600	-700	-750	2	1700	91.03	201.87	3.00
-550	-600	-750	-800	3	1700	69.81	387.03	3.98
-550	-600	-800	-850	4	1700	33.37	370.01	4.82
-550	-600	-850	-900	5	1700	22.36	433.87	8.53
-600	-650	-700	-750	1	3100	563.09	171.19	1.07
-600	-650	-750	-800	2	3100	340.49	414.07	1.90
-600	-650	-800	-850	3	3100	147.16	447.40	2.62
-600	-650	-850	-900	4	3100	91.55	556.67	7.10
-600	-650	-900	-950	5	3100	75.27	800.94	8.57

Kekoro Line-N750

Curr.Elect		Pot.Elect		n	Current (mA)	Potential (mV)	App.Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-650	-700	-750	-800	1	1400	237.78	160.07	2.03
-650	-700	-800	-850	2	1400	73.00	196.57	2.21
-650	-700	-850	-900	3	1400	38.84	261.47	6.63
-650	-700	-900	-950	4	1400	31.23	420.48	8.78
-650	-700	-950	-1000	5	1400	17.33	408.33	12.30
-700	-750	-800	-850	1	1000	156.18	147.20	2.74
-700	-750	-850	-900	2	1000	58.83	221.78	6.79
-700	-750	-900	-950	3	1000	42.59	401.40	9.72
-700	-750	-950	-1000	4	1000	22.90	431.65	13.14
-700	-750	-1000	-1050	5	1000	13.57	447.63	18.50
-750	-800	-850	-900	1	1100	187.80	160.91	5.01
-750	-800	-900	-950	2	1100	97.40	333.81	9.16
-750	-800	-950	-1000	3	1100	46.82	401.15	12.68
-750	-800	-1000	-1050	4	1100	25.49	436.80	18.19
-750	-800	-1050	-1100	5	1100	19.23	576.67	21.99
-800	-850	-900	-950	1	1200	143.12	112.41	6.84
-800	-850	-950	-1000	2	1200	54.47	171.12	11.01
-800	-850	-1000	-1050	3	1200	26.55	208.52	17.00
-800	-850	-1050	-1100	4	1200	18.77	294.84	21.55
-800	-850	-1100	-1150	5	1200	8.21	225.68	20.99
-850	-900	-950	-1000	1	2250	237.96	99.68	6.69
-850	-900	-1000	-1050	2	2250	88.33	148.00	13.95
-850	-900	-1050	-1100	3	2250	55.02	230.47	18.86
-850	-900	-1100	-1150	4	2250	22.57	189.08	18.85
-850	-900	-1150	-1200	5	2250	10.67	156.43	18.29
-900	-950	-1000	-1050	1	1800	241.50	126.45	10.05
-900	-950	-1050	-1100	2	1800	101.77	213.15	17.03
-900	-950	-1100	-1150	3	1800	34.33	179.75	17.73
-900	-950	-1150	-1200	4	1800	14.50	151.84	17.13
-900	-950	-1200	-1250	5	1800	9.42	172.63	17.95
-950	-1000	-1050	-1100	1	1100	162.93	139.60	13.61
-950	-1000	-1100	-1150	2	1100	36.36	124.61	17.29
-950	-1000	-1150	-1200	3	1100	12.03	103.07	18.77
-950	-1000	-1200	-1250	4	1100	7.16	122.69	18.89
-950	-1000	-1250	-1300	5	1100	2.39	71.67	22.27
-1000	-1050	-1100	-1150	1	1200	146.13	114.77	12.26
-1000	-1050	-1150	-1200	2	1200	28.84	90.60	18.43
-1000	-1050	-1200	-1250	3	1200	13.60	106.81	19.92
-1000	-1050	-1250	-1300	4	1200	4.48	70.37	24.02
-1000	-1050	-1300	-1350	5	1200	4.56	125.35	21.44
-1050	-1100	-1150	-1200	1	2300	212.59	87.11	11.66
-1050	-1100	-1200	-1250	2	2300	71.98	117.98	15.66
-1050	-1100	-1250	-1300	3	2300	19.44	79.66	21.50
-1050	-1100	-1300	-1350	4	2300	17.09	140.06	20.26
-1050	-1100	-1350	-1400	5	2300	9.26	132.81	19.80
-1100	-1150	-1200	-1250	1	840	115.24	129.30	5.88
-1100	-1150	-1250	-1300	2	840	22.23	99.77	13.67
-1100	-1150	-1300	-1350	3	840	14.59	163.70	15.33
-1100	-1150	-1350	-1400	4	840	6.98	156.63	15.59
-1150	-1200	-1250	-1300	1	700	63.65	85.70	7.53
-1150	-1200	-1300	-1350	2	700	29.25	157.53	11.92
-1150	-1200	-1350	-1400	3	700	11.81	159.01	12.69
-1200	-1250	-1300	-1350	1	900	111.56	116.83	7.88
-1200	-1250	-1350	-1400	2	900	30.10	126.08	10.66
-1250	-1300	-1350	-1400	1	720	97.26	127.31	3.84

Kekoro Line-N500

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
1000	950	900	850	1	200	29.83	140.57	8.39
1000	950	850	800	2	200	13.34	251.45	14.41
1000	950	800	750	3	200	5.11	240.80	11.98
1000	950	750	700	4	200	3.02	284.63	13.25
1000	950	700	650	5	200	2.08	343.06	17.83
950	900	850	800	1	360	86.83	227.32	9.03
950	900	800	750	2	360	25.08	262.64	7.22
950	900	750	700	3	360	12.55	328.56	8.26
950	900	700	650	4	360	7.60	397.94	10.41
950	900	650	600	5	360	5.15	471.89	8.48
900	850	800	750	1	360	44.35	116.11	8.70
900	850	750	700	2	360	16.36	171.32	7.11
900	850	700	650	3	360	8.39	219.65	10.06
900	850	650	600	4	360	5.31	278.03	9.10
900	850	600	550	5	360	3.80	348.19	7.77
850	800	750	700	1	400	56.80	133.83	7.32
850	800	700	650	2	400	19.24	181.33	11.13
850	800	650	600	3	400	10.10	237.98	9.36
850	800	600	550	4	400	6.47	304.89	8.59
850	800	550	500	5	400	5.05	416.46	8.65
800	750	700	650	1	420	42.23	94.76	11.04
800	750	650	600	2	420	14.74	132.31	7.57
800	750	600	550	3	420	7.86	176.38	6.96
800	750	550	500	4	420	5.78	259.41	7.57
800	750	500	450	5	420	2.52	197.92	7.00
750	700	650	600	1	160	37.26	219.48	25.59
750	700	600	550	2	160	5.22	122.99	2.98
750	700	550	500	3	160	3.39	199.69	4.33
750	700	500	450	4	160	1.39	163.76	3.56
750	700	450	400	5	160	0.82	169.06	8.28
700	650	600	550	1	180	15.84	82.94	2.88
700	650	550	500	2	180	7.68	160.85	3.92
700	650	500	450	3	180	2.81	147.13	2.77
700	650	450	400	4	180	1.53	160.22	5.62
700	650	400	350	5	180	0.98	179.59	7.06
650	600	550	500	1	590	50.07	79.98	3.10
650	600	500	450	2	590	14.72	94.06	3.10
650	600	450	400	3	590	7.06	112.78	5.04
650	600	400	350	4	590	4.30	137.38	6.73
650	600	350	300	5	590	2.27	126.92	12.00
600	550	500	450	1	400	25.50	60.08	1.91
600	550	450	400	2	400	9.26	87.27	2.97
600	550	400	350	3	400	5.13	120.87	4.54
600	550	350	300	4	400	2.47	116.40	9.80
600	550	300	250	5	400	1.77	145.97	6.87
550	500	450	400	1	480	25.91	50.87	3.99
550	500	400	350	2	480	11.45	89.93	7.08
550	500	350	300	3	480	4.47	87.77	11.22
550	500	300	250	4	480	3.09	121.34	9.69
550	500	250	200	5	480	1.78	122.33	10.14
500	450	400	350	1	1000	40.45	38.12	6.14
500	450	350	300	2	1000	12.82	48.33	10.83
500	450	300	250	3	1000	7.24	68.24	10.73
500	450	250	200	4	1000	3.66	68.99	9.61
500	450	200	150	5	1000	3.11	102.59	10.89

Kekoro Line-N500

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
450	400	350	300	1	320	73.25	215.74	7.82
450	400	300	250	2	320	20.25	238.56	10.73
450	400	250	200	3	320	7.91	232.97	10.00
450	400	200	150	4	320	6.13	361.09	10.53
450	400	150	100	5	320	4.57	471.09	11.26
400	350	300	250	1	1500	87.52	54.99	7.91
400	350	250	200	2	1500	22.74	57.15	10.18
400	350	200	150	3	1500	14.24	89.47	11.56
400	350	150	100	4	1500	9.13	114.73	12.51
400	350	100	50	5	1500	11.71	257.52	14.93
350	300	250	200	1	2100	120.72	54.18	4.42
350	300	200	150	2	2100	45.67	81.99	8.31
350	300	150	100	3	2100	22.44	100.71	12.06
350	300	100	50	4	2100	25.80	231.58	14.81
350	300	50	0	5	2100	12.50	196.35	15.39
300	250	200	150	1	3300	198.32	56.64	4.59
300	250	150	100	2	3300	74.43	85.03	8.28
300	250	100	50	3	3300	73.68	210.43	12.48
300	250	50	0	4	3300	34.67	198.03	12.61
300	250	0	-50	5	3300	16.52	165.13	14.69
250	200	150	100	1	2200	111.13	47.61	5.03
250	200	100	50	2	2200	81.56	139.76	9.55
250	200	50	0	3	2200	34.66	148.48	10.00
250	200	0	-50	4	2200	14.37	123.12	12.34
250	200	-50	-100	5	2200	5.50	82.47	13.82
200	150	100	50	1	900	90.74	95.02	7.02
200	150	50	0	2	900	30.40	127.34	7.33
200	150	0	-50	3	900	10.71	112.15	9.17
200	150	-50	-100	4	900	3.78	79.17	10.43
200	150	-100	-150	5	900	3.19	116.92	12.87
150	100	50	0	1	160	12.77	75.22	3.99
150	100	0	-50	2	160	3.23	76.11	8.32
150	100	-50	-100	3	160	0.99	58.32	11.16
150	100	-100	-150	4	160	0.80	94.25	15.94
150	100	-150	-200	5	160	0.56	115.45	15.43
100	50	0	-50	1	120	13.10	102.89	10.37
100	50	-50	-100	2	120	2.50	78.54	10.57
100	50	-100	-150	3	120	1.83	143.73	14.27
100	50	-150	-200	4	120	1.20	188.50	13.86
100	50	-200	-250	5	120	0.70	192.42	16.24
50	0	-50	-100	1	160	7.28	42.88	6.12
50	0	-100	-150	2	160	4.18	98.49	9.01
50	0	-150	-200	3	160	2.39	140.78	8.10
50	0	-200	-250	4	160	1.31	154.33	7.76
50	0	-250	-300	5	160	0.93	191.74	8.64
0	-50	-100	-150	1	240	17.87	70.18	5.65
0	-50	-150	-200	2	240	6.23	97.86	7.67
0	-50	-200	-250	3	240	2.73	107.21	7.12
0	-50	-250	-300	4	240	1.75	137.44	8.07
0	-50	-300	-350	5	240	1.43	196.55	9.34
-50	-100	-150	-200	1	900	46.41	48.60	8.27
-50	-100	-200	-250	2	900	13.56	56.80	9.67
-50	-100	-250	-300	3	900	6.99	73.20	10.95
-50	-100	-300	-350	4	900	4.99	104.51	11.97
-50	-100	-350	-400	5	900	2.72	99.69	14.14

Kekoro Line-N500

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-100	-150	-200	-250	1	420	20.05	44.99	8.17
-100	-150	-250	-300	2	420	7.40	66.42	12.24
-100	-150	-300	-350	3	420	4.56	102.33	14.38
-100	-150	-350	-400	4	420	2.23	100.08	16.18
-100	-150	-400	-450	5	420	1.54	120.95	17.02
-150	-200	-250	-300	1	170	8.56	47.46	4.78
-150	-200	-300	-350	2	170	4.20	93.14	10.42
-150	-200	-350	-400	3	170	1.75	97.02	14.76
-150	-200	-400	-450	4	170	1.08	119.75	18.18
-150	-200	-450	-500	5	170	0.62	120.30	20.07
-200	-250	-300	-350	1	160	8.61	50.72	5.80
-200	-250	-350	-400	2	160	2.79	65.74	10.00
-200	-250	-400	-450	3	160	1.49	87.77	11.56
-200	-250	-450	-500	4	160	0.78	91.89	14.96
-200	-250	-500	-550	5	160	0.51	105.15	12.66
-250	-300	-350	-400	1	450	23.70	49.64	6.58
-250	-300	-400	-450	2	450	9.55	80.01	8.84
-250	-300	-450	-500	3	450	4.55	95.29	13.85
-250	-300	-500	-550	4	450	2.57	107.65	13.30
-250	-300	-550	-600	5	450	2.53	185.46	10.74
-300	-350	-400	-450	1	2000	131.77	62.10	5.91
-300	-350	-450	-500	2	2000	46.57	87.78	11.27
-300	-350	-500	-550	3	2000	22.11	104.19	12.58
-300	-350	-550	-600	4	2000	19.57	184.44	10.34
-300	-350	-600	-650	5	2000	14.76	243.44	10.81
-350	-400	-450	-500	1	2700	167.94	58.62	7.85
-350	-400	-500	-550	2	2700	53.91	75.27	11.92
-350	-400	-550	-600	3	2700	41.61	145.25	10.77
-350	-400	-600	-650	4	2700	28.97	202.25	11.55
-350	-400	-650	-700	5	2700	14.59	178.25	14.34
-400	-450	-500	-550	1	2000	125.38	59.08	7.70
-400	-450	-550	-600	2	2000	65.77	123.97	8.51
-400	-450	-600	-650	3	2000	40.17	189.30	9.59
-400	-450	-650	-700	4	2000	17.78	167.57	13.32
-400	-450	-700	-750	5	2000	13.44	221.67	13.67
-450	-500	-550	-600	1	1300	117.19	84.96	4.03
-450	-500	-600	-650	2	1300	53.84	156.13	6.67
-450	-500	-650	-700	3	1300	19.37	140.43	12.21
-450	-500	-700	-750	4	1300	13.25	192.12	13.80
-450	-500	-750	-800	5	1300	7.91	200.71	16.57
-500	-550	-600	-650	1	1200	108.94	85.56	2.37
-500	-550	-650	-700	2	1200	29.76	93.49	9.00
-500	-550	-700	-750	3	1200	18.01	141.45	10.99
-500	-550	-750	-800	4	1200	10.00	157.08	14.08
-500	-550	-800	-850	5	1200	8.57	235.58	16.81
-550	-600	-650	-700	1	730	60.68	78.34	8.28
-550	-600	-700	-750	2	730	28.95	149.51	12.33
-550	-600	-750	-800	3	730	14.52	187.46	15.75
-550	-600	-800	-850	4	730	11.56	298.49	19.48
-550	-600	-850	-900	5	730	9.39	424.31	21.89
-600	-650	-700	-750	1	250	26.35	99.34	6.00
-600	-650	-750	-800	2	250	10.63	160.30	10.49
-600	-650	-800	-850	3	250	7.46	281.24	15.91
-600	-650	-850	-900	4	250	5.43	409.41	18.98
-600	-650	-900	-950	5	250	3.13	412.99	21.67

Kekoro Line-N500

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-650	-700	-750	-800	1	200	22.81	107.49	1.57
-650	-700	-800	-850	2	200	13.12	247.31	7.20
-650	-700	-850	-900	3	200	8.10	381.70	12.77
-650	-700	-900	-950	4	200	4.20	395.84	17.32
-650	-700	-950	-1000	5	200	2.06	339.76	21.26
-700	-750	-800	-850	1	400	61.81	145.64	4.50
-700	-750	-850	-900	2	400	29.79	280.76	11.22
-700	-750	-900	-950	3	400	13.76	324.21	16.51
-700	-750	-950	-1000	4	400	6.28	295.94	21.15
-700	-750	-1000	-1050	5	400	2.56	211.12	23.43
-750	-800	-850	-900	1	1700	289.88	160.71	8.60
-750	-800	-900	-950	2	1700	101.78	225.71	15.23
-750	-800	-950	-1000	3	1700	41.21	228.47	21.28
-750	-800	-1000	-1050	4	1700	14.80	164.10	24.35
-750	-800	-1050	-1100	5	1700	7.92	153.68	25.63
-800	-850	-900	-950	1	1700	279.88	155.17	13.17
-800	-850	-950	-1000	2	1700	91.82	203.62	21.04
-800	-850	-1000	-1050	3	1700	27.47	152.29	26.70
-800	-850	-1050	-1100	4	1700	13.23	146.69	29.53
-800	-850	-1100	-1150	5	1700	5.89	114.29	25.97
-850	-900	-950	-1000	1	1800	300.05	157.11	15.35
-850	-900	-1000	-1050	2	1800	65.83	137.87	24.10
-850	-900	-1050	-1100	3	1800	27.01	141.42	29.61
-850	-900	-1100	-1150	4	1800	10.75	112.57	26.59
-850	-900	-1150	-1200	5	1800	7.09	129.93	24.16
-900	-950	-1000	-1050	1	2600	218.65	79.26	16.71
-900	-950	-1050	-1100	2	2600	65.25	94.61	26.11
-900	-950	-1100	-1150	3	2600	21.20	76.85	26.01
-900	-950	-1150	-1200	4	2600	12.80	92.80	24.14
-900	-950	-1200	-1250	5	2600	8.11	102.89	22.69
-950	-1000	-1050	-1100	1	2000	229.46	108.13	14.62
-950	-1000	-1100	-1150	2	2000	51.34	96.77	21.50
-950	-1000	-1150	-1200	3	2000	25.78	121.49	21.72
-950	-1000	-1200	-1250	4	2000	13.84	130.44	22.30
-950	-1000	-1250	-1300	5	2000	8.08	133.27	24.09
-1000	-1050	-1100	-1150	1	2300	189.15	77.51	11.91
-1000	-1050	-1150	-1200	2	2300	77.28	126.67	14.49
-1000	-1050	-1200	-1250	3	2300	35.29	144.61	16.85
-1000	-1050	-1250	-1300	4	2300	18.59	152.35	19.58
-1000	-1050	-1300	-1350	5	2300	10.61	152.17	20.51
-1050	-1100	-1150	-1200	1	1700	219.05	121.44	3.07
-1050	-1100	-1200	-1250	2	1700	77.96	172.88	7.61
-1050	-1100	-1250	-1300	3	1700	35.55	197.09	12.01
-1050	-1100	-1300	-1350	4	1700	18.73	207.68	13.70
-1050	-1100	-1350	-1400	5	1700	10.61	205.88	14.67
-1100	-1150	-1200	-1250	1	1700	77.62	43.03	4.43
-1100	-1150	-1250	-1300	2	1700	29.35	65.09	9.40
-1100	-1150	-1300	-1350	3	1700	14.21	78.78	11.14
-1100	-1150	-1350	-1400	4	1700	7.79	86.38	11.76
-1150	-1200	-1250	-1300	1	1100	78.95	67.64	6.84
-1150	-1200	-1300	-1350	2	1100	29.55	101.27	9.42
-1150	-1200	-1350	-1400	3	1100	14.75	126.38	9.97
-1200	-1250	-1300	-1350	1	2400	175.02	68.73	6.24
-1200	-1250	-1350	-1400	2	2400	66.96	105.18	7.30
-1250	-1300	-1350	-1400	1	1500	104.13	65.43	2.40

Kekoro Line-N250

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
1000	950	900	850	1	290	43.71	142.05	2.66
1000	950	850	800	2	290	25.45	330.84	4.40
1000	950	800	750	3	290	15.76	512.19	6.19
1000	950	750	700	4	290	10.35	672.73	9.72
1000	950	700	650	5	290	6.85	779.17	11.67
950	900	850	800	1	300	39.35	123.62	2.70
950	900	800	750	2	300	19.83	249.19	4.16
950	900	750	700	3	300	11.44	359.40	8.75
950	900	700	650	4	300	7.29	458.04	10.50
950	900	650	600	5	300	3.07	337.56	9.65
900	850	800	750	1	360	50.97	133.44	5.55
900	850	750	700	2	360	21.65	226.72	9.27
900	850	700	650	3	360	12.64	330.91	11.37
900	850	650	600	4	360	5.06	264.94	9.09
900	850	600	550	5	360	3.60	329.87	5.38
850	800	750	700	1	330	49.86	142.40	12.71
850	800	700	650	2	330	19.56	223.45	13.22
850	800	650	600	3	330	6.57	187.64	9.84
850	800	600	550	4	330	4.30	245.62	5.69
850	800	550	500	5	330	2.82	281.89	5.25
800	750	700	650	1	520	91.69	166.18	16.95
800	750	650	600	2	520	19.65	142.46	12.69
800	750	600	550	3	520	10.04	181.97	7.62
800	750	550	500	4	520	5.78	209.52	6.35
800	750	500	450	5	520	3.56	225.83	7.19
750	700	650	600	1	500	63.64	119.96	13.11
750	700	600	550	2	500	20.25	152.68	8.60
750	700	550	500	3	500	9.40	177.19	7.19
750	700	500	450	4	500	5.24	197.54	6.62
750	700	450	400	5	500	3.60	237.50	7.78
700	650	600	550	1	450	66.79	139.88	5.53
700	650	550	500	2	450	20.99	175.85	4.56
700	650	500	450	3	450	9.52	199.39	4.01
700	650	450	400	4	450	6.21	260.12	5.35
700	650	400	350	5	450	3.42	250.70	8.88
650	600	550	500	1	1600	106.84	62.93	1.41
650	600	500	450	2	1600	35.41	83.43	1.83
650	600	450	400	3	1600	20.87	122.93	2.65
650	600	400	350	4	1600	10.60	124.88	5.23
650	600	350	300	5	1600	5.54	114.22	11.01
600	550	500	450	1	2300	154.42	63.28	2.19
600	550	450	400	2	2300	73.22	120.01	3.05
600	550	400	350	3	2300	31.93	130.84	5.08
600	550	350	300	4	2300	14.16	116.05	10.62
600	550	300	250	5	2300	6.64	95.23	13.13
550	500	450	400	1	1200	111.67	87.71	2.44
550	500	400	350	2	1200	34.44	108.20	3.97
550	500	350	300	3	1200	12.07	94.80	9.95
550	500	300	250	4	1200	4.73	74.30	13.59
550	500	250	200	5	1200	3.84	105.56	16.13
500	450	400	350	1	1100	71.06	60.88	3.44
500	450	350	300	2	1100	19.34	66.28	9.77
500	450	300	250	3	1100	7.52	64.43	13.28
500	450	250	200	4	1100	6.00	102.82	15.03
500	450	200	150	5	1100	5.30	158.94	11.93

Kekoro Line-N250

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
450	400	350	300	1	1200	41.61	32.68	7.64
450	400	300	250	2	1200	12.84	40.34	12.04
450	400	250	200	3	1200	9.10	71.47	14.48
450	400	200	150	4	1200	7.68	120.64	12.38
450	400	150	100	5	1200	4.08	112.15	12.09
400	350	300	250	1	600	32.01	50.28	5.07
400	350	250	200	2	600	13.92	87.46	9.24
400	350	200	150	3	600	6.26	98.33	11.65
400	350	150	100	4	600	2.56	80.42	13.85
400	350	100	50	5	600	3.23	177.58	10.40
350	300	250	200	1	560	30.80	51.84	7.57
350	300	200	150	2	560	9.39	63.21	13.32
350	300	150	100	3	560	3.29	55.37	15.48
350	300	100	50	4	560	3.61	121.51	12.27
350	300	50	0	5	560	2.55	150.21	14.09
300	250	200	150	1	900	36.66	38.39	8.62
300	250	150	100	2	900	9.69	40.59	11.55
300	250	100	50	3	900	7.67	80.32	9.82
300	250	50	0	4	900	4.50	94.25	11.16
300	250	0	-50	5	900	2.71	99.33	13.35
250	200	150	100	1	2000	77.15	36.36	8.99
250	200	100	50	2	2000	40.20	75.78	10.61
250	200	50	0	3	2000	19.83	93.45	13.21
250	200	0	-50	4	2000	11.25	106.03	14.13
250	200	-50	-100	5	2000	5.62	92.69	14.78
200	150	100	50	1	2100	105.67	47.42	7.70
200	150	50	0	2	2100	36.36	65.27	11.77
200	150	0	-50	3	2100	18.80	84.37	12.48
200	150	-50	-100	4	2100	9.25	83.03	13.16
200	150	-100	-150	5	2100	5.48	86.08	14.67
150	100	50	0	1	1900	72.61	36.02	5.44
150	100	0	-50	2	1900	27.96	55.48	7.81
150	100	-50	-100	3	1900	11.54	57.24	9.46
150	100	-100	-150	4	1900	7.04	69.84	9.76
150	100	-150	-200	5	1900	5.15	89.41	10.26
100	50	0	-50	1	2400	132.77	52.14	5.95
100	50	-50	-100	2	2400	40.95	64.32	7.56
100	50	-100	-150	3	2400	21.45	84.23	7.90
100	50	-150	-200	4	2400	14.72	115.61	7.75
100	50	-200	-250	5	2400	8.47	116.42	7.13
50	0	-50	-100	1	2600	121.19	43.93	7.01
50	0	-100	-150	2	2600	43.44	62.99	9.06
50	0	-150	-200	3	2600	25.35	91.89	9.10
50	0	-200	-250	4	2600	13.52	98.02	7.79
50	0	-250	-300	5	2600	10.32	130.93	9.29
0	-50	-100	-150	1	2200	100.50	43.05	6.78
0	-50	-150	-200	2	2200	40.23	68.94	8.55
0	-50	-200	-250	3	2200	17.87	76.55	7.76
0	-50	-250	-300	4	2200	12.49	107.01	9.14
0	-50	-300	-350	5	2200	13.44	201.52	10.84
-50	-100	-150	-200	1	2000	93.65	44.13	4.93
-50	-100	-200	-250	2	2000	28.04	52.85	6.31
-50	-100	-250	-300	3	2000	16.47	77.61	8.45
-50	-100	-300	-350	4	2000	15.78	148.72	11.20
-50	-100	-350	-400	5	2000	9.57	157.84	13.37

Kekoro Line-N250

Curr. Elect		Pot. Elect		n	Current (mA)	Potential (mV)	App. Resistivity ($\Omega \cdot m$)	Chargeability (mV/V)
C1	C2	P1	P2					
-100	-150	-200	-250	1	600	18.45	28.98	3.15
-100	-150	-250	-300	2	600	7.89	49.57	6.44
-100	-150	-300	-350	3	600	6.57	103.20	10.89
-100	-150	-350	-400	4	600	3.67	115.30	13.39
-100	-150	-400	-450	5	600	2.67	146.79	14.13
-150	-200	-250	-300	1	400	12.33	29.05	3.93
-150	-200	-300	-350	2	400	7.08	66.73	8.99
-150	-200	-350	-400	3	400	3.82	90.01	12.56
-150	-200	-400	-450	4	400	2.39	112.63	14.53
-150	-200	-450	-500	5	400	1.26	103.91	15.25
-200	-250	-300	-350	1	350	17.08	45.99	5.00
-200	-250	-350	-400	2	350	6.23	67.10	10.37
-200	-250	-400	-450	3	350	3.20	86.17	12.54
-200	-250	-450	-500	4	350	1.53	82.40	15.04
-200	-250	-500	-550	5	350	1.19	112.15	13.94
-250	-300	-350	-400	1	340	21.05	58.35	8.03
-250	-300	-400	-450	2	340	7.65	84.82	13.03
-250	-300	-450	-500	3	340	3.22	89.26	15.65
-250	-300	-500	-550	4	340	2.10	116.42	17.29
-250	-300	-550	-600	5	340	1.48	143.59	19.38
-300	-350	-400	-450	1	420	31.63	70.98	9.02
-300	-350	-450	-500	2	420	9.88	88.68	14.80
-300	-350	-500	-550	3	420	5.47	122.75	17.68
-300	-350	-550	-600	4	420	3.35	150.35	20.48
-300	-350	-600	-650	5	420	2.67	209.70	19.44
-350	-400	-450	-500	1	700	43.16	58.11	7.53
-350	-400	-500	-550	2	700	18.24	98.23	13.43
-350	-400	-550	-600	3	700	8.72	117.41	18.53
-350	-400	-600	-650	4	700	5.87	158.07	18.71
-350	-400	-650	-700	5	700	3.54	166.82	15.81
-400	-450	-500	-550	1	900	74.90	78.44	8.90
-400	-450	-550	-600	2	900	27.48	115.11	15.39
-400	-450	-600	-650	3	900	16.14	169.02	15.58
-400	-450	-650	-700	4	900	8.12	170.06	13.43
-400	-450	-700	-750	5	900	6.40	234.57	15.01
-450	-500	-550	-600	1	1300	101.75	73.77	9.45
-450	-500	-600	-650	2	1300	40.58	117.68	11.20
-450	-500	-650	-700	3	1300	17.06	123.68	10.27
-450	-500	-700	-750	4	1300	11.94	173.13	12.46
-450	-500	-750	-800	5	1300	9.27	235.22	13.78
-500	-550	-600	-650	1	900	108.25	113.36	8.73
-500	-550	-650	-700	2	900	29.44	123.32	8.19
-500	-550	-700	-750	3	900	17.72	185.56	10.48
-500	-550	-750	-800	4	900	11.88	248.81	12.93
-550	-600	-650	-700	1	400	35.51	83.67	9.36
-550	-600	-700	-750	2	400	15.53	146.37	12.95
-550	-600	-750	-800	3	400	9.08	213.94	16.41
-600	-650	-700	-750	1	330	42.37	121.01	7.58
-600	-650	-750	-800	2	330	17.84	203.80	11.30
-650	-700	-750	-800	1	350	44.68	120.31	7.71