No. 61

JAPAN INTERNATIONAL COOPERATION AGENCY (JICA)

MINISTRY OF SETTLEMENT AND REGIONAL DEVELOPMENT
THE REPUBLIC OF INDONESIA

THE DETAILED DESIGN OF FLOOD CONTROL, URBAN DRAINAGE AND WATER RESOURCES DEVELOPMENT IN SEMARANG IN THE REPUBLIC OF INDONESIA

FINAL REPORT

We sharply the sound of the sou




AUGUST 2000

CTI ENGINEERING INTERNATIONAL CO., LTD.
IN ASSOCIATION WITH
PACIFIC CONSULTANTS INTERNATIONAL
AND
PASCO INTERNATIONAL INC.

SSS

CR (5)

00-132



JAPAN INTERNATIONAL COOPERATION AGENCY (JICA)

MINISTRY OF SETTLEMENT AND REGIONAL DEVELOPMENT THE REPUBLIC OF INDONESIA

THE DETAILED DESIGN OF FLOOD CONTROL, URBAN DRAINAGE AND WATER RESOURCES DEVELOPMENT IN SEMARANG IN THE REPUBLIC OF INDONESIA

FINAL REPORT

COMPONENT A: WEST FLOODWAY / GARANG RIVER IMPROVEMENT

VOLUME I MAIN REPORT

AUGUST 2000

CTI ENGINEERING INTERNATIONAL CO., LTD.
IN ASSOCIATION WITH
PACIFIC CONSULTANTS INTERNATIONAL
AND
PASCO INTERNATIONAL INC.



ESTIMATE OF PROJECT COST

Price Level Currency Conversion Rate As of July 1999 US\$1.00 = 1 Yen = Rp. 6,885 Rp. 60.39

CONSTITUTION OF THE REPORT

1. SUMMARY

2. COMPONENT A: WEST FLOODWAY/GARANG RIVER IMPROVEMENT

VOLUME I MAIN REPORT

VOLUME II DESIGN CRITERIA

VOLUME III DESIGN NOTES

VOLUME IV WORK QUANTITY CALCULATION

VOLUME V CONSTRUCTION PLANNING

VOLUME VI COST ESTIMATE

VOLUME VII DATA BOOK

3. COMPONENT B: JATIBARANG MULTIPURPOSE DAM CONSTRUCTION

VOLUME I MAIN REPORT

VOLUME II DESIGN CRITERIA

VOLUME III DESIGN NOTES

VOLUME IV WORK QUANTITY CALCULATION

VOLUME V CONSTRUCTION PLANNING

VOLUME VI COST ESTIMATE

VOLUME VII DATA BOOK

VOLUME VIII ANNEX

4. COMPONENT C: URBAN DRAINAGE SYSTEM IMPROVEMENT

VOLUME I MAIN REPORT

VOLUME II DESIGN NOTES

VOLUME III WORK QUANTITY CALCULATION

VOLUME IV CONSTRUCTION PLANNING

VOLUME V COST ESTIMATE

VOLUME VI DATA BOOK

PREFACE

In response to a request from the Government of the Republic of Indonesia, the Government of Japan decided to conduct the Detailed Design of Flood Control, Urban Drainage and Water Resources Development in Semarang and entrusted the study to the Japan International Cooperation Agency (JICA).

JICA selected and dispatched a study team headed by Mr. TOMIOKA Yoshiyuki of CTI Engineering International Co., Ltd. and constituted of members of CTI Engineering International Co., Ltd., Pacific Consultants International and Pasco International Inc., six times between August 1997 and June 2000. In addition, JICA set up an advisory committee, which examined the study from specialist and technical points of view.

The team held discussions with the officials concerned of the Government of Indonesia and conducted field surveys at the study area. Upon returning to Japan, the team conducted further studies and prepared this final report.

I hope that this report will contribute to the promotion of this project and to the enhancement of friendly relationship between our two countries.

Finally, I wish to express my sincere appreciation to the officials concerned of the Government of Indonesia for their close cooperation extended to the Team.

August 2000

Kimio Fujita President

Japan International Cooperation Agency

Mr. FUJITA Kimio
President
Japan International Cooperation Agency
Tokyo, Japan

LETTER OF TRANSMITTAL

Sir:

We are pleased to submit herewith the Final Report on the Detailed Design of Flood Control, Urban Drainage and Water Resources Development in Semarang in the Republic of Indonesia.

Under a contract with the Japan International Cooperation Agency, the Study was conducted by CTI Engineering International Co., Ltd., in association with Pacific Consultants International and PASCO International, Inc., during the period from August 1997 to August 2000.

This Final Report presents the results of the detailed design of the following three (3) components, which consist of (1) West Floodway/Garang River Improvement including reconstruction of Simongan Weir, (2) Construction of Jatibarang Multipurpose Dam, and (3) Urban Drainage System Improvement. It also presents the pre-qualification and contract documents, and general and technical specifications necessary for the construction stage. In the course of the Study, much attention was given to the particular issues on the present situation in Semarang, and reflected them in the proposed facilities.

We wish to take this opportunity to express our sincere gratitude to the officials concerned of JICA, the Ministry of Foreign Affairs, and the Ministry of Construction. We would also like to extend our deep appreciation to the officials concerned of the Government of the Republic of Indonesia, Jratunseluna Project Office in Semarang, the JICA Indonesia Office, the Embassy of Japan in Indonesia for their cooperation and assistance throughout our field survey.


Finally, we hope that this Report will contribute to the improvement of the flood control and urban drainage facilities, and water resources development in Semarang.


Very truly yours,


TOMIOKA Yosiyuki


Team Leader


Detailed Design of Flood Control, Urban Drainage and Water Resources Development in Semarang in the Republic of Indonesia











VOLUME I MAIN REPORT

TABLE OF CONTENTS

PREFACE
LETTER OF TRANSMITTAL
GENERAL MAP
LOCATION OF PROJECT SITE
SCENIC SKETCH

		Page
CHAPTER	1 IN	TRODUCTION
1.1	Backgr	ound1 - 1
1.2	Objecti	ves of the Study
1.3	Study A	Area
1.4	_	otion of Project Component : West Floodway/Garang
1.5	Scope	of the D/D Study
CHAPTER	2 PR	ESENT CONDITION OF THE STUDY AREA
2.1	Natura	and Other Conditions
	2.1.1	General
	2.1.2	Climatic Characteristics
	2.1.3	Geomorphology and Geology 2 - 2
	2.1.4	River Features and Characteristics
	2.1.5	River Structures
	2.1.6	Environmental Condition
	2.1.7	Land Use Pattern 2 - 19
2.2	Socio-	Economic Condition
	2.2.1	Population and Labor Force
	2.2.2	General Economic Features
	2.2.3	Industrial Perspective
	2.2.4	Family Economy
	2.2.5	Price Fluctuation
	2.2.6	Relationships with Other Related Projects 2 - 41

2.3	Floods and Flood Control Works	2 - 42
	2.3.1 Major Floods and Flood Damages	
	2.3.2 River Flow Capacity	
	2.3.3 Previous and Ongoing Flood Control Works	•
•		
CHAPTER	3 INVESTIGATION AND ANALYSIS	
3.1	Photogrammetric Mapping, Topographic and River Survey	3 - 1
	3.1.1 Aerial Photography and Mapping	3 - 1
	3.1.2 Ground Survey	. 3 - 11
	3.1.3 Topographic Survey	. 3 - 13
	3.1.4 Sounding Survey	. 3 - 14
	3.1.5 Land Subsidence	
3.2	Geological and Soil Mechanical Investigation	. 3 - 15
	3.2.1 Boring and Tests	. 3 - 15
	3.2.2 Geological Condition and Soil Properties	. 3 - 17
3.3	Hydrological Analysis	. 3 - 19
	3.3.1 Data Collection and Compilation	
	3.3.2 Probable Rainfall	
	3.3.3 Probable Peak Discharge	
	3.3.4 Flood Run-off Model	. 3 - 22
	3.3.5 Flood Control Plan	
	3.3.6 Low Flow Analysis	. 3 - 27
	3.3.7 Design Tidal Level at River Mouth	
CHAPTER	4 FORMULATION OF DEFINITIVE PLAN	
4.1	River Improvement Plan	
	4.1.1 Planning Criteria	The second secon
	4.1.2 Project Works	
	4.1.3 Basic Matters to be Considered	
•	4.1.4 Measures of River Improvement	and the second of the second o
4.2	Basic Design	
	4.2.1 Planning/Design Criteria	
	4.2.2 West Floodway Channel	
	4.2.3 Garang River Channel	4 - 21
	4.2.4 Dike Embankment and Raising of Existing Floodwall	
	4.2.5 Reconstruction of Simongan Weir	4 - 27
	요. 이번 사는 사고 있다. 얼마 요. 그런 그는 사람은	

	4.2.6 River Structures	4 - 37
	4.2.7 Raising of the Existing Railway Bridge	4 - 44
4.3	Project Evaluation	4 - 47
CHAPTER	5 ENVIRONMENTAL AND SOCIAL IMPACTS	
5.1	Environmental and Social Impact Analysis	5 - 1
	5.1.1 Natural Environment	5 - 1
	5.1.2 Social Environment	5 - 8
5.2	Environmental and Social Impact Assessment	5 - 13
	5.2.1 Present Environmental Condition	5 - 13
	5.2.2 Predicted Impacts and Impact Sources	5 - 17
	5.2.3 Environmental Management Plan	
	5.2.4 Environmental Monitoring Plan	5 - 23
5.3	River Basin Management Plan	5 - 26
	5.3.1 Basic Issues and Problems	5 - 26
	5.3.2 Key Idea and Countermeasures	5 - 28
	5.3.3 On-going Countermeasures and Practice	5 - 31
CHAPTER	6 DETAILED DESIGN	
6.1	Structures and Design Criteria	6-1
6.2	River Channel	
	6.2.1 West Floodway Channel	6-3
	6.2.2 Garang River Channel	
6.3	River Dike and Floodwall	
	6.3.1 Earth Dike/Embankment	
	6.3.2 Floodwall	
6.4	Simongan Weir	
	6.4.1 Principal Features of Weir and Layout Plan	
	6.4.2 Major Dimensions of Weir	
	6.4.3 Design Conditions	
	6.4.4 Stability Analysis of Weir	
	6.4.5 Design of Gate	6 - 37
	0.4.0 Intake Structures	. 13
	6.4.7 Protection Works for Riverbed and River Bank	6 - 49
	6.4.8 Maintenance Bridge and Approach Bridges	
	6.4.9 Weir Management Complex and Gate Control House	6 - 55
	iii iii iii iii iii iii iii iii iii ii	

		6.4.10 Preservation of Part of Existing Simongan Weir	6 - 58
	6.5	Protection Works for Riverbank and Bridge Pier	6 - 58
	-	6.5.1 Revetment	6 - 59
		6.5.2 Groin	6 - 63
-		6.5.3 Riverbed Protection	6 - 64
	6.6	Ground Sill	6 - 65
;	6.7	Drainage Facilities	6 - 68
		6.7.1 Drainage Sluiceway	6 - 68
		6.7.2 Drainage Outlets	6 - 70
	6.8	Maintenance and Amenity Facilities	
	6.9	Raising of Railway Bridge and Approach Tracks	6 - 73
CHAI	PTER	7 CONSTRUCTION PLANNING	
	7.1	Outline of Construction Works	7 - 1
	· .	7.1.1 Summary of Construction Works	7 - 1
		7.1.2 Possible Spoil Bank Areas	
:. :	7.2	Construction Method of West Floodway/Garang River	
		Improvement	7 2
		7.2.2 Channel Excavation and Dike Embankment Works	
		7.2.3 Earth Dike Embankment	
2 7 7		7.2.4 Raising of Existing Floodwall	
		7.2.5 Protection Works for Riverbank and Riverbed	
		7.2.6 Ground Sill	7 4
		7.2.7 Raising of the Existing Railway Bridge	7 - 4
	7.3	Construction Method of Reconstruction of Simongan Weir	
	7.5	7.3.1 Staged Construction	
		7.3.2 Temporary Cofferdam	7-0
		7.3.3 Channel Diversion and Water Supply	
		7.3.4 Demolition and Removal of Existing Weir and Intake Structures	
		7.3.5 Earth Work	7 - 8
		7.3.6 Foundation Piles and Seepage Blocking Sheet Piles	4
		7.3.7 Concrete Work	
* * * *		7.3.8 Gate Installation Work	
		1997年 - 1997年 - 1998年 -	7 - 10
	7.4	Construction Time Schedule	7 - 10

	7.4.1 Planning Condition
	7.4.2 Construction Time Schedule
CHAPTER	8 COST ESTIMATE
8.1	Introduction 8 - 1
8.2	Constitution of Project Cost and Conditions of Cost Estimate 8 - 1
	8.2.1 Constitution of Project Cost
	8.2.2 Composition of Construction Base Cost 8 - 2
	8.2.3 Conditions of Project Cost Estimate
8.3	Basic Cost
	8.3.1 Condition of Currency Component
	8.3.2 Basic Cost of Laborer
	8.3.3 Basic Cost of Material 8 - 6
	8.3.4 Basic Cost of Equipment 8 - 6
	8.3.5 Reference Book 8 - 6
8.4	Unit Rates for Work Items and Unit Cost for Payment Items 8 - 7
	8.4.1 Unit Rate 8 - 7
	8.4.2 Unit Cost for Payment Items
	8.4.3 Reference Book
8.5	Project Cost 8 - 9
	8.5.1 Construction Schedule
	8.5.2 Project Cost
	8.5.3 Total Project Cost
	8.5.4 Disbursement Schedule
CHAPTER	9 OPERATION AND MAINTENANCE
9.1	General
9.2	Operation Plan
	9.2.1 Simongan Gated Weir and Intake Gate
	9.2.2 Drainage Facilities
9.3	Maintenance Plan
9.3	
	9.3.2 River Structures 9 - 17 9.3.3 Simongan Weir 9 - 19
	9.3.4 River Amenity Facilities
	9.3.5 Bridges 9 - 23

		9.3.6	Water Level Gauging Station
		9.3.7	Use of O&M Equipment
	9.4	Manage	ement of River Flow and Sand Mining
		9.4.1	Flood Observation and Data Transmission System 9 - 25
		9.4.2	Low Flow Management
		9.4.3	Sand Mining
	9.5	River P	atrolling
		9.5.1	General
		9.5.2	Implementation
		9.5.3	Emergency Patrolling
СНАР	TER	10 OF	GANIZATION AND INSTITUTION
	10.1	Region	al Government System in Indonesia
	10.1	_	Structure and Powers of Regional Governments
			Finance of Regional Governments
	10.2		Situations of Organization and Institution for Operation
7			intenance
		10.2.1	Related Laws and Regulations
		10.2.2	Related Authorities
	10.3	Propos	ed Organizations and Cost for Operation and Maintenance . 10 - 14
		10.3.1	Proposed Organizations
		10.3.2	Budgetary Arrangement
		10.3.3	Preparation of Schedule and Budget 10 - 17
CHAD	TED	11 ND	O IECT IMPLEMENTATION
СНАР	IEK	11 PK	OJECT IMPLEMENTATION
	11.1	Implen	nentation Method and Time Schedule 11 - 1
			Executing System
		11.1.2	Project Packaging and Construction Schedule
	:	11.1.3	Implementation Schedule
-	11.2	Fund R	lequirement
	. :	11.2.1	Project Cost and Loan Amount
* .		11.2.2	Disbursement Schedule
	11.3	Works	Required for Project Implementation
•		11.3.1	Clearance of Environmental Issue
	1	11.3.2	Compensation Works 11 - 5

TABLES

FIGURES

DRAWINGS

ANNEXES

ANNEX I	Minutes of Meeting on Inception Report, Jakarta
ANNEX 2	Minutes of Meeting on Interim Report (1), Jakarta
ANNEX 3	Minutes of Meeting on Interim Report (1), Semarang
ANNEX 4	Minutes of Meeting on Interim Report (2), Jakarta-1
ANNEX 5	Minutes of Meeting on Interim Report (2), Jakarta-2
ANNEX 6	Minutes of Meeting on Progress Report (1), Semarang
ANNEX 7	Minutes of Meeting on Progress Report (1), Jakarta
ANNEX 8	Minutes of Meeting on Interim Report (3), Jakarta
ANNEX 9	Minutes of Meeting on Interim Report (3), Semarang
ANNEX 10	Minutes of Meeting on Interim Report (4), Jakarta
ANNEX 11	Minutes of Meeting on Interim Report (4), Semarang

LIST OF TABLES

Table 2.1.1	Climatological Date at BMG-Semarang Station	T - 2 - 1
Table 2.1.2	Geological Strata of Study Area	T - 2 - 2
Table 2.1.3	Water Level Discharge Relation at Simongan Weir	T - 2 - 3
Table 2.1.4	Existing Drainage Outlet	T - 2 - 4
Table 2.2.1	Area and Population in Indonesia	T - 2 - 5
Table 2.2.2	Area and Population in Central Java	T - 2 - 6
Table 2.2.3	Area and Population in Semarang City	T - 2 - 7
Table 2.2.4	Labour Force in Indonesia	T - 2 - 8
Table 2.2.5	Labour Force in Central Java	
Table 2.2.6	Labour Force in Semarang City	T - 2 - 10
Table 2.2.7	Economic Active Population by Districts and Working Group in Semarang City	T - 2 - 11
Table 2.2.8	Gross Domestic Product in Indonesia	T - 2 - 12
Table 2.2.9	Gross Regional Domestic Product in Central Java Province.	T - 2 - 13
Table 2.2.10	Gross Regional Domestic Product in Semarang City	T - 2 - 14
Table 2.2.11	Government Finance of Indonesia in Budget	T - 2 - 15
Table 2.2.12	Government Finance of Indonesia in Realization	T - 2 - 16
Table 2.2.13	Realized Local Government Finance in Central Java Province	e T - 2 - 17
Table 2.2.14	Realized Local Government Finance in Semarang City	T - 2 - 18
Table 2.2.15	Industrial Situation in Indonesia	T - 2 - 19
Table 2.2.16	Industrial Situation for Large and Medium Scale Manufacturing in Central Java Province	T - 2 - 20
Table 2.2.17	Industrial Situation for Large and Medium Scale Manufacturing in Semarang City	T - 2 - 21
Table 2.2.18	Actual Working Population by Districts and Working Group in Semarang City	T - 2 - 22
Table 2.2.19	Infrastructure in Indonesia	T - 2 - 23
Table 2.2.20	Infrastructure in Central Java Province	T - 2 - 24
Table 2.2.21	Infrastructure in Semarang City	T - 2 - 25
Table 2.2.22	Family Economy in Semarang City	T - 2 - 26
Table 2.2.23	Consumer's Price Index in Indonesia and Semarang City	
Table 2.2.24	Exchange Rate	T - 2 - 28
Table 2.3.1	Record of Improvement Works for Garang River / West Floodway	T - 2 - 29

	Table 3.1.1	Final Result of Control Points	T - 3 - 1
	Table 3.1.2	Map Symbols	
÷	Table 3.1.3	Coordinates of Cross Section Point	T - 3 - 5
	Table 3.1.4	Longitudinal Profile	
	Table 3.2.1	The Specification of Core Drilling	T - 3 - 16
	Table 3.2.2	Summary of Laboratory Test	T - 3 - 17
	Table 3.3.1	Hydrological Stations and Data Collection	T - 3 - 22
	Table 3.3.2	Annual Maximum Rainfall for Each Duration at BMG-Semarang Station	T - 3 - 23
	Table 3.3.3	Probable Rainfall for Each Duration at BMG-Semarang Station	T - 3 - 24
	Table 3.3.4	Rainfall Intensity Formula for Short Duration	
•	Table 3.3.5	Rainfall Intensity Formula for Long Duration	T - 3 - 26
	Table 3.3.6	Hourly Rainfall Data in Annual Maximum Daily Rainfall at BMG-Semarang Station	Т - 3 - 27
	Table 3.3.7	Hourly Rainfall Ratio in Annual Maximum Daily Rainfall and Design Storm	T - 3 - 27
	Table 3.3.8	Annual Maximum Discharge at Simongan Weir	T - 3 - 28
	Table 3.3.9	Probable Peak Discharge at Simongan	T - 3 - 29
	Table 3.3.10	Daily Rainfall at Flood Time	T - 3 - 30
	Table 3.3.11	Hourly Data Observed at Flood Time	T - 3 - 30
	Table 3.3.12	Parameters Estimated by Flood Analysis	T - 3 - 32
	Table 3.3.13	Parameters in Storage Function Method	T - 3 - 32
	Table 3.3.14	100- Year Probable Flood Control by Jatibarang Dam	the growth of the control of the con
	Table 3.3.15	Outlet Condition of Dam for Flood Control	T - 3 - 33
	Table 3.3.16	Probable Peak Discharge and Design Discharge	T - 3 - 34
•	Table 3.3.17	Monthly Rainfall for 30 Years at Sumurjurang Station	
	Table 3.3.18	Monthly Discharge Observed in Garang River System	T - 3 - 36
	Table 3.3.19	Flow Regime and Balance in Observed Daily Discharge Records	
	Table 3.3.20	Thiessen Coefficient and Basin Rainfall	
	Table 3.3.21	Monthly Evaporation in Tank Model	T - 3 - 38
	Table 3.3.22	Comparison of Flow Regime Between Tank-Model and Observation	
	Table 3.3.23	Flow Regime for 30 Years at Simongan Weir	
	Table 3.3.24	5-Days Discharge at Panjangan in Garang River	T - 3 - 41
	Table 3.3.25	Maximum and Minimum Value of Tidal Level in the Period form April to August 1997	Т - 3 - 44
			e de la companya de l

Table 4.2	.1 Comparison on Weir Location	m a s
	·	
Table 4.2		the state of the s
Table 4.2	1	
Table 4.2		
Table 4.2		
Table 4.2	.6 Comparison of Construction Method in Railroad Bridge	T - 4 - 6
Table 5.1	.1 Result of Water Quality Test (Dry Season) (West Floodway / Garang River)	T - 5 - 1
Table 5.1	.2 Abundance and Diversity of Plankton (Dry Season) (West Floodway / Garang River)	T - 5 - 3
Table 5.1	.3 Abundance and Diversity of Benthos (Dry Season) (West Floodway / Garang River)	T - 5 - 5
Table 5.1		**
Table 5.2	and the contract of the contra	
Table 5.2		
Table 6.4	.1 Design Procedure for Dimensions of Stilling Basin	
14010 0.	and Buffle Pier	T - 6 - 1
Table 6.4	Design Loads on Center Pier	T - 6 - 2
Table 6.4	Design Loads on End Pier	T - 6 - 6
Table 6.4	.4 Comparative Study on Pile Foundation for End Pier	T - 6 - 10
Table 7.	2.1 Work Volume of Channel Excavation and Dike Embankm	ent T - 7 - 1
Table 7.	2.2 Construction Time Schedule of the Raising Railway Bridg	ge T - 7 - 2
Table 7.	Construction Time Schedule of West Floodway / Garang I	
Table 7.		
ing section of the se		
Table 8.	2.1 The Ratio of Each Cost Item	T_8_1
Table 8.		
Table 8.		1 - 0 - 2
i aule 8.	and North American Countries	T - 8 - 3
Table 8.	Ratio of Currency Portion for Main Material Groups	T-8-4
Table 8.	3.2 Basic Costs and Computation of Laborer Cost	T-8-5
Table 8.	化氯化甲基二甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基	
Table 8.		
Table 8.		

	•	
	Table 8.4.2	Number of Track in General Transportation for Mobilization and Demobilization
	Table 8.4.3	Number of Trailer Transportation for Mobilization and Demobilization
	Table 8.5.1	Payment Item and the Cost for Package-1 T - 8 - 27
2	Table 8.5.2	Payment Item and the Cost for Package-2 T - 8 - 36
	Table 8.5.3	Payment Item and the Cost for Package-3 T - 8 - 43
	Table 8.5.4	Engineering Service Cost
	Table 8.5.5	Calculation Sheet for Compensation Cost
	Table 8.5.6	Price Contingency T - 8 - 50
	Table 8.5.7	Disbursement Schedule T - 8 - 51
	Table 9.5.1	Items for Inspection Works T - 9 - 1
	Table 10.3.1	Annual Schedule for Maintenance T - 10 - 1
	Table 10.3.2	Staff of the O&M Office for West Floodway / Garang River T - 10 - 1
	Table 10.3.3	Task and Responsibilities of the Staff of Simongan Weir Operation / Management Office
	Table 10.3.4	Annual Budget Required for West Floodway / Garang River Operation and Maintenance
	Table 10.3.5	Annual Budget Required for Simongan Weir Operation and Maintenance

LIST OF FIGURES

Fig. 1.1.1	Study Area for Master Plan and Feasibility Study on Flood Control and Urban Drainage in Semasrang	F - 1 - 1
Fig. 1.5.1	Flowchart of the Detailed Design Study	
Fig. 2.1.1	Location of Observatories and Isohyetal Line	F - 2 - 1
Fig. 2.1.2	Regional Geological Map around The Study Area	F - 2 - 2
Fig. 2.1.3	Existing Garang River System	F - 2 - 3
Fig. 2.1.4	River Characteristics of Garang	
Fig. 2.1.5	Existing Longitudinal Profile of West Floodway and Garang River Channels	F - 2 - 5
Fig. 2.1.6	Structural Profile of Existing Simongan Weir	F - 2 - 6
Fig. 2.1.7	Riverbed Lowering around Simongan Weir	F - 2 - 7
Fig. 2.1.8	Existing Bridges and River Cross Sections	F - 2 - 8
Fig. 2.1.9	Existing River Structures and Drainage Outlet	F - 2 - 11
Fig. 2.1.10	Outline of PDAM Intake Structure	F - 2 - 13
Fig. 2.1.11	Water Sampling Locations for Prokasih	F - 2 - 14
Fig. 2.1.12	Water Analysis Record by PDAM (1993 - 1997)	F - 2 - 15
Fig. 2.1.13	Land Use Map of Garang River Basin (1992 - 1995)	
Fig. 2.1.14	Land Use Map of Semarang City	
Fig. 2.3.1	Flood Inundation Map	F - 2 - 19
Fig. 2.3.2	Existing River Cross Sections	F - 2 - 21
Fig. 2.3.3	Flow Capacity of Existing West Floodway Channel	F - 2 - 26
Fig. 2.3.4	Flow Capacity of Existing Garang River Channel	F - 2 - 27
Fig. 2.3.5	Flood Water Level Profile of Exisitng West Floodway	F - 2 - 28
Fig. 3.1.1	Flight Index Map	F - 3 - 1
Fig. 3.1.2	Uncontrolled Mosaic Area	F - 3 - 2
Fig. 3.1.3	GPS Quality Control (Semarang Area)	
Fig. 3.1.4	GPS Quality Control (Ungaran Area)	F - 3 - 4
Fig. 3.1.5	Leveling Quality Control (Semarang Area)	
Fig. 3.1.6	Leveling Quality Control (Ungaran Area)	F - 3 - 6
Fig. 3.1.7	Field Verification	
Fig. 3.1.8	Aerial Triangulation (Semarang Area)	F - 3 - 8
Fig. 3.1.9	Aerial Triangulation (Ungaran Area)	F - 3 - 9
Fig. 3.1.10	Sheet Index	F - 3 - 10

Fig. 3.1.11	Sheet Index Scale 1:2,000 (Semarang Area)	F - 3 - 11
Fig. 3.1.12	Sheet Index Scale 1:2,000 (Ungaran Area)	F - 3 - 12
Fig. 3.1.13	Sheet Index Scale 1:1,000	F - 3 - 13
Fig. 3.1.14	Sounding Survey Area	F - 3 - 14
Fig. 3.1.15	Subsidence	F - 3 - 15
Fig. 3.2.1	Location of Borings	F - 3 - 16
Fig. 3.2.2	Geological Profile of West Floodway / Garang River	F - 3 - 18
Fig. 3.2.3	Geological Profile of Upstream of Simongan Weir	F - 3 - 20
Fig. 3.3.1	Probable Rainfall in 10 and 60 Minutes	F - 3 - 21
Fig. 3.3.2	Probable Rainfall in 6 Hours and 1 Day	F - 3 - 22
Fig. 3.3.3	Rainfall Intensity Curve	
Fig. 3.3.4	Design Storm of 100-Year Return Period	F - 3 - 24
Fig. 3.3.5	Probable Discharge at Simongan Weir	F - 3 - 25
Fig. 3.3.6	Thiessen Polygon for Flood Analysis	F - 3 - 26
Fig. 3.3.7	Calibration of Flood Model by Storage Function Method	
Fig. 3.3.8	Sub-Basin Division for Flood Model	F - 3 - 29
Fig. 3.3.9	Model Diagram for Flood Calculation	F - 3 - 30
Fig. 3.3.10	Area Reduction Factor for Garang River Basin	F - 3 - 31
Fig. 3.3.11	Flood Control Effect by Jatibarang Dam	F - 3 - 32
Fig. 3.3.12	Distribution of Design Flood Discharge in Garang River	F - 3 - 33
Fig. 3.3.13	Daily Discharge Chart Observed at Panjangan Station in Garang River	F - 3 - 34
Fig. 3.3.14	Tank Model Parameters	F - 3 - 36
Fig. 3.3.15	Result Chart of Tank Model Simulation	
Fig. 4.1.1	Comparison of Longitudinal Profile of West Floodway	. '
7. P	Between 1991 and 1997	F - 4 - 1
Fig. 4.2.1	Plan for West Floodway Improvement	F - 4 - 2
Fig. 4.2.2	Design Longitudinal Profile of West Floodway	F - 4 - 5
Fig. 4.2.3	Standard Cross Section of River Channel (West Floodway)	F - 4 - 6
Fig. 4.2.4	Plan for Garang River Improvement	F - 4 - 8
Fig. 4.2.5	Design Longitudinal Profile of Garang River	F - 4 - 11
Fig. 4.2.6	Uniform Flow Calculation for Design Cross Section of Garang River	F - 4 - 12
Fig. 4.2.7	Standard Cross Section of River Channel (Garang River)	
Fig. 4.2.8	Longitudinal Profile of Kalito River and Water Level of Garang River	F - 4 - 14

Fig. 5.1.9	Reasons for Agreement about 1 toject	r - J - 10
G	Reasons for Agreement about Project	2.5
Fig. 5.1.8	Public Perception for the Project and Expected Method of Compensation	
Fig. 5.1.7	Economy of Project - Affected Families	
Fig. 5.1.6	Comparison of Heavy Metal Concentration between Water and Sediment	F - 5 - 6
Fig. 5.1.5	Concentration of Heavy Metal in Sediment	F - 5 - 5
Fig. 5.1.4	BOD and DO at PDAM Water Intake Location	F - 5 - 4
Fig. 5.1.3	BOD, COD and DO Compared with Results of 1992	
Fig. 5.1.2	Concentrations of BOD, COD and DO	F - 5 - 2
Fig. 5.1.1	Water Sampling Location	F - 5 - 1
Fig. 4.2.31	Design Longitudinal Profile for Approach Track	F - 4 - 40
Fig. 4.2.30	Existing Railway Bridge	F - 4 - 39
Fig. 4.2.29	Location Map of Railway Bridge	F - 4 - 38
Fig. 4.2.28	Waterfront Facilities	F - 4 - 36
Fig. 4.2.27	Typical Drawing for Drainage Outlet	F - 4 - 35
Fig. 4.2.26	Riverbed Protection around Bridge Pier	F - 4 - 34
Fig. 4.2.25	General Feature of Groin	
Fig. 4.2.24	General Feature of Ground Sill (WF.173)	
Fig. 4.2.23	General Feature of Ground Sill (WF.124)	
Fig. 4.2.22	Typical Cross Section of Revetment	F - 4 - 28
Fig. 4.2.21	Discharge Rating for Flood Discharge Gate and Sediment Flush Gate	F - 4 - 27
Fig. 4.2.20	Structural Features of Alternative 3	F - 4 - 26
Fig. 4.2.19	Structural Features of Alternative 2	and the second second
Fig. 4.2.18	Structural Features of Alternative 1	F - 4 - 24
Fig. 4.2.17	Number of Pier and Gate Length for Alternatives	F - 4 - 23
Fig. 4.2.16	Water Level - Discharge Relation in River Channel near Simongan Weir	F - 4 - 22
Fig. 4.2.15	General Features of Weir (Alternative - 2)	F - 4 - 21
Fig. 4.2.14	Longitudinal Profile of Garang River Channel (Alternative - 2)	F - 4 - 20
Fig. 4.2.13	Location of Weir (Alternative - 2)	F - 4 - 19
Fig. 4.2.12	Design Plan for Simongan Weir	
Fig. 4.2.11	Structural Detailed Drawings for Floodwall Raising	
Fig. 4.2.10	. Typical Cross Section of Proposed Earth Dike	F - 4 - 16
Fig. 4.2.9	Longitudinal Profile of Cengkek Channel and Water Level of Garang River	

	Fig. 5.1.10	Reasons for Disagreement about Project F - 5 - 11
	Fig. 5.3.1	Groundwater Reservoir and Conditions of Aquifer Zone F - 5 - 12
	Fig. 6.2.1	Calculated Water Level and Design High Water Level in West FloodwayF - 6 - 1
	Fig. 6.2.2	Flow Velocity of Design River Channel under Design Flood Discharge F - 6 - 2
	Fig. 6.2.3	Calculated Water Level and Design High Water Level in Garang River F - 6 - 3
	Fig. 6.2.4	Water Level Profile in the Upstream and Downstream of Simongan Weir F - 6 - 4
	Fig. 6.3.1	Result of Stability at River Mouth DikeF - 6 - 5
	Fig. 6.4.1	Pile Arrangement for Footing of Both Center Pier and End Pier F - 6 - 6
•	Fig. 6.4.2	Loads Acting on WeirF - 6 - 7
	Fig. 6.4.3	Interaction Curve on PC Pile Strength F - 6 - 9
	Fig. 6.4.4	Calculation of Bearing Capacity of PC Pile F - 6 - 11
-	Fig. 6.4.5	Relation between Bridge Span Length and Bridge Type F - 6 - 12
	Fig. 6.4.6	General View of Maintenance Bridges F - 6 - 13
	Fig. 6.4.7	Structure of Simongan Approach Bridge F - 6 - 14
	Fig. 6.5.1	Result of Stability Analysis on River Bank Slope F - 6 - 17
	Fig. 7.1.1	Possible Spoil Bank Areas F - 7 - 1
	Fig. 7.2.1	Raising of Existing FloodwallF - 7 - 2
* .	Fig. 7.2.2	General Feature of Groin F - 7 - 3
-	Fig. 7.2.3	Standard Section of Coffering TypesF - 7 - 4
	Fig. 7.2.4	Procedure of Rising of the Existing Railway Bridge F - 7 - 6
	Fig. 7.3.1	Procedure of the First Stage CofferingF - 7 - 7
	Fig. 7.3.2	Procedure of the Second Stage CofferingF - 7 - 9
	Fig. 7.3.3	Channel Diversion and Water Supply for Semarang River F - 7 - 12
	Fig. 7.3.4	Installation of Flood Discharge Gate F - 7 - 13
	Fig. 7.3.5	Installation of Sediment Flush Gate F - 7 - 14
	Fig. 8.1.1	Flowchart of Cost Estimate F - 8 - 1
	Fig. 9.2.1	Operation Record of PDAM Intake Pump (1994 to 1998) F - 9 - 1
i satur. Mara	Fig. 9.2.2	Relation between State of Gate Operating System and Flood Discharge Volume F - 9 - 2
	Fig. 9.2.3	Overflow Depth - Discharge Relation of Flood Discharge Gate F - 9 - 4

Fig. 9.2.4	Relation Between Gate Opening and Underflow Discharge	
	for Flood Discharge Gate	F - 9 - 5
Fig. 9.2.5	Relation Between Gate Opening and Underflow Discharge for Sediment Flush Gate	., F - 9 - 6
Fig. 9.2.6	Discharge Rating for Right Intake Gate	F-9-7
Fig. 9.2.7	Discharge Rating for Left Intake Gate	F - 9 - 8
Fig. 10.1.1	The Structure of the Regional Governments	F - 10 - 1
Fig. 10.2.1	Organization of Jratunseluna Master Project Office and It's Related Authorities	F - 10 - 2
Fig. 10.2.2	Water Resources Development Service of Central Java Province	
Fig. 10.2.3	The Organization of Public Works Service	F - 10 - 4
Fig. 10.3.1	Proposed Organizations	F - 10 - 5
Fig. 11.1.1	Project Packaging	F - 11 - 1
Fig. 11.1.2	Implementation Schedule of West Floodway / Garang River Improvement	F - 11 <i>-</i> 2

LIST OF DRAWINGS

DWG. 6.2.1	Plan of West Floodway	
DWG. 6.2.2	Longitudinal Profile of West Floodway	
DWG. 6.2.3	Standard Cross Section of West Floodway	D - 6
DWG. 6.2.4	Plan of Garang River	D - 8
DWG. 6.2.5	Longitudinal Profile of Garang River	
DWG. 6.2.6	Standard Cross Section of Garang River	D - 12
DWG. 6.2.7	Longitudinal Profile and Cross Section of Tributary	D - 14
DWG. 6.2.8	Standard Cross Section of Earth Dike	D - 15
DWG. 6.3.1	Longitudinal Profile of Rising of Existing Floodwall	D - 16
DWG. 6.3.2	Typical Cross Section and Structural Details of Raising of Existing Floodwall	D - 18
DWG. 6.4.1	Plan of Simongan Weir	D - 19
DWG. 6.4.2	Upstream Elevation of Simongan Weir	
DWG. 6.4.3	Profile of Simongan Weir	
DWG. 6.4.4	Center Pier	
DWG. 6.4.5	End Pier	
DWG. 6.4.6	Gate Floor Slab	D - 28
DWG. 6.4.7	Flood Discharge Gates	D - 29
DWG. 6.4.8	Sediment Flush Gate	D - 30
DWG. 6.4.9	Layout Plan of Simongan Weir and Intake Structures	D - 31
DWG. 6.4.10	Right Bank Intake Structure	D - 32
DWG. 6.4.11	Hoisting System of Right Bank Intake Structure	D - 33
DWG. 6.4.12	Left Bank Intake Structure	
DWG. 6.4.13	Hoisting System of Left Bank Intake Structure	
DWG. 6.4.14	Downstream Concrete Apron - 1	D - 36
DWG. 6.4.15	Downstream Concrete Apron - 2	D - 37
DWG. 6.4.16	Upstream Concrete Apron	D - 38
DWG. 6.4.17	Concrete Block and Gabion Mattress	D - 39
DWG. 6.4.18	Downstream Approach Walls on Left bank	
DWG. 6.4.19	Downstream Approach Walls on Right Bank	
DWG. 6.4.20	Upstream Approach Walls on Left Bank	D - 42
DWG. 6.4.21	Upstream Approach Walls on Right Bank	D - 43
DWG. 6.4.22	Revetment of Downstream Channel	
DWG 6423	Location of Maintenance and Approach Bridges	D - 45

DWG. 6.5.8	Standard Cross Section and Profile of Revetment and Leaning Wall (WF.175 R to WF.180 R)	D - 72
DWG. 6.5.8	Standard Cross Section and Profile of Revetment	
	(WF.175 R to WF.180 R)	D - 71
DWG. 6.5.7	General Layout Plan of Revetment and Leaning Wall	
DWG. 6.5.6	Standard Cross Section and Profile of Revetment and Leaning Wall (WF.147 to WF.155)	D - 70
	(WF.147 to WF.155)	D - 69
DWG. 6.5.5	General Layout Plan of Revetment and Leaning Wall	
DWG. 6.5.4	Standard Cross Section and Profile of Revetment and Leaning Wall (WF.100 to WF.112)	D - 68
	(WF.100 to WF.112)	D - 67
DWG. 6.5.3	General Layout Plan of Revetment and Leaning Wall	
DWG. 6.5.2	Standard Cross Section and Profile of Revetment and Leaning Wall (WF.64 to WF.75)	D - 66
DWG 652	(WF.64 to WF.75)	D - 65
DWG. 6.5.1	General Layout Plan of Revetment and Leaning Wall	D 65
DWG. 6.4.42	Profile of Reconstruction of Part of Weir	D - 64
DWG. 6.4.41	Profile of Preserved Structures of Existing Weir	D - 63
DWG. 6.4.40	Profile of Gate Shed for Left Bank Intake Structure	
DWG. 6.4.39	Profile of Gate Shed for Right Bank Intake Structure	D - 61
DWG. 6.4.38	Profile of Control House II	
DWG. 6.4.37	Profile of Control House I	
DWG. 6.4.36	Elevation and Cross Section of Guard House	D - 58
DWG. 6.4.35	Plan of Guard House	
DWG. 6.4.34	Elevation and Cross Section of Storage House II	
DWG. 6.4.33	Cross Section of Storage House I	D - 55
DWG. 6.4.32		
DWG. 6.4.31	Plan and Elevation of Storage House I	and the second of
DWG. 6.4.30	Standard Cross Section of Electrical Building	
DWG. 6.4.29	Plan of Electrical Building	
DWG. 6.4.28	Elevation of Operation / Management Building	
DWG. 6.4.27	Plan of Operation / Management Building	
DWG. 6.4.26	Layout Plan of Simongan Weir Management Complex	
DWG. 6.4.25	Superstructures of Maintenance Bridge (No.1 and 5)	
DWG. 6.4.24	Superstructures of Maintenance Bridge (No.2, 3, and 4)	D - 46

DWG. 6.5.13	Plan and Longitudinal Profile of Stone Facing (WF 9 L to WF.3 L)	. D - 77
DWG. 6.5.14	Plan and Cross Section of Stone Facing (WF.4 R to WF.6 R)	
DWG. 6.5.15	Pile Type Groin	. D - 79
DWG. 6.5.16	Riverbed Protection for North Ring Road Bridge	D - 80
DWG. 6.5.17	Riverbed Protection for Railway Bridge	. D - 81
DWG. 6.5.18	Riverbed Protection for New Simongan Bridge	. D - 82
DWG. 6.6.1	Plan of Ground Sill with Head at WF.124	. D - 83
DWG. 6.6.2	Profile and Cross section of Ground Sill with Head at WF.124	. D - 84
DWG. 6.6.3	Plan of Ground Sill without Head at WF.173	. D - 85
DWG. 6.6.4	Profile and Cross section of Ground Sill without Head at WF.173	. D - 86
DWG. 6.7.1	Plan and Profile of Drainage Channel and Sluiceway	. D - 87
DWG. 6.7.2	Sluiceway	D - 88
DWG. 6.7.3	Gate and Blockout	
DWG. 6.7.4	Connecting Channel	
DWG. 6.7.5	Outlet Channel (R 9)	D - 91
DWG. 6.7.6	Flap Gate (R 9)	. D - 92
DWG. 6.7.7	Drainage Pipe (R 18, R 19)	D - 93
DWG. 6.8.1	Mooring Facility	D - 94
DWG. 6.8.2	Approach Steps in West Floodway	. D - 95
DWG. 6.8.3	Approach Steps in Garang River	. D - 96
DWG. 6.8.4	Water Level Gauging Station	D - 97
DWG. 6.9.1	Profile of Ranway Bridge	10 " 30
DWG. 6.9.2	Left Bank Abutment	. D - 99
DWG. 6.9.3	Bridge Pier	. D - 100
DWG. 6.9.4	Right Bank Abutment	. D - 101
DWG. 6.9.5	Plan and Longitudinal Profile of Track	
DWG. 6.9.6	Standard Cross Section of Raising Track	D - 104
DWG 697	Track Crossing Bridge	D- 105

TERMS AND ABBREVIATIONS

1. INDONESIAN GOVERNMENT AGENCIES AND ORGANIZATIONS

GOI : Government of Indonesia

BAPPENAS: Badan Perencanaan Pembangunan National (National

Development Planning Board)

BAPPEDA: Badan Perencanaan Pembangunan Daerah (Provincial Develop-

ment Planning Board)

BINAMARGA: Directorate General of Road and Bridge, Ministry of Public

Works

BAPEDAL : Badan Pengendalian Dampak Lingkungan (Environmental Impact

Assessement Board)

BPN: Badan Pertanahan Nasional (National Land Agency)

BPP : Balai Penyuluhan Pertanian (Agricultural Extension Center)

DPU : Departemen Pekerjaan Umum (Ministry of Public Works)

DGWRD : Directorate General of Water Resources Development, Ministry

of Public Works

DGCK : Directorate General of Cipta Karya (Housing, Building and Urban

Development, Ministry of Public Works)

DGRD : Directorate General of Research and Development, Ministry of

Public Works)

DOR : Directorate of Rivers

DPUP : Dinas Pekerjaan Umum Propinsi (Provincial Public Works

Services)

IHE : Institute of Hydraulic Engineering (Bandung)

PJKA : Perusahaan Jawatan Kereta Api (Railway Company, Old Name)

PERUMKA : Perusahaan Umum Kereta Api (Indonesian Railway Public

Corporation, New Name)

PDAM : Perusahaan Daerah Air Minum (Water Works Company)

PMG : Pusat Meteorologi dan Geofisika (Center of Meteorology and

Geographysics)

PLN : Perusahaan Listrik Negara (State Electricity Corporation)

P3SA : Proyek Pengembangan dan Penyelidikan Sumber-Sumber Air

(Water Resources Development and Investigation Project)

2. JAPANESE GOVERNMENT / INTERNATIONAL ORGANIZATIONS

GOJ : Government of Japan

JICA : Japan International Cooperation Agency

JBIC : Japan Bank for International Cooperation

MOC : Ministry of Construction, Japan

Japan Electric Machine Industry JEM

ADB Asian Development Bank

International Bank for Reconstruction and Development (World **IBRD**

United Nations Development Program UNDP

WMO World Meteorological Organization

American Society for Testing and Materials **ASTM**

American Society of Mechanical Engineer **ASME**

United States of America Standards **USASI**

International Electrotechnical Committee **IEC**

NEMA National Electrical Manufacturers Association

MEASUREMENT UNITS

(Weight) (Length)

millimeter(s) gram(s) mm g, gr

kilogram(s) centimeter(s) kg cm

tonnage (s) t, ton meter(s) m

kilometer(s) km

(Area) (Time)

square meter(s)

second(s) square millimeter(s) mm^2 sec., s

minute(s) square centimeter(s) min cm^2

h (hrs)

hour(s)

square kilometer(s) day(s) km² d (dys).

year(s) ha(has) hectare(s) y, yr(yrs)

(Discharge) (Volume)

liter(s) cm3 cubic centimeter(s) l, ltr Elevation

 m^3 cubic meter(s) EL., El.

(Combined Units)

Speed/Velocity

cm/sec, cm/s centimeter per second

m/sec, m/s meter per second

kilometer per hour km/hr, km/h

Stress

 m^2

kgf/cm² kilogram per square centimeter

tf/m² ton per square meter

N/mm² newton per square millimeter Mpa

mega pascal

Discharge

ltr/sec, 1/s

liter per second

m³/sec, m³/s

cubic meter per second

m³/yr, m³/y

cubic meter per year

(Note: Other combined units may be constructed similarly as above)

Electricity

MW

megawatt

GW

gegawatt

MWh

megawatt hour

GWh

gegawatt hour

kV

kilovolt

MONETARY TERMS

¥

Japanese Yen

US\$

United States Dollar

Rp.

Indonesian Rupiah

INDONESIAN TERMS

JKT

Jakarta

Jawa

Java

Propinsi

Province

Kabupaten, Kab.

District (Regency)

Kotamadya, Kodya

Municipality

Kecamatan, Kec.

Sub-District

Desa

Village (Rural Area)

Kampung, Kp.

Village (Rural Area)

Kelurahan

Village (Urban Area)

Kali, Sungai

River

Gunung

Mountain

Rawa

Swamp

Danau

Lake

Laut

Sea

PT.

Incorporated or Limited

PPT

Panitia Pembebasan Tanah (Land Acquisition Committee)

KOMPUS

Komisi Pusat (Central Committee for Environmental Impact

Assessment)

KA-ANDAL

Terms of Reference of Environmental Impact Statement

ANDAL

Environmental Impact Statement

RKL : Environmental Management Plan

RPL: Environmental Monitoring Plan

AMDAL : Environmental Impact Assessment

BPPM2 : Semarang Port Bench Mark

SPB : Semarang Peil Baru (New Semarang Level)

TTG : Tanda Tinggi Geodesi (National Bench Mark)

6. OTHERS

JRATUNSELUNA PROJECT: Water Resources Development Projects for Jragung,

Tuntang, Serang, Lusi and Juwana Rivers

SSUDP : Semarang and Surakarta Urban Development Program

IUIDP : Integrated Urban Infrastructures Development Program

SWL : Surcharge Water Level

DFWL : Design Flood Water Level

PMP : Probable Maximum Precipitation

PMF : Probable Maximum Flood

EIRR : Economic Internal Rate of Return

JIS : Japanese Industrial Standard

USASI : United States of America Standards

SWR : Shadow Wage Rate

CIF : Cost, Insurance and Freight

VAT : Value Added Tax.

CHAPTER

INTRODUCTION

CHAPTER 1. INTRODUCTION

1.1 Background

Semarang City, the capital of Central Java Province, had the population of 1,250,000 in 1996. The city and its surrounding areas suffer almost every year from floods in rainy seasons and from shortage of water supply in dry seasons. The problem on water shortage will aggravate further in the future due to the recent trend of population concentration in the urban area.

To mitigate these chronic economic problems and to enhance the economic development and stabilization of people's livelihood, appropriate measures are indispensable for Semarang City and its surrounding areas. To this end, the Government of Indonesia requested technical assistance from the Government of Japan.

In response to the request of the Government of Indonesia, the Government of Japan dispatched a study team through the Japan International Cooperation Agency (JICA) to formulate a master plan and to carry out a feasibility study on the selected priority projects from 1992 to 1993. The study was named as "The Master Plan on Water Resources Development and Feasibility Study for Urgent Flood Control and Urban Drainage in Semarang City and Suburbs". (refer to Fig. 1.1.1)

In the final report of the above study, three priority projects were proposed from the viewpoint of economic viability and urgent necessity of project realization. The proposed priority projects are:

- (1) West Floodway/Garang River Improvement (including reconstruction of Simongan Weir);
- (2) Construction of Jatibarang Multipurpose Dam on Kreo River; and,
- (3) Urban Drainage System Improvement.

For the urgent realization of the proposed priority projects, the Government of Indonesia requested further technical assistance from the Government of Japan in 1996. JICA then decided to dispatch another study team to carry out the detailed design of the priority projects, and the study is named as "The Detailed Design of Flood Control, Urban Drainage and Water Resources Development in Semarang in the Republic of Indonesia" (hereinafter referred to as "the Study").

1.2 Objectives of the Study

The objectives of the Study are: to carry out the detailed design of the following three (3) components of the Study, which consist of (1) West Floodway/Garang River Improvement, (2) Construction of Jatibarang Multipurpose Dam, and (3) Urban Drainage System Improvement, and to pursue transfer of technical knowledge to the counterpart personnel in the course of the Study.

1.3 Study Area

The study area is administratively covered by Semarang City and Semarang Regency (Kabupaten) in Central Java Province, and is topographically included in Garang river basin and the central area of Semarang City.

1.4 Description of Project Component : West Floodway/Garang River Improvement

Previous Study

The flood control master plan was formulated under the JICA Study mentioned above for the six (6) rivers of Blorong River, Bringin River, Silandak River, West Floodway/Garang River, East Floodway and Babon River. Feasibility Study was, then, conducted for the selected priority project namely, River Improvement of West Floodway/Garang River and Construction of Jatibarang Multipurpose Dam on Kreo River.

The flood of January 1990 caused overflow along West Floodway/Garang River resulting in the enormous flood damage in Semarang City and suburbs. With this as a turning point, improvement of West Floodway/Garang River including reconstruction of Simongan Weir was taken up as the Urgent Project to facilitate the immediate formulation and implementation of necessary river improvement works.

According to the previous study, the planning criteria of flood control scheme for West Floodway/Garang River is as shown below.

	Master Plan	Priority Project	Urgent Project
Project Works	River improvement of West Floodway/Garang	River improvement of West Floodway/Garang	River improvement of West Floodway/Garang
	River (9.57 km)	River (9.57 km)	River (9.57 km)
	Construction	Construction	
	of Jatibarang Dam and	of Jatibarang Dam	
	Mundingan Dam		The state of the state of
Project Scale	100-Year	100-Year	25-Year
Target Year	2015	2005	2000

Necessity of the Project

West Floodway/Garang River pass through the urban area of Semarang City, the largest city and the center of economic and social development in Central Java Province. The urban area of Semarang City is expanding every year with the rapid urbanization and, correspondingly, the damage inflicted by river floods has become more serious, hampering development and giving an adverse environmental impacts to the area.

For West Floodway/Garang River, the river improvement works focusing on earth dike and floodwall construction were almost completed in accordance with a 10 to 25-year return period floods. Still, fear of flood has not been overcome because of the potential high flood level of the channel. In addition, the possibility of recurrence of flood overflow of the river channel like the one in 1990 is still high.

Under the circumstances, the flood control project composed of improvement of West Floodway/Garang River and construction of Jatibarang multipurpose Dam has been given higher priority for implementation. Among the components, improvement of West Floodway/Garang River including Reconstruction of Simongan Weir is urgently required.

Study Area of the D/D

The river improvement work of West Floodway/Garan River is to be undertaken for the river stretch from the river mouth up to the confluence of Garang and Kreo rivers, amounting to about 9.6 km. Simongan Weir is located at about 5.4 km upstream point from the river mouth, and the downstream channel from the weir is called West Floodway.

1.5 Scope of the D/D Study

The D/D Study for the three (3) project components mentioned above was commenced in August 1997 and is scheduled to be completed in July 2000 with submission of the final reports for all components. Before the completion of the final reports, the draft final reports are to be prepared and submitted in accordance with the follow schedule.

Component

(1) West Floodway/Gaarang River Improvement

(2) Urban Drainage System Improvement

(3) Construction of Jatibarang Multipurpose Dam

Date

Middle of September, 1999

End of November, 1999

End of March, 2000

The D/D Study is divided into two phases, namely, (1) Definitive Plan and (2) Detailed Design.

The D/D Study is to consist of field and home office works. The flow of work is as illustrated in Fig. 1.5.1, and the details of scope of works are as outlined below.

Definitive Plan

The main study items of "Definitive Plan" are as follows:

- (1) Data Collection and Compilation
- (2) Review of Feasibility Study
- (3) Aerophotograph/Mapping, Topographic and River Survey
- (4) Geological and Soil Mechanics Survey
- (5) Environmental/Social Impact Analysis, RKL, RPL and River Basin Management Plan
- (6) Formulation of Basic Plan
- (7) Basic Design
- (8) Preliminary Construction Plan and Cost Estimate
- (9) Socioeconomic Evaluation
- (10) Preparation of Project Implementation Program

Detailed Design

The detailed design work includes the following items.

- (1) Preparation of Design Criteria
- (2) Detailed Design Work (Design Calculation and Drawings)
- (3) Quantity Estimation
- (4) Construction Plan
- (5) Cost Estimate
- (6) Operation and Maintenance Plan
- (7) Organization and Institution
- (8) Preparation of Prequalification, Tender Documents and Tender Drawings

Prequalification and tender documents are prepared after the preparation of detailed designs, and the tender documents includes the following:

- (1) Invitation to Tender
- (2) Instructions to Tenderers
- (3) Form of Tender
- (4) Form of Contract
- (5) Specimens of Various Bonds
- (6) Bill of Quantities
- (7) General Conditions of Contract
- (8) Special Conditions of Contract
- (9) General Specifications
- (10) Technical Specifications
- (11) Tender Drawings

FIGURES

CHAPTER 1

INTRODUCTION

