

## **4. Well Construction Data**

## 4.1. INTRODUCTION

### 1.1 General

This final report on Drilling Work for the Study on Rural Water Supply and Sanitation Improvement in North-West Region in Lao People's Democratic Republic presents the results of the studies on the construction of deep boreholes and hand dug wells as an evaluation of the groundwater potential and planning of its development for water supply facilities. The study, which was organized by the Japan International Cooperation Agency (JICA) and under supervised by Japan Techno Co., Ltd., has conducted by Siam Tone Co., Ltd. The study was carried out in accordance with the scope of work agreed upon by the JICA and the Ministry of Health. The study commenced geophysical survey in December, 1999 and the construction of deep boreholes and hand dug wells during January - February, 2000.

### 1.2 Purpose

The purpose of the drilling work is to construct hand dug wells and deep boreholes as water supply facilities. Specially, the work aims to formulate a suitable water supply in the target villages.

### 1.3 Scope

The scope for the drilling work is described below :


Location	Site No.	H-9	H-37	H-3
	Village Name	May Phatthana	Leang	Nam Ngao
	District	Houayxai District		
	Province	Bokeo Province		
Well Specifications	Type	Borehole	Borehole	Dug well
	Number	1	1	2
	Drilling Diam.	$\phi$ 10" ~ 8-1/2"	$\phi$ 10" ~ 8-1/2"	$\phi$ 1m (+)
	Depth (m)	50	50	10
	Casing Diam. & Length	$\phi$ 6" 32 m	$\phi$ 6" 32 m	$\phi$ 1m
	Casing Material	PVC	PVC	Concrete
	Screen Diam. & Length	$\phi$ 6" 18 m	$\phi$ 6" 18 m	$\phi$ 1m 3~4 m
	Screen Material	PVC	PVC	Concrete


Geophysical Survey	Geoelectric Prospecting	5 points/well	5 points/well	3 points/well
	Prospecting Method	Wenner	Wenner	Wenner
	Prospecting Depth (m)	100	100	20
	Well Logging	1 time	1 time	-
Pumping Test	Step drawdown Test	5 Steps	5 Steps	None
	Continuous Test	24 Hours	24 Hours	
	Recovery Test	12 Hours	12 Hours	
Measurements to be made during Water Level Measurements	pH, temp., conductivity			
Water Quality Analysis	Standard	Drinking Water Standard according to WHO		
	Items as per attached list	25	25	25

Service Items	Contract Items	
Color	1. TDS	14. Pb
Odor	2. Total Hardness	15. Hg
Taste	3. Cu	16. Ca
pH	4. Fe	17. B
Turbidity	5. Mn	18. CN
Electric Conductivity	6. Cl-	19. Se
Temperature	7. SO <sub>4</sub> <sup>2-</sup>	20. Al
	8. Zn	21. NH <sub>4</sub> -N
	9. As	22. NO <sub>2</sub> -N
	10. Ba	23. NO <sub>3</sub> -N
	11. Cd	24. Coliform Group
	12. Cr <sup>6+</sup>	25. Alkalinity
	13. F-	

#### 1.4 Study Area

The study area is located in the north-west region of Lao People 's Democratic Republic. The Location of work is at Ban May Patthana, Ban Leang and Ban Nam ngao in Houayxai District , Bokeo Province as attached map.





## 4.2. GEOPHYSICAL SURVEY

The Vertical Electrical Sounding (Resistivity Method) of geophysical exploration was conducted at target villages before construction of deep boreholes and hand dug wells to make clear basic information on drilling points and depths. The two villages, which targets for deep boreholes drilling comprise of H-9 Ban May Phatthana and H-37 Ban Leang were conducted resistivity survey with prospecting depth 100 m of 4 points at H-9 and 5 points at H-37. The H-3 Ban Namngao, which targets for hand dug wells construction was conducted resistivity survey with prospecting depth 20 m of 5 points. Specially, at Ban Houayxay Noy which is not the target village but also was conducted resistivity survey with prospecting depth 100 m of 1 point. The location of survey points were shown as attached map.


### 2.1 Resistivity Survey


Wenner arrangement was adopted for this work. It is considered to be the most commonly used arrangement for groundwater prospecting. It is effective to detect a flat layered geological structure. The OYO McOHM meter was used. This instrument is an electric survey unit of stacking type. The resistivity survey curves were analyzed by the graphical method using standard curves and computer aided program.

### 2.2 Results of Resistivity Survey

The analysis was first carried out graphically using the standard curves and the estimated resistivities were inputted as initial values for the computer program. Resistivities and depths of layers were estimated.

D4-6





**SKETCH VILLAGE MAP OF BAN NAM NGAO H-3**


- R-RESISTIVITY SURVEY POINT
- ▲ H-HAND DUG WELL LOCATION



**SKETCH VILLAGE MAP OF BAN LEANG H-37**

● R-RESISTIVITY SURVEY POINT

▲ H-DRILLING POINT



D48

#### 4.3. HAND DUG WELLS CONSTRUCTION

Hand dug wells construction were conducted 2 wells at H-3 Ban Nam Ngao. The digging locations were determined by and between JICA study team, Nam Saat Division of Bokeo Province and the villager. Well No. H-3 1/2 was located on nearby resistivity survey point 5 and dug to the depth of 8 m. Well No. H-3 2/2 were dug at 2 locations. The first location, H-3 2/2A was located on nearby between resistivity survey point 1 and temple. The well was dug to the depth of 4 m until reach rock surface but dry. The successful well is second location, H-3 2/2B was located on nearby river. The depth of well is 9 m. The total amount of digging depth is 21 m and total casing length is 17 m. The 1 m diameter of concrete casing was used. The aquifer was gravel pack in order to stabilize aquifer and minimized sand pumping. A grain size of the gravel was 2 - 5 cm. In the completion of the gravel packed, the annular space outside the casing was backfilled by digging cutting. In addition, 0.5 m from the surface of the ground, cement grout was placed to avoid entering of water from surface. Well development was carried out by continuous pumping used submersible pump until the water turned clean and without sand. The details of the wells are Presented in attached table.

Summary of the Details of Hand Dug wells

Well No.	Location	Dig Depth (m)	Well Depth (m)	S.W.L (GL-m)	Casing		Aquifer	Gravel Pack (m)	Back Filled (m)	Cement Seal (m)	Remark
					Diameter (m)	Type					
H-3 1/2	B. Nam Ngao	8.00	8.00	6.65	1.00	Concrete	Sand	6.00-8.00	0.50-6.00	0.00-0.50	-
H-3 2/2A	B. Nam Ngao	4.00	-	-	-	-	-	-	-	-	Dry
H-3 2/2B	B. Nam Ngao	9.00	9.00	6.41	1.00	Concrete	Sand	6.00-9.00	0.50-6.00	0.00-0.50	-
TOTAL :		21.00	17.00								

#### 4.4. BOREHOLES DRILLING

Boreholes drilling were conducted 2 wells at H-9 Ban May Phatthana and H-37 Ban Leang. The drilling locations were determined by and between JICA study team, Nam Saat Division of Bokeo Province and the villager. well No. H-9 were drilled at 2 locations. The first location, H-9A was located on nereby risistivity survey point 3 and drilled to the depth of 67.50 m but dry. The second location, H-9B was located on nereby resistivity point 1 and 2 which was successfull well. The depth of drilling is 47 m. Well No. H-37 was located on nereby resistivity survey point 3 and drilled to the depth of 60 m.

The total amount of drilling depth is 174.50 m. Down-the-hole drilling method was trial used but it was not successfull because of the formation is weak and possibility to collapse. The rotary drilling method with mud flushing of polymer was adopted. The diameter of drilling is 216 mm. The drilling cutting were collected and observed at every 1.5 m. The drilling speed was also recorded. The resistivity and spontaneous potential loggings were conducted at the boreholes.

The total amount of casing length were installed is 100.40 m. The 150 mm diameter of PVC pipes were used. The screen used for the well was a spiral slot type PVC screen, with and openning ratio 5% and a slot size 1 mm. The screen length and the position were determined by judging the aquifer unit based on the lithological and geophysical logging data. The screen length of 16 and 20 m were set on well No.H-9B and H-37 respectively. The total amount of screen length were used is 36 m. The annular space of the screen was filled with gravel in oder to stabilze aquifer, minimized sand pumping and increase well yields. A grain size of the gravel was 2 - 5 mm. From the top of the gravel, the annular space was filled with bentonite and the drilling cutting in order to avoid seepage from the surface. Upper most 3 m were grouted by cement. The wells were developed by a combination of water jetting, air surging and air lifting until the water turned clean and without sand. The details of the wells are presented in attached table.

Summary of the Details of Borehole Wells

Well No.	Location	Drilling			Well Depth (m)	Casing		Screen		Depth of (m)			S.W.L (GL-m)	Lithology	Remark
		Method	Dia. (mm)	Depth (m)		Dia. (mm)	Type	Depth (m)	Total (m)	Gravel Pack	Back Filled	Cement Seal			
H-9A	B. May Phattana	DTH	216	30.00	--	--	--	--	--	--	--	--	--	Sandstone	Dry
		DTH	165	67.50										Mudstone	
H-9B	B. May Phattana	Rotary	216	47.00	45.40	150	PVC	16-24	16	45.40	9.75	3.00	1.50	Sandstone	--
								28-32		--	--	--		Mudstone	
								36-40		10.75	3.00	0.00		Mudstone	
H-37	B. Leang	Rotary	216	60.00	55.00	150	PVC	23-31	20	55.00	16.40	3.00	7.50	Mudstone	--
								35-43		--	--	--		Mudstone	
								47-51		17.40	3.00	0.00		Mudstone	
TOTAL :				174.50	100.40			36							

D4-12

SUMMARY OF TYPE AND INSTALL DEPTH OF HAND PUMP

Well No.	Location	Type of Well	Well depth (m)	Type of Hand pump	Pump Depth (m)
H-3 1/2	B. Nam Ngao	Hand Dug Well	8.00	Lao-99	7.70
H-3 2/2 B	B. Nam Ngao	Hand Dug Well	9.00	Tara	8.80
H-9B	B. May Phattana	Borehole	45.40	Tara	26.00
H-37	B. Leang	Borehole	55.00	Afridev	35.00

#### 4.5.PUMPING TEST

Pumping tests were performed in order to obtain aquifer constants. The step draw-down test, continuous pumping test and recovery test were conducted on borehole wells at H-9B Ban May Phattana and Ban Leang. Hand dug wells at H-3 Ban Nam ngao were conducted only continuous pumping test and recovery test. Pumping tests were conducted by using submersible pump.

The step draw-down test was conducted at 5 steps in 2 hours interval. The step number and discharge rate were determined by using a maximum pumping rate by air lifting during well development. The continuous pumping test was conducted at a constant discharge rate until reach stable condition after the step draw-down test. After the continuous pumping test, pumping was stopped and the recovery of groundwater level was measured until water level recover to static level. The quantities of pumping test are presented in attached table.

The aquifer constants, Transmissivity (T) and Hydraulic Gradient (K), were analyzed by using Jacob 's method calculated from the result of continuous pumping test and recovery test datas. Specific capacity (Sc) was calculated by using the draw-down and the pumping rate at stable conditions during the pumping test. An optimum discharge rate of the test well was evaluated by using the step draw-down test data. Taking the critical water level found on the linear relation between the pumping rate (Q) and the draw-down (s) . The aquifer constants, specific capacity and optimum discharge of the test well are summarized in attached table.

Summary of Quantities of Pumping Test

Well No.	Location	Type of Well	Well depth (m)	S.W.L (GL-m)	Pumping Test			Remark
					Step	Continuous	Recovery	
H-3 1/2	B. Nam Ngao	Hand Dug Well	8.00	6.65	-	3 H	4 H	-
H-3 2/2 B	B. Nam Ngao	Hand Dug Well	9.00	6.41	-	7 H	12 H	-
H-9B	B. May Phattana	Borehole	45.40	1.50	5	6 H	1 H	-
H-37	B. Leang	Borehole	55.00	7.50	3	2:30 H	12 H	-



SUMMARY OF THE AQUIFER CONSTANTS, SPECIFIC CAPACITY AND OPTIMUM DISCHARGE OF THE TEST WELLS

Well No.	Location	Type of Well	S.W.L. (Gf-m.)	Transmissivity (T)			Hydraulic Gradient (K)			Specific Capacity (Sc) (m <sup>3</sup> /day/cm.)	Optimum Discharge (m <sup>3</sup> /day)
				T = (m <sup>2</sup> /day)			K (m/day)				
				Continuous Pumping Test	Recovery Test	Means	Continuous Pumping Test	Recovery Test	Means		
H-3 1/2	B. Nam Ngao	Hand Dug Well	6.650	52.704	40.464	46.584	26.352	20.270	23.311	-	-
H-3 2/2 B	B. Nam Ngao	Hand Dug Well	6.410	9.246	18.173	13.709	3.082	6.057	4.569	-	-
H-9B	B. May Phattana	Bore Hole	1.500	2.325	0.964	1.644	0.147	0.061	0.104	2.787	14.400
H-37	B. Leang	Bore Hole	7.500	0.135	0.141	0.138	0.007	0.007	0.007	0.613	0.010

#### 4.6. WATER QUALITY ANALYSIS

Groundwater dissolves parts of the soil and rock as it infiltrates and percolates through them. The cations occurring in groundwater are commonly calcium, magnesium, sodium, iron, manganese and potassium. The anions are mostly carbonate, bicarbonate, sulfate, chloride and nitrate.

In this study, water samplings from the test wells were conducted analysis according to Japanese standard of drinking water. The analysis was entrusted to a private laboratory. The following tables show the result of analysis.



บริษัท ดีเทอร์มิเนชั่น กรุ๊ป จำกัด

Determination Group Co., Ltd.

81/96 ถ.วิภาวดีรังสิต ซ.25 แขวงทุ่งสองห้อง เขตดอนเมือง กทม.10210

โทร. 591-1732 โทรสาร (662) 591-1732

81/96 Viphavadee-Rungsil Rd., Thungsoonghong, Donmuang,

Bangkok.10210, THAILAND. Tel.591-1732 Fax. (662) 591-1732

Project Name: **Laboratory No. 43060**

**The Study on Rural water supply and Sanitation improvement in North-West Region in Lao P.D.R.**

Sample Type Dug well

Well No. H - 3 1/2 B.Nam Gnao

Sampling date March1,2000

Reference No. 060/2543

Date March2,2000

Sample from **SIAM TONE Co.,Ltd.**  
(Mr. Supoch)

Physical Characteristic	Result	Guideline Value
pH	6.10	5.8-8.6
Electric Conductivity**	170	-
Color (Platinum Cobalt Scale)	0	5
Odor	Odourless	Odourless
Taste	Tasteless	Tasteless
Turbidity (NTU.)	0.3	2

Bacteriological Characteristic	Result	Guideline Value
Coliform Group	7	0/100 cc.
Number of General Bacteria	-	<100/1cc.

Toxic Substances	Result*	Guideline Value
Arsenic (As)	<0.001	0.05
Barium (Ba)	0.00	-
Chromium (Cr <sup>6+</sup> )	0.01	0.05
Cadmium (Cd)	<0.001	0.01
Lead (Pb)	0.00	0.1
Selenium (Se)	<0.002	-
Mercury (Hg)	<0.0005	0.000
Aluminium (Al)	0.01	-
Cyanide (CN)	<0.002	0.000

Chemical Characteristic	Result* (mg/L)	Guideline Value
Calcium (Ca)	16	300(hardness)
Magnesium (Mg)	5.9	300(hardness)
Sodium (Na)	9.1	-
Potassium (K)	1.6	-
Total-Iron (Fe)	0.00	0.3
Manganese (Mn)	0.00	0.3
Copper (Cu)	0.00	1.0
Zinc (Zn)	0.2	1.0
Ammonia (NH <sub>4</sub> )	0.98	0
Silica (SiO <sub>2</sub> )	19	-
p_Alkalinity "Carbonate (CO <sub>3</sub> )"	0	-
m_Alkalinity "Bicarbonate (HCO <sub>3</sub> )"	69	-
Carbondioxide gas (CO <sub>2</sub> )	87	-
Chloride (Cl)	1.6	200
Sulfate (SO <sub>4</sub> )	2.4	-
Nitrite (NO <sub>2</sub> )	0.000	0
Nitrate (NO <sub>3</sub> )	10	10
Fluoride (F)	0.0	0.8
Boron (B)	0.08	-
Total Hardness as CaCO <sub>3</sub>	64	300
Permanent Hardness as CaCO <sub>3</sub>	6	-
Total Dissolved Solids (TDS)	100	500

Appearance of water Small amount of insoluble matters.


Date March 3-12,2000

\* Unit milligram/cubic decimetre (milligram/Litre)

\*\* Unit microsiemen/cm. at 25 Degree celcius.

\*\*\* N.D: Non Detectable

Analysed and approved by

  
(Mr. Chakan) Prayoonchart  
Chemical and Research Division  
Determination Group Co., Ltd.

The above results are valid exclusively for tested/analysed sample as mentioned in this report.

**Japanese Standard.**



บริษัท ดีเทอร์มิเนชั่น กรุ๊ป จำกัด

Determination Group Co., Ltd.

81/96 ถนนวิภาวดีรังสิต ซ.25 แขวงทุ่งสองห้อง เขตดอนเมือง กทม.10210

โทร. 591-1732 โทรสาร (662) 591-1732

81/96 Viphavadee-Rungsit Rd., Thungsonghong, Donmuang,

Bangkok.10210, THAILAND. Tel.591-1732 Fax. (662) 591-1732

Project Name: **Laboratoty No. 43061**  
**The Study on Rural water supply and Sanitation improvement in North-West Region in Lao P.D.R.**  
 Sample Type Dug well  
 Well No. H - 3 2/2 B.Nam Gnao  
 Sampling date March1,2000

Reference No. 061/2543

Date March2,2000

Sample from **SIAM TONE Co.,Ltd.**  
 (Mr. Supoch)

Chemical Characteristic	Result* (mg/L)	Guideline Value
Calcium (Ca)	27	300(hardness)
Magnesium (Mg)	4.9	300(hardness)
Sodium (Na)	11	-
Potassium (K)	6.7	-
Total-Iron (Fe)	0.70	0.3
Manganese (Mn)	0.00	0.3
Copper (Cu)	0.02	1.0
Zinc (Zn)	0.3	1.0
Ammonia (NH <sub>4</sub> )	1.1	0
Silica (SiO <sub>2</sub> )	19	-
p_Alkalinity "Carbonate (CO <sub>3</sub> )"	0	-
m_Alkalinity "Bicarbonate (HCO <sub>3</sub> )"	82	-
Carbondioxide gas (CO <sub>2</sub> )	64	-
Chloride (Cl)	14	200
Sulfate (SO <sub>4</sub> )	12	-
Nitrite (NO <sub>2</sub> )	0.076	0
Nitrate (NO <sub>3</sub> )	26	10
Fluoride (F)	0.1	0.8
Boron (B)	0.05	-
Total Hardness as CaCO <sub>3</sub>	88	300
Permanent Hardness as CaCO <sub>3</sub>	21	-
Total Dissolved Solids (TDS)	162	500

Physical Characteristic	Result	Guideline Value
pH	6.31	5.8-8.6
Electric Conductivity**	248	-
Color (Platinum Cobalt Scale)	35	5
Odor	Odor	Odorless
Taste	Slightly Taste	Tasteless
Turbidity (NTU.)	50	2

Bacteriological Characteristic	Result	Guideline Value
Coliform Group	6	0/100 cc.
Number of General Bacteria	-	<100/1cc.

Toxic Substances	Result*	Guideline Value
Arsenic (As)	<0.001	0.05
Barium (Ba)	0.00	-
Chromium (Cr <sup>6+</sup> )	0.00	0.05
Cadmium (Cd)	<0.001	0.01
Lead (Pb)	0.00	0.1
Selenium (Se)	<0.002	-
Mercury (Hg)	<0.0005	0.000
Aluminium (Al)	0.00	-
Cyanide (CN)	<0.002	0.000


Appearance of water Precipitated iron and insoluble matters.  
 Date March 3-12,2000

\* Unit milligram/cubic decimetre (milligram/Litre)

\*\* Unit microsiemen/cm. at 25 Degree celcius.

\*\*\* N.D: Non Detectiable

Analysed and approved-by:

  
 (Mr. Chakan Prayoonchart)  
 Chemical and Research Division  
 Determination Group Co., Ltd.

The above results are valids exclusively for tested/analysed sample as mentioned in this report.

**Japanese Standard.**



บริษัท ดีเทอร์มิเนชั่น กรุ๊ป จำกัด

Determination Group Co., Ltd.

81/96 ถ.วิภาวดีรังสิต ซ.25 แขวงทุ่งสองห้อง เขตดอนเมือง กทม.10210

โทร. 591-1732 โทรสาร (662) 591-1732

81/96 Viphavadee-Rungsit Rd., Thungsonghong, Donmuang,

Bangkok.10210, THAILAND. Tel.591-1732 Fax. (662) 591-1732

Project Name:	Laboratory No.	43062
The Study on Rural water supply and Sanitation Improvement in North-West Region in Lao P.D.R.		
Sample Type	Groundwater	
Well No.	H - 9 B B.MayPhattana	
Sampling date	March 1, 2000	

Reference No. 062/2543

Date March 2, 2000

Sample from SIAM TONE Co., Ltd.  
(Mr. Supoch)

Chemical Characteristic	Result* (mg/L)	Guideline Value
Calcium (Ca)	106	300(hardness)
Magnesium (Mg)	14	300(hardness)
Sodium (Na)	20	-
Potassium (K)	2.4	-
Total-Iron (Fe)	0.09	0.3
Manganese (Mn)	0.00	0.3
Copper (Cu)	0.02	1.0
Zinc (Zn)	0.1	1.0
Ammonia (NH <sub>4</sub> )	1.0	0
Silica (SiO <sub>2</sub> )	53	-
p_Alkalinity "Carbonate (CO <sub>3</sub> )"	0	-
m_Alkalinity "Bicarbonate (HCO <sub>3</sub> )"	290	-
Carbondioxide gas (CO <sub>2</sub> )	41	-
Chloride (Cl)	1.2	200
Sulfate (SO <sub>4</sub> )	145	-
Nitrite (NO <sub>2</sub> )	0.000	0
Nitrate (NO <sub>3</sub> )	0.4	10
Fluoride (F)	0.2	0.8
Boron (B)	0.0	-
Total Hardness as CaCO <sub>3</sub>	325	300
Permanent Hardness as CaCO <sub>3</sub>	88	-
Total Dissolved Solids (TDS)	486	500

Physical Characteristic	Result	Guideline Value
pH	7.05	5.8-8.6
Electric Conductivity**	657	-
Color (Platinum Cobalt Scale)	35	5
Odor	Odor	Odorless
Taste	Slightly Taste	Tasteless
Turbidity (NTU.)	10	2

Bacteriological Characteristic	Result	Guideline Value
Coliform Group	16	0/100 cc.
Number of General Bacteria	-	<100/1cc.

Toxic Substances	Result*	Guideline Value
Arsenic (As)	<0.001	0.05
Barium (Ba)	0.00	-
Chromium (Cr <sup>6+</sup> )	0.00	0.05
Cadmium (Cd)	<0.001	0.01
Lead (Pb)	0.01	0.1
Selenium (Se)	<0.002	-
Mercury (Hg)	<0.0005	0.000
Aluminium (Al)	0.02	-
Cyanide (CN)	<0.002	0.000

Appearance of water Color and small amount of insoluble matters.


Date March 3-12, 2000

\* Unit milligram/cubic decimetre (milligram/Litre)

\*\* Unit microsiemen/cm. at 25 Degree celcius.

\*\*\* N.D: Non Detectable

Analysed and approved by

  
(Mr. Chakan Prajochart)  
Chemical and Research Division  
Determination Group Co., Ltd.

The above results are valid exclusively for tested/analysed sample as mentioned in this report.

Japanese Standard.



บริษัท ดีเทอร์มิเนชัน กรุ๊ป จำกัด

Determination Group Co., Ltd.

81/96 ด.วิภาวดีรังสิต ซ.25 แขวงทุ่งสองห้อง เขตดอนเมือง กทม.10210

โทร. 591-1732 โทรสาร (662) 591-1732

81/96 Viphavadee-Rungsit Rd., Thungsohong, Donmuang,

Bangkok.10210, THAILAND. Tel.591-1732 Fax. (662) 591-1732

Project Name: **Laboratoty No. 43063**

**The Study on Rural water supply and Sanitation Improvement in North-West Region in Lao P.D.R.**

Sample Type **Groundwater**

Well No. **H - 37 B.Leang**

Sampling date **March1,2000**

Reference No. 063/2543

Date **March2,2000**

Sample from **SIAM TONE Co.,Ltd.**  
(Mr. Supoch)

Chemical Characteristic	Result* (mg/L)	Guideline Value
Calcium (Ca)	35	300(hardness)
Magnesium (Mg)	41	300(hardness)
Sodium (Na)	16	-
Potassium (K)	7.1	-
Total-Iron (Fe)	1.1	0.3
Manganese (Mn)	0.00	0.3
Copper (Cu)	0.02	1.0
Zinc (Zn)	0.1	1.0
Ammonia (NH <sub>4</sub> )	1.3	0
Silica (SiO <sub>2</sub> )	13	-
p_Alkalinity "Carbonate (CO <sub>3</sub> )"	0	-
m_Alkalinity "Bicarbonate (HCO <sub>3</sub> )"	135	-
Carbondioxide gas (CO <sub>2</sub> )	18	-
Chloride (Cl)	6.0	200
Sulfate (SO <sub>4</sub> )	186	-
Nitrite (NO <sub>2</sub> )	0.007	0
Nitrate (NO <sub>3</sub> )	0.4	10
Fluoride (F)	0.2	0.8
Boron (B)	0.0	-
Total Hardness as CaCO <sub>3</sub>	258	300
Permanent Hardness as CaCO <sub>3</sub>	148	-
Total Dissolved Solids (TDS)	373	500

Physical Characteristic	Result	Guideline Value
pH	7.08	5.8-8.6
Electric Conductivity**	560	-
Color (Platinum Cobalt Scale)	50	5
Odor	Odor	Odorless
Taste	Slightly Taste	Tasteless
Turbidity (NTU.)	15	2

Bacteriological Characteristic	Result	Guideline Value
Coliform Group	16	0/100 cc.
Number of General Bacteria	-	<100/1cc.

Toxic Substances	Result*	Guideline Value
Arsenic (As)	<0.001	0.05
Barium (Ba)	0.00	-
Chromium (Cr <sup>6+</sup> )	0.00	0.05
Cadmium (Cd)	<0.001	0.01
Lead (Pb)	0.00	0.1
Selenium (Se)	<0.002	-
Mercury (Hg)	<0.0005	0.000
Aluminium (Al)	0.00	-
Cyanide (CN)	<0.002	0.000

Appearance of water **Precipitated iron and insoluble matters.**

Date **March 3-12,2000**

\* Unit milligram/cubic decimetre (milligram/Litre)

\*\* Unit microsiemen/cm. at 25 Degree celcius.

\*\*\* N.D: Non Detectable

Analysed and approved by:

*(Signature)*  
 (Mr. Chakhan Prayoonchart)  
 Chemical and Research Division  
 Determination Group Co., Ltd.


The above results are valids exclusively for tested/analysed sample as mentioned in this report.

#### 4.7. WATER SUPPLY SYSTEM

In order to obtain design standard of the water supply systems, the test wells were completed and the pumps were installed. For H-37 Ban Leang, the afridev hand pump was installed. The cylinder was setted to the depth of 35 m. The Tara hand pumps were installed at H-9B Ban May Phattana and H-3 2/2B Ban Nam Ngao, The cylinders were setted to the depth of 26 m and 8.80 m at H-9B and H-3 2/2B respectively. For H-3 1/2 Ban Nam Ngao, the hand pum Lao-99 was installed. The cylinder was setted to the depth of 7.70 m. The following table shows the type and depth of hand pump for test wells.

The reinforced concrete platform with drain were constructed around the well for sanitary protection at each wells. The types of concrete platform are show in figure attached.

D4-23



- ※Average Well Depth; 50m
- ※Average Drainage Length; 10m
- ※PVC Casing/Screen Dia.; 150 mm
- ※PVC Casing/Screen Length; 4m
- ※Final Drilling Dia.; 215 mm
- ※Grain Size of Gravel Packing; 2-5mm
- ※Hand Pump Riser Pipe; PVC
- ※Hand Pump Connecting Rod; Stainless Steel

PLATFORM FOR AFRIDEV HAND  
PUMP AT H+37 BAN LEANG

Drawing title  
Deep Well  
"Hand Pump Type"


Scale  
-:-  
Sheet No.


NEW, Ministry of Public Health



ການນຳໃຊ້ໂປມມືຊະນິດ ທາຣາ

# Borehole System Tara Hand Pump






ຮູບແທ່ນກັນເປື້ອນສຳລັບໂປມມີໂຍກທຸກຊະນິດ


**PLATFORM FOR TARA HAND PUMP**

# TARA HAND PUMP INSTALLATION AND PLATFORM

ການຕິຕັ້ງໂປມມືໂຍກຊະນິດ ທາລາພ້ອມດ້ວຍເທແທ່ນ  
ກັນເປື້ອນແລະເທຮ່ອງກັນລະບາຍນ້ຳເສງ




# PLATFORM FOR HAND DUG WELL WHICH INSTALLED H.PUMP LAO-99



ລະບົບການຕິດຕັ້ງ ປຸ່ມມືລາວ-99A

System assembly of Hand Pump LAO-99A For Dug Well



#### 4.8. CONCLUSIONS

The work was conducted for this study included well constructions, pumping test, water quality analysis and water supply system were summarized and show in figure attached.


# HAND DUG WELL CONSTRUCTION

**DRILLING WORK FOR THE STUDY ON RURAL WATER SUPPLY AND SANITATION IMPROVEMENT IN NORTH-WEST REGION, LAO P.D.R.**

CLIENT : MINISTRY OF HEALTH, LAO P.D.R.  
 CONSULTANT : JAPAN TECHNO CO., LTD.  
 CONTRACTOR : SIAM TONE CO., LTD.

WELL NO. H-3 1/2  
 LOCATION BAN. Nam Ngao  
 PROVINCE: Bokeo

DEPTH (m)	LITHOLOGY	
	COLUMN	DESCRIPTION
1	x x x x x x x x	Silt, pale brown
2	- - - - - - - -	Silty Clay, orangish brown, yellowish brown mottled
3	- - - - - - - -	
4	- - - - - - - -	
5	- - - - - - - -	Sandy Clay, light orangish brown, fine to medium grain
6	- - - - - - - -	
7	. . . . . . . . . . . . . . . .	Sand, light orangish brown, fine grain
8	. . . . . . . . . . . . . . . .	
9		
10		



WATER QUALITY	
pH	6.10
EC	170
Colour	0
Odour	Odourless
Taste	Tasteless
Turbidity	0.3 NTU
Ca	16 mg/l
Mg	5.9 mg/l
Na	9.05 mg/l
K	1.57 mg/l
Fe	0 mg/l
Mn	0 mg/l
Cu	0 mg/l
Zn	0.2 mg/l
NH4	0.98 mg/l
SiO <sub>2</sub>	19 mg/l
CO <sub>3</sub>	0 mg/l
HCO <sub>3</sub>	69 mg/l
CO <sub>2</sub>	87 mg/l
Cl	1.6 mg/l
SO <sub>4</sub>	2 mg/l
NO <sub>2</sub>	0 mg/l
NO <sub>3</sub>	10 mg/l
F	0 mg/l
B	0.08 mg/l
CaCo <sub>3</sub> (Total)	64 mg/l
CaCo <sub>3</sub> (Per.)	6 mg/l
TDS	100 mg/l
Coliform	7
As	< 0.001 mg/l
Ba	0 mg/l
Cr <sup>6+</sup>	0.01 mg/l
Cd	< 0.001 mg/l
Pb	0 mg/l
Se	< 0.002 mg/l
Hg	< 0.0005 mg/l
Al	0.01 mg/l
CN	< 0.002 mg/l

DIGGING	
DATE OF STARTED :	28 / 12 / 1999
DATE OF COMPLETED :	20/12/2000
DIG DIAMETER (m)	1.20
DIG DEPTH (m)	8.00

CASING INSTALLATION	
DATE :	25/1/2000
CASING TYPE :	Concrete Casing dia. 1m
WELL DEPTH (m) :	8.00 m
GRAVEL PACK :	FROM 8.00 m TO 8.00 m, VOLUME 682 l
BACK FILLING :	FROM 6.00 m TO 0.50 m, VOLUME 2,249 l
CEMENT SEALING :	FROM 0.50 m TO 0.00 m, VOLUME 344 l

PUMPING TEST	
DATE :	8/2/2000
S.W.L (m) :	6.65
TRANSMISSIVITY (T) :	46.584 m <sup>2</sup> /day
HYDRAULIC GRADIENT (K) :	23.311 m/day
SPECIFIC CAPACITY (Sc) :	

WELL DEVELOPMENT	
DATE :	7/2/2000
METHOD :	Continue Pumping
PERIOD :	5 Hr.

PLATFORM CONSTRUCTION	
DATE :	21-22/2/2000
TYPE :	4.00 x 4.00 with Drain 3 m

HANDPUMP INSTALLATION	
DATE :	25/2/2000
TYPE :	LAO-99
DEPTH :	7.70 m

file: hdwch-w

# HAND DUG WELL CONSTRUCTION

<b>DRILLING WORK FOR THE STUDY ON RURAL WATER SUPPLY AND SANITATION IMPROVEMENT IN NORTH-WEST REGION, LAO P.D.R.</b>		CLIENT : MINISTRY OF HEALTH, LAO P.D.R. CONSULTANT : JAPAN TECHNO CO., LTD. CONTRACTOR : SIAM TONE CO., LTD.	WELL NO. H-3 2/2B LOCATION BAN. Nam Ngao PROVINCE: Bokeo																																																																												
DEPTH	LITHOLOGY	WELL CONSTRUCTION																																																																													
(m)	COLUMN DESCRIPTION																																																																														
1	Silty Clay, brown, with organic matter																																																																														
2	Clay, orangish brown																																																																														
3																																																																															
4																																																																															
5																																																																															
6	Silty Sand, light orangish brown, fine grain																																																																														
7	Silt, light grayish brown																																																																														
8	Weathered Mudstone, grayish brown, weak																																																																														
9	Weathered Mudstone, light grayish brown and yellowish brown mottled, weak																																																																														
10																																																																															
<b>DIGGING</b> DATE OF STARTED : 21/1/2000 DATE OF COMPLETED : 13/2/2000 DIG DIAMETER (m) : 1.20 DIG DEPTH (m) : 9.00 <b>WELL DEVELOPMENT</b> DATE : 7/2/2000 METHOD : Continue Pumping PERIOD : 5 Hr.		<b>CASING INSTALLATION</b> DATE : 15-19/2/2000 CASING TYPE : Concrete Casing dia. 1m WELL DEPTH (m) : 9.00 GRAVEL PACK : FROM 9.00 m TO 6.00 m, VOLUME 1,038 l BACK FILLING : FROM 6.00 m TO 0.50 m, VOLUME 1,903 l CEMENT SEALING : FROM 0.50 m TO 0.00 m, VOLUME 344 l <b>PLATFORM CONSTRUCTION</b> DATE : 24-26/2/2000 TYPE : 1.70 x 1.50 with Drain 4 m																																																																													
		<b>PUMPING TEST</b> DATE : 9/2/2000 S.W.L (m) : 6.41 TRANSMISSIVITY (T) : 13.709 m <sup>2</sup> /day HYDRAULIC GRADIENT (K): 4.569 m/day SPECIFIC CAPACITY (Sc):																																																																													
		<b>HANDPUMP INSTALLATION</b> DATE : 27/2/2000 TYPE : Tara Hand Pump DEPTH : 8.80 m																																																																													
		<table style="width: 100%; border-collapse: collapse;"> <tr><td style="width: 20%;">pH</td><td style="width: 80%;">6.31</td></tr> <tr><td>EC</td><td>248 Us/cm</td></tr> <tr><td>Colour</td><td>35</td></tr> <tr><td>Odour</td><td>Odor</td></tr> <tr><td>Taste</td><td>Silty Taste</td></tr> <tr><td>Turbidity</td><td>50 NTU</td></tr> <tr><td>Ca</td><td>27 mg/l</td></tr> <tr><td>Mg</td><td>4.9 mg/l</td></tr> <tr><td>Na</td><td>11 mg/l</td></tr> <tr><td>K</td><td>6.7 mg/l</td></tr> <tr><td>Fe</td><td>0.7 mg/l</td></tr> <tr><td>Mn</td><td>0 mg/l</td></tr> <tr><td>Cu</td><td>0.02 mg/l</td></tr> <tr><td>Zn</td><td>0.3 mg/l</td></tr> <tr><td>NH<sub>4</sub></td><td>1.1 mg/l</td></tr> <tr><td>SiO<sub>2</sub></td><td>19 mg/l</td></tr> <tr><td>CO<sub>3</sub></td><td>0 mg/l</td></tr> <tr><td>HCO<sub>3</sub></td><td>82 mg/l</td></tr> <tr><td>CO<sub>2</sub></td><td>64 mg/l</td></tr> <tr><td>Cl</td><td>14 mg/l</td></tr> <tr><td>SO<sub>4</sub></td><td>12 mg/l</td></tr> <tr><td>NO<sub>2</sub></td><td>0.076 mg/l</td></tr> <tr><td>NO<sub>3</sub></td><td>26 mg/l</td></tr> <tr><td>F</td><td>0.1 mg/l</td></tr> <tr><td>B</td><td>0.05 mg/l</td></tr> <tr><td>CaCo<sub>3</sub> (Total)</td><td>88 mg/l</td></tr> <tr><td>CaCo<sub>3</sub> (Per.)</td><td>21 mg/l</td></tr> <tr><td>TDS</td><td>162 mg/l</td></tr> <tr><td>Colliform</td><td>6</td></tr> <tr><td>As</td><td>&lt; 0.001 mg/l</td></tr> <tr><td>Ba</td><td>0 mg/l</td></tr> <tr><td>Cr<sup>6+</sup></td><td>0 mg/l</td></tr> <tr><td>Cd</td><td>&lt; 0.001 mg/l</td></tr> <tr><td>Pb</td><td>0 mg/l</td></tr> <tr><td>Se</td><td>&lt; 0.002 mg/l</td></tr> <tr><td>Hg</td><td>&lt; 0.0005 mg/l</td></tr> <tr><td>Al</td><td>0 mg/l</td></tr> <tr><td>CN</td><td>&lt; 0.002 mg/l</td></tr> </table>		pH	6.31	EC	248 Us/cm	Colour	35	Odour	Odor	Taste	Silty Taste	Turbidity	50 NTU	Ca	27 mg/l	Mg	4.9 mg/l	Na	11 mg/l	K	6.7 mg/l	Fe	0.7 mg/l	Mn	0 mg/l	Cu	0.02 mg/l	Zn	0.3 mg/l	NH <sub>4</sub>	1.1 mg/l	SiO <sub>2</sub>	19 mg/l	CO <sub>3</sub>	0 mg/l	HCO <sub>3</sub>	82 mg/l	CO <sub>2</sub>	64 mg/l	Cl	14 mg/l	SO <sub>4</sub>	12 mg/l	NO <sub>2</sub>	0.076 mg/l	NO <sub>3</sub>	26 mg/l	F	0.1 mg/l	B	0.05 mg/l	CaCo <sub>3</sub> (Total)	88 mg/l	CaCo <sub>3</sub> (Per.)	21 mg/l	TDS	162 mg/l	Colliform	6	As	< 0.001 mg/l	Ba	0 mg/l	Cr <sup>6+</sup>	0 mg/l	Cd	< 0.001 mg/l	Pb	0 mg/l	Se	< 0.002 mg/l	Hg	< 0.0005 mg/l	Al	0 mg/l	CN	< 0.002 mg/l
pH	6.31																																																																														
EC	248 Us/cm																																																																														
Colour	35																																																																														
Odour	Odor																																																																														
Taste	Silty Taste																																																																														
Turbidity	50 NTU																																																																														
Ca	27 mg/l																																																																														
Mg	4.9 mg/l																																																																														
Na	11 mg/l																																																																														
K	6.7 mg/l																																																																														
Fe	0.7 mg/l																																																																														
Mn	0 mg/l																																																																														
Cu	0.02 mg/l																																																																														
Zn	0.3 mg/l																																																																														
NH <sub>4</sub>	1.1 mg/l																																																																														
SiO <sub>2</sub>	19 mg/l																																																																														
CO <sub>3</sub>	0 mg/l																																																																														
HCO <sub>3</sub>	82 mg/l																																																																														
CO <sub>2</sub>	64 mg/l																																																																														
Cl	14 mg/l																																																																														
SO <sub>4</sub>	12 mg/l																																																																														
NO <sub>2</sub>	0.076 mg/l																																																																														
NO <sub>3</sub>	26 mg/l																																																																														
F	0.1 mg/l																																																																														
B	0.05 mg/l																																																																														
CaCo <sub>3</sub> (Total)	88 mg/l																																																																														
CaCo <sub>3</sub> (Per.)	21 mg/l																																																																														
TDS	162 mg/l																																																																														
Colliform	6																																																																														
As	< 0.001 mg/l																																																																														
Ba	0 mg/l																																																																														
Cr <sup>6+</sup>	0 mg/l																																																																														
Cd	< 0.001 mg/l																																																																														
Pb	0 mg/l																																																																														
Se	< 0.002 mg/l																																																																														
Hg	< 0.0005 mg/l																																																																														
Al	0 mg/l																																																																														
CN	< 0.002 mg/l																																																																														



## WELL CONSTRUCTION

**DRILLING WORK FOR THE STUDY ON RURAL WATER SUPPLY AND SANITATION IMPROVEMENT IN NORTH-WEST REGION, LAO P.D.R.**

CLIENT : MINISTRY OF HEALTH, LAO P.D.R.

WELL NO. H-98

CONSULTANT : JAPAN TECHNO CO., LTD.

LOCATION BAN. May Phattana

CONTRACTOR : SIAM TONE CO., LTD.

PROVINCE Bokuo

DEPTH (m)	COLLUMEN	LITHOLOGY DESCRIPTION	GEOPHYSICAL LOGGING		DRILL RATE (m/hr)	WELL CONSTRUCTION	DEPTH (m)
			SP (mV)	RESISTIVITY (ohm-m)			
1		Silty Clay, light yellowish brown					1
2							2
3		Sand, brown, fine to medium grain					3
4							4
5		Weathered tuff, reddish brown, weak					5
6							6
7							7
8							8
9							9
10		Tuff, reddish brown, quartz mottled, moderately weak					10
11							11
12							12
13							13
14							14
15							15
16							16
17							17
18							18
19							19
20							20
21							21
22							22
23							23
24							24
25							25
26							26
27							27
28							28
29							29
30		Tuff, reddish brown, quartz mottled, hard					30
31							31
32							32
33							33
34							34
35		Tuff, reddish brown, quartz mottled, moderately hard					35
36							36
37							37
38							38
39							39
40							40
41		Tuff, reddish brown, quartz mottled, very hard					41
42							42
43							43
44							44
45							45
46							46
47							47
48							48
49							49
50							50
51							51
52							52
53							53
54							54
55							55
56							56
57							57
58							58
59							59
60							60
61							61
62							62
63							63
64							64
65							65

<b>DRILLING</b> DATE OF STARTED : 16/2/2000 DATE OF COMPLETED : 24/9/2000 RIG TYPE : Top-900 SURFACE CASING DIA. 250 mm DEPTH 8.00 m DRILL METHOD Rotary DRILL DIAMETER (mm) 216 DRILL DEPTH (m) 47.00	<b>CASING INSTALLATION</b> DATE : 26/2/2000 CASING TYPE : PVC Pipe dia. 150 mm Grade 13.5 bars CASING : 8 pcs x 3.95 = 31.60 m SCREEN : 4 pcs x 3.95 = 15.80 m TOTAL LENGTH : 47.40 m BALANCE : 2.00 m WELL DEPTH : 45.40 m GRAVEL PACK : FROM 16.80 m TO 10.75 m VOLUME 510 BENTONITE SEAL : FROM 10.75 m TO 9.75 m VOLUME 15 BACK FILLING : FROM 9.75 m TO 3.00 m VOLUME 140 CEMENT SEALING : FROM 3.00 m TO 0.90 m VOLUME 34 SCREEN POSITION (m) : 16.75-24.65 28.80-32.55 36.50-40.45	<b>PUMPING TEST</b> DATE : 27-28/2/2000 SWL (m) : 1.50 TRANSMISSIBILITY (T) : 1.64 m <sup>2</sup> /day HYDRAULIC GRADIENT (H) : 0.104 m/day SPECIFIC CAPACITY (SC) : 2.87 m <sup>3</sup> /day/m OPTIMUM DISCHARGE : 14.40 m <sup>3</sup> /day <b>PLATFORM CONSTRUCTION</b> DATE : 29/2/2000 TYPE : 1.70 x 1.50 with Drain 4.00 m <b>HAND PUMP INSTALLATION</b> DATE : 1/3/2000 TYPE : Tare Hand Pump DEPTH : 26.00 m	<b>WATER QUALITY</b> pH : 7.05 EC : 637 Us/cm Color : 35 Odor : Odor Taste : Slightly Taste Turbidity : 10 NTU Ca : 106 mg/l Mg : 14 mg/l Na : 20 mg/l K : 2.4 mg/l Fe : 0.09 mg/l Mn : 0.00 mg/l Cu : 0.02 mg/l Zn : 0.1 mg/l NH4 : 1.0 mg/l SO4 : 53 mg/l CO3 : 0 mg/l HCO3 : 280 mg/l CO2 : 41 mg/l Cl : 1.2 mg/l SO : 145 mg/l NO3 : 0 mg/l NO2 : 0.4 mg/l F : 0.2 mg/l B : 0 mg/l CaCo3 (Temp) : 329 mg/l CaCo3 (Pw) : 86 mg/l TDS : 486 mg/l Coliform : 15
---	---	---	---


Re: Well H-98

**WELL CONSTRUCTION**

**DRILLING WORK FOR THE STUDY ON RURAL WATER SUPPLY AND SANITATION IMPROVEMENT IN NORTH-WEST REGION, LAO P.D.R.**

CLIENT : MINISTRY OF HEALTH, LAO P.D.R.  
 CONSULTANT : JAPAN TECHNO CO., LTD.  
 CONTRACTOR : SIAM TONE CO., LTD.

WELL NO. H-37  
 LOCATION BAN, Leang  
 PROVINCE Bokeo




<b>DRILLING</b> DATE OF STARTED: 18/1/2000 DATE OF COMPLETED: 25/1/2000 RIG TYPE: Top-500 SURFACE CASING DIA. 250 mm DEPTH 11.00 m DRILL METHOD: Rotary DRILL DIAMETER (mm): 216 DRILL DEPTH (m): 80.00	<b>CASING INSTALLATION</b> DATE: 28/1/2000 CASING TYPE: PVC Pipe dia. 150 mm. Grade 13.5 bars CASING: 9 pcs x 3.95 m = 35.55 m SCREEN: 5 pcs x 3.95 m = 19.75 m TOTAL LENGTH: 55.30 m BALANCE: 0.30 m WELL DEPTH: 55.00 m GRAVEL PACK: FROM 55.00 m TO 17.40 m, VOLUME 780 l BENTONITE SEAL: FROM 17.40 m TO 16.40 m, VOLUME 15 l BACK FILLING: FROM 16.40 m TO 3.00 m, VOLUME 378 l CEMENT SEALING: FROM 3.00 m TO 0.00 m, VOLUME 344 l SCREEN POSITION (m): 23.40-31.30 35.25-43.15 47.10-51.05	<b>PUMPING TEST</b> DATE: 4-5/2/2000 S.W.L (m): 7.50 TRANSMISSIVITY (T): 0.128 m <sup>2</sup> /day HYDRAULIC GRADIENT (K): 0.0089 m/day SPECIFIC CAPACITY (Sc): 0.813 m <sup>3</sup> /day/m OPTIMUM DISCHARGE: 0.01 m <sup>3</sup> /day <b>PLATFORM CONSTRUCTION</b> DATE: 1/3/2000 TYPE: 1.50 x 2.00 with Oriran 10 m <b>SCREENING INSTALLATION</b> DATE: 2/3/2000 TYPE: Afloat Hand Pump DEPTH: 35.00 m	<b>WATER QUALITY</b> pH: 7.08 EC: 360 Us/cm Colour: 50 Odour: Odor Taste: Slightly Taste Turbidity: 15 NTU Ca: 35 mg/l Mg: 41 mg/l Na: 16 mg/l K: 7.1 mg/l Fe: 1.1 mg/l Mn: 0 mg/l Cu: 0.02 mg/l Zn: 0.1 mg/l NH4: 1.3 mg/l SiO <sub>2</sub> : 13 mg/l CO <sub>2</sub> : 0 mg/l HCO <sub>3</sub> : 135 mg/l CO: 18 mg/l Cl: 6.0 mg/l SO <sub>4</sub> : 186 mg/l NO <sub>2</sub> : 0.007 mg/l NO <sub>3</sub> : 0.4 mg/l F: 0.2 mg/l B: 0 mg/l CaCo <sub>3</sub> (Total): 258 mg/l CaCo <sub>3</sub> (Part): 148 mg/l TDS: 373 mg/l Coliform: 15
--	---	--	--

APPENDIX A

RESISTIVITY SURVEY DATA AND ANALYSIS

**SKETCH VILLAGE MAP  
FOR RESISTIVITY SURVEY**

BAN : NAM NGAO (DUG WELL)  
DISTRICT : HUI SAI  
PROVINCE : BO KAEW



D4-35

JICA (Japan International Cooperation Agency)  
 Nam Se-At (National Center for Environmental Health and Water Supply)  
 Rural Water Supply and Sanitation Improvement

**PROJECT:**  
 Phase II: Model Study-Groundwater Development

### RESISTIVITY DATA

MISSION NO. : NSA-R1  
 LOCATION : BAN NAM GNAO, HEOUXAY DISTRICT,  
 BORKEAW PROVINCE, LAO P.D.R.  
 DATE OF SURVEY : 23/11/1999  
 DATE OF REPORT : 30/11/1999

### HEAD OFFICE

5/15 MOO 6 (KM. 15)  
 BANGNA-TRAD ROAD  
 BANGPLEE, BANGCHALONG  
 SAMUTPRAKARN 10540  
 TEL. 3125281-300 FAX. (66-2) 3125304

### SIAM TONE CO.,LTD.



OYO-INSTRUMENTS  
 MODEL-2115


### BANGPAKONG FACTORY

700/47 BANGPAKONG  
 INDUSTRIAL, PARK 2  
 CHONBURI 20000  
 TEL. (038) 213-073-7  
 FAX. (038) 213-078

### WENNER CONFIGURATION

NO.	a(m.)	F (m.)	C (m.)	2πa (u)	mV	mA	RESISTANCE (ohm.)	RESISTIVITY (ohm.m.)
1	1	0.5	1.50	6.283	3,116.00	49.90	62.445	392.341
2	2	1.0	3.00	12.570	2,317.00	49.90	46.433	583.661
3	3	1.5	4.50	18.850	1,210.00	49.90	24.248	457.084
4	5	2.5	7.50	31.420	474.00	49.90	9.499	298.459
5	10	5.0	15.00	62.850	150.00	49.90	3.006	188.928
6	15	7.5	22.50	94.280	6.36	49.90	0.127	12.016
7	20	10.0	30.00	125.710	1.51	49.90	0.030	3.804
8	25	12.5	37.50	157.140				
9	30	15.0	45.00	188.570				
10	40	20.0	60.00	251.420				
11	50	25.0	75.00	314.280				
12	60	30.0	90.00	376.990				
13	70	35.0	105.00	439.990				
14	80	40.0	120.00	502.850				
15	90	45.0	135.00	565.710				
16	100	50.0	150.00	628.570				
17								
18								
19								
20								

### GEOPHYSICAL SURVEY




D4-36

### RESISTIVITY DATA

MISSION NO. : NSA-R2  
 LOCATION : BAN NAM GNAO, HEOUXAY DISTRICT,  
 BORKEAW PROVINCE, LAO P.D.R.  
 DATE OF SURVEY : 23/11/1999  
 DATE OF REPORT : 30/11/1999

HEAD OFFICE  
 5/15 MOO 6 (KM. 15)  
 BANGNA-TRAD ROAD  
 BANGPLEE, BANGCHALONG  
 SAMUTPRAKARN 10540  
 TEL. 3125281-300 FAX. (66-2) 3125304


SIAM TONE CO.,LTD.  
  
 OYO-INSTRUMENTS  
 MODEL-2115

BANGPAKONG FACTORY  
 700/47 BANGPAKONG  
 INDUSTRIAL, PARK 2  
 CHONBURI 20000  
 TEL. (038) 213-073-7  
 FAX. (038) 213-078

### WENNER CONFIGURATION

NO.	a(m.)	F (m.)	C (m.)	$2\pi a$ (u)	mV	mA	RESISTANCE (ohm.)	RESISTIVITY (ohm.m.)
1	1	0.5	1.50	6.283	3,428.00	49.90	68.697	431.626
2	2	1.0	3.00	12.570	1,121.00	49.90	22.465	282.384
3	3	1.5	4.50	18.850	708.00	49.90	14.188	267.451
4	5	2.5	7.50	31.420	362.00	49.90	7.255	227.937
5	10	5.0	15.00	62.850	171.00	49.90	3.427	215.378
6	15	7.5	22.50	94.280	106.00	49.90	2.124	200.274
7	20	10.0	30.00	125.710	82.20	49.90	1.647	207.081
8	25	12.5	37.50	157.140				
9	30	15.0	45.00	188.570				
10	40	20.0	60.00	251.420				
11	50	25.0	75.00	314.280				
12	60	30.0	90.00	376.990				
13	70	35.0	105.00	439.990				
14	80	40.0	120.00	502.850				
15	90	45.0	135.00	565.710				
16	100	50.0	150.00	628.570				
17								
18								
19								
20								

### GEOPHYSICAL SURVEY




D4-37

### RESISTIVITY DATA

MISSION NO. : NSA-R3  
 LOCATION : BAN NAM GNAO, HEOUXAY DISTRICT,  
 BORKEAW PROVINCE, LAO P.D.R.  
 DATE OF SURVEY : 23/11/1999  
 DATE OF REPORT : 30/11/1999

HEAD OFFICE  
 5/15 MOO 6 (KM. 15)  
 BANGNA-TRAD ROAD  
 BANGPLEE, BANGCHALONG  
 SAMUTPRAKARN 10540  
 TEL. 3125281-300 FAX. (66-2) 3125304


SIAM TONE CO.,LTD.  
  
 OYO-INSTRUMENTS  
 MODEL-2115

BANGPAKONG FACTORY  
 700/47 BANGPAKONG  
 INDUSTRIAL, PARK 2  
 CHONBURI 20000  
 TEL. (038) 213-073-7  
 FAX. (038) 213-078

### WENNER CONFIGURATION

NO.	a(m.)	F(m.)	C(m.)	$2\pi a$ ( $\mu$ )	mV	mA	RESISTANCE (ohm.)	RESISTIVITY (ohm.m.)
1	1	0.5	1.50	6.283	2,137.00	49.90	42.826	269.074
2	2	1.0	3.00	12.570	647.00	49.90	12.966	162.982
3	3	1.5	4.50	18.850	391.00	49.90	7.836	147.702
4	5	2.5	7.50	31.420	190.00	49.90	3.808	119.635
5	10	5.0	15.00	62.850	162.00	49.90	3.246	204.042
6	15	7.5	22.50	94.280	67.50	49.90	1.353	127.533
7	20	10.0	30.00	125.710	38.80	49.90	0.778	97.746
8	25	12.5	37.50	157.140				
9	30	15.0	45.00	188.570				
10	40	20.0	60.00	251.420				
11	50	25.0	75.00	314.280				
12	60	30.0	90.00	376.990				
13	70	35.0	105.00	439.990				
14	80	40.0	120.00	502.850				
15	90	45.0	135.00	565.710				
16	100	50.0	150.00	628.570				
17								
18								
19								
20								

### GEOPHYSICAL SURVEY



### RESISTIVITY DATA

MISSION NO. : NSA-R4  
 LOCATION : BAN NAM GNAO, HEOUXAY DISTRICT,  
 BORKEAW PROVINCE, LAO P.D.R.  
 DATE OF SURVEY : 23/11/1999  
 DATE OF REPORT : 30/11/1999

### HEAD OFFICE

5/15 MOO 6 (KM. 15)  
 BANGNA-TRAD ROAD  
 BANGPLEE, BANGCHALONG  
 SAMUTPRAKARN 10540  
 TEL. 3125281-300 FAX. (66-2) 3125304

### SIAM TONE CO.,LTD.



OYO-INSTRUMENTS  
 MODEL-2115


### BANGPAKONG FACTORY

700/47 BANGPAKONG  
 INDUSTRIAL, PARK 2  
 CHONBURI 20000  
 TEL. (038) 213-073-7  
 FAX. (038) 213-078

### WENNER CONFIGURATION

NO.	a(m.)	F (m.)	C (m.)	$2\pi a$ (u)	mV	mA	RESISTANCE (ohm.)	RESISTIVITY (ohm.m.)
1	1	0.5	1.50	6.283	778.00	4.99	155.912	979.594
2	2	1.0	3.00	12.570	287.00	4.99	57.515	722.964
3	3	1.5	4.50	18.850	89.20	4.99	17.876	336.958
4	5	2.5	7.50	31.420	32.00	4.99	6.413	201.491
5	10	5.0	15.00	62.850	10.30	4.99	2.064	129.730
6	15	7.5	22.50	94.280	2.50	4.99	0.501	47.234
7	20	10.0	30.00	125.710	24.00	49.90	0.481	60.462
8	25	12.5	37.50	157.140	1.97	49.90	0.039	6.204
9	30	15.0	45.00	188.570				
10	40	20.0	60.00	251.420				
11	50	25.0	75.00	314.280				
12	60	30.0	90.00	376.990				
13	70	35.0	105.00	439.990				
14	80	40.0	120.00	502.850				
15	90	45.0	135.00	565.710				
16	100	50.0	150.00	628.570				
17								
18								
19								
20								

### GEOPHYSICAL SURVEY




D4-39



### RESISTIVITY DATA

MISSION NO. : NSA-R5  
 LOCATION : BAN NAM GNAO, HEUXAY DISTRICT,  
 BORKEAW PROVINCE, LAO P.D.R.  
 DATE OF SURVEY : 23/11/1999  
 DATE OF REPORT : 30/11/1999

HEAD OFFICE  
 5/15 MOO 6 (KM. 15)  
 BANGNA-TRAD ROAD  
 BANGPLEE, BANGCHALONG  
 SAMUTPRAKARN 10540  
 TEL. 3125281-300 FAX. (66-2) 3125304

SIAM TONE CO.,LTD.  
  
 OYO-INSTRUMENTS  
 MODEL-2115


BANGPAKONG FACTORY  
 700/47 BANGPAKONG  
 INDUSTRIAL, PARK 2  
 CHONBURJ 20000  
 TEL. (038) 213-073-7  
 FAX. (038) 213-078

### WENNER CONFIGURATION

NO.	a(m.)	F(m.)	C(m.)	2πa (u)	mV	mA	RESISTANCE (ohm.)	RESISTIVITY (ohm.m.)
1	1	0.5	1.50	6.283	1,237.00	49.90	24.790	155.753
2	2	1.0	3.00	12.570	448.00	49.90	8.978	112.853
3	3	1.5	4.50	18.850	266.00	49.90	5.331	100.483
4	5	2.5	7.50	31.420	207.00	49.90	4.148	130.339
5	10	5.0	15.00	62.850	102.00	49.90	2.044	128.471
6	15	7.5	22.50	94.280	68.00	49.90	1.363	128.478
7	20	10.0	30.00	125.710	35.20	49.90	0.705	88.677
8	25	12.5	37.50	157.140				
9	30	15.0	45.00	188.570				
10	40	20.0	60.00	251.420				
11	50	25.0	75.00	314.280				
12	60	30.0	90.00	376.990				
13	70	35.0	105.00	439.990				
14	80	40.0	120.00	502.850				
15	90	45.0	135.00	565.710				
16	100	50.0	150.00	628.570				
17								
18								
19								
20								

D4-40

### GEOPHYSICAL SURVEY



### RESISTIVITY DATA

MISSION NO. : NSA-R6  
 LOCATION : BAN NAM GNAO, HEOUXAY DISTRICT,  
 BORKEAW PROVINCE, LAO P.D.R.  
 DATE OF SURVEY : 23/11/1999  
 DATE OF REPORT : 30/11/1999

### HEAD OFFICE

5/15 MOO 6 (KM. 15)  
 BANGNA-TRAD ROAD  
 BANGPLEE, BANGCHALONG  
 SAMUTPRAKARN 10540  
 TEL. 3125281-300 FAX. (66-2) 3125304

### SIAM TONE CO.,LTD.



OYO-INSTRUMENTS  
 MODEL-2115


### BANGPAKONG FACTORY

700/47 BANGPAKONG  
 INDUSTRIAL, PARK 2  
 CHONBURI 20000  
 TEL. (038) 213-073-7  
 FAX. (038) 213-078

### WENNER CONFIGURATION

NO.	a(m.)	F(m.)	C(m.)	$2\pi a$ (u)	mV	mA	RESISTANCE (ohm.)	RESISTIVITY (ohm.m.)
1	1	0.5	1.50	6.283	1,892.00	40.10	47.182	296.445
2	2	1.0	3.00	12.570	650.00	49.90	13.026	163.737
3	3	1.5	4.50	18.850	556.00	49.90	11.142	210.032
4	5	2.5	7.50	31.420	418.00	49.90	8.377	263.198
5	10	5.0	15.00	62.850	246.00	49.90	4.930	309.842
6	15	7.5	22.50	94.280	74.60	49.90	1.495	140.948
7	20	10.0	30.00	125.710	36.80	49.90	0.737	92.708
8	25	12.5	37.50	157.140				
9	30	15.0	45.00	188.570				
10	40	20.0	60.00	251.420				
11	50	25.0	75.00	314.280				
12	60	30.0	90.00	376.990				
13	70	35.0	105.00	439.990				
14	80	40.0	120.00	502.850				
15	90	45.0	135.00	565.710				
16	100	50.0	150.00	628.570				
17								
18								
19								
20								

### GEOPHYSICAL SURVEY



D4-41

DATA SET: NSA-R1

CLIENT: JICA  
 LOCATION: BAN NAM GNAO  
 COUNTY: NAM GNAO, LAO P.D.R.  
 PROJECT: Water Supply & Sanitation  
 ELEVATION: 0.00  
 SOUNDING COORDINATES: X: 0.0000 Y: 0.0000

DATE: NOV., 1999  
 SOUNDING: -  
 AZIMUTH: -  
 EQUIPMENT: -

Wenner Configuration

FITTING ERROR: 39.121 PERCENT

L #	RESISTIVITY (ohm-m)	THICKNESS (meters)	ELEVATION (meters)	LONG. COND. (Siemens)	TRANS. RES. (Ohm-m <sup>2</sup> )
			0.0		
1	253.7	0.610	-0.610	0.00241	154.9
2	1034.9	0.974	-1.58	9.414E-04	1008.3
3	997.6	1.15	-2.74	0.00116	1155.3
4	100.6	0.740	-3.48	0.00735	74.50
5	6.91	1.13	-4.61	0.164	7.85
6	0.250				

ALL PARAMETERS ARE FREE

No.	SPACING (m)	RHO-A (ohm-m)		DIFFERENCE (percent)
		DATA	SYNTHETIC	
1	1.00	392.3	399.6	-1.85
2	2.00	583.6	523.3	10.33
3	3.00	457.0	525.2	-14.90
4	5.00	298.4	383.9	-28.63
5	10.00	188.9	95.53	49.43
6	15.00	12.01	18.77	-56.27
7	20.00	3.80	3.57	6.07

PARAMETER RESOLUTION MATRIX:  
 "F" INDICATES FIXED PARAMETER

P 1	0.88					
P 2	-0.14	0.67				
P 3	0.02	0.31	0.35			
P 4	0.01	0.00	0.01	0.00		
P 5	0.00	0.00	0.00	0.00	0.00	
P 6	0.02	0.01	-0.06	-0.01	0.00	0.77

\*

OYO CORPORATION

\*

T 1	-0.21	-0.28	0.11	0.01	0.00	0.03	0.64						
T 2	0.06	0.03	0.18	0.03	0.00	0.01	0.09	0.32					
T 3	0.08	0.00	0.19	0.03	0.01	0.04	0.11	0.38	0.46				
T 4	0.00	-0.02	0.00	0.00	0.00	0.00	0.00	0.04	0.05	0.01			
T 5	0.00	-0.01	-0.01	0.00	0.00	0.02	0.00	0.01	0.01	0.00	0.00	0.00	0.00
	P 1	P 2	P 3	P 4	P 5	P 6	T 1	T 2	T 3	T 4	T 5		



\*

OYO CORPORATION

\*

D4-44

# NSA-R1



DATA SET: NSA-R2

CLIENT: JICA  
 LOCATION: NAM GNAO SCHOOL  
 COUNTY: HEOUXAY, LAO. P.D.R.  
 PROJECT: WATER SUPPLY & SANITATION  
 ELEVATION: 0.00  
 SOUNDING COORDINATES: X: 0.0000 Y: 0.0000

DATE: NOV., 1999  
 SOUNDING: -  
 AZIMUTH: -  
 EQUIPMENT: -

Wenner Configuration

FITTING ERROR: 2.344 PERCENT

L #	RESISTIVITY (ohm-m)	THICKNESS (meters)	ELEVATION (meters)	LONG. COND. (Siemens)	TRANS. RES. (Ohm-m <sup>2</sup> )
			0.0		
1	783.2	0.500	-0.500	6.392E-04	392.1
2	253.0	0.909	-1.40	0.00359	230.1
3	253.1	2.75	-4.16	0.0108	697.8
4	184.6	10.08	-14.25	0.0546	1861.8
5	228.1				

ALL PARAMETERS ARE FREE

No.	SPACING (m)	RHO-A (ohm-m)		DIFFERENCE (percent)
		DATA	SYNTHETIC	
1	1.00	431.6	430.2	0.322
2	2.00	282.3	287.5	-1.82
3	3.00	267.4	258.1	3.48
4	5.00	227.9	235.3	-3.25
5	10.00	215.3	209.9	2.53
6	15.00	200.2	204.4	-2.09
7	20.00	207.0	205.6	0.687

PARAMETER RESOLUTION MATRIX:  
 "F" INDICATES FIXED PARAMETER

P 1	0.38						
P 2	0.02	0.50					
P 3	-0.08	0.20	0.76				
P 4	0.02	-0.07	0.11	0.79			
P 5	-0.01	0.04	-0.08	0.25	0.36		
T 1	0.35	0.29	-0.02	0.01	0.00	0.50	
T 2	0.00	-0.01	0.04	0.03	-0.02	0.00	0.00

\*

OYO CORPORATION

\*



T 3	0.01	-0.03	0.11	0.08	-0.05	0.00	0.01	0.04	
T 4	0.00	-0.01	0.02	-0.07	-0.07	0.00	0.00	0.01	0.02
	P 1	P 2	P 3	P 4	P 5	T 1	T 2	T 3	T 4

\*

OYO CORPORATION

\*

# NSA-R2



D4-47



DATA SET: NSA-R3

CLIENT: JICA  
 LOCATION: VILLANGE BAN NAM GNAO  
 COUNTY: BORKEAW, LAO. P.D.R.  
 PROJECT: WATER SUPPLY & SANITATION  
 ELEVATION: 0.00  
 SOUNDING COORDINATES: X: 0.0000 Y: 0.0000

DATE: NOV., 1999  
 SOUNDING: -  
 AZIMUTH: -  
 EQUIPMENT: -

Wenner Configuration

FITTING ERROR: 12.544 PERCENT

L #	RESISTIVITY (ohm-m)	THICKNESS (meters)	ELEVATION (meters)	LONG. COND. (Siemens)	TRANS. RES. (Ohm-m <sup>2</sup> )
			0.0		
1	321.9	1.13	-1.13	0.00353	365.7
2	55.92	1.79	-2.92	0.0320	100.1
3	1746.6	1.30	-4.22	7.449E-04	2272.6
4	89.48	1.22	-5.44	0.0136	109.2
5	0.0961				

ALL PARAMETERS ARE FREE

No.	SPACING (m)	RHO-A (ohm-m)		DIFFERENCE (percent)
		DATA	SYNTHETIC	
1	1.00	269.0	266.2	1.05
2	2.00	162.9	170.7	-4.76
3	3.00	147.7	135.3	8.34
4	5.00	119.6	143.4	-19.89
5	10.00	204.0	163.2	19.97
6	15.00	127.5	136.6	-7.11
7	20.00	97.74	100.1	-2.42

PARAMETER RESOLUTION MATRIX:  
 "F" INDICATES FIXED PARAMETER

P 1	1.00						
P 2	-0.01	0.78					
P 3	0.00	0.00	0.50				
P 4	0.00	0.00	0.03	0.00			
P 5	0.00	0.00	0.00	0.00	0.00		
T 1	0.00	0.05	0.00	0.00	0.00	0.99	
T 2	-0.01	-0.23	0.00	0.00	0.00	0.05	0.76

\*

OYO CORPORATION

\*

T 3	0.00	0.00	0.50	0.03	0.00	0.00	0.01	0.50		
T 4	0.00	0.00	0.03	0.00	0.00	0.00	0.00	0.03	0.00	
	P 1	P 2	P 3	P 4	P 5	T 1	T 2	T 3	T 4	



\*

OYO CORPORATION

\*

D4-50

# NSA-R3



## DATA SET: NSA-R4

CLIENT: JICA DATE: NOV., 1999  
 LOCATION: BAN NAM GNAO SOUNDING: -  
 COUNTY: BORKEAW, LAO. P.D.R. AZIMUTH: -  
 PROJECT: WATER SUPPLY & SANITATION EQUIPMENT: -  
 ELEVATION: 0.00  
 SOUNDING COORDINATES: X: 0.0000 Y: 0.0000

## Wenner Configuration

FITTING ERROR: 16.019 PERCENT

L #	RESISTIVITY (ohm-m)	THICKNESS (meters)	ELEVATION (meters)	LONG. COND. (Siemens)	TRANS. RES. (Ohm-m <sup>2</sup> )
			0.0		
1	1267.8	1.26	-1.26	9.990E-04	1605.9
2	88.06	0.730	-1.99	0.00829	64.32
3	358.2	2.94	-4.93	0.00821	1053.7
4	10.07	4.70	-9.64	0.467	47.36
5	63.03	3.50	-13.14	0.0555	220.6
6	575.2				

ALL PARAMETERS ARE FREE

No.	SPACING (m)	RHO-A (ohm-m)		DIFFERENCE (percent)
		DATA	SYNTHETIC	
1	1.00	979.5	1056.6	-7.86
2	2.00	722.9	616.5	14.71
3	3.00	336.9	369.8	-9.76
4	5.00	201.4	215.6	-7.02
5	10.00	129.7	103.3	20.34
6	15.00	47.23	61.61	-30.45
7	20.00	60.46	54.95	9.09
8	25.00	62.03	60.38	2.66

PARAMETER RESOLUTION MATRIX:  
"F" INDICATES FIXED PARAMETER

P 1 0.99  
 P 2 -0.01 0.42  
 P 3 0.00 0.15 0.61  
 P 4 0.00 -0.01 0.00 0.48  
 P 5 0.00 0.00 0.00 0.06 0.01

\*

OYO CORPORATION

\*

P 6	0.00	0.01	0.01	0.05	0.01	0.02							
T 1	0.01	0.05	-0.01	0.00	0.00	0.00	0.98						
T 2	0.01	-0.41	-0.14	0.02	0.00	-0.01	0.00	0.40					
T 3	-0.01	-0.16	0.42	0.02	0.00	-0.02	0.02	0.19	0.54				
T 4	0.00	-0.01	0.01	-0.49	-0.06	-0.05	0.00	0.01	0.01	0.50			
T 5	0.00	0.00	0.00	-0.06	-0.01	-0.01	0.00	0.00	0.00	0.06	0.0		
	P 1	P 2	P 3	P 4	P 5	P 6	T 1	T 2	T 3	T 4			



\*

OYO CORPORATION

\*

D4-53

# NSA-R4



## DATA SET: NSA-R5

CLIENT: JICA  
 LOCATION: BAN NAM GNAO  
 COUNTY: BORKEAW, LAO. P.D.R.  
 PROJECT: WATER SUPPLY & SANITATION  
 ELEVATION: 0.00  
 SOUNDING COORDINATES: X: 0.0000 Y: 0.0000

DATE: NOV., 1999  
 SOUNDING: -  
 AZIMUTH: -  
 EQUIPMENT: -

## Wenner Configuration

FITTING ERROR: 5.157 PERCENT

L #	RESISTIVITY (ohm-m)	THICKNESS (meters)	ELEVATION (meters)	LONG. COND. (Siemens)	TRANS. RES. (Ohm-m <sup>2</sup> )
			0.0		
1	195.8	0.992	-0.992	0.00507	194.3
2	36.32	0.860	-1.85	0.0236	31.24
3	224.3	9.73	-11.58	0.0434	2184.6
4	2.79				

ALL PARAMETERS ARE FREE

No.	SPACING (m)	RHO-A (ohm-m)		DIFFERENCE (percent)
		DATA	SYNTHETIC	
1	1.00	155.7	156.6	-0.554
2	2.00	112.8	110.2	2.29
3	3.00	100.4	105.0	-4.58
4	5.00	130.3	123.3	5.38
5	10.00	128.4	138.5	-7.81
6	15.00	128.4	119.1	7.22
7	20.00	88.67	91.19	-2.84

## PARAMETER RESOLUTION MATRIX:

"F" INDICATES FIXED PARAMETER

```



P 1  1.00
P 2 -0.01  0.54
P 3  0.00 -0.02  0.99
P 4  0.00  0.01 -0.02  0.03
T 1  0.00  0.07  0.00  0.00  0.99
T 2 -0.01 -0.49 -0.02 -0.01  0.08  0.48
T 3  0.00  0.02  0.01  0.05  0.00  0.03  0.99
      P 1   P 2   P 3   P 4   T 1   T 2   T 3
  
```

\*

OYO CORPORATION

\*

# NSA-R5



D4-65



DATA SET: NSA-R6

CLIENT: JICA DATE: NOV., 1999  
 LOCATION: BAN NAM GNAO SOUNDING: -  
 COUNTY: BORKEAW, LAO. P.D.R. AZIMUTH: -  
 PROJECT: WATER SUPPLY & SANITATION EQUIPMENT: -  
 ELEVATION: 0.00  
 SOUNDING COORDINATES: X: 0.0000 Y: 0.0000

Wenner Configuration

FITTING ERROR: 10.632 PERCENT

L #	RESISTIVITY (ohm-m)	THICKNESS (meters)	ELEVATION (meters)	LONG. COND. (Siemens)	TRANS. RES. (Ohm-m <sup>2</sup> )
			0.0		
1	7706.8	0.279	-0.279	3.622E-05	2151.2
2	22.09	0.288	-0.567	0.0130	6.36
3	282.7	0.351	-0.918	0.00124	99.30
4	2325.0	1.23	-2.15	5.324E-04	2878.1
5	69.80	1.12	-3.27	0.0160	78.18
6	0.285				

ALL PARAMETERS ARE FREE

No.	SPACING (m)	RHO-A (ohm-m)		DIFFERENCE (percent)
		DATA	SYNTHETIC	
1	1.00	296.4	296.3	0.0355
2	2.00	163.7	166.0	-1.40
3	3.00	210.0	218.6	-4.11
4	5.00	263.1	274.5	-4.31
5	10.00	309.8	247.3	20.16
6	15.00	140.9	160.6	-13.97
7	20.00	92.70	92.35	0.375

PARAMETER RESOLUTION MATRIX:  
 "F" INDICATES FIXED PARAMETER

P 1	0.05					
P 2	0.00	0.49				
P 3	0.00	0.05	0.00			
P 4	0.00	0.00	0.02	0.50		
P 5	0.00	0.00	0.00	0.01	0.00	
P 6	0.00	0.00	0.00	0.00	0.00	0.00

\*

OYO CORPORATION

\*



T 1	0.19	0.00	0.00	0.00	0.00	0.00	0.00	0.96				
T 2	0.00	-0.49	-0.05	-0.02	0.00	0.00	0.00	0.00	0.50			
T 3	0.00	-0.05	0.00	0.02	0.00	0.00	0.00	0.00	0.05	0.00		
T 4	0.00	-0.02	0.02	0.50	0.01	0.00	0.00	0.00	0.00	0.02	0.50	
T 5	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0
	P 1	P 2	P 3	P 4	P 5	P 6	T 1	T 2	T 3	T 4		

\*

OYO CORPORATION

\*


# NSA-R6



D4-58

**SKETCH VILLAGE MAP  
FOR RESISTIVITY SURVEY**

BAN : MAY PHATTANA (DEEP WELL)  
DISTRICT : HUI SAI  
PROVINCE : BO KAEW



JICA (Japan International Cooperation Agency)  
Nam Se-At (National Center for Environmental Health and Water Supply)  
Rural Water Supply and Sanitation Improvement

PROJECT:  
Phase II: Model Study-Groundwater Development

### RESISTIVITY DATA

MISSION NO. : BPP-R2  
 LOCATION : BAN MAY NATTANA, HEOUXAY DISTRICT,  
 BORKEAW PROVINCE, LAO P.D.R.  
 DATE OF SURVEY : 23/11/1999  
 DATE OF REPORT : 30/11/1999

HEAD OFFICE  
 5/15 MOO 6 (KM. 15)  
 BANGNA-TRAD ROAD  
 BANGPLEE, BANGCHALONG  
 SAMUTPRAKARN 10540  
 TEL. 3125281-300 FAX. (66-2) 3125304


SIAM TONE CO.,LTD.  
  
 OYO-INSTRUMENTS  
 MODEL-2115

BANGPAKONG FACTORY  
 700/47 BANGPAKONG  
 INDUSTRIAL, PARK 2  
 CHONBURI 20000  
 TEL. (038) 213-073-7  
 FAX. (038) 213-078

### WENNER CONFIGURATION

NO.	a(m.)	F(m.)	C(m.)	$2\pi a$ (u)	mV	mA	RESISTANCE (ohm.)	RESISTIVITY (ohm.m.)
1	1	0.5	1.50	6.283	1,035.00	49.90	20.741	130.319
2	2	1.0	3.00	12.570	482.00	49.90	9.659	121.418
3	3	1.5	4.50	18.850	319.00	49.90	6.393	120.504
4	5	2.5	7.50	31.420	160.00	49.90	3.206	100.745
5	10	5.0	15.00	62.850	78.00	49.90	1.563	98.242
6	15	7.5	22.50	94.280	48.20	49.90	0.966	91.068
7	20	10.0	30.00	125.710	99.00	49.90	1.984	249.405
8	25	12.5	37.50	157.140	33.20	49.90	0.665	104.550
9	30	15.0	45.00	188.570	22.50	49.90	0.451	85.027
10	40	20.0	60.00	251.420	16.30	49.90	0.327	82.127
11	50	25.0	75.00	314.280	3.00	9.99	0.300	94.378
12	60	30.0	90.00	376.990	2.60	9.98	0.261	98.214
13	70	35.0	105.00	439.990	3.48	9.98	0.349	153.423
14	80	40.0	120.00	502.850	2.05	9.98	0.205	103.291
15	90	45.0	135.00	565.710	1.84	9.98	0.184	104.299
16	100	50.0	150.00	628.570	1.87	9.98	0.187	117.778
17								
18								
19								
20								

### GEOPHYSICAL SURVEY




D4-60

### RESISTIVITY DATA

MISSION NO. : BPP-R1  
 LOCATION : BAN MAY PHITUMA, HEOUXAY DISTRICT,  
 BORKEAW PROVINCE, LAO P.D.R.  
 DATE OF SURVEY : 23/11/1999  
 DATE OF REPORT : 30/11/1999

HEAD OFFICE  
 5/15 MOO 6 (KM. 15)  
 BANGNA-TRAD ROAD  
 BANGPLEE, BANGCHALONG  
 SAMUTPRAKARN 10540  
 TEL. 3125281-300 FAX. (66-2) 3125304


SIAM TONE CO.,LTD.  
  
 OYO-INSTRUMENTS  
 MODEL-2115

BANGPAKONG FACTORY  
 700/47 BANGPAKONG  
 INDUSTRIAL, PARK 2  
 CHONBURI 20000  
 TEL. (038) 213-073-7  
 FAX. (038) 213-078

### WENNER CONFIGURATION

NO.	a(m.)	F(m.)	C(m.)	$2\pi a$ (u)	mV	mA	RESISTANCE (ohm.)	RESISTIVITY (ohm.m.)
1	1	0.5	1.50	6.283	614.00	50.00	12.280	77.155
2	2	1.0	3.00	12.570	274.00	50.00	5.480	68.884
3	3	1.5	4.50	18.850	197.00	50.00	3.940	74.269
4	5	2.5	7.50	31.420	148.00	50.00	2.960	93.003
5	10	5.0	15.00	62.850	81.80	50.00	1.636	102.823
6	15	7.5	22.50	94.280	13.80	9.59	1.439	135.669
7	20	10.0	30.00	125.710	17.10	10.00	1.710	214.964
8	25	12.5	37.50	157.140	5.91	10.00	0.591	92.870
9	30	15.0	45.00	188.570	4.13	10.00	0.413	77.879
10	40	20.0	60.00	251.420	10.00	10.00	1.000	251.420
11	50	25.0	75.00	314.280	5.85	10.00	0.585	183.854
12	60	30.0	90.00	376.990	2.83	10.00	0.283	106.688
13	70	35.0	105.00	439.990	2.53	10.00	0.253	111.317
14	80	40.0	120.00	502.850	1.20	9.99	0.120	60.402
15	90	45.0	135.00	565.710	1.90	9.99	0.190	107.592
16	100	50.0	150.00	628.570	1.74	9.99	0.174	109.481
17								
18								
19								
20								

### GEOPHYSICAL SURVEY



D4-61

### RESISTIVITY DATA

MISSION NO.	: BPP-R3
LOCATION	: BAN MAY MATIAMA, HEOUXAY DISTRICT, BORKEAW PROVINCE, LAO P.D.R.
DATE OF SURVEY	: 23/11/1999
DATE OF REPORT	: 30/11/1999

### HEAD OFFICE

5/15 MOO 6 (KM. 15)  
BANGNA-TRAD ROAD  
BANGPLEE, BANGCHALONG  
SAMUTPRAKARN 10540  
TEL. 3125281-300 FAX. (66-2) 3125304

### SIAM TONE CO.,LTD.



OYO-INSTRUMENTS  
MODEL-2115


### BANGPAKONG FACTORY

700/47 BANGPAKONG  
INDUSTRIAL, PARK 2  
CHONBURI 20000  
TEL. (038) 213-073-7  
FAX. (038) 213-078

### WENNER CONFIGURATION

NO.	a(m.)	F (m.)	C (m.)	2xa (u)	mV	mA	RESISTANCE (ohm.)	RESISTIVITY (ohm.m.)
1	1	0.5	1.50	6.283	4,123.00	45.90	89.826	564.375
2	2	1.0	3.00	12.570	527.00	43.90	12.005	150.897
3	3	1.5	4.50	18.850	257.00	49.90	5.150	97.083
4	5	2.5	7.50	31.420	77.40	49.90	1.551	48.736
5	10	5.0	15.00	62.850	14.10	46.90	0.301	18.895
6	15	7.5	22.50	94.280	19.60	9.78	2.004	188.946
7	20	10.0	30.00	125.710	0.61	9.98	0.061	7.684
8	25	12.5	37.50	157.140	29.60	44.50	0.665	104.525
9	30	15.0	45.00	188.570	39.40	49.90	0.790	148.891
10	40	20.0	60.00	251.420	4.49	9.98	0.450	113.114
11	50	25.0	75.00	314.280	171.00	19.90	8.593	2700.597
12	60	30.0	90.00	376.990	70.90	49.90	1.421	535.643
13	70	35.0	105.00	439.990	5.90	47.90	0.123	54.195
14	80	40.0	120.00	502.850	57.60	9.98	5.772	2902.220
15	90	45.0	135.00	565.710	23.00	9.98	2.305	1303.740
16	100	50.0	150.00	628.570	5.42	9.24	0.587	368.707
17								
18								
19								
20								

### GEOPHYSICAL SURVEY



D4-62

### RESISTIVITY DATA

MISSION NO. : BPP-R4  
 LOCATION : BAN ~~PHU~~ PHATANA, HELOUXAY DISTRICT,  
 BORKEAW PROVINCE, LAO P.D.R.  
 DATE OF SURVEY : 23/11/1999  
 DATE OF REPORT : 30/11/1999

HEAD OFFICE  
 5/15 MOO 6 (KM. 15)  
 BANGNA-TRAD ROAD  
 BANGPLEE, BANGCHALONG  
 SAMUTPRAKARN 10540  
 TEL. 3125281-300 FAX. (66-2) 3125304


SIAM TONE CO.,LTD.  
  
 OYO-INSTRUMENTS  
 MODEL-2115

BANGPAKONG FACTORY  
 700/47 BANGPAKONG  
 INDUSTRIAL, PARK 2  
 CHONBURI 20000  
 TEL. (038) 213-073-7  
 FAX. (038) 213-078

### WENNER CONFIGURATION

NO.	a(m.)	F(m.)	C(m.)	2xa(u)	mV	mA	RESISTANCE (ohm.)	RESISTIVITY (ohm.m.)
1	1	0.5	1.50	6.283	2,639.00	19.90	132.613	833.208
2	2	1.0	3.00	12.570	833.00	19.90	41.859	526.171
3	3	1.5	4.50	18.850	839.00	19.90	42.161	794.731
4	5	2.5	7.50	31.420	437.00	19.90	21.960	689.977
5	10	5.0	15.00	62.850	85.80	19.90	4.312	270.981
6	15	7.5	22.50	94.280	45.50	19.90	2.286	215.565
7	20	10.0	30.00	125.710	25.10	19.90	1.261	158.559
8	25	12.5	37.50	157.140	15.30	19.90	0.769	120.816
9	30	15.0	45.00	188.570	13.90	19.90	0.698	131.715
10	40	20.0	60.00	251.420	9.22	19.90	0.463	116.487
11	50	25.0	75.00	314.280	7.38	19.90	0.371	116.552
12	60	30.0	90.00	376.990	6.53	19.90	0.328	123.706
13	70	35.0	105.00	439.990	5.63	19.90	0.283	124.480
14	80	40.0	120.00	502.850	5.08	19.90	0.255	128.366
15	90	45.0	135.00	565.710	8.64	19.90	0.434	245.615
16	100	50.0	150.00	628.570	4.36	19.90	0.219	137.717
17								
18								
19								
20								

### GEOPHYSICAL SURVEY



D4-63



## DATA SET: BPP-R1

CLIENT: JICA  
LOCATION: BAN MAY PHATTANA, HEOUXAY  
COUNTY: BORKEE, LAO P.D.R.  
PROJECT: WATER SUPPLY & SANITATION  
ELEVATION: 0.00  
SOUNDING COORDINATES: X: 0.0000 Y: 0.0000

DATE: NOV., 1999  
SOUNDING: -  
AZIMUTH: -  
EQUIPMENT: -

## Wenner Configuration

FITTING ERROR: 31.600 PERCENT

L #	RESISTIVITY (ohm-m)	THICKNESS (meters)	ELEVATION (meters)	LONG. COND. (Siemens)	TRANS. RES. (Ohm-m <sup>2</sup> )
			0.0		
1	70.67	3.45	-3.45	0.0489	244.4
2	144.9	8.70	-12.16	0.0600	1261.3
3	161.3	20.87	-33.03	0.129	3368.1
4	70.29	30.25	-63.29	0.430	2126.9
5	70.51	30.07	-93.36	0.426	2120.8
6	94.25				

ALL PARAMETERS ARE FREE

No.	SPACING (m)	RHO-A (ohm-m)		DIFFERENCE (percent)
		DATA	SYNTHETIC	
1	1.00	77.15	71.09	7.85
2	2.00	68.85	73.50	-6.74
3	3.00	74.36	78.02	-4.92
4	5.00	93.19	89.58	3.87
5	10.00	102.8	112.2	-9.20
6	15.00	130.4	124.0	4.91
7	20.00	215.2	129.6	39.76
8	25.00	92.87	131.4	-41.53
9	30.00	77.87	130.8	-68.02
10	40.00	153.3	125.7	17.99
11	50.00	183.8	118.6	35.44
12	60.00	106.3	111.7	-5.08
13	70.00	111.3	105.6	5.07
14	80.00	60.34	100.7	-67.00
15	90.00	108.6	96.98	10.71
16	100.0	109.3	94.13	13.92

\*

OYO CORPORATION

\*

## PARAMETER RESOLUTION MATRIX:



"F" INDICATES FIXED PARAMETER

P 1	0.93													
P 2	0.02	0.61												
P 3	-0.01	0.21	0.60											
P 4	0.01	-0.05	0.19	0.31										
P 5	0.00	-0.03	0.03	0.16	0.10									
P 6	0.00	-0.03	0.01	0.17	0.12	0.14								
T 1	-0.08	-0.28	0.05	0.03	0.01	0.00	0.28							
T 2	0.00	-0.05	0.06	0.09	0.04	0.03	0.02	0.03						
T 3	0.00	-0.02	0.25	0.21	0.08	0.07	0.04	0.07	0.18					
T 4	0.00	0.01	0.00	-0.03	-0.02	-0.02	0.00	-0.01	-0.01	0.00				
T 5	0.00	0.01	0.00	-0.03	-0.02	-0.02	0.00	-0.01	-0.01	0.00	0.00			
	P 1	P 2	P 3	P 4	P 5	P 6	T 1	T 2	T 3	T 4	T 5			

\* OYO CORPORATION \*

# BPP-R1

D4-66



## DATA SET: BPP-R2

CLIENT: JICA  
 LOCATION: BAN MAY PHATTANA, HEOUXAY  
 COUNTY: BORKEO, LAO P.D.R.  
 PROJECT: WATER SUPPLY & SANITATION  
 ELEVATION: 0.00  
 SOUNDING COORDINATES: X: 0.0000 Y: 0.0000

DATE: NOV., 1999  
 SOUNDING: -  
 AZIMUTH: -  
 EQUIPMENT: -

## Wenner Configuration

FITTING ERROR: 26.974 PERCENT

L #	RESISTIVITY (ohm-m)	THICKNESS (meters)	ELEVATION (meters)	LONG. COND. (Siemens)	TRANS. RES. (Ohm-m <sup>2</sup> )
			0.0		
1	136.3	1.99	-1.99	0.0146	272.6
2	74.16	4.31	-6.31	0.0582	320.3
3	255.6	8.36	-14.68	0.0327	2138.2
4	28.59	15.71	-30.39	0.549	449.3
5	370.5	27.59	-57.99	0.0744	10227.2
6	162.3				

ALL PARAMETERS ARE FREE

No.	SPACING (m)	RHO-A (ohm-m)		DIFFERENCE (percent)
		DATA	SYNTHETIC	
1	1.00	130.3	133.5	-2.47
2	2.00	121.4	123.1	-1.46
3	3.00	120.5	112.3	6.79
4	5.00	100.7	102.6	-1.91
5	10.00	98.24	112.5	-14.59
6	15.00	91.06	119.6	-31.36
7	20.00	249.4	117.8	52.76
8	25.00	104.5	112.2	-7.33
9	30.00	85.02	106.3	-25.05
10	40.00	82.12	98.70	-20.18
11	50.00	94.37	97.35	-3.15
12	60.00	98.21	100.1	-1.96
13	70.00	153.4	104.9	31.58
14	80.00	103.2	110.4	-6.96
15	90.00	104.2	115.9	-11.20
16	100.0	117.7	121.1	-2.84

\*

OYO CORPORATION

\*

## PARAMETER RESOLUTION MATRIX:

"F" INDICATES FIXED PARAMETER

P 1	0.99													
P 2	-0.01	0.83												
P 3	0.00	0.04	0.60											
P 4	0.00	0.01	0.04	0.50										
P 5	0.00	-0.01	0.01	0.07	0.15									
P 6	0.00	-0.02	0.02	-0.01	0.26	0.54								
T 1	0.02	0.18	-0.06	0.01	0.00	0.01	0.75							
T 2	-0.01	-0.26	-0.10	0.04	-0.04	-0.04	0.26	0.52						
T 3	0.00	-0.02	0.45	0.05	-0.05	-0.05	0.03	0.14	0.46					
T 4	0.00	0.00	0.02	-0.47	-0.10	-0.03	0.00	0.01	0.04	0.47				
T 5	0.00	-0.01	0.01	0.02	0.10	0.19	0.00	-0.02	-0.03	-0.04	0.00			
	P 1	P 2	P 3	P 4	P 5	P 6	T 1	T 2	T 3	T 4	T 5			



\*

OYO CORPORATION

\*

D4-69

# BPP-R2



## DATA SET: BPP-R3

CLIENT: JICA  
 LOCATION: BAN MAY PHATTANA, HEOUXAY  
 COUNTY: BORKEO, LAO P.D.R.  
 PROJECT: WATER SUPPLY & SANITATION  
 ELEVATION: 0.00  
 SOUNDING COORDINATES: X: 0.0000 Y: 0.0000

DATE: NOV., 1999  
 SOUNDING: -  
 AZIMUTH: -  
 EQUIPMENT: -

## Wenner Configuration

FITTING ERROR: 236.576 PERCENT

L #	RESISTIVITY (ohm-m)	THICKNESS (meters)	ELEVATION (meters)	LONG. COND. (Siemens)	TRANS. RES. (Ohm-m <sup>2</sup> )
			0.0		
1	640.3	1.07	-1.07	0.00168	687.3
2	29.33	7.37	-8.44	0.251	216.3
3	243.8	2.29	-10.74	0.00943	560.4
4	17951.5	8.10	-18.85	4.514E-04	145479.3
5	1.309E+06	185.2	-204.0	1.414E-04	2.425E+08
6	2114.3				

ALL PARAMETERS ARE FREE

No.	SPACING (m)	RHO-A (ohm-m)		DIFFERENCE (percent)
		DATA	SYNTHETIC	
1	1.00	564.3	471.0	16.53
2	2.00	150.8	195.3	-29.47
3	3.00	97.08	88.06	9.29
4	5.00	48.73	41.35	15.13
5	10.00	18.89	54.69	-189.4
6	15.00	188.9	79.39	57.97
7	20.00	7.68	105.4	-1272.6
8	25.00	104.5	131.7	-26.07
9	30.00	148.8	158.1	-6.19
10	40.00	113.1	210.7	-86.35
11	50.00	2700.5	263.5	90.24
12	60.00	535.6	316.1	40.97
13	70.00	54.19	368.8	-580.5
14	80.00	2902.2	421.5	85.47
15	90.00	1303.7	474.1	63.63
16	100.0	368.7	526.7	-42.86

\*

OYO CORPORATION

\*

## PARAMETER RESOLUTION MATRIX:

"F" INDICATES FIXED PARAMETER

P 1	1.00													
P 2	0.00	1.00												
P 3	0.00	0.00	0.00											
P 4	0.00	0.00	0.00	0.00										
P 5	0.00	0.00	0.00	0.00	0.00									
P 6	0.00	0.00	0.00	0.00	0.00	0.00								
T 1	0.00	0.00	0.00	0.00	0.00	0.00	1.00							
T 2	0.00	0.00	-0.03	0.00	0.00	0.00	0.00	1.00						
T 3	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.00					
T 4	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
T 5	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.0	
	P 1	P 2	P 3	P 4	P 5	P 6	T 1	T 2	T 3	T 4	T 5			

\*



OYO CORPORATION

\*



D4-72

# BPP-R3



## DATA SET: BPP-R4

CLIENT: JICA  
 LOCATION: BAN MAY PHATTANA, HEOUXAY  
 COUNTY: BORKEO, LAO P.D.R.  
 PROJECT: WATER SUPPLY & SANITATION  
 ELEVATION: 0.00  
 SOUNDING COORDINATES: X: 0.0000 Y: 0.0000

DATE: NOV., 1999  
 SOUNDING: -  
 AZIMUTH: -  
 EQUIPMENT: -

## Wenner Configuration

FITTING ERROR: 18.862 PERCENT

L #	RESISTIVITY (ohm-m)	THICKNESS (meters)	ELEVATION (meters)	LONG. COND. (Siemens)	TRANS. RES. (Ohm-m <sup>2</sup> )
			0.0		
1	721.3	1.10	-1.10	0.00153	795.6
2	792.7	3.52	-4.62	0.00445	2793.3
3	158.2	15.75	-20.38	0.0995	2494.6
4	55.57	25.89	-46.27	0.465	1438.9
5	476.7	37.87	-84.15	0.0794	18056.8
6	416.4				

ALL PARAMETERS ARE FREE

No.	SPACING (m)	RHO-A (ohm-m)		DIFFERENCE (percent)
		DATA	SYNTHETIC	
1	1.00	833.2	728.3	12.58
2	2.00	526.1	729.4	-38.63
3	3.00	794.7	700.3	11.87
4	5.00	689.9	583.9	15.36
5	10.00	270.9	316.8	-16.92
6	15.00	215.5	202.1	6.22
7	20.00	158.5	155.7	1.76
8	25.00	120.8	133.3	-10.39
9	30.00	131.7	121.2	7.97
10	40.00	116.4	112.4	3.49
11	50.00	116.5	115.0	1.33
12	60.00	123.7	123.1	0.464
13	70.00	124.4	133.6	-7.35
14	80.00	128.3	144.9	-12.88
15	90.00	245.6	156.1	36.42
16	100.0	137.7	167.0	-21.27

\*

OYO CORPORATION

\*

## PARAMETER RESOLUTION MATRIX:

"F" INDICATES FIXED PARAMETER

P 1	0.99													
P 2	0.01	0.99												
P 3	0.01	-0.01	0.93											
P 4	0.00	0.01	0.02	0.72										
P 5	0.00	0.00	0.03	0.04	0.12									
P 6	0.00	0.01	0.06	-0.07	0.18	0.37								
T 1	-0.01	0.00	-0.02	0.01	0.00	0.00	0.07							
T 2	-0.01	0.02	0.05	-0.02	-0.01	-0.03	0.23	0.90						
T 3	-0.01	0.02	0.12	0.17	-0.14	-0.15	0.00	-0.07	0.56					
T 4	0.00	0.00	0.00	-0.36	-0.16	-0.13	0.00	0.00	0.25	0.42				
T 5	0.00	0.00	0.01	0.00	0.03	0.05	0.00	0.00	-0.03	-0.02	0.			
	P 1	P 2	P 3	P 4	P 5	P 6	T 1	T 2	T 3	T 4				



\*

OYO CORPORATION

\*


# BPP-R4

D4-75



# SKETCH VILLAGE MAP FOR RESISTIVITY SURVEY

BAN : LEANG (DEEP WELL)  
DISTRICT : HUI-SAI  
PROVINCE : BO-KAEW



D4-76


JICA (Japan International Cooperation Agency)  
Nam Sa-At (National Center for Environmental Health and Water Supply)  
Rural Water Supply and Sanitation Improvement

PROJECT:  
Phase II: Model Study-Groundwater Development

### RESISTIVITY DATA

MISSION NO. : BL-RI  
 LOCATION : BAN LEANG, HEOUXAY DISTRICT,  
 BORKEAW PROVINCE, LAO P.D.R.  
 DATE OF SURVEY : 23/11/1999  
 DATE OF REPORT : 30/11/1999

HEAD OFFICE  
 5/15 MOO 6 (KM. 15)  
 BANGNA-TRAD ROAD  
 BANGPLEE, BANGCHALONG  
 SAMUTPRAKARN 10540  
 TEL. 3125281-300 FAX. (66-2) 3125304

SIAM TONE CO.,LTD.  
  
 OYO-INSTRUMENTS  
 MODEL-2115


BANGPAKONG FACTORY  
 700/47 BANGPAKONG  
 INDUSTRIAL, PARK 2  
 CHONBURI 20000  
 TEL. (038) 213-073-7  
 FAX. (038) 213-078

### WENNER CONFIGURATION

NO.	a(m.)	F(m.)	C(m.)	2xa(u)	mV	mA	RESISTANCE (ohm.)	RESISTIVITY (ohm.m.)
1	1	0.5	1.50	6.283	1,737.00	50.00	34.740	218.271
2	2	1.0	3.00	12.570	412.00	49.90	8.257	103.784
3	3	1.5	4.50	18.850	314.00	49.90	6.293	118.615
4	5	2.5	7.50	31.420	308.00	49.90	6.172	193.935
5	10	5.0	15.00	62.850	106.00	49.90	2.124	133.509
6	15	7.5	22.50	94.280	50.40	49.90	1.010	95.225
7	20	10.0	30.00	125.710	30.60	49.90	0.613	77.089
8	25	12.5	37.50	157.140	22.90	49.90	0.459	72.114
9	30	15.0	45.00	188.570	20.20	49.90	0.405	76.335
10	40	20.0	60.00	251.420	17.80	49.90	0.357	89.685
11	50	25.0	75.00	314.280	16.00	49.90	0.321	100.771
12	60	30.0	90.00	376.990	12.80	49.90	0.257	96.703
13	70	35.0	105.00	439.990	11.30	49.90	0.226	99.637
14	80	40.0	120.00	502.850	7.50	49.90	0.150	75.579
15	90	45.0	135.00	565.710	9.74	49.90	0.195	110.421
16	100	50.0	150.00	628.570	7.55	49.90	0.151	95.104
17								
18								
19								
20								

D4-77

### GEOPHYSICAL SURVEY



### RESISTIVITY DATA

MISSION NO.	: BL-R2
LOCATION	: BAN LEANG, HEOUXAY DISTRICT, BORKEAW PROVINCE, LAO P.D.R.
DATE OF SURVEY	: 23/11/1999
DATE OF REPORT	: 30/11/1999

### HEAD OFFICE

5/15 MOO 6 (KM. 15)  
BANGNA-TRAD ROAD  
BANGPLEE, BANGCHALONG  
SAMUTPRAKARN 10540  
TEL. 3125281-300 FAX. (66-2) 3125304

### SIAM TONE CO.,LTD.

**STC**  
OYO-INSTRUMENTS  
MODEL-2115


### BANGPAKONG FACTORY

700/47 BANGPAKONG  
INDUSTRIAL, PARK 2  
CHONBURI 20000  
TEL. (038) 213-073-7  
FAX. (038) 213-078

### WENNER CONFIGURATION

NO.	a(m.)	F(m.)	C(m.)	2πa (u)	mV	mA	RESISTANCE (ohm.)	RESISTIVITY (ohm.m.)
1	1	0.5	1.50	6.283	2,627.00	49.90	52.645	330.770
2	2	1.0	3.00	12.570	595.00	49.90	11.924	149.883
3	3	1.5	4.50	18.850	459.00	49.90	9.198	173.390
4	5	2.5	7.50	31.420	263.00	49.90	5.271	165.600
5	10	5.0	15.00	62.850	111.00	49.90	2.224	139.807
6	15	7.5	22.50	94.280	52.00	49.90	1.042	98.248
7	20	10.0	30.00	125.710	33.60	49.90	0.673	84.646
8	25	12.5	37.50	157.140	22.10	49.90	0.443	69.595
9	30	15.0	45.00	188.570	18.30	49.90	0.367	69.155
10	40	20.0	60.00	251.420	13.20	49.90	0.265	66.508
11	50	25.0	75.00	314.280	11.40	49.90	0.228	71.799
12	60	30.0	90.00	376.990	8.09	49.90	0.162	61.119
13	70	35.0	105.00	439.990	7.90	49.90	0.158	69.658
14	80	40.0	120.00	502.850	5.68	40.00	0.142	71.405
15	90	45.0	135.00	565.710	7.00	49.90	0.140	79.358
16	100	50.0	150.00	628.570	6.32	49.90	0.127	79.610
17								
18								
19								
20								

### GEOPHYSICAL SURVEY



D4-78

### RESISTIVITY DATA

MISSION NO. : BL-R3  
 LOCATION : BAN LEANG, HEOUXAY DISTRICT,  
 BORKEAW PROVINCE, LAO P.D.R.  
 DATE OF SURVEY : 23/11/1999  
 DATE OF REPORT : 30/11/1999

### HEAD OFFICE

5/15 MOO 6 (KM. 15)  
 BANGNA-TRAD ROAD  
 BANGPLEE, BANGCHALONG  
 SAMUTPRAKARN 10540  
 TEL. 3125281-300 FAX. (66-2) 3125304

### SIAM TONE CO.,LTD.

**STC**  
 OYO-INSTRUMENTS  
 MODEL-2115


### BANGPAKONG FACTORY

700/47 BANGPAKONG  
 INDUSTRIAL, PARK 2  
 CHONBURI 20000  
 TEL. (038) 213-073-7  
 FAX. (038) 213-078

### WENNER CONFIGURATION

NO.	a(m.)	F(m.)	C(m.)	2πa (u)	mV	mA	RESISTANCE (ohm.)	RESISTIVITY (ohm.m.)
1	1	0.5	1.50	6.283	1,012.00	49.90	20.281	127.423
2	2	1.0	3.00	12.570	386.00	49.90	7.735	97.235
3	3	1.5	4.50	18.850	381.00	49.90	7.635	143.925
4	5	2.5	7.50	31.420	247.00	49.90	4.950	155.526
5	10	5.0	15.00	62.850	126.00	49.90	2.525	158.699
6	15	7.5	22.50	94.280	69.40	49.90	1.391	131.123
7	20	10.0	30.00	125.710	38.00	49.90	0.762	95.731
8	25	12.5	37.50	157.140	27.50	49.90	0.551	86.600
9	30	15.0	45.00	188.570	19.30	49.90	0.387	72.934
10	40	20.0	60.00	251.420	13.20	48.00	0.275	69.141
11	50	25.0	75.00	314.280	12.10	49.90	0.242	76.208
12	60	30.0	90.00	376.990	10.80	49.90	0.216	81.593
13	70	35.0	105.00	439.990	9.13	46.20	0.198	86.950
14	80	40.0	120.00	502.850	8.84	49.90	0.177	89.082
15	90	45.0	135.00	565.710	8.98	49.90	0.180	101.805
16	100	50.0	150.00	628.570	7.58	47.90	0.158	99.469
17								
18								
19								
20								

### GEOPHYSICAL SURVEY



D4-79



### RESISTIVITY DATA

MISSION NO. : BL-R4  
 LOCATION : BAN LEANG, HEOUXAY DISTRICT,  
 BORKEAW PROVINCE, LAO P.D.R.  
 DATE OF SURVEY : 23/11/1999  
 DATE OF REPORT : 30/11/1999

### HEAD OFFICE

S/15 MOO 6 (KM. 15)  
 BANGNA-TRAD ROAD  
 BANGPLEE, BANGCHALONG  
 SAMUTPRAKARN 10540  
 TEL. 3125281-300 FAX. (66-2) 3125304

### SIAM TONE CO.,LTD.



OYO-INSTRUMENTS  
 MODEL-2115


### BANGPAKONG FACTORY

700/47 BANGPAKONG  
 INDUSTRIAL, PARK 2  
 CHONBURI 20000  
 TEL. (038) 213-073-7  
 FAX. (038) 213-078

### WENNER CONFIGURATION

NO.	a(m.)	F (m.)	C (m.)	2xa (u)	mV	mA	RESISTANCE (ohm.)	RESISTIVITY (ohm.m.)
1	1	0.5	1.50	6.283	4,464.00	49.90	89.459	562.070
2	2	1.0	3.00	12.570	1,915.00	49.90	38.377	482.396
3	3	1.5	4.50	18.850	1,444.00	49.90	28.938	545.479
4	5	2.5	7.50	31.420	507.00	49.90	10.160	319.237
5	10	5.0	15.00	62.850	131.00	43.80	2.991	187.976
6	15	7.5	22.50	94.280	78.20	49.90	1.567	147.749
7	20	10.0	30.00	125.710	39.60	43.80	0.904	113.656
8	25	12.5	37.50	157.140	29.80	49.90	0.597	93.843
9	30	15.0	45.00	188.570	22.90	49.90	0.459	86.538
10	40	20.0	60.00	251.420	16.60	49.90	0.333	83.639
11	50	25.0	75.00	314.280	14.20	49.90	0.285	89.434
12	60	30.0	90.00	376.990	11.60	49.90	0.232	87.637
13	70	35.0	105.00	439.990	9.46	49.90	0.190	83.413
14	80	40.0	120.00	502.850	8.18	49.90	0.164	82.431
15	90	45.0	135.00	565.710	7.97	49.90	0.160	90.355
16	100	50.0	150.00	628.570	8.49	49.90	0.170	106.945
17								
18								
19								
20								

### GEOPHYSICAL SURVEY




D4-80

### RESISTIVITY DATA

MISSION NO. : BL-R5  
 LOCATION : BAN LEANG, HEOUXAY DISTRICT,  
 BORKEAW PROVINCE, LAO P.D.R.  
 DATE OF SURVEY : 23/11/1999  
 DATE OF REPORT : 30/11/1999

HEAD OFFICE  
 5/15 MOO 6 (KM. 15)  
 BANGNA-TRAD ROAD  
 BANGPLEE, BANGCHALONG  
 SAMUTPRAKARN 10540  
 TEL. 3125281-300 FAX. (66-2) 3125304


SIAM TONE CO.,LTD.  
  
 OYO-INSTRUMENTS  
 MODEL-2115

BANGPAKONG FACTORY  
 700/47 BANGPAKONG  
 INDUSTRIAL, PARK 2  
 CHONBURI 20000  
 TEL. (038) 213-073-7  
 FAX. (038) 213-078

### WENNER CONFIGURATION

NO.	a(m.)	F(m.)	C(m.)	2xa (u)	mV	mA	RESISTANCE (ohm.)	RESISTIVITY (ohm.m.)
1	1	0.5	1.50	6.283	1,309.00	49.90	26.232	164.819
2	2	1.0	3.00	12.570	1,197.00	49.90	23.988	301.529
3	3	1.5	4.50	18.850	735.00	49.90	14.729	277.650
4	5	2.5	7.50	31.420	451.00	49.90	9.038	283.976
5	10	5.0	15.00	62.850	399.00	49.90	7.996	502.548
6	15	7.5	22.50	94.280	595.00	49.90	11.924	1124.180
7	20	10.0	30.00	125.710	957.00	49.90	19.178	2410.911
8	25	12.5	37.50	157.140	680.00	49.90	13.627	2141.387
9	30	15.0	45.00	188.570	159.00	49.90	3.186	600.854
10	40	20.0	60.00	251.420	250.00	49.90	5.010	1259.619
11	50	25.0	75.00	314.280	37.20	49.90	0.745	234.293
12	60	30.0	90.00	376.990	30.60	49.90	0.613	231.180
13	70	35.0	105.00	439.990	21.10	49.90	0.423	186.048
14	80	40.0	120.00	502.850	12.30	49.90	0.246	123.949
15	90	45.0	135.00	565.710	21.40	49.90	0.429	242.609
16	100	50.0	150.00	628.570	49.20	49.90	0.986	619.752
17								
18								
19								
20								

### GEOPHYSICAL SURVEY



D4-81

DATA SET: BL-R1

CLIENT: JICA	DATE: NOV., 1999
LOCATION: BAN LAENG, HEOUXAY	SOUNDING: -
COUNTY: BOR KEO, LAO P.D.R.	AZIMUTH: -
PROJECT: WATER SUPPLY & SANITATION	EQUIPMENT: -
ELEVATION: 0.00	
SOUNDING COORDINATES: X: 0.0000	Y: 0.0000

Wenner Configuration

FITTING ERROR: 19.336 PERCENT

L #	RESISTIVITY (ohm-m)	THICKNESS (meters)	ELEVATION (meters)	LONG. COND. (Siemens)	TRANS. RES. (Ohm-m <sup>2</sup> )
			0.0		
1	145.1	3.92	-3.92	0.0270	569.2
2	832.6	1.11	-5.03	0.00134	931.5
3	8.78	3.46	-8.50	0.394	30.46
4	414.0	18.14	-26.65	0.0438	7513.8
5	63.65	21.77	-48.43	0.342	1386.2
6	37.40				

ALL PARAMETERS ARE FREE

No.	SPACING (m)	RHO-A (ohm-m)		DIFFERENCE (percent)
		DATA	SYNTHETIC	
1	1.00	218.2	145.7	33.24
2	2.00	103.7	148.5	-43.12
3	3.00	118.6	152.8	-28.88
4	5.00	193.8	157.3	18.85
5	10.00	133.5	129.2	3.19
6	15.00	95.22	95.83	-0.644
7	20.00	77.08	79.53	-3.16
8	25.00	72.11	75.43	-4.60
9	30.00	76.33	77.19	-1.12
10	40.00	89.68	85.27	4.91
11	50.00	100.7	92.16	8.54
12	60.00	96.70	96.21	0.502
13	70.00	99.63	97.81	1.82
14	80.00	75.57	97.58	-29.11
15	90.00	110.4	96.04	13.01
16	100.0	95.10	93.64	1.52

\*

OYO CORPORATION

\*

PARAMETER RESOLUTION MATRIX:  
 "F" INDICATES FIXED PARAMETER

P 1	1.00													
P 2	0.00	0.51												
P 3	0.00	0.01	0.50											
P 4	0.00	0.00	0.00	0.51										
P 5	0.00	0.00	-0.01	0.10	0.03									
P 6	0.00	0.00	0.00	0.00	0.06	0.73								
T 1	0.00	-0.02	0.01	-0.01	0.00	0.01	0.99							
T 2	0.00	0.50	0.01	0.00	0.00	0.00	0.02	0.49						
T 3	0.00	0.01	-0.49	-0.04	0.01	0.02	0.01	0.01	0.51					
T 4	0.00	0.00	-0.03	0.47	0.10	0.07	0.00	0.00	0.00	0.45				
T 5	0.00	0.00	0.00	0.03	0.01	0.08	0.00	0.00	0.00	0.03	0			
	P 1	P 2	P 3	P 4	P 5	P 6	T 1	T 2	T 3	T 4				



\*

OYO CORPORATION

\*

D4-84

# BL-R1



## DATA SET: BL-R2

CLIENT: JICA DATE: NOV., 1999  
 LOCATION: BAN LAENG, HEOUXAY SOUNDING: -  
 COUNTY: BOR KEAW, LAO, P.D.R. AZIMUTH: -  
 PROJECT: WATER SUPPLY & SANITATION EQUIPMENT: -  
 ELEVATION: 0.00  
 SOUNDING COORDINATES: X: 0.0000 Y: 0.0000

## Wenner Configuration

FITTING ERROR: 5.409 PERCENT

L #	RESISTIVITY (ohm-m)	THICKNESS (meters)	ELEVATION (meters)	LONG. COND. (Siemens)	TRANS. RES. (Ohm-m <sup>2</sup> )
			0.0		
1	977936.6	0.138	-0.138	1.415E-07	135289.1
2	167.1	9.15	-9.29	0.0548	1530.5
3	46.02	11.69	-20.99	0.254	538.3
4	65.05	82.70	-103.6	1.27	5380.3
5	89.37	18.70	-122.4	0.209	1672.0
6	410.8				

ALL PARAMETERS ARE FREE

No.	SPACING (m)	RHO-A (ohm-m)		DIFFERENCE (percent)
		DATA	SYNTHETIC	
1	1.00	330.7	333.3	-0.770
2	2.00	149.8	166.4	-11.07
3	3.00	173.3	166.4	4.01
4	5.00	165.6	159.2	3.83
5	10.00	139.8	130.6	6.55
6	15.00	98.24	102.2	-4.07
7	20.00	84.64	83.65	1.17
8	25.00	69.59	73.30	-5.32
9	30.00	69.15	68.08	1.54
10	40.00	66.50	64.98	2.29
11	50.00	71.79	65.58	8.64
12	60.00	61.11	67.51	-10.46
13	70.00	69.65	70.02	-0.532
14	80.00	71.40	72.91	-2.11
15	90.00	79.35	76.11	4.08
16	100.0	79.61	79.62	-0.0153

\*

OYO CORPORATION

\*

## PARAMETER RESOLUTION MATRIX:

"F" INDICATES FIXED PARAMETER

P 1	0.04																			
P 2	0.00	0.99																		
P 3	0.00	-0.01	0.67																	
P 4	0.00	0.00	0.13	0.89																
P 5	0.00	0.00	-0.03	0.03	0.02															
P 6	0.00	0.00	-0.04	0.03	0.03	0.04														
T 1	0.09	0.00	0.00	0.00	0.00	0.00	0.99													
T 2	0.00	0.01	0.16	-0.06	0.01	0.02	0.00	0.91												
T 3	0.00	0.00	-0.15	-0.12	0.00	0.00	0.00	0.03	0.06											
T 4	0.00	0.00	0.18	-0.17	-0.10	-0.14	0.00	-0.07	-0.02	0.52										
T 5	0.00	0.00	0.03	-0.03	-0.02	-0.02	0.00	-0.01	0.00	0.08	0.									
	P 1	P 2	P 3	P 4	P 5	P 6	T 1	T 2	T 3	T 4										



\*

OYO CORPORATION

\*

D4-87

BL-R2





DATA SET: BL-R3

CLIENT: JICA  
 LOCATION: BAN LAENG, HEOUXAY  
 COUNTY: BOR KEAW, LAO, P.D.R.  
 PROJECT: WATER SUPPLY & SANITATION  
 ELEVATION: 0.00  
 SOUNDING COORDINATES: X: 0.0000 Y: 0.0000

DATE: NOV., 1999  
 SOUNDING: -  
 AZIMUTH: -  
 EQUIPMENT: -

Wenner Configuration

FITTING ERROR: 7.131 PERCENT

L #	RESISTIVITY (ohm-m)	THICKNESS (meters)	ELEVATION (meters)	LONG. COND. (Siemens)	TRANS. RES. (Ohm-m <sup>2</sup> )
			0.0		
1	111.7	3.39	-3.39	0.0303	379.5
2	1137.5	1.40	-4.80	0.00124	1600.7
3	25.57	14.34	-19.14	0.561	366.8
4	162.4	30.34	-49.49	0.186	4927.9
5	155.0	21.30	-70.80	0.137	3303.3
6	153.4	21.58	-92.38	0.140	3312.8
7	127.8				

ALL PARAMETERS ARE FREE

No.	SPACING (m)	RHO-A (ohm-m)		DIFFERENCE (percent)
		DATA	SYNTHETIC	
1	1.00	127.4	113.0	11.28
2	2.00	97.23	120.0	-23.42
3	3.00	143.9	131.7	8.43
4	5.00	155.5	154.6	0.533
5	10.00	158.6	159.2	-0.357
6	15.00	131.1	128.6	1.87
7	20.00	95.73	100.5	-5.03
8	25.00	86.60	82.73	4.46
9	30.00	72.93	73.65	-0.988
10	40.00	69.14	70.35	-1.75
11	50.00	76.20	74.91	1.69
12	60.00	81.59	81.14	0.546
13	70.00	86.95	87.16	-0.245
14	80.00	89.08	92.50	-3.84
15	90.00	101.8	97.12	4.60
16	100.0	99.46	101.0	-1.63

\*

OYO CORPORATION



\*

PARAMETER RESOLUTION MATRIX:  
 "F" INDICATES FIXED PARAMETER

P 1	1.00											
P 2	0.00	0.50										
P 3	0.00	0.01	0.80									
P 4	0.00	0.01	-0.11	0.67								
P 5	0.00	0.00	-0.02	0.29	0.21							
P 6	0.00	0.00	0.01	0.11	0.13	0.10						
P 7	0.00	-0.01	0.05	0.00	0.19	0.23	0.76					
T 1	0.00	-0.02	0.01	0.00	0.00	0.00	0.00	1.00				
T 2	0.00	0.50	0.02	0.00	0.00	0.00	0.00	0.01	0.49			
T 3	0.00	0.02	-0.25	-0.21	0.03	0.04	0.07	0.01	0.02	0.67		
T 4	0.00	0.00	0.00	0.05	0.04	0.03	0.07	0.00	0.00	0.01	0.	
T 5	0.00	0.00	0.00	0.01	0.02	0.02	0.04	0.00	0.00	0.01	0.	
T 6	0.00	0.00	0.00	0.01	0.02	0.02	0.04	0.00	0.00	0.01	0.	
	P 1	P 2	P 3	P 4	P 5	P 6	P 7	T 1	T 2	T 3		

\* OYO CORPORATION \*

BL-R3



DATA SET: BL-R4

CLIENT: JICA  
 LOCATION: BAN LAENG, HEUXAY  
 COUNTY: BOR KEAW, LAO, P.D.R.  
 PROJECT: WATER SUPPLY & SANITATION  
 ELEVATION: 0.00  
 SOUNDING COORDINATES: X: 0.0000 Y: 0.0000

DATE: NOV., 1999  
 SOUNDING: -  
 AZIMUTH: -  
 EQUIPMENT: -

Wenner Configuration

FITTING ERROR: 6.678 PERCENT

L #	RESISTIVITY (ohm-m)	THICKNESS (meters)	ELEVATION (meters)	LONG. COND. (Siemens)	TRANS. RES. (Ohm-m <sup>2</sup> )
			0.0		
1	576.9	2.83	-2.83	0.00491	1634.9
2	187.0	9.69	-12.52	0.0518	1813.3
3	33.87	8.00	-20.52	0.236	271.0
4	182.1	15.21	-35.74	0.0835	2772.7
5	22.30	24.84	-60.59	1.11	554.1
6	1738.2				

ALL PARAMETERS ARE FREE

No.	SPACING (m)	RHO-A (ohm-m)		DIFFERENCE (percent)
		DATA	SYNTHETIC	
1	1.00	562.0	568.6	-1.16
2	2.00	482.3	527.8	-9.42
3	3.00	545.4	463.7	14.97
4	5.00	319.2	340.5	-6.67
5	10.00	187.9	193.8	-3.11
6	15.00	147.7	139.9	5.28
7	20.00	113.6	111.9	1.51
8	25.00	93.84	96.98	-3.35
9	30.00	86.53	89.43	-3.34
10	40.00	83.63	84.20	-0.672
11	50.00	89.43	83.47	6.66
12	60.00	87.63	84.31	3.79
13	70.00	83.41	86.29	-3.45
14	80.00	82.43	89.41	-8.46
15	90.00	90.35	93.58	-3.57
16	100.0	106.9	98.65	7.75

\*

OYO CORPORATION

\*

PARAMETER RESOLUTION MATRIX:  
"F" INDICATES FIXED PARAMETER

P 1	1.00										
P 2	-0.01	0.91									
P 3	0.00	-0.04	0.45								
P 4	0.00	0.01	0.12	0.51							
P 5	0.00	0.01	-0.02	0.07	0.49						
P 6	0.00	0.00	0.01	-0.01	0.03	0.00					
T 1	0.01	0.06	0.02	-0.01	0.00	0.00	0.94				
T 2	0.00	0.10	0.15	-0.05	0.00	0.00	-0.06	0.84			
T 3	0.00	0.04	-0.40	-0.09	0.01	-0.01	-0.02	-0.04	0.36		
T 4	0.00	0.02	0.02	0.44	0.03	-0.02	-0.01	-0.05	0.01	0.40	
T 5	0.00	0.00	0.01	0.01	-0.49	-0.04	0.00	0.00	0.01	0.05	0
	P 1	P 2	P 3	P 4	P 5	P 6	T 1	T 2	T 3	T 4	



\*

OYO CORPORATION

\*

D4-93

# BL-R4



DATA SET: BL-R5

CLIENT: JICA  
 LOCATION: BAN LAENG, HEOUXAY  
 COUNTY: BOR KEAW, LAO, P.D.R.  
 PROJECT: WATER SUPPLY & SANITATION  
 ELEVATION: 0.00  
 SOUNDING COORDINATES: X: 0.0000 Y: 0.0000

DATE: NOV., 1999  
 SOUNDING: -  
 AZIMUTH: -  
 EQUIPMENT: -

Wenner Configuration

FITTING ERROR: 76.161 PERCENT

L #	RESISTIVITY (ohm-m)	THICKNESS (meters)	ELEVATION (meters)	LONG. COND. (Siemens)	TRANS. RES. (Ohm-m <sup>2</sup> )
			0.0		
1	129.7	1.32	-1.32	0.0101	171.5
2	3996.8	1.79	-3.12	4.503E-04	7193.5
3	7260.4	2.65	-5.77	3.658E-04	19285.0
4	15.09	8.41	-14.19	0.557	127.0
5	276.6	11.99	-26.18	0.0433	3317.8
6	11175.3				

ALL PARAMETERS ARE FREE

No.	SPACING (m)	RHO-A (ohm-m)		DIFFERENCE (percent)
		DATA	SYNTHETIC	
1	1.00	164.8	161.3	2.10
2	2.00	301.5	259.4	13.95
3	3.00	277.6	369.2	-32.97
4	5.00	283.9	564.5	-98.79
5	10.00	502.5	874.8	-74.09
6	15.00	1124.1	982.3	12.61
7	20.00	2410.9	965.8	59.93
8	25.00	2141.3	885.8	58.63
9	30.00	600.8	780.9	-29.97
10	40.00	1259.6	575.2	54.33
11	50.00	234.2	421.4	-79.86
12	60.00	231.1	324.2	-40.23
13	70.00	186.0	270.3	-45.29
14	80.00	123.9	245.6	-98.17
15	90.00	242.6	239.6	1.22
16	100.0	619.7	244.8	60.49

\*

OYO CORPORATION

\*

PARAMETER RESOLUTION MATRIX:  
"F" INDICATES FIXED PARAMETER

P 1	0.61											
P 2	0.01	0.06										
P 3	-0.01	0.16	0.41									
P 4	0.00	0.01	0.03	0.41								
P 5	0.00	0.00	0.00	0.03	0.00							
P 6	0.00	0.00	0.00	0.01	0.00	0.00						
T 1	-0.37	-0.03	-0.01	0.03	0.00	0.00	0.53					
T 2	-0.01	0.06	0.15	0.01	0.00	0.00	0.01	0.06				
T 3	-0.01	0.15	0.40	0.03	0.00	0.00	0.00	0.16	0.40			
T 4	-0.01	0.00	-0.03	-0.41	-0.03	-0.01	-0.03	-0.01	-0.03	0.41		
T 5	0.00	0.00	0.00	-0.03	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.
	P 1	P 2	P 3	P 4	P 5	P 6	T 1	T 2	T 3	T 4		

\* OYO CORPORATION \*



BL-R5

D4-96

