




7.1.3 Treatment Plant











#### CALCULATION FOR WASTEWATER TREAMENT PLANT STRUCTURES

### PIPE GALLERY AND PRIMARY SEDIMENTATION TANK

(The calculation based on Japanese standard )

#### 1-GEOMETRY DIMENSIONS FOR CALCULATION

(As shown on drawings attached):

Ground level;	GL =	
Ground water level:	GWL=	
Bottom level of pipegallery	: BL =	
Bottom level of primary see	dimentation tank: BL =	
Bottom level of primary see	dimentation tank: BL =	

Water level of upper inflow water way: Water level of primary sedimentation tank

Thickness of pipegallery bottom: Thickness of primary sedimentation tank Thickness under inflow waterway bottom Cinder concrete thickness

		2	20
	13	ζ,	00
	1	3.	10
		2.	78
		5.	30

					22		910	28
					26	è	u.	2.61
			1.12		24		22	83
			244		6	2	u	(ji
4	2,1	100	112.51	1.	2.5	a	-01	- 14

Contra la		Ô.	70	m
			60	
		0	60	m
		0.	10	m

And all other dimensions shown on the drawing attached 2-MATERIAL PROPERTIES AND SOIL CONDITIONS:

Concrete: Grade C21,	Rn =	70 (Kg/cm2)
	RS=	3.6 (Kg/cm2)
Reinforcement type JIS:	Ra=	1600 (Kg/cm2)

Back fill sand: ys= 1.80T/m3 ; Coeficient of earth pressure at rest Ko 0.5

Internal friction 20deg

3-LOAD CALCULATION (BASE ON JAPANESE STANDARD):

#### 3.1- Maximum loads from architect part to be taken in calculation as in analysis 3.2- Soil load:

#### In case of ground water level at 0.00 (Permanent case):

-Horizontal triangle distributed load due to earth under ground water level (outside of primary sed. tank): p<sub>h1</sub>=0.8x5.9x0.5 + 5.9x1 = 8.26T/m2

-Uplift pressure to bottom of under inflow waterway:

- 71.1

Puplitt=(Hground water)X1,U=	5.90T/m2
-Uplift pressure to bottom of pipegallery:	
pupifi=(Hground water)x1.0=	3.80T/m2

#### 3.3-Water load

According to highest water level and bottom level as inlustrated in the drawing, water loads to be calculated and shown on the attached drawing.

3.4-Load of non-reinforced concrete layer on bottom slab:

(Due to machanical supports and cinder concrete) -Uniform load:

-Uniform load: 9contayer 2.5x0.10= 0.250T/m2

3.5-Live load:


-Live load for all operating floor and walking way : q<sub>ive</sub> =

4-ANALYSING BY SAP 2000: THERE ARE 3 COMBOS FOR ANALYSING AS ATTACHED HEREAFTE

0.50T/m2

## ALL THE LOADS, FACTORS, AND OTHER INPUT DATUM TO BE TAKEN IN ANALYSIS AND CALCUL

The reaction results of combo 3 as attached shows that no uplift case happen to the structure



7 - 1 - 38

#### reinl

SAP2000 v6.11 File: REIN1 Ton-m Units PAGE 1 March 6, 2001 9:50

ABC

LOAD COMBINATION MULTIPLIERS

COMBO	TYPE	CASE	FACTOR	TYPE	TITLE
COMB1 ater outside	ADD R				In case water full in all tanks, no ground w
		SELF WATER CINDERCO MAN	1.0000 1.0000 1.0000 1.0000	STATIC(DEAD) STATIC(LIVE) STATIC(DEAD) STATIC(LIVE)	
COMB2 no ground w	ADD				In case of tank-full and tank empty. Outside
		SELF CINDERCO MAN WATER1	1.0000 1.0000 1.0000 1.0000	STATIC(DEAD) STATIC(DEAD) STATIC(LIVE) STATIC(LIVE)	
COMB3 evel up to 4	ADD 0.00				All tanks are empty, out side ground water 1
		SELF CINDERCO UPLIFT EARTHPRE	1.0000 1.0000 1.0000 1.0000	STATIC (DEAD) STATIC (DEAD) STATIC (OTHER) STATIC (OTHER)	
ENVE 2, combo3	ENVE				Maximum and minimum results of combol, combo
		COMB1 COMB2 COMB3	1.0000 1.0000 1.0000	COMBO COMBO COMBO	

#### 5-CALCULATION FOR BAR ARRANGEMENT:

Base on attached results of shell forces and frame forces analised by SAP2000, choosing the most dangerous forces for calculation:

$$A_0 = M/R_0 bh_0^2$$

Where, M: Maximum bending moment(T.m)

h<sub>o</sub>: Effective depth of bearing area(cm)

h<sub>o</sub>= (Element thickness-Cover thickness)

b: Width of calculated area(cm)

Required area of reinforcement:

Fa= M/yRaho Where: y = 0.5 + (( 1-2Ao)<sup>1/2</sup>)/2

5-1 SLABS AND WALLS:

Moments	Values	alues Ao	γ Fa (cm <sup>2</sup> )	Bar arra	Remark		
	(T.m)			(cm <sup>2</sup> )	φ(mm)	a(mm)	
(Bottom							
Slab level	-6.600	0.0510	0.974	9.85	14	125	
-5.3)	2.700	0.0267	0.986	4.50	14	250	
t=0.50							
(Bottom	-2.400	0.0315	0.984	4.62	14	250	
Slab level	6.500	0.1184	0.937	15.49	16	125	
-3.00)							
t=0.40							
t=0.70	-21.200	0.0763	0.960	21.90	20	125	
	-10.000	0.0360	0.982	10.11	20	250	
	14.700	0.0624	0.968	16.37	18	125	
	7.400	0.0314	0.984	8.10	18	250	
	-15.700	0.0667	0.965	17.52	18	125	Slope
	21.200	0.0763	0.960	21.90	20	125	Slope
	-9.000	0.0382	0.981	9.89	18	250	Slope
Pri. Sed.	9.000	0.0558	0.971	12.07	14	125	
Tank bottom	-4.500	0.0229	0.988	5.37	14	250	
Slab	12.800	0.0794	0.959	17.39	18	125	
Level +2.78	-4.500	0.0229	0.988	5.37	14	250	125
t=0.60							
Slab	-11.100	0.1456	0.921	22.83	20	125	
Level +3.7	4.400	0.0577	0.970	8.59	14	150	125
1=0.40	-10.600	0.1391	0.925	21.71	20	125	
	5.600	0.0735	0.962	11.03	14	125	
Water way	-2.100	0.0567	0.971	5.88	14	250	
floor L+5.8	3.200	0.0864	0.955	9.11	14	150	125
=0.30							
	-1.350	0.0857	0.955	5.89	12	150	125
Top floor	0.900	0.0571	0.971	3.86	14	250	
evel +8.0	-0.800	0.0508	0.974	3.42	12	250	
=0.20	0.650	0.0413	0.979	2.77	12	250	
Wall of pri	9.300	0.0719	0.963	14.04	16	125	
Sed. Tank	-9.300	0.0719	0.963	14.04	16	125	

Moments	Values	Ao	У	Fa	Bar arrangement		Remark
	(T.m)			(cm <sup>2</sup> )	φ(mm)	a(mm)	
t=0.50							
Wall of pri	9.500	0.0734	0.962	14.36	16	125	
Sed. Tank	-11.100	0.0858	0.955	16.89	22	200	125
&Pri.Gallery	-17.300	0.1337	0.928	27.10	22	125	
t=0.50			8		100.00		
Water way	5.500	0.0722	0.963	10.82	14	125	
wall							
t=0.40							
t=0.30	-2.900	0.0783	0.959	8.22	12	125	

#### 5-2 BEAMS:

AREA	LOCATION	Values	Ao	γ	Fa	Bar arra	ngement
m2		(T.m)			(cm <sup>2</sup> )	¢(mm)	quantity
b=0.50	At the end	12.300	0.0659	0.966	10.90	20	4
h=0.80	In the mid.	9.980	0.0535	0.972	8.79	18	4

#### 5-2.1-CHECKING SHEAR FORCES:

-Height of hand for supporting coverslab s, so the section need to be checked shear bearing capacity is [c/2+(h+s)/2]

- In case Q >= Rsxbxd so the below case is to be considered

- In case concrete is not enough to bear shearing force, stirrups will be considered

Sc/2 + Ss >= Q (shearing force at section calculated) Sc: shearing bearing capacity of concrete (kg)

Where

Ss: shearing bearing capacity of reinforcement (kg)

Ss=AsxRaxjxd/a = Q - Sc/2

As: area of all stirrup in section considered

d: effective height of beam

a: pilch of stirrup (distance between two stirrups)

j: coefficient that consider safety factor (=1/1.15) =0.87

WWTR Pipe geliery Pointry and Tash\_20301

in village		ALC: N
column	hand	~
	5 (m) 2	b (m) s (m) s
0	0	0.5 0

ľ

Ŀ

6- COLUMNS: A. MATERIAL PROPERTIES:

(Kalam2)	230000 (Kg/cm2)	(Kg/cm2)	(Kg/cm2)
70	230000	2000000	1500
п			
Rin	ŵ	E.	Ra = Ra
G21		IV.	
Grade		add	
Concrete		_ Reinforcement	
			B. CALCULATION:

(CAAP NO I LÁZO 3 - NITER-MIDUR ÚMG)

(Ko) N	0.1405+04
M (Ko.m)	0.06E+00
4- (cm4)	\$28(0.000
J, (cm4)	1521
0 H (%)	0.65
42	0.45
0.0	0.62
Rot Rot (Kg/cm2)	10
Ê	1.00
-	9.92
en) le	475
2 (13	5
ara' (an)	
h (cm)	30
q (ucu)	20
(cm)	11501
POSITICN	1001
NAME OF COULWN	

CHECK BOTRIDOLXUNG		Pitter 47 D18	8 D18
47		020	
Ficon (cm2)	-	-	
a Z		-14	
Safa and		-15.6	
1.7 3	ъ	211.	
(cm)		5	
2°°F		201	
" (j		ā	
o (cm)	1	1	
100		-	
land (cml	-	1.1	
E.	1.040		
(Kg)	1.417.404	-	
ź	2021		
0Kg)	0.1425404		
(Kg.m)	0.00(5400)		
n	0.51		
6	10401		
s (in)	10		
5	1001		
NAMO			

### 6- CALCULATION FOR PILE NUMBER (as attached sheets):


(Pile number to be decided by pile calculation sheet, please refer to pile calculation sheet for more information)

						Г		MON	/IEN	50	- RO	110	MC	SL	ar (f	EVE	L -5.3	0)		T				
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$																								
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$																								
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	4					-	-						-								_	_	_	
						-																_		
																						1		
	+					+	-							-						1	>	-		
	-	-				-							-							ſ	1	+	-	
					_	-		-		-			-	-		-	-	-		4		_	~	
	1			-		+	+				-	-		-	-	+	¢				-	+	+	N N
	Ì		~	=	5		ы	¢1	¥	ы	¥	۵	à	5 55	u	2	6	71	3			5	1	31
	X	-	-	14	*	8	2	2	ы	¥	â	2			E	2	8	2	74	z	z z	=	7	2
													7											
							1						1	+							+			
													6.9									1	1	
165	_					_	-		_				P	-							-	+		
Vo																							1	5
																							V	5
	_					-	_							_							-	_		
																1								

March 3,2001 14:48

					1	BC	ו רדכ	roi	I M S	SLA	ι 4Β (	LE\	/El	3	1 .10	))	1						
				2,538	zim	2570	347	2548	247	01	63	σ	67	υu	2712	713	2714	2743	2744				-
				2.682	2681	214	ോ	2572	2371	454	465	456	40	2715	2714	20	2718	2745	3946				
				2584	2543	zin	23/7	2574	875	64	455	-54	457	2717	2728	1721	2722	20	2748				
				34.8	16.2 16.2	2352		_	2577	591.	10	496 4714	947		2721	2725	2726	2619	hite		 	_	
_				Julia.	2407	2544	2545	594 595	245	Gr Gr	435	64 64	417 417	2727	1726 1721	2729	2738	2121	2714		 -	-	
				2168	2487	2594	1993	1592	2591	414	411	415	417	vn	2734	33	8675	2751	2752				T
		- 10,0		8116	2.004	25%	4597	Zits	2395	801	ets	800	407	22	2748	2741	2142	1733	254				Ť
				54	695	8.8	BB	88	80	294	295	295	297	250	2648	2110	2179	2137	2710		+6.	5	
				2554	259	2539	1519	Zin	2127	284	32.5	344	100	1671	2017	2173	2014	2781	2782				T
	-	24.20	5	2548	2559	2514	25.33	2532	2531	374	295	391	287	201	2474	2477	201	2783	2004		14.	7	
			k	402	201		21.32	1.00	2535	384	365	364	30	2077	2658		-	2015	2515		4.3.4		
				2562	2473 2541	2542	2541 2545	2548 2544	250	34	255	24	20	2012		2582	2128	2715	2010 2010	>		-	+
				2564	1543	2158	2549	1548	250	231	305	234	311	2191	2692	C84	2134	2910	2781			1	+
		e el		1548	1545	2154	2153	255.2	2551	224	25	24	זע	an	2494	har	zun	vn	211				+
				1715	4510	2442	2-41	2410	2477	314	36	216	318	2423	2624	21.15	21.24	2455	2414				T
				314	80	2485	145	2454	2413	364	321	354	мг	2429	24.24	24.17	24.38	2657	2/54				T
				2515	2515	3498	1489	2444	2412	25	7%	235	237	2631	2512	2133	2534	2529	2008				1
				2458	2457	2004		2492	2011	204	283	288	282	2635	21336	_	-	2511	28/2				
				204	24.9	2582		205	2495	234	275	23.6	217	3143	2548	-	2642	2513	2814	-	 	-	-
				2528	2519	2584	1585	2514	2503	254	255	236	25	150	2645	21+8	2150	260	2164				1
				2522	2021	2518	1:00	2548	2587	214	245	245	20	2051	2452	2450	Juia	2005	2568				
													*										

## BOTTOM SLAB (LEVEL +2.78) ( ENVE COMBO Max (M<sub>11</sub> ))




March 5,2001 10:10

## BOTTOM SLAB (LEVEL +2.78) ( ENVE COMBO Min (M11 ))

55	116	RT .					54	92	15
						-		-	-
142	FSB	PLt					912	853	95
-u	344	753			•		745		24
19	924	VD				+	245	541	
131	412	923				÷	¥14	835	T
45	ytu	917	•			t	128	525	7
						-			
19	928	921					712	523	
	0.0254204	160.00				- 1			
на	9.4	42					F15	3.0	
-	-								-
in .	788	745					918	911	
						-			1
191	W.I	183					784	985	
195	174	407	÷		-	-	171	679	
	1.1.1.1.1.1.1.1	100000				1	10000		1
122	100	151				1	895	8/3	
843	134	HAL.				1	dia .	867	-
677	171	177	-				878	821	A
101	872	873					674	175	
	1.4	128							
845	815	M7					848	5.17	
-		-						-	
E\$P	213	M1					642	10	-
						-			-
C29	gia	835					854	857	1
ισ	845	117				Î	6.9	451	K
141	842	143					144	Arth	
125	#36	812	-		-	-	4.38	4.79	
L/P	8.18	. 121				-			+
-							1.75	413	-
cu,	824	625			-4	5.	Kin .	425	
517	1.1	10		۲ ۲			- 4	>	-
	1000						109	621	- K

SAP2000 v6.11 - File:rein1 - Resultant M11 Diagram (ENVE) - Ton-m Units 7 - 1 - 48



<sup>7 1 49</sup> 


## BOTTOM SLAB (LEVEL +2.78) ( ENVE COMBO Min (M<sub>22</sub> ))

\$15	73	12						- yik	19	344	
ж 140	F18 -	851						15.2	143	5714	
H2	944	945						+ut	Pet	745	
89	FIR	1.5						948	941	742	
801	812	433						934	P.E.	836	
25	#ls	127						926	929	9.28	
	828	NP1						122	833	924	
213	994	915						P16	912	¥ 16.	
, no	121	98						114	911	912	
101	982	10						VBA	981	538	
	en	137						.876	809	919	
14.9	dia	10's						892	83	8M	
46.1	864	845						884,	W,	2.62	. A
87	873	819						100	MAT	M2 _0	
וש	872	2/2						324	en.	174	
845	844	567						618	147	171	
414	ыя	841						4.2	83	84	
84.2	#14	815						858	807	850	
40	843	- 10						5.0	151	412	
811	142	141						514	145	ML	
4.05	8.36	137						834	8.9	848	
125	4.58	aju.						KSF.	823	834	
623	414	815			v			\$25	Ш <sup>*</sup>	12	
4.0	818	10			Î			629	821	872	
					└> X						2
-17.5	-	14.0	-10.5	-7.0	-3.5	0.0	3.5	7.0	)	10.5	
		and the second second	CONTRACTOR OF THE OWNER	CONTRACTOR OF THE OWNER		C DECK T					

													6							
							FL	.00	RSI	AB	LEV	/EL	+3.7	0)	1					
										1	1	1		1	1					
		-		+-				+		-	-			-	-					
								1217		u										
								1315		13										+
	1			-		-	· ·	100		13		•		-	-	-	_	_		-
		-	-					山湯湯		1998						-	-			-
		1						1203	†	138	+				_	-	_			-
		1				1		1301		132	-									-
_			-			+ .	_	-				_								
						1	40.6	217	+5.6	1.30			Ċ							
								1207	拉角	109			1		-					-
		1	-				-	-		-	-	-			+4	-	_			_
								195		1274		1	1		17	1		1		
								1293		1294	10.02	1	V							
_		-					200	「「「「「「」」」		1202	-	1	X	$\leftrightarrow$	-					-
-							+363	un)		1704	1	X	¥		-1	<u>1, 1</u>				
								1251		12.52			N							
								1277		1214	1				+	-				-
-	_	-	-			+		-		-	-	-	1			-				
_								4177		1178										
								1275		127.6						T				-
								1972		1274	-	•	-		-		_		-	
-	_			-	_			101		107							-			
								1263		100	-	-				-	-	-	_	
						1		1201		1242		-	-		-					
-									_	1404		+								
								1259	î	1210					1					
						1				×					1	+			-	
																1				
1												1								

SAP2000 v6.11 - File:rein1 - X-Y Plane @ Z=6.82 - Ton-m Units

## WATERWAY FLOOR LEVEL +5.80) (ENVE COMBO Max (M11))





-10.5

-7.0


-3.5


7-1-52

14.0

17.5

## WATERWAY FLOOR LEVEL +5.80) ( ENVE COMBO Min (M<sub>11</sub> ))





-14.0

-21.0

-17.5


-3.5

0.0

3.5

7.0

COVER SLAB (LEVEL +8.00) ( ENVE COMBO Max (M<sub>11</sub> ))




-10.5 -7.0 -3.5 0.0 3.5 7.0 10.5 14.0 17.5


SAP2000 v6.11 - File:rein1 - Resultant M11 Diagram (ENVE) - Ton-m Units

7-1-54

# (ENVE COMBO Min (M<sub>11</sub>))




-21.0 -17.5 -14.0 -10.5 -7.0 -3.5 0.0 3.5 7.0 SAP2000 v6.11 - File:rein1 - Resultant M11 Diagram (ENVE) - Ton-m Units 7 - 1 - 55



## COVER SLAB (LEVEL +8.00)

## (ENVE COMBO Min (M22))



SAP2000 v6.11 - File:rein1 - Resultant M22 Diagram (ENVE) - Ton-m Units

-3.5

0.0

-7.0

-17.5

-14.0


-10.5

7 - 1 - 57

7.0

10.5

3.5



## WALL OF PIPE GALLERY AND PRIMARY SED. TANK

(ENVE COMBO MAX M2-2) x = +6.25


294	1772	179	D2002	3994	391	1585	1817	121	1691	14.54	2.3	244	1851	15.4	80	1875	1503	100	0.57	13/15	015	1912
	_									_												
211	215	212	723 727	лі	725	19	740	751	755	759	762	767	m	775	70	732	791	376	1997	583	887	RII.
\$299	483	str	611.615	619	623	625	615	63	60	10	651	455	43.9	843	<i>(</i> 7)	675	479	14.3		691	65	.97
				procession in the					-						and the second		1.000		12.1			Distant.

Dizz


the second second	-7.0	-3.5	0.0	3.5	7.0	10.5	14.0	17.5	21.0
SAP20	00 v6.11 - I	File:rein1 -	Resultant M22	? Diagram	(ENVE) -	Ton-m Units		7 - 1 - 59	

## WALL OF PIPE GALLERY AND PRIMARY SED. TANK

#### (ENVE COMBO MAX M2-2) x = +6.25



M2-2



## WALL OF WATER WAY

## (ENVE COMBO MAX M2-2) x=1.25

2130	2136	21.07	nene	2145	2151	2154	212	-2348	\$192	216210	2172	5112	2158	145	2184	2107	1968	2194	2:99	2762
12404	1771	1776		1793	1008	1989	特法	1823	10.00		1045	1852	1857	1515	1875	110.7		1897	1704	1911
535	7548	745		15.68	1545	100	-542	1972	1587		1612	1417	1612	1529	1644	14.65		14.64	15.87	1574
1312	1336	048	1344.352	1356	1358	DM	1338	L2H	1.304	13.1 68	142.8	(485	1412	14,08	жу	1436	inere	952	HSI	1418


5.5

Z 1

-7.0

-3.5

0.0



7.0

10.5

14.0

3.5

21.0

17.5

## WALL OF WATER WAY

## (ENVE COMBO MAX) x=1.25

 2	. 1	9
	-	~

2:02	2136	2139	1010	2148	2151	\$154	2/67	2158	2163	\$112510	202	502	21/8	2181	2184	2167	2126123	2.96	2.99	2292
104	1721	1778		1771	1598	1007	1815	1623	1538		1815	1852	1829	1568	1825	1852		1897	1784	811
1535	1540	tisti.		1548	1565	1578	iso.	1522	1897		1612	1617	1622	1629	1544	1649		1561	1547	1674
1332	1336	1348	044052	1256	1348	1344	1.188	1384	1358	125 23 400	1484	1408	1412	14,25	1632	168		162	1456	1412

Ĩ

-17.5

-14.0

SAP2000 v6.11 - File:rein1 - Resultant M22 Diagram (ENVE) - Ton-m Units

-7.0

-3.5

0.0


3.5

-10.5


7 - 1 - 62


7.0

10.5



SAP2000 v6.11 - File:rein1 - Moment 3-3 Diagram (COMB2) - Ton-m Units





SAP2000 v6.11 - File:rein1 - Axial Force Diagram (COMB1) - Ton-m Units

## SAP2000

January 5,2001 17:26

## CALCULATION FOR PILE NUMBER

PIPE GALLERY - PRIMARY SEDIMENTATION TANK

	D														
26	78.9														
- fill	jen	2404	240	учн	2004	~~~				,ca	$\mu v$	218	$\mathbf{t}_{\mathrm{rc}}$	244	10
140	240	2465	244		2001					2004		24	Tes.	143	210
										•				1-	-
2est	$p_{i0}$	2412	200		200					2005		244	$T^{O}$	240	$l^{ap}$
2400	21.0	2416	246		3000					252		241	270	271	<u>542</u>
2422	2421	2400	240		300%					200		10	272	273	4.0
2425	245	2121	2423		jon					751		jas	274	275	344
jan	24.00	2428	200		200					1384				-	
										140		Ine	217	218	In
jain	2403	202	201		Jus.					,pan		lan .	In	\$15	lan lan
328	23%	1214	$p_{0}$	27.16	$\mu x$							21	214	116	jen.
257	25%	2223	1172		115										
1.	1.	1	tas.		3026					1.80 J		2.12	210	211	t <sub>11</sub>
222	2361	3100	2279		\$co					1297		218	\$19	220	$\sharp^{i_1}$
2006	2005	2384	230		200					70		200	621	824	110
2198	- 3369	2300	2307		20270								223	223	314
2184	jasa -	3892	2191		100					202		254	<u>\$24</u>	225	Z <sup>il</sup>
tuse .	Jan	70%	285		jun .					244		302	1524	ţ.,	her
			1		1					124		224	1414	\$10	$I_{11}$
par.	Per	2400	7209		200					1285		242	<b>1</b> 82	$l^{ps}$	225
2012	254	2286	2005	3484	2424					112					
	-		•							315	tun.	1a	Per .	ges.	Įυ
290	2170	$\mu w$	2nm		201					jen.		tra	Per	40	$P^{es}$
2046	2045	2000	jusi		$e^{\mu u}$					1249		In	w	Įa	$P^{o}$
2254	100	2148	214		2.74								Sec.		See.
2054	100	182			7576					128		345	$p_{i}$	$P^{1}$	346
2054	1x1 Tra		315.1		2064				-	1e		21	Ins	$p_2$	15
		have.	3155		2584					12		ha	$p_{\beta}$	$h_{\ell}$	bu.
100	lou -	lora.	220		Jes -					1m		\$76	$p_{1}$	low	100
tem	788	psa	2040		Jun		ŗ			.097		210	311	μ	$_{lm}$
157	260	2308	po	24/28	2006		1	1000		23	pin				
2678.0						100		→ X		22	pu	μ,	tur	Pro Pro	12
e.							31.0	)							~

Preaction = 10.50 T/m<sup>2</sup> and Pile Capacity = 45 T/pile

⇒ Area of one pile that can used for an area of 4.29 m<sup>z</sup>

⇒ The arrangement may be (2x2)m. Please refer to pile arrangement No. PE - WWTP - 252 - 01 No. PE - WWTP - 252 - 02

SAP2000 v6.11 - File:p1 - X-Y Plane @ Z=5.9 - Ton-m Units 7 - 1 - 66

#### pl.txt

SAP2000 v6.11 File: P1 Ton-m Units PAGE 1 January 5, 2001 17:16

ABC

#### LOAD COMBINATION MULTIPLIERS

#### COMBO TYPE CASE FACTOR TYPE TITLE

PILECOMB ADD for calculating number of piles SELF 1.0000 STATIC(DEAD) WATER 1.0000 STATIC(DEAD) CINDERCO 1.0000 STATIC(DEAD) MAN 1.0000 STATIC(DEAD)

SAP2000 v6.11 File: P1 Ton-m Units PAGE 2 January 5, 2001 17:16

#### ABC

### JOINT REACTIONS

#### JOINT LOAD F1 F2 F3 M1 M2 M3

14 14 14	WATER CINDERCO MAN UPLIFT	98.8886 -331.0858 1513.8496 0.0000 0.0000 0.0000 58.0416 -187.2215 1026.9735 0.0000 0.0000 0.0000 3.3893 -6.5370 25.7813 0.0000 0.0000 0.0000 12.1968 -25.8121 112.2825 0.0000 0.0000 0.0000 -78.8528 189.9668 -793.8288 0.0000 0.0000 0.0000 172.5163 -551.6603 2678.8870 0.0000 0.0000 0.0000
421	SELF	98.8898 331.0898 1513.8495 0.0000 0.0000 0.0000
42	WATER	50.0411 187.2215 1026.9735 0.0000 0.0000 0.0000
421	CINDERCO	3.3894 6.5370 25.7813 0.0000 0.0000 0.0000
421	I MAN	12.1971 26.8121 112.2825 0.0000 0.0000 0.0000
421	UPLIFT	-78.8538 -189.9668 -793.8298 0.0000 0.0000 0.0000
421	PILECOMB	172.5174 551.0003 2678.8870 0.0000 0.0000 0.0000
337	0 SELF	98.8885 -331.0898 1513.8495 0.0000 0.0000 0.0000
337	0 WATER	-58.0416 -187.2215 1025.9735 0.0000 0.0000 0.0000
337	I CINDERCO	-3.3893 -5.5370 25.7813 0.0000 0.0000 0.0000
337	0 MAN	-12 1968 -26.8121 112.2825 0.0000 0.0000 0.0000
337	UPLIFT	78.8520 189.9668 -793.8298 0.0000 0.0000 0.0000
337	9 PILECOMB	-172.5163 -551.6603 2678.8870 0.0000 0.0000 0.0000

 3410
 SELF
 -90.8098
 331.0898
 1513.8496
 0.0000
 0.0000
 0.0000

 3410
 WATER
 -58.0411
 187.2215
 1026.9735
 0.0000
 0.0000
 0.0000

 3410
 CINDERCO
 -3.3894
 6.5370
 25.7813
 0.0000
 0.0000
 0.0000

 3410
 MAN
 -12.1971
 26.8121
 112.2825
 0.0000
 0.0000
 0.0000

 3410
 UPLIFT
 78.8538
 -189.9660
 -793.8298
 0.0000
 0.0000
 0.0000

 3410
 PILECOMB
 -172.5174
 551.6603
 2678.8870
 0.0000
 0.0000
 0.0000

									Marc	ch 6,2	001 12:0
		2	4								
		1	6F	4: 10	10		24 24	145	20	jui -	242
2	70 7		28	211	211						
Ĩ		Î			1		200	214	325	No.	211
2	a 2	0 2	19	§21	222		225	214	110	214	
							1	324	105	314	800
T	T			11	§12		210	214	215	24	117
	· · · · ·			201	92		193	294	jus.	294	100
2	us pr	0 10	10	171	192		293	124	195	EN.	jar .
		. 1							1	Î	
2	rs ju	9 - 5 <sup>4</sup>		(A)	ju?		0.1	314	juri.	246	10
									1		
- f	et ju	9 V	a .	pi .	302		pa .	974	175	an .	107
				8 1 8							
M	54 JS	, .	a	359 948	561					1.	1
1	1	1	-	-			342 Jul	544	105	344	w
	46 34	2 24	0	10	10		151	10			
	- T	1	1					ju-	253	154	and a second
											1
	w 10	7 ju	1	17	242		241	142	10	204	945
									1	1	
	24 12	T		57 57	130		(O)	12	ju .	in .	\$75
21		T .			200		80	102	10	24	jan .
	N JE	, h		av .	20		20	312	ju .	114	15
27	16 28		, l		pine .				1	1	I
1	1	-	· •				ju:	342	100	jui	NS
n.	u 25	70	, j		79	the last the state line is	771	712		L. 3	1.00
1	Ī		Ĩ				1	fre .	100	114	m
77	u ja	27	1 2	97 JU	77		244 244	210	203	754	715
							Ĩ	Î	Î	1	1
1.0											1
754	64 <u>243</u>	- Ju	P	47	ha.		10	778	221	772	<b>C</b> 77
24	4 255	10	l.	0			L. 1				
	1 m	134	-	-	54		759	749	761	342	283
244	4 76	24	,	0	40		2.40				
j>	· · · ·				78		147	758	151	ju	753
-					28		18	14		10	242
10	-		Î					278	731	<u>μ</u>	731
pre-			1 L	17	18		10	2.28	21	772	723
70	· 215	14					·	4		e**	1
1	· 215	24	1					1 .			
70											
1					10.	Y	700	712	211	712	713
70					R.		700	210	2:1	712	213
714	e guet	204	70	v ,			700	212	211	212	<u>713</u>
70	e guet	206	70	U J	10.						210 710

## CALCULATION FOR WASTEWATER TREAMENT PLANT STRUCTURES

# PRIMARY SEDIMENTATION TANK-PIPE GALLERY-AERATION TANK

(The calculation based on Japanese standard )

# 1-GEOMETRY DIMENSIONS FOR CALCULATION

(As shown on drawings attached):

Ground level:	GL =	+ 2.20
Ground water level;	GWL=	+ 0.00
Bottom level of pipegallery:	BL =	-3.10
Bottom level of primary sedime	entation tank: BL	2.94
Bottom level of aeration tank: I	3L =	-0.35
Water level of primary sedimer	ntation tank	+ 6.06
Water level of aeration tank:		5.28
Thickness of primary sediment	lation tank	0.60 m
Thickness of pipegallery bottor	m:	0.60 m
Thickness of aeration tank both	lom	0.60 m
Cinder concrete thickness		0.10 m

And all other dimensions shown on the drawing attached

#### 2-MATERIAL PROPERTIES AND SOIL CONDITIONS:

Concrete: Grade C2	1, Rn =	70 (Kg/cm2)
	RS=	3.6 (Kg/cm2)
Reinforcement type A	II: Ra=	1600 (Kg/cm2)
Back fill sand; ys=	1.80T/m3	; Coeficient of earth pressure at rest Ke 0.5
Internal	friction	20deg

ternal inction 20deg

## 3-LOAD CALCULATION (BASE ON JAPANESE STANDARD):

## 3.1- Maximum loads from architect part to be taken in calculation as in analysis 3.2- Soil load:

# In case of ground water level at 0.00 (Permanent case):

-Horizontal triangle distributed load	due to earth under ground water level (under primary sed. tank):
p <sub>h1</sub> =0.8x6.1x0.5 + 6.1x1 =	8.54T/m2

-Horizontal triangle distributed load due to earth under ground water level (under aeration tank): ph1=0.8x2.75x0.5 + 2.75x1 = 3.9T/m2

<ul> <li>Uplift pressure to bottom of pipegallery;</li> </ul>	
pupilt=(Hground water)×1.0=	3.70T/m2
-Uplift pressure to bottom of aeration tank:	
puplit=(Hground water)x1.0=	1.0T/m2
Water load	

#### 3.3-Water load

According to highest water level and bottom level as inlustrated in the drawing, water loads to be calculate and shown on the attached drawing.

# 3.4-Load of non-reinforced concrete layer on bottom slab:


(Due to mechanical supports and cinder concrete)

-Uniform load: q<sub>conJayer</sub> 2.5x0.10= 0.25T/m2

### 3.5-Live load:

-Live load for all operating floor and walking way : qive =

0.50T/m2



7-1-70

### 4-ANALYSING BY SAP 2000: THERE ARE 3 COMBOS FOR ANALYSING AS ATTACHED HEREAFTER:

ALL THE LOADS, FACTORS, AND OTHER INPUT DATUM TO BE TAKEN IN ANALYSIS AND CALCULATED BY SAP 2000 The reaction results of combo 2 as atlached shows that no uplift case happen to the structure

#### LOAD COMBINATION MULTIPLIERS

#### COMBO TYPE CASE FACTOR TYPE TITLE

COMB1 ADD In case of all tanks are full of water, no ground water outside WATER 1.0000 STATIC(LIVE) CINDERCO 1.0000 STATIC(DEAD) MAN 1.0000 STATIC(LIVE) SELF 1.0000 STATIC(DEAD) ONLYSOIL 1.0000 STATIC(OTHER)

COMB2 ADD In case of all tanks are empty, ground water level is up to 0.00 CINDERCO 1.0000 STATIC(DEAD) SELF 1.0000 STATIC(DEAD) UPLIFT 1.0000 STATIC(OTHER) SUBMSOIL 1.0000 STATIC(OTHER)

COMB3 ADD In case of tank-empty and tank-full, no ground water CINDERCO 1.0000 STATIC(DEAD) SELF 1.0000 STATIC(DEAD) WATER1 1.0000 STATIC(LIVE) MAN 1.0000 STATIC(LIVE) ONLYSOIL 1.0000 STATIC(OTHER)

ENVE ENVE Max min of all combos to calculate for reinforcement COMB1 1.0000 COMBO COMB2 1.0000 COMBO COMB3 1.0000 COMBO

### 5-CALCULATION FOR BAR ARRANGEMENT:

# Base on attached results of shell forces and frame forces analised by SAP2000, choosing

# the most dangerous forces for calculation:

A<sub>o</sub> = M/R<sub>n</sub>bh<sub>o</sub><sup>2</sup> Where, M: Maximum bending moment(T.m)

ho: Effective depth of bearing area(cm)

h<sub>o</sub>= (Element thickness-Cover thickness)

b: Width of calculated area(cm)

Required area of reinforcement:


Fa= M/yRaho Where: y = 0.5 + (( 1-2Ao)<sup>1/2</sup>)/2

Moments	Values	Ao	γ	Fa	r arrangeme	nt	
	(T.m)			(cm <sup>2</sup> )	ộ(mm)	a(mm)	
Bottom	21.000	0.1302	0.930	29.40	22	125	245125
Slab level	10.000	0.0620	0.968	13.45	22	250	24a250
-3.10)	-10.200	0.0519	0.973	12.36	16	125	
t=0.60							1
aeration	19.000	0.1178	0.937	26.40	22	125	Not in DWG.
tank bottom	12.300	0.0763	0.960	16.68	18	125	
slab	-5.300	0.0270	0.986	6.34	14	200	2 125
level -0.35	7.500	0.0465	0,976	10.00	14	125	
1=0.60	-10.900	0.0554	0.971	13.23	16	125	
Pri. Sed.	10,900	0.0676	0.965	14.71	16	125	
tank bottom	8.650	0.0536	0.972	11.58	14	125	
Level +2.78	-4.700	0.0239	0.988	5.61	12	200	a-125
t=0.60						10 I I I I	
Water way							
bottom slab	11.600	0.1522	0.917	23.96	20	125	
0.4	-3.300	0.0433	0.978	6.39	16	250	s. 125
Cover slab	-5.500	0.1964	0.890	19.32	18	125	
t=0.25	-4.700	0.1679	0.908	16.18	18	125	
	2.250	0.0804	0.958	7.34	12	125	
Wall for pri.	9.600	0.0742	0.961	14.51	16	125	
sed. Tank	-9.900	0.0765	0.960	14.99	24	250	
& pipe ga.	-7.400	0.0572	0.971	11.08	20	250	
0.5							
Wall of							
water way	-5.500	0.0722	0.963	10.82	14	125	
0.4	11.600	0.1522	0.917	23.96	20	125	_
Wall of Pipe	11.100	0.0858	0.955	16.89	18	125	
gallery and	21.300	0.1646	0.910	34.04	24	125	
aeration tank	-11.800	0.0912	0.952	18.01	18	125	
0.5	5.000	0.0386	0.980	-7.41	16	250	
	-4.400	0.0340	0.983	6.51	16	250	
Longitudinal	-6.000	0.0464	0.976	8.93	14	150	p 125
wall	-6.200	0.0479	0.975	9.24	14	125	
0.5	7.300	0.0564	0.971	10.93	14	125	

## 5-1 SLABS AND WALLS:

# 6- CALCULATION FOR PILE NUMBER (as attached sheets):

(Pile number to be decided by pile calculation sheet, please refer to pile calculation sheet for more information)



# BOTTOM SLAB OF PIPE GALLERY(LEVEL - 3.1)

# (ENVE COMBO MIN)



691	240	244	eit	m	755	nz	784	686	727	728	665	-	735	736	688	42	711	712	544	454	38	728	656
w	7.61	742	430	677	749	758	781	663	725	726	615	ers .	733	734	4277	435	789	710	641.	451	80	ra.	624
664	7.39	248	454	655	142	745	458	6.68	723	128	ш."	1 02	231	7.22	84	363	787	788	636	648	75	тe	658
481	2.52	738	40	63	245	745	es	0.2	321	722	618.5	567	729	738	671	633	765	785	65	65	70	ля	40

-22.0 -16.5 -11.0 -5.5 0.0 5.5 11.0 16.5

SAP2000 v6.11 - File:p2-rein - Resultant M22 Diagram (ENVE) - Ton-m Units

7 - 1 - 74

# AERATION TANK BOTTOM SLAB LEVEL -0.35 (ENVE COMBO MAX)

578	157	758	472	875	P63	M2	en	658	54	958	648	664	153	<b>F</b> 54	dak	846	541	22	848	152	145	745	874
м	155	758	MP	173	957	358	875	855	907	548	157	661 1-+12.3		12	663	143	535	94	M5	649	943	941	851
Jui	121	912	413	542	837	5.28	142	6.0	\$1.9	578.	15		825	8.74	834	775	yıt	986	717	884	713	714	885
\$25	125	738	838	117	535	536	830	6.8	517	918	8.2	A.S	823	524	AU1	792	985	786	74	881	911	712	883
835	RU.	728	w	834	133	534	836	887	515	7%	587	84 3 12.3		522	816	71.0	983	784	791	798	787	210	340
788	817	495	762	785	981	942	798	198	847	576	πe	4	103	874	776	754	681	802	758	742	h#5	MA	214
m	155	240	179	263	177	100	205	216	w	188.	10	771	m	872	773	753	679	388	755	759	51.3	an.	761

Î

-13.5 -9.0 -4.5 0.0 4.5 9.0 13.5 18.0

SAP2000 v6.11 - File:p2-rein - Resultant M22 Diagram (ENVE) - Ton-m Units

# AERATION TANK BOTTOM SLAB LEVEL -0.35 (ENVE COMBO MIN)

178	957	958	M2	878	96.1	N2	613	858	513	958	648	BA1	953	95A	866	846	941	942	54	852	745	76	854
w	955	154	10	873	70	168	873	855	947	318	157	841	951	952	EM	(A)	52	14	86	547	943	744	851
31	221	172	833	548	111	F38	142	in	517	528	815	8.12	10	978	825	775	587	998	777	684	713	214	184
1211	2.79	938	131	837	935	F36	137	118	517	518	812	110 个一元6		924	8/1	712	595	784	774	881	711	712	DAD I
53	527	928	A27	лн	913	234	836	887	715	715	884	4	52)	922	.816	768	583	2014	291	278	7407	710	
59	877	154	112	лы	981	nı	785	748	347	208	779	774	673	874	176	256	Ŵ1	112	258	w	885	885	754
π	85	ES	779	713	4.09	780	785	125	400	3.8.6	NI	V 771	871	872	773	753	677	652	255	252	10.3	104	781

-10.2

-22.0

-16.5

-11.0

\_10.9

SAP2000 v6.11 - File:p2-rein - Resultant M22 Diagram (ENVE) - Ton-m Units

0.0

-5.5

7 - 1 - 76

11.0

16.5

22.0

# AERATION TANK BOTTOM SLAB LEVEL -0.35

# (ENVE COMBO MIN)

SY.			37	199			FILL S	1112	135		2	13-1-						1.8	SY.				100
578	957	958.	UT.	876	261	942	878	858	50	854	848	861	753	754	866	845	941	512	648	652	945	246	Rid .
80	155	754	867	873	559	718	175	855	512	54	652	861	351	12	863	843	131	542	MS	145	943	244	851
.KII	931	832	410	141	820	738	842	813	919	328	815	622	925	725	824	795	745'	550	797	an	A13	714	885
528	929	538	E38	639	935	936	839	818	\$17	918	812	819	3723	724	621	792	785	760	794	581	911	912	883
125	17	315	827	834	973	97H	836	867	915	315	807	414	\$21	772		787	763	784	771	798	989	510	500
254		115	762	786	391	942	785	766	812	878	778	274		154	778	758	81	82	758	762	685	664	714
m		154	179	283	879	1142	ns	715		365	715	m	821	602	293	253	577	898	755	757	683	654	751

SAP2000 v6.11 - File:p2-rein - Resultant M11 Diagram (ENVE) - Ton-m Units

-5.2

-2.6

0.0

-7.8


-13.0


-10.4

5.2

7.8

# AERATION TANK BOTTOM SLAB LEVEL -0.35 (ENVE COMBO MAX)





6.0

9.0

12.0

3.0


-3.0

0.0

7 - 1 - 78

18.0

21.0



19:23

	•		•	1881 1882 244 522 1885 2866 724	910 1000 141 140 140 140 140		+2.78
	•	٠	•	Plu In	64 64		-AB LEVEL
	•		*	HE DE HS	841 184		SOTTOM SI
	•			514 1285 11.14 245	124 105 104	1-4-7	NTATION TANK BOTTOM
8	•		•	151 1515 500 500	- 101 500 101	1 (S	PRIMARY SEDIMENTATION TANK BOTTOM SLAB LEVEL +2.78
	•		•	747	144 SH	t -	PRIMARY S
•	•		•	200 IBU 311	A 847 1845 1846		

SAP2000 v6.11 - File:p2-rein - Resultant M11 Diagram (ENVE) - Ton-m Units

SAP2000

	18.0
	13.5
4X M22)	9.0
ENVE COMBO MAX M22	4.5
(ENV	0.0
	4.5
	-9.0
	-13.5

SAP2000 v6.11 - File:p2-rein - Resultant M22 Diagram (ENVE) - Ton-m Units


22.5

PRIMARY SEDIMENTATION TANK BOTTOM SLAB LEVEL +2.78

	Ť.	Ē
	site.	ž
	1865	CALL
	1/2 1015 1015 974	VALI CALI 674
	2	2
	20 A	<u>R</u>
İ	ž	
	No 1811 1802	1 2
	91 1	2
	1.62	
	0.181	ii.
	113 1385 13.8 13.0 13.0 13.1 13.1 13.0 13.0 14.0 14.0 14.0 14.0 14.0 14.0 14.0 14	741 INI INZ
	2	lî.
-	7 8	
Ī	ä	B
	514	100 IO
	Wi (82) (82) Wi	£
t	18	Ē
	ä	1. E
	705	1417 1424
	28	R
	8	ŝ
		Ê
1	poa - 1817	747 1115 1115
- 1		- 1

SAP2000

March 6,2001 19:32



,
APARTA PARA
Ű.
Ċ
2
0

SAP2000

SAP2000

ž	꽃	2
Z	ĥ	ri,
5	ñ	ii,
ž	2.	ŝ
â	B	ដ
12	6	E
ī.	r.	2
2	ā	5
쾨	2	ž
ŝ	ñ	E
572	1	R
R	N	ā
R	R	R
킍	Ē	ž
2	×	75
8	R	52
2	2	ž
Ā	R	×
R	R	ŝ.
2	ž	S.
3	192	3
Ē	R.	787
Ē	<u>z</u> ,	2
2	2	2

(ENVE COMBO MAX M22)

COVER SLAB (LEVEL +6.9)

22.5

18,0

13.5

9.0

4.5

0.0

4.0

-9.0

-13.5

SAP2000 v6.11 - File:p2-rein - Resultant M22 Diagram (ENVE) - Ton-m Units

ř

SAP2000

COVER SLAB (LEVEL +6.9)

(ENVE COMBO MIN M22)

	ž	ź,	Z	
	2	5	Ť.	
	Б	512	12	
	<del>z</del>	2	2	
	17	E.	4	
	ī,	Ę	E	
	<u>F</u> ;	E	3	
	ß	ă	8	
	ñ	13	12	
	E	15	E	
	Ð	12	ħ	
+++	3	13	ñ	
	22	£	Z	
	Ē	E	202	
	÷.	* 18	ži,	
	£	Z	Ę	
	R	3	Z	
	ň	R	9i	
	Ħ	ji ji	IS.	
	12	ā		
	Ħ	12	2	
	E	Ri	Ē	
	Ē	ř,	E	
	2	5	ħ	

22.0 16.5 11.0 5.5 0.0 SAP2000 v6.11 - File:p2-rein - Resultant M22 Diagram (ENVE) - Ton-m Units -5.5 -11.0 -16.5 -22.0

ř

SAP2000

WALL OF PRIMARY SED. TANK & PIPE GALLERY AXIS 3 (Y= +4.5) (ENVE COMBO MAX, MIN M11)

**	ñ	N.	Ē	
7	5	5	5	
-	ž	Ð	5	
ä		×	R	
â	, and the second	×	ň	
-tri	E	Đ	5	
3	8	8	평	
ā	- Pre-	E	Ŕ	
×		R	R	
4	3	9	Э	0
E.	2	5	5	-
R	4	â	R	1 ar 42 - 5
¥	-	7	*	ac 4
-	2	\$	\$	
	ų.	3	ŝ	
R		R	R	
я		8	ž	
-	17		\$	
11	Ð	219	7	
1	iR	ล้	K.	
212	N	R	R	
11	9	Ê	9	
5	ž.	104	3	
M	Ŕ	Ř	편	14

21.0 18.0 15,0 12.0 9.0 SAP2000 v6.11 - File:p2-rein - Resultant M11 Diagram (ENVE) - Ton-m Units 6.0 3.0 0.0 -3.0

SAP2000

	ß	R	Æ	Ē.			
	¥	1	U	Đ			
	8	4	ų.	8			
	Ħ	B	я	R			
	Ħ	Ē	87	ā		(0	
	₽	8	þ	÷		4	
	4	U	5	Ð		,≍	
	ă	X	ñ	ž		WALL OF PRIMARY SED. TANK & PIPE GALLERY AXIS 3 (Y= +4.5)	
	x	ж.	ĥ	R		ERY A	
00	8	Ţ	ą	Ð		ALL	
14.2	Ţ	*	ð	5	57	6	1.1.1
	8	R	R	R	1-3.	& PIPE	
	ž	я	R	я		ANK	000
	Ę	Ş	ē	ð		<u> </u>	10.00
	₩ ₩	2	5	3		S	ļ
	N.	Ø	R	W		MARY	1
	' A	a	A	Ŗ		OF PRI	
	÷	5	ž	ŧ		E C	
	÷	IJ	¥	3		MAL	
	\$9£	ä	ī,	Ä			
	N.	X	ž -	Ŗ			
	en T	Ð	ş	19			
	ų	¥.	ŧ	Ξ			
	R	Ā	Ē, '	B	*		

22.0

16.5

11.0

9.9

0.0

-9.5

-11.0

-16.5

-22.0

SAP2000 v6.11 - File:p2-rein - Resultant M22 Diagram (ENVE) - Ton-m Units

7 - 1 - 87

SAP2000

	2010/01/02			
A	Ĥ	ž	Ę.	
Ę	4	Ø	ş	Ĩ
ų	ą	4	5	Î
Ħ	ħ	я	R	
R	Ħ	R	ā.	Ĩ
8	Ð	Đ	÷	
÷	U	5	ą	[
ă,	X	Ē	â	
ā -	¥	ĥ	R	
ġ	Ę	8	Ð	ľ
Ť	ŧ	õ	5	[
8	×	R	Ħ	
Ŧ	a.	*	N	-
ŧ	÷	Ę	8	Î
a	2	\$	8	Î
345	ß	×	×	0
R	R	a	ĸ	
11. V	Ū	_	~	î –
Ŧ	· ·	Ŧ	402	
2	8	2 2 7	÷	0
		the second s		•
2	ij	2÷	÷	*
10 10	2 U	351 445	ž	· · · · · · · · · · · · · · · · · · ·
5 %	X ¥	74 IS 25	E A R	0 0 0 0
10 N N	S X X X	24 14 24 D+		

SAP2000 v6.11 - File:p2-rein - Resultant M22 Diagram (ENVE) - Ton-m Units


(ENVE COMBO MAX M22)

WALL OF PRIMARY SED. TANK & PIPE GALLERY AXIS 3 (Y= +4.5)

+9.51

7 - 1 - 88

SAP2000



SAP2000

10 01	Ę	¢4			412			. 01	
a	13	3			3		1	ä	
110	ŝ	8			à			31	
	6	5			9			Q1	
100	10	3			ed.			IJ	
192	9	Fr			ii.			ß	
X	а	10			E			3	
14	ti	5			10			E	
		-			ñ			1.01	
7	5i	p.2	1		5			я	
H.	R	5			NV.			35	
2	U)	¥			113			63	
3	R	ž			5.2			64	
3	Б	ţ;	1					3	
2	ŭ	55			9			Ŗ	
1	H	3	1.1	10	HE			e	
	ä	B.	+	*	a			11	
2	5	ō			17 M			R	
2.7	З	1			125			ā	
PP4	5	õ			175			517	
104	85	ð			EK.			518	
2	3 -	A CONTRACTOR OF A CONTRACTOR O			205			3	
110	E	ā			212			245	
12	a	×			E	1		2	

VIBO MAX Miri)	
(ENVE CON	

21.0

18.0

15.0

12.0

9.0

0.6

3.0

0.0

-3.0

SAP2000 v6.11 - File:p2-tein - Resultant M11 Diagram (ENVE) - Ton-m Units

WALL OF PIPE GALLERY AND AERATION TANK( Y=+13)

SAP2000

10	Ę	Ę	ŧ	9
8	B	B	3	ä
25	25	3	ã	Э
451	6	÷	Ð	9
42	50	a	3	E
W.	3	ā	3	8
3	25	51	Ē	ā
151	E	ā	5	E
10	6	R	a	ē
3	5.	5	2	3
Ŧ	5î	ŝ	22	3
0	8	s.	a	e
429	ž	* · ·	/ В	ŧ
343	5	B	ž	3
2	5	5	Bl	ŝ
89	â	ā	ž	ε
40	ä	5	я	1
26	3	ä	£	3
14	3	ã	ŝ	ž
10	8	5	s	â
11	đ	đ	84	Ξ
8	3	E	5	ii ii
3	5	ň	5	3
414	23	B	3	2

SAP2000 v6.11 - File:p2-rein - Resultant M11 Diagram (ENVE) - Ton-m Units

0.7

29

5.0

0.0

-2.6

-6.2

1.8

-10.4

-13.0

WALL OF PIPE GALLERY AND AERATION TANK( Y=+13)

(ENVE COMBO MIN M11)

7 - 1 - 91

SAP2000

21	5	5		÷
2	191	B	R	Ē
215	***	3	2	H
41	415	R	Ð	9
62	4.0	a	3	5
115	9	ä	Ŕ	3
215	5	Ĩ	ž	ž
Ht	Li,	44	5	42
13	6	3	ŝ	ō
3	5	5	5	Э
Ŧ	S.	ñ	8	Е
0	5	18	TI I	10
57	ž	я	55	ē
36	E	5	iii	S.
100	5	£	N	5
409	а	5	314	8
101	ü	Ð	ŝ	515
£	R	ä	š.	3
3	5	ŝ	3	3
24 / N	5	8	ä	212
101	N/9	đ	đ	E
101	3	E	R	53
85	2	5.	5	R
454	515	Ħ	а	

SAP2000 v6.11 - File:p2-rein - Resultant M22 Diagram (ENVE) - Ton-m Units

22.6

18.0

13.5

0.6

4.6

0.0

4.6

0.6

-13.5

WALL OF PIPE GALLERY AND AERATION TANK( Y=+13)

(ENVE COMBO MAX M22)

SAP2000

		]	Э		IJ	\$	10	40
		-	ž		Я	0	11	52
		-	3		3	3	Ē	HI I
						the second s		
		_	3		Ð	ē	65	9
			5		ą	3	10	5
		1	З		R	ä	a	3
	~		ł		3	я	B	15 15
	Y=+13		3		8	414	5	414
	FANK(		ō		R	8	6	4
_	Z		3		5	R	5	3
A Acce	UTIO		E		8	ñ	5	HAT.
A A IN I	AERA	5	Ţ\$		-(0.0	R	5	e
(TAN IT COMPONING MINI Mar)	AND		¢	3	N.	н	R	3
C L	ER		> 3	10.3	ñ	5	5	3
ALM.	TLL		5	1.4	X	R	ž	35
17	WALL OF PIPE GALLERY AND AERATION TANK( Y=+13)	1408	đ		514	8	¥	55
	OF P		11	-Esi	B	D.	ž	18
	ALL		я		5	5	3	242
	12	1	3		2	K	E	245 242
		- 40.6	B		ŝ	5.	a	655
			1		ž	ž	ă	144
			ŝ	1	B.	2	3	105
			ŝ	1	ā	ž.	8	2
		T X 1	5		ā	ä	EI.	m
								24

22.0

16.5

11.0

10

0.0


9.5

-11.0

-16.5

-22.0

SAP2000 v6.11 - Filerp2-rein - Resultant M22 Diagram (ENVE) - Ton-m Units




% SAP2000

SAP2000


4.8 11 191 3 8.01-2 9 2 2.2 LONGITUDINAL WALL OF PRIMARY SED. TANK AND AERATION TANK X= +22 1211 1120 2.6 2 641 127 211 5 107 0.0 51.30 (ENVE COMBO MIN M11) ¥ ž 2 -2.6 2 191 1146 SAP2000 v6.11 - File;p2-rein - Resultant M11 Diagram (ENVE) - Ton-m Units 2-6.d--5.2 .7.8 6-2-6-5 -10.4 HI1 1116 2 12 -13.0 ì

SAP2000




7 - 1 - 96

© SAP2000



# PILE ARRANGEMENT CALCULATION



Preaction = 9.2 Ton/m<sup>2</sup> and Pile Capacity = 45(Ton)

⇒ one pile can bear for an area of 4.9m<sup>2</sup>

 $\Rightarrow$  R.C pile to be arranged as on drawing No. | -PE - WWTP - 252 - 01 -PE - WWTP - 252 - 02

#### CALCULATION FOR WASTEWATER TREAMENT PLANT STRUCTURES

#### AERATION TANK - PIPE GALLERY - FINAL SEDIMENTATION TANK

(The calculation based on Japanese standard)

#### 1-GEOMETRY DIMENSIONS FOR CALCULATION

(As shown on drawings attached):

Ground level:	GL =	+ 2.20
Ground water level:	GWL=	± 0.00
Bottom level of pipegallery:	BL =	-3.10
Bottom level of aeration tank	-0.25	
Bottom level of final sedimer	1.01	
Water level of aeration tank	+ 5.28	
Water level of final sediment	5.18	
Thickness of pipegallery both	0.60 m	
Thickness of aeration tank b	0.60 m	
Thickness of final sedimenta	0.60 m	
Cinder concrete thickness	0.10 m	
onder obnörete unickness	0.10 11	

And all other dimensions shown on the drawing attached

#### 2-PARAMETERS FOR CALCULATTION:

Concrete: C21,	Rn =	70 (Kg/cm2)		
	RS=	3.6 (Kg/cm2)		
Reinforcement type	All: Ra=	1600 (Kg/cm2)		
Back fill sand: $\gamma_s$ =	1.80T/m3	; Coeficient of earth pressure at rest	0.5	
Intern	al friction	20deg		

3-LOAD CALCULATION (BASE ON JAPANESE STANDARD):

## 3.1- Maximum loads from architect part to be taken in calculation as in analysis 3.2- Soil load:

#### In case of ground water level at 0.00 (Permanent case):

-Horizontal triangle distributed load due to earth under ground water level (Under aeration tank):

-Horizontal triangle distributed load due to earth under ground water level (Under final sedimentation tank):

ph:=0.8x3.8x0.5 + 3.8x1 =	5.32T/m2
-Uplift pressure to bottom of pipegallery:	
puplit=(Hground water)×1.0=	3.70T/m2

-Uplift pressure to bottom of aeration tank:


pupitt=(Hground water)x1.0= 2.5T/m2

## 3.3-Water load

According to highest water level and bottom level as inlustrated in the drawing, water loads to be calculated and shown on the attached drawing.

#### 3.4-Load of non-reinforced concrete layer on bottom slab:

(Due to mechanical supports and cinder concrete)



	1		/											
		2		124	1512	NN N	245	5						
		2+76		012	322	1005	191	5						-
		17		CIPALINA 200	0027 e	1211204 2741	12/241 216	2122 242628						-
	-			21% 12%2T	2851 2255229	224 2222	127-1272	dist 123674	÷	 Ξ.	-			-
	Ţ			ro Y ZZ	1	8	MIR	100	-	-3.1	-			-
		~		22	20	8	419	2354	Ì	- III	-			-
	1			ğ	8	2	410	1121		PILE GALLERY BOTTOM SLAB LEVEL -3.10	(ENVE COMBO MAX M22)			
				s .	8.2	14	Dia	412		A SL	MA			
				15.0		NACKA IFI	40-012	82. 0	00	10L	MBC			
	-			101 10100 101	1011	202 1000	1212-1112-122	ALS CONT ANTI	+16.8	BO	ы Ш			
 				2451	5	iz.	121	- Rei		LER	(ENV			-
		1	1	id:	2017	1206	(RL)	in in		GAL	-			
				8	5.0	2	2	dir		PILE	-			
				z	12	12	2	5						-
				Eeo	112	1	1	5	60					-
	+			а + 1 1 1	28 (C	111 K21 CR2	10 10 10	E E	+					-
 -	T			8	ž	21	it	R						
	1			3	E	Ē	742	8				Î	-	1
						-	-					~ <		-

-Uniform load:

q<sub>contaver</sub> 2.5x0.10= 0.25T/m2

3.5-Live load:

-Live load for all operating floor and walking way : q<sub>live</sub> = 0.50T/m2

4-ANALYSING BY SAP 2000: THERE ARE 3 COMBOS FOR ANALYSING AS ATTACHED HEREAFTER:

ALL THE LOADS, FACTORS, AND OTHER INPUT DATUM TO BE TAKEN IN ANALYSIS AND CALCULATED BY SAP 2000 The reaction results of combo 2 as attached shows that no uplift case happen to the structure

AERATION TANK - PIPE GALLERY - FINAL SEDIMENTATION TANK COMBOS

LOAD COMBINATION MULTIPLIERS

COMBO TYPE CASE FACTOR TYPE TITLE

COMB1 ADD In case of all tanks are full of water, no ground water outside SELF 1.0000 STATIC(DEAD) WATER 1.0000 STATIC(OTHER) CINDERCO 1.0000 STATIC(DEAD) MAN 1.0000 STATIC(LIVE) SOILPRES 1.0000 STATIC(OTHER)

COMB2 ADD In case of all tanks are empty, ground water level is up to 0.00 SELF 1.0000 STATIC(DEAD) CINDERCO 1.0000 STATIC(DEAD) SUSOILPR 1.0000 STATIC(OTHER) UPLIFT 1.0000 STATIC(OTHER)

COMB3 ADD In case of tank-empty and tank-full, no ground water SELF 1.0000 STATIC(DEAD) CINDERCO 1.0000 STATIC(DEAD) SOILPRES 1.0000 STATIC(OTHER) MAN 1.0000 STATIC(LIVE) WATER1 1.0000 STATIC(OTHER)

ENVE ENVE Max min of all combos to calculate for reinforcement COMB1 1.0000 COMBO COMB2 1.0000 COMBO COMB3 1.0000 COMBO

### 5-CALCULATION FOR BAR ARRANGEMENT:

Base on attached results of shell forces analised by SAP2000, choosing the most dangerous forces for calculation:

 $A_0 = M/R_n bh_0^2$ 

Where, M: Maximum bending moment(T.m) h<sub>o</sub>; Effective depth of bearing area(cm) he= (Element thickness-Cover thickness)

b: Width of calculated area(cm)

Required area of reinforcement:

Fa= M/yRaho Where:  $\gamma = 0.5 + ((1-2Ao)^{1/2})/2$ 


### 5-1 SLABS AND WALLS:

Moments	Values	Ao	γ	Fa	Bar arra	ngement	Remarks
	(T.m)			(cm <sup>2</sup> )	φ(mm)	a(mm)	
(Bottom	18.000	0.1116	0.941	24,92	20	125	
Slab level	15.400	0.0955	0.950	21.11	20	125	-
-3,10)	5.600	0.0347	0.982	7.42	12	125	
=0.60	7.600	0.0471	0.976	10.14	18	250	20/a.250
	-9.300	0.0473	0.976	11.24	16	150	
	-7.400	0.0376	0.981	8.90	12	125	
	-2.400	0.0122	0.994	2.85	12	250	125
	-10.750	0.0547	0.972	13.04	16	125	
Aeration	12.800	0.0794	0.959	17.39	18	125	
ank bottom	12.300	0.0763	0.960	16.68	18	125	
Level25	12.000	0.0744	0.961	16.25	18	125	
	-11.900	0.0605	0.969	14.49	16	125	
	-5.600	0.0285	0.986	6,70	12	150	125
0.6	16.300	0.1011	0.947	22.42	20	125	Not in Dwg
Final sed.	17.800	0.1104	0.941	24.62	20	125	
ank bottom	16.600	0.1029	0.946	22.86	20	125	Not in Dwg
slab	5,300	0.0329	0.983	7.02	12	125	
evel +1.01 0.6	-8.000	0.0407	0.979	9.63	14	125	
Bottom slab	-10,400	0.1029	0.946	18.09	18	125	
of water way	-9.300	0.0920	0.952	16.07	16	125	18 a 25
evel +4.7	5.600	0.0554	0.971	9.48	14	125	LANDAR CONTRACTOR
0.45	3.500	0.0346	0.982	5.86	12	150	e 125
Cover slab	-3,400	0.2159	0.877	16.16	18	125	AND PROPERTY.
of final sed. tank lv +5.9 0,2	1.400	0.0889	0.953	6.12	14	250	
Cover slab	-3.500	0.2222	0.873	16.71	12	50	Beam
of pipe ga.	-0.850	0.0540	0.972	3.64	12'	250	
level +6.4	-1.910	0.1213	0.935	8.51	12	125	
0.2	1.750	0.1111	0.941	7.75	12	125	
	0.750	0.0476	0.976	3.20	12	250	
Wall of	-17.600	0,1360	0.927	27.61	22	125	
Aeration Tank	-7.400	0.0572	0.971	11.08	22	250	
& pipe ga.	-5.800	0.0448	0.977	8.63	14	150	a125
0.5	12,300	0.0950	0.950	18.82	16	100	Wall

	8.200	0.0634	0.967	12.32	16	125	
	8.400	0.0649	0.966	12.63	16	125	
Wall of	11.500	0.0889	0.953	17.53	18	125	
Final sed. Yank	9.200	0.0711	0.963	13.88	18	150	a.125
& pipe ga.	-5,400	0.0417	0.979	8.02	14	150	a125
0.5	2.900	0.0224	0.989	4.26	14	250	
	-4.300	0.0332	0.983	6.36	12	150	e 125
Longitudinal	-15.800	0.1221	0.935	24.57	20	125	
wall	6.300	0.0487	0.975	9.39	14	125	
0.5	-12.400	0.0958	0.950	18.98	18	125	
	-7.400	0.0572	0.971	11.08	14	125	
	-6.600	0.0510	0.974	9.85	14	125	
	-4.800	0.0371	0.981	7.11	12	125	a 125
	3.100	0.0240	0.988	4.56	14	250	
	1.800	0.0139	0.993	2.63	12	250	

6- CALCULATION FOR PILE NUMBER (as attached sheets):

(Pile number to be decided by pile calculation sheet, please refer to pile calculation sheet for more information)



14.2

	1	R.	A COLUMN AND A COLUMN	an an	3-10-1-01-01-01-01-01-01-01-01-01-01-01-0		87	Eg.	En .				20. 1	970	72	1ª			
NUT AND AN AND AND AND AND AND AND AND AND		6		A R		H H	7.6	E E					un k	2 IZ	10	E E	8		
	Æ		-	10.00	1000	1	412	ē	Ŀ	E	ala	10.000	211	ii.	â		12	tur serie	iai un su

(ENVE COMBO MAX M11)

PIPE GALLERY BOTTOM SLAB LEVEL -3.10

15.4

13.2

11.0

(0) (0)

6.6

4.4

2.2

0.0

-2.2

Ť

SAP2000 v6.11 - File:p3-rein1 - Resultant M11 Diagram (ENVE) - Ton-m Units

22

10 10

27

2

2

112

20 102

02

N

Ē

12

177 198

ži.

H.

ē

ñ

161 821

12

R

10

\*

11 22

Z.

-

2

-2.4

SAP2000 v6.11 - File:p3-rein1 - Resultant M11 Diagram (ENVE) - Ton-m Units

4.0

2.4

0.0

-2.4

-4.8

-7.2

-9.6

-12.0

-14.4

ĩ



SAP2000

AERATION TANK BOTTOM SLAB LEVEL -0.25 (ENVE COMBO MAX M22)

142.3 +42.3

12 III III	ALE AND AND AND AND	174 274 254 254 254 254 254	in the second second second second	101 201 202 202 201 201 201 101	AND ZAN ZAN ZAN AND AND
54	n wa sta	1 A.	5 754 D6	8	ari
298 (22) 268 (154	0.0 mm 200 0	7.4 HIL 23	a and have a	ini tra tra	121 SIN SIN
RE	ii.	NR O	ž	ž	E
24 120	200 D.4	10 00	94.0 7.0	441	ILI INI
A		E	in	a.	z
IR IN IN W	40 44 40 EV	12 80 80 90	in the second	12 21 20 20-	241 129 250
2		R	w	100	N - 21

SAP2000 v6.11 - File:p3-rein1 - Resultant M22 Diagram (ENVE) - Ton-m Units

31.5

27.0

22.5

18.0

13.5

9.0

4.0

0.0

4.5

+12.8

SAP2000

AERATION TANK BOTTOM SLAB LEVEL -0.25

(ENVE COMBO MIN M22)

	Ř	1962	8 12	20	10	W12
	Ħ	90622	ΠĘŢ	102	2112	1287
	20	661	2112	12	5	10 M
-	1477 (1777	4.172 1.427	652 S.42	102	2022 2122	0.22 (122
		CONTRACTOR OF THE	A stranger to the local of the			13
	ħ	Ň	li i	1007	EK2	992
	E.	6672	262	Ei.	2012	1044
	ħ	7677	1412	E.	162	022
	2	841	2L	184	M	N.
	2	351	654	24 M	345	
	ē	8	No 92 0	No.	1919	121
	N <sub>D</sub>	222 022	15 - U	100 020 120	8	21
4	7.8	1221	1211	120	p.55 1286	9
	NU NU NU SU	àç	9.6	22	Ē	Ξ
	Ē	E	ž	ŝ	82	Ē
	B	Dia.	20	ŝ	6921	E
	2	256	275	2/2	E.	Z
	Ā	2	67	g,	ñ	R
	я	12	Ē.	Ř	E.	8
	ħ	ř.	h	2	z	2
	B	5	n	ři.	ā	8
	2	22	N.	62	22	ž
	412	72	B	E	12	52
	R	ā	ž	2	52	ž

SAP2000 v6.11 - File:p3-rein1 - Resultant M22 Diagram (ENVE) - Ton-m Units

8.0

4.0

0.0

4.0

-8.0

-12.0

-16.0

-20.0

-24.0

AERATION TANK BOTTOM SLAB LEVEL -0.25 (ENVE COMBO MAX M11)

15.4		ă.		3	nii Iii	8	
	1	B	the second	2014	19.1 1	200	Ř
13.2		SIZ	512	-1-	210	1	2422
÷		2.52	Non Lizz	in in	10 mm 10	E E	anten a
			R H	27.00		ă.	5
11.0		ł	g	an	124	<u>1</u>	Wei
		CR21	H	E.	5672	NIZ	A
		Ĕ	¥	192	12	220	anii (
8.8		-	745	Sind	S.L	710	tris.
		10	12	8	THE .	2	2
		- Market	and the	Li Ili	24, 122, 22.	112 02	20 m m
6.6		E	E	-	1. 92	2 2	2
			KI		ME.	Ē	R.C.
4,4	0.00	ILI	- 421	940	Pé	au re + AP	Ē
4	+ 16.3	ž	Ę	ĩ	R	22 F	E
		W	ñ	10	Ę	R	7
2.2		. 8	ß	Ē.	ħ	3	R
	1	8	21 24	7 2	B B	2	10 12
	-	2	22			2	N
0.0		8		a	ą	a	÷.
	1	2		13	3		2

SAP2000 v6.11 - File:p3-rein1 - Resultant M11 Diagram (ENVE) - Ton-m Units

-2.2

SAP2000

SAP2000

AERATION TANK BOTTOM SLAB LEVEL -0.25 (ENVE COMBO MIN Mit)

÷.	12	812	112	104	100
12	182	110	n D	111	012
1	R.	सर	2015	5	1172
102722	422402	9522522	1625.02	000.000	22112112
1677	N622	10	2100	191	H
51 1	14.17	NUT	E52	2002	Ť
611	NAR	ig.	52	1972	92
121	8	ē.	121	MC	N21
8 .	7	5.0	12 E	94	12.0
K.	10	2	20	1941	7Ca
9241 124	20 212	80.02	621 624	N21 1241	001.000 100
Ē			121	Ē	E.
1176	E I	PH H	34	8	28.41
10.11	- 041	1941	pe	96	*
22	ä	2	2.0	ŝa	\$4
214	NA.	E.	Ę	52	19
SI .	82	ĥ	ř.	R	2
07 172	107 F24	812 517	100	N ig	3 2
10.2011	ž	2	n	2	1
542	R	8	2	7	2
Z	4	ā	ħ	2	22

40 2.4 0.0 -2.4 -4.8 SAP2000 v6.11 - File:p3-rein1 - Resultant M11 Diagram (ENVE) - Ton-m Units -7.2 9.6--12.0 -14.4

	1116	10.6	1112	Kil.
	120	IN1	9407	116
	202 21222-0 2942	ME DESERT	DIZ NOTICZ NZZ	2201 22120216 2226
	12 412	2125	2 1222	12 8222
	882	ß	222	52
	1116 110	1746	1215	202
	1174	ellei	- FILS	tip
	2	ß	142	MO
74		200012	Yest	1
	11 11 110	10 E	111 211/124	10
	1 44	E	1 121	ITAL ITA MARAN UN
	NIG - 64	Ē	at in	an
	R	E.	24	E
	R	an.	20	12
->0	ñ,	R	×	E
-	100 100	N.	10	
		2	NI 20	
	422 162	105 254 291 MI	2 202	5
	2	Æ	14	Ē

FINAL SED. TANK BOTTOM SLAB LEVEL +1.01

(ENVE COMBO MAX M22)

SAP2000 v6.11 - File:p3-rein1 - Resultant M22 Diagram (ENVE) - Ton-m Units

31.5

27.0

22.5

18.0

13.5

0.6

4.5

0.0

4.6

ĩ

1112	8467	1102	1922	
100	22	¥12	512	
	1000			
07-42214	2012246	202202	2110234	
127	1221	R	8072	
877	1222	2115	Ĥ	
2115	1911	1105	2228	
212	295	shi	1242	
90	905	82	801	
M	1521	<u>82</u>	041	
100 1004	279.074	210 012	191 191	
20	111	E	100	
Da	100	124	101	
1921	8/21	E	124	
£	×.	K.	12	1
		×	12	16
ñ	6	R	Ŗ	
£	N	R	ā	
2	8	Ř	R	
÷	E,	ž,	12	
Ę	2	20	8	
642	342	Ê	В	
112	12	ž	12	

1014

2222

1002


5772

## FINAL SED. TANK BOTTOM SLAB LEVEL +1.01 (ENVE COMBO MIN M22)

8.0 4.0 0.0 -4.0 0.8-SAP2000 v6.11 - File:p3-rein1 - Resultant M22 Diagram (ENVE) - Ton-m Units -12.0 -16.0 -20.0 -24.0

7 - 1 - 113

SAP2000



15.4

SAP2000

	MIZ	412	2012 2012	23.05
	222	19 2	572	2962
	2128	002	ž	X
	9.124122	211 244	orana	WC2DC2
	1212	NHZ	672	100
	1200	111	1214	522
	10.6	2202	222	572
	2741	1785	Ē	26
	120	016	Ē	840
	ž	1641	2	52
	100.0051	1279 1754	1195	20.074
18:0	112	1272	\$211	177
T	SMA	121	141	E
	20	PTR.	55	1715
	R	12	Fi.	15
2	R.	942	R	ä
-1	E	3	R	ň
	s.1 19	19 10 10	*	R
			ž	
	27	8	推	2
	ii,	22	22	12
	12	12	ñ	3

FINAL SED. TANK BOTTOM SLAB LEVEL +1.01 (ENVE COMBO MIN M11) SAP2000 v6.11 - File:p3-rein1 - Resultant M11 Diagram (ENVE) - Ton-m Units

0.4

2.4

0.0

-2.4

-4.8


-7.2

9.6-

-12.0

-14.4

		110				-	
+-4 +-8	3+3.1	424 m	24-9 2431 1402-135 248	4.04			Y LEVEL +4.7 IIN M22)
0. tT	\$+3.5	4.5.6 2001 (2002) 200	2181 2012 2105 2105 A	-9.4			BOTTOM SLAB OF WATERWAY LEVEL +4.7 (ENVE COMBO MAX, MIN M22)
			107 53				BOTTOM (E
		* 12 10 10 10 10	13				



24.42	11.2	10.2	202	
1000	R.	122	1257	
3999	2440	2014	1.92	1
Condition of	an these	ant sasters	11509490	
2002	Net.	date 0	84.6	
25.04	2445	1	PU4	
1977	N.	1mL	1212	
2126	2151	2112	2128	
21.67	2148	210	2127	
144	19:2	2146	2112	÷
11 11 11 11 11	21160	CI-CE-CE-CE-CE-CE-CE-CE-CE-CE-CE-CE-CE-CE-	STOC 25	-3.4
2125	2138 2136212	12	2:23	-1
212	512 2	42	1:17	
212	2120	2.01	171	
8	E.	10	14	
2	z	Ľ	0	
2	2	5	25	9-1
2	10 2	14	18	en I
5	15	2	=	
2		a	2	
\$	4	\$	10	

COVER SLAB OF FINAL SED. TANK LEVEL +5.9

(ENVE COMBO MIN M11)

SAP2000 v6.11 - File;p3-rein1 - Resultant M11 Diagram (ENVE) - Ton-m Units

4.0

2.4

0.0

-2.4

0.7


-7.2

-9.6

-12.0

-14,4

×





COVER SLAB OF FINAL SED. TANK LEVEL +6.4 (ENVE COMBO MIN M22)

SAP2000 v6.11 - File:p3-rein1 - Resultant M22 Diagram (ENVE) - Ton-m Units

8.0

4.0

0.0

4.0

-8.0


-12.0

-16.0

-20.0

-24.0

ř



×.

13.5 01 LOVER SLAB OF PIPE GALLERY LEVEL +6.4 (ENVE COMBO MIN MAI) 221 01-0-76

42.01				
ng na wa	2.0	10.54 1	61.67	2728
R 14	ng oa na uwua	Ē	2.2	11/2
114 814924	RR	the	20 53	2 14
andara I	0.000	a second .	010	14212
122	NUT 6	The second	84.2	21 IS
ha	and and	Ē	ahat.	27.09
su sa sa uz	U.	12,2	942	1200
na fais	AE.	2115	2.0	2141
1512	THE DAY AND TOT HADAN THE THE TAN	1.80	245	2.44
12000	R	me man unant	510	12
201 112629 2124	INCON	12.0512	CH 2 1912/012	29120012
id.	202	and a	512	8112
201	1	47.2	2155	9512
CUT ANT ANY THE	U anz	9.2 2	5115	Mitz
an de	88	54	3	ž
31	ur fee	8	ä	3
- E	3	and and	0- 10	5
100	Sis Sec	8	0.0	8
ži,	E	3/2	5	Ð
. 3	in ha	ß	ŧ,	13
and an	-	2	2	4/3



(ENVE COMBO MIN M11)

SAP2000 v6.11 - File:p3-rein1 - Resultant M11 Diagram (ENVE) - Ton-m Units

40.

2.4

0.0

-2.4

4 0

-7.2

-9.6

-12.0

-14.4

ĩ

SAP2000

	240	R	BIT	815	25.16	1912	8
	25.1 61	14	233	ā	DAT .	à	1.10
	10	5	E 22	201	2	h	278
	205 215		1111 1111	172 192	1012 1012	10.0	12 15
	198	*	N.	×.	5962	H	ŝ
S	102 103	214	2458	ż	181	9	ā
1	200	2	Line of the second seco	2	2	R >	1
	210	314	12	ž	1041	aNI	E
	12	PA -	IM	3	8-11 1	241	E
	INI I	0	Ē	E.	E	205	jî.
	State of the last	14. 14	IPA IFA	500 IN	irisk pro	1000	Inte Crist
	1.1	10071-00	De	100	540	001	Ē.
	IN TU	Ē.	2 N	g	21,6	1981	R.
	12.0	2	50 E	59	1.54	111	<u>R</u>
	R 6	2	212	g	¥.E	R	X
	11 22	Ŗ	215	JIF.	Ħ	W	ä
	20	2	315	212	ž,	CR	Ŧ
		ă	ži –	₿.	â	CI S 810	KA WK
	1000	2	×	3	11	12120302	States and States
	111	11A	E.	10	÷	ж	2
	19	Э	*	8	8	R	*
	3 3	7	1	121	5	2	

0.0 4.5 9.0 13.5 18.0

SAP2000 v6.11 - File:p3-rein1 - Resultant M22 Diagram (ENVE) - Ton-m Units

-4.5

31.5

27.0

22.5

+ 8.4

+12.3

(ENVE COMBO MAX M22)

WALL OF AERATION TANK AND PIPE GALLERY Y =+12.75

----

SAP2000

	175	2	άž	12	90 22	1912	21/2	
	201	15	5	ā	ij.	121	2942	
	12	5	52 2	ž	12	442	2772	
	202 2315			121 222	1027 1021	15.02 APG	75.2 855	->
- 11	0.002	1	262	2002	192	2019	1	
	207	124	892	R	ň	1913	ñ	
	242	104	152	9972	9	165	212	
	56	ME	1141	1746	NI O	Ē	E	
	1	24	THE .	ani	au i	26	E.	
	181	112	Ē	E	Ę	114	2	
	241 142	100 100	⇒ E	50 21	810 P21	1002 1200	ma con	> 3
- 81	7.0520	35	12	22	2	Ξ.	Ē	1
	16.55	107	34	96	26	100	2841	
	10.1	NR.	56	g	15	6281	E	
	S 7	12	717	30	314	я	R	
	9 2	8	115	315	317	я	X	
	a 1		315	211	R	я	¥	
		Ť	Ā	ž	R	4	¥.	
	ž i	9.9	3	21	212	345	ž	
-	3	1	Ξ	â	7	R	ж.	
	1	9	3	8	ž	a	я	
-	3 3	3	ī	5	<u>n</u>	'n	7	X

(ENVE COMBO MIN M22)

8.0

4.0

0.0

4.0

0.0

-12.0

-16.0

-20.0

-24.0

WALL OF AERATION TANK AND PIPE GALLERY Y =+12.75

SAP2000 v6.11 - File:p3-rein1 - Resultant M22 Diagram (ENVE) - Ton-m Units

SAP2000

$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	1412	з	222	112	214	241	2427	
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	192	D.	121	Ē.	1701	ą	812	
W       W	251) 520	E	171	10	-	222	12	
W       W	5 25.5	E .	NIZ 7	N.	10	5122 6	i.	
W     W <td>100 C 110</td> <td></td> <td>States and states of the</td> <td></td> <td></td> <td>1000004000</td> <td></td> <td></td>	100 C 110		States and states of the			1000004000		
10     <			-	RI .	12	N	*	
W     IM     HM     HM <t< td=""><td></td><td></td><td>10</td><td>Ξ.</td><td>ā</td><td>Ę</td><td>N.</td><td>1.84</td></t<>			10	Ξ.	ā	Ę	N.	1.84
U     U <td>200</td> <td>8</td> <td>202</td> <td></td> <td></td> <td>Ē</td> <td>au</td> <td>-1</td>	200	8	202			Ē	au	-1
10         114         121         221         121	195	ā	1921	ž	NH	and.	/	
10         114         114         127         125         126         126         126         126	and the	ส	Int	S.	1.0	191	IMA	
10         114         114         127         125         126		1	Ē	E	tin a	12		
Tr     <		345	1000					
Th         TH<	10000	2	121		N.N.	ŧ	ŝ	
11     11     12     12     13       11     11     11     11     11     11       11     11     11     11     11     11       11     11     11     11     11     11       11     11     11     11     11     11       11     11     11     11     11     11       11     11     11     11     11     11       11     11     11     11     11     11       11     11     11     11     11     11       11     11     11     11     11     11       11     11     11     11     11     11       11     11     11     11     11     11       11     11     11     11     11     11       11     11     11     11     11     11       12     13     14     11     11     11       13     11     11     11     11     11       14     11     12     12     12     12       14     14     14     14     14     14	1725	2	DM.	2	1921	Dig.	17th	
TUP         HM         TUP	M	R	ž.		4	1841		5
TUP         TUP <td>1</td> <td></td> <td>SDAL</td> <td></td> <td></td> <td>Ē</td> <td>n</td> <td></td>	1		SDAL			Ē	n	
10         14         12         12           11         11         11         20           11         11         21         21           12         21         21         21           22         21         21         21           22         20         11         21           22         20         11         21			11E	at .	HC	R	1-2-	
	11/11	*	,ut	ψc	н	×	3	
A A A A A A A A A A A A A A A A A A A	11 12	11	315	e.	R	5	Ā	
e a constant de la co	10.1	Ĩ4					115	
	1000		10000000	120000	State of the second			
No. 19 19 19 19 19 19 19 19 19 19 19 19 19	10	*	6	2	III	141	2	
	N:	ġ	ā	Ξ	ž	110	N	

SAP2000 v6.11 - File:p3-rein1 - Resultant M11 Diagram (ENVE) - Ton-m Units

15.4

13.2

11.0

8.8

6.6

4.4

2.2

0.0

-2.2

(ENVE COMBO MAX M11)

WALL OF AERATION TANK AND PIPE GALLERY Y =+12.75 8:5-12:00

40.00

2.4

0.0

-2.4

4.0

-7.2

0.0

-12.0


-14.4

SAP2000 v6.11 - File:p3-rein1 - Resultant M11 Diagram (ENVE) - Ton-m Units

(ENVE COMBO MIN M11)

	100	0000	Saw and		0015128	19	
	212	ž	20 20	10	ti D	5	
	1248	12.12	12	ii	252	141	614
	1	2	12	ă	192	ŝ	1 10
	77.62	22	122	3	ź	ŝ	1 1
	2520	22	1	2	120 223	17	645 175
	102	5	32	2962	14.52		100
	152	121	ň	ž	\$112	sie	615
	212	162	R	8402	1444	2	10
e L	E	Ē	M N	ž	1949	r.	313
-	R	14	Rui	2	the	Ā	1
	20	94	E	266	i.	1	1.4
	Ť	0922	Ē	E	Ē		
	The C	12	12.0	1921	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	19	11 100
	161	12	2541	22	195	(C)	10
	INK	100	216	90	ž	ñ	20
	Ē	6481		R	545	21	100
4	-1_	8	T.	CE	212	15	10
t m	X	712	317	SIE	315	88	500
12	ā	я	57	417	115	11	
	4	E14 840	8	N	Ñ	ň	-
8	X	25	212	3	21	2	-
	7	R	Ŧ	ß	E	2	-
	я	8	B	ß	19	691	-
4	21	8	E	E	X	7	

SAP2000



7 - 1 - 127

SAP2000

2515	ii.	8	
12	Ŋ	a	l
ā	21	E	
91 91	292 Cili	TH ZIN ZI	
22	24 22	tin Ing	
24	11	10	
ž	2	1	
192	1962	22	
N	Ē	M	
N	R	R	
R	÷ 62	Ē	_
 2102	1112 CU10 11102	110 310 200	
100 C			
Ē	M	E.	
2,47	56. 1	1	
ii.	1994	1961	
×	я	R	
Ä	я	я	
я	я	я	
2	Ř	R	
12 12	2	E E	
<b>F</b> i	ñ	R	
E	E	R	
77	24	E ×	

7 - 1 - 128


March 8,2001 16:57

SAP2000

SAP2000 v6.11 - File:p3-rein1 - Resultant M11 Diagram (ENVE) - Ton-m Units

# (ENVE COMBO MAX M11)

WALL OF PIPE GALLERY AND FINAL SED. TANK Y=+21.25



SAP2000

SAP2000 v6.11 - File:p3-rein1 - Resultant M11 Diagram (ENVE) - Ton-m Units

4.8

2.4

0.0

-2.4

4.8

-7.2

9.6-

-12.0

-14.4

WALL OF PIPE GALLERY AND FINAL SED. TANK Y=+21.25


(ENVE COMBO MIN Mrt)

	2145	and a	24L
	1514	188	3
	10	32	2540
	105 250	202 012	2114 2544
	246 25	10 PE	22
	1917	196	Ħ
41	02	7912	24
14	N	TREE .	5002
	THE	le:	2002
	R	10 10	Ē
	2182	842 (147) 1862	2002 2014
	101 2006 2012	and the second se	1442 AM
	130	N.	8
	192	iž	1941 .
	1921	1651	1001
	Ħ	N	R
	N.	н	я
	R	R	R
	245 246	ii. fe	14 N
	B B	R II.	R
	25	Ē	847
	3	75	25


SAP2000


SAP2000

1-6.6 8.0 1919 1006 22 Ē 1.9ž Ē 12 R 5 1213 1910 4.0 6 5 1736 ₽ LONGITUDINAL WALL OF AERATIONTANK AND FINAL SED. TANK X=+2.2 3 켵 226 -100 R -178 1943 ŝ 202 ž 2 ŝ 0.0 4.0 (ENVE COMBO MIN M22) 9.0 SAP2000 v6.11 - File:p3-rein1 - Resultant M22 Diagram (ENVE) - Ton-m Units 2222 -12.0 1 1712 101 4 22 E 5 111 3 15.2 -16.0 11 23.07 ŝ 1211 5 2115 1 ŝ 3 2001 -20.0 MIR 212 398 1845 ž 2112 Ē 1843 ł 1911 -24.0



SAP2000





	9	L
	1	1
J	7-	Т
	1	٦
	,	-1

SAP2000 v6.11 - File:p3-rein1 - Resultant M11 Diagram (ENVE) - Ton-m Units

4.8

2.4

0.0

4.2-

4.8

-7.2

-9.6

-12.0

-14.4

LONGITUDINAL WALL OF AERATIONTANK AND FINAL SED. TANK X=+2.2

(ENVE COMBO MIN Mi1)

7 - 1 - 134

ì


SAP2000 v6.11 File: F3 Ton-m Units FAGE 1 March 9, 2001 15:50 AERATION TANK - FIPS GALLERY - FINAL SED. TANK For calculating pile quantity CONBINATION MULTIFLIERS LOAD 0.00990 TYPE CASE FACTON TYPE 71716 000191 ADD In case of all tanks are full of water, no ground water outside 1.0000 SELF STATIC (DEAD) WATER CINDERCO STATIC (OTHER) STATIC (DEAD) 1.0000 STATIC(LIVE) STATIC(OTHEN) MAN 1,0000 SOILPRES 1.0000 00892 ADD. In case of all tanks are empty, ground water level is up to 0.00 STATIC(DEAD) STATIC(DEAD) STATIC(OTHER) 1.0000 SELP CINDERCO SUSOILIN 1.0000 UPLIFT 1.0000 STATIC (OTHER) COMB 3 ADD In case of tank-empty and tank-full, no ground water 1.0000 1.0000 1.0000 1.0000 STATIC(DEAD) STATIC(DEAD) STATIC(OTHER) SELP CINEERCO SOLLERES STATIC(LIVE) STATIC(OTHER) MAN NATER1 1.0000 PILECOMB ADD For calculating number of piles 1.0000 1.0000 1.0000 1.0000 SELF STATIC (DEAD) STATIC (OTHER) STATIC (DEAD) STATIC (LIVE) NATER CINDERCO MAN SOLLPRES 1.0000 STATIC IOTHERI

SAP2000 v6.11 File: P3 Ton-m Units PAGE 2 March 9, 2001 15:50

ABBATION TANK - FIFE GALLERY - FINAL SED. TANK For calculating pile quantity

JOINT REACTIONS

JUINT	LOAD	F1	F2	P.3	M1	H2	N3
3	CONSI	724.1200	1399.9903	2134.1050	0.0000	0.0000	0.0000
а	CON8.2	198,7584	399.6479	553,6505	D.000D	0.0000	0,0000
3	CON53	511.5924	1057.6506	1860,6975	0.0000	0.0000	D.0000
3	PILECOMB	724,1208	1399.9983	2134.1050	D_000D	0,0000	0.0000
9	const.	-41.1836	-754,5016	2009.3667	D.0000	0.0000	0.0000
	C0H32	36,5920	-290.4719	450,8175	D.00DD	0.0000	0.0000
9	C0H053	230.0340	-1156,5034	1796.3126	0,0005	0,0000	D.0000
9	PTLECOM8.	-41,1836	-754.5016	2009.3667	D.00DD	0.0000	0.0000
2100	00991	-724,1241	1400.0000	2134.1042	0.0000	0.0000	0.0000
2100	C0M32	-190.7507	399.6480	593,8503	0,0000	0.0000	D.0000
2100	C0999-3	-511.5953	1057,6517	1560.6960	0.0000	0,0000	0.0000
2100	PILECOM	-724,3241	1400.0000	2134.1042	0.0000	0.0000	D.000D
2144	0.0691	41,1970	-754,4969	2009.3877	0.0000	0.0000	0.0000
21.44	000432	-36.5017	-290.4714	450,8176	0,0000	0.0000	D.000D
2144	0.0149-3	-230.0809	-1156,4993	1796.3134	0.0000	0.0000	0.0000
2144	PILECOM	41.1970	-754.4969	2009.3677	0.0000	0.0000	0.0000



-PE - WWTP - 252 - 02

### CALCULATION FOR WASTEWATER TREAMENT PLANT STRUCTURES

### FINAL SEDIMENTATION TANK

(The calculation based on Japanese standard)

### 1-GEOMETRY DIMENSIONS FOR CALCULATION

(As shown on drawings attached):

Ground level: GL = Bottom level of final sedimentation tank: BL =

Water level of final sedimentation tank:

Thickness of final sedimentation tank 0,60 m

And all other dimensions shown on the drawing attached

### 2-PARAMETERS FOR CALCULATION:

Concrete: Grade C21,	Rn =	70 (Kg/cm2)
	RS=	3.6 (Kg/cm2)
Reinforcement type JIS:	Ra=	1600 (Kg/cm2)
Back fill sand: ys= 1	.80T/m3	; Coeficient of earth pressure at rest K 0.5
Internal fri	ction	20deg

### 3-LOAD CALCULATION (BASE ON JAPANESE STANDARD):

### 3.1-Water load

According to highest water level and bottom level as inlustrated in the drawing, water loads to be calculat and shown on the attached drawing.

+ 2.20

1.15

5.05

### 3.2-Live load:

-Live load for all operating floor and walking way : qive = 0.50T/mz

4-ANALYSING BY SAP 2000: THERE ARE 3 COMBOS FOR ANALYSING AS ATTACHED HEREAFTER:

ALL THE LOADS, FACTORS, AND OTHER INPUT DATUM TO BE TAKEN IN ANALYSIS AND CALCULATED BY SAP 2000 There no need to check uplift for final sed. Tank, because the tank is to be put not deeply in ground.


### LOAD COMBINATION MULTIPLIERS

COMBO TYPE CASE FACTOR TYPE TITLE

COMB1 ADD All tanks full of water SELF 1.0000 STATIC(DEAD) WATER 1.0000 STATIC(OTHER)

COMB2 ADD tan full, tank empty SELF 1.0000 STATIC(DEAD) WATER1 1.0000 STATIC(OTHER)

ENVE ENVE max min of combos to calculate for reinforcement COMB1 1.0000 COMBO COMB2 1.0000 COMBO



### **5-CALCULATION FOR BAR ARRANGEMENT:**

Base on attached results of shell forces analised by SAP2000, choosing the most dangerous forces for calculation:

A<sub>o</sub> = M/R<sub>n</sub>bh<sub>o</sub><sup>2</sup> Where, M: Maximum bending moment(T.m)

h<sub>o</sub>: Effective depth of bearing area(cm)

h<sub>a</sub>= (Element thickness-Cover thickness)

b: Width of calculated area(cm)

Required area of reinforcement:


Fa= M/yRaho Where: y = 0.5 + (( 1-2Ao)<sup>1/2</sup>)/2

### Moments Values Fa Ao r arrangement γ (cm<sup>2</sup>) (T.m) ò(mm) a(mm) (Bottom -10.500 0.0651 0.966 14.15 16 125 4.89 Slab level -4,100 0.0209 0.989 12 200 a125 +1.15)9.500 0.0589 0.970 12.76 16 125 0.6 0.0780 Wall of -10.1000.959 15.30 16 125 Tank 0.5

### 5-1 SLABS AND WALLS:

### 5- CALCULATION FOR PILE QUANTITY (as attached sheets):

(Pile number to be decided by pile calculation sheet, please refer to pile calculation sheet for more information)



SAF2000 v6.1: File: F-S-TANK Ton-m Units FAGE 1 March 9, 2001 17:35 FIRAL SED. TANK


3 0 A D	COM	BINAT	соя я	0171911	8 K 3
COMBO	TYPE	CASE	FACTOR	TYPE	TITLE
соива ,	ADD	SELF NATER	1.0000	STATIC(DEAD) STATIC(OTHER)	All tans full of water
COMB2	ADD	SELF WATER1	1.000D	STATIC(DEAD) STATIC(OTHER)	tan full, tank empty
ENVE	ENVE	C0MB1 C0MB2	1.0000	00000	max min of combas to calculate for reinforcement

SAF2000 v6.11 File: F-8-TANK Ton-m Units FAGE 2 Narch 9, 2001 17:35

FINAL SED. TASK

SHELL ELENENT RESULTANTS

SHELL	LOAD JOINT	¥11	\$22	P12	HL1	M22	M12	V13	V23
239	Ninina	-3.39 ENVE	-2.83 ENVE	-4.51 ESVE	-2.08 ENVE	-10.16 EMVE	-8.439E-D3- ENVS		-4.38
239	Maxima	3.34 SNVE					4.7458-02	2.7518-02 ENVE	L.141E-02 ENVE
240	Ninima	-1.66 ENVE	-2.60-5 ENVE	. G3DE-01	-1.99 ENVE	-10.08 ENVE	-2.138E-02 EMVE	0.00	-4,18 ENVE
246	Maxima	3.04-4. ENVE	964E-D1 S		1.4618-03- ENVE		2.130E-02		1.253E-02 ENVE



SAP2000 v6.11 - File:f-s-tank - Resultant M22 Diagram (ENVE) - Ton-m Units

-4.40

-6.60

-8.80

7-1-141

March 9,2001 17:50

