

Japan International Cooperation Agency
National Water Resources Board
The Republic of The Philippines

**The Study
on
Water Resources Development
for
Metro Manila
in
the Republic of the Philippines**

Final Report

**Volume II
Master Plan Study
Main Report**

March 2003

Nippon Koei Co., Ltd.
NJS Consultants

S	S	S
J	R	
03	-	43

List of Volumes

Volume I : Executive Summary

Volume II : Phase 1: Master Plan Study - Main Report

Volume III : Phase 1: Master Plan Study - Supporting Report

Volume IV : Phase 2: Feasibility Study - Main Report

Volume V : Phase 2: Feasibility Study – Supporting Report

Volume VI : Phase 2: Feasibility Study - Data Book

The cost estimate is based on the price level and exchange rate of June 2001.

The exchange rate is:

US\$1.00 = PHP52.0 = ¥125.0

PREFACE

In response to a request from the Government of the Republic of the Philippines, the Government of Japan decided to conduct the Study on Water Resources Development for Metro Manila in the Republic of the Philippines and entrusted the study to the Japan International Cooperation Agency (JICA).

JICA selected and dispatched the study team headed by Mr. Michito Kato of Nippon Koei, Co., LTD. (consisting of Nippon Koei, Co., LTD. and NJS Consultants) to the Philippines, three times between March 2001 and February 2003. In addition, JICA set up the advisory committee headed by Mr. Takuji Oikawa, Director, Ikeda Dams and Canal Integrated Office, Water Resources Development Public Corporation between March 2001 and March 2003.

The team held discussions with the officials concerned of the Government of the Republic of the Philippines, and conducted field surveys at the study area. Upon returning to Japan, the team conducted further studies and prepared this final report.

I hope that this report will contribute to the promotion of this project and to the enhancement of friendly relationship between our two countries.

Finally, I wish to express my sincere appreciation to the officials concerned of the Government of the Republic of the Philippines for their close cooperation extended to the Study.

2003 March



Takao Kawakami
President
Japan International Cooperation Agency

March 2003

Mr. Takao Kawakami
President
Japan International Cooperation Agency (JICA)
Tokyo, Japan

Letter of Transmittal

It is a great pleasure that we submit herewith the Final Report of the "Study on Water Resources Development for Metro Manila in the Republic of the Philippines".

The main objective of the Study was placed on the formulation of water supply development plan for the Metro Manila and its vicinity for meeting the water demand up to the year 2025. The Study prepared in its Phase I a master plan for the water resources development in the Agos River Basin and the associated water conveyance facilities, and successively in the Phase II a feasibility study for the priority project selected from the master plan. The Report presents the outcomes of the master plan and feasibility study.

We hope that this Report will be helpful for the realization of the project proposed in this Study. We believe that the successful undertaking of the proposed project would assure stable water supply in the Metro Manila area in the long term and thus contribute to the further socio-economic development in the region.

We wish to express our sincere gratitude to the personnel concerned of your Agency for the guidance and support given throughout the Study period. Our deep gratitude is also expressed to the National Water Resources Board and other concerned authorities of the Government of the Republic of the Philippines, JICA Philippines Office and the Embassy of Japan in the Philippines for their close cooperation and assistance extended during the course of the Study.

Very truly yours,










Michito Kato
Team Leader

The Study on Water Resources
Development for Metro Manila
in the Republic of the Philippines



LEGEND

-  River
-  Province Boundary
-  Catchment Boundary
-  Major Road
-  Road
-  City



The Study on Water Resources Development
for Metro Manila in the Republic of the Philippines

VOLUME II MASTER PLAN STUDY- MAIN REPORT

SUMMARY

Study Activities in Master Plan Stage: (Chapter I)

1. As the first phase program of the Study, the JICA Study Team carried out field investigation works and home office studies during the period from March 2001 to November 2001. The main subject of the first phase study was the preparation of a master plan for the water resources development for Metro Manila towards the year 2025 by exploiting the water resources in the Agos River Basin. This Volume II summarizes the outcomes from the master plan study. The report was submitted to NWRB as an Interim Report for the Study and explained to the Philippine side in January 2002.

Socio-Economic Framework: (Chapter II)

2. The future population in the Study area covering NCR, Rizal Province and a part of Cavite Province was projected for the period up to year 2025, the target year of the present Study. The projection aims at providing data for the estimate of future water demand in the Study area at city/municipality level.

Population Projection up to 2025

(Unit: 1,000)

	Populati on 2000 (Census)	Projected Population					Annual Growth Rate	
		2005	2010	2015	2020	2025	2000- 2010	2010- 2025
The Philippines	76,499	84,241	91,868	99,016	105,507	113,661	1.8%	1.4%
Region IV	11,794	12,860	14,525	16,357	18,225	20,320	2.1%	2.3%
NCR *1	9,933	10,680	11,291	12,434	12,854	13,241	1.3%	1.0%
Cavite Province *2	2,063	2,357	2,411	2,715	2,987	3,250	1.6%	2.1%
Rizal Province *3	1,707	2,152	2,681	3,409	4,222	5,139	4.6%	4.4%
Study Area Total	13,073	15,189	16,383	18,558	20,063	21,630	2.3%	1.9%

Note: *1 12 cities and 5 municipalities
*2 1 city (Cavite) and 5 municipalities
*3 1 city (Antipolo) and 13 municipalities

As shown above, the population of the Study area is projected to increase at 2.3% and 1.9% for the periods of 2000-2010 and 2010-2025, respectively.

3. Gross Regional Domestic Product (GRDP) in the Study area was projected for the three major sectors of agriculture, industry and service for the period up to the year 2025. The GRDP projection is also needed to provide basic data for the estimate of future municipal and industrial water demands in the Study area.

GDP/GRDP Projections for 2000-2025

(Unit: Billion Pesos)

	2000	2005	2010	2015	2020	2025	Growth 2000-25	Share to Nation 2025
Philippines (GDP)	962	1,236	1,604	2,097	2,760	3,652	5.5%	
NCR	294	388	520	696	933	1,250	6.0%	34.2%
- Agriculture Sec.	0	0	0	0	0	0	0%	0%
- Industrial Sec.	112	144	192	254	339	450	5.7%	28.0%
- Service Sector	182	244	328	441	594	800	6.1%	44.7%
Region IV	148	191	249	328	435	582	5.6%	15.9%
- Agriculture Sec.	34	37	38	39	40	41	0.7%	16.1%
- Industrial Sec.	64	86	119	164	225	310	6.5%	19.3%
- Service Sector	50	68	92	125	170	231	6.3%	12.9%

As shown above, the GRDP of NCR and Region IV is projected to grow at 6.0% and 5.6% per annum, respectively, for the period of 2000-2025, which is higher than the GDP growth of the whole country.

Water Demand Projection: (Chapter II)

4. Water demand consists of billed water (domestic + commercial + industrial) and non-revenue water (NRW). The projected water demand is summarized in the table below, together with the projection of per capita consumption, service coverage and NRW ratio:

Water Demand Projection up to Year 2025

Description	2000	2005	2010	2015	2020	2025
Projected Water Demand: (MLD)						
Day average demand	3,663	3,783	4,250	5,033	5,866	6,980
Day peak demand	(4,400)	4,577	5,143	6,090	7,097	8,446
Existing Supply Capacity (MLD)	4,090					
Per capita consumption (Lpcd)	119	125	139	153	170	188
Service coverage (%)	69	71	75	81	88	97
Served population (1000)	8,120	9,703	11,286	13,785	16,147	19,109
Billed water (%)	39.1	46	52	58	64	70
NRW ratio (%)	60.9	54	48	42	36	30
of which, - Physical loss (%)	33.5	30	28	26	20	20
- Commercial loss (%)	27.4	24	20	16	10	10

Note: Day peak demand is assumed as 1.21 times the average demand. The figure of day peak demand for 2000 represents the potential day peak demand.

5. The water demand projection above falls in the middle range of various previous projections made in the Water Supply and Sewerage Master Plan Study (JICA, 1995), Water Resources Master Plan Study (JICA, 1998) and the latest MWSS projection (2001).

Development Scale of New Water Resources: (Chapter IV)

6. As indicated in the table above, water supply capacity in the year 2000 (4,090 MLD) is already critical, if potential day peak demand is deemed to be 1.21 times the average daily demand, i.e. 4,400 MLD (3,663 MLD x 1.21=4,400 MLD). In

order to cope with the growing demand, MWSS and two water companies are contemplating the augmentation of supply capacity by implementing several projects. The schemes contemplated at the stage of M/P Study were Wawa Water Supply Project (50 MLD), Laguna Lake Bulk Water Supply Project (300 MLD) and Angat Aqueduct Rehabilitation Project (350 MLD), giving a total of 700 MLD in supply capacity. These schemes are herein called the “Interim Schemes”.

7. After these Interim Schemes are added, the total supply capacity becomes 4,790 MLD. This affords the stable supply of 3,960 MLD in terms of daily average supply quantity if a day peak factor of 1.21 is assumed (4,790 MLD/1.21). The need for further development of water resources towards year 2025 is then estimated as 3,020 MLD in terms of daily average supply quantity (6,980 MLD-3,960 MLD).

Note: In this Study, water resources development is planned for daily average supply requirement, while the proposed facilities are planned to have the capacity to meet the day peak demand.

8. On one hand, the earliest commissioning of the Agos water supply scheme is foreseen to be around the year 2010 at the earliest on the basis of a rushed implementation program. This means that water demand growth up to 2010 should be met by additional inputs of the Interim Schemes (a total of 1,053 MLD in day peak supply capacity, 5,143 MLD-4,090 MLD). If all the demand up to 2010 is met by the additional Interim Schemes, the need for water resources development in the Agos River Basin is 2,730 MLD to meet the water demand growth between 2010 and 2025 (6,980 MLD-4,250 MLD) in daily average supply quantity.
9. Assessing the overall figures derived in Para.7 and 8 above, this Study assumes that the development requirement of water resources in the Agos River Basin is 3,000 MLD in daily average supply quantity. This corresponds to the figure assessed in Para.7 above and includes about 10 % allowance for the figure assessed in Para.8 above. The allowance for the latter is deemed to cover the uncertain factors involved in the actual achievement of implementation of the Interim Schemes and also in the assumptions set forth for water demand projection, particularly the projection of NRW reduction.

Exploitable Water Resources: (Chapter III)

10. Long-term runoff of the Kaliwa River was estimated using tank model analysis. The Agos River runoff was estimated from the runoff records at Banugao Station and the Kanan runoff by deducting the Kaliwa runoff from the Agos runoff. Low flow study and reservoir operation study revealed the exploitable water resources at selected water development sites to be as follows:

Exploitable Water Resources at Water Development Sites

Water Resources Development Scheme	Reservoir Water Level (EL. m)		Exploitable Water Resources		Figures Assessed in Previous Study
	FSL	MOL	(MLD)	(m ³ /sec)	
Reservoir Scheme:					
Laiban Dam	270	237	1,830	21.2	1,900 MLD at FSL 270 *1
Kanan No.2 Dam	310	278	3,310	38.3	
	310	225	3,770	43.6	3,170 MLD at FSL 295 *1
Agos Dam	159	133	5,210	60.2	
Run-of-River Intake:					
Kaliwa Low Dam	-		550	6.4	8.6 m ³ /sec *2
Laiban Low Dam	-		340	3.9	
Kanan Low Dam			770	8.9	

Notes: (1) Reservoir Scheme: Design year is regarded to be a dry year occurring once in 10 years, roughly corresponding to a 97-98 % dependability for the whole period

(2) Run-of-River Scheme: 90 % dependable discharge, after releasing river maintenance discharge, which is taken at 10 % of 80 % discharge

(3) Exploitable water at Agos Dam represents the total yield usable for water supply and hydropower

*1 MWSP III Study *2 EDCOP Study

Geological Survey: (Chapter III)

11. Initial survey conducted during the M/P study identified the following geological issues to be taken into account in formulating the master plan:
 - (a) Seismicity due to proximity to the active Philippine Fault (Infanta Fault). This issue is common to all dam schemes
 - (b) The existence of many faults near the proposed damsites and along waterways, some of which are categorized by PHILVOLCS as assumed active fault. This issue is also common to all dam and waterway schemes, although the extent varies by scheme
 - (c) Concern for reservoir watertightness due to limestone masses occurring in the reservoir areas, for both the Laiban and Agos Dams
 - (d) Thick riverbed deposit at Agos Dam and potential landslide problems at both the Agos and Kanan No.2 Damsites

Initial Environmental Examination: (Chapter IV)

12. Initial environmental examination (IEE) has identified varying degrees of socio-environmental impacts that may arise due to the proposed projects. The major issues are as follows:
 - (a) Impact on the riverine environment in the downstream reaches due to reduction of flow caused by water transfer to Metro Manila and reduction of sediment discharges caused by construction of dams.
 - (b) Change of flow regime will force local people to change the way of river use. Of a more serious concern is the possible change of morphology of the river mouth and coastlines in the lowermost Infanta-General Nakar alluvial

plain, which would be especially serious in the case of Agos Dam being constructed.

- (c) Need for watershed management, especially for the Kaliwa River basin
- (d) Need for protection of ecosystems already being affected by illegal logging and human encroachment. This issue is particularly important in the Kanan-Agos watersheds.
- (e) Need for preparation of a feasible Resettlement Action Plan (RAP) for relocating 300 to 3,000 households. The number varies by scheme and is most serious in the case of Laiban Dam (3,000 families to be relocated) and Agos Dam (300 families)

Formulation of Water Resources Development Plans: (Chapter V & VI)

13. In order to find the least costly development plan, eight (8) alternative development scenarios were formulated for comparison. The development scenarios were formulated as the combination of three (3) dam/reservoir schemes and three (3) run-of-river schemes for water source development and three (3) waterway schemes for water conveyance to Metro Manila area. The formulated scenarios are shown in the table below:

Alternative Development Scenarios

Develop. Scenario	Ultimate Supply Capacity (MLD)	First Stage Development	Second Stage Development		Water way
			Stage 2-1	Stage 2-2	
A	5,110	Laiban Dam + 1 st Waterway	Kanan No.2 Dam + 2 nd Waterway	-	*1
B	3,000	Kaliwa Low Dam + 1 st Waterway	Agos Dam	2 nd Waterway	*2
C	3,000	Agos Dam + 1 st Waterway	2 nd Waterway	-	*2
D	3,600	Kaliwa Low Dam + 1 st Waterway	Kana No.2 Dam	2 nd Waterway	*2
E	4,060	Kaliwa Low Dam + 1 st Waterway	Kanan Low Dam	Kanan No.2 Dam	*2
F	3,330	Laiban Dam + 1 st Waterway	Agos Dam + 2 nd Waterway		*1 *2
G	3,430	Kaliwa Low Dam + 1 st Waterway	Laiban Dam	Agos Dam + 2 nd Waterway	*2
H	3,420	Laiban Low Dam + 1 st Waterway	Kanan No.2 Dam	2 nd Waterway	*3

- Notes: 1. Supply Capacity: Day average supply quantity
 2. Waterway Scheme: *1 Laiban~Pantay~Taytay *2 Kaliwa~Abuyod~Angono
 *3 Laiban~Karan Batu~Angono
 3. Layout Plan: See Figure 5.4 of Main Text

Comparison of Alternative Development Scenarios: (Chapter VII)

14. The relative attractiveness of the eight (8) alternative development scenarios presented above was evaluated through comparison of “unit water cost” per m³ of water supply. The project cost estimated in this Study included the costs of water

source exploitation (dam/reservoir), a water treatment plant and water conveyance facilities up to a main service reservoir planned at Taytay (Scenarios A and F) or Angono (Scenarios B to H). Hence, the water cost evaluated herein represents the cost at the main service reservoir, which is regarded as the off-take point for distribution to the supply network.

15. Since the proposed development scenarios are formulated to differ in their development scales, the comparison should take into account not only cost factor but also time factor. Hence, the “unit water cost” is calculated by comparing the present worth of total incurred costs and expected revenues by discounting to 2001 prices at a discount rate of 12 % per annum. It is assumed that a part of the invested cost is recovered by electricity energy revenue and the remainder should be recovered by water revenue. On this basis, a trial calculation was made to find a “unit water cost” that would equalize the present worth of the cost portion to be recovered by water revenue (the portion remaining after deducting the portion to be recovered by energy revenue) and the present worth of water revenue.
16. The evaluation horizon is set at 40 years after the first stage scheme is commissioned. Although the earliest attainable completion year of the first stage scheme varies by scenario from 2010 to 2013, the Study assumed that the first stage project of all the Scenarios would be completed in year 2010 to enable a comparison of the Scenarios within the same time frame. Therefore, the evaluation horizon assumed is from 2011 to 2050 in this comparative study.
17. The results of ‘unit water cost’ comparison are summarized in the table below:

Summary of Comparison of Unit Water Cost Index

Scenario	Proposed Scheme	Project Cost *1 (US\$ Mil.)	Present Worth		Equalizing Unit Water Cost *2 (US\$/ m ³)
			Water Volume Supplied (Mil. m ³)	Cost to be Recovered (US\$ Mil.)	
A	Laiban + Kanan No.2 Dam	2,256	1,650	1,429	0.400
B	Kaliwa Low Dam + Agos Dam	1,826	1,449	1,129	0.379
C	Agos Dam	1,820	1,449	1,171	0.391
D	Kaliwa Low Dam + Kanan No.2 Dam	1,884	1,531	1,248	0.389
E	Kaliwa Low Dam + Kanan Low Dam + Kanan No.2 Dam	2,200	1,580	1,411	0.421
F	Laiban Dam + Agos Dam	2,064	1,498	1,236	0.390
G	Kaliwa Low Dam + Laiban Dam + Agos Dam	2,284	1,513	1,337	0.424
H	Laiban Low Dam + Kanan No.2 Dam	1,778	1,511	1,254	0.398
(For Reference)					
-	Laiban Dam	871	1,166	868	0.380

Notes: *1 Base cost estimate at 2001 price, comprising construction cost, land acquisition/resettlement cost, engineering/administration cost (7%) and physical contingency (15%)

*2 Unit water cost at 2001 price, which equalizes the present worth of costs and the present worth of water sale amount, discounted at 12% per annum. The water sale price is escalated at 3% per annum.

18. As indicated in the table above, the unit water cost index is evaluated to be the least for Scenario B, followed by Scenarios C, D, F and H being at an almost equal level. The favorable index of Scenario B can be explained by the larger quantity of water exploitable by the Agos reservoir, which is usable either for water supply and hydropower, as indicated in the table shown in Para.10 above.
19. On one hand, the unit water cost index of the Laiban Dam project showed an index value almost comparable to that of Scenario B. Hence, this Study proposes that both the Scenario B (evaluated as least costly on scenario basis) and Laiban Dam (evaluated as attractive on an individual project basis) would be worthy of further consideration in formulation of the master development plan of the Agos River Basin.

Proposed Master Plan: (Chapter VIII)

20. A master plan was formulated basically in line with the plans proposed in Development Scenario B. The configuration of the proposed master plan is shown in Figure 8.1 of the main text.

Water Supply Development Plan:

21. Scenario B envisages the development of Kaliwa Low Dam initially and Agos Dam ultimately for meeting water demand up to the year 2025 (3,000 MLD in daily average supply quantity). The sequence of proposed development is shown in the table below:

Sequence of Proposed Water Supply Development

Proposed Facilities	1 st Stage Develop	2 nd Stage Development	
		Stage 2-1	Stage 2-2
Water Supply Q'ty	550 MLD initially	Additional 950 MLD	Additional 1,500 MLD
Kaliwa Low Dam	Supply of 550 MLD initially	(Supply substituted by Agos Dam)	-
Agos Dam	-	Supply of 1,500 MLD, including 550 MLD earlier supplied by Kaliwa Low Dam	Supply of additional 1,500 MLD
Waterways	1 st Waterway for 1,500 MLD	-	2 nd Waterway for additional 1,500 MLD
Water Treatment Plant (WTP)	WTP #1 – 750 MLD	WTP #2 - 750 MLD	WTP #3 & #4, each 750 MLD
Main Service Reservoir (SR)	SR #1 for 750 MLD	SR #2 for 750 MLD	SR #3&4 for additional 1,500 MLD

Note: The above figures in MLD represent daily average supply quantity. The capacity of waterway and WTP is planned to be 1.21 times the daily average supply capacity to meet the day peak demand.

22. As stated above, the Laiban Dam project was retained for consideration in the master plan. The project is already committed by the Memorandum Order No.10 of August 5, 1998, which mandated the MWSS to resume the implementation of the project.
23. There are two hurdles for the implementation of Laiban Dam. One is the resettlement of about 3,000 households or 15,000 people, which constitutes a large social problem. The other is the concern for possible delay in completion due to the

time requirement for solving the resettlement issue before construction and also potential problems that may arise during the construction. The implementation of Laiban Dam depends on MWSS's confidence in how quickly the resettlement issue could be solved and how fast the project could be commissioned.

Hydropower Development:

24. Three (3) potential hydropower development schemes are proposed in the master plan: (i) Abuyod power station at the downstream end of the water conveyance tunnel, (ii) Agos power station at the toe of Agos Dam, and (iii) Kanan No.2 power station at the toe of Kanan No.2 Dam. The proposed hydropower development is summarized in table below:

Summary of Hydropower Development Plan

Scheme	Power Output (MW)		Energy Production (GWh)		
	Installed Capacity	95 % Guaranteed	Primary Energy	Secondary Energy	Total
Abuyod P/S *1	12.5	7.0	98.6	-	98.6
Agos P/S	85.6	71.3	178.0	240.9	418.9
Kanan No.2 P/S *2	209.5	135.3	406.4	97.2	503.6

Notes: *1 Installed after the completion of Agos Dam and 2nd Waterway

*2 Can be implemented independently from the water supply schemes

Measures for Mitigation of Socio-Environmental Issues:

25. The socio-environmental study (Chapter IV) has identified several potential issues to arise due to the proposed projects. These issues should be taken into account in the subsequent feasibility study.

(1) Impact to River Mouth Alluvial Plain due to Reduced Sediment Yield

A major impact of serious concern is, as stated in Para.12 above, the possible change morphology of river mouth and coastlines.

(2) Resettlement Scheme

The proposed water resources development and conveyance projects will require a varying degree of relocation of households. This issue is an important sociological parameter determining the viability of the proposed projects and hence is taken up as a planning element of the master plan.

(3) Watershed Management in the Kaliwa River Basin

The Kaliwa River Basin is yielding a large quantity of sediments due mainly to deforestation over a long period and active development of land for cultivation. Also, the destruction of forest cover results in wildlife habitat loss, and consequently diminishing biodiversity and wildlife.

The DENR-Forest Management Bureau (FMB) is currently implementing a Watershed Rehabilitation and Management Improvement Project for the Kaliwa catchment. Since the recovery of a fair watershed environment takes a relatively long period, the activities of Kaliwa Watershed Management Project should be further strengthened and continued henceforward.

(4) Conservation of Eco-Systems in Kanan-Agos Watershed

The Kanan and Agos River Basins are covered by thick vegetation. This vegetation cover is home to some migratory and permanent endangered fauna, such as the Philippine deer, wild pig, monitor lizard and kalaw. These species are important components in the stability and productivity of the ecosystem.

Extensive logging especially in the Kanan River watershed is already posing a serious threat to the primary forest in the upper catchment. Furthermore, the impoundment of the Agos reservoir and the construction of Kanan No.2 Dam (including the reservoir, access road and transmission line) will have significant impacts on the forest environment and ecological system in the basin.

Projects for Enhancement of Regional Development:

26. The implementation of water resources development will cause various types of inconveniences to people in the project area, such as the relocation of settlements, change of river environments, disconnection of local communities due to reservoir impoundment, etc. For compensation for those inconveniences, the project will have to provide necessary measures to improve people's livelihood and enhance regional economic activities. The following describe the outline of the projects proposed in this respect:

(1) Bank Erosion Protection Work in the Infanta-General Nakar Alluvial Plain

In the Infanta-General Nakar alluvial plain, severe bank erosion is taking place along the both banks of the Agos River. The erosion at the heaviest portion was as large as 300-400 m during 1952 and 1995. The bank has already been incised very close to the main part of the General Nakar town. According to people in the area and the Municipality Office, the most urgent project needed in this area is the protection of the banks from further erosion. The proposed work consists of revetment work coupled with the installation of groins in selected portions of the river course.

(2) Provision of Riverbank Structure for Facilitating the People's River Use

The riverine environment downstream of the Agos Dam will change significantly, e.g. degradation of riverbed level, decrease of dry season flow, etc. This will cause the people in the area to change the ways of water use or river. The proposed project is to provide riverbank structures for facilitating the people's use of the river at places where people use the river. The proposed structures are for boat landing and bathing/washing that will be usable at any river water level.

(3) Provision of Access Roads/Footpaths for the Communities

The resettlement scheme for the Agos Dam contemplates relocation of the existing settlements to lands at higher elevations in the vicinity of the original locations. The project being proposed herein is to provide access to those new resettlement areas by extending a road from the access roads built for the construction works. If the resettlement site is less populated or in a relatively remote location, access will be by footpath. In addition, a trunk footpath connecting Agos Dam, Kaliwa Low Dam

and Barangay Daraitan will be built. This footpath will facilitate the people's access to shops, schools, medical facilities and other public facilities located in the vicinity. Also, for improving access to Barangay Daraitan during flood season, a footpath suspension bridge will be built just upstream of the existing ferry site.

(4) Establishment of a Manpower Training Center

Some of the PAFs (project affected families) will have to change their occupation due mainly to resettlement outside the present livelihood area. To support sustainable livelihood of the PAFs, a manpower training center will be established at Barangay Daraitan or new resettlement site.

(5) Establishment of a Health Center at Barangay Daraitan

In Barangay Daraitan, there are at present two health centers staffed by a nurse and a midwife, the latter visiting once a week, which is a lower level of service than is required for a medical facility in an area with a population in the order of 4,000. The proposed project is to build a health center equipped with the minimum equipment required and being staffed by a physician and a nurse.

(6) Power Supply to Infanta-General Nakar Area

The proposed master plan contemplates to supply the power generated at Agos Power Station to the Infanta-General Nakar area by a 69 kV transmission line. The stable supply of power will contribute to further development of economic activities in the area through stimulating industrial development.

Economic Evaluation of Proposed Schemes: (Chapter VIII)

27. Economic evaluation was made for two major schemes proposed in the master plan: one is the scheme comprised of Kaliwa Low Dam, Agos Dam and Kaliwa-Angono Waterway for multi-purpose development of water supply and hydropower. The other is Kanan No.2 Dam scheme for hydropower development. The economic benefit of water supply is regarded to be the willingness-to-pay for water. The hydropower benefit is regarded as the cost of alternative thermal power plant.
28. Analysis of the cost and benefit streams revealed that the economic internal rate of return (EIRR) is 13.5 % for the former multi-purpose scheme and 5.4 % for the Kanan No.2 hydropower scheme. The EIRR evaluated for the Kanan No. 2 scheme is relatively low. The Kanan No.2 scheme will require a further elaboration of the plans for justifying the viability.

Proposed Implementation Organizations: (Chapters VIII & X)

29. The Steering Committee meeting for this Study, held on August 21, 2001, agreed that "MWSS will handle the implementation of the water resources development of the Agos River Basin until such time that a River Basin Authority is created". The Study assumes that MWSS would act as the Executing Agency for the proposed project.

30. In order to assist and coordinate the roles and duties of the MWSS, an “Inter-Agency Coordinating Committee” will be organized. The Committee will be composed of representatives from NEDA, DPWH, DENR, DILG, DOE/NPC, NWRB, NIA, MWSS, and Quezon and Rizal Province. MWSS will chair the Committee. Chapter X of the main text describes the detail of the roles and functions of the Committee and also the proposed organizational structure in the operation and maintenance stage.

Proposed Financial Arrangement: (Chapter VIII)

31. This Study proposes the following procurement approaches to be most advantageous to the project:

(1) Project under BOT (Build-Operate-and-Transfer) Scheme:

In line with the policy of the Government as well as that of the MWSS, a basic principle would be to procure the work through the maximum use of private financing resources (e.g. BOT). This procurement will be applied to the following work components:

- Water treatment plant and conveyance facilities (from water treatment plant up to service reservoirs)
- Distribution mains (preferably to be implemented by the present water distribution concessionaires)
- Hydropower plants at Abuyod and Agos Dam

(2) Projects under Government Project

On the other hand, construction of the water resources facilities (dam and tunnel) involves greater technical risks and requires a large investment cost, which would be a large burden to most BOT Proponents. The least costly approach is to build the water resources facilities as a government project by utilizing the ODA soft loans of a low interest rate longer repayment period, which affords minimizing the annual costs and accordingly minimizing the water cost. The work components proposed for the implementation as a government project include:

- Water source development, i.e. Kaliwa Low Dam and Agos dam
- Water conveyance tunnel up to Abuyod hydropower plant
- Projects proposed for regional development (See Para.27 above)

The fund for repayment of loans can be generated from the sale of raw water to the BOT concessionaires for water supply and electricity supply.

Selection of Project for Subsequent Feasibility Study: (Chapter IX)

32. Among the projects included in the proposed master plan (Para.20 to 27 above), the most urgent project is water supply development for attaining the earliest supply of water to Metro Manila. Hence, the subsequent feasibility study will take up the 1st stage development of the water supply schemes proposed in Development Scenario B, which is outlined in the table shown in Para.21 above.
33. The 1st stage project consists of the Kaliwa Low Dam with the 1st waterway. A matter to be noted is that the viability of the 1st stage project relies largely on the feasibility of the Agos Dam. Therefore, the feasibility study should also include the investigation and studies of the Agos Dam as well.

**THE STUDY
ON
WATER RESOURCES DEVELOPMENT
FOR
METRO MANILA
IN
THE REPUBLIC OF THE PHILIPPINES

FINAL REPORT

VOLUME II
PHASE 1: MASTER PLAN STUDY
MAIN REPORT**

Table of Contents

Location Map of the Study Area
Abbreviations
Measurements

		<u>Page</u>
CHAPTER I	INTRODUCTION	1-1
1.1	General	1-1
	1.1.1 Background	1-1
	1.1.2 Objectives of the Study	1-2
	1.1.3 Study Area	1-2
	1.1.4 Overall Work Schedule of the Study	1-2
1.2	Progress of Phase I Study	1-3
	1.2.1 Activities during the First Field Investigation Stage (March- August 2001)	1-3
	1.2.2 Supporting Works Undertaken by NWRB	1-4
	1.2.3 First Home Office Work (September-November 2001)	1-4
1.3	Master Plan Study Reports	1-5
1.4	Necessity of Water Resources Development in the Agos River Basin	1-5
	1.4.1 General	1-5
	1.4.2 Present Situation of Water Demand and Supply Balance in Metro Manila	1-6
	1.4.3 National Policy of Expansion of Water Supply Capacity for Metro Manila	1-7
	1.4.4 Prioritized Water Supply Projects for Metro Manila in Previous Studies	1-7
	1.4.5 Interim Water Supply Schemes Contemplated by MWSS	1-9
	1.4.6 Necessity of Agos Water Resources to Meet Water Demand of Metro Manila	1-9

CHAPTER II	SCIO-ECONOMIC FRAMEWORK OF STUDY AREA AND WATER DEMAND PROJECTION	2-1
2.1	Present Socio-Economic Conditions of the Study Area	2-1
2.1.1	Current Status of Socio-Economy in the Philippines.....	2-1
2.1.2	Profiles of Region, Province and Municipality	2-2
2.2	National Economic Development Plan	2-2
2.2.1	Long-term Philippines Development Plan (LTPDP)	2-2
2.2.2	Medium-term Philippines Development Plan (MTPDP).....	2-2
2.3	Socio-Economic Projection	2-3
2.3.1	Population Projection	2-3
2.3.2	GRDP Projection.....	2-5
2.4	Current Situation of Water Supply in Metro Manila	2-8
2.4.1	Privatization of MWSS and Present Situation of Water Supply	2-8
2.4.2	Service Area and Population Served	2-8
2.4.3	Existing Water Supply Facilities	2-9
2.4.4	Current Water Production and Billed Water.....	2-11
2.4.5	Water Tariff in MWSS's Service Area	2-13
2.5	Water Demand Projection for Metro Manila	2-13
2.5.1	Domestic Water Demand	2-13
2.5.2	Commercial Water Demand.....	2-16
2.5.3	Industrial Water Demand	2-16
2.5.4	Total Water Demand.....	2-17
2.5.5	Comparison with Previous Water Demand Projections.....	2-18
2.6	Water to be Exploited in the Agos River Basin to Meet Water Demand of MWSS's Service Area	2-19
2.6.1	Interim Water Supply Projects Envisaged by MWSS.....	2-19
2.6.2	Water Demand and Supply Balance Until 2025.....	2-20
2.6.3	Water to be Exploited in the Agos River Basin to Meet Water Demand up to 2025	2-21
2.7	Recommended Measures to Reduce Non-Revenue Water Ratio.....	2-21
2.7.1	Field Survey to Clarify Water Leakage.....	2-21
2.7.2	Recommended Rehabilitation Works for Reducing Water Leakage	2-21
2.7.3	Water Tariff Collection System on a Community Basis	2-22
2.8	Present Condition of Power Market.....	2-22
2.8.1	Power Sector in the Philippines	2-22
2.8.2	Power Development Program by NPC	2-23
CHAPTER III	THE AGOS RIVER BASIN	3-1
3.1	Geography and Topography	3-1
3.1.1	Geography	3-1
3.1.2	Topographic Data Available for Master Plan Study.....	3-2

3.2	Meteorology and Hydrology	3-3
3.2.1	Available Data	3-3
3.2.2	Hydrological Investigation Works Performed during the Master Plan Stage.....	3-4
3.2.3	Meteorology	3-5
3.2.4	Runoff Analysis.....	3-5
3.2.5	Flood Study	3-7
3.2.6	Sediment Study	3-8
3.3	River Water Quality	3-9
3.3.1	Previous Water Quality Analysis.....	3-9
3.3.2	Water Quality Analyses Carried out in the First Field Investigation Works.....	3-9
3.3.3	Matters to be Considered in Design of Water Treatment Facility in Relation to River Water Quality.....	3-10
3.4	Geology	3-10
3.4.1	Regional Geology.....	3-10
3.4.2	Faults	3-11
3.4.3	Seismicity	3-11
3.4.4	Geotechnical Evaluation of Respective Schemes	3-11
3.4.5	Construction Materials	3-20
3.5	Water Demand and Supply for Lowermost Reach of the Agos	3-22
3.5.1	Present Condition of Water Supply for Lowermost Reach of the Agos	3-23
3.5.2	Future Water Demand and Availability of Water Source	3-23
3.6	Flood Damages in Lowermost Reach of the Agos.....	3-24
3.6.1	General.....	3-24
3.6.2	Major Typhoon Records and Flood Damage Records	3-24
3.6.3	Present Condition.....	3-25
CHAPTER IV INITIAL ENVIRONMENTAL ASSESSMENT.....		4-1
4.1	General.....	4-1
4.2	Environmental Legal Framework Relevant to the Project	4-1
4.2.1	Environmental Legal Framework in the Philippines	4-1
4.2.2	Environmental Regulatory Standards and Other Laws Relevant to the Study	4-2
4.2.3	Legal Framework for Resettlement and Indigenous People	4-4
4.3	Environmental Survey Works Carried Out in First Field Investigation Period.....	4-5
4.3.1	Site Reconnaissance.....	4-5
4.3.2	Review of Previous Studies and Meeting with Agencies and Communities Concerned.....	4-6
4.3.3	Initial Environmental Examination (IEE).....	4-6

4.4	Overview of Environmental Conditions in the Study Area	4-7
4.4.1	General Environmental Conditions.....	4-7
4.4.2	Findings from IEE Survey	4-7
4.5	Environmental Features Particular to Each River Basin.....	4-9
4.5.1	Kaliwa River Basin	4-9
4.5.2	Kanan River Basin	4-15
4.5.3	Agos River Basin	4-16
4.5.4	Agos Lower Basin.....	4-17
4.5.5	Coastal Areas of Infanta/General Nakar	4-18
4.6	Resettlement Issues	4-19
4.6.1	General.....	4-19
4.6.2	Resettlement Requirement of Respective Development Schemes.....	4-20
4.6.3	Proposed Resettlement Plans	4-28
4.7	Summary of Environmental and Resettlement Problems by Scheme.....	4-32
CHAPTER V	WATER RESOURCES DEVELOPMENT PLAN IN THE AGOS	
	RIVER BASIN	5-1
5.1	Basic Framework of Plan Formulation	5-1
5.1.1	General.....	5-1
5.1.2	Development Scale for Meeting Water Demand up to Year 2025	5-1
5.1.3	Formulation of Water Resources Development Plans in the Agos River Basin.....	5-3
5.2	Background and Development Concepts of Water Source Development Schemes in the Agos River Basin	5-4
5.2.1	Laiban Dam on the Kaliwa River.....	5-4
5.2.2	Kanan No.2 Dam on the Kanan River	5-4
5.2.3	Agos Dam on Agos Mainstream	5-5
5.2.4	Kaliwa Low Dam on the Kaliwa River.....	5-5
5.2.5	Laiban Low Dam on the Kaliwa River	5-6
5.2.6	Kanan Low Dam on the Kanan River.....	5-6
5.3	Optimization of Reservoir Type Schemes.....	5-7
5.3.1	Selection of Optimum Full Supply Water Level (FSL)	5-7
5.3.2	Selection of Dam Type.....	5-8
5.4	Formulation of Alternative Development Scenarios	5-8
5.4.1	Water Balance Study	5-8
5.4.2	Exploitable Water Resources at Each Water Source Development Site.....	5-9
5.4.3	Formulation of Alternative Development Scenarios.....	5-10
5.5	Main Features of Eight (8) Alternative Development Scenarios to Meet Water Demands of Metro Manila until Year 2025	5-11
5.5.1	Alternative Development Scenario A (Laiban Dam + Kanan No.2 Dam)	5-11

5.5.2	Alternative Development Scenario B (Kaliwa Low Dam + Agos Dam)	5-11
5.5.3	Alternative Development Scenario C (Agos Dam without Kaliwa Low Dam)	5-12
5.5.4	Alternative Development Scenario D (Kaliwa Low Dam + Kanan No.2 Dam)	5-12
5.5.5	Alternative Development Scenario E (Kaliwa Low Dam + Kanan Low Dam + Kanan No.2 Dam)	5-13
5.5.6	Alternative Development Scenario F (Laiban Dam + Agos Dam)	5-14
5.5.7	Alternative Development Scenario G (Kaliwa Low Dam + Laiban Dam + Agos Dam)	5-14
5.5.8	Alternative Development Scenario H (Laiban Low Dam + Kanan No.2 Dam)	5-14
5.6	Future Developments in Each Development Scenario.....	5-15
5.6.1	Plan A-3: Additional Development Plan (Agos Dam).....	5-15
5.6.2	Plan B-3: Additional Development Plan (Laiban Dam and Kanan No.2 Dam)	5-16
5.6.3	Plan C-3: Development Plan of 3rd Stage Onward	5-16
5.6.4	Plan D-3: Development Plan of 3rd Stage Onward	5-16
5.6.5	Plan E-3: Development Plan of 3rd Stage Onward.....	5-16
5.6.6	Plan F-3: Development Plan of 3rd Stage Onward.....	5-17
5.6.7	Plan G-3: Development Plan of 3rd Stage Onward	5-17
5.6.8	Plan H-3: Development Plan of 3rd Stage Onward	5-17
5.7	Hydropower Development Potentials in Each Development Scenario.....	5-17
CHAPTER VI WATER CONVEYANCE AND TREATMENT PLANT		6-1
6.1	Alternative Water Conveyance Routes Identified	6-1
6.1.1	General.....	6-1
6.1.2	Laiban-Taytay Water Conveyance Route for Laiban High Dam	6-1
6.1.3	Alternative Water Conveyance Routes for Kaliwa Low Dam and Agos Dam.....	6-1
6.1.4	Laiban-Angono Water Conveyance Route for Laiban Low Dam.....	6-2
6.2	Selection of Least Costly Route for Kaliwa-Angono Waterway	6-2
6.3	Water Conveyance Facilities and Treatment Plant for Selected Kaliwa-Angono Water Conveyance Route	6-3
6.3.1	Water Conveyance Facilities	6-3
6.3.2	Hydraulic Conditions	6-4
6.3.3	Water Treatment Facility.....	6-4
6.3.4	Treated Water Conveyance and Delivery Facilities	6-5
6.4	Preliminary Plan of Distribution Trunk Mains in MWSS's Service Area	6-7
6.4.1	Existing Distribution Trunk Mains.....	6-7
6.4.2	Preliminary Plan of New Distribution Trunk Mains	6-8
6.4.3	Preliminary Cost Estimate of New Distribution Trunk Mains.....	6-9

CHAPTER VII	COMPARISON ON PRIORITY OF ALTERNATIVE DEVELOPMENT SCHEMES.....	7-1
7.1	General	7-1
7.2	Preliminary Design of Proposed Structures.....	7-1
7.2.1	Dam in Reservoir Type Scheme.....	7-1
7.2.2	Low Dam in Run-of-River Scheme	7-2
7.2.3	Waterways.....	7-3
7.3	Preliminary Cost Estimate and Implementation Schedule	7-4
7.3.1	Preliminary Cost Estimate for Each Development Scenario	7-4
7.3.2	Implementation Schedule.....	7-6
7.4	Comparison of Alternative Development Scenarios in Terms of Unit Water Cost Index.....	7-7
7.4.1	Methodology and Procedure Adopted.....	7-7
7.4.2	Comparison of Indexes on the Basis of Same Time-Fame	7-9
7.4.3	Evaluation of Indexes on the Basis of Assumed Implementation Schedule	7-10
7.4.4	Evaluation of Indexes on the Basis of Assumed Implementation Schedule with Consideration of Penalty for Delay in Completion....	7-11
7.4.5	Conclusion of Unit Water Cost Comparison.....	7-11
7.5	Technical Assessment of Development Scenario B.....	7-11
7.5.1	Overall Technical Comparison with Other Scenarios	7-11
7.5.2	Water Resources Potential Exploitable for Water Demand After Year 2025	7-14
CHAPTER VIII	FORMULATION OF MASTER PLAN	8-1
8.1	General.....	8-1
8.2	Water Supply Development toward Year 2025.....	8-1
8.2.1	Configuration of Proposed Development Plans.....	8-1
8.2.2	Kaliwa Low Dam	8-2
8.2.3	Agos Dam.....	8-3
8.2.4	Kaliwa-Angono Waterway.....	8-3
8.2.5	Abuyod Water Treatment Plant.....	8-4
8.2.6	Angono (Taytay) and Antipolo Service Reservoirs	8-4
8.2.7	Distribution Mains	8-5
8.3	Hydropower Development	8-5
8.3.1	Abuyod Power Station	8-5
8.3.2	Agos Power Station.....	8-6
8.4	Measures for Mitigation of Socio-Environmental Issues.....	8-6
8.4.1	Reduced Sediment Yield at Agos River Mouth	8-6
8.4.2	Resettlement Schemes.....	8-7
8.4.3	Watershed Management in Kaliwa River Basin	8-8
8.4.4	Conservation of Eco-System in Kanan-Agos Watershed.....	8-9

8.5	Projects for Enhancement of Regional Development	8-9
8.5.1	Bank Erosion Protection Work in the Infanta-General Nakar Alluvial Plain	8-10
8.5.2	Provision of Riverine Facilities.....	8-10
8.5.3	Provision of Access Roads/Footpaths for the Communities	8-10
8.5.4	Establishment of a Vocational Training Center at Barangay Daraitan	8-10
8.5.5	Establishment of a Medical Clinic at Barangay Daraitan	8-11
8.5.6	Power Supply to Infanta-General Nakar Area	8-11
8.6	Optional Development Plan	8-11
8.6.1	Option of Laiban Dam Development for Water Supply Development	8-11
8.6.2	Options of Hydropower Development	8-12
8.6.3	Resettlement Issues in Optional Development Plan	8-13
8.7	Implementation Schedule of Master Plan	8-15
8.8	Proposed Implementation Organizations	8-15
8.9	Proposed Financial Arrangement	8-16
8.9.1	Procurement of Works.....	8-16
8.9.2	Financing for the Government-initiated Portion.....	8-17
8.9.3	Financing and Procurement Method for BOT Portion.....	8-17
8.9.4	Risks Factors in Financing for the Project.....	8-18
8.10	Economic Evaluation of the Master Plan.....	8-20
8.10.1	General	8-20
8.10.2	Conditions and Assumptions.....	8-20
8.10.3	Derivation of Economic Cost.....	8-21
8.10.4	Estimate of Economic Benefit	8-21
8.10.5	Computation of EIRR	8-23
8.11	Technical and Social Aspects	8-23
CHAPTER IX PRIORITY PROJECT FOR FEASIBILITY STUDY		9-1
9.1	Selection of Priority Project for Feasibility Study	9-1
9.2	Components of the Project for the Feasibility Study	9-1
9.3	Major Issues to be Examined in the Feasibility Study	9-2
9.3.1	Hydrological Investigation.....	9-2
9.3.2	Geological Investigation	9-2
9.3.3	Socio-Environmental Investigation.....	9-3
9.3.4	Plan Formulation and Design Aspects	9-3
9.3.5	Projects for Regional Development	9-4
CHAPTER X ORGANIZATIONAL AND INSTITUTIONAL ASPECTS.....		10-1
10.1	Introduction.....	10-1
10.2	Current Organization/institution concerned with Water Resources Development for Metro Manila Water Supply.....	10-1

10.2.1	Key Agencies related to Metro Manila Water Supply.....	10-1
10.2.2	Ambiguity of Responsibilities among Water-related Agencies	10-6
10.3	Organizational Structure for Implementation of Agos Project.....	10-7
10.3.1	Decision of Steering Committee Meeting.....	10-7
10.3.2	Implementing Framework.....	10-7
10.4	Organizational Structure for Operation and Management after Completion...	10-8
10.4.1	Creation of Agos River Basin Committee.....	10-8
10.4.2	Rationale for creation of ARBC.....	10-9
10.4.3	Relationship between ARBC and River Basin Authority	10-10
10.5	Recommendation for Water Resources Sector Reform.....	10-10

List of Tables

	<u>Page</u>
Table 1.1	Members of Steering Committee..... T1-1
Table 1.2	Members of Technical Working Group T1-2
Table 1.3	Counterpart Personnel of NWRB..... T1-3
Table 1.4	Comparison of Water Sources in and around Metro Manila in Study of MWSP III, 1979 T1-4
Table 2.1	Comparison of Socio-Economic Indices in the Study Area T2-1
Table 2.2	Growth Target under Philippine National Development Plan..... T2-2
Table 2.3	Growth Target under Medium-term Philippines Development Plan, 1999-2004..... T2-3
Table 2.4	Present Service Coverage by City/Municipality (CY 2000) T2-4
Table 2.5	Water Production and Distribution, MWCI..... T2-5
Table 2.6	Water Production and Distribution, MWSI..... T2-6
Table 2.7	Past Trend of Water Volume T2-7
Table 2.8	Assumed Share of Water Consumption by City/Municipality (CY 2000)..... T2-8
Table 2.9	Proposed Per Capita Consumption..... T2-9
Table 2.10	Proposed Service Coverage..... T2-10
Table 2.11	Projected Population Served..... T2-11
Table 2.12	Projected Water Demand by City/Municipality for Year 2005 T2-12
Table 2.13	Projected Water Demand by City/Municipality for Year 2010 T2-13
Table 2.14	Projected Water Demand by City/Municipality for Year 2015 T2-14
Table 2.15	Projected Water Demand by City/Municipality for Year 2020 T2-15
Table 2.16	Projected Water Demand by City/Municipality for Year 2025 T2-16
Table 2.17	Energy Sales and Peak Power Demand in 2000 Power Development Program T2-17
Table 2.18	System Capacity Addition –2000 Power Development Program..... T2-18
Table 2.19	Meralco System – Operating Statistics..... T2-19
Table 3.1	Estimated Mean Monthly Discharge T3-1
Table 3.2	Flow Duration Curve..... T3-6

Table 3.3	Result of River Water Quality Analysis	T3-9
Table 3.4	Water Quality of Raw/Treated Water at La Mesa No.1 Water Treatment Plant.....	T3-10
Table 3.5	Table of Geological Formation.....	T3-11
Table 3.6	Acceleration Value of Each Proposed Dam Site	T3-12
Table 3.7	List of Typhoon Records in the Agos River Basin (1974-2000)	T3-13
Table 3.8	Record of the Flood Damage due to Typhoons in Infanta Municipality and General Nakar Municipality.....	T3-14
Table 3.9	Result of Flood Damage Survey.....	T3-15
Table 4.1	Environmental Conditions of the Study Area, Agos River Basin	T4-1
Table 4.2	Preliminary Estimate of Resettlement and Compensation Cost.....	T4-5
Table 4.3	Summary of Environmental and Resettlement Issues by Development Scheme - Major Items	T4-8
Table 5.1	Summary of Alternative Development Scenarios	T5-1
Table 5.2	Summary of Hydropower Output of Alternative Development Scenarios.....	T5-2
Table 6.1	General Features of Proposed Waterways.....	T6-1
Table 6.2	Technical Features of Three Alternative Waterway Routes (Kaliwa-Angono Waterway).....	T6-2
Table 6.3	Cost Summary for Kaliwa-Angono Waterway.....	T6-3
Table 6.4	Staged Plan of Primary Distribution Main	T6-4
Table 7.1	Cost Summary for Alternative Development Scenarios.....	T7-1
Table 7.2	Summary of Project Cost for Scenario B	T7-2
Table 7.3	Unit Water Cost Index for Comparison of Alternative Development Scenarios.....	T7-4
Table 7.4	Summary of Technical Comparison of Alternative Development Scenarios.....	T7-5
Table 7.5	90% Discharge Available in River Reach Downstream of Agos Damsite at Each Development Stage.....	T7-7
Table 7.6	Water Resources Exploitable for Water Demand after 2025.....	T7-8
Table 8.1	Investment Schedule: Scenario B Scheme	T8-1
Table 8.2	Investment Schedule: Kanan No.2 Scheme.....	T8-2
Table 8.3	Derivation of Economic Cost from Financial Cost: Scenario B Scheme	T8-3
Table 8.4	Derivation of Economic Cost from Financial Cost: Kanan No.2 Scheme	T8-4
Table 8.5	Yearly Disbursement of Capital Cost for Economic Evaluation: Scenario B Scheme.....	T8-5
Table 8.6	Yearly Disbursement of Capital Cost for Economic Evaluation: Kanan No.2 Scheme	T8-6
Table 8.7	Computation of kW and kWh Values of Alternative Thermal Power Plants	T8-7
Table 8.8	Calculation of Power Generation Benefits.....	T8-8

Table 8.9	Computation of Economic Internal Rate of Return (EIRR): Scenario B Scheme	T8-9
Table 8.10	Computation of EIRR: Kanan No.2 Hydropower Station Scheme	T8-10
Table 10.1	Key Organizations concerned with Metro Manila Water Supply	T10-1

List of Figures

	<u>Page</u>	
Figure 1.1	Water Resources Potential Area to Metro Manila	F1-1
Figure 2.1	Service Area of MWCI and MWSI	F2-1
Figure 2.2	Schematic Diagram of MWSS Headworks	F2-2
Figure 2.3	Major Interconnection Projects	F2-3
Figure 3.1	Location Map of Hydrological Stations	F3-1
Figure 3.2	Available Hydrological Data	F3-2
Figure 3.3	Regional Geological Map	F3-3
Figure 3.4	Distribution of Active Faults in Southern Luzon	F3-4
Figure 3.5	Philippine Significant Earthquakes (1608-1996)	F3-5
Figure 3.6	Distribution of Faults around the Project Area (1)	F3-6
Figure 3.7	Distribution of Faults around the Project Area (2)	F3-7
Figure 3.8	Distribution of Limestone and Young Sediments around Agos ~ Laiban Reservoir Area	F3-8
Figure 3.9	Profile of Laiban Dam Axis	F3-9
Figure 3.10	Profile Sketch of Kaliwa Low Dam No.2 Site	F3-10
Figure 3.11	Profile of Agos Dam Axis	F3-11
Figure 3.12	Assumed Geological Profile of Mt. Daraitan ~ Pagus	F3-12
Figure 3.13	Profile of Kanan No.2 Dam Axis	F3-13
Figure 3.14	Geological Profile of Kaliwa-Abuyod Transfer Tunnel (Upstream Part of Kaliwa-Angono Waterway)	F3-14
Figure 3.15	Geological Profile of Laiban-Tanay Transfer Tunnel (Upstream Part of Laiban-Angono Waterway)	F3-15
Figure 3.16	Comparison of Coastlines and River Channels of Infanta Peninsula in 1952 and 1995	F3-16
Figure 3.17	River Conditions of the Lower Agos	F3-17
Figure 4.1	Potential Damsites and Water Conveyance Routes and Land Status/Regulatory of the Study Area	F4-1
Figure 4.2	Project Affected Area	F4-2
Figure 5.1	Proposed Dam Development Sites in the Agos River Basin	F5-1
Figure 5.2	Comparison of Unit Cost of Water Resources Development for Dams Planned in the Agos River Basin	F5-2
Figure 5.3	General Layout of Development Plans	F5-3
Figure 5.4	Alternative Development Scenario A	F5-4
Figure 5.5	Alternative Development Scenario B	F5-5
Figure 5.6	Alternative Development Scenario C	F5-6

Figure 5.7	Alternative Development Scenario D.....	F5-7
Figure 5.8	Alternative Development Scenario E.....	F5-8
Figure 5.9	Alternative Development Scenario F.....	F5-9
Figure 5.10	Alternative Development Scenario G.....	F5-10
Figure 5.11	Alternative Development Scenario H.....	F5-11
Figure 6.1	Layout Plan of Three Alternative Routes.....	F6-1
Figure 6.2	General Layout and Profile of Selected Kaliwa-Angono Water Conveyance Route.....	F6-2
Figure 6.3	Existing Primary Main	F6-3
Figure 6.4	Preliminary Layout Plan of Distribution Trunk Mains.....	F6-4
Figure 7.1	General Layout Plan and Typical Section of Agos Dam.....	F7-1
Figure 7.2	General Layout Plan and Typical Section of Kanan No.2 Dam.....	F7-2
Figure 7.3	General Layout Plan and Typical Section of Kaliwa Low Dam (Temporary Type).....	F7-3
Figure 7.4	General Layout Plan and Typical Section of Laiban Low Dam.....	F7-4
Figure 7.5	Implementation Schedule of Alternative Development Scenarios.....	F7-5
Figure 8.1	Proposed Master Plan.....	F8-1
Figure 8.2	Morphological Change of Infanta-General Nakar Alluvial Plain and Coastlines during 1952-1995.....	F8-2
Figure 8.3	Master Plan – Implementation Schedule.....	F8-3
Figure 10.1	Structural Organization of Water-related Departments and Agencies of the Government.....	F10-1

ABBREVIATION

ACP	:	Asbestos Cement Pipe
ADB	:	Asian Development Bank
AMSL	:	Above Mean Sea Level
ANR	:	Assisted Natural Regeneration
ASEAN	:	Association of Southeast Asian Nations
AWLR	:	Automatic Water Level Recorder
AWSOP	:	Angat Water Supply Optimization Project
AWWA	:	American Waterworks Association
BIR	:	Bureau of Internal Revenue
BOD	:	Biochemical Oxygen Demand
BOO	:	Build Operate Own
BOT	:	Build-Operate-and-Transfer
BP	:	Bank Policy
BRS	:	Bureau of Research and Standards
BSWM	:	Bureau of Soils and Water Management
CA	:	Concession Agreement
CALABARZON	:	"Cavite, Laguna, Batangas, Rizal and Quezon Provinces"
CAPEX	:	Capital Expenditure
CARP	:	Comprehensive Agrarian Reform Program
CBFM	:	Community-Based Forestry Management
CD	:	Community Development
CDO	:	Cease and Desist Order
CENRO	:	Community Environment and Natural Resources Office
CERA	:	Currency Exchange Rate Adjustment
CFRD	:	Concrete Face Rockfill Dam
CO	:	Community Organization
COA	:	Commission On Audit
CPC	:	Certificate for Public Convenience
CPCN	:	Certificate for Public Conveniences and Necessity
CPI	:	Consumer's Price Index
DA	:	Department of Agriculture
DAO	:	DENR Administrative Order
DAR	:	Department of Agrarian Reform
DBCC	:	Development Budget Coordination Committee of NEDA
DECS	:	Department of Education, Culture and Sports
DENR	:	Department of Environment and Natural Resources
DFI	:	Development Financing Institutes
DILG	:	Department of Interior and Local Government
DMA	:	District Metering Area
DMS	:	Detailed Measurement Survey
DMZ	:	District Monitoring Zone
DO	:	Dissolved Oxygen
DOE	:	Department Energy
DOF	:	Department Of Finance
DOH	:	Department of Health
DPWH	:	Department of Public Works and Highways
DSCR	:	Debt Service Coverage Ratio
DSWD	:	Department of Social Welfare and Development

DTI	:	Department of Trade and Industry
EA	:	Executing Agency
ECAs	:	Environmentally Critical Areas
ECC	:	Environmental Compliance Certificate
ECPs	:	Environmental Critical Projects
ECRD	:	Earth Core Rockfill Dam
EDCOP	:	Engineering and Development Corporations Of the Philippines
EIA	:	Environmental Impact Assessment
EIARC	:	EIA Review Committee
EIRR	:	Economic Internal Rate of Return
EIS	:	Environmental Impact Statement
ELC	:	ELC Electroconsult
EMB	:	Environmental Management Bureau
EMMP	:	Environmental Management and Monitoring Plan
EMP	:	Environmental Management Plan
EMS	:	Environmental Management System
EO	:	Executive Order
EPA	:	Extraordinary Price Adjustment
ERB	:	Energy Regulatory Board (of DOE)
EVAT	:	Expanded Value Added Tax
FC	:	Foreign Currency
FGD	:	Focus Group Discussion
FIRR	:	Financial Internal Rate of Return
FMB	:	Forest Management Bureau
F/S	:	Feasibility Study
FSL	:	Full Supply Level
G.S.	:	Gauging Station
GDP	:	Gross Domestic Products
GHD	:	Gutteridge Haskins and Davey Pty Ltd.
GI	:	Galvanized Iron
GNP	:	Gross National Products
GOCC	:	Government Owned and Controlled Corporations
GOJ	:	Government of Japan
GOP	:	Government of the Philippines
GRDP	:	Gross Regional Domestic Products
HP	:	Hydropower
HUDCC	:	Housing and Urban Development Coordinating Council
HWL	:	High Water Level
IAs	:	Implementing Agencies
IBRD	:	International Bank for Reconstruction and Development or the World Bank
ICC	:	Investment Coordination Committee of NEDA
ICCs	:	Indigenous Cultural Communities
IEC	:	Information-Education and Communications
IEE	:	Initial Environmental Examination
IICDA	:	Infanta Integrated Community Development Assistance
IOL	:	Inventory of Losses
IPs	:	Indigenous Peoples
IPRA	:	Indigenous People's Right Act
IRR	:	Implementing Rules and Regulations

IU	:	International Union for the Conservation of Nature and Natural Resources
JBIC	:	The Japan Bank for International Cooperation
JICA	:	Japan International Cooperation Agency
JVC	:	Joint Venture Company
JWWA	:	Japan Waterworks Association
LC	:	Local Currency
LCB	:	Local Competitive Bidding
LFPR	:	Labor Force Participation Rate
LGU	:	Local Government Unit
LLDA	:	Laguna Lake Development Authority
Lpcd	:	Liter per capita per day
LPG	:	Liquefied Petroleum Gas
LTPDP	:	Long-term Philippines Development Plan
LWL	:	Low Water Level
LWUA	:	Local Water Utilities Administration
M/P	:	Master Plan Study
MARILAQUE	:	Manila-Rizal-Laguna-Quezon
MEMSI	:	"MADECOR Environmental Management Systems, Inc."
MENT	:	Multi-Partite Environment Monitoring Team
MERALCO	:	Manila Electric Company
MGB	:	Mines and Geosciences Bureau
MLD	:	Million Liter per Day
MMDA	:	Metro Manila Development Authority
MMT	:	Multi-partite Monitoring Team
MMUTIS	:	Metropolitan Manila Urban Transportation Information System
MOA	:	Memorandum of Agreement
MOL	:	Minimum Operation Level
MTPDP	:	Medium-Term Philippines Development Plan
MWCI	:	Manila Water Company Inc.
MWSI	:	Maynilad Water Services Inc.
MWSP	:	Manila Water Supply Project
MWSRP	:	Manila Water Supply Rehabilitation Project
MWSS	:	Metropolitan Waterworks and Sewerage System
NAMRIA	:	National Mapping and Resource Information Authority
NATM	:	New Austrian Tunneling Method
NCIP	:	National Commission on Indigenous Peoples
NCR	:	National Capital Region
NEDA	:	National Economic and Development Authority
NEPC	:	National Environmental Protection Council
NGO	:	Non-Government Organization
NGOs	:	Non-Government Organizations
NIA	:	National Irrigation Administration
NP Junction	:	Novaliches Portal Junction
NPC	:	National Power Corporation
NPCC	:	National Pollution Control Commission
NRW	:	Non-Revenue Water
NSCB	:	National Statistical Coordination Board
NSDW	:	National Standard for Drinking Water
NSO	:	National Statistical Office
NTFW	:	Non-timber Forest Product

NTU	:	Nephelometric Turbidity Unit
NWDCC	:	National Water Data Coordinating Center (to be created)
NWRB	:	National Water Resources Board
NWRMP	:	National Water Resources Master Plan
O&M	:	Operation and Maintenance
ODA	:	Official Development Assistance
OP	:	Office of the President
PAC	:	Poly Aluminum Chloride
PAFs	:	Project Affected Families
PAGASA	:	Philippine Atmospheric, Geophysical and Astronomical Services Administration
PAMB	:	Protected Area Management Board
PAPs	:	Project Affected Persons
PD	:	Presidential Decree
PENRO	:	Provincial Environment and Natural Resources Officer
PFDA	:	Philippine Fisheries Development Authority
PHILVOLCS	:	Philippine Institute of Volcanology and Seismology
PHP	:	Philippine Peso
PMF	:	Probable Maximum Flood
PMP	:	Probable Maximum Precipitation
PNSDW	:	Philippine National Standards for Drinking Water
PO	:	People's Organization
PR	:	Public Relations
PROC	:	Proclamation
P/S	:	Power Station
PSY 2000	:	Philippine Statistical Yearbook 2000
PTFWRDM	:	Presidential Task Force on Water Resources Development and Management
PVC	:	Poly Vinyl Chloride
QUEZELCO	:	Quezon Electric Company
RA	:	Republic Act
RAP	:	Resettlement Action Plan
RBW	:	Receiving Body of Water
RBWA	:	River Basin and Watershed Authorities
RCCD	:	Roller Compacted Concrete Dam
REECS	:	"Resources, Environment and Economics Center for Studies"
RIZWADA	:	Rizal Water Districts Association
ROE	:	Return on Equity
ROW	:	Right Of Way
RPV	:	Pressure Reducing Valve
SAMAKA	:	Samahang Mahalin ang Kalikasan
SAMAKABAY	:	Samahang Magsasaka ng Bantay Bayan
SCP	:	Strategic Communications Plan
SEC	:	Securities and Exchange Commission
SES	:	Socio-Economic Survey
S.G.S.	:	Streamflow Gauging Station
SMBDSM	:	Samahan ng Magsasaka sa Bundok na Dahilig ng Sierra Madre, Inc.
SO ₂	:	Sulfur Oxides
STP	:	Sewerage Treatment Plant
SR	:	Service Reservoir
SRD	:	Social Resettlement Division

TBM	:	Tunnel Boring Machine
TCD	:	Tribal Community Development
TCU	:	True Color Unit
TDS	:	Total Dissolved Solids
TOR	:	Terms Of Referece
TRANSCO	:	National Transmission Company
TSS	:	Total Suspended Solids
UATP	:	Umiray-Angat Transbasin Project
UP	:	Univerdity of the Philippines
UPSARDFI	:	"UP Social Action and Research for Development Foundation, Inc."
WACC	:	Weighted Average Cost of Capital
WB	:	World Bank
WCS	:	Water Conveyance Schemes
WCT	:	Water Conveyance Tunnel
WD	:	Water District
WRAP	:	Water Resources Authority of the Philippines
WRDP	:	Water Resources Development Project
WTP	:	Water Treatment Plant
WtP	:	Willingness to Pay

Measurements

Length

mm	=	millimeter
cm	=	centimeter
m	=	meter
km	=	kilometer

Area

m ²	=	square meter
ha	=	hectare
km ²	=	square kilometer
cu m	=	cubic meter

Volume

cm ³	=	cubic centimeter
l	=	liter
kl	=	kiloliter
m ³	=	cubic meter

Derived Measures

m/sec	=	meter per second
m ³ /sec	=	cubic meter per second
kWh	=	kilowatt hour
MWh	=	megawatt hour
GWh	=	gigawatt hour
PPM	=	parts per million
kmph	=	kilometer per hour
MLD	=	million liter per day
mg/l	=	milligram per liter

Weight

g	=	gram
kg	=	kilogram
ton	=	metric ton

Currency

PHP	=	Philippine Peso
¥	=	Japanese Yen
US\$	=	US Dollar

Time

sec	=	second
min	=	minute
hr	=	hour
d	=	day
y	=	year

Other Measure

%	=	percent
°	=	degree
°C	=	degree(s) Celsius
10 ³	=	thousand
10 ⁶	=	million
10 ⁹	=	billion

Energy

W	=	watt
kW	=	kilowatt
MW	=	Megawatt