

**PART 2**  
**DATA BOOK**


## **I DRAWINGS**

## **I. Drawings**


1. General Layout Plan
2. Entire Flow Monitoring System
3. General Layout Plan of Optical Fiber Cable
4. Intake Facilities ; Yard Pipe (Conveyance Pipeline)
5. Intake Facilities; Process Flow Diagram
6. Intake/WTP Facilities; General Single Line
7. Surge Tank 1 (from Intake to WTP)
8. WTP; General Layout Plan
9. WTP; General Plan and Section
10. WTP; Hydraulic Profile (Phase 1 &2)
11. Surge Tank 2 (from WTP to Nashirabad Reservoir)
12. Nashirabad Reservoir; General Layout Plan
13. Nashirabad Reservoir ; Section
14. Hydraulic Profile from Nashirabad Reservoir to each Elevated Tank/Distribution Reservoir
15. Nashirabad Elevated Tank (Phase 1 Project)
16. Nashirabad Reservoir; General Single Line Diagram
17. Battali Hill Reservoir(Phase 1 Project) and Location of Sector Inlet Chamber
18. Hali Shahar Elevated Tank ; Plan and Section
19. General Layout Plan of KSA
20. General Layout Plan of Sector
21. Sector and DMA Inlet Chamber
22. House Connection ; Section



2. Entire Flow Monitoring System



### 3. General Layout Plan of Optical Fiber Cable



**Preparatory Survey on Chittagong Water Supply Improvement Project**

**Karnaphuli Water Supply System**


**General Layout Plan of Optical Fiber Cable**

SCALE: NONE

DWG No. WWS-IG-01




5. Intake Facilities; Process Flow Diagram





6. Intake / WTP Facilities; General Single Line




Preparatory Survey on Chittagong Water Supply Improvement Project	
Kamaphuli Water Treatment Plant	SCALE: NONE
<b>GENERAL SINGLE LINE DIAGRAM -1</b>	DWG. No. WTP-E-01




### 8. WTP; General Layout Plan



9. WTP; General Plan and Section




10. WTP; Hydraulic Profile (Phase 1&2)




Preparatory Survey on Chittagong Water Supply Improvement Project		SCALE:	NONE
Karnaphuli Water Treatment Plant		DWG. No.	WTP-G-IP-02
WTP	Hydraulic Profile (Phase 1 & 2)		

11. Surge Tank 2 (from WTP to Nashirabad Reservoir)




12. Nashirabad Reservoir; General Layout Plan



13. Nashirabad Reservoir; Section


Section S=1/400



Preparatory Survey on Chittagong Water Supply Improvement Project	
Nashirabad Reservoir	SCALE: NONE
Section	DWG. No. NR-R-G-02




14. Hydraulic Profile from Nashirabad Reservoir to each Elevated Tank/Distribution Reservoir




Preparatory Survey on Chittagong Water Supply Improvement Project	
Transmission Facilities	SCALE: NONE
Hydraulic Profile (from Nashirabad Reservoir to Elevated Tank/Distribution Reservoir)	DWG. No. G-WI-HP-01

15. Nashirabad Elevated Tank (Phase 1 Project)



Preparatory Survey on Chittagong Water Supply Improvement Project		SCALE:	NONE
Nashirabad Reservoir		DWG. No.	NR-E (1-6-0)
Plan & Section under Phase 1 Project			


16. Nashirabad Reservoir; General Single Line Diagram




Nashirabad Reservoir

Preparatory Survey on Chittagong Water Supply Improvement Project	
Karnaphuli Water Treatment Plant	SCALE: NONE
<b>GENERAL SINGLE LINE DIAGRAM -2</b>	DWG.No. WTP-E-02

17. Battali Hill Reservoir (Phase 1 Project) and Location of Sector Inlet Chamber




18. Halishahar Elevated Tank; Plan and Section




Preparatory Survey on Chittagong Water Supply Improvement Project		SCALE: NONE
Halishahar Elevated Tank		DWG. No: MH-ET-0-01
Elevated Tank	Plan and Section	


19. General Layout Plan of KSA



20. General Layout Plan of Sector




21. Sector and DMA Inlet Chamber



Preparatory Survey on Chittagong Water Supply Improvement Project		SCALE:
Distribution Facilities		DWG. No. NONE
Sector and DMA Inlet Chamber		DR-DMA-C-01



22. House Connection; Section



Preparatory Survey on Chittagong Water Supply Improvement Project	
Distribution Pipeline	SCALE: NONE
House Connection : Section	DWG. No. DP-HC-C-01

## **II SOIL INVESTIGATION**

## II. Soil Investigation

### II.1 Halishahar Site

**CLIENT:**  
JICA/CWASA



**REPORT ON:**  
SUB-SOIL INVESTIGATION OF HALISHAHOR PROJECT FOR  
FEASIBILITY STUDY OF KARNAPHULI WATER SUPPLY PROJECT  
PHASE-2 AT HALISHAHOR, CHITTAGONG.

**CONSULTANT:**  
NJS CONSULTANTS

SEPTEMBER - 2012.

## REPORT ON SUB-SOIL INVESTIGATION (Halishahar Site)

SLNO.	CONTENTS
1	INTRODUCTION
2	METHODOLOGY
3	CLIENT
4	LOCATION
5	SCOPE OF WORK
6	FIELD WORK
7	LABORATORY TESTS
8	SOIL COMPOSITION
9	CORRELATION TABLE OF SOILS BASED ON SPT
10	PHYSICAL PROPERTIES
11	ENGINEERING PROPERTIES
12	EVALUATION OF BEARING CAPACITY
13	FORMULA USED FOR COMPUTATION
14	COMPUTATION FOR CONSOLIDATION SETTLEMENT
15	CONCLUSIONS
16	RECOMMENDATIONS
17	ATTACHMENT:
	A. SITE PLAN
	B. BORING LOGS
	C. GRAIN SIZE ANALYSIS TEST
	D. UNCONFINED COMPRESSION TEST
	E. CONSOLIDATION TEST
	F. DIRECT SHEAR TEST
	G. SUMMARY SHEET

## 1.0 INTRODUCTION:

A reasonably accurate conception about the subsoil parameters of any project site is an essential priority for proper planning and designing the foundation of the concerned structure, So that the structure after its construction would remain safe and stable throughout its service period. Paying due considerations to JICA Survey Team, was agreed to offer the sub-surface investigation work of the same in favour of **BETS Consulting Services Ltd.**, Engineering Consultant, a well reputed geotechnical firm in Dhaka, Bangladesh.

According to work order of representative of the client, a detailed sub-soil study comprising execution of **3 (Three)** number borings up to **19.5-21.0m** deep, including the different field and laboratory tests was carried out and results analysis, report preparation & report submission etc had been undertaken and all official correspondence carried out by BETS, during the period of **SEPTEMBER-2012**.

## 2.0 METHODOLOGY:

BETS sent one SPT Test team for field test at the site. According to the work order, Team Leader of SPT Test team contacted with representative of client for recognizing the selected land and locations for field test. The location of bore holes was selected in presence of the representative of client.

## 3.0 CLIENT:

JICA Survey Team.  
NJS CONSULTANTS

## 4.0 LOCATION:

HALISHAHOR, CHITTAGONG.

## 5.0 SCOPE OF WORK:

*The main scopes of this investigation work are:*

- a. Execution of exploratory borings, recording of sub-soil stratification and position of ground water table.
- b. Execution of standard penetration test (SPT) at an interval of **1.5m** depth with collection of disturbed soil samples up to final depth exploration of each boring.
- c. Collection of 1 nos. undisturbed soil samples by thin walled Shelby tubes for each bore hole.
- d. Preparation of final report with all works including detailed description of soil stratification sub-soil.
- e. From the field tests and laboratory tests, scope of calculation for bearing capacity values for design shallow foundation.
- f. For loose and soft strata, from the field test and laboratory tests, scope of calculation for skin friction and bearing values for design deep foundation.

## 6.0 FIELD WORKS:

All the field works and field tests were conducted as per standard procedure as laid down in ASTM specification are as follows:

### **6.1 EXPLORATORY BORING DRILLING:**

Drilling was executed by wash boring method. A hole was started by driving vertically a 4" diameter steel casing into the ground to some depth and then the formation ground casing was broken up by repeated drops of a chopping bit attached to the lower end of drilling pipe. The upper end of the same was forced at high pressure through pressure pipe. Forced slurry or water emerges at high velocity through the pores of the chopping bit, and returns to the surface through the annular space between drilling pipe and the side of the casing or hole, carrying with it the broken-up soil. In this way drilling is advanced up to a level of 6" above the depth, where SPT has to be executed.

### **6.2 STANDARD PENETRATION TEST:**

Standard penetration Tests have been executed in all the bore holes at 1.5m. intervals of depth up to the final depth of in this test, a split spoon sampler of 2" out diameter and 1-3/8" inner diameter, is made to penetrate 18", for boring. Into the soil by drops of a hammer weighing 140lb. falling freely for a height of 30 inches. Number of blows of hammer required for penetration of each 6" length of the sampler is recorded. The number of blows last 12" penetration of the total 18" is know as the standard penetration value (N-values) as specified by ASTM and is plotted the SPT value of the particular depth.

### **6.3 EXTRACTION OF SOIL SAMPLE:**

The Disturbed soil samples were collected at 1.5m. intervals and at every change of soil strata split spoon sampler. These soil samples were studied visually and the soil classification were done to prepare strata chart of soils up to the explored depth. Before collection of samples, the hole is washed and cleaned the drill pipe with the help of an adapter and is lowered into the hole. The sampler is then pressed down into the ground in one rapid continuous movement until the tube, except 4inches from the top is filled with soil sample.

Undisturbed soil samples were collected at a depth where layer of soil is changed such as 8ft to 12ft. Undisturbed soil samples area collected by means of thin walled sharp ended 3inch dia. stationary piston sampler from the cohesive soil formation. The collected tubes were then labeled with detailed job designation, date and shifted the laboratory for testing.

## **7.0 LABORATORY TESTS:**

All Laboratory Tests conducted on soil samples collected either in the disturbed or in the undisturbed state. All tests were done as per ASTM procedures, are as follows:

### **7.1 NATURAL MOISTURE CONTENT:**

The water content of a soil sample is the ratio of the weight of the water in the sample to its dry weight. It is usually expressed as a percentage. The soil sample is weight both in natural state and in over dry state and the moisture content is calculated by dividing the loose of weight of the sample by its dry weight.

### **7.2 COMPLETE GRAIN SIZE ANALYSIS:**

The object of grain size analysis is to determine the size of the soil grains, and the percentage by weight of soil particles of different particles size, comprising a soil sample. The process consists of either sieve analysis or hydrometer analysis or both. The hydrometer analysis is adopted for sample passing sieve No. 200. For hydrometer analysis, a 40 gms of the over dry sample, is thoroughly mixed with required quantity of water in a calibrated glass cylinder. In order to avoid flocculation, a little dispersing agent is added. The density of the suspension is measured at specified time intervals, by means of a hydrometer or special design. At any particular time the size of the largest particle remounting in suspension at the level of the hydrometer can be computed by means of stocks Law, where as he weight of the particles finer than that size, can be computed from the density of the suspension at the same level.

The mixture is washed through U.S standard sieve No. 200 and the fraction retained is dried. The fraction retained on each sieve is weighed for calculation of the percentage of different fraction. The results are represented by cumulative curves plotted on semi-logarithmic graph paper.

### 7.3 ATTERBERG LIMITS:

Physical properties of clay are greatly influenced by water content. A given soil behave as a fluid or a soil or, as a plastic materials, depending on how much water its contains. The water contents that correspond to the boundaries between the states of consistency are called as the Atterberg limit.

Liquid Limit is the minimum water content at which a clay soil just starts behaving like a fluid. It is determined with the help of a standard limit device which consists of brass cup and an arrangement to impart blows to cap at a uniform rate. The water content at which 25 blows are required is termed as the limit.

The plastic limit is the minimum water content at which a soil is just plastic and is determined by rolling out a soil sample at slowly decreasing water content until, the desired water content is reached, at which a thread of 3mm diameter just begins to crumble. The thread is rolled on glass plate with hand.

### 7.4 SPECIFIC GRAVITY TEST:

The specific gravity of soil particles ( $G_s$ ) is defined as the ratio of the mass of given volume of soil particles to the mass of an equal volume of water at 40C. The specific gravity of a solid for most natural soils falls in general range of 2.60 to 2.80. To determine the specific gravity of soil sample, 25 grams of over dried soil sample is thoroughly pulverized and is placed in a calibrated psychomotor. Water is poured inside the pycnometer until its top is slightly below the calibrated mark. The mixture is then boiled thoroughly in order to eliminate all the air bubbles. More water is then added to the mixture till it over-night, the temperature is then recorded and the bottle is weighed.

The specific gravity  $G_s$  is given by:

$$G_s = \frac{G_t \cdot W_s}{W_s - W_1 + W_2}$$

Where,

- $G_t$  = Specific gravity of water at TOC.
- $W_s$  = The weight of over dry soil (25gms.)
- $W_1$  = Weight of flask + soil + water.
- $W_2$  = Weight of flask + water.

### 7.5 DIRECT SHEAR TEST:

Direct shear test can be performed for both cohesion less & cohesive soil to determine shear strength, angle of internal friction, cohesion  $c$ , volume change etc. The test is done in a direct shear machine which consists of a normal loading device; shearing displacement of approximately 10mm per minute is often for a sample used for a sample thickness of about 1.2cm.

The results of a direct shear test on a cohesion less & cohesive soil can be presented in a summary table & by stress-strain curve. A stress-strain curve normally consists of shear stress, various shear displacement for both the undisturbed and the remolded test under a specified normal load the normal load usually varies from  $1/3\text{kg/cm}^2$  to  $1\text{kg/cm}^2$ . Another curve of normal stress verses shearing stress will give angle of internal and cohesion for cohesive soil.

### 7.6 UNCONFINED COMPRESSION TEST:

Unconfined compression test is a simple method for determination of shearing strength of cohesive soil which is important to determine the bearing capacity of soil. As the name implies, the lateral confining pressure in an unconfined compression test is kept zero, unsupported specimen and at failure is measured. The specimen is prepared from the undisturbed soil sample by carefully trimming it to a cylindrical shape of 7cm height and 3.5cm dia. The specimen is then placed on the level pedestal of the unconfined compression apparatus in a vertical position. The load is applied axially on the top of the specimen an is distributed uniformly over surface of the specimen with the help of

double providing ring assembly fitted with a strain gauge, fitted with the apparatus. The load is applied at such a rate that the vertical deformation of the sample is nearly 2% (two percent) per minute in order to avoid and drainage during compression. The load is kept increasing until the specimen fails along shearing plane. The maximum load at failure known as the unconfined compressive strength of the sample the shearing strength of the sample is half of the unconfined compressive strength.

### 7.7 CONSOLIDATION TEST:

The gradual process of compression of soil under the action of static load and with decrease of void ratio due to expulsion of water from the soil pores is termed consolidation. The phenomenon compressibility characteristics of a soil as the period and magnitude of settlement of a foundation depends on these characteristics. The test is performed on a specimen of circular shape of 6.35cm dia and 2.54cm thickness, the specimen is prepared from the undisturbed sample by carefully trimming it to the required dimension with the help of a cutting edge and wire saw.

The specimen is then placed in the consolidation ring and its top and bottom are trimmed off level with that of the ring. The specimen along with the ring on the top and the other at the bottom of the specimen. The load is then applied on porous stone and on the specimen with the help of a level arrangement with the apparatus.

Decreases in volume of specimen are read from a strain gauge attached to the consolidation unit at specified time intervals the consolidation unit is always kept full with water in order to avoid evaporation of the specimen. The load increment is allowed after each twenty four hours, The observed readings are then plotted on semi-logarithmic graph paper to give the pressure-void ratio curve from which compression index,  $C_c$  can be calculated.  $C_c$  is an important factor governing the settlement process of underlying soils.

### 8.0 SOIL COMPOSITION:

#### 8.1 DESCRIPTION OF SOIL COMPOSITION:

The following terms are used in this report for description of soil composition:

- Trace fine sand : 1 to 10% fine sand.
- Little silt : 11 to 20% silt.
- Some clay : 20 to 35% clay.
- Sandy silt : 35 to 50% sand & 50 to 70% silt.
- Clayey silt : 35 to 50% clay & 50 to 70% silt.
- Silty sand : 35 to 50% silt & 50 to 70 % sand.

### 9.0 CORRELATION TABLE OF SOILS BASED ON SPT-VALUES:

Two tables for Cohesion-less and cohesive soils based on N- Values as below:

#### 9.1 values of Unit Weight and Angle of Internal Friction of Cohesion-less soil Based on N-Values (After K. Terzaghi and R. B. Peck):

**Table No. 1.**

N-Values	Condition	Relative Density	Angle of Internal Friction	Moist Unit Wt. in gm/cc.
0-4	Very loose	0.0-0.2	25 <sup>0</sup> -30 <sup>0</sup>	1.12-1.60
4-10	Loose	0.2-0.4	30 <sup>0</sup> -35 <sup>0</sup>	1.44-1.84
10-30	Medium	0.4-0.6	35 <sup>0</sup> -40 <sup>0</sup>	1.76-2.08
30-50	Dense	0.6-0.85	40 <sup>0</sup> -45 <sup>0</sup>	1.76-2.24
Over 50	Very dense	1.00	45 <sup>0</sup>	2.08-2.40



The tabulated values apply for dry/moist cohesion less sand. For silty sands the bearing capacity values must be reduced by study of grain size classification and applying judgment. Correction for water table close to bottom of foundation the bearing values should be reduced to half. The bearing values are, however, not affected by the water table at a depth greater than 1.5B below foundation level, B being least dimension of the bottom of foundation. Bearings values for intermediate position of water table may be reduced by liner interpolation.

**9.2 Values of approximate Unconfined Compressive Strength Based on N-Values for Cohesive Soil (After K. Terzaghi and R.B. Peck):**

**Table No.- 2.**

N-Values	Condition	Unconfined compressive Strength in Kg/cm <sup>2</sup> .
Below 2	Very soft	Below 0.25
2-4	Soft	0.25-0.50
4-8	Medium	0.50-1.00
8-16	Stiff	1.00-2.00
16-32	Very stiff	2.00-4.00
Over 32	Hard	Over 4.00

In the above table the shear strength of cohesive soil is equal to 1/2 of unconfined compressive strength and the angle of shearing resistance is equal to zero. It should be remembered that the correlation for cohesive soil is always much reliable.

**10.0 PHYSICAL PROPERTIES:**

Physical Properties of the subsoil formation of the project area have been evaluated by the execution of **3(Three)** number borings of **19.5-21.0m** deep (firm strata). The overall physical properties may be summarized as follows:

**10.1 STRATIFICATION OF SOIL:**

The top soil is light brown soft to medium clay, some silt the underlying soil is grey coarse sand, trace silt.

**10.2 CONSISTENCY/COMPACTNESS:**

Up to the depth of EGL to 6.0m, consistency of the top soil usually varies from soft to medium consistency of soil, however, gradually increase the consistency. The subsequent deep layers stiff to medium stiff soil state.

**10.3 GROUND WATER TABLE:**

The position of Ground Water Table (GWT) is about (-) **0.0-0.60m** from existing ground level.

**10.4 Natural Moisture Content, Unit Weight, Specific Gravity and Liquid Limit:**

**Table No .3 Name of the Laboratory Test:**

Name of the Soil Test
Natural Moisture Content
Natural Unit Weight
Dry density
Specific Gravity
Liquid Limit
Plasticity index
Grain Size Distribution
Direct shear test
Consolidation test
Unconfined compressive test

## 11.0 ENGINEERING PROPERTIES:

The engineering properties of soil, including the cohesion, compressibility and the angle of internal granular friction have been determined by performing laboratory tests on the soil samples collected during field investigation. These are as follows:

**11.1 COHESION:** The values of cohesion, as reported from the performance of unconfined compression tests from Laboratory Test Sheet.

### 11.2 ANGLE OF INTERNAL FRICTION:

The angle of internal friction values of the investigated of soil, as reported from the performance of direct shear test from Laboratory Test Sheet.

**11.3 COMPRESSIBILITY:** The top layer of plastic silty soil usually has been observed moderately compressible in nature by consolidation tests from Laboratory Test Sheet.

## 12.0 EVALUATION OF BEARING CAPACITY:

### 12.1 BEARING CAPACITIES OF THE SHALLOW CONDITION FROM THE SPT:

The Bearing capacities of the shallow foundation particularly for the top layer of cohesive soil may be estimated from the SPT values, as suggested by Terzaghi, according to the following table.

**Table No.- 4:** Bearing Capacities of the shallow foundation (Values in kg/cm<sup>2</sup>, F. S. =2.50):

SPT range	Allowable Bearing Capacity (Tsf)	
	Continuous Footing (B=4ft)	Isolated Column Footing (B=8ft)
0-2	0.00 - 0.225	0.00 - 0.30
2-4	0.225 - 0.45	0.30 - 0.60
4-8	0.45 - 0.90	0.60 - 1.20
8-15	0.90 - 1.80	1.20 - 2.40
15-30	1.80-3.60	2.40-4.80
>30	> 3.60	> 4.80

Note:

- width = 4ft for strip footing and width = 8ft for isolated footing respectively.
- The above values are the net allowable Bearing capacities.
- The cohesive soil has been considered in a saturated condition.

### 12.2 BEARING CAPACITY OF THE SHALLOW FOUNDATION FROM THE SOIL PARAMETERS:

The bearing capacities of the shallow foundation may more appropriately be determined from the parameters of soil such as the values of cohesion and the angle of internal friction as obtained from the performance of laboratory tests. These have been done considering the general equations of the Bearing capacity of the foundation as suggested by Terzaghi. The evaluated values are provided in the following Table no. 5, and Table no.6

**Table No. 5.** Bearing Capacities of the Shallow Foundation from Field and Laboratory Test  
(Values in kg/cm<sup>2</sup>, F. S. = 2.50):

Bore Hole	Depth in m	Field SPT	Cohesion kg/cm <sup>2</sup>	Bearing Capacity (kg/cm <sup>2</sup> )	
				For strip Foundation	For circular or square footing
BH-01	1.5	5	0.23	0.56	0.75
	3.0	1	0.05	0.11	0.15
	4.5	4	0.18	0.45	0.60
	6.0	7	0.32	0.79	1.05

BH-02	1.5	2	0.09	0.23	0.30
	3.0	1	0.05	0.11	0.15
	4.5	1	0.05	0.11	0.15
	6.0	12	0.55	1.35	1.80
BH-03	1.5	4	0.18	0.45	0.60
	3.0	3	0.14	0.34	0.45
	4.5	2	0.09	0.23	0.30
	6.0	14	0.64	1.58	2.10

**Table No.6:** The Skin Friction and the End Bearing Capacities of Piles (F.S. =2.50)

Depth m	BH-01					BH-02				
	N	N <sub>cor</sub>	Cu kg/cm <sup>2</sup>	f <sub>s</sub> kg/cm <sup>2</sup>	f <sub>b</sub> kg/cm <sup>2</sup>	N	N <sub>cor</sub>	Cu kg/cm <sup>2</sup>	f <sub>s</sub> kg/cm <sup>2</sup>	f <sub>b</sub> kg/cm <sup>2</sup>
1.5	5	-	0.23	0.03	-	2	-	0.09	0.01	-
3.0	1	-	0.05	0.01	-	1	-	0.05	0.01	-
4.5	4	-	0.18	0.03	-	1	-	0.05	0.01	-
6.0	7	-	0.32	0.05	-	12	-	0.55	0.08	-
7.5	14	-	-	0.10	6.24	15	-	-	0.10	6.69
9.0	25	20	-	0.14	10.70	18	17	-	0.11	8.83
10.5	28	22	-	0.15	13.42	21	18	-	0.12	11.23
12.0	35	25	-	0.17	17.85	24	20	-	0.13	13.92
13.5	43	29	-	0.20	23.29	35	25	-	0.17	20.08
15.0	50	33	-	0.22	28.99	40	28	-	0.19	24.53
16.5	50	33	-	0.22	31.88	40	28	-	0.19	26.98
18.0	50	33	-	0.22	34.78	47	31	-	0.21	33.17
19.5	50	33	-	0.22	37.70	50	33	-	0.22	37.70
21.0						50	33	-	0.22	40.59

Depth m	BH-03				
	N	N <sub>cor</sub>	Cu kg/cm <sup>2</sup>	f <sub>s</sub> kg/cm <sup>2</sup>	f <sub>b</sub> kg/cm <sup>2</sup>
1.5	4	-	0.18	0.03	-
3.0	3	-	0.14	0.02	-
4.5	2	-	0.09	0.01	-
6.0	14	-	0.64	0.10	-
7.5	12	-	-	0.08	5.35
9.0	17	16	-	0.11	8.56
10.5	21	18	-	0.12	11.23
12.0	16	16	-	0.11	11.07
13.5	27	21	-	0.14	16.86
15.0	43	29	-	0.20	25.87
16.5	35	25	-	0.17	24.53
18.0	48	32	-	0.21	33.71
19.5	50	33	-	0.22	37.70
21.0	50	33	-	0.22	40.59

Note:

- N=Blows/ft, Cu=C
- f<sub>s</sub> = Allowable value of the skin friction.
- f<sub>b</sub> = Allowable value of the pile end bearing capacity.
- SPT (N) values are corrected within calculation.
- The values of f<sub>s</sub> and f<sub>b</sub> have been making preliminary estimate about the carrying capacity of a Bored R.C.C. pile.
- In the case of plastic silty soil, the values of the cohesion have been obtained from the SPT values.

### 13.0 FORMULA USED FOR COMPUTATION:

#### **FOR COHESIVE SOIL:**

The ultimate bearing capacity:

$$Q_{ult} = CN_c = \frac{Q_u \cdot N_c}{2} \text{ ( J. E. Bowles)}$$

$$q_{all} = \frac{q_u \cdot N_c}{2 \times 3} + \gamma D_f = \frac{q_u \cdot N_c}{6} + \gamma D_f \text{ (Factor of safety = 2.50)}$$

Where, q<sub>u</sub> = Unconfined Compressive Strength in kg/cm<sup>2</sup>.

N<sub>c</sub> = Bearing Capacity Factor

= 6.8 square footing.

= 5.7 continuous footing.

**FOR COHESION-LESS SOIL:**

$$Q_{ult} = C N_c S_c + \gamma D_f N_q + 0.5 \gamma B N_\gamma S_\gamma \quad (\text{J. E. Bowles})$$

Where, C = Cohesion,  $\gamma$  = Unit weight of soil

$D_f$  = Depth of footing, B = Width of footing

$N_c$ ,  $N_q$  &  $N_\gamma$  = bearing capacity factors =  $f(\Phi) = f(N)$

$S_c$ ,  $S_\gamma$  = Shape Factors =  $f(B, D_f)$

$$Q_{allowable} = Q_{ult}/F.S. \quad (F.S. = 2.5)$$

(Ref. Book: Foundation Analysis and Design by J. E. Bowles, page No. 213-277)

**ULTIMATE SKIN FRICTION ( $f_s$ ) AND END BEARING ( $f_b$ )**

**FOR COHESIVE SOIL :**

$$f_s = FC_d \quad (\text{M. J. Tomlinson})$$

Where,  $C_d = q_u/2$ ;

$q_u$  = Unconfined Compressive strength of soil and

F = Bearing Capacity Factor (Ranges between 0.45 to 0.60)

**FOR COHESION-LESS SOIL:**

For high displacement piles,  $f_s = 2.0 N \text{ kN/m}^2$

For low displacement  $f_s = 1.0 N \text{ kN/m}^2$

Where, N average of corrected N- value along the length of the pile.

For bored piles in sand,  $f_b = 14 N (D_b/B) \text{ kN/m}^2$

Where  $D_b$  = actual penetration into the granular soil.

For bored pile in sand, the unit frictional resistance ( $f_s$ ) is given by

$$f_s = 0.67 N \text{ kN/m}^2 \quad (\text{K. R. Arora}).$$

**CONSOLIDATION SETTLEMENT:**

$$S = C_c / (1+e_o) * H * \log (p_o + \Delta p) / p_o.$$

(Ref. Book: Soil Mechanics and Foundation Engineering by K. R. ARORA, Page NO. - 383-450, 638-647 & 1003-1006).

**STANDARD PENETRATION TEST:**

$$N \text{ correction} = 15 + 0.5(N' - 15)$$

Where, N correction = Corrected N- value

$N'$  = SPT value from the field

(Ref. Book: Theory and Practice of Foundation Design by N.N. SOM & S.C. DAS. Page no-42.)

**LOAD CALCULATION FOR ANY DIAMETER/ANY LENGTH OF PILE:**

$$P = \pi D L f_s + \pi D^2 / 4 f_b$$

Where,

P = Allowable working Load

$f_s$  = Average Allowable value of the skin friction =  $\text{Kg/cm}^2$

$f_b$  = Allowable value of the pile end bearing capacity =  $\text{Kg/cm}^2$

$\pi$  = A constant = 3.1416

D = Pile Diameter

L = Required length of pile = m

**14.0 COMPUTATION FOR CONSOLIDATION SETTLEMENT:**

The vertical downward movement of the base of a structure is called settlement and its effect upon the structure depends on its magnitude, its uniformity, the length of the time over which it takes place, and the nature of the clay soils. The consolidation settlement can be calculated from test result of unit weight and consolidation tests. The average settlement depends on column load of structure.

## 15.0 CONCLUSIONS:

On the basis of above analysis and discussions, the following conclusions may be drawn regarding the sub-soil condition of the project area.

- a. The overall soil formation of the investigated site are more or less regular in between the Bore hole locations.
- b. The top layers of the investigated site have been encountered with comprising light brown soft to medium clay, some silt (Ref. Bore logs).
- c. The underlying soil is grey coarse sand, trace silt. (Ref. Bore logs).
- d. Bearing capacities for shallow foundation including isolated column footings are may not be suitable (Ref. - Table – 5 )
- e. Shallow foundation as isolated column footing may not be provided at the project site.
- f. **R. C. C. Cast-In-Situ Pile** may be provided for all borings at project site.

## 16.0 RECOMMENDATIONS:

On the basis of aforesaid conclusions, the following recommendations are suggested for **PROJECT: GEOTECHNICAL INVESTIGATION OF FEASIBILITY STUDY OF KARNAPHULI WATER SUPPLY PROJECT PHASE-2 AT HALISHAHOR, CHITTAGONG.**

### **R.C.C CAST-IN-SITU PILE:**

The average bearing capacities (F.S=2.50) of different or same diameter piles with embedment length up to **50.0ft or 15.0m** from **EGL** for each bore hole, may be considered as follows:

**31.16** Ton for 400 mm or 16 inch.dia pile


**37.10** Ton for 450 mm or 18 inch.dia pile

**43.50** Ton for 500 mm or 20 inch.dia pile

**57.67** Ton for 600 mm or 24 inch.dia pile

Note:


- a.  $1 \text{ Tsf} = 1 \text{ kg/cm}^2 = 2\text{ksf}$ ,  $1 \text{ Ton} = 2000 \text{ lbs} = 9.81 \text{ kN}$ ,  $1\text{m} = 3.28\text{ft}$ , **EGL** = Existing Ground level & **F. S.** = Factor of Safety.
- b. **The designer may select any other alternative type, depth as well as the bearing capacity of the foundation in the light of information provided in this report.**
- c. Foundation base should be kept dry during construction period.




<b>BETS</b>	<b>SUMMARY SHEET</b>	CLIENT : CWASA. PROJECT : PROPOSED PROJECT. LOCATION : HALISHAHOR, CHITTAGONG.
-------------	----------------------	--


Bore Hole No.	Sample No.	Depth In m	Wet Unit Weight (kg/m <sup>3</sup> )	Dry Unit Weight (kg/m <sup>3</sup> )	Natural Moisture Content (%)	Liquid Limit (%)	Plasticity Index (%)	Unconfined Compression Test		Consolidation Test		Triaxial Shear Test		Direct Shear Test		Grain Size Test			
								Strength (kg/cm <sup>2</sup> )	Strain at failure (%)	Compression Index (cc)	Void (e <sub>v</sub> )	φ°	Cohesion (kg/cm <sup>2</sup> )	φ°	Cohesion (kg/cm <sup>2</sup> )	SAND (%)	SILT (%)	CLAY (%)	S. P. Gravity
01	D-02	3.00	1947.19	1521.24	26								29.65	0.36	-	35	65	2.65	
	D-07	10.50	-	-	27								32.35	0.00	61	39	-	2.66	
	D-10	15.00	-	-	26								37.49	0.00	85	15	-	2.68	
02	D-02	3.00	1942.96	1517.94	28					0.721			28.83	0.31	-	36	64	2.64	
	D-07	10.50	-	-	26					-			33.12	0.00	65	35	-	2.65	
	D-10	15.00	-	-	26					-			36.89	0.00	86	14	-	2.69	
03	D-02	3.00	1932.99	1498.45	29					0.718			27.00	0.28				2.65	
	D-07	10.50	-	-	28					-			33.45	0.00				2.66	
	D-10	15.00	-	-	27					-			36.73	0.00				2.68	



TESTED BY: \_\_\_\_\_ CHECKED BY: \_\_\_\_\_















## II.2 Nashirabad Site

**CLIENT:**  
**JICA/CWASA**



**REPORT ON:**  
**SUB-SOIL INVESTIGATION OF NASHIRABAD RESERVOIR FOR  
FEASIBILITY STUDY OF KARNAPHULI WATER SUPPLY PROJECT  
PHASE-2 AT NASHIRABAD, CHITTAGONG.**

**CONSULTANT:**  
**NJS CONSULTANTS**

**SEPTEMBER - 2012.**

## REPORT ON SUB-SOIL INVESTIGATION (Nashirabad Site)

SLNO.	CONTENTS
1	INTRODUCTION
2	METHODOLOGY
3	CLIENT
4	LOCATION
5	SCOPE OF WORK
6	FIELD WORK
7	LABORATORY TESTS
8	SOIL COMPOSITION
9	CORRELATION TABLE OF SOILS BASED ON SPT
10	PHYSICAL PROPERTIES
11	ENGINEERING PROPERTIES
12	EVALUATION OF BEARING CAPACITY
13	FORMULA USED FOR COMPUTATION
14	COMPUTATION FOR CONSOLIDATION SETTLEMENT
15	CONCLUSIONS
16	RECOMMENDATIONS
17	ATTACHMENT:
	A. SITE PLAN
	B. BORING LOGS
	C. GRAIN SIZE ANALYSIS TEST
	D. UNCONFINED COMPRESSION TEST
	E. CONSOLIDATION TEST
	F. DIRECT SHEAR TEST
	G. SUMMARY SHEET

## 1.0 INTRODUCTION:

A reasonably accurate conception about the subsoil parameters of any project site is an essential priority for proper planning and designing the foundation of the concerned structure, So that the structure after its construction would remain safe and stable throughout its service period. Paying due considerations to JICA Survey Team, was agreed to offer the sub-surface investigation work of the same in favour of **BETS Consulting Services Ltd.**, Engineering Consultant, a well reputed geotechnical firm in Dhaka, Bangladesh.

According to work order of representative of the client, a detailed sub-soil study comprising execution of **4(Four)** number borings up to **13.5-19.5m** deep, including the different field and laboratory tests was carried out and results analysis, report preparation & report submission etc had been undertaken and all official correspondence carried out by BETS, during the period of **SEPTEMBER-2012**.

## 2.0 METHODOLOGY:

BETS sent one SPT Test team for field test at the site. According to the work order, Team Leader of SPT Test team contacted with representative of client for recognizing the selected land and locations for field test. The location of bore holes was selected in presence of the representative of client.

## 3.0 CLIENT:

JICA Survey Team.  
NJS CONSULTANTS

## 4.0 LOCATION:

NASIRABAD, CHITTAGONG.

## 5.0 SCOPE OF WORK:

The main scopes of this investigation work are:

- a. Execution of exploratory borings, recording of sub-soil stratification and position of ground water table.
- b. Execution of standard penetration test (SPT) at an interval of **1.5m** depth with collection of disturbed soil samples up to final depth exploration of each boring.
- c. Collection of 1 nos. undisturbed soil samples by thin walled Shelby tubes for each bore hole.
- d. Preparation of final report with all works including detailed description of soil stratification sub-soil.
- e. From the field tests and laboratory tests, scope of calculation for bearing capacity values for design shallow foundation.
- f. For loose and soft strata, from the field test and laboratory tests, scope of calculation for skin friction and bearing values for design deep foundation.

## 6.0 FIELD WORKS:

All the field works and field tests were conducted as per standard procedure as laid down in ASTM specification are as follows:

### **6.1 EXPLORATORY BORING DRILLING:**

Drilling was executed by wash boring method. A hole was started by driving vertically a 4" diameter steel casing into the ground to some depth and then the formation ground casing was broken up by repeated drops of a chopping bit attached to the lower end of drilling pipe. The upper end of the same was forced at high pressure through pressure pipe. Forced slurry or water emerges at high velocity through the pores of the chopping bit, and returns to the surface through the annular space between drilling pipe and the side of the casing or hole, carrying with it the broken-up soil. In this way drilling is advanced up to a level of 6" above the depth, where SPT has to be executed.

### **6.2 STANDARD PENETRATION TEST:**

Standard penetration Tests have been executed in all the bore holes at 1.5m. intervals of depth up to the final depth of in this test, a split spoon sampler of 2" out diameter and 1-3/8" inner diameter, is made to penetrate 18", for boring. Into the soil by drops of a hammer weighing 140lb. falling freely for a height of 30 inches. Number of blows of hammer required for penetration of each 6" length of the sampler is recorded. The number of blows last 12" penetration of the total 18" is know as the standard penetration value (N-values) as specified by ASTM and is plotted the SPT value of the particular depth.

### **6.3 EXTRACTION OF SOIL SAMPLE:**

The Disturbed soil samples were collected at 1.5m. intervals and at every change of soil strata split spoon sampler. These soil samples were studied visually and the soil classification were done to prepare strata chart of soils up to the explored depth. Before collection of samples, the hole is washed and cleaned the drill pipe with the help of an adapter and is lowered into the hole. The sampler is then pressed down into the ground in one rapid continuous movement until the tube, except 4inches from the top is filled with soil sample.

Undisturbed soil samples were collected at a depth where layer of soil is changed such as 8ft to 12ft. Undisturbed soil samples area collected by means of thin walled sharp ended 3inch dia. stationary piston sampler from the cohesive soil formation. The collected tubes were then labeled with detailed job designation, date and shifted the laboratory for testing.

## **7.0 LABORATORY TESTS:**

All Laboratory Tests conducted on soil samples collected either in the disturbed or in the undisturbed state. All tests were done as per ASTM procedures, are as follows:

### **7.1 NATURAL MOISTURE CONTENT:**

The water content of a soil sample is the ratio of the weight of the water in the sample to its dry weight. It is usually expressed as a percentage. The soil sample is weight both in natural state and in over dry state and the moisture content is calculated by dividing the loose of weight of the sample by its dry weight.

### **7.2 COMPLETE GRAIN SIZE ANALYSIS:**

The object of grain size analysis is to determine the size of the soil grains, and the percentage by weight of soil particles of different particles size, comprising a soil sample. The process consists of either sieve analysis or hydrometer analysis or both. The hydrometer analysis is adopted for sample passing sieve No. 200. For hydrometer analysis, a 40 gms of the over dry sample, is thoroughly mixed with required quantity of water in a calibrated glass cylinder. In order to avoid flocculation, a little dispersing agent is added. The density of the suspension is measured at specified time intervals, by means of a hydrometer or special design. At any particular time the size of the largest particle remounting in suspension at the level of the hydrometer can be computed by means of stocks Law, where as he weight of the particles finer than that size, can be computed from the density of the suspension at the same level.

The mixture is washed through U.S standard sieve No. 200 and the fraction retained is dried. The fraction retained on each sieve is weighed for calculation of the percentage of different fraction. The results are represented by cumulative curves plotted on semi-logarithmic graph paper.

### 7.3 ATTERBERG LIMITS:

Physical properties of clay are greatly influenced by water content. A given soil behave as a fluid or a soil or, as a plastic materials, depending on how much water its contains. The water contents that correspond to the boundaries between the states of consistency are called as the Atterberg limit.

Liquid Limit is the minimum water content at which a clay soil just starts behaving like a fluid. It is determined with the help of a standard limit device which consists of brass cup and an arrangement to impart blows to cap at a uniform rate. The water content at which 25 blows are required is termed as the limit.

The plastic limit is the minimum water content at which a soil is just plastic and is determined by rolling out a soil sample at slowly decreasing water content until, the desired water content is reached, at which a thread of 3mm diameter just begins to crumble. The thread is rolled on glass plate with hand.

### 7.4 SPECIFIC GRAVITY TEST:

The specific gravity of soil particles ( $G_s$ ) is defined as the ratio of the mass of given volume of soil particles to the mass of an equal volume of water at 40C. The specific gravity of a solid for most natural soils falls in general range of 2.60 to 2.80. To determine the specific gravity of soil sample, 25 grams of over dried soil sample is thoroughly pulverized and is placed in a calibrated psychomotor. Water is poured inside the pycnometer until its top is slightly below the calibrated mark. The mixture is then boiled thoroughly in order to eliminate all the air bubbles. More water is then added to the mixture till it over-night, the temperature is then recorded and the bottle is weighed.

The specific gravity  $G_s$  is given by:

$$G_s = \frac{G_t \cdot W_s}{W_s - W_1 + W_2}$$

Where,

- $G_t$  = Specific gravity of water at TOC.
- $W_s$  = The weight of over dry soil (25gms.)
- $W_1$  = Weight of flask + soil + water.
- $W_2$  = Weight of flask + water.

### 7.5 DIRECT SHEAR TEST:

Direct shear test can be performed for both cohesion less & cohesive soil to determine shear strength, angle of internal friction, cohesion  $c$ , volume change etc. The test is done in a direct shear machine which consists of a normal loading device; shearing displacement of approximately 10mm per minute is often for a sample used for a sample thickness of about 1.2cm.

The results of a direct shear test on a cohesion less & cohesive soil can be presented in a summary table & by stress-strain curve. A stress-strain curve normally consists of shear stress, various shear displacement for both the undisturbed and the remolded test under a specified normal load the normal load usually varies from  $1/3\text{kg/cm}^2$  to  $1\text{kg/cm}^2$ . Another curve of normal stress verses shearing stress will give angle of internal and cohesion for cohesive soil.

### 7.6 UNCONFINED COMPRESSION TEST:

Unconfined compression test is a simple method for determination of shearing strength of cohesive soil which is important to determine the bearing capacity of soil. As the name implies, the lateral confining pressure in an unconfined compression test is kept zero, unsupported specimen and at failure is measured. The specimen is prepared from the undisturbed soil sample by carefully trimming it to a cylindrical shape of 7cm height and 3.5cm dia. The specimen is then placed on the level pedestal of the unconfined compression apparatus in a vertical position. The load is applied axially on the top of the specimen and is distributed uniformly over surface of the specimen with the help of



double providing ring assembly fitted with a strain gauge, fitted with the apparatus. The load is applied at such a rate that the vertical deformation of the sample is nearly 2% (two percent) per minute in order to avoid and drainage during compression. The load is kept increasing until the specimen fails along shearing plane. The maximum load at failure known as the unconfined compressive strength of the sample the shearing strength of the sample is half of the unconfined compressive strength.

### 7.7 CONSOLIDATION TEST:

The gradual process of compression of soil under the action of static load and with decrease of void ratio due to expulsion of water from the soil pores is termed consolidation. The phenomenon compressibility characteristics of a soil as the period and magnitude of settlement of a foundation depends on these characteristics. The test is performed on a specimen of circular shape of 6.35cm dia and 2.54cm thickness, the specimen is prepared from the undisturbed sample by carefully trimming it to the required dimension with the help of a cutting edge and wire saw.

The specimen is then placed in the consolidation ring and its top and bottom are trimmed off level with that of the ring. The specimen along with the ring on the top and the other at the bottom of the specimen. The load is then applied on porous stone and on the specimen with the help of a level arrangement with the apparatus.

Decreases in volume of specimen are read from a strain gauge attached to the consolidation unit at specified time intervals the consolidation unit is always kept full with water in order to avoid evaporation of the specimen. The load increment is allowed after each twenty four hours, The observed readings are then plotted on semi-logarithmic graph paper to give the pressure-void ratio curve from which compression index,  $C_c$  can be calculated.  $C_c$  is an important factor governing the settlement process of underlying soils.

### 8.0 SOIL COMPOSITION:

#### 8.1 DESCRIPTION OF SOIL COMPOSITION:

The following terms are used in this report for description of soil composition:

- Trace fine sand : 1 to 10% fine sand.
- Little silt : 11 to 20% silt.
- Some clay : 20 to 35% clay.
- Sandy silt : 35 to 50% sand & 50 to 70% silt.
- Clayey silt : 35 to 50% clay & 50 to 70% silt.
- Silty sand : 35 to 50% silt & 50 to 70 % sand.

### 9.0 CORRELATION TABLE OF SOILS BASED ON SPT-VALUES:

Two tables for Cohesion-less and cohesive soils based on N- Values as below:

#### 9.1 values of Unit Weight and Angle of Internal Friction of Cohesion-less soil Based on N-Values (After K. Terzaghi and R. B. Peck):

**Table No. 1.**

N-Values	Condition	Relative Density	Angle of Internal Friction	Moist Unit Wt. in gm/cc.
0-4	Very loose	0.0-0.2	25 <sup>0</sup> -30 <sup>0</sup>	1.12-1.60
4-10	Loose	0.2-0.4	30 <sup>0</sup> -35 <sup>0</sup>	1.44-1.84
10-30	Medium	0.4-0.6	35 <sup>0</sup> -40 <sup>0</sup>	1.76-2.08
30-50	Dense	0.6-0.85	40 <sup>0</sup> -45 <sup>0</sup>	1.76-2.24
Over 50	Very dense	1.00	45 <sup>0</sup>	2.08-2.40

The tabulated values apply for dry/moist cohesion less sand. For silty sands the bearing capacity values must be reduced by study of grain size classification and applying judgment. Correction for

water table close to bottom of foundation the bearing values should be reduced to half. The bearing values are, however, not affected by the water table at a depth greater than 1.5B below foundation level, B being least dimension of the bottom of foundation. Bearings values for intermediate position of water table may be reduced by liner interpolation.

**9.2 Values of approximate Unconfined Compressive Strength Based on N-Values for Cohesive Soil (After K. Terzaghi and R.B. Peck):**

**Table No.- 2.**

N-Values	Condition	Unconfined compressive Strength in kg/cm <sup>2</sup> .
Below 2	Very soft	Below 0.25
2-4	Soft	0.25-0.50
4-8	Medium	0.50-1.00
8-16	Stiff	1.00-2.00
16-32	Very stiff	2.00-4.00
Over 32	Hard	Over 4.00

In the above table the shear strength of cohesive soil is equal to 1/2 of unconfined compressive strength and the angle of shearing resistance is equal to zero. It should be remembered that the correlation for cohesive soil is always much reliable.

**10.0 PHYSICAL PROPERTIES:**

Physical Properties of the subsoil formation of the project area have been evaluated by the execution of **4(Four)** number borings of **13.5-19.5m** deep (firm strata). The overall physical properties may be summarized as follows:

**10.1 STRATIFICATION OF SOIL:**

The top soil is light brown medium clay, some silt, the underlying soil is grey coarse sand, trace silt.

**10.2 CONSISTENCY/COMPACTNESS:**

Up to the depth of EGL to 6.0m, consistency of the top soil usually varies from soft to medium consistency of soil, however, gradually increase the consistency. The subsequent deep layers stiff to medium stiff soil state.

**10.3 GROUND WATER TABLE:**

The position of Ground Water Table (GWT) is about (-) **0.0-4.50m** from existing ground level.

**10.4 Natural Moisture Content, Unit Weight, Specific Gravity and Liquid Limit:**

**Table No .3 Name of the Laboratory Test:**

Name of the Soil Test
Natural Moisture Content
Natural Unit Weight
Dry density
Specific Gravity
Liquid Limit
Plasticity index
Grain Size Distribution
Direct shear test
Consolidation test
Unconfined compressive test

**11.0 ENGINEERING PROPERTIES:**

The engineering properties of soil, including the cohesion, compressibility and the angle of internal granular friction have been determined by performing laboratory tests on the soil samples collected during field investigation. These are as follows:

**11.1 COHESION:** The values of cohesion, as reported from the performance of unconfined compression tests from Laboratory Test Sheet.

**11.2 ANGLE OF INTERNAL FRICTION:**

The angle of internal friction values of the investigated of soil, as reported from the performance of direct shear test from Laboratory Test Sheet.

**11.3 COMPRESSIBILITY:** The top layer of plastic silty soil usually has been observed moderately compressible in nature by consolidation tests from Laboratory Test Sheet.

**12.0 EVALUATION OF BEARING CAPACITY:**

**12.1 BEARING CAPACITIES OF THE SHALLOW CONDITION FROM THE SPT:**

The Bearing capacities of the shallow foundation particularly for the top layer of cohesive soil may be estimated from the SPT values, as suggested by Terzaghi, according to the following table.

**Table No.- 4: Bearing Capacities of the shallow foundation (Values in kg/cm<sup>2</sup>, F. S. =2.50):**

SPT range	Allowable Bearing Capacity (Tsf)	
	Continuous Footing (B=4ft)	Isolated Column Footing (B=8ft)
0-2	0.00 - 0.225	0.00 - 0.30
2-4	0.225 - 0.45	0.30 - 0.60
4-8	0.45 - 0.90	0.60 - 1.20
8-15	0.90 - 1.80	1.20 - 2.40
15-30	1.80-3.60	2.40-4.80
>30	> 3.60	> 4.80

Note:

- a. width = 4ft for strip footing and width = 8ft for isolated footing respectively.
- b. The above values are the net allowable Bearing capacities.
- c. The cohesive soil has been considered in a saturated condition.

**12.2 BEARING CAPACITY OF THE SHALLOW FOUNDATION FROM THE SOIL PARAMETERS:**

The bearing capacities of the shallow foundation may more appropriately be determined from the parameters of soil such as the values of cohesion and the angle of internal friction as obtained from the performance of laboratory tests. These have been done considering the general equations of the Bearing capacity of the foundation as suggested by Terzaghi. The evaluated values are provided in the following Table no. 5, and Table no.6

**Table No. 5. Bearing Capacities of the Shallow Foundation from Field and Laboratory Test**  
(Values in kg/cm<sup>2</sup>, F. S. = 2.50):

Bore Hole	Depth in m	Field SPT	Cohesion kg/cm <sup>2</sup>	Bearing Capacity (kg/cm <sup>2</sup> )	
				For strip Foundation	For circular or square footing
BH-01	1.5	4	0.18	0.45	0.60
	3.0	7	0.32	0.79	1.05
	4.5	12	0.55	1.35	1.80
	6.0	20	0.92	2.25	3.00

BH-02	1.5	4	0.18	0.45	0.60
	3.0	3	0.14	0.34	0.45
	4.5	41	1.88	4.61	6.15
	6.0	50	2.29	5.63	7.50
BH-03	1.5	5	0.23	0.56	0.75
	3.0	18	0.83	2.03	2.70
	4.5	9	0.41	1.01	1.35
	6.0	12	0.55	1.35	1.80
BH-04	1.5	6	0.28	0.68	0.90
	3.0	7	0.32	0.79	1.05
	4.5	11	0.50	1.24	1.65
	6.0	18	0.83	2.03	2.70

**Table No.6: The Skin Friction and the End Bearing Capacities of Piles (F.S. =2.50)**

Depth m	BH-01					BH-02				
	N	N <sub>cor</sub>	Cu kg/cm <sup>2</sup>	f <sub>s</sub> kg/cm <sup>2</sup>	f <sub>b</sub> kg/cm <sup>2</sup>	N	N <sub>cor</sub>	Cu kg/cm <sup>2</sup>	f <sub>s</sub> kg/cm <sup>2</sup>	f <sub>b</sub> kg/cm <sup>2</sup>
1.5	4	-	0.18	0.03	-	4	-	0.18	0.03	-
3.0	7	-	0.32	0.05	-	3	-	0.14	0.02	-
4.5	12	-	0.55	0.08	-	41	28	1.28	0.19	-
6.0	20	18	0.80	0.12	-	50	33	1.49	0.22	-
7.5	25	20	-	0.14	8.92	50	33	-	0.22	14.50
9.0	27	21	-	0.14	11.24	50	33	-	0.22	17.39
10.5	24	20	-	0.13	12.17	50	33	-	0.22	20.28
12.0	18	17	-	0.11	11.78	50	33	-	0.22	23.21
13.5	28	22	-	0.15	17.26	50	33	-	0.22	26.10
15.0	43	29	-	0.20	25.87					
16.5	50	33	-	0.22	31.88					
18.0	50	33	-	0.22	34.78					
19.5	50	33	-	0.22	37.70					

Depth m	BH-03					BH-04				
	N	N <sub>cor</sub>	Cu kg/cm <sup>2</sup>	f <sub>s</sub> kg/cm <sup>2</sup>	f <sub>b</sub> kg/cm <sup>2</sup>	N	N <sub>cor</sub>	Cu kg/cm <sup>2</sup>	f <sub>s</sub> kg/cm <sup>2</sup>	f <sub>b</sub> kg/cm <sup>2</sup>
1.5	5	-	0.23	0.03	-	6	-	0.28	0.04	-
3.0	18	17	0.76	0.11	-	7	-	0.32	0.05	-
4.5	9	-	0.41	0.06	-	11	-	0.50	0.07	-
6.0	12	-	0.55	0.08	-	18	17	0.76	0.11	-
7.5	14	-	-	0.10	6.24	21	18	-	0.12	8.03
9.0	20	18	-	0.12	9.36	27	21	-	0.14	11.24
10.5	50	33	-	0.22	20.28	40	28	-	0.19	17.16
12.0	50	33	-	0.22	23.21	50	33	-	0.22	23.21
13.5	50	33	-	0.22	26.10	50	33	-	0.22	26.10
15.0						50	33	-	0.22	28.99

Note:

- N=Blows/ft, Cu=C
- f<sub>s</sub> = Allowable value of the skin friction.
- f<sub>b</sub> = Allowable value of the pile end bearing capacity.
- SPT (N) values are corrected within calculation.
- The values of f<sub>s</sub> and f<sub>b</sub> have been making preliminary estimate about the carrying capacity of a Bored R.C.C. pile.
- In the case of plastic silty soil, the values of the cohesion have been obtained from the SPT values.

### 13.0 FORMULA USED FOR COMPUTATION:

#### **FOR COHESIVE SOIL:**

The ultimate bearing capacity:

$$Q_{ult} = CN_c = \frac{Q_u \cdot N_c}{2} \text{ ( J. E. Bowles)}$$

$$q_{all} = \frac{q_u \cdot N_c}{2 \times 3} + \gamma D_f = \frac{q_u \cdot N_c}{6} + \gamma D_f \text{ (Factor of safety = 2.50)}$$

Where,  $q_u$  = Unconfined Compressive Strength in  $\text{kg/cm}^2$ .

$N_c$  = Bearing Capacity Factor

= 6.8 square footing.

= 5.7 continuous footing.

#### **FOR COHESION-LESS SOIL:**

$$Q_{ult} = C N_c S_c + \gamma D_f N_q + 0.5 \gamma B N_\gamma S_\gamma \text{ ( J. E. Bowles)}$$

Where, C = Cohesion,  $\gamma$  = Unit weight of soil

$D_f$  = Depth of footing, B = Width of footing

$N_c$ ,  $N_q$  &  $N_\gamma$  = bearing capacity factors =  $f(\Phi) = f(N)$

$S_c$ ,  $S_\gamma$  = Shape Factors =  $f(B, D_f)$

$$Q_{allowable} = Q_{ult} / F.S. \text{ ( F.S. = 2.5)}$$

(Ref. Book: Foundation Analysis and Design by J. E. Bowles, page No. 213-277)

#### **ULTIMATE SKIN FRICTION ( $f_s$ ) AND END BEARING ( $f_b$ ) FOR COHESIVE SOIL :**

$$f_s = FC_d \text{ ( M. J. Tomlinson)}$$

Where,  $C_d = q_u / 2$ ;

$q_u$  = Unconfined Compressive strength of soil and

F = Bearing Capacity Factor (Ranges between 0.45 to 0.60)

#### **FOR COHESION-LESS SOIL:**

For high displacement piles,  $f_s = 2.0 \text{ N kN/m}^2$

For low displacement  $f_s = 1.0 \text{ N kN/m}^2$

Where, N average of corrected N- value along the length of the pile.

For bored piles in sand,  $f_b = 14 \text{ N } (D_b/B) \text{ kN/m}^2$

Where  $D_b$  = actual penetration into the granular soil.

For bored pile in sand, the unit frictional resistance ( $f_s$ ) is given by

$$f_s = 0.67 \text{ N kN/m}^2 \text{ ( K . R. Arora).}$$

#### **CONSOLIDATION SETTLEMENT:**

$$S = C_c / (1 + e_o) * H * \log (p_o + \Delta p) / p_o.$$

(Ref. Book: Soil Mechanics and Foundation Engineering by K. R. ARORA, Page NO. - 383-450, 638-647 & 1003-1006).

#### **STANDARD PENETRATION TEST:**

$$N \text{ correction} = 15 + 0.5(N' - 15)$$

Where, N correction = Corrected N- value

$N'$  = SPT value from the field

(Ref. Book: Theory and Practice of Foundation Design by N.N. SOM & S.C. DAS. Page no-42.)

#### **LOAD CALCULATION FOR ANY DIAMETER/ANY LENGTH OF PILE:**

$$P = \pi D L f_s + \pi D^2 / 4 f_b$$

Where,

P = Allowable working Load

$f_s$  = Average Allowable value of the skin friction =  $\text{Kg/cm}^2$

$f_b$  = Allowable value of the pile end bearing capacity =  $\text{Kg/cm}^2$

$\pi = A$  constant=3.1416  
D =Pile Diameter  
L =Required length of pile = m

#### 14.0 COMPUTATION FOR CONSOLIDATION SETTLEMENT:

The vertical downward movement of the base of a structure is called settlement and its effect upon the structure depends on its magnitude, its uniformity, the length of the time over which it takes place, and the nature of the clay soils. The consolidation settlement can be calculated from test result of unit weight and consolidation tests. The average settlement depends on column load of structure.

#### 15.0 CONCLUSIONS:

On the basis of above analysis and discussions, the following conclusions may be drawn regarding the sub-soil condition of the project area.

- a. The overall soil formation of the investigated site are more or less regular in between the Bore hole locations.
- b. The top layers of the investigated site have been encountered with comprising light brown medium clay, some silt (Ref. Bore logs).
- c. The underlying soil is grey course sand, trace silt. (Ref. Bore logs).
- d. Bearing capacities for shallow foundation including isolated column footings are may not be suitable (Ref. - Table – 5 )
- e. Shallow foundation as isolated column footing may not be provided at the project site.
- f. **R. C. C. Cast-In-Situ Pile** may be provided for all borings at project site.

#### 16.0 RECOMMENDATIONS:

On the basis of aforesaid conclusions, the following recommendations are suggested for **PROJECT: GEOTECHNICAL INVESTIGATION OF FEASIBILITY STUDY OF KARNAPHULI WATER SUPPLY PROJECT PHASE-2 AT NASIRABAD, CHITTAGONG.**

##### **R.C.C CAST-IN-SITU PILE:**

The average bearing capacities (F.S=2.50) of different or same diameter piles with embedment length up to **50.0ft or 15.0m** from **EGL** for **BH-01**, may be considered as follows:

**28.08** Ton for 400 mm or 16 inch.dia pile  
**33.42** Ton for 450 mm or 18 inch.dia pile  
**39.17** Ton for 500 mm or 20 inch.dia pile  
**51.88** Ton for 600 mm or 24 inch.dia pile

The average bearing capacities (F.S=2.50) of different or same diameter piles with embedment length up to **25.0ft or 7.5m** from **EGL** for **BH-02**, may be considered as follows:


**15.58** Ton for 400 mm or 16 inch.dia pile  
**18.56** Ton for 450 mm or 18 inch.dia pile  
**21.76** Ton for 500 mm or 20 inch.dia pile  
**28.84** Ton for 600 mm or 24 inch.dia pile

The average bearing capacities (F.S=2.50) of different or same diameter piles with embedment length up to **35.0ft or 10.5m** from **EGL** for **BH-03 & BH-04**, may be considered as follows:

**21.81** Ton for 400 mm or 16 inch.dia pile  
**25.96** Ton for 450 mm or 18 inch.dia pile  
**30.44** Ton for 500 mm or 20 inch.dia pile  
**40.35** Ton for 600 mm or 24 inch.dia pile

Note:


- a. 1 Tsf =  $1 \text{ kg/cm}^2 = 2\text{ksf}$ , 1 Ton = 2000 lbs = 9.81 kN, 1m = 3.28ft, EGL = Existing Ground level & F. S. = Factor of Safety.
- b. The designer may select any other alternative type, depth as well as the bearing capacity of the foundation in the light of information provided in this report.**
- c. Foundation base should be kept dry during construction period.





<b>BETS</b>		<b>SUMMARY SHEET</b>										CLIENT : CWASA					
												PROJECT : PROPOSED PROJECT.					
												LOCATION : MASIRABAD, CHITTAGONG.					
Bore Hole No.	Sample No.	Depth in m	Wet Unit Weight (kg/m <sup>3</sup> )	Dry Unit Weight (kg/m <sup>3</sup> )	Natural Moisture Content (%)	Liquid Limit (%)	Plasticity Index (%)	Unconfined Compression Test		Consolidation Test		Torsional Shear Test		Grain Size Test			S. F. Gravity
								Strength (kg/cm <sup>2</sup> )	Strain at Failure (%)	Compression Index (cc)	Void (%)	$\phi'$	cohesion (kg/cm <sup>2</sup> )	$\phi'$	cohesion (kg/cm <sup>2</sup> )	SS&D (%)	
01	D-2	3.00	1963.95	1534.34	28					0.720		30.47°	0.37				2.67
	D-19	15.00	-	-	27					-		34.06°	0.00				2.69
02	D-2	3.00	1959.78	1531.08	28					0.718		31.47°	0.45	-	34	66	2.66
	D-47	10.50	-	-	27					-		36.8°	0.00	66	15	-	2.68
03	D-2	3.00	1955.60	1527.81	28					0.689		39.75°	0.39				2.65
	D-47	10.50	-	-	26					-		35.86°	0.00				2.67
04	D-2	3.00	1957.59	1541.34	27					0.712		30.07°	0.41	-	32	66	2.66
	D-47	10.50	-	-	27					-		35.74°	0.00	67	13	-	2.69


TESTED BY:
CHECKED BY:



















### **III GROUND LEVEL SURVEY**

### III Ground Level Survey

