


4.1.6 Willingness-To-Pay Survey For Use of CLLEX (Private Car Users)

a. Survey Locations and Hypothetical Question for Willingness-to-pay Survey

Figure 4.1.6-1 shows the survey locations where the willingness-to-pay survey was carried-out. Samples collected from each site were treated differently to know car users' response depending on their location in relation to CLLEX. This process allows us to determine areas where high shift to expressway can be expected and areas where shift cannot be expected.

CLLEX can provide congestion-free travel to residents of Tarlac City and Cabanatuan City and neighboring municipalities. For those living in Cabanatuan side, the expressway can be used for their trips to Subic or to Baguio or to Metro Manila. See Figure 4.1.6-2 for the survey questionnaire which also presents a map showing the possible routes that can be served by the CLLEX.



Note: the same color denotes data were combined and analyzed together

FIGURE 4.1.6-1 LOCATION FOR WILLINGNESS-TO-PAY SURVEY




Expressway Projects in Mega Manila Region in the Republic of the Philippines



WILLINGNESS TO PAY SURVEY (FORM 3)

FOR STUDY PURPOSE ONLY

General Info.	Sample ID No: <input style="width: 40px;" type="text"/>	Date (month/day) <input style="width: 40px;" type="text"/>
	Location: <input type="checkbox"/> Sta. Rosa-Tarlac Road <input type="checkbox"/> Maharlika Highway (bet. Cabanatuan & Gapan) <input type="checkbox"/> Maharlika Highway (bet. Cabanatuan & Talavera)	Time <input style="width: 40px;" type="text"/>
Personal Information	1-Sex <input type="checkbox"/> Male <input type="checkbox"/> Female	
	2-Age 1)20-29 <input type="checkbox"/> 2)30-39 <input type="checkbox"/> 3)40-49 <input type="checkbox"/> 4)50-59 <input type="checkbox"/> 5)>60 <input type="checkbox"/>	
	3-Occupation <input style="width: 40px;" type="text"/> 1- Admin. 2- Professional 3- Tech./assist. 4- Clerk 5- Sale/Services 6- Farmer/fisher 7- Craftman 8- Production 9- Unskilled 10- Student 11- House wife 12- Retired 13- Jobless 14- Other (specify): _____	
Trip Information	4-Monthly Income (Pesos) 1) None 2) Under 5,000 3) 5,000-9,999 4) 10,000 - 14,999 5) 15,000 - 19,999 6) 20,000 - 29,999 7) 30,000-39,999 8) 40,000-59,999 9) 60,000-99,999 10) 100,000-149,000 11) 150,000 and above	
	5- Trip OD Where did you start this trip? _____ <i>(City/Municipality)</i> Where do you end this trip? _____ <i>(City/Municipality)</i>	
	6- Trip purpose 1.Work 2.Education 3.Home 4.Selling/Delivering 5.Meeting/business 6.Return to work place 7.Shopping/Eating 8.Sending/ Fetching 9.Recreation 10.Medical treatment 11.Social 12.Other	
Willingness to Pay	7- Current Route Which route do you usually take going to Metro Manila and back? 1. Route 1 (Maharlika Highway - NLEX) 2. Route 2 (Sta. Rosa Road - SCTEX - NLEX) 3. Others: _____	
	Hypothetical Question The government is planning to construct the Central Luzon Link Expressway (CLLEX) to link Cabanatuan City to SCTEX. Like other expressways in the country, certain amount will be collected to use the expressway.	
	8 - If you go to Tarlac or Subic, will you use CLLEX for your travel? [via Sta. Rosa Road = 70 min] [CLLEX = 20 min] Time Saved is about 40 min! 1) Yes → How much you are willing to pay? a) 50 b) 70 c) 100 2) No, I will take ordinary road why _____	
9 - If you go to Manila, will you use CLLEX for your travel? - Cabanatuan-NLEX via Maharlika Highway (166 min) - Cabanatuan-Sta.Rosa Rd-SCTEX-NLEX (130 min) - Cabanatuan-CLLEX-SCTEX-NLEX (90 min) 1) Yes → How much you are willing to pay? a) 50 b) 70 c) 100 2) No, I will take ordinary road why _____		



That's All. Thank You Very Much for Your Cooperation.

FIGURE 4.1.6-2 WILLINGNESS-TO-PAY SURVEY FORM

b. Sex Distribution

For sex distribution, most of the car users captured in the survey are male (82.8%) and the remaining 17.2% are female. See **Figure 4.1.6-3**.




FIGURE 4.1.6-3 SEX DISTRIBUTION

c. Age Distribution

For age distribution, more than half of the respondents (69.5%) are between the age range of 30 to 49. See **Figure 4.1.6-4**.




FIGURE 4.1.6-4 AGE DISTRIBUTION

d. Occupation Distribution

For occupation of the captured respondents, most of them are engaged in professional work (21.8%) and sales/services (20.5%). See **Figure 4.1.6-5**.




FIGURE 4.1.6-5 OCCUPATION DISTRIBUTION

e. Monthly Income Distribution

For monthly income, notable income brackets which the respondents belong are: 10,000-14,999 (24.0%) and 15,000-19,999 (23.8%). For respondents which declared 'none' or lack of income, they are normally students or housewives. See **Figure 4.1.6-6**.




FIGURE 4.1.6-6 MONTHLY INCOME DISTRIBUTION

f. OD Distribution

The captured OD trips at Station 1 (Tarlac – Sta. Rosa Road) are discussed below.

- 36.6% of trips come from municipalities of Nueva Ecija such as Zaragoza, San Leonardo, Munoz, Jaen, San Antonio, etc. Although Cabanatuan City is under Nueva Ecija, trip from this city is separated to distinguish the number of trips coming from this city. As shown in the figure below, 18.8% of trips originate from Cabanatuan city. Other notable origin of trips is Tarlac 17.9% and Metro Manila 14.3%. See **Figure 4.1.6-7**.
- For destination, major destinations are municipalities of Nueva Ecija such as Gapan, Zaragoza, Sta. Rosa (29.5%), Cabanatuan City (21.4%), and Tarlac (21.4%). See **Figure 4.1.6-8**.




FIGURE 4.1.6-7 ORIGIN OF TRIPS AT STATION 1 (TARLAC – STA. ROSA ROAD)




FIGURE 4.1.6-8 DESTINATION OF TRIPS AT STATION 1 (TARLAC – STA. ROSA ROAD)

For the captured OD trips at Station 2 (Cabanatuan – Gapan), this has the following features:

- Places with substantial trips originated are: Cabanatuan (30.9%), other cities/municipalities of Nueva Ecija (34.2%), and Tarlac (14.8%).
- For destinations, places which have major share are: other cities/municipalities of Nueva Ecija (21.8%), Tarlac (21.5%) and Cabanatuan City (20.8%).




FIGURE 4.1.6-9 ORIGIN OF TRIPS AT STATION 2 (PAN PHILIPPINE HIGHWAY AT CABANATUAN - GAPAN)




FIGURE 4.1.6-10 DESTINATION OF TRIPS AT STATION 2 (PAN PHILIPPINE HIGHWAY AT CABANATUAN - GAPAN)

For the captured OD trips at Station 3, this has the following features:

- Most trips come from other cities/municipalities of Nueva Ecija (36.6%), Cabanatuan City (26.8%) and Tarlac (17.2%).
- For destinations, places which have major share are: Tarlac (31.9%), Metro Manila (18.4%), other cities/municipalities of Nueva Ecija (15.7%) and Cabanatuan city (7.9%).




FIGURE 4.1.6-11 ORIGIN OF TRIPS AT STATION 3 (PAN PHILIPPINE HIGHWAY AT CABANATUAN - TALAVERA)




FIGURE 4.1.6-12 DESTINATION OF TRIPS AT STATION 2 (PAN PHILIPPINE HIGHWAY AT CABANATUAN - TALAVERA)

g. Trip Purpose Distribution

For trip distribution, most of the respondents have the following trip purpose: social (19.6%), selling/delivering (13.7%), going home (13.5%) and meeting/business (11.5%). See **Figure 4.1.6-13**.




FIGURE 4.1.6-13 TRIP PURPOSE DISTRIBUTION

h. Current Route Choice to/from Manila

The respondents were asked of their current route choice in going/from Metro Manila. There were three locations where the surveys were conducted: (i) Station 1 - Along Sta Rosa-Tarlac Road, (ii) Station 2 - Pan Philippine Highway between Gapan-Cabanatuan section, and (iii) Station 3 - Pan Philippine Highway Cabanatuan – Talavera section (See **Figure 4.1.6-1**). **Figure 4.1.6-14** illustrates the route choice per location.

Station 1 (Sta. Rosa – Tarlac Road at Zaragoza Municipality)

89% of interviewed respondents are using Route 2 (Sta. Rosa – SCTEX – NLEX route) when they travel to/from Manila and the remaining 11% still uses the direct but congested route (Pan Philippine Highway – NLEX route).

Station 2 (Gapan – Cabanatuan near Sta. Rosa Municipality)

65 % of respondents are travelling to/from Manila via Route 2 (Sta. Rosa – SCTEX – NLEX route) and substantial number (35%) still uses the shorter but congested route of Pan Philippine Highway – NLEX.

Station 3 (Cabanatuan – Talavera)

64 % of respondents are travelling to/from Manila via Route 2 (Sta. Rosa – SCTEX – NLEX route) and the remaining 36% still uses the direct Pan Philippine Highway – NLEX.





FIGURE 4.1.6-14 CURRENT ROUTE CHOICE TO/FROM MANILA

i. Will they Use CLEX to/from Tarlac/Subic (Time saved is 40 min)

As mentioned, aside from going to Metro Manila, motorists making trips between the two towns of Cabanatuan City and Tarlac City might use the expressway for their daily trips. Thus, such question was asked for car users. And as can be seen in the figure below, at all survey stations, car users' willingness to use CLLEX is very high which is above 90%. See **Figure 4.1.6-15**.




Sample size (Sta. Rosa-Tarlac = 112; Gapan-Cabanatuan = 298; Cabanatuan-Talavera = 410)

FIGURE 4.1.6-15 WILL THEY USE CLEX TO/FROM TARLAC/SUBIC

j. How much they are willing to pay to use CLEX to/from Tarlac/Subic?

As for the amount they are willing to pay to use the expressway for their trip between Tarlac/Subic and Cabanatuan City, most of the respondents is willing to pay 50 pesos. See **Figure 4.1.6-16**.




Sample size (Sta. Rosa-Tarlac = 112; Gapan-Cabanatuan = 298; Cabanatuan-Talavera = 410)

FIGURE 4.1.6-16 AMOUNT THEY ARE WILLING TO PAY TO/FROM TARLAC/SUBIC

k. Will they Use CLEX to/from Metro Manila (Time saved is 40 min)

When respondents were asked if they would also use the expressway when they travel to/from Metro Manila, motorists interviewed at Pan Philippine Highway (between Gapan – Cabanatuan) all indicated their willingness to use the expressway. Majority of respondents from other two survey stations expressed also their willingness to use the expressway (97.3% at Sta. Rosa- Tarlac Road and 93.2% at Pan Philippine Highway, Cabanatuan-Talavera Section). See **Figure 4.1.6-17**.




Sample size (Sta. Rosa-Tarlac = 112; Gapan-Cabanatuan = 298; Cabanatuan-Talavera = 410)

FIGURE 4.1.6-17 WILL THEY USE EXPRESSWAY TO/FROM METRO MANILA

l. How much they are willing to pay to use CLEX from/to Manila?

For the amount of money they are willing to pay for the use of CLLEX, majority of the respondents revealed that they are willing to pay 50 pesos. See **Figure 4.1.6-18**.



Sample size (Sta. Rosa-Tarlac = 112; Gapan-Cabanatuan = 298; Cabanatuan-Talavera = 410)

FIGURE 4.1.6-18 AMOUNT THEY ARE WILLING TO PAY TO/FROM METRO MANILA

4.1.7 Willingness-To-Pay Survey For Use of CLLEX (Bus Operators)

a. How many buses you owned? (Q5)

The number of bus owned and used for operation by the nine (9) bus companies interviewed is presented in **Table 4.1.7-1**. The total number of bus used by these companies is 1,587 bus unit or an average of 176 buses per company. Taking into account the share of each type of bus, 64% are composed of two-seater air-conditioned bus and this followed by ordinary bus (24%) and others (most of buses refer as others are 2x3 bus which means five seats in one row all together and normally 'ordinary bus' without air-conditioned) with a share of 9.0%. See survey form in Appendix 4-1.


TABLE 4.1.7-1 NUMBER OF BUS OWNED BY BUS COMPANIES

Bus Type	BC 1	BC 2	BC 3	BC 4	BC 5	BC 6	BC 7	BC 8	BC 9	Total
Mini-bus										0
Ordinary bus			20		100			19	247	386
Air-conditioned bus (single-seater)						15			29	44
Air-conditioned bus (two-seater)	10	42	45	3	200	115	10		590	1,015
Others (2x3 bus)				57		4		15	66	142
Total	10	42	65	60	300	134	10	34	932	1,587

Note: BC = Bus Company; Number of sample = 9


b. Do you allow your driver to use expressways? (Q7)

Interviewed bus managers revealed that they allow their drivers to use expressway both for single-seater (special bus) and double-seater bus (regular bus). Refer to the two figures below.



Number of sample = 9 (note that only 4 companies have single-seater bus)

FIGURE 4.1.7-1 SINGLE-SEATER BUS




Number of sample = 9

FIGURE 4.1.7-2 TWO-SEATER BUS

c. Bus Route - Cabanatuan to/from Manila? (Q8)

The bus managers were also queried regarding the route used by their drivers for Manila – Cabanatuan (and neighboring municipalities) route. Seven managers (54%) said that they are still using the NLEX-Pan Philippine highway which passes medium size towns like Bustos, San Miguel, Gapan, etc. The others revealed that they are using the NLEX - SCTEX - Sta. Rosa route which is longer but faster. See **Figure 4.1.7-3**.




Number of sample = 9; the missing 8% are not using both route (destination is Pangasinan)

FIGURE 4.1.7-3 BUS ROUTE FOR MANILA - CABANATUAN


d. Willingness-to-pay to Use CLLEX - from SCTEX to Cabanatuan? (Q10)

All of the interviewed managers except one revealed that they will allow their bus drivers to use the expressway if it served their route. The amount of toll they are willing to pay for the expressway is 200 pesos. See the two figures below.



Number of sample = 9

FIGURE 4.1.7-4 WILL THEY ALLOW THEIR BUS DRIVERS TO USE CLLEX?




Number of sample = 9

FIGURE 4.1.7-5 AMOUNT THEY ARE WILLING TO PAY?

e. Perceived Benefits by Bus Managers from CLLEX? (Q14)

If the Central Luzon Link Expressway is constructed in the future, managers of bus companies were asked if what kind of benefits that this new infrastructure can bring to their business. Most managers believed that the new expressway would reduce their operation cost (29.2%), increase frequency of trips (28.8%), and would help in reduction of accident (12.5%). Others which have a share of 12.5% refer to shortening of travel time. See **Figure 4.1.7-6**.



Number of sample = 9; Note: Respondents were allowed for multiple answers

FIGURE 4.1.7-6 PERCEIVED BENEFITS BY BUS OPERATORS OF CLLEX

f. Problems Encountered by Bus Company in their daily operations. (Q12)

Interviewed operation managers of nine (9) bus companies reveal the following as the problems they encountered in their daily operation:

- Traffic congestion along town/city center
- High maintenance cost due to poor road condition
- High operation cost due to poor road condition
- High cost of fuel
- Bad road condition of road
- Road accidents


g. Comments and Suggestions to Improve Business Operation of Bus Industry. (Q13)

The following were the comments and suggestions expressed by the interviewed bus managers' which could help improve their operation.


- Expedite repairs of damage roads and highways
- Construction of more durable and accessible roads
- To have continuous education process with our drivers on how to prevent accident and how to use expressway.
- Full implementation of traffic rules and regulations like in Subic.
- Evaluation of franchise given to bus companies

h. Bus Routes Before and After Construction of CLLEX


The current routes and number of buses that is likely to use the CLLEX if constructed in the future is shown in **Figure 4.1.7-7**. Most of these buses have their destination in Cagayan Valley which is further north from Cabanatuan City. These buses are utilizing the heavily congested Pan Philippine Highway with the exception of few which are plying through NLEX, SCTEX, Tarlac-Sta. Rosa road. The total number of buses that would utilize the CLLEX from these six (6) companies is 282 per day.




Bus Company 1




Bus Company 2



Bus Company 3



Bus Company 4



Bus Company 5



Bus Company 6

FIGURE 4.1.7-7 EXISTING BUS ROUTE AND AFTER CLLEX BUS ROUTE (WILLINGNESS TO USE)

4.1.8 Willingness-To-Pay Survey For Use of CLLEX (Truck Operators)

a. How many vehicles used for operation? (Q5)


The number of trucks used for operation by the interviewed trucking companies is shown in **Table 4.1.8-1**. The total number of trucks used for operation and owned by these ten (10) companies is 282 while the number of rented trucks reaches 444.

TABLE 4.1.8-1 NUMBER OF TRUCKS OWNED BY TRUCK COMPANIES

Type	T-1	T-2	T-3	T-4	T-5	T-6	T-7	T-8	T-9	T-10	Total	
Pick-up		2			1	1	4			6	14	
2-axle truck		2	3	9	4	6	2		(8)	8	34	(8)
3-axle truck	10			6	2	10 (10)	2	(160)	(20)	40	70	(190)
4 or more axles truck						15		(240)	(6)	73	88	(246)
Others					3					63	66	
Total	10	4	3	15	10	42 (10)	8	(400)	(34)	190	282	(444)

Note: T= Truck Company; () rented trucks used for operation

The average number of trucks per company used for operation is around 73 trucks (owned and rented). For type of trucks used by these companies, the dominant types are: 4-axle trucks (47%), 3-axle trucks (36%), and others (e.g. vans, pick-up, canter) with 9% share. See **Figure 4.1.8-1**.




No. of sample = 10

FIGURE 4.1.8-1 DISTRIBUTION OF TRUCK TYPES


b. Do you allow your truck drivers to use expressways? (Q6)

When the truck company managers were asked if they allow their drivers to use expressway in their trips, all of them revealed that they allow them to use expressway. For the issue of toll fee, all interviewed managers said that their company is the one shouldering the toll fee. See **Figure 4.1.8-2** and **Figure 4.1.8-3**.



No. of sample = 10

FIGURE 4.1.8-2 DO YOU ALLOW YOUR TRUCK DRIVERS TO USE EXPRESSWAY (YES OR NO)



No. of sample = 10

FIGURE 4.1.8-3 WHO SHOULDER THE TOLL FEE

c. Which route do you take in delivering goods from Manila to Cabanatuan and neighboring municipalities? (Q7)

Five (5) of the ten (10) managers reveals that their drivers still uses NLEX-Pan Philippine Highway when they have delivery from Manila to Cabanatuan or at neighboring municipalities. Four managers said that their drivers are using both Route 1 (NLEX-Pan Philippine) and Route 2 (NLEX-SCTEX-Sta. Rosa). One manager said that their delivery is mostly in the Pangasinan area thus their route is via NLEX-SCTEX most of the time. See **Figure 4.1.8-4**.




FIGURE 4.1.8-4 TRUCK ROUTES FOR MANILA – CABANATUAN DELIVERY

d. Will they allow their truck drivers to use CLLEX in delivering their goods? (Q10)

Only one manager expressed his intention not to allow their drivers to use CLLEX. The other nine (9) managers revealed that they will allow their drivers to use the CLLEX if it serves their route. For the amount of toll fee they are willing to pay, all of them said 200 pesos. See **Figure 4.1.8-5** and **Figure 4.1.8-6**.




FIGURE 4.1.8-5 WILL YOU ALLOW YOUR TRUCK DRIVERS TO USE CLLEX (YES OR NO)





FIGURE 4.1.8-6 HOW MUCH ARE YOU WILLING TO PAY FOR USE CLLEX

e. Perceived Benefits by Truck Managers from CLLEX (Q11)

Truck managers were also asked if what kind of benefits the Central Luzon Link Expressway can bring to their business. Most managers believed that it would help them to deliver their cargo on time (27%) and it could also help in reduction of road accidents (23%). Some believed it would increase their frequency of trips (19%) and minimize damage to cargoes (15%). See **Figure 4.1.8-7**.



No. of sample = 10; Note: Respondents were allowed for multiple answers

FIGURE 4.1.8-7 PERCEIVED BENEFITS BY TRUCK OPERATORS FROM CLLEX

f. Problems Encountered in their operations? (Q12)

The most common problems mentioned by the twenty (20) managers of trucking companies are:

- Heavy traffic at main arterials roads (Pan Philippine Highway going Cagayan Valley)
- Problem at ports and shipping lines
- Traffic congestion at roads going to client's place
- Overweight limit
- Overloading causes accidents
- Corrupt traffic enforcers
- LTO/MMDA are more interested of finding violations of trucks that enforcing traffic rules during night time
- Traffic congestion at inner roads of small towns


g. Comments that could improve their business operations? (Q13)

The following were comments made by the managers of trucking companies:


- Open new alternative routes, example Baloc - Sto. Domingo
- No truck overloading
- Government plans should be acceptable to manufacturers/trucking companies
- Fuel increase should be controlled
- Traffic enforcer should follow the government's rules and regulations
- Provisions for motorcycle lane

h. Truck Routes Before and After Construction of CLLEX


Of the ten (10) interviewed companies, nine (9) companies found the CLLEX to be useful to their current operation. As a result, at least 852 trips per month (28 trips/day) will be attracted to the CLLEX from these companies. Current routes of their trucks as well as possible routes after the construction of CLLEX are shown in **Figure 4.1.8-8**.




Truck Company 1



Truck Company 2




Truck Company 3




Truck Company 4


FIGURE 4.1.8-8 (1/2) EXISTING TRUCK ROUTE AND AFTER CLLEX BUS ROUTE




Truck Company 5



Truck Company 6



Truck Company 7



Truck Company 8

FIGURE 4.1.8-8 (2/2) EXISTING TRUCK ROUTE AND AFTER CLEX BUS ROUTE

4.1.9 Willingness-To-Pay Survey For Use of CLLEX (Manufacturing Companies)

a. Are you willing to shoulder the toll fee to be paid by trucking companies?(Q7)

The five (5) officials of manufacturing companies interviewed revealed different opinions. Three (3) of them agreed to shoulder toll fee of expressway if this can help for speedy delivery of their cargoes. On the other hand, the two (2) other interviewed officials representing two manufacturing companies said that they are not willing to pay for toll fee because this should be paid by trucking companies (See **Figure 4.1.9-1**). It should be noted that for the case of CALAX, all interviewed officials of manufacturing companies in Cavite Province expressed their willingness to shoulder toll fee.





FIGURE 4.1.9-1 PERCENTAGE OF WILLING AND NOT WILLING TO SHOULDER TOLL FEE

b. Perceived Benefits by Manufacturing Companies from CLLEX?(Q8)

For the benefits they are hoping to get after the construction of expressway, these are: faster delivery of cargoes (46%), cost reduction (18%), minimize damage on cargoes (18%) and increase access to source of raw materials (18%). See **Figure 4.1.9-2**.



No. of sample = 5; Note: Respondents were allowed for multiple answers

FIGURE 4.1.9-2 PERCEIVED BENEFITS BY MANUFACTURING COMPANIES FROM CLLEX

c. Plans by Manufacturing Companies after construction of CLLEX?(Q9)

The plans after the construction of CLLEX revealed by interviewed officials of manufacturing companies are:

- Better scheduling of delivery of raw materials
- Better scheduling of delivery of finished goods
- Try to realize cost reduction

d. Problems Encountered by Manufacturing Companies?(Q10)

The problems mentioned by the officials of manufacturing companies are:

- Late arrival of raw materials which affect our operations
- Difficulty in maintaining huge inventory levels of stock
- High cost of expressway toll fees

e. Comments and Suggestions by Manufacturing Companies?(Q11)

The following were comments made by officials of manufacturing companies:

- Roll back of diesel price
- Continuous implementation of government rules and regulations

f. Summary of Transportation Routes of Manufacturing Companies

As mentioned, five manufacturing companies were interviewed to understand their freight movement among others. Three (3) were Japanese-affiliated companies and two (2) were locally owned and some of the biggest companies in the country. Three of five (5) interviewed manufacturing companies have their factory in Tarlac. These three companies have very simple transportation routes – i.e. Tarlac via SCTEX and NLEX to Manila port or Cavite and Batangas area. Therefore, these companies have no opportunity to use CLLEX.

Two other companies are located in Nueva Ecija. CLLEX is useful to both these companies but only one company reveals their intention to use CLLEX. Another company has no plan to use the expressway because their product is not time sensitive (rice distribution). Below is the discussion for the company that had expressed intention to use CLLEX. See **Figure 4.1.9-3** for the summary of transportation routes.

1. Manufacturing Company A (Local Company)

Location : San Leonardo, Nueva Ecija
Products : Line of business is poultry and livestock feeds

- The company is getting its supplies from Tarlac City, municipalities of Ibaan and Mariveles (Batangas), and other cities/municipalities of the country via ports of Manila.
- They are currently using the Tarlac – Sta. Rosa Road in getting raw materials from Tarlac to their factory in San Leonardo and it takes them almost one hour.
- For other supplies, they are using the heavily congested Pan Philippine Highway (from Manila ports to San Leonardo and from Ibaan, Mariveles (Batangas) to San Leonardo).
- They are hoping for early construction of CLLEX which will help realize faster delivery of supplies and it will also increase their access to source of materials.
- ***If CLLEX is constructed, they intend to use the expressway instead of Tarlac – Sta. Rosa Road to avoid heavy traffic congestion which causes late arrival of raw materials.***




FIGURE 4.1.9-3 TRUCK ROUTES OF MANUFACTURING INDUSTRY IN CLLEX

4.1.10 Summary

Based on the results of the survey carried out on private car users, bus companies, trucking companies, and manufacturing companies, the following are the noted findings:

- **PRIVATE CARS:** Private car users captured at all stations revealed that they intend to use CLLEX if constructed in the future (more than 90%) for their trips to/from Manila or other regular trips that would be served by the said expressway.
- The dominant amount (85% to 97% depending on interview sites) of toll they are willing to pay to use CLLEX is 50 pesos.
- **BUS COMPANY:** Eight (8) out of nine (9) bus managers interviewed (89%) disclosed that if CLLEX is constructed in the future, they will allow their bus drivers to use it.
- All eight (8) bus managers revealed that the amount of toll they are willing to pay for the use of CLLEX is 200 pesos.
- **TRUCKING COMPANY:** Out of ten (10) interviewed managers, nine (9) affirmed their intention to allow their truck drivers to use CLLEX if it serves their delivery route.
- All nine (9) managers pointed out that the amount of toll they are willing to pay for the use of CLLEX is 200 pesos.
- **MANUFACTURING COMPANIES:** Of the five (5) managers interviewed, only two manufacturing companies found the CLLEX useful for their operations. However, only one company will utilize the expressway in getting their material supply. Another company is rice distributor and they don't intend to use CLLEX since their products are not time sensitive. The three (3) other companies have found CLLEX not useful to their current routes thus they could not use it.

4.2 FUTURE TRAFFIC DEMAND

4.2.1 Approach

To estimate the traffic volumes on CLLEX, traffic demand system data developed on the Study of Master plan on High Standard Highway Network Development funded by Japan International Cooperation Agency (hereinafter HSH), was used.

The overall flow diagram of the methodology used in forecasting the traffic volumes on CLLEX, and the present road network in the two cases of “Without Project” and “With Project”, is shown in **Figure 4.2.1-1**.




FIGURE 4.2.1-1 FORECAST OF TRAFFIC VOLUMES ON ROAD NETWORK

Traffic volumes are assigned first on the existing road network without CLLEX, which is the case of “Without Project”. Next, volume of traffic which will be handled in the future on CLLEX network are determined, which is the case of “With Project”.

In the Study, the zone system comprised of Region III (Nueva Ecija, Tarlac, Pampanga, Bulacan and etc.), NCR, Region IV-A and Region I. The total zoning number is 320 zones, presented in **Figure 4.2.1-2~3** and **Table 4.2.1-1**.

TABLE 4.2.1-1 (1) TRAFFIC ZONING SYSTEM

Small Zone	Barangay	Medium Zone	City/Municipality	Large Zone	Province	Region
1	City of Manila 1 - Barangay 20	1	City of Manila	1	Metro Manila	NCR
2	City of Manila 2 - Barangay 105					
3	City of Manila 3 - Barangay 375					
4	City of Manila 4 - Barangay 48					
5	City of Manila 5 - San Nicolas					
6	City of Manila 6 - Binondo					
7	City of Manila 7 - Barangay 310					
8	City of Manila 8 - Quiapo					
9	City of Manila 9 - Barangay 413					
10	City of Manila 10 - San Miguel					
11	City of Manila 11 - Barangay 570					
12	City of Manila 12 - Barangay 450					
13	City of Manila 13 - Port Area					
14	City of Manila 14 - Intramuros, Ermita					
15	City of Manila 15 - Paco					
16	City of Manila 16 - Malate					
17	City of Manila 17 - Santa Ana					
18	City of Manila 18 - Barangay 601					
19	City of Manila 19 - Pandacan	2	Pasay City			
20	Pasay City 1 - Barangay 46					
21	Pasay City 2 - Barangay 132					
22	Pasay City 3 - Barangay 183					
24	Pasay City 4 - Barangay 1					
82	Pasay City 5 - Barangay 76	3	Parañaque City			
23	Parañaque City 1 - Don Bosco					
25	Parañaque City 2 - Baclaran					
84	Parañaque City 2 - Sun Valley, San Martin De Porres					
85	Parañaque City 3 - Marcelo Green Village					
86	Parañaque City 4 - B.F. Homes					
92	Parañaque City 5 - San Isidro	4	Makati City			
93	Parañaque City 6 - San Dionisio					
26	Makati City 1 - Bangkal, San Lorenzo					
27	Makati City 2 - Palanan					
28	Makati City 3 - Olympia					
29	Makati City 4 - Guadalupe Viejo					
30	Makati City 5 - Bel-Air					
31	Makati City 6 - Rizal, Pembo	5	Taguig			
34	Makati City 7 - Magallanes					
32	Santa Ana	6	Mandaluyong City			
33	Taguig 1 - Western Bicutan					
81	Taguig 2 - Upper Bicutan					
83	Taguig 3 - Signal Village, Lower Bicutan					
35	Mandaluyong City 1 - Poblacion					
36	Mandaluyong City 2 - Plainview	7	Pasig City			
37	Mandaluyong City 3 - Mauway					
39	Mandaluyong City 4 - Wack-wack Greenhills					
40	San Juan 1 - West Crame					
41	San Juan 2 - Corazon de Jesus	8	Quezon City			
38	Pasig City 1 - Ugong					
78	Pasig City 2 - Santolan					
79	Pasig City 3 - Santa Lucia					
80	Pasig City 4 - Pinagbuhatan					
42	Quezon City 1 - Tatalon, Damayang Lagi					
43	Quezon City 2 - Santo Domingo (Matalahib)					
44	Quezon City 3 - Baesa, Sangandaan					
45	Quezon City 4 - Bagong Pag-asa					
46	Quezon City 5 - Pinyahan, (Trinoma/SM West)					
47	Quezon City 6 - Paltok, Del Monte					
48	Quezon City 7 - Kamuning					
49	Quezon City 8 - E. Rodriguez, Crame					
50	Quezon City 9 - Camp Aguinaldo					
51	Quezon City 10 - Kamias (East/West)					
52	Quezon City 11 - U.P. Campus					
53	Quezon City 12 - Pasong Tamo					
54	Quezon City 13 - Batasan Hills					
55	Quezon City 14 - Commonwealth					
56	Quezon City 15 - Payatas					
57	Quezon City 16 - North Fairview					
61	Quezon City 17 - Greater Lagro, Novaliches Proper					
62	Quezon City 18 - Tandang Sora					
75	Quezon City 19 - Pansol, Loyola Heights					
77	Quezon City 20 - White Plains, Libis (Eastwood)					
58	Kalookan City (North) 1 - Barangay 178	9	Kalookan City (North)			
59	Kalookan City (North) 2 - Barangay 176					
60	Kalookan City (North) 3 - Barangay 171					
63	Valenzuela City 1 - Ugong	10	Valenzuela City			
64	Valenzuela City 2 - Canumay, Maysan					
65	Valenzuela City 3 - Malinta					
66	Valenzuela City 4 - Malanday					
71	Valenzuela City 5 - Marulas					

TABLE 4.2.1-1 (2) TRAFFIC ZONING SYSTEM

Small Zone	Barangay	Medium Zone	City/Municipality	Large Zone	Province	Region	
67	Malabon 1 - Concepcion	11	Malabon	1	Metro Manila	NCR	
70	Malabon 2 - Potrero		Malabon				
68	Navotas - North Bay Blvd South		Navotas				
69	Kalookan City (South) 1 - Barangay 12		Kalookan City (South)				
72	Kalookan City (South) 2 - Barangay 132						
73	Kalookan City (South) 3 - Barangay 120						
74	Marikina City 1 - Concepcion Uno, Parang						
76	Marikina City 2 - Malanday		12				Marikina City
87	Muntinlupa City 1 - Sucat						Muntinlupa City
88	Muntinlupa City 2 - Alabang						
89	Muntinlupa City 3 - Putatan						
90	Las Pinas City 1 - Almanza (Uno, Dos)	13	Las Pinas City				
91	Las Pinas City 2 - B.F. International Village						
94	Las Pinas City 3 - Zapote						
320	Manila Port	-	-	1	Metro Manila	NCR	
133		24	BACOOR	2	CAVITE	Region IV-A	
134			IMUS				
135			CAVITE CITY				
136			KAWIT				
137			NOVELETA				
138		ROSARIO					
139	Tejero	25	GENERAL TRIAS				
140	Pasong Camachile II						
141							
142	Amaya						
143	Halayhay						
144	Bagtas	26	TANZA				
146	Ibayo Silangan						
147	Palangue 2 & 3						
161							
145		27	NAIC				
148	Datu Esmel (Bago-a-ingud)		GENERAL EMILIO AGUINALDO				
149	Paliparan III		TRECE MARTIRES CITY (Capital)				
150	Langkaan II	28	DASMARINAS				
151			SILANG				
153			GEN. MARIANO ALVAREZ				
154			CARMONA				
162			AMADEO				
163			ALFONSO				
164		TAGAYTAY CITY					
152		29	SAN PEDRO	3	LAGUNA	Region IV-A	
155			BINAN				
156			CITY OF SANTA ROSA				
157		CABUYAO					
158	Pansol, Parian	30	CITY OF CALAMBA				
159	Canlubang						
160		31	BAY				
165			SANTA MARIA				
166			MABITAC				
167		32	FAMY				
168			KALAYAAN				
169		33	CAVINTI				
170			LILIW				
171			PAGSANJAN				
172			ALAMINOS				
173	Del Remedio	34	SAN PABLO CITY				
174	Santisimo Rosario						
175	San Francisco						
176	Santo Angel						
116	San Jose	19	RODRIGUEZ (MONTALBAN)	4	RIZAL	Region III	
117	Burgos		SAN MATEO				
118		20	CITY OF ANTIPOLO (Capital)				
119	Cupang						
120	San Jose (Pob.)						
121	Inarawan						
122		21	CAINTA				
123			TAYTAY				
124			ANGONO				
125		22	BINANGONAN				
126			TERESA				
127			MORONG				
128			CARDONA				
129		23	BARAS				
130			TANAY				
131			PILILLA				
132			JALA-JALA				
95		14	CITY OF MEYCAUAYAN	5	BULACAN	Region III	
96			MARILAO				
97			OBANDO				
98			BULACAN				
99		15	BOCAUE				

TABLE 4.2.1-1 (3) TRAFFIC ZONING SYSTEM

Small Zone	Barangay	Medium Zone	City/Municipality	Large Zone	Province	Region
100			BALAGTAS (BIGAA)			
101		15	GUIGUINTO			
102			CITY OF MALOLOS (Capital) 1			
103			PAOMBONG			
104		16	HAGONOY			
105			CALUMPTIT			
106			PULILAN			
107			PLARIDEL			
108			PANDI			
109	Poblacion, Guyong	17	SANTA MARIA	5	BULACAN	
110	Pulong Buhangin					
111	Muzon					
112	Gumaoc	18	SAN JOSE DEL MONTE			
113	Kaypian					
114	Tigbe		NORZAGARAY			
115	San Mateo					
205		43	BALUAG			
206			BUSTOS			
207			ANGAT			
208		44	SAN ILDEFONSO			
209			DONA REMEDIOS TRINIDAD			
214		46	APALIT			
220			CANDABA			
215			MINALIN			
219		47	BACOLOR			
224	Dolores		CITY OF SAN FERNANDO			
225	Bulaon					
216		48	MASANTOL			
217			LUBAO			
218			FLORIDABLANCA			
221		49	ARAYAT	6	PAMPANGA	
222			MAGALANG			
223			PORAC			
226	Dau					
227	Mabiga, Calumpang	50	MABALACAT			
228	Cutcut					
229	Santo Domingo					
230	Balibago		ANGELES CITY			
231	Malabanas					
177		35	BALAYAN			
178			AGONCILLO			
179			LAUREL			
180			CITY OF TANAUAN			
181			SANTO TOMAS			
182			BALETE			
188	Marauoy	36	LIPA CITY	7	BATANGAS	
189	Antipolo Del Norte					
190	Lodlod					
191	San Jose					
183		37	CUENCA			
187			ALITAGTAG			
184			PADRE GARCIA			
185		38	SAN JUAN			
186			LOBO			
192	Santa Rita Karsada					
193	Gulod Itaas	39	BATANGAS CITY (Capital)			
194	Libjo					
195	Pinamucan					
196		40	GENERAL NAKAR			
197			LUCBAN			
198		41	CITY OF TAYABAS	8	QUEZON	
203			LUCENA CITY (Capital)			
204			AGDANGAN			
199			SARIAYA			
200		42	CANDELARIA			
201			DOLORES			
202			SAN ANTONIO			
210			LIMAY			
211		45	ABUCAY	9	BATAAN	
212			BAGAC			
213			DINALUPIHAN			
249	Barreto	56	OLONGAPO CITY			
250	East Bajac-bajac					
251	Santa Rita					
252	New Cabalan					
253	Calapacuan					
254	Cawag	57	SUBIC	10	ZAMBALES	
255	Pamatawan					
256	Naugsol					
257		58	CASTILLEJOS			

TABLE 4.2.1-1 (4) TRAFFIC ZONING SYSTEM

Small Zone	Barangay	Medium Zone	City/Municipality	Large Zone	Province	Region		
258		59	BOTOLAN	10	ZAMBALES	Region III		
259		60	CANDELARIA					
232		51	BAMBAN	11	TARLAC			
234			CAPAS					
233		CONCEPCION						
236		LA PAZ						
246	Matatalaib	52	CITY OF TARLAC					
247	San Rafael							
248	Maliwalo							
235								
240		53	SAN JOSE CAMILING					
237		54	VICTORIA					
238			PURA					
239			GERONA					
241								
242		55	RAMOS					
243			ANAO					
244	Poblacion Norte		SAN MANUEL					
245	Balaoang		PANQUI					
260	San Nicolas	61	CITY OF GAPAN	12	NUEVA ECIJA			
261	San Roque		CABIAO					
262			JAEN					
263			SAN LEONARDO					
264			GENERAL TINIO (PAPAYA)					
265			SANTA ROSA					
266			GABALDON (BITULOK & SABANI)					
267		BONGABON						
268		62	CARRANGLAN					
282								
269		63	GENERAL MAMERTO NATIVIDAD					
270			SANTO DOMINGO					
275			SCIENCE CITY OF MUÑOZ					
276			LUPAO					
281		64	SAN JOSE CITY					
271			ALIAGA					
272			LICAB					
277	Bantug Norte	65	CABANATUAN CITY					
278	Caalibangbangan							
279	San Josef Norte							
280	Campo Tinio							
273		66	GUIMBA	13	PANGASINAN			
274		CUYAPO						
284		68	UMINGAN					
285			NATIVIDAD					
286			ASINGAN					
287			SAN MANUEL					
298		69	BALUNGAO					
288			POZZORUBIO					
289			BUGALLON					
290			CALASIAO					
291		70	BINMALEY					
294			AGUILAR					
295			BASISTA					
296			BAUTISTA					
297			VILLASIS					
299	Bayaos		71			CITY OF URDANETA		
300	Pinnaludpod							
301	Palina East							
292		71	CITY OF ALAMINOS	14	AURORA			
293			AGNO					
283		67	All Municipalities					
302	Zone 302-319 Out of Study Area.	72				15	Benguet	CAR
303							Ifugao	
308							Mt. Province	
309							Kalinga	
312							Abra	
313						Apayao		
314							15	
316					Quirino			
304					Isabela			
305					15		CAGAYAN	Region I
306							LA UNION	
307							ILOCOS SUR	
310							ILOCOS NORTE	
311					15		All Provinces	Region IV-B
315							All Provinces	Region V
318								
319								




FIGURE 4.2.1-2 ZONING MAP – METRO MANILA




FIGURE 4.2.1-3 ZONING MAP – OUTSIDE METRO MANILA

4.2.2 Future Socio-Economic Framework

The future socio-economic indicators were formulated by the Study of Master Plan on High Standard Highway Network Development based on the past trend.

The socio-economic profile is summarized below.

(1) Population projection

The population annual growth rate of HSH Study is 2.3% up to 2020 and 1.8% from 2021 to 2030.

Tarlac and Nueva Ecija is the almost same growth rate.

TABLE 4.2.2-1 FUTURE POPULATION

	Population(thousand)			AAGR	
	Y2009	Y2020	Y2030	09-20(%)	21-30(%)
Metro Manila	11,962	14,511	15,942	1.8%	0.9%
Cavite	3,242	5,154	7,102	4.3%	3.3%
Laguna	2,625	3,511	4,194	2.7%	1.8%
Rizal	2,481	3,535	4,419	3.3%	2.3%
Bulacan	3,020	4,199	5,300	3.0%	2.4%
Pampanga	2,336	3,000	3,676	2.3%	2.1%
Batangas	2,347	3,050	3,843	2.4%	2.3%
Quezon	1,792	2,143	2,496	1.6%	1.5%
Bataan	694	895	1,114	2.3%	2.2%
Zambales	749	921	1,101	1.9%	1.8%
Tarlac	1,297	1,627	1,950	2.1%	1.8%
Nueva Ecija	1,914	2,400	2,870	2.1%	1.8%
Pangasinan	2,705	3,046	3,356	1.1%	1.0%
Aurora	192	216	241	1.1%	1.1%
Total	37,356	48,041	57,214	2.3%	1.8%

Source: HSH (JICA 2010)

(2) GRDP projection

The estimated GRDP growth rate of Region III (Central Luzon) is between 6.0 ~ 6.5% .

TABLE 4.2.2-2 GDP AND GRDP GROWTH RATE

			2012-2014	2015-2020	2021-2025	2026-2030
GDP			5.0%	5.5%	5.5%	5.0%
GRDP	NCR	National Capital Region	6.5%	6.5%	6.5%	6.0%
	III	Central Luzon	6.0%	6.5%	6.5%	6.5%
	IV-A	CARABARZON	6.5%	7.0%	7.0%	6.5%

Source: HSH (JICA 2010)

(3) Employment projection

The number of employment is estimated on population and GRDP in HSH Study.

The employment annual growth rate of HSH Study is higher than that of population. The growth rate of employment is 2.8% up to 2020 and 2.0% from 2021 to 2030.

The growth rate of Tarlac and Nueva Ecija is a little higher than the rate of study area.

TABLE 4.2.2-3 FUTURE EMPLOYMENT

	Employment(thousand)			AAGR	
	Y2009	Y2020	Y2030	09-20(%)	21-30(%)
Metro Manila	4,575	6,103	7,378	2.7%	1.9%
Cavite	1,092	1,583	2,058	3.4%	2.7%
Laguna	1,371	1,807	2,214	2.5%	2.1%
Rizal	454	654	821	3.4%	2.3%
Bulacan	675	976	1,240	3.4%	2.4%
Pampanga	800	1,124	1,427	3.1%	2.4%
Batangas	485	683	872	3.2%	2.5%
Quezon	218	283	344	2.4%	2.0%
Bataan	227	297	357	2.5%	1.9%
Zambales	339	478	604	3.2%	2.4%
Tarlac	282	398	506	3.2%	2.4%
Nueva Ecija	293	409	520	3.1%	2.4%
Pangasinan	651	739	798	1.2%	0.8%
Aurora	21	26	33	2.0%	2.4%
Total	11,483	15,560	19,172	2.8%	2.1%

Source: HSH (JICA 2010)

4.2.3 Present and Future OD Matrix

Traffic demand forecast was conducted in HSH Study. Annual growth rate in study area is 2.8 %(2009-2017) and 2.0 %(2021-2030). The growth rate of Tarlac and Nueva Ecija is the same rate of study area.

TABLE 4.2.3-1 ESTIMATED GENERATION TRIP AND ANNUAL GROWTH RATE

	Generation Trip(Vehicle/day)			Annual Growth Rate	
	Y2009	Y2020	Y2030	2009-2017	2021-2030
Metro Manila	3,539,909	4,496,863	5,173,752	2.2%	1.4%
Cavite	570,765	838,206	1,159,496	3.6%	3.3%
Laguna	400,087	619,695	811,382	4.1%	2.7%
Rizal	303,205	431,995	544,728	3.3%	2.3%
Bulacan	509,021	811,307	1,050,340	4.3%	2.6%
Pampanga	31,055	44,979	52,820	3.4%	1.6%
Batangas	38,817	51,355	59,416	2.6%	1.5%
Quezon	17,390	23,253	26,719	2.7%	1.4%
Bataan	14,690	18,468	20,446	2.1%	1.0%
Zambales	4,563	6,253	7,805	2.9%	2.2%
Tarlac	12,552	16,970	21,177	2.8%	2.2%
Nueva Ecija	20,484	28,016	35,037	2.9%	2.3%
Pangasinan	12,908	17,868	19,666	3.0%	1.0%
Aurora	430	562	687	2.5%	2.0%
Out of study area	11,322	14,941	18,665	2.6%	2.3%
Total	5,487,198	7,420,728	9,002,132	2.8%	2.0%

Source: HSH (JICA 2010)

Future OD was prepared in Year 2017, 2020 and 2030. Year 2017 is the opening year of CLLEX.

Table 4.2.3-2 to 4.2.3-3 shows the Vehicle OD Table.

TABLE 4.2.3-2 FUTURE VEHICLE OD TABLE (YEAR 2020)

	Metro Manila	Cavite	Laguna	Rizal	Bulacan	Pampanga	Batangas	Quezon	Bataan	Zambales	Tarlac	Nueva Ecija	Pangasinan	Aurora	Out of study area	Total
Metro Manila	4,122,744	95,382	66,285	115,250	65,312	3,538	12,042	3,292	1,514	1,456	848	2,401	2,145	315	4,340	4,496,863
Cavite	95,382	706,597	26,667	1,804	2,908	201	2,929	1,052	42	57	14	26	53	0	477	838,206
Laguna	115,250	1,804	8,977	489,063	3,016	56	269	791	31	25	0	32	44	108	231	619,695
Rizal	66,285	26,667	320,055	8,977	1,922	157	6,331	856	67	38	83	32	79	0	449	431,995
Bulacan	65,312	2,908	1,922	3,016	718,670	9,343	390	33	692	946	307	6,200	484	7	1,079	811,307
Pampanga	3,538	201	157	56	9,343	24,266	52	20	1,453	1,660	1,085	558	2,025	1	566	44,979
Batangas	12,042	2,929	6,331	269	390	52	25,891	2,730	101	27	2	106	36	0	451	51,355
Quezon	3,292	1,052	856	791	33	20	2,730	14,200	0	14	129	0	20	0	118	23,253
Bataan	1,514	42	67	31	692	1,453	101	0	12,455	1,118	416	328	112	2	140	18,468
Zambales	1,456	57	38	25	946	1,660	27	14	1,118	98	212	188	82	120	214	6,253
Tarlac	848	14	83	0	307	1,085	2	129	416	212	12,016	940	604	1	316	16,970
Nueva Ecija	2,401	26	32	32	6,200	558	106	0	328	188	940	14,467	1,423	1	1,315	28,016
Pangasinan	2,145	53	79	44	484	2,025	36	20	112	82	604	1,423	5,977	0	4,787	17,868
Aurora	315	0	0	108	7	1	0	0	2	120	1	1	0	0	8	562
Out of study area	4,340	477	449	231	1,079	566	451	118	140	214	316	1,315	4,787	8	453	14,941
Total	4,496,863	838,206	431,995	619,695	811,307	44,979	51,355	23,253	18,468	6,253	16,970	28,016	17,868	562	14,941	7,420,728

Source: HSH (JICA 2010)

TABLE 4.2.3-3 FUTURE VEHICLE OD TABLE (YEAR 2030)

	Metro Manila	Cavite	Laguna	Rizal	Bulacan	Pampanga	Batangas	Quezon	Bataan	Zambales	Tarlac	Nueva Ecija	Pangasinan	Aurora	Out of study area	Total
Metro Manila	4,710,201	119,731	81,228	144,569	80,310	4,061	14,268	3,853	1,718	1,768	1,386	2,862	2,285	374	5,142	5,173,752
Cavite	119,731	992,007	35,395	2,540	3,808	266	3,708	1,188	52	75	21	34	64	0	610	1,159,496
Laguna	81,228	35,395	403,660	12,149	2,492	182	7,722	1,000	77	54	118	42	86	0	526	544,728
Rizal	144,569	2,540	12,149	645,949	4,152	90	332	1,006	44	37	0	41	49	141	286	811,382
Bulacan	80,310	3,808	2,492	4,152	935,477	11,422	464	42	886	1,199	434	7,647	548	9	1,455	1,050,340
Pampanga	4,061	266	182	90	11,422	28,144	57	23	1,601	2,026	1,251	715	2,314	2	669	52,820
Batangas	14,268	3,708	7,722	332	464	57	28,945	3,089	128	33	2	130	38	0	502	59,416
Quezon	3,853	1,188	1,000	1,006	42	23	3,089	16,191	0	16	147	0	23	0	142	26,719
Bataan	1,718	52	77	44	886	1,601	128	0	13,315	1,376	543	409	117	2	181	20,446
Zambales	1,768	75	54	37	1,199	2,026	33	16	1,376	133	326	261	93	146	264	7,805
Tarlac	1,386	21	118	0	434	1,251	2	147	543	326	14,677	1,172	739	2	362	21,177
Nueva Ecija	2,862	34	42	41	7,647	715	130	0	409	261	1,172	17,270	1,670	2	2,785	35,037
Pangasinan	2,285	64	86	49	548	2,314	38	23	117	93	739	1,670	6,486	0	5,158	19,666
Aurora	374	0	0	141	9	2	0	0	2	146	2	2	0	0	12	687
Out of study area	5,142	610	526	286	1,455	669	502	142	181	264	362	2,785	5,158	12	574	18,665
Total	5,173,752	1,159,496	544,728	811,382	1,050,340	52,820	59,416	26,719	20,446	7,805	21,177	35,037	19,666	687	18,665	9,002,132

Source: HSH (JICA 2010)

4.2.4 Traffic Assignment Model

The traffic assignment procedure allocates vehicle traffic into individual road links. This step uses as input the matrix of flows (vehicles) that indicate the volume of traffic between origin and destination pairs.

1) Assignment Method

There are many assignment techniques that can be used to estimate traffic volume ranging from manual methods to complex iterative procedures by computer programs. In this study, the capacity restraint assignment which is the most straightforward for use in network models was applied. This assignment technique is based on the speed – flow relationship. Flowchart of the applied methodology is presented in **Figure 4.2.4-1**.

In this assignment technique, and by calculating the required travel time for each link according to its travel speed and road conditions, the program determines the fastest routes between each origin and destination by evaluating the consuming time on links, and assigns the trips between the given origin and destination. As congestion increases until a certain level, alternative routes are introduced to handle the unassigned traffic. Zone-to-zone routing is built, which is the fastest path from each zone to any other, and all trips are assigned to these optimum routes.

Regarding tolled expressway, travel time adds the sum up of travel time conversion from toll fee (= toll fee divided by time evaluation value) and time calculation from travel speed.

Since the link-travel time varies with the traffic volume of vehicles using that link, which can be explained as a degree of link congestion, the OD tables are divided to apply an iteration procedure on ten stages. At each iteration, and depending upon the current link loadings, the flows are divided between all the shortest routes generated and a new travel time is computed for the average assigned link flow at each pass. The iteration continues to re-estimate the speed on that links considering the assigned traffic on links, and to produce alternative routes so that more accurate allocation can be achieved. The accumulated assigned traffic volume from each OD pair on the links composes the total assigned traffic volumes per direction for the network. JICA STRADA is used to estimate traffic volumes.




FIGURE 4.2.4-1 TRAFFIC ASSIGNMENT PROCEDURE

2) Speed Flow Relationship

The speed-flow relationship used in the traffic assignment procedure is shown in **Figure 4.2.4-2**. When the traffic volumes are over the maximum capacity $0.3 \cdot Q_{\max}$, it is assumed that vehicle speed drastically reduces. The basic free flow and capacity is shown in **Table 4.2.4-1**.




FIGURE 4.2.4-2 SPEED – FLOW RELATIONSHIP

TABLE 4.2.4-1 FREE SPEED AND CAPACITY BY ROAD TYPE

QV Type	Pavement	Road Class	Topography	Lane	Vmax	Qmax	
1	Paved	Inter-Urban Expressway	Plain	4	100	80,000	
2				3	100	60,000	
3				2	100	40,000	
4			Mountains	1	70	20,000	
5				2	70	28,000	
6			Intra-Urban Expressway	Plain	1	60	10,500
7		3			80	60,000	
8		2			60-80	40,000	
9		Interstate Highway	Plain	1	60	15,000	
10				4	40	60,000	
11			Mountains	2	30	18,000	
12				4	30	42,000	
13			Urban Arterial	Mountains	2	25	12,600
14					10	60	120,000
15		8			60	96,000	
16		6			50	72,000	
17		Local	Plain	4	40	48,000	
18				2	30	14,400	
19				4	40	40,000	
20		Unpaved		Mountains	2	30	12,000
21					2	30	8,400
22	Plain			2	20	6,000	
23		Mountains	2	10	4,200		

3) Passenger Car Unit

Table 4.2.4-2 shows the Passenger Car Unit (PCU) used in vehicle traffic conversion. This value is the same used by the DPWH.

TABLE 4.2.4-2 PASSENGER CAR UNIT (PCU)

Vehicle Type	Passenger Car Unit
Passenger Car	1.0
Jeepney	1.5
Bus	2.2
Truck	2.5

4) Time Evaluation Value

An important input for the demand forecast is the trip maker's time value. This time value is the basis for a trip maker to decide whether to use toll expressway or not. The time values were derived from MMUEN (JICA, The Development of the Public –Private Partnership Technique for the Metro Manila Urban Expressway Network) survey results. Though MMUEN data is based on the Metro Manila and surrounding area, Time Evaluation Value in Region III is lower than that of MMUEN. Based on the rate of GRDP per capita (GRDP per capita of Region III / that of NCR and Region IV-4A = 50,176 peso / 96,505 peso = 0.52), Time Evaluation Value in Region III is set.

Supposing time value will increase in accordance with inflation rate of 5% per year, the figures in Table 4.2.4-3 will be the time value.

TABLE 4.2.4-3 TIME EVALUATION VALUE BY VEHICLE TYPE

Unit: Peso/hour

Area	MMUEN (Metro Manila and surrounding Area)	Region III (Study Area)		
		Y2009	Y2020	Y2030
Year	Y2009	Y2009	Y2020	Y2030
	(a)	(b=a*0.52)	(c=b*1.05 ¹¹)	(d=c*1.05 ¹⁰)
Car	331.4	172.4	294.8	480.2
Jeepney	465.9	242.3	414.4	675.0
Bus	1,524.2	792.8	1,355.9	2,208.7
Truck	873.2	454.1	776.6	1,265.0

4.2.5 Assignment Validation

The procedure of model validation entails two steps: first, the current OD matrix is assigned on an existing network. Second, the assigned traffic volume is compared with the result of the traffic count surveys at each corresponding location. This verification aims to check the accuracy of both the current OD matrix and an existing network model representing the existing transport situation.

Table 4.2.5-1 presents traffic volumes generated from traffic assignment and observed traffic (traffic count survey). **Figure 4.2.5-2** shows the result of comparison between the assigned traffic volumes and observed traffic volume. This comparison between observed traffic count and assigned traffic flow at individual sites is done via the Mean Absolute Difference (MAD)¹ Ratio. For daily traffic counts, the value of the MAD ratio is 0.21 which is considered to reflect a good calibration.

TABLE 4.2.5-1 COMPARISON OF OBSERVED AND ASSIGNED TRAFFIC VOLUME (Veh/day)

Road Name, Site	Observed Traffic Volume	Assigned Traffic Volume	Difference	Rate
1.SCTEX (Between Luisita IC and Capas IC)	8,790	10,432	-1,642	16%
2.SCTEX (Between Floridablanca and Porac IC)	9,039	8,564	475	-6%
3.Pan-Philippine HWY, Sto. Domingo	7,950	6,242	1,708	-27%
4.Pan-Philippine HWY, San Jose City	8,048	9,417	-1,369	15%
5.Pan-Philippine HWY, Zaragosa	14,246	12,089	2,157	-18%
6.Pan-Philippine HWY, Gapan	19,657	19,864	-207	1%
7.Pan-Philippine HWY, Plaridel	8,043	8,359	-316	4%
8.Sta Rosa-Tarlac Rd-1	5,124	5,422	-298	5%
9.Sta Rosa-Tarlac Rd-2	4,431	3,658	773	-21%
10.Caalibangbangan - Aliaga Rd-1	3,225	1,835	1,390	-76%
11.Caalibangbangan - Aliaga Rd-2	2,848	1,777	1,071	-60%
12.Nueve Ecija-Aurora Rd	1,273	2,092	-819	39%
13.Pinagpanaan-Rizal-Pantabangan Rd	2,179	2,990	-811	27%
14.MacArthur Hwy, Paniqui	5,635	6,409	-774	12%
15.NLEX-Dau Exit, National Hwy	13,516	14,536	-1,020	7%

¹ MAD Ratio is defined by the following formula: $MAD\ Ratio = \frac{\sum |Count - assignment|}{assignment} / n$ where n is the number of observations.




FIGURE 4.2.5-2 COMPARISON OF OBSERVED AND ASSIGNED TRAFFIC VOLUME (Veh/day)

4.2.6 Toll Rate vs. Revenue

In order to set the proper toll rate of CLLEX, the traffic volume and the amount of revenue are estimated by traffic assignment model. **Figure 4.2.6-1** shows the result of traffic assignment of toll rate.

- In case of toll free, total traffic volume to enter CLLEX is 16,197 vehicles/day
- The toll rate for getting higher revenue is about 3.0 to 4.5 Peso/km and the amount of revenue is about 1.14 and 1.18 million Peso/day. Although maximum amount of revenue is 4.0 peso case, traffic volume to enter CLLEX is only 8,628 vehicle /day which is about half of toll free case.
- The desirable toll rate for attractive to motorist and higher revenue is **3.0 Peso/km**. total traffic volume to enter CLLEX is 11,236 vehicle/day (70% of toll free case) and estimated toll revenue 1.14 million Peso/day. 3.0 Peso/km in year 2017 converts about 2.2 Peso /km in year 2011. This toll rate is the almost same as that of NLEX and other present interurban expressway (see **Table 4.2.6-1**). Most motorists may accept the 3.0 peso/km in year 2017.




FIGURE 4.2.6-1 TOLL RATE VS REVENUE (YEAR 2017)

TABLE 4.2.6-1 PRESENT TOLL RATE

(Peso/km)

Toll Road		Class 1	Class 2	Class 3	Remarks
		<i>Car, Jeep, Pick-up</i>	<i>Light Truck</i>	<i>Heavy Truck, Trailer</i>	
Metro Manila Skyway (MMS)	Elevated Phase 1	6.84	13.68	20.53	Skyway/Buendia - Bicutan (9.50 km)
	Elevated Phase 2	11.92	23.84	35.76	Alabang - Bicutan (6.88 km)
	At grade	7.85	15.70	23.56	Magallanes - Alabang (13.50 km)
North Luzon Expressway (NLEX)		2.38	5.92	7.08	
South Luzon Expressway (SLEX)		3.02	6.04	9.10	
Manila Cavite Toll Expressway (MCTE)	Phase 1	3.33	6.82	9.85	R-1 Extension to Bacoor (6.6 km)
	Phase 2	8.96	17.92	26.87	Bacoor Bay to Kawit (6.475 km)
Southern Tagalog Arterial Road (STAR)		1.43	2.86	4.26	
Subic-Clark-Tarlac Expressway (SCTEX)		2.68	5.36	8.04	

Source: TRB, 2011 May

4.2.7 Traffic Assignment Result

1) Case-1 CLLEX (Phase-1) Initial Stage 2 lane

a) Total Traffic Efficiency

Table 4.2.7-1 shows the traffic assignment of without CLLEX (Phase-1) case and with case.

This study area is Tarlac, Nueva Ecija, Bulacan, Pampanga,

TABLE 4.2.7-1 TRAFFIC INDICATORS OF W/O CLLEX CASE AND WITH CASE

Year	Case	Total Travel Time	Total Vehicle Km	Average Travel Speed
		(PCU*hr)	(PCU*km)	(km/hr)
2017	With	922,689	27,459,992	29.8
	W/O	933,781	27,351,557	29.3
	With-W/O	-11,092	108,435	0.5
2020	With	1,036,424	29,758,637	28.7
	W/O	1,053,098	29,710,937	28.2
	With-W/O	-16,674	47,700	0.5
2030	With	1,452,642	37,346,746	25.7
	W/O	1,474,010	37,219,691	25.3
	With-W/O	-21,368	127,055	0.4

Source JICA Study Team

Note: PCU: Passenger Car Unit

- If CLLEX were constructed, many motorists may use this expressway even though their trips become longer. Total PCU*km of with case will be higher than that of without case.
- Total travel time will be decrease if CLLEX were constructed. The difference of total travel time is 11,092 hours/day in year 2017 which much traffic time can be saved by CLLEX.

b) Traffic Assignment

Figure 4.2.7-1 to 4.2.7-3 shows the estimated traffic volume of CLLEX (Phase-1) 2lane.

- The highest IC section is between Tarlac IC and Aliaga IC, which number of traffic are 11,222 (vehicle/day) in year 2017, 12,966 (vehicle/day) in year 2020 and 17,118 (vehicle/day) in year 2030.

Figure 4.2.7-4 to 4.2.7-6 shows the traffic assignment result with CLLEX (Phase-1) and Figure 4.2.7-7 to 4.2.7-9 shows the difference of traffic volume with case and without case.

Figure 4.2.7-10 to 4.2.7-12 shows the number of traffic CLLEX (Phase-1) destination.

- About 60% of CLLEX traffic from west side to east are going to Cabanatuan City.
- The major destinations of CLLEX traffic from east to west are Bulacan or Metro Manila...

Table 4.2.7-2 shows the total traffic volume to enter CLLEX and total vehicle km of CLLEX

TABLE 4.2.7-2 TOTAL TRAFFIC VOLUME AND TOTAL VEHICLE KM (CLLEX PHASE-1, 2LANE)

Year	Traffic Volume (Veh/day)				Total vehicle*km			
	Class1	Class2	Class3	Total	Class1	Class2	Class3	Total
2017	8,427	2,576	219	11,222	222,318	69,635	5,722	297,675
2018	8,931	2,618	223	11,772	237,330	70,581	5,823	313,735
2019	9,464	2,661	227	12,352	253,356	71,541	5,927	330,823
2020	10,030	2,705	232	12,966	270,463	72,513	6,032	349,009
2021	10,268	2,818	242	13,328	276,853	75,721	6,332	358,906
2022	10,512	2,936	253	13,700	283,393	79,070	6,647	369,110
2023	10,761	3,058	264	14,084	290,088	82,568	6,977	379,633
2024	11,017	3,186	276	14,480	296,942	86,220	7,324	390,486
2025	11,279	3,320	289	14,887	303,957	90,034	7,688	401,679
2026	11,546	3,459	302	15,307	311,137	94,016	8,071	413,224
2027	11,821	3,603	316	15,740	318,488	98,175	8,472	425,135
2028	12,101	3,754	330	16,185	326,012	102,517	8,893	437,422
2029	12,389	3,911	345	16,645	333,714	107,052	9,335	450,101
2030	12,683	4,074	361	17,118	341,597	111,787	9,800	463,184
2031	12,984	4,245	377	17,606	349,667	116,732	10,287	476,686
2032	13,293	4,422	394	18,109	357,928	121,895	10,798	490,622
2033	13,608	4,607	412	18,627	366,384	127,287	11,335	505,006
2034	13,931	4,800	430	19,162	375,040	132,918	11,899	519,856
2035	14,262	5,001	450	19,713	383,900	138,797	12,490	535,187
2036	14,601	5,210	470	20,281	392,969	144,936	13,111	551,017
2037	14,948	5,428	492	20,867	402,253	151,347	13,763	567,363
2038	15,303	5,655	514	21,472	411,756	158,042	14,448	584,245
2039	15,666	5,891	537	22,095	421,483	165,033	15,166	601,682
2040	16,038	6,138	561	22,738	431,440	172,333	15,920	619,693
2041	16,419	6,395	587	23,401	441,633	179,956	16,712	638,300
2042	16,809	6,662	614	24,085	452,066	187,916	17,542	657,524
2043	17,208	6,941	641	24,790	462,746	196,228	18,415	677,388
2044	17,617	7,231	670	25,518	473,678	204,908	19,330	697,916
2045	18,035	7,533	701	26,270	484,868	213,971	20,291	719,131
2046	18,464	7,849	732	27,045	496,323	223,436	21,300	741,059


2-LANE

CLLEX

Year 2017

Unit: Veh/Day

4-50



Total Traffic Volume Enter to CLLEX	
Class 1	8,427
Class 2	2,576
Class 3	219
Total	11,222

FIGURE 4.2.7-1 TRAFFIC PROJECTION (YEAR 2017) OF CLLEX (PHASE-1) 2-LANE CASE


2-LANE

CLLEX

Year 2020

Unit: Veh/Day

4-51



Total Traffic Volume Enter to CLLEX	
Class 1	10,030
Class 2	2,705
Class 3	232
Total	12,966

FIGURE 4.2.7-2 TRAFFIC PROJECTION (YEAR 2020) OF CLLEX (PHASE-1) 2-LANE CASE


2-LANE

CLLEX

Year 2030

Unit: Veh/Day

4-52



Total Traffic Volume Enter to CLLEx	
Class 1	12,683
Class 2	4,074
Class 3	361
Total	17,118

FIGURE 4.2.7-3 TRAFFIC PROJECTION (YEAR 2030) OF CLLEX (PHASE-1) 2-LANE CASE




FIGURE 4.2.7-4 RESULT OF TRAFFIC ASSIGNMENT IN YEAR 2017 (PHASE-1, 2-LANE)




FIGURE 4.2.7-5 RESULT OF TRAFFIC ASSIGNMENT IN YEAR 2020 (PHASE-1, 2-LANE)




FIGURE 4.2.7-6 RESULT OF TRAFFIC ASSIGNMENT IN YEAR 2030 (PHASE-1, 2-LANE)




FIGURE 4.2.7-7 COMPARISON OF WITH CASE AND WITHOUT CASE IN YEAR 2017 (PHASE-1, 2-LANE)




FIGURE 4.2.7-8 COMPARISON OF WITH CASE AND WITHOUT CASE IN YEAR 2020 (PHASE-1, 2-LANE)






FIGURE 4.2.7-9 COMPARISON OF WITH CASE AND WITHOUT CASE IN YEAR 2030 (PHASE-1, 2-LANE)




Unit: Vehicle/day

**FIGURE 4.2.7-10 TRAFFIC VOLUME OF CLLEX DESTINATION (YEAR 2017)
(PHASE 1, 2 LANES)**



Unit: Vehicle/day

**FIGURE 4.2.7-11 TRAFFIC VOLUME OF CLLEX DESTINATION (YEAR 2020)
(PHASE 1, 2 LANES)**



Unit: Vehicle/day

**FIGURE 4.2.7-12 TRAFFIC VOLUME OF CLLEX DESTINATION (YEAR 2030)
(PHASE 1, 2 LANES)**

2) Case-2 CLLEX (Phase-1) 4 lane

Figures 4.2.7-13 to 4.2.7-15 shows the estimated traffic volume of CLLEX (Phase-1).

- Traffic assignment of CLLEX (Phase-1) 4lane case is a little higher than that of 2lane case. Traffic volume between Tarlac IC and Aliaga IC are 12,630 (vehicle/day) in year 2017, 14,255 (vehicle/day) in year 2020 and 20,177 (vehicle/day) in year 2030.

Table 4.2.7-3 shows the total traffic volume to enter CLLEX (Phase-1) and total vehicle km of CLLEX(Phase-1).

3) Case-3 CLLEX (Phase-2) 2 lane

Traffic assignment of CLLEX (Phase-2) was estimated based on the assumption of CLLEX (Phase-1) also 2-lane.

Figures 4.2.7-16 to 4.2.7-18 shows the estimated traffic volume of CLLEX (Phase-2).

- Traffic assignment of CLLEX (Phase-2) case is lower than phase-1 traffic. Traffic volume between Cabanatuan IC and Llanera IC are 7,402(vehicle/day) in year 2017, 8,402 (vehicle/day) in year 2020 and 12,984 (vehicle/day) in year 2030.

Figures 4.2.7-19 to 4.2.7-21 shows the number of traffic CLLEX (Phase-1) destination.

Table 4.2.7-4 shows the total traffic volume to enter CLLEX (Phase-2) and total vehicle km of CLLEX (Phase-2).

TABLE 4.2.7-3 TOTAL TRAFFIC VOLUME AND TOTAL VEHICLE KM (CLLEX PHASE-1, 4-LANE)


Year	Traffic Volume (Veh/day)				Total vehicle*km			
	Class1	Class2	Class3	Total	Class1	Class2	Class3	Total
2017	9,502	2,886	241	12,629	256,672	78,158	6,321	341,151
2018	9,967	2,933	246	13,147	267,212	79,654	6,489	353,355
2019	10,455	2,981	252	13,688	278,185	81,179	6,660	366,025
2020	10,967	3,030	257	14,254	289,609	82,733	6,837	379,179
2021	11,349	3,141	267	14,758	299,881	85,845	7,134	392,859
2022	11,745	3,257	278	15,280	310,517	89,073	7,443	407,034
2023	12,155	3,376	289	15,820	321,530	92,423	7,767	421,720
2024	12,578	3,500	301	16,379	332,934	95,899	8,104	436,937
2025	13,017	3,629	313	16,959	344,743	99,506	8,455	452,704
2026	13,471	3,762	325	17,558	356,970	103,249	8,822	469,041
2027	13,940	3,900	339	18,179	369,631	107,132	9,205	485,968
2028	14,426	4,044	352	18,822	382,741	111,161	9,605	503,507
2029	14,929	4,192	366	19,488	396,316	115,342	10,022	521,680
2030	15,450	4,346	381	20,177	410,372	119,680	10,457	540,509
2031	15,989	4,506	396	20,891	424,927	124,181	10,911	560,019
2032	16,546	4,671	412	21,629	439,998	128,852	11,385	580,234
2033	17,123	4,843	429	22,394	455,604	133,698	11,879	601,180
2034	17,720	5,021	446	23,187	471,763	138,726	12,394	622,884
2035	18,338	5,205	464	24,007	488,495	143,944	12,932	645,372
2036	18,977	5,396	483	24,856	505,821	149,358	13,494	668,673
2037	19,639	5,594	502	25,735	523,762	154,975	14,079	692,816
2038	20,324	5,800	522	26,645	542,338	160,804	14,691	717,833
2039	21,032	6,013	543	27,588	561,574	166,851	15,328	743,754
2040	21,766	6,234	565	28,564	581,492	173,127	15,994	770,612
2041	22,524	6,463	588	29,574	602,116	179,638	16,688	798,442
2042	23,310	6,700	611	30,621	623,471	186,394	17,412	827,278
2043	24,122	6,946	636	31,704	645,584	193,405	18,168	857,157
2044	24,963	7,201	661	32,826	668,482	200,679	18,957	888,118
2045	25,834	7,466	688	33,987	692,191	208,226	19,780	920,198
2046	26,735	7,740	715	35,190	716,742	216,058	20,638	953,438

4-LANE

CLLEX

Year 2017

Unit: Veh/Day



Total Traffic Volume Enter to CLLEx	
Class 1	9,502
Class 2	2,886
Class 3	241
Total	12,630

FIGURE 4.2.7-13 TRAFFIC PROJECTION (YEAR 2017) OF CLLEX (PHASE-1) 4-LANE CASE

4-LANE

CLLEX

Year 2020

Unit: Veh/Day





FIGURE 4.2.7-14 TRAFFIC PROJECTION (YEAR 2020) OF CLLEX (PHASE-1) 4-LANE CASE

4-LANE

CLLEX

Year 2030

Unit: Veh/Day



Total Traffic Volume Enter to CLLEX	
Class 1	15,450
Class 2	4,346
Class 3	381
Total	20,177

FIGURE 4.2.7-15 TRAFFIC PROJECTION (YEAR 2030) OF CLLEX (PHASE-1) 4-LANE CASE

TABLE 4.2.7-4 TOTAL TRAFFIC VOLUME AND TOTAL VEHICLE KM (CLLEX PHASE-2, 2-LANE)

Year	Traffic Volume (Veh/day)				Total vehicle*km			
	Class1	Class2	Class3	Total	Class1	Class2	Class3	Total
2017	5,583	1,875	159	7,617	190,890	66,585	5,667	263,142
2018	5,865	1,915	163	7,944	200,733	68,020	5,793	274,547
2019	6,162	1,957	166	8,285	211,084	69,487	5,922	286,493
2020	6,474	1,999	170	8,643	221,968	70,985	6,054	299,007
2021	6,769	2,077	177	9,023	232,266	73,744	6,302	312,312
2022	7,077	2,158	184	9,419	243,042	76,609	6,561	326,213
2023	7,399	2,242	192	9,833	254,318	79,587	6,830	340,735
2024	7,736	2,329	200	10,265	266,117	82,680	7,111	355,907
2025	8,088	2,420	208	10,716	278,464	85,893	7,402	371,759
2026	8,457	2,514	217	11,187	291,383	89,231	7,706	388,320
2027	8,842	2,612	226	11,679	304,902	92,698	8,022	405,622
2028	9,244	2,714	235	12,193	319,048	96,301	8,352	423,700
2029	9,665	2,819	245	12,729	333,850	100,043	8,694	442,587
2030	10,105	2,929	255	13,289	349,339	103,931	9,051	462,321
2031	10,565	3,043	266	13,874	365,547	107,970	9,422	482,939
2032	11,046	3,162	277	14,484	382,506	112,166	9,809	504,481
2033	11,549	3,285	288	15,122	400,253	116,525	10,212	526,989
2034	12,075	3,413	300	15,787	418,822	121,053	10,631	550,506
2035	12,625	3,545	312	16,482	438,254	125,758	11,067	575,078
2036	13,199	3,684	325	17,208	458,586	130,645	11,521	600,752
2037	13,800	3,827	339	17,966	479,862	135,722	11,994	627,578
2038	14,429	3,976	353	18,757	502,126	140,996	12,486	655,608
2039	15,086	4,131	367	19,584	525,422	146,476	12,998	684,896
2040	15,772	4,292	383	20,447	549,799	152,168	13,532	715,499
2041	16,491	4,459	398	21,348	575,307	158,082	14,087	747,475
2042	17,241	4,632	415	22,289	601,998	164,225	14,665	780,888
2043	18,026	4,813	432	23,271	629,928	170,607	15,267	815,802
2044	18,847	5,000	450	24,297	659,153	177,237	15,893	852,284
2045	19,705	5,195	468	25,369	689,735	184,125	16,545	890,405
2046	20,602	5,397	488	26,487	721,735	191,281	17,224	930,240


2-LANE

CLLEX Phase-2

Year 2017

Unit: Veh/Day

4-68



Total Traffic Volume Enter to CLLEX	
Class 1	5,583
Class 2	1,875
Class 3	159
Total	7,618

FIGURE 4.2.7-16 TRAFFIC PROJECTION (YEAR 2017) OF CLLEX (PHASE-2) 2-LANE CASE


2-LANE

CLLEX Phase-2

Year 2020

Unit: Veh/Day

4-69



Total Traffic Volume Enter to CLLEX	
Class 1	6,474
Class 2	1,999
Class 3	170
Total	8,643

FIGURE 4.2.7-17 TRAFFIC PROJECTION (YEAR 2020) OF CLLEX (PHASE-2) 2-LANE CASE


2-LANE

CLLEX Phase-2

Year 2030

Unit: Veh/Day

4-70



Total Traffic Volume Enter to CLLEx	
Class 1	10,105
Class 2	2,929
Class 3	255
Total	13,289

FIGURE 4.2.7-18 TRAFFIC PROJECTION (YEAR 2030) OF CLLEX (PHASE-2) 2-LANE CASE




FIGURE 4.2.7-19 TRAFFIC FLOW OF CLLEX PHASE-1 BY DESTINATION (YEAR 2017) 4 LANES

Year 2020

Unit: Veh/Day




FIGURE 4.2.7-20 TRAFFIC FLOW OF CLLEX PHASE-1 BY DESTINATION (YEAR 2020) 4 LANES

Year 2030

Unit: Veh/Day




FIGURE 4.2.7-21 TRAFFIC FLOW OF CLLEX PHASE-1 BY DESTINATION (YEAR 2030) 4 LANES

CHAPTER 5

REVIEW OF 2010 FEASIBILITY STUDY

CHAPTER 5

REVIEW OF 2010 FEASIBILITY STUDY

5.1 NECESSITY OF THE PROJECT

1) Traffic Congestion on Pan Philippine Highway

Eastern areas of Region III and whole Region II are served by Pan Philippine Highway, which passes through urban areas at 5-10 km interval. Urban sections of Pan Philippine Highway suffer chronic traffic congestions due to sharp increase of local traffic such as jeepneys and tricycles, and travel speed becomes less than 20 km/hr.

With the completion of SCTEx, some traffic of long distance trips, such as between Metro Manila and Cabanatuan City or Region II, are already diverting to the route of NLEx-SCTEx-Tarlac-Sta. Rosa Road from Pan Philippine Highway. When Tarlac-Sta. Rosa Road is replaced by CLLEx, more traffic will be diverted to this route from Pan Philippine Highway, thus traffic congestion of Pan Philippine Highway will be mitigated.

2) Need of Strengthening of Lateral (East-West) Road Network

Figure 5.1-1 shows the distribution of population in Region III and road network. For north-south direction, traffic is served by NLEx-SCTEx-TPLEx, Manila North Road and Pan Philippine Highway along which major urban centers are distributed. However, road network in the east-west direction is still weak and needs to be strengthened, thereby socio-economic interaction in that direction is stimulated and overall socio-economic activities will be activated for socio-economic development of the Region and the country as a whole.

3) Need to Develop Regional Growth Pole Cities

Overconcentration of socio-economic activities in Metro Manila has been one of the critical issues of the country. To mitigate such conditions, Regional Growth Pole Cities must be developed, so that socio-economic activities of Metro Manila can be shared with such Regional Growth Pole Cities as Tarlac City and Cabanatuan City.

4) Need to Develop Impoverish Area

Pacific Ocean Coastal area in Region III is one of the impoverished areas of the country. Cabanatuan City is the base city (or hub city) for the development of Pacific Ocean Coastal area. If accessibility to Cabanatuan City is improved, the impact will be extended to Pacific Ocean Coastal area.

5) Need to Develop Integrated Multi-modal Logistics/Transport System

In order to achieve faster, safer, more cost effective and reliable logistics/transport system, an expressway network development in the Region is vitally needed.

Approach sections of Rio Chico River Bridge along Tarlac-Sta. Rosa Road which is currently an important to provide transport services in the east-west direction is often flooded and traffic is interrupted. More reliable transport facility is needed.




FIGURE 5.1-1 DISTRIBUTION OF POPULATION IN REGION 3 AND ROAD NETWORK

5.2 TECHNICAL ISSUES

5.2.1 Summary of Technical Issues

After thorough review of 2010 FS, the following technical issues were identified (see **Figure 5.2.1-1**);

TECHNICAL ISSUES

- How to connect with SCTEx or TPLeX
- Needs additional interchange at Aliaga Municipality
- Cabanatuan IC location and how to attract more traffic from/to Cabanatuan City
- Appropriate Location of Alignment in the Flood-prone Area
- Toll Collection System
- Need to Study Stage Construction




FIGURE 5.2.1-1 TECHNICAL ISSUES OF CLLEX PHASE I

5.2.2 How to connect with SCTEx or TPEx

2010 FS proposed that CLEx is to be connected with the existing SCTEx Tarlac Interchange exit/entrance, thus, CLEx is not directly connected with SCTEx, but is connected via the national road of Tarlac – Sta. Rosa Road. Another new development is that the type of Tarlac Interchange was changed. According to the latest plan of SCTEx and TPEx, Tarlac Interchange is a half interchange at CLEx and another half interchange at TPEx as shown in **Figure 5.2.2-1**.

To maintain efficient traffic flow on the expressways, two expressways should be directly connected, but not via national or provincial road. Three (3) alternative connection options were studied (see **Table 5.2.2-1**);

ALTERNATIVES OF CONNECTION POINT

Alternative-1	:	2010 FS Option Proposed by 2010 FS
Alternative-2	:	Direct connection with SCTEx
Alternative-3	:	Direct connection with TPEx

Traffic volume attracted to CLEx is about 11,000 veh./day in the proposed opening year of 2017 and approximately composed of the following;

• Traffic between Manila side and Cabanatuan City	:	70%
• Traffic between Pangasinan side and Cabanatuan City	:	20%
• Traffic between Tarlac side and Cabanatuan City	:	10%

As shown above, traffic between Manila side and Cabanatuan City is predominant. Connection point between CLEx and SCTEx/TPEx should be selected giving primary consideration of traffic between Manila side and Cabanatuan City.

Evaluation of 3 alternatives is shown in **Table 5.2.2-2**, and Alternative-2 (connected with SCTEx) was recommended due to the following reasons;

• Alternative-2 provides direct connection between 2 expressways.
• Most preferred alternative for traffic between Manila side and Cabanatuan City, which is the predominant traffic flow.




FIGURE 5.2.2-1 CONNECTION BETWEEN SCTEX AND TPLEX

TABLE 5.2.2-1 ALTERNATIVES OF CONNECTION BETWEEN CLLEX AND SCTEX/TPLEX

ALTERNATIVE - 1			ALTERNATIVE - 2			ALTERNATIVE - 3		
<p>Concept :</p> <ul style="list-style-type: none"> Proposed plan by 2010 FS. CLLEx is connected with SCTEx via Intersection. 			<p>Concept :</p> <ul style="list-style-type: none"> CLLEx is directly connected with SCTEx. On and off ramps is provided from/to Tarlac-Sta. Rosa Road for better linkage between Tarlac and Cabanatuan. 			<p>Concept :</p> <ul style="list-style-type: none"> CLLEx is directly connected with TPLEX. 		
<p>Note : At-grade Intersection</p>			<p>Note : At-grade Intersection</p>			<p>Note : At-grade Intersection</p>		
Manila ⇄ Cabanatuan	Pangasinan ⇄ Cabanatuan	Tarlac ⇄ Cabanatuan	Manila ⇄ Cabanatuan	Pangasinan ⇄ Cabanatuan	Tarlac ⇄ Cabanatuan	Manila ⇄ Cabanatuan	Pangasinan ⇄ Cabanatuan	Tarlac ⇄ Cabanatuan
<ul style="list-style-type: none"> All via national road Longer than Alternative-2 	<ul style="list-style-type: none"> All via national road 	<ul style="list-style-type: none"> All via national road Shortest connection 	<ul style="list-style-type: none"> Shortest connection Best linkage 	<ul style="list-style-type: none"> Longer than Alternative-3, but traffic is not so high 	<ul style="list-style-type: none"> Good connection Longer than Alternative-1 	<ul style="list-style-type: none"> Longest connection 	<ul style="list-style-type: none"> Shortest connection 	<ul style="list-style-type: none"> Complicated
X	X	O	O	△	O	△	O	X
Not Recommended			Recommended			Not Recommended		

TABLE 5.2.2-2 EVALUATION OF ALTERNATIVES

Traffic Between	Alternative-1	Alternative-2	Alternative-3
From Manila side to Cabanatuan City	<ul style="list-style-type: none"> • SCTEx off-ramp → Intersection with National Road → CLLEx (Travel distance is longer by 2 km than Alternative-2) • Passes 2 toll booths (or 2 stops) 	<ul style="list-style-type: none"> • SCTEx → CLLEx (Direct), Shortest distance • Passes 1 toll booth (or 1 stop only) 	<ul style="list-style-type: none"> • TPLEx → CLLEx (Direct), Longer by 7.1 km than Alternative-2. • Passes 2 toll booths (or 2 stops)
	X		
From Cabanatuan City to Manila side	<ul style="list-style-type: none"> • CLLEx → National Road (2.2 km) → TPLEx IC • Longer by 8.2 km. than Alternative-2. • Passes 3 toll booths (or 3 stops) 	<ul style="list-style-type: none"> • CLLEx → SCTEx (Direct), shortest distance. • Passes 1 toll booth (or 1 stop only) 	<ul style="list-style-type: none"> • CLLEx → TPLEx (Direct), Longer by 7.1 km. • Passes 2 toll booths (or 2 stops)
	X		
From Pangasinan side to Cabanatuan City	<ul style="list-style-type: none"> • TPLEx off-ramp → National Road (2.2 km.) → CLLEx. • Passes 2 toll booths (or 2 stops) 	<ul style="list-style-type: none"> • TPLEx → SCTEx → CLLEx (Direct), Longer by 7.1km than Alternative-3. 	<ul style="list-style-type: none"> • TPLEx → CLLEx (Direct), Shortest • Passes 1 toll booth (or only 1 stop)
	X		
From Cabanatuan City to Pangasinan side	<ul style="list-style-type: none"> • CLLEx → Intersection with National Road → TPLEx • Passes 2 toll booths (or 2 stops) 	<ul style="list-style-type: none"> • CLLEx → TPLEx (Direct), Longer by 7.1 km than Alternative-3. • Passes 2 toll booths (or 2 stops) 	<ul style="list-style-type: none"> • CLLEx → TPLEx (Direct), Shortest • Passes 1 toll booth (or 1 stop only)
	X		
From Tarlac side to Cabanatuan City	<ul style="list-style-type: none"> • National Road → CLLEx • Passes 1 toll booths (or 1 stop only) 	<ul style="list-style-type: none"> • National Road → CLLEx • Passes 1 toll booth (or 1 stop only) 	<ul style="list-style-type: none"> • National Road → SCTEx → TPLEx → CLLEx • Passes 2 toll booths (or 2 stops)
	○		
From Cabanatuan City to Tarlac side	<ul style="list-style-type: none"> • CLLEx → National Road • Passes 1 toll booths (or 1 stop only) 	<ul style="list-style-type: none"> • CLLEx → National Road • Passes 1 toll booth (or 1 stop only) 	<ul style="list-style-type: none"> • CLLEx → TPLEx → National Road • Passes 2 toll booths (or 2 stops)
	○		
Overall Evaluation	X Not Recommended	⊙ Recommended	△ Not Recommended

5.2.3 Needs of Additional Interchange at Aliaga Municipality

2010 FS proposed no interchange between Tarlac and Cabanatuan City for the extension of 28 km. In Japan, the longest interval of interchanges is set at 15 to 25 kms. as follows;

- Maximum Interval : 30 km
- Standard Interval
 - Mega City, Major Industrial Area : 5 ~ 10 km
 - Rural Area with Small to Medium Cities : 15 ~ 25 km
 - Rural Area and Mountainous Area : 20 ~ 30 km

An interval of 28 km is too long and additional exits should be needed during emergency cases.

There is also strong request from the Municipal Government of Aliaga to provide an interchange within the municipality.

In view of the above, it is necessary to add an interchange in the Municipality of Aliaga. Urbanization condition of Aliaga town proper and its vicinity is shown in **Figure 5.2.3-1**. Aliaga Town Proper is traversed by Quezon-Aliaga-Cabanatuan Road. New development site is being developed at the north-west area of Aliaga Town Proper, the Health Center was already built and Aliaga Trading Center and Bus Terminal are currently under construction. CLLEx passes northern periphery of Aliaga Town Proper. Location of Aliaga Interchange was so selected that it is not so far from Aliaga Town Proper and efficient access can be provided to new development site.

Three (3) interchange alternatives were prepared for comparison as shown in **Table 5.2.3-1**, which also shows evaluation of alternatives. Alternative-2 was recommended due to the following reasons;

- It provides efficient access to New Development Site.
- Least construction cost.
- Although two houses are affected, it achieves the minimum ROW acquisition or land take.




FIGURE 5.2.3-1 ALIAGA TOWN PROPER AND ITS VICINITY

TABLE 5.2.3-1 ALIAGA INTERCHANGE OF COMPARATIVE STUDY

Plan						
	Alternative 1		Alternative 2		Alternative 3	
Concept	Indirect connection with Aliaga Trading Center		Direct connection with Aliaga Trading Center		Direct connection with Aliaga Trading Center	
Ramp length	1,581m		1,204m		2,081m	
Relocation	0		2 houses		0	
Construction Cost	△	Middle	○	Least	X	Highest
Social Environment	○	No relocation	△	2 houses of relocation	○	No relocation
Natural Environment	△	Medium land take of Agri-land.	○	Smallest land take of Agri-land.	X	Largest land take of Agri-land.
Construction Cost	△	Higher than Alt. 2	○	Lowest	X	Highest
Accessibility to Aliaga Trading Center and Bus Terminal	X	Poor	○	Good	○	Good
Rank	2		1	Recommended	3	

5.2.4 Cabanatuan IC Location and How to Attract More Traffic To/From Cabanatuan City

1) Cabanatuan IC Location

At the location of Cabanatuan Interchange proposed by 2010 FS, new church was built, thus IC location is required to be re-planned.

The Cabanatuan City Government recommended the following;

- CLLEEx center line alignment be shifted to avoid affecting the new church.
- Interchange location be almost at the same location selected by 2010 FS.
- An alignment of the proposed Cabanatuan Ring Road will be selected by the City Government with due consideration of new interchange location.

2010 FS proposed two (2) stages development of the interchange for CLLEEx Phase I and Phase II, and ramps constructed during Phase I are proposed to be abandoned during Phase II. The stage development of the interchange is necessary, however, it should be planned to avoid useless investment during Phase-II. Two alternatives were studied and evaluated as shown in **Table 5.2.4-1**. Alternative-2 was recommended, since it can avoid useless investment during Phase-I.



2) How to Attract More Traffic To/From Cabanatuan City

The only road traversing Cabanatuan City in the north-south direction is the Pan-Philippine Highway (or Daang Maharlika) which is heavily congested due to huge number of slow moving vehicles such as tricycles and jeepneys (see **Figure 5.2.4-1**). Travel speed on this road within Cabanatuan City is very slow with less than 15km/hour.

Cabanatuan IC of CLLEEx is located at northern periphery of Cabanatuan City, which will attract traffic to/from northern area of Cabanatuan City. Traffic from southern area will rarely utilize Cabanatuan IC, thus some measures is required for traffic generated in southern areas of Cabanatuan City.

It is recommended that another half interchange (only on-ramp and off-ramp from/to southern Cabanatuan City) should be constructed. Traffic generated from southern Cabanatuan City will use City Bypass and Quezon-Aliaga-Cabanatuan Road to access to CLLEEx. This Cabanatuan City Bypass Interchange is proposed to be located at about 4 km west of Cabanatuan City Bypass.

TABLE 5.2.4-1 CABANATUAN INTERCHANGE COMPARATIVE STUDY

Plan		
Alternative 1		Alternative 2
Concept	<ul style="list-style-type: none"> Recommended by FS 2010 To construct interim ramp for Phase I and to construct trumpet type of IC for Phase II To demolish interim ramp when extension of Phase II is implemented. 	<ul style="list-style-type: none"> To construct trumpet type of IC with stage development. Two ramps (in red color) is constructed at the initial stage. Remaining two ramps (in black color) is constructed when Phase II is implemented.
Road Length (Main)	+0m	+200m
Ramp Length (Phase I)	820m	1,413m
Relocation	Phase I: 3 houses, Phase II : 12 houses (including new church)	Phase I: 12 houses, Phase II: 0 house
Social Environment	X <ul style="list-style-type: none"> Relocation of a new church is practically impossible. Relocation of 3 houses along interim ramps during Phase 1 becomes useless (unnecessary relocation is required). 	○ <ul style="list-style-type: none"> Unnecessary relocation can be avoided.
Natural Environment	△ <ul style="list-style-type: none"> Land acquired for the interim ramps during Phase I becomes useless during Phase II. (Unnecessary land take of agri-land.) 	○ <ul style="list-style-type: none"> Unnecessary ROW acquisition can be avoided.
Traffic flow of expressway and ordinal road	△ <ul style="list-style-type: none"> Phase I: 2 at-grade intersection required. Traffic flow is disturbed at these intersections. Phase II: 1 at-grade intersection required. 	○ <ul style="list-style-type: none"> Phase I and II: 1 at-grade intersection. Traffic is less disturbed than Alternative-I.
Phase I Construction Cost	X <ul style="list-style-type: none"> Phase I: Construction cost for interim ramps wasted since these are not used in Phase II. 	○ <ul style="list-style-type: none"> Unnecessary investment can be avoided.
Rank	2	1 Recommended




FIGURE 5.2.4-1 NEED OF CABANATUAN CITY BYPASS IC


5.2.5 Appropriate Location of Alignment in the Flood-prone Area

1) Condition of Flood-prone Area

The project has to traverse the flood-prone area. There are two (2) big rivers, namely Rio Chico River and Talavera River. There are other four (4) small rivers. All of these rivers join into one river, and then it is called as Rio Chico River (see **Figure 5.2.5-1**).

- Rio Chico River has a west bank but no east bank at the up-stream side of the confluence point. West bank has damage at the upstream side and the river water flows outside the bank when medium to heavy rainfall occurs.
- The downstream side of Rio Chico River from the confluence point has both west and east banks.
- Talavera River has both west and east banks until near the confluence point, however, west bank ends before it reaches to the confluence point. West bank has damage at Aliaga Municipality and Water flows outside the west bank.
- After the confluence point, Rio Chico River has both west and east banks.
- Discharge of 50-year return period estimated by Feasibility Study on Pampanga Delta Development Project (1982) is as follows;

○ Rio Chico River before the confluence point	:	1,260 m ³ /sec
○ Talavera River	:	1,203 m ³ /sec
○ Rio Chico River after the confluence point	:	2,463 m ³ /sec
- River bed longitudinal slope is very flat at about 1/3,000 (or 0.03%), therefore, velocity of the flood water is estimated as not so fast.
- All rivers overflow the banks and flood area extends for quite wide area.
- At downstream side of Rio Chico River, Tarlac – Sta. Rosa Road crosses this river with the 246 m bridge. West approach of the bridge is provided with the equalizer (or series of box-culverts). The bridge constricts the flood water due to insufficient bridge length, flood water back flows towards upstream side until near the confluence point.
- Flood areas were identified by interviews to municipality officials is shown in **Figure 5.2.5-1**.
 - Ordinary river flow area in orange color
 - Frequent flood area (average 1 time/1-2 years)
 - Past maximum flood area by Typhoon Ondoy/Pepeng in 2009) in green color
- Water velocity in the frequent flood areas (blue area) is very slow except the vicinity of the ordinary river flow area.
- Water velocity in the area (green area) between the frequent flood area and the past maximum flood area is minimal and almost dead water.



Note 1: The flood area was identified by interview to the municipality by the Study Team.

Note 2: The Discharge of 50-year return period is from Feasibility Report on the Pampanga Delta Development Project Feb 1982

FIGURE 5.2.5-1 FLOOD CONDITION AT RIO CHICO AND TALAVERA RIVER CONFLUENCE POINT

2) CLLEx Alignment Selection

Three (3) alternative alignments were studied.

Alternative-1: Alignment recommended by 2010 FS.

The alignment starts at SCTEx Tarlac Interchange entrance/exit point. It traverses at slightly upstream side of confluence point of Rio Chico River and Talavera River.

Alternative-2: This alignment starts at SCTEx and traverses at the downstream side of confluence point.

Alternative-3: This alignment starts at TPLEx and passes through the upstream side of confluence point.

TABLE 5.2.5-1 OUTLINE OF ALTERNATIVE ALIGNMENTS

		Alternative-1	Alternative-2	Alternative-3
Starting Point		Existing SCTEx Tarlac Interchange	About 2 km south of SCTEx Tarlac Interchange	About 5.1 km north of SCTEx Tarlac Interchange
Crossing Point in Flood-prone area		About 1.2 km upstream side of confluence point	About 1.2 km downstream side of confluence point	About 4.5 km upstream side of confluence point
Bank Condition	Rio Chico River (upstream)	No east bank	–	No east bank
	Talavera River	East and west banks	–	East and west bank
	Rio Chico River (after 2 rivers merged)	–	East and west banks	–
Bridge Crossing	Rio Chico River (upstream)	Skewed crossing	–	Crossing perpendicular to water flow
	Talavera River	Skewed crossing	–	Crossing perpendicular to water flow
	Rio Chico River (after 2 rivers merged)	–	Crossing perpendicular to water flow	–

Evaluation of alternative alignments is shown in **Table 5.2.5-2**. Alternative-2 was recommended due to the following;

- The most preferred alignment for traffic between Manila side and Cabanatuan City which is dominant traffic on CLLEx.
- The alignment passes through the area where there are banks on both sides of the river; therefore water course is controlled and stable. Flood water overflows the banks, thus enough bridge length needs to be provided.

- Number of affected houses is the least.
- Construction cost is the least, although it is almost the same as Alternative-3.
- Alternative-1 passes through the confluent points of two rivers, not appropriate for the alignment to pass.
- From the view point of river crossing location, Alternative-3 is also appropriate, however, from the view points of traffic efficiency, Alternative-3 is not recommended.

TABLE 5.2.5-2 EVALUATION OF ALIGNMENT ALTERNATIVES

(Confidential)

5.2.6 Proposed CLLEEx Alignment and Interchange Layout

Proposed CLLEEx alignment and interchange layout is shown in **Figure 5.2.6-1**.

OUTLINE OF CLLEX

Expressway Length	30.7 km
Number of Bridges	7
Bridge Length	1,886 m
Equalizing Zone Length	3.78 km
Number of Overpass or Underpass for Intersecting Roads including underpasses for farm roads	Overpass : 1 Underpass : 37 Total : 38
Number of Interchanges:	5
• Between expressways (SCTEx and CLLEEx)	1
• Between CLLEEx and intersecting roads	4




FIGURE 5.2.6-1 PROPOSED CLLEX ALIGNMENT AND LAYOUT OF INTERCHANGES


5.2.7 Toll Collection System

Toll fee should be imposed based on travel distance based toll to assure fairness to expressway users, hence the closed toll collection system should be established which is shown in **Table 5.2.7-1**.


Number of toll booth was computed on the assumption that toll collection would be done manually and is shown in **Table 5.2.7-2**. Actual toll collection shall be partially done by the electronic toll collection system.

Weigh-in-motion equipment for overloaded truck control, administrative maintenance office, and toll houses are planned at the strategic locations as shown in **Table 5.2.7-3**.

TABLE 5.2.7-1 PROPOSED TOLL COLLECTION SYSTEM OF CLLEX



5-23



Tarlac Main Barrier Schematic Map

Toll Collection System Is Proposed As CLOSED SYSTEM

NAME	DESCRIPTION	NO. OF TOLL BOOTH *
(1) Tarlac Main Barrier	From SCTEX : Pay SCTEX Toll And Get Ticket For CLLEX	3
	From Tarlac IC : Get Ticket For CLLEX	2
	To SCTEX : Pay CLLEX Toll And Get Ticket For SCTEX	3
	To Tarlac IC : Pay CLLEX Toll	2
(2) Aliaga IC	Entrance : Get Ticket	2
	Exit : Pay CLLEX Toll	2
(3) Cabanatuan City Bypass IC	Entrance : Get Ticket	2
	Exit : Pay CLLEX Toll	2
(4) Cabanatuan IC	Entrance : Get Ticket	2
	Exit : Pay CLLEX Toll	3
TOTAL		23

Note: * Number of Toll Booth is estimated by future traffic volume and service time (entrance - 6 sec/veh., exit 14 sec/veh.)

TABLE 5.2.7-2 NUMBER OF TOLL BOOTH REQUIRED

Assumption : All Manual Toll Collection

Year 2017

No.	Interchange		AADT (2017)	Peak (%)	Peak Hr. Traffic Total	Toll Collection	Toll Capacity (Manual)	Necessary Toll Booth (Manual)	Necessary Toll Booth (Add.)	Necessary Toll Booth (Total)
			(a)	(b)	(c=a*b)			(d)	(e=c/d)	(f)
1	Tarlac	Main -->	4,461	8%	357	Pay	255	1.4		2
2	Tarlac	Main <--	4,204	8%	336	Pay	255	1.3		2
3	Tarlac	Entrance	1,279	8%	102	Ticket	600	0.2	1	2
4	Tarlac	Exit	1,278	8%	102	Pay	255	0.4	1	2
5	Aliaga	Entrance	955	8%	76	Ticket	600	0.1	1	2
6	Aliaga	Exit	908	8%	73	Pay	255	0.3	1	2
7	Cabana. By	Entrance	1,916	8%	153	Ticket	600	0.3	1	2
8	Cabana. By	Exit	1,554	8%	124	Pay	255	0.5	1	2
9	Cabanatuan	Entrance	2,625	8%	210	Ticket	600	0.4	1	2
10	Cabanatuan	Exit	3,292	8%	263	Pay	255	1.0		2
Total										20

Exit	255	14 sec/veh
Entry	600	6 sec/veh
Flat	450	8 sec/veh

Year 2020

No.	Interchange		AADT (2020)	Peak (%)	Peak Hr. Traffic Total	Toll Collection	Toll Capacity (Manual)	Necessary Toll Booth (Manual)	Necessary Toll Booth (Add.)	Necessary Toll Booth (Total)
			(a)	(b)	(c=a*b)			(d)	(e=c/d)	(f)
1	Tarlac	Main -->	5,106	8%	408	Pay	255	1.6		2
2	Tarlac	Main <--	5,074	8%	406	Pay	255	1.6		2
3	Tarlac	Entrance	1,394	8%	112	Ticket	600	0.2	1	2
4	Tarlac	Exit	1,393	8%	111	Pay	255	0.4	1	2
5	Aliaga	Entrance	852	8%	68	Ticket	600	0.1	1	2
6	Aliaga	Exit	816	8%	65	Pay	255	0.3	1	2
7	Cabana. By	Entrance	2,259	8%	181	Ticket	600	0.3	1	2
8	Cabana. By	Exit	1,913	8%	153	Pay	255	0.6	1	2
9	Cabanatuan	Entrance	3,374	8%	270	Ticket	600	0.4	1	2
10	Cabanatuan	Exit	3,788	8%	303	Pay	255	1.2		2
Total										20


Exit	255	14 sec/veh
Entry	600	6 sec/veh
Flat	450	8 sec/veh

Year 2030

No.	Interchange		AADT (2030)	Peak (%)	Peak Hr. Traffic Total	Toll Collection	Toll Capacity (Manual)	Necessary Toll Booth (Manual)	Necessary Toll Booth (Add.)	Necessary Toll Booth (Total)
			(a)	(b)	(c=a*b)			(d)	(e=c/d)	(f)
1	Tarlac	Main -->	7,568	8%	605	Pay	255	2.4		3
2	Tarlac	Main <--	5,185	8%	415	Pay	255	1.6	1	3
3	Tarlac	Entrance	2,375	8%	190	Ticket	600	0.3	1	2
4	Tarlac	Exit	2,373	8%	190	Pay	255	0.7	1	2
5	Aliaga	Entrance	1,524	8%	122	Ticket	600	0.2	1	2
6	Aliaga	Exit	1,497	8%	120	Pay	255	0.5	1	2
7	Cabana. By	Entrance	2,309	8%	185	Ticket	600	0.3	1	2
8	Cabana. By	Exit	2,899	8%	232	Pay	255	0.9	1	2
9	Cabanatuan	Entrance	3,906	8%	312	Ticket	600	0.5	1	2
10	Cabanatuan	Exit	6,328	8%	506	Pay	255	2.0	1	3
Total										23

Exit	255	14 sec/veh
Entry	600	6 sec/veh
Flat	450	8 sec/veh

TABLE 5.2.7-3 LOCATION FOR TRAFFIC AND MAINTENANCE OFFICE



5-25

INTERCHANGE	DESCRIPTION	NO. OF TOLL BOOTH *	WEIGHT IN MOTION	ADMIN/MAINT. OFFICE	TOLL HOUSE
(1) Tarlac Main Barrier	From SCTEX : Pay SCTEX Toll And Get Ticket For CLEX	3	-	-	1
	From Tarlac IC : Get Ticket For CLEX	2	1	-	-
	To SCTEX : Pay CLEX Toll And Get Ticket For SCTEX	3	-	-	-
	To Tarlac IC : Pay CLEX Toll	2	-	-	-
(2) Aliaga IC	Entrance : Get Ticket	2	1	-	1
	Exit : Pay CLEX Toll	2	-	-	-
(3) Cabanatuan City Bypass IC	Entrance : Get Ticket	2	1	-	1
	Exit : Pay CLEX Toll	2	-	-	-
(4) Cabanatuan IC	Entrance : Get Ticket	2	1	1	-
	Exit : Pay CLEX Toll	3	-	-	-
TOTAL		23	4	1	3

Note: * Number of Toll Booth is estimated by future traffic volume and service time (entrance - 6 sec/veh., exit 14 sec/veh.)

5.2.8 Study on Stage Construction

Traffic volume attracted to CLLEx was estimated in Section 4.2.7 of this report. Traffic volume in 2017, 2020, 2030 was estimated at 11,221, 12,967, 17,340 veh./day, respectively. For this level of traffic volume, there is a need to study the options; one is the stage construction, and the other is on full development from the initial stage;

Option-1: Stage Construction

Initial Stage – 2-lane (1-lane by direction) with overtaking lane at strategic location
Second Stage – Widening to 4-lane

Option-2: Full Development

4-lane from the initial stage

1) 2-lane Expressway in the Philippines and Japan

In the Philippines, there are two (2) existing 2-lane expressways and one (1) 2-lane expressway under construction as follows;

- Section between Lipa City and Batangas City of STAR (*existing*)
 - Traffic Volume in 2009 : **9,181 veh/day**
 - No overtaking lanes, thus fatal traffic accidents are being experienced.
- Subic-Tipo Expressway (*existing*)
 - Traffic Volume in 2009 : **6,798 veh/day**
 - Climbing lane is provided.
- Tarlac-Pangasinan-La Union Expressway (TPLEx) (*under construction*)
 - Estimated traffic volume is as follows;

TRAFFIC FORECAST OF TPLEX

Section	2015	2020	2030
Tarlac – Victoria	14,595	19,196	34,167
Victoria – Gerona	14,824	19,653	35,559
Gerona – Paniqui	12,822	16,940	30,428
Paniqui – Moncada	11,471	15,105	26,952
Moncada – Carmen	9,138	12,033	21,467
Carmen – Urdaneta	4,281	5,656	10,155
Urdaneta – Pozorrubio	8,270	10,969	19,847
Pozorrubio – Rosario	7,501	9,956	18,040

Source: Terms of Reference for Tarlac-La Union Toll Expressway Phase I, August 2007

- 2-lane Expressway in Japan

There are thirty one (31) 2-lane expressways in Japan, of which traffic volume in April, 2011 is shown in **Table 5.2.8-1**.

- Traffic volume more than 10,000 veh./day – 20 expressways
- Traffic volume more than 20,000 veh./day – 3 expressways

Expressways with traffic volume of 10,000 ~ 20,000 veh./day are built and operated as a 2-lane expressway.

**TABLE 5.2.8-1 DAILY TRAFFIC VOLUME OF TWO-LANE EXPRESSWAY
IN JAPAN (2011 APRIL)**

Unit: Vehicle/day

	Expressway name	Min. Section. (vehicle/day)	Max. Section. (vehicle/day)	Average (vehicle/day)
1	Do-ou Expressway	2,549	11,575	5,073
2	Do-tou Expressway	2,046	8,034	6,110
3	Aomori Expressway	5,399	6,443	5,807
4	Hachinohe Expressway	7,277	10,253	7,310
5	Kamaishi Expressway	2,429	2,894	2,579
6	Akita Expressway	5,636	11,626	7,694
7	Yamagata Expressway	4,919	14,799	7,102
8	Tohoku Chuo Expressway	8,876	18,040	11,885
9	Nihonkai Tohoku Expressway	18,095	23,143	20,619
10	Ban'etsu Expressway	6,961	7,776	7,446
11	Jyoban Expressway	902	4,206	4,206
12	Higashi Kanto Expressway	1,655	1,655	1,655
13	Tateyama Expressway	10,420	11,482	11,400
14	Jo-Shin'etsu Expressway	10,896	12,103	11,517
15	Chubu Transversal Expressway	5,391	7,615	6,290
16	Tokai Hokuriku Expressway	6,034	11,647	8,864
17	Kise Expressway	9,431	12,256	11,021
18	Maizuru Wakasa Expressway	6,700	16,709	12,469
19	Hanwa Expressway	12,179	13,428	12,947
20	Harima Expressway	1,367	1,367	1,367
21	Tottori Expressway	6,066	9,818	8,152
22	Okayama Expressway	12,441	13,135	12,788
23	Yonago Expressway	8,496	12,135	9,913
24	Hamada Expressway	5,648	13,220	6,552
25	Sanyo Expressway	5,283	6,281	5,849
26	Takamatsu Expressway	16,671	19,324	17,988
27	Matsuyama Expressway	15,542	20,136	18,240
28	Tokushima Expressway	6,066	9,818	8,152
29	Kochi Expressway	17,959	21,476	18,352
30	Nagasaki Expressway	9,845	11,574	10,709
31	Higashi Kyushu Expressway	7,010	16,149	11,303

Note: Traffic Volume more than 10,000 veh./day
 Traffic Volume more than 20,000 veh./day

2) Level of Service (LOS) Analysis

Definition of Level of Service (LOS) by Highway Capacity Manual (HCM) 2000 of USA for the 2-lane highway and for the multi-lane highway is shown in **Table 5.2.8-2** and **5.2.8-3**, respectively.

TABLE 5.2.8-2 DEFINITION OF LOS FOR TWO-LANE HIGHWAY

LOS A	The highest quality of traffic service, when motorists are able to travel at their desired speed. Without strict enforcement, this highest quality would result in average speeds of 90 km/h or more on two-lane highways.
LOS B	Traffic flow with speeds of 80 km/h or slightly higher on level terrain. The demand for passing to maintain desired speeds becomes significant and approximates the passing capacity at the lower boundary of LOS B.
LOS C	Further increases in flow, resulting in noticeable increases in platoon formation, platoon size, and frequency of passing impediments. The average speed still exceeds 70 km/h on level-terrain.
LOS D	Unstable traffic flow. The two opposing traffic streams begin to operate separately at higher volume levels, as passing becomes extremely difficult. Speeds of 60 km/h still can be maintained under base conditions.
LOS E	Even under base conditions, speeds may drop below 60 km/h. Average travel speeds on highways with less than base conditions will be slower, even down to 40 km/h on sustained upgrades. The capacity of the highway, generally 3,200 pc/h total in both directions. Operating conditions at capacity are unstable and difficult to predict.
LOS F	Heavily congested flow with traffic demand exceeding capacity. Volumes are lower than capacity and speeds are highly variable.

Source: HCM 2000

TABLE 5.2.8-3 DEFINITION OF LOS FOR MULTI-LANE HIGHWAY

LOS A	Free-flow operations. Free-flow speeds prevail. Vehicles are almost completely unimpeded in their ability to maneuver within the traffic stream.
LOS B	Reasonably free flow. Free-flow speeds are maintained. The ability to maneuver within the traffic stream is only slightly restricted, and the general level of physical and psychological comfort provided to drivers is still high.
LOS C	Flow with speeds at or near the Free Flow Speed of the freeway. Freedom to maneuver within the traffic stream is noticeably restricted, and lane changes require more care and vigilance on the part of the driver.
LOS D	The level at which speeds begin to decline slightly with increasing flows and density begins to increase somewhat more quickly. Freedom to maneuver within the traffic stream is more noticeably limited, and the driver experiences reduced physical and psychological comfort levels.
LOS E	Operation at capacity. Operations at this level are volatile, because there are virtually no usable gaps in the traffic stream. Vehicles are closely spaced leaving little room to maneuver within the traffic stream at speeds that still exceed 80 km/h. Maneuverability within the traffic stream is extremely limited, and the level of physical and psychological comfort afforded the driver is poor

LOS F	<p>Breakdowns in vehicular flow. Such conditions generally exist within queues forming behind breakdown points. Breakdowns occur for a number of reasons:</p> <ul style="list-style-type: none"> • Traffic incidents can cause a temporary reduction in the capacity of a short segment, so that the number of vehicles arriving at the point is greater than the number of vehicles that can move through it. • Points of recurring congestion, such as merge or weaving segments and lane drops, experience very high demand in which the number of vehicles arriving is greater than the number of vehicles discharged. • In forecasting situations, the projected peak-hour (or other) flow rate can exceed the estimated capacity of the location.
-------	--

Source: HCM 2000



Source: HCM 2000

FIGURE 5.2.8-1 LEVEL OF SERVICE FOR MULTI-LANE HIGHWAY

Appropriate Level of Service by AASHTO

A Policy on Geometric Design of Highways and Streets, 2004 (AASHTO) suggests the appropriate level of service for each functional class of road as follows;

GUIDELINES FOR SELECTION OF DESIGN LEVEL OF SERVICE

Functional class	Appropriate level of service for specified combinations of area and terrain type			
	Rural level	Rural rolling	Rural mountainous	Urban and suburban
Freeway	B	B	C	C
Arterial	B	B	C	C
Collector	C	C	D	D
Local	D	D	D	D

Source: A Policy on Geometric Design of Highways and Streets, 2004, AASHTO

According to the above guidelines, expressways are recommended that LOS be “B” or “C”, however, the guideline seems to be aiming quite high LOS. LOS may be lowered by one rank, say from “B” to “C”.

Service Traffic Volume of Two-lane CLLEEx

In accordance with HCM formula, the service traffic volume of two-lane CLLEEx was estimated as shown in **Table 5.2.8-4**. Estimated traffic volume and LOS is shown in **Table 5.2.8-5**. The LOS of the 2-lane CLLEEx at the opening year will be “D” and it will be “E” in year 2029. The widening to a 4-lane expressway should be made before LOS reaches to “E”. In consideration of some allowance, CLLEEx needs to be widened by the end of 2025. Development scenario of Option-1 will be as follows;

Initial Stage (2-lane)	:	2017 – 2024 (8 years)
Second Stage (4-lane)	:	2025 -

TABLE 5.2.8-4 SERVICE TRAFFIC VOLUME OF TWO-LANE CLLEEx

LOS	Service volume for LOS	
	Veh/Hour (both directions)	Veh/Day (both directions)
A	Less than 110	Less than 1,375
B	Less than 320	Less than 4,000
C	Less than 700	Less than 8,750
D	Less than 1,310	Less than 16,375
E	Less than 2,430	Less than 30,375
F	More than 2,430	More than 30,375

Consultant’s estimate based on Highway Capacity Manual 2000 (HCM2000)

Note:

Assumptions: 60/40 directional split; 80-percent no-passing zones for level, 23 percent truck and bus; free flow speed; 100km/hr.

TABLE 5.2.8-5 ESTIMATED 2-LANE CLLEX TRAFFIC VOLUME

Year	Daily Traffic Assignment (Veh./day)	Peak Hour Traffic Volume (Veh./hour)	LOS	Volume/Capacity Ratio
2017	11,221	898	D	0.37
2018	11,771	942		0.39
2019	12,352	988		0.41
2020	12,967	1,037		0.43
2021	13,344	1,068		0.43
2022	13,733	1,099		0.45
2023	14,135	1,131		0.47
2024	14,550	1,164		0.48
2025	14,979	1,198		0.49
2026	15,421	1,234		0.51
2027	15,878	1,270		0.52
2028	16,349	1,308		0.54
2029	16,836	1,347		E
2030	17,340	1,387	0.57	
2031	17,859	1,429	0.59	
2032	18,396	1,472	0.61	
2033	18,951	1,516	0.62	
2034	19,524	1,562	0.64	
2035	20,116	1,609	0.66	
2036	20,728	1,658	0.68	
2037	21,360	1,709	0.70	
2038	22,013	1,761	0.72	
2039	22,688	1,815	0.75	
2040	23,386	1,871	0.77	

Assumption: Peak hour rate: 8 percent

Service Traffic Volume of Four-Lane CLLEEx

Service traffic volume of four-lane CLLEEx is shown in **Table 5.2.8-6**. Estimated traffic volume and LOS of four-lane CLLEEx is shown in **Table 5.2.8-7**. The LOS of the 4-lane CLLEEx will be “A” from the opening year of 2017 until 2035 and “B” thereafter until 2040, which suggests that a 4-lane CLLEEx is too much ideal.

Which option to be selected, namely Option-1: Stage Construction or Option-2: Full Development should be determined based on the economic viability of the option.

Service Traffic Volume of CLLEEx Phase-II: Cabanatuan – San Jose Section

Estimated 2-lane Phase-II (Cabanatuan – San Jose Section) of CLLEEx traffic volume and LOS is shown in **Table 5.2.8-8**.

LOS of Phase-II section will be as follows;
2017 - 2022 : LOS C
2023 - 2040 : LOS D

LOS of the Phase II section will not reach to “E” before 2040, thus 2-lane will be enough for Phase-II.

TABLE 5.2.8-6 SERVICE TRAFFIC VOLUME OF FOUR-LANE CLLEX

LOS	Service volume for LOS	
	Veh/Hour (2-lane)	Veh/Day (4-lane)
A	Less than 1,170	Less than 24,374
B	Less than 1,850	Less than 38,541
C	Less than 2,660	Less than 55,415
D	Less than 3,260	Less than 67,915
E	Less than 3,590	Less than 74,790
F	More than 3,590	More than 74,790

Consultant's estimate based on Highway Capacity Manual 2000 (HCM2000)

Note:

Assumptions: Rural Area, 23 percent truck and bus; free flow speed; 100km/hr.

**TABLE 5.2.8-7 ESTIMATED 4-LANE CLLEX TRAFFIC VOLUME
(TARLAC IC – ALIAGA IC SECTION)**

Year	Daily Traffic Assignment (Veh./day) (both directions)	Daily Traffic Assignment (Veh./day) (one direction)	Peak Hour Traffic Volume (Veh./hour) (one direction)	LOS	Volume/Capacity Ratio	
	(a)	(b = a * 0.6)	(c = b * 0.08)			
2017	12,630	7,578	606	A	0.17	
2018	13,150	7,890	631		0.18	
2019	13,691	8,215	657		0.18	
2020	14,255	8,553	684		0.19	
2021	14,759	8,855	708		0.20	
2022	15,281	9,168	733		0.20	
2023	15,821	9,493	759		0.21	
2024	16,380	9,828	786		0.22	
2025	16,959	10,176	814		0.23	
2026	17,559	10,535	843		0.23	
2027	18,180	10,908	873	A	0.24	
2028	18,823	11,294	903		0.25	
2029	19,488	11,693	935		0.26	
2030	20,177	12,106	968		0.27	
2031	20,890	12,534	1,003		0.28	
2032	21,629	12,977	1,038		0.29	
2033	22,394	13,436	1,075		0.30	
2034	23,185	13,911	1,113		0.31	
2035	24,005	14,403	1,152		0.32	
2036	24,854	14,912	1,193		B	0.33
2037	25,732	15,439	1,235			0.34
2038	26,642	15,985	1,279			0.36
2039	27,584	16,550	1,324			0.37
2040	28,559	17,136	1,371			0.38

Assumptions: 60/40 directional split, Peak hour rate : 8 percent

TABLE 5.2.8-8 ESTIMATED 2-LANE CLLEX PHASE-II TRAFFIC VOLUME AND LOS (CABANATUAN – SAN JOSE SECTION)

Year	Daily Traffic Assignment (Veh./day)	Peak Hour Traffic Volume (Veh./hour)	LOS	Volume/Capacity Ratio
2017	7,288	583	C	0.24
2018	7,556	604		0.25
2019	7,834	627		0.26
2020	8,122	650		0.27
2021	8,372	670		0.28
2022	8,630	690		0.28
2023	8,896	712	D	0.29
2024	9,170	734		0.30
2025	9,452	756		0.31
2026	9,743	779		0.32
2027	10,043	803		0.33
2028	10,353	828		0.34
2029	10,671	854		0.35
2030	11,000	880		0.36
2031	11,339	907		0.37
2032	11,688	935		0.38
2033	12,048	964		0.40
2034	12,419	994		0.41
2035	12,801	1,024		0.42
2036	13,196	1,056		0.43
2037	13,602	1,088		0.45
2038	14,021	1,122		0.46
2039	14,453	1,156		0.48
2040	14,898	1,192		0.49

Assumption: Peak hour rate: 8 percent