

**SOCIALIST REPUBLIC OF VIET NAM
PROJECTS MANAGEMENT UNIT NO.2**

FINAL REPORT

**FOR ROAD & BRIDGE PORTION
ON LACH HUYEN PORT
INFRASTRUCTURE CONSTRUCTION
PROJET IN VIET NAM**

(Vol. 2 of 2)

MARCH 2013

Japan International Cooperation Agency (JICA)

ORIENTAL CONSULTANTS CO., LTD. (OC)

NIPPON KOEI CO., LTD. (NK)

PADECO CO., LTD. (PADECO)

JAPAN BRIDGE & STRUCTURE INSTITUTE, INC. (JBSI)

CONTENTS

CHAPTER 1	GENERAL	1-1
1.1	INTRODUCTION	1-1
1.1.1	Background	1-1
1.1.2	Outline of Design Study	1-2
1.1.3	Study Area	1-2
1.2	SCOPE OF DESIGN STUDY	1-4
1.2.1	Scope of Design Study	1-4
1.2.2	Work Schedule	1-6
1.2.3	Main History of the Study	1-7
CHAPTER 2	TOPOGRAPHIC AND HYDROLOGICAL SURVEY	2-1
2.1	TOPOGRAPHIC SURVEY	2-1
2.1.1	Scope and Purpose of Survey	2-1
2.1.2	Applied Standards	2-1
2.1.3	Work Volume	2-2
2.1.4	Equipment for Survey	2-3
2.1.5	Control Point Survey	2-3
2.1.6	Route Survey for Road Portion	2-13
2.1.7	Route Survey for Bridge Portion	2-14
2.1.8	Positioning of Boring Pits	2-16
2.1.9	Survey Results	2-21
2.1.10	Points to be Noted for Drawings	2-27
2.2	HYDROLOGICAL SURVEY	2-28
2.2.1	General	2-28
2.2.2	Review of Hydrological Survey Report in FS Stage	2-28
2.2.3	Supplemental Hydrological Survey	2-31
CHAPTER 3	SUBSOIL CONDITIONS	3-1
3.1	GENERAL	3-1
3.2	STRATUM CLASSIFICATION	3-2
3.3	SUBSOIL CONDITIONS OF APPROACH ROAD AREA IN HAI AN SIDE	3-4
3.3.1	Stratum Classification	3-4
3.3.2	N-value	3-7
3.3.3	Soil Parameters	3-7
3.3.4	Soil Parameters for Design	3-16
3.4	SUBSOIL CONDITIONS OF BRIDGE AREA	3-17
3.4.1	Stratum Classification	3-17
3.4.2	N-value	3-21
3.4.3	Soil Parameters	3-21
3.4.4	Rock Parameters	3-28
3.4.5	Soil and Rock Parameters for Design	3-31
3.5	SUBSOIL CONDITIONS OF APPROACH ROAD AREA IN CAT HAI SIDE	3-32
3.5.1	Stratum Classification	3-32
3.5.2	N-value	3-36
3.5.3	Soil Parameters	3-36
3.5.4	Soil Parameters for Design	3-49

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJEC IN VIET NAM
FINAL REPORT

3.6	CONCLUSIONS AND RECOMMENDATIONS	3-50
3.6.1	Conclusions	3-50
3.6.2	Recommendations	3-52
CHAPTER 4	MATERIAL SURVEY	4-1
4.1	INTRODUCTION	4-1
4.1.1	General	4-1
4.1.2	Objectives of Survey	4-1
4.2	MATERIAL QUANTITIES REQUIRED FOR THE PROJECT	4-2
4.3	CONDITIONS OF SURVEY	4-3
4.3.1	Standards to be applied	4-3
4.3.2	Procedures of Survey	4-4
4.3.3	Contents of Survey	4-5
4.3.4	Quantities of Survey	4-5
4.4	RESULTS OF SURVEY	4-6
4.4.1	List of Material Sources	4-6
4.4.2	Borrow Pits	4-7
4.4.3	Sand Resources for Embankment	4-10
4.4.4	Sand Resources for Soft Soil Treatment	4-13
4.4.5	Rock Quarries for Asphalt Concrete and Cement Concrete	4-15
4.4.6	Fine Aggregate for Asphalt Concrete and Cement Concrete	4-18
4.4.7	Asphalt and Cement Concrete Mixing Plants	4-20
4.5	CONCLUSIONS AND RECOMMENDATIONS	4-21
4.5.1	Conclusions	4-21
4.5.2	Recommendations	4-21
CHAPTER 5	HIGHWAY DESIGN	5-1
5.1	DESIGN CONDITION OF HIGHWAY	5-1
5.1.1	Future development plan of Dinh Vu - Cat Hai Economic Zone	5-1
5.1.2	Design concept in Cat Hai area	5-7
CHAPTER 6	TRAFFIC DEMAND FORECAST	6-1
6.1	GENERAL	6-1
6.2	OBJECTIVE	6-1
6.3	ABOUT THE PROJECT AREA & ROAD	6-1
6.4	REVIEW OF FS & SAPROF TRAFFIC DEMAND FORECASTS	6-2
6.4.1	Target Years	6-2
6.4.2	Traffic Forecasting Methodology	6-3
6.5	UPDATING OF TRAFFIC DEMAND FORECAST	6-5
6.5.1	Traffic Model Variables	6-5
6.5.2	Traffic Model Assumptions	6-7
6.6	FUTURE TRAFFIC FLOWS ON PROJECT ROAD	6-13
6.7	CONCLUSION	6-21

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJCT IN VIET NAM
FINAL REPORT

CHAPTER 7	HIGHWAY DESIGN	7-1
7.1	HIGHWAY DESIGN	7-1
7.1.1	Design Standard	7-1
7.1.2	Basic Design Concept	7-1
7.1.3	Typical Cross Section.....	7-5
7.1.4	Land acquisition and ROW	7-11
7.1.5	Horizontal and Longitudinal Alignment	7-12
7.1.6	Local Approach Road Design	7-17
7.2	PAVEMENT DESIGN	7-24
7.2.1	Design Condition	7-24
7.2.2	Design Result	7-25
7.2.3	Design Sheet.....	7-25
7.3	INTERCHANGE/INTERSECTION DESIGN.....	7-44
7.3.1	Location of Interchange/Intersections.....	7-44
7.4	DRAINAGE DESIGN	7-68
7.4.1	Road Surface Drainage	7-68
7.4.2	Irrigation.....	7-74
7.5	SOFT SOIL TREATMENT.....	7-78
7.5.1	Design Criteria	7-78
7.5.2	Method of analysis	7-80
7.5.3	Result of the analysis	7-82
7.5.4	Typical Cross Section of Soft Soil Treatment	7-94
7.6	ROAD STRUCTURE DESIGN	7-95
7.6.1	Road Structures	7-95
7.7	TRAFFIC SAFETY	7-104
7.7.1	Guardrail	7-104
7.7.2	Guard post.....	7-105
7.7.3	Concrete curb	7-105
7.7.4	Delineators	7-105
7.7.5	Traffic signs.....	7-106
7.7.6	Road marking.....	7-106
CHAPTER 8	DESIGN OF BRIDGES.....	8-1
8.1	DESIGN CONDITIONS.....	8-1
8.1.1	Basic Conditions	8-1
8.1.2	Material to be used.....	8-2
8.1.3	Conditions of Design Load	8-3
8.1.4	Load Modifier Factors and Load Combinations	8-11
8.1.5	Concrete Cover.....	8-13
8.1.6	Site Condition.....	8-14
8.1.7	Concept on Comparative Study for Structure Optimization	8-22
8.2	SPAN LENGTH AND SPAN ARRANGEMENT	8-23
8.2.1	Study on Span Length of Main Bridge.....	8-23
8.2.2	Study on Span Length of Approach Bridge.....	8-24
8.2.3	Study on Number on Continuous Spans of Approach Bridge.....	8-26
8.2.4	Study on Span Length of Flyover Bridge.....	8-28
8.2.5	Recommended Span Arrangement in Bridge Section	8-34
8.3	STUDY OF MAIN BRIDGE	8-35
8.3.1	Selection of Type of Main Bridge	8-35
8.3.2	Selection of Erection Method for Main Bridge.....	8-38
8.3.3	Superstructure of Main Bridge	8-41
8.3.4	Substructure of Main Bridge	8-45

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJCT IN VIET NAM
FINAL REPORT

8.3.5	Study on Main Bridge Foundation	8-62
8.3.6	Detailed Design of Main Bridge	8-85
8.4	DESIGN OF APPROACH BRIDGE.....	8-115
8.4.1	Study on Structure of Approach Bridge	8-115
8.4.2	Substructure of Approach Bridge.....	8-201
8.4.3	Study on Foundation	8-207
8.4.4	Study on Type of Bridge Foundation	8-219
8.4.5	Detailed Design of Approach Bridge	8-227
8.5	DESIGN OF CAM RIVER BRIDGE.....	8-259
8.5.1	Background	8-259
8.5.2	General Plan and Site Conditions of Cam River Bridge.....	8-260
8.5.3	Design of Superstructure.....	8-265
8.5.4	Design of Substructure	8-269
8.5.5	Precast T Girder Erection Method.....	8-272
8.6	STUDY ON BRIDGE ACCESSORIES	8-273
8.6.1	Bearings	8-273
8.6.2	Expansion Joint.....	8-295
8.6.3	Railing.....	8-304
 CHAPTER 9 ELECTRIC WIRING AND LIGHTING FACILITY		9-1
9.1	GENERAL	9-1
9.1.1	Design concept for Electric Wiring.....	9-1
9.1.2	Scope of Works	9-3
9.2	DESIGN STANDARDS.....	9-3
9.3	DESIGN CONDITIONS	9-4
9.3.1	Service conditions	9-4
9.3.2	Design criteria	9-5
9.4	EQUIPMENT AND MATERIAL	9-7
9.4.1	General	9-7
9.4.2	Equipment	9-8
9.4.3	Material	9-10
9.5	INSPECTION AND TEST	9-11
9.6	DRAWINGS	9-12
9.7	FIGURES	9-12
 CHAPTER 10 CONSTRUCTION PLANNING.....		10-1
10.1	PROJECT OUTLINE	10-1
10.1.1	Work Content	10-1
10.1.2	Major Work Quantity	10-2
10.1.3	Major Materials to be incorporated in the works.....	10-5
10.2	TEMPORARY FACILITIES	10-6
10.2.1	Temporary Facilities Outline.....	10-6
10.2.2	Summary of Temporary Facilities	10-6
10.2.3	Temporary Access Road.....	10-7
10.2.4	Navigation Channel Safety	10-11
10.2.5	Existing Utilities and Connection	10-11
10.2.6	Access to and Possession of Site.....	10-12
10.3	SOFT SOIL TREATMENT AND EMBANKMENT WORK	10-13
10.3.1	Soft Soil Treatment Works	10-13
10.3.2	Geo-textile Sheet Spreading Works	10-14
10.4	ROAD WORKS.....	10-15
10.4.1	Road Works Outline	10-15

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJCT IN VIET NAM
FINAL REPORT

10.4.2	Sub grade, Sub -base course and Base- course Works	10-16
10.4.3	Asphalt Treated Base Course and Pavement Works.....	10-16
10.5	APPROACH BRIDGE	10-17
10.5.1	Approach Bridge Works Outline.....	10-17
10.5.2	Approach Bridge (SBS Method) Working Sequence.....	10-17
10.5.3	Sub Structure Works.....	10-18
10.5.4	Fabrication of PC Segments.....	10-22
10.5.5	Segment Erection Work (Span By Span Method).....	10-27
10.5.6	Cast in-place Cantilever Method.....	10-30
10.6	MAIN BRIDGE	10-32
10.6.1	MAIN BRIDGE WORK OUTLINE.....	10-32
10.6.2	Main Bridge Overall Working Program	10-33
10.6.3	Main Bridge Sub-structure Construction Method.....	10-35
10.6.4	Pier Head construction	10-37
10.6.5	Main Bridge Girder Construction Method.....	10-38
10.7	PROGRAM.....	10-40
10.7.1	Total construction period.....	10-40
10.7.2	Basis of program	10-40
10.7.3	Construction Program	10-43
10.7.4	Network Program.....	10-44
10.7.5	Work Days Calculation	10-50
10.8	MACHINE LIST	10-53
10.8.1	Machinery selection study.....	10-53
10.8.2	Machine list.....	10-55
CHAPTER 11 STUDY ON SAFETY IN CONSTRUCTION		11-1
11.1	SAFETY PLAN.....	11-1
11.1.1	Introduction.....	11-1
11.1.2	Objectives.....	11-1
11.1.3	Safety Organization Chart and Responsibility	11-2
11.1.4	Safety Training.....	11-6
11.1.5	Safety Meeting	11-8
11.1.6	Personal Protective Equipment	11-9
11.1.7	Access Control on Site.....	11-11
11.1.8	Safety Control and Activity.....	11-12
11.1.9	Safety Inspection / Remedying Defects	11-13
11.1.10	Penalties for Safety Violations / Failure to Comply.....	11-22
11.1.11	First Aid.....	11-23
11.1.12	Special Obligations and Care of the works	11-23
11.1.13	Working under Extreme Conditions.....	11-26
11.1.14	Emergency Preparedness.....	11-27
11.1.15	Triggering must be done to conform to the following conditions:.....	11-27
11.1.16	Motivation.....	11-28
11.1.17	Effective Communication for Safety.....	11-28
11.1.18	Safety Reports and Notification of Accidents	11-28
11.2	SAFETY WORKING PRACTICES.....	11-30
11.2.1	Objectives.....	11-30
11.2.2	Statutory Requirements on Safe Practices.....	11-30
11.2.3	Preliminary Works / Typical Erection Works	11-30
11.2.4	Excavation and Backfilling.....	11-31
11.2.5	Road Works	11-32
11.2.6	Temporary Jetty Work.....	11-32
11.2.7	Bored Piling Work.....	11-33

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJCT IN VIET NAM
FINAL REPORT

11.2.8	Sheet Pile Work	11-33
11.2.9	Pile Cap / Pier Column Work	11-34
11.2.10	Construction of Bridge Superstructure (Main Bridge).....	11-34
11.2.11	Construction of Bridge Superstructure (Approach Bridge)	11-36
11.2.12	Breach of Safety Plan	11-37
CHAPTER 12 ENVIRONMENTAL AND SOCIAL CONSIDERATIONS		12-1
12.1	OBJECTIVES OF ENVIRONMENTAL AND SOCIAL CONSIDERATIONS AND REQUIRED ACTIONS ..	12-1
12.1.1	Objectives of the tasks on environmental and social considerations	12-1
12.2	REVIEW OF EIA REPORT	12-5
12.2.1	Brief description on the approval of the EIA Report.....	12-5
12.2.2	Deficiencies found in the EIA Report and proposed actions to improve deficiencies	12-5
12.2.3	Impacts to living and livelihood of local residents.....	12-10
12.2.4	Impacts to air ambient and noise.....	12-24
12.2.5	Impacts to surface water quality.....	12-33
12.2.6	Impacts of solid wastes, and waste soils	12-37
12.2.7	Impacts caused by the waste soils dumping sites.....	12-38
12.2.8	Impacts to local traffic, local topography, traffic accidents, etc.....	12-38
12.2.9	Impacts to ecosystem	12-40
12.2.10	Restoration of construction sites and yards after completion of construction.....	12-42
12.3	ENVIRONMENTAL MANAGEMENT PLAN	12-42
12.3.1	Objectives.....	12-42
12.3.2	EMP Implementing Organization.....	12-43
12.3.3	Impact mitigation measures	12-48
12.3.4	Site environmental supervision	12-48
12.3.5	Complaint Procedure.....	12-49
12.3.6	Reporting.....	12-49
12.3.7	Environmental Monitoring Plan.....	12-50
12.3.8	EMP implementing schedule.....	12-53
12.4	OPERATION PHASE EMP	12-54
12.5	RAP MONITORING PLAN	12-54
12.5.1	Objectives of RAP Monitoring Plan	12-54
12.5.2	Various stages to be covered by the RAP Monitoring Plan.....	12-55
12.5.3	Scope of RAP Monitoring Plan.....	12-55
12.5.4	Reports and Reporting.....	12-58
12.5.5	Data Management	12-58
12.6	INFORMATION DISSEMINATION AND PUBLIC CONSULTATIONS.....	12-59
12.7	ESTIMATED COST FOR ENVIRONMENTAL MANAGEMENT	12-61
12.8	SUPPLEMENTARY EIA DUE TO DREDGING WORKS	12-70
CHAPTER 13 HIV/AIDS PREVENTION PROGRAM.....		13-1
13.1	INTRODUCTION	13-1
13.1.1	Situation in Vietnam.....	13-1
13.1.2	Situation in the Project Sites	13-2
13.2	ISSUES	13-4
13.3	DESIGN AND IMPLEMENTATION STRATEGY.....	13-6
13.4	SCOPE OF THE PROGRAM	13-7
13.4.1	Program Title.....	13-7
13.4.2	The Program Period and Schedule	13-8
13.4.3	Supervision, Implementing Agencies, and Manager/Service Providers	13-8

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJCT IN VIET NAM
FINAL REPORT

13.4.4	Site and Immediate Community.....	13-9
13.5	EXPECTED ACTIVITIES	13-11
13.5.1	Implementation Arrangement.....	13-11
13.5.2	Advocacy and Capacity Building.....	13-11
13.5.3	Information, Education, Communication (IEC) and Behavior Change Communication (Peer Education)	13-12
13.5.4	Provision of Health Service and Counseling.....	13-13
13.5.5	Monitoring and Evaluation	13-13
13.6	NOTES FOR DESIGN ADJUSTMENT AND IMPLEMENTATION	13-14
13.7	COST ESTIMATES.....	13-15
13.8	ANNEXES	13-15
13.8.1	Annex-1: Draft Program Design and Monitoring Framework.....	13-15
13.8.2	Annex-2: Tentative Plan of Operation.....	13-23
13.8.3	Annex-3: Sample Implementation Guide.....	13-25
13.8.4	Annex-4: TOR for Management and Monitoring Consultants (Roads & Bridge).....	13-30
13.8.5	Annex-5: Sample TOR for Service Provider	13-32
13.8.6	Annex-6: Sample HIV Clause for Inclusion in Construction Contracts	13-36
13.8.7	Annex-7: Cost estimates	13-38
13.8.8	Annex-8: Abbreviations	13-41
 CHAPTER 14 OPERATION AND MAINTENANCE PLAN		14-1
14.1	OUTLINE OF CONSTRUCTED ROAD	14-1
14.1.1	Legislation Related to the Route	14-1
14.1.2	Details of the Road Facilities	14-2
14.1.3	Ambient Circumstances of Route	14-3
14.2	EXISTING STATE OF THE ROAD OPERATION AND MAINTENANCE.....	14-4
14.2.1	Outline of Responsible Organization for the Operation and Maintenance	14-4
14.2.2	Recent Topics Related to Road Maintenance.....	14-23
14.2.3	Technical Level of Operation and Maintenance Work.....	14-27
14.3	FINANCIAL AND BUDGET SITUATION OF ROAD OPERATION AND MAINTENANCE ORGANIZATION	14-30
14.3.1	Legislation of National Budget Related to Road Operation and Maintenance	14-30
14.3.2	National Budget Related to Road Operation and Maintenance	14-31
14.4	PROPOSAL OF OPERATION AND MAINTENANCE TO CONSTRUCTED ROAD	14-37
14.4.1	Proposal of Management Organization for Operation and Maintenance.....	14-37
14.4.2	Proposal of Organization and Activities in the Management Organization	14-40
14.4.3	Contract Method for Operation and Maintenance Works	14-49
14.4.4	Estimated Cost for Operation and Maintenance Activities	14-49
 CHAPTER 15 COST ESTIMATE AND PROCUREMENT		15-1
15.1	THE POLICY OF THE COST ESTIMATE FOR ROAD AND BRIDGE PORTION	15-1
15.1.1	Application Standard and Related Laws and Regulations	15-1
15.1.2	Construction Cost Structure	15-3
15.1.3	Conditions of Cost Estimate.....	15-4
15.2	PROJECT COST	15-7
15.2.1	Structure of Project Cost	15-7
15.2.2	Project Cost	15-8
15.3	ANNUAL FUND REQUIREMENT	15-17
15.4	PROCUREMENT RATIO FROM JAPAN	15-19
15.5	THE DETAILED EXPLANATION OF COST ESTIMATE.....	15-21
15.5.1	General Items	15-21
15.5.2	Borrow Pit for Earth Work.....	15-24

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJCT IN VIET NAM
FINAL REPORT

15.5.3	Quarry site for Pavement Work and Concrete Work	15-26
15.5.4	SBS Erection Method.....	15-29
15.5.5	Temporary expense contained in Pay-item "Concrete 50Mpa for Segment".....	15-31
15.5.6	Temporary expense contained in Pay-item "concrete 50Mpa for Pier Head Cast in Place"	15-55
15.5.7	Temporary expense contained in Pay-item "Erection of Segment"	15-56
15.5.8	Depreciation of Steel Sheet Pile.....	15-70
CHAPTER 16 PROJECT EFFECTIVENESS.....		16-1
16.1	GENERAL	16-1
16.2	ECONOMIC ANALYSIS	16-1
16.2.1	Review of the Existing Studies	16-1
16.2.2	Preconditions of the Analysis.....	16-2
16.2.3	Evaluation of Project Benefits	16-7
16.2.4	Evaluation of Project Benefits	16-12
16.3	MONITORING OF PROJECT PERFORMANCE	16-15
16.3.1	Qualitative Benefit of the Project.....	16-15
16.3.2	Indicators and Targets	16-16
CHAPTER 17 ROJECT IMPLEMENTATION PLAN.....		17-1
17.1	LOAN AGREEMENT	17-1
17.2	IMPLEMENTATION STRUCTURE	17-1
17.2.1	Related Organizations	17-1
17.3	IMPLEMENTATION SCHEDULE	17-1
17.3.1	Pre-construction Works	17-1
17.3.2	Construction Works.....	17-2
17.3.3	Implementation Program (I/P)	17-2
17.4	CONSTRUCTION PACKAGING PLAN.....	17-4
17.4.1	Background	17-4
17.4.2	Alternatives of Packaging Plans.....	17-4
17.4.3	Comparative Study.....	17-8
CHAPTER 18 FUTURE UPGRADE PLAN.....		18-1
18.1	GENERAL	18-1
18.1.1	Basic Concept.....	18-1
18.1.2	Expected Timing of Second Stage	18-1
18.2	FUTURE UPGRADE PLAN OF ROAD SECTION	18-2
18.2.1	Second Stage	18-2
18.3	FUTURE UPGRADE PLAN OF BRIDGE SECTION	18-3
18.3.1	Abutment.....	18-3
18.3.2	Approach Bridge	18-3
18.3.3	Main Bridge	18-4
18.4	FUTURE UPGRADE PLAN OF TAN VU INTERCHANGE	18-6
18.4.1	First Stage.....	18-6
18.4.2	Second Stage	18-7

CHAPTER 19	PREPARATION OF TENDER DOCUMENTS	19-1
19.1	PREQUALIFICATION DOCUMENTS	19-1
19.1.1	Descriptions.....	19-1
19.1.2	Types of Contract	19-1
19.1.3	Prequalification Documents	19-1
19.2	BIDDING DOCUMENTS	19-2
19.2.1	Descriptions.....	19-2
19.2.2	Sample Bidding Documents Under Japanese ODA Loans	19-2
19.2.3	Bidding Documents for the Project.....	19-2

List of Tables

Table 2.1.2-1	Standards System.....	2-1
Table 2.1.3-1	Contracted and Actual Work Volume.....	2-2
Table 2.1.4-1	Equipment for Survey.....	2-3
Table 2.1.5-1	Parameters in 364:2006 standards	2-5
Table 2.1.5-2	Observation error tolerance in TCXDVN 364:2006 standards.....	2-5
Table 2.1.5-3	Comparison for D/D stage.....	2-6
Table 2.1.5-4	Comparison for F/S stage	2-7
Table 2.1.5-5	Comparison for D/D and F/S stages	2-7
Table 2.1.5-6	Comparison of Elevation of F/S and D/D stages.....	2-9
Table 2.1.5-7	Result of quality control of IV class leveling	2-10
Table 2.1.5-8	Dimensions of secondary control point.....	2-11
Table 2.1.5-9	Results of quality control for Secondary control points	2-12
Table 2.1.8-1	Coordinates of Boring Pits for Road portion.....	2-16
Table 2.1.8-2	Coordinates of Boring Pits for Bridge portion	2-18
Table 2.1.9-1	Final Results of Grade IV control points	2-21
Table 2.1.9-2	Final Result of Secondary control points.....	2-22
Table 2.1.9-3	Detail of Drawings of Longitudinal.....	2-25
Table 2.1.9-4	Detail of Drawings of Cross-section.....	2-25
Table 2.1.9-5	Detail of Drawings of Plan-metric.....	2-25
Table 2.1.9-6	Detail of Drawings of Longitudinal.....	2-26
Table 2.1.9-7	Detail of Drawings of Cross-section.....	2-26
Table 2.1.9-8	Detail of Drawings of Plan-metric.....	2-26
Table 2.1.9-9	Detail of Drawings of Plan-metric.....	2-27
Table 2.1.9-10	Detail of Drawings of Cross-section.....	2-27
Table 2.2.2-1	Scope and Quantities of Hydrological Survey in FS Stage	2-28
Table 2.2.3-1	Highest Water Levels equivalent to frequencies at Hon Dau Station	2-32
Table 2.2.3-2	Highest Water Levels equivalent to frequencies in Bridge Section (Current Status).....	2-32

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJEC IN VIET NAM
FINAL REPORT

Table 2.2.3-3	Highest Water Levels equivalent to frequencies in Bridge Section (After Dinh Vu Industrial Zone completed).....	2-32
Table 2.2.3-4	Highest Water Levels equivalent to frequencies in Road Section Km0-Km4+200	2-33
Table 2.2.3-5	Difference of water level between investigated data and high WLS equivalent to frequencies.....	2-33
Table 2.2.3-6	Design high water levels along the section.....	2-33
Table 2.2.3-7	Summary of Design Water Levels at Locations of Drainage Structures	2-34
Table 3.1-1	Contents of Geotechnical Investigation.....	3-2
Table 3.2-1	Stratum Classification (Main Layer)	3-2
Table 3.3.1-1	Stratum Classification (Hai An side)	3-4
Table 3.3.1-2	Thickness of Each Layer (Hai An side).....	3-5
Table 3.3.2-1	N-value of Each Layer (Hai An side)	3-7
Table 3.3.3-1	Soil Characteristics of Each Layer (Hai An side).....	3-8
Table 3.3.3-2	Shear Strength of Clay for Short Term Stability (Hai An side)	3-10
Table 3.3.3-3	Shear Strength of Clay for Long Term Stability (Hai An side).....	3-11
Table 3.3.3-4	Shear Strength of Sand (Hai An side).....	3-11
Table 3.3.3-5	Soil Parameters for Settlement Analysis (Hai An side).....	3-14
Table 3.3.4-1	Soil Parameters for Design (Hai An side).....	3-16
Table 3.4.1-1	Stratum Classification (Bridge Area).....	3-17
Table 3.4.1-2	Thickness of Each Layer (Bridge Area)	3-18
Table 3.4.2-1	N-value of Each Layer (Bridge Area).....	3-21
Table 3.4.3-1	Soil Characteristics of Each Layer (Bridge Area)	3-22
Table 3.4.3-2	Shear Strength of Clay for Short Term Stability (Bridge Area).....	3-24
Table 3.4.3-3	Shear Strength of Sand (Bridge Area)	3-24
Table 3.4.3-4	Soil Parameters for Settlement Analysis (Bridge Area).....	3-26
Table 3.4.4-1	Results of Rock Test (Bridge Area).....	3-29
Table 3.4.4-2	Rock Parameters for Design (Bridge Area)	3-30
Table 3.5.1-1	Stratum Classification (Cat Hai side)	3-32
Table 3.5.1-2	Thickness of Each Layer (Cat Hai side).....	3-33
Table 3.5.3-1	Soil Characteristics of Each Layer (Cat Hai side)	3-37
Table 3.5.3-2	Shear Strength of Clay for Short Term Stability (Cat Hai side)	3-39
Table 3.5.3-3	Shear Strength of Clay for Long Term Stability (Cat Hai side).....	3-40
Table 3.5.3-4	Shear Strength of Sand (Cat Hai side).....	3-41
Table 3.5.3-5	Soil Parameters for Settlement Analysis (Cat Hai side).....	3-46
Table 3.5.4-1	Soil Parameters for Design (Cat Hai side).....	3-49
Table 3.6.1-1	Stratum Classification (Main Layer)	3-50
Table 3.6.1-2	Soil Parameters for Design (Hai An side).....	3-51
Table 3.6.1-3	Soil and Rock Parameters for Design (Bridge Area).....	3-51
Table 3.6.1-4	Soil Parameters for Design (Cat Hai side).....	3-52
Table 3.6.2-1	Additional Geotechnical Investigation in Construction Stage.....	3-52

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJECT IN VIET NAM
FINAL REPORT

Table 4.1.2-1	Quantities of soil, sand and macadam required for the project.....	4-2
Table 4.1.2-2	Quantities of aggregate for concrete.....	4-2
Table 4.3.1-1	Specification for Soil and Aggregate.....	4-3
Table 4.3.4-1	Quantities of Construction Material Source Survey.....	4-5
Table 4.4.1-1	List of Material Sources	4-6
Table 4.4.2-1	List of Material Sources	4-7
Table 4.4.2-2	Results of Laboratory Tests of Samples at Borrow Pits	4-9
Table 4.4.2-3	Transportation distance.....	4-9
Table 4.4.3-1	Results of Laboratory Tests of Sand Resources for Embankment.....	4-10
Table 4.4.3-2	Reserve, Capacities and Transportation Distance.....	4-12
Table 4.4.4-1	Reserve, Capacities and Transportation Distance.....	4-13
Table 4.4.4-2	Results of Laboratory Tests of Sand Resources for Soft Soil Treatment.....	4-14
Table 4.4.5-1	Reserve, Capacities and Transportation Distance.....	4-15
Table 4.4.5-2	Results of Laboratory Tests of Rock Samples	4-17
Table 4.4.6-1	Reserve, Capacities and Transportation Distance.....	4-18
Table 4.4.6-2	Results of Laboratory Tests of Sand Samples	4-19
Table 4.4.7-1	Location, Actuality, and Technology of Mixing Plants	4-20
Table 5.1.1-1	Area of None-Tariff Zone	5-4
Table 5.1.1-2	Area of Industrial Zone.....	5-4
Table 5.1.1-3	Area of Industrial Zone.....	5-5
Table 6.4.1-1	FS & SAPROF Target Years.....	6-2
Table 6.4.2-1	Dinh Vu Island Trip Generation/Attraction Variables & Values for FS & SAPROF..	6-3
Table 6.4.2-2	Cat Hai Island Trip Generation/Attraction Variables & Values for FS & SAPROF ...	6-3
Table 6.4.2-3	Cat Ba Island Trip Generation/Attraction Variables & Values for FS & SAPROF	6-3
Table 6.4.2-4	Trip Generation & Attraction Rates.....	6-4
Table 6.4.2-5	Comparison of FS & SAPROF Traffic Forecasts for Morning Peak Hour (unit: PCU)	6-5
Table 6.5.1-1	Dinh Vu Island Trip Generation/Attraction Variables for LH Project	6-5
Table 6.5.1-2	Southern Dinh Vu Island Trip Generation/Attraction Variable for LH Project	6-6
Table 6.5.1-3	Cat Hai Island Trip Generation/Attraction Variables for LH Project	6-6
Table 6.5.1-4	Cat Hai Island Trip Generation/Attraction Variables for LH Project	6-7
Table 6.5.2-1	Peak Hour Factors by Vehicle Type.....	6-8
Table 6.5.2-2	PCU Conversion Factors	6-8
Table 6.5.2-3	Modal Split of Industrial Employees in Dinh Vu	6-10
Table 6.5.2-4	Modal Split of Residents in Dinh Vu.....	6-11
Table 6.5.2-5	Project Road Usage	6-11
Table 6.5.2-6	Modal Split for Cat Hai (unit: %)... ..	6-12
Table 6.5.2-7	Modal Split for Cat Ba (unit: %)	6-12
Table 6.6-1	Daily Traffic by Year for Project Area.....	6-13

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJEC IN VIET NAM
FINAL REPORT

Table 6.6-2	Average Annual Growth in Daily Traffic for Project Area	6-13
Table 6.6-3	Daily Traffic by Vehicle Type per Direction for 2015	6-18
Table 6.6-4	Daily Traffic by Vehicle Type per Direction for 2020	6-18
Table 6.6-5	Daily Traffic by Vehicle Type per Direction for 2030	6-18
Table 6.7-1	Comparison of FS & LH Project Traffic Forecasts for Morning Peak Hour(unit: PCU)	6-21
Table 6.7-2	Comparison of SAPROF & LH Project Traffic Forecasts for Morning Peak Hour(unit: PCU)	6-21
Table 7.1.2-1	Dimensions for Design Vehicles	7-1
Table 7.1.2-2	Summary of the Geometric Design Criteria for the Highway	7-2
Table 7.1.3-1	Comparison table of Alternatives of Design of Road Cross Section	7-6
Table 7.1.3-2	Fill slope gradient	7-8
Table 7.1.5-1	Alignment Elements and Coordinates of IP	7-13
Table 7.1.5-2	Comparative Main Control Points for Longitudinal Design	7-14
Table 7.1.5-3	Summary of additional control points for longitudinal alignment design	7-15
Table 7.1.6-1	vertical clearance for local approach road	7-17
Table 7.1.6-2	Summary of underpass box culvert	7-20
Table 7.1.6-3	Summary of frontage road	7-20
Table 7.1.6-4	Design criteria for local approach road	7-23
Table 7.2.1-1	Summary of Design Values	7-24
Table 7.3.1-1	Location of Intersections	7-44
Table 7.3.1-2	Evaluation of Interchange/Intersection Type for Tan Vu Interchange	7-47
Table 7.3.1-3	Capacity Analysis of Tan Vu Interchange	7-48
Table 7.3.1-4	Dimension of Trailer	7-50
Table 7.3.1-5	Intersection Treatment	7-51
Table 7.3.1-6	Minimum Curve Radius for Right Turn Lane	7-52
Table 7.3.1-7	Length of Deceleration Taper	7-52
Table 7.3.1-8	Length of Acceleration Taper	7-53
Table 7.3.1-9	Taper and Deceleration lane length	7-55
Table 7.3.1-10	Evaluation of Interchange/Intersection Type for No.1 Interchange	7-60
Table 7.3.1-11	Capacity Analysis of No.1 Interchange	7-61
Table 7.3.1-12	Design Speed of No.1 Intersection	7-63
Table 7.3.1-13	Entry Width for No.1 Intersection	7-64
Table 7.3.1-14	Flare Length for No.1 Intersection	7-65
Table 7.3.1-15	Entry Angle for No.1 Intersection	7-65
Table 7.4.1-1	Existing and Anticipated Main Land Use along Tan Vu Lach Huyen Highway	7-69
Table 7.4.1-2	Drainage Pipe List	7-71
Table 7.4.1-3	Types of Drainage Pipe Outlet	7-73
Table 7.4.2-1	List of Irrigation Culvert	7-75
Table 7.4.2-2	Comparison Irrigation Culverts between F/S and D/D	7-76

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJEC IN VIET NAM
FINAL REPORT

Table 7.5.1-1	Allowable residual settlement after construction of pavement.....	7-78
Table 7.5.2-1	Friction angle and Ratio of stress division depending on replacement ratio	7-84
Table 7.5.3-1	Sectioning for Detailed Design (Hai An side)	7-86
Table 7.5.3-2	Soil parameters for settlement calculation (Hai An side)	7-88
Table 7.5.3-3	Recommended Countermeasures and Applicable Condition in Detailed Design.....	7-90
Table 7.5.3-4	Soft Soil Treatment Methods.....	7-91
Table 7.5.3-5	Selected countermeasures and result of calculation of the treatment (Hai An side).	7-92
Table 7.5.3-6	Selected countermeasures and result of calculation of the treatment (Cat Hai side)	7-93
Table 7.6.1-1	List of Drainage/Irrigation box culvert type	7-96
Table 7.6.1-2	List of Drainage/Irrigation pipe culvert type	7-96
Table 7.6.1-3	Technical comparison for retaining wall between SAPROF and D/D	7-98
Table 7.7.1-1	Schedule of guardrail.....	7-104
Table 8.1.2-1	Specification for PC Cable	8-2
Table 8.1.3-1	Dynamic Load Allowance	8-4
Table 8.1.3-2	Multiple Presence Factor	8-5
Table 8.1.3-3	Temperature Ranges (degree in Celsius)	8-6
Table 8.1.3-4	Wind Velocity	8-7
Table 8.1.3-5	Correct Coefficient for Wind Zone and Elevation.....	8-7
Table 8.1.3-6	Acceleration and Seismic Zone	8-8
Table 8.1.3-7	Site Coefficient	8-8
Table 8.1.3-8	Response Modification Factor.....	8-9
Table 8.1.4-1	Load Modifier Factors	8-11
Table 8.1.4-2	Load Combinations.....	8-12
Table 8.1.4-3	Minimum Concrete Cover.....	8-13
Table 8.1.4-4	Design data for Approach Bridge at Boring NoBB7	8-14
Table 8.1.4-5	Pier Height and Seawater Depth.....	8-15
Table 8.1.4-6	Correction factor for pier scour	8-17
Table 8.1.4-7	Results of Design Scour Depth.....	8-21
Table 8.1.5-1	Evaluation Criteria of Alternative Study	8-22
Table 8.1.5-2	Scoring System for Evaluation of Alternative Structure.....	8-22
Table 8.2.1-1	Comparison Table on Span Length and Shape of Piers of Approach Bridge	8-25
Table 8.2.2-1	Comparison on Number of Continuous Spans of Approach Bridge.....	8-27
Table 8.2.3-1	Comparison in Flyover Bridge for Intersection No.2	8-32
Table 8.2.3-2	Comparison in Flyover Bridge for Intersection No.3	8-33
Table 8.2.4-1	Recommended Span Arrangement in comparison with SAPROF Study	8-34
Table 8.3.1-1	Comparison on Type of Main Bridge	8-37
Table 8.3.2-1	Comparison between Cast-in-place Cantilever Method and Precast Segment Method of Main Bridge	8-39
Table 8.3.4-1	Comparison Study on Angle of V-shaped Pier	8-46
Table 8.3.4-2	Comparison Study on Pier Appearance in Longitudinal Direction	8-48

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJCT IN VIET NAM
FINAL REPORT

Table 8.3.4-3	Summary of Section Forces* of Pier due to Creep and Shrinkage.....	8-55
Table 8.3.4-4	Summary of Stress* of Pier due to Creep and Shrinkage.....	8-56
Table 8.3.4-5	Summary of Bending Moment of Pier due to Pressurization.....	8-60
Table 8.3.4-6	Summary of Stress of Pier due to Pressurization.....	8-61
Table 8.3.4-7	Summary of Preliminary Cost Estimate of Pressurization Work (One Set).....	8-61
Table 8.3.5-1	Site Conditions for Study.....	8-62
Table 8.3.5-2	Comparison on Foundation for Main Bridge.....	8-63
Table 8.3.5-3	Comparison on Foundation Style for Main Bridge.....	8-65
Table 8.3.5-4	Determined design boring No.....	8-70
Table 8.3.5-5	Safety Factor for Bearing Capacity and Allowable Stress in Steel Pipe.....	8-71
Table 8.3.5-6	Properties and Stress Limit of Steel Pipe for Steel Pipe Sheet Pile.....	8-73
Table 8.3.5-7	Design of Estimated Corrosion Thicknesses.....	8-73
Table 8.3.5-8	Stability Calculation model.....	8-74
Table 8.3.5-9	Determined design model.....	8-76
Table 8.3.6-1	Dimensions of Structural Members of Substructure.....	8-85
Table 8.3.6-2	Dimensions of Structural Members of Superstructure.....	8-85
Table 8.3.6-3	Properties of Concrete.....	8-86
Table 8.3.6-4	Properties of Prestressing Steel.....	8-86
Table 8.3.6-5	Properties of Reinforcing Steel.....	8-86
Table 8.3.6-6	Construction Sequence simulated in Structural Analysis.....	8-89
Table 8.3.6-7	Required Reinforcement for Shear Force in Longitudinal Direction.....	8-95
Table 8.3.6-8	Required Reinforcement in Transversal Direction.....	8-101
Table 8.3.6-9	Design Results of SPSP for Longitudinal Direction.....	8-110
Table 8.3.6-10	Design Results of SPSP for Transversal Direction.....	8-111
Table 8.3.6-11	Design Results of Top Slab for Longitudinal Direction.....	8-112
Table 8.3.6-12	Design Results of Top Slab for Transverse Direction.....	8-113
Table 8.3.6-13	Design Results connection between Top Slab and SPSP.....	8-114
Table 8.4.1-1	Comparison on Erection Method for Approach Bridge.....	8-116
Table 8.4.1-2	Comparison on Erection for Approach Bridge (A1-P75).....	8-118
Table 8.4.1-3	Comparison on Erection for Approach Bridge (P79-A2).....	8-119
Table 8.4.1-4	Concrete covering for reinforcing bars (22TCN-272-05).....	8-124
Table 8.4.1-5	Approximate dimension of each member.....	8-125
Table 8.4.1-6	Necessary thickness for arrangement of tendon.....	8-126
Table 8.4.1-7	Thickness of Lower Slab.....	8-126
Table 8.4.1-8	Thickness of Web.....	8-127
Table 8.4.1-9	Temperature Gradient.....	8-128
Table 8.4.1-10	Load Factor and Load Combination.....	8-129
Table 8.4.1-11	Properties of Concrete (Main Girder).....	8-129
Table 8.4.1-12	Properties of Prestressing Steel (PC Strand Cable).....	8-130
Table 8.4.1-13	Properties of Prestressing Steel (PC Bar - SBPR930/1180).....	8-130
Table 8.4.1-14	Rc reinforcing Bars.....	8-130

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJCT IN VIET NAM
FINAL REPORT

Table 8.4.1-15	Spring Constants of Pile	8-132
Table 8.4.1-16	Spring Constants of Shoe	8-132
Table 8.4.1-17	Structure clarification of Main girder	8-147
Table 8.4.1-18	Direct wheel load on Upper slab	8-147
Table 8.4.1-19	Bending moment (Live load) [A]	8-148
Table 8.4.1-20	Designed Bending moment (D+LL+IM+Ps+Cr+SH) [A].....	8-148
Table 8.4.1-21	Composite bending fiber stress [A].....	8-149
Table 8.4.1-22	Safety factor for ultimate load working state [A].....	8-150
Table 8.4.1-23	Bending moment (live load) [B].....	8-151
Table 8.4.1-24	Designed Bending moment (D+LL+IM+Ps+Cr+SH) [B].....	8-151
Table 8.4.1-25	Arrangement of reinforced bars.....	8-152
Table 8.4.1-26	Stress of reinforcing bars.....	8-152
Table 8.4.1-27	Safety factor under ultimate load working state [B].....	8-153
Table 8.4.1-28	Bending moment (live load) [C].....	8-154
Table 8.4.1-29	Designed bending moment (D+LL+IM+Ps+Cr+SH) [C]	8-154
Table 8.4.1-30	Composite bending stress [C].....	8-155
Table 8.4.1-31	Safety factor under ultimate load working state [C].....	8-156
Table 8.4.1-32	Bending moment (live load) [D].....	8-157
Table 8.4.1-33	Designed bending moment (D+LL+IM+Ps+Cr+SH) [D]	8-157
Table 8.4.1-34	Arrangement of reinforced bars.....	8-158
Table 8.4.1-35	Stress of reinforcing bars.....	8-158
Table 8.4.1-36	Safety factor under ultimate load working state [D].....	8-159
Table 8.4.1-37	Concrete covering for reinforcing bars (TCXDVN327: 2004)	8-160
Table 8.4.1-38	Approximate dimension of each member.....	8-161
Table 8.4.1-39	Necessary thickness for arrangement of tendon	8-162
Table 8.4.1-40	Thickness of Lower Slab	8-163
Table 8.4.1-41	Necessary thickness for arrangement of cable.....	8-163
Table 8.4.1-42	Standard classification of traveler.....	8-165
Table 8.4.1-43	Length of Pier Table	8-165
Table 8.4.1-44	Relation between segment length and area of main girder.....	8-166
Table 8.4.1-45	Temperature Gradient.....	8-168
Table 8.4.1-46	Load Factor and Load Combination.....	8-168
Table 8.4.1-47	Properties of Concrete (Main Girder).....	8-169
Table 8.4.1-48	Properties of Pre stressing Steel (PC Strand Cable)	8-169
Table 8.4.1-49	Properties of Pre-stressing Steel (PC Bar - SBPR930/1180).....	8-170
Table 8.4.1-50	Properties of Pre-stressing Steel (Reinforcement Bar).....	8-170
Table 8.4.1-51	Spring Constants of Pile	8-171
Table 8.4.1-52	Spring Constants of Shoe	8-172
Table 8.4.1-53	Structure clarification of Main girder	8-181
Table 8.4.1-54	Direct wheel load on Upper deck slab.....	8-181
Table 8.4.1-55	Bending moment (Live load) [A]	8-182

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJCT IN VIET NAM
FINAL REPORT

Table 8.4.1-56	Designed Bending moment (D+LL+IM+Ps+Cr+SH) [A].....	8-182
Table 8.4.1-57	Composite bending stress [A].....	8-183
Table 8.4.1-58	Safety factor for ultimate load working state [A].....	8-184
Table 8.4.1-59	Bending moment (live load) [B].....	8-184
Table 8.4.1-60	Designed Bending moment (D+LL+IM+Ps+Cr+SH) [B].....	8-184
Table 8.4.1-61	Arrangement of reinforced bars.....	8-185
Table 8.4.1-62	Stress of reinforcing bars.....	8-185
Table 8.4.1-63	Safety factor under ultimate load working state [B].....	8-186
Table 8.4.1-64	Bending moment (live load) [C].....	8-186
Table 8.4.1-65	Designed bending moment (D+LL+IM+Ps+Cr+SH) [C]	8-186
Table 8.4.1-66	Composite bending stress [C].....	8-187
Table 8.4.1-67	Safety factor under ultimate load working state [C].....	8-188
Table 8.4.1-68	Bending moment (live load) [D].....	8-189
Table 8.4.1-69	Designed bending moment (D+LL+IM+Ps+Cr+SH) [D]	8-189
Table 8.4.1-70	Arrangement of reinforced bars.....	8-190
Table 8.4.1-71	Stress of reinforcing bars.....	8-190
Table 8.4.2-1	Stress of external cable and reinforcing bar.....	8-195
Table 8.4.3-1	Stress of external cable and reinforcing bar.....	8-204
Table 8.4.3-2	Length of approach cushion slab.....	8-214
Table 8.4.3-3	Comparative Study on Pier Sharpe of Approach Bridge	8-216
Table 8.4.3-4	Width of bridge seats	8-218
Table 8.4.3-5	Refer from JSHB	8-219
Table 8.4.4-1	Pier Height and Seawater Depth.....	8-221
Table 8.4.4-2	Foundation Study Type for Approach Bridge and Main Bridge.....	8-222
Table 8.4.4-3	Pile arrangement.....	8-223
Table 8.4.4-4	Connections between pile and pile cap.....	8-224
Table 8.4.4-5	Comparison for pile diameter of steel pipe pile at Pier	8-226
Table 8.4.4-6	Comparison for pile diameter of steel pipe pile at abutment.....	8-226
Table 8.4.4-7	Comparison for pile diameter of cast in place pile.....	8-227
Table 8.4.4-8	Load combination and load factor.....	8-229
Table 8.4.4-9	The results of Study of Foundation Type.....	8-231
Table 8.4.5-1	Site Condition for Study of Type-1	8-232
Table 8.4.5-2	Comparison on Foundation Type-1 for Approach Bridge	8-234
Table 8.4.5-3	Site Condition for Study of Type-2.....	8-235
Table 8.4.5-4	Comparison on Foundation Type-2 for Approach Bridge	8-236
Table 8.4.5-5	Site Conditions for Study of Type-4	8-237
Table 8.4.5-6	Comparison on Foundation type-4 for Approach Bridge	8-239
Table 8.4.6-1	Elevation and Reclamation thickness from bottom of pile cap	8-240
Table 8.4.6-2	Dimension list of Substructure(1/2).....	8-244
Table 8.4.6-3	Dimension list of Substructure(2/2).....	8-245
Table 8.4.6-4	Grouping of Pier	8-246

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJCT IN VIET NAM
FINAL REPORT

Table 8.4.6-5	List of reinforcement for each type of Pier(1/2).....	8-247
Table 8.4.6-6	List of reinforcement for each type of Pier(1/2).....	8-248
Table 8.4.6-7	Properties and Stress Limit and used Steel Pipe.....	8-249
Table 8.4.6-8	Range of thickness and used thickness.....	8-249
Table 8.4.6-9	Design of Estimated Corrosion Thicknesses.....	8-249
Table 8.4.6-10	Type of Steel pipe pile.....	8-251
Table 8.4.6-11	List of Steel pipe pile(1/2).....	8-252
Table 8.4.6-12	List of Steel pipe pile(2/2).....	8-253
Table 8.4.6-13	Type of Bored pile.....	8-257
Table 8.4.6-14	List of Bored pile.....	8-258
Table 8.5.2-1	Hydrological Conditions of Cam River.....	8-260
Table 8.5.2-2	Soil Condition at Boring No.BA-13 and BA-14.....	8-261
Table 8.5.2-3	Calculation of Scour Depth.....	8-263
Table 8.5.2-4	Total Scour Depth.....	8-263
Table 8.6.1-1	Comparison on Type of Bearing for Main Bridge.....	8-274
Table 8.6.1-2	Reaction Forces and Displacements at Bearings.....	8-275
Table 8.6.1-3	Reaction force of rubber bearing.....	8-278
Table 8.6.1-4	Reaction force of rubber bearing.....	8-278
Table 8.6.1-5	Amount of Movement at each bearing.....	8-279
Table 8.6.1-6	Amount of Movement in each support.....	8-279
Table 8.6.1-7	Allowable value of rubber.....	8-280
Table 8.6.1-8	Allowable value of Inner Steel Plate.....	8-280
Table 8.6.1-9	Detail Dimension of Bearing.....	8-281
Table 8.6.1-10	Longitudinal movement.....	8-281
Table 8.6.1-11	Check result of stress.....	8-282
Table 8.6.1-12	Check result of transformation performance.....	8-282
Table 8.6.1-13	Check result of stress.....	8-282
Table 8.6.1-14	Check result of transformation performance.....	8-283
Table 8.6.1-15	The amount of the movement at earthquake.....	8-283
Table 8.6.1-16	The result of the buckling stress, shearing strain and tensile stress.....	8-284
Table 8.6.1-17	Reaction force of rubber bearing.....	8-286
Table 8.6.1-18	Reaction force of rubber bearing.....	8-286
Table 8.6.1-19	Amount of Movement in each support.....	8-287
Table 8.6.1-20	Amount of Movement in each support.....	8-287
Table 8.6.1-21	Allowable value of rubber.....	8-288
Table 8.6.1-22	Allowable value of Inner Steel Plate.....	8-288
Table 8.6.1-23	Detail Dimension of Bearing.....	8-289
Table 8.6.1-24	Longitudinal movement.....	8-290
Table 8.6.1-25	Check result of stress.....	8-290
Table 8.6.1-26	Check result of transformation performance.....	8-291
Table 8.6.1-27	Check result of stress.....	8-291

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJCT IN VIET NAM
FINAL REPORT

Table 8.6.1-28	Check result of transformation performance	8-291
Table 8.6.1-29	The amount of the movement at earthquake.....	8-292
Table 8.6.1-30	The result of the buckling stress, shearing strain and tensile stress.....	8-293
Table 8.6.2-1	Comparison on Type of Expansion.....	8-296
Table 8.6.2-2	Longitudinal Movement at Ends of Main Girders.....	8-297
Table 8.6.2-3	Amount of the movement	8-299
Table 8.6.2-4	The design movement applied to the expansion joint considers T he movement after the girder	8-300
Table 8.6.2-5	The amount of design movement at the abutment and pic	8-300
Table 8.6.2-6	Amount of the movement	8-301
Table 8.6.2-7	The design movement applied to the expansion joint considers the movement after the girder	8-302
Table 8.6.2-8	The amount of design movement at the abutment and pic	8-302
Table 8.6.3-1	Comparison on Type for Handrail	8-305
Table 9.1.1-1	Available Product in Vietnam.....	9-2
Table 9.3.2-1	Technical parameters of power receiving and distribution system.....	9-5
Table 10.1.2-1	Major Work Quantity.....	10-2
Table 10.1.3-1	Major Materials	10-5
Table 10.2.2-1	Summary of Temporary Facilities	10-7
Table 10.2.4-1	Navigation Safety Equipment.....	10-11
Table 10.3.1-1	Soft Soil Treatment and Embankment Work Procedure	10-13
Table 10.5.3-1	Approach Bridge Piling Machinery and Working Platform	10-19
Table 10.7.2-1	Frequency in Occurrence of Normal Wave Height by Direction.....	10-42
Table 10.7.2-2	Work Limit natural conditions for marine activity	10-42
Table 11.1.8-1	Example of Table of Safety Activity.....	11-13
Table 12.1.1-1	Required actions for environmental considerations.....	12-1
Table 12.1.1-2	Required actions on social considerations	12-3
Table 12.2.2-1	EIA Report Appraisal Council's major comments and proposed actions to improve	12-5
Table 12.2.2-2	Deficiencies in the EIA Report found by the JICA D/D Study Team and proposed actions to improve	12-9
Table 12.2.3-1	Land use in the project-affected wards/communes.....	12-11
Table 12.2.3-2	Population of the wards/communes in the Project area.....	12-12
Table 12.2.3-3	Category of house by its built material and story	12-12
Table 12.2.3-4	Coverage of public facilities.....	12-13
Table 12.2.3-5	Land to be acquired for the Project (unit: m ²)	12-13
Table 12.2.3-6	Affected structures and households	12-14
Table 12.2.3-7	Expected works during construction phase (Road & Bridge Portion).....	12-21

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJEC IN VIET NAM
FINAL REPORT

Table 12.2.4-1	Background air pollution concentration (unit:µg/m3)	12-25
Table 12.2.4-2	Predicted ambient quality (unit: µg/m ³) (at the survey point 10m from the road embankment side).	12-26
Table 12.2.4-3	Predicted noise level at survey point A1.....	12-27
Table 12.2.4-4	Predicted noise level at survey point A2.....	12-28
Table 12.2.4-5	Predicted noise level at survey point A3.....	12-28
Table 12.2.4-6	Predicted noise level at survey point A4.....	12-28
Table 12.2.4-7	Summarization of predicted noise level at 4 survey points	12-29
Table 12.2.4-8	Typical Noise Mitigation Measures.....	12-30
Table 12.2.4-9	Location of materials exploitation sources, transportation routes, and distance to the Project site.....	12-31
Table 12.2.5-1	Location of additional site for surface water quality survey and its sampling time	12-35
Table 12.2.5-2	Result of water quality survey at supplemental site	12-36
Table 12.2.9-1	Mangrove trees found in the Project area	12-40
Table 12.3.1-1	Policy, objective, and target of EMP	12-42
Table 12.3.7-1	Coordination of location of sampling sites of ambient air and surface water	12-51
Table 12.3.7-2	Environmental Monitoring – Pre-construction phase.....	12-51
Table 12.3.7-3	Environmental Monitoring Program - Construction Phase	12-52
Table 12.5.2-1	Stages of resettlement and targeted activities covered by the RAP Monitoring Plan.....	12-55
Table 12.5.3-1	Indicators to be applied for the internal monitoring	12-56
Table 12.5.3-2	Indicators to be applied for the external monitoring.....	12-57
Table 12.5.4-1	Proposed reporting cycle for RAP monitoring	12-58
Table 12.7-1	Personnel Training Program	12-61
Table 12.7-2	Estimated Costs for Environmental Protection for construction of environmental facilities.....	12-62
Table 12.7-3	Estimated cost for maintenance of environmental facilities (during the first 2 years of operation phase).....	12-62
Table 12.7-4	Estimated cost for socio-economic survey	12-63
Table 12.7-5	Estimated cost for environmental sampling survey – direct expenses	12-64
Table 12.7-6	Estimated cost for environmental sampling survey – indirect expenses	12-65
Table 12.7-7	Estimated cost for monitoring	12-66
Table 12.7-8	Estimated cost for public consultation and information dissemination	12-67
Table 12.7-9	Estimated cost for implementation of RAP	12-68
Table 12.7-10	Total estimated cost for environmental management and monitoring.....	12-69
Table 13.4.2-1	Program Schedule.....	13-8
Table 13.4.4-1	Expected Participants in the Program.....	13-10
Table 13.7-1	Summary Table for Cost Estimates	13-15
Table 14.1.1-1	Law, Regulation, Decree and Circular for the Development of Tan Vu - Lach Huyen Highway	14-1

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJEC IN VIET NAM
FINAL REPORT

Table 14.1.2-1	Outline of Tan Vu - Lach Huyen Highway.....	14-2
Table 14.1.3-1	Ambient Surrounding Tan Vu - Lach Huyen Highway	14-3
Table 14.1.3-2	Related Organizations along Tan Vu - Lach Huyen Highway	14-4
Table 14.2.1-1	Role and Duties of Representative Departments of DRVN.....	14-7
Table 14.2.1-2	Function of Infrastructure and Road Safety Department.....	14-8
Table 14.2.1-3	Roles in Road Traffic Safety Activities between DRVN and Traffic Police.....	14-9
Table 14.2.1-4	Function of Maintenance and Management Department.....	14-9
Table 14.2.1-5	Expenditure of Road Operation and Maintenance in DRVN (2006 - 2010).....	14-10
Table 14.2.1-6	RRMUs under DRVN.....	14-10
Table 14.2.1-7	Organizational Profile of RRMU2.....	14-11
Table 14.2.1-8	Expenditure of Road Operation and Maintenance in RRMU2 (2006 - 2010).....	14-12
Table 14.2.1-9	RRMCs under RRMU2	14-13
Table 14.2.1-10	Organizational profile of RRMC (240)	14-14
Table 14.2.1-11	Expenditures for Road Development and Maintenance in RRMC (240).....	14-16
Table 14.2.1-12	Organizational Profile of County Unit.....	14-16
Table 14.2.1-13	Organizational Profile of Hai Phong PDOT	14-18
Table 14.2.1-14	Expenditures for Road Operations and Maintenance in Hai Phong PDOT (2006 - 2010).....	14-20
Table 14.2.1-15	Organizational Profile of RRMC (Overland Road Company)	14-20
Table 14.2.1-16	Expenditures for Road Development and Maintenance in RRMC (Hai Phong Overland road one member limited Company)	14-22
Table 14.2.2-1	Organizational Profile of RRMC (236)	14-23
Table 14.2.2-2	Expenditures for Road Development and Maintenance in RRMC (236).....	14-25
Table 14.2.2-3	Outline of PBMC.....	14-26
Table 14.2.2-4	Monitoring Items of Each Facilities	14-26
Table 14.2.2-5	Outline of PBMC Workshop in Vietnam	14-27
Table 14.2.3-1	Function of Science, Technology, Environment and International-Cooperation Department by DRVN's Regulation	14-28
Table 14.2.3-2	List of Prepared Standards and Specifications on Road Operation and Maintenance by DRVN.....	14-28
Table 14.2.3-3	Outline of Technical Co-operation Project on Road Maintenance by JICA.....	14-29
Table 14.3.1-1	Law, Regulation, Decree and Circular of Fiscal Resources for Road Development, Operation and Maintenance	14-30
Table 14.3.1-2	List of Tax, Fee and Charge for Road Maintenance Fund.....	14-30
Table 14.3.2-1	Analysis Results of Ten Years Plan	14-31
Table 14.3.2-2	Government Budget System and Process	14-32
Table 14.3.2-3	State Budget for Maintenance, Repair Work and Construction.....	14-35
Table 14.3.2-4	Sufficiency Ratio of the Maintenance Budget.....	14-36
Table 14.4.1-1	Typical Process and Schedule to Determine the Road Operator	14-37
Table 14.4.1-2	Options of the Assumed Management Organization	14-37
Table 14.4.1-3	Comparison Table of the Maintenance Organization	14-38
Table 14.4.2-1	Size of the RRMC's Office by NORM.....	14-42
Table 14.4.2-2	Responsible Organization to Each Maintenance Work.....	14-43

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJEC IN VIET NAM
FINAL REPORT

Table 14.4.2-3	Details of the Site Office	14-43
Table 14.4.2-4	Construction Equipment in RRMC (240) and RRMC (236).....	14-44
Table 14.4.2-5	Concrete Activities of the Maintenance Works	14-45
Table 14.4.2-6	Needed Operation and Maintenance Technique for Tan Vu - Lach Huyen Highway.....	14-46
Table 14.4.4-1	Outline of Each Calculation Method for Operation and Maintenance Cost.....	14-50
Table 14.4.4-2	Routine Maintenance Annual Cost.....	14-50
Table 14.4.4-3	Periodic Maintenance Cost for 10 Years.....	14-51
Table 14.4.4-4	Estimate of Future Operation and Maintenance Cost.....	14-51
Table 14.4.4-5	Routine and Periodic Maintenance Cost Estimation by SAPROF	14-52
Table 14.4.4-6	Routine and Periodic Maintenance Cost Estimation by This Study.....	14-52
Table 15.1.1-1	Application of a Japanese cost estimate standard.....	15-2
Table 15.1.1-2	The composition of the labour in SBS construction method.....	15-2
Table 15.1.3-1	The Currency Classification and The Tax in Project Cost Item	15-5
Table 15.2.1-1	Composition of Bill item of Project cost	15-7
Table 15.2.2-1	Verification Cost of MOC.....	15-9
Table 15.2.2-2	Approved Cost of DRVN.....	15-10
Table 15.2.2-3	Project Cost Based On Present Exchange Rate of Road and Bridge Portion	15-12
Table 15.2.2-4	Project Cost based on M/D (19 th March 2010) of Road of “Lach Huyen Port Infrastructure Construction Project”	15-13
Table 15.2.2-5	Comparison of a direct construction cost (without VAT)	15-14
Table 15.2.2-6	The Detail Factor of Change.....	15-15
Table 15.2.2-7	Consultant Recommendation Cost	15-16
Table 15.3-1	The output by year (Based on the construction plan)	15-17
Table 15.3-2	Yearly Price Index	15-17
Table 15.3-3	Annual Fund Requirement.....	15-18
Table 15.4-1	Summary of Procurement Ratio from Japan.....	15-19
Table 15.4-2	Amount of Procurement from Japan.....	15-20
Table 15.5.1-1	Summary of Temporary Facilities	15-21
Table 15.5.1-2	Temporary Roads and Site Compound	15-22
Table 15.5.1-3	Water Cut-off Expense for Road Construction.....	15-22
Table 15.5.2-1	The procurement place of filling material	15-24
Table 15.5.2-2	Required quantity of filling and procurement distribution	15-25
Table 15.5.3-1	Required quantity of sand and a crushed stone Existing Sand Stockpiles.....	15-26
Table 15.5.3-2	Summary of Distribution of Sand Pit and Quarry Site	15-28
Table 15.5.3-3	Existing Sand Stockpiles	15-28
Table 15.5.3-4	Existing Quarry Site	15-29
Table 15.5.4-1	The SBS equipment included in pay-items	15-29
Table 15.5.5-1	Quantity of Rail Foundation of Gantry Crane (80t)	15-31
Table 15.5.5-2	Quantity of Rail Foundation of Gantry Crane (7.5t)	15-31
Table 15.5.5-3	Quantity of Shed Rail Foundation	15-32

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJCT IN VIET NAM
FINAL REPORT

Table 15.5.5-4	Quantity of Reinforcement assembly stand Foundation.....	15-32
Table 15.5.5-5	Quantity of Short Line Equipment Foundation	15-33
Table 15.5.5-6	Quantity of Segment Stockyard Foundation.....	15-35
Table 15.5.5-7	Japan Norm of Rail Equipment installation and Removal (Per 100m)	15-36
Table 15.5.5-8	Japan Norm of Gantry crane (80t) assembly and demolition	15-36
Table 15.5.5-9	Concrete foundation (per one crane)	15-38
Table 15.5.5-10	Japan norm of Tower crane (180t-m) installation and demolition.....	15-38
Table 15.5.5-11	Product Cost of No.1, No.2 Erection Girder (Quotation)	15-39
Table 15.5.5-12	Japan norm of Movable shed assemble and demolition	15-40
Table 15.5.5-13	Japan Norm of Support Installation and Removal (per 10m).....	15-41
Table 15.5.5-14	Japan Norm of Reinforcement assembly stand ground assembly	15-42
Table 15.5.5-15	Reinforcement assembly stand installation Per 10t.....	15-42
Table 15.5.5-16	Reinforcement assembly stand removal Per 10t.....	15-43
Table 15.5.5-17	Short line form installation and removal Per 1.0t.....	15-43
Table 15.5.5-18	Quantity of Side form main part.....	15-44
Table 15.5.5-19	Quantity of Side form support beam	15-44
Table 15.5.5-20	Quantity of Frame of Side form.....	15-45
Table 15.5.5-21	Quantity of Bottom form (for L= 3.000 m).....	15-45
Table 15.5.5-22	Quantity of Bottom frame support beam (for L=3.000m).....	15-45
Table 15.5.5-23	Quantity of Frame of bottom form (for L=3.0m)	15-46
Table 15.5.5-24	Quantity of Bottom form pillar (replacement type).....	15-46
Table 15.5.5-25	Quantity of Bottom form rail material.....	15-46
Table 15.5.5-26	Type of Inner Form.....	15-47
Table 15.5.5-27	Quantity of Inner Form Type-1	15-48
Table 15.5.5-28	Quantity of Inner Form Type-2.....	15-48
Table 15.5.5-29	Quantity of Inner Form Type-3.....	15-49
Table 15.5.5-30	Quantity of Inner Form Type-4.....	15-49
Table 15.5.5-31	Quantity of Inner Form Type-5.....	15-50
Table 15.5.5-32	Quantity of Inner form support beam	15-50
Table 15.5.5-33	Quantity of Inner form move cart.....	15-51
Table 15.5.5-34	Quantity of Inner form rail material	15-51
Table 15.5.5-35	Quantity of Lateral beam parts of Inner form.....	15-52
Table 15.5.5-36	Quantity of Edge form main part.....	15-52
Table 15.5.5-37	Quantity of Frame of edge form	15-52
Table 15.5.5-38	List of Hydraulic-machines equipment hire for beam separation.....	15-53
Table 15.5.5-39	Reference norm of Standard Segment production	15-54
Table 15.5.5-40	Manufacture yard power supply equipment	15-54
Table 15.5.6-1	Japan Norm of Bracket support and scaffold.....	15-55
Table 15.5.6-2	Japan Norm of Segment support on the bracket.....	15-56
Table 15.5.7-1	Japan Norm of Steel Plate Foundation	15-56
Table 15.5.7-2	Quantity of Bent Foundation	15-58

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJEC IN VIET NAM
FINAL REPORT

Table 15.5.7-3	Japan Norm of Driven and pulling cost of H beam pile	15-59
Table 15.5.7-4	Japan Norm of foundation installation and removal.....	15-59
Table 15.5.7-5	Japan Norm of Installation and removal of bent equipment.....	15-60
Table 15.5.7-6	Capacity of 150t Crawler Crane	15-61
Table 15.5.5-7	Japan Norm of Rail Equipment installation and Removal (Per 100m)	15-61
Table 15.5.7-8	Japan Norm of Field preassembling of erection girder.....	15-63
Table 15.5.7-9	Weight of main girder.....	15-63
Table 15.5.7-10	Attached structure.....	15-63
Table 15.5.7-11	Product Cost of No.1, No.2 Erection Girder (Quotation)	15-64
Table 15.5.7-12	Product Cost of No.3 Erection Girder (Quotation).....	15-64
Table 15.5.7-13	Japan Norm of Movement and installation of a SBS girder (per one time)	15-65
Table 15.5.7-14	Compound hire of a gantry crane with a leg width of 30 m	15-67
Table 15.5.7-15	Japan Norm of Segment connection.....	15-68
Table 15.5.7-16	Japan Norm of PC steel bar fixation.....	15-68
Table 15.5.7-17	Japan Norm of PC steel bar strain	15-69
Table 15.5.8-1	Diversion of The Steel Sheet Pile	15-70
Table 15.5.8-2	Diversion Times and Quantity of Steel Sheet Pile.....	15-71
Table 15.5.8-3	Diversion Times of Other Material.....	15-71
Table 16.2.1-1	Comparison of Economic Analysis of the Past Studies and This Study.....	16-1
Table 16.2.2-1	Summary of Project Cases for Evaluation.....	16-3
Table 16.2.2-2	Conditions of Each Section	16-4
Table 16.2.2-3	Traffic Volume Used for Benefit Calculation	16-5
Table 16.2.2-4	Demand of Barge Transport.....	16-6
Table 16.2.3-1	Benefit Items Considered in This Study	16-8
Table 16.2.3-2	Unit Value of VOC	16-8
Table 16.2.3-3	Unit Value of Vessel Operating Cost	16-9
Table 16.2.3-4	Estimation of Freight Opportunity Cost	16-9
Table 16.2.3-5	Unit Value of TTC	16-10
Table 16.2.3-6	Summary of Project Benefit	16-11
Table 16.2.4-2	Annual Requirement of Economic Project Cost (First Stage).....	16-12
Table 16.2.4-3	Result of Economic Evaluation	16-13
Table 16.2.4-4	Summary of Sensitivity Analysis.....	16-14
Table 16.2.4-5	Result of Lower Container Scenario.....	16-14
Table 16.3.2-1	Proposed Operation Indicators and Benchmarks.....	16-16
Table 17.3.3-1	Implementation Milestone.....	17-3
Table 17.4.2-1	Alternatives in Procurement Plan and Construction Cost	17-5
Table 17.4.3-1	Evaluation Criteria of Alternative Study and Maximum Scores	17-8
Table 17.4.3-2	Comparison of Alternatives in Construction Packaging Plan.....	17-10

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJEC IN VIET NAM
FINAL REPORT

Table 18.1.1-1	Outline of Stage Construction	18-1
----------------	-------------------------------------	------

List of Figures

Figure 1.1.3-1	Study Area.....	1-3
Figure 1.2.2-1	Overall Study Schedule (Original).....	1-6
Figure 1.2.2-2	Overall Study Schedule (Actual)	1-6
Figure 1.2.2-3	Work Schedule of Design Study of Road/Bridge Portion for Lach Huyen Port Infrastructure Construction (Original).....	1-7
Figure 2.1.5-1	Specifications for a Grade IV control point	2-4
Figure 3.1-1	Geotechnical Investigation Area	3-1
Figure 3.3.1-1	Soil Profile of Approach Road Area in Hai An side (1/2).....	3-5
Figure 3.3.1-2	Soil Profile of Approach Road Area in Hai An side (2/2).....	3-6
Figure 3.3.3-1	Chart of Soil Parameters (Hai An side).....	3-9
Figure 3.3.3-2	Determination Method of C and ϕ using $(\sigma_{1f}+\sigma_3)/2$ and $(\sigma_{1f}-\sigma_3)$	3-10
Figure 3.3.3-3	Shear Strength of Clay for Short Term Stability (Hai An side).....	3-12
Figure 3.3.3-4	Shear Strength of Clay for Long Term Stability (Hai An side).....	3-13
Figure 3.3.3-5	Relationship between Cc and W_L (Hai An side)	3-14
Figure 3.3.3-6	$e\sim\log P$ Curve and $\log P\sim\log C_v$ Curve (Hai An side)	3-15
Figure 3.4.1-1	Soil Profile of Bridge Area (1/2).....	3-19
Figure 3.4.1-2	Soil Profile of Bridge Area (2/2).....	3-20
Figure 3.4.3-1	Chart of Soil Parameters (Bridge Area)	3-23
Figure 3.4.3-2	Shear Strength of Clay for Short Term Stability (Bridge Area)	3-25
Figure 3.4.3-3	Relationship between Cc and W_L (Bridge Area).....	3-26
Figure 3.4.3-4	$e\sim\log P$ Curve and $\log P\sim\log C_v$ Curve (Bridge Area)-1/2.....	3-27
Figure 3.4.3-5	$c\sim\log P$ Curve and $\log P\sim\log C_v$ Curve (Bridge Area)-2/2.....	3-28
Figure 3.4.4-1	Relationship between Unconfined Strength and Bulk Density (Bridge Area).....	3-29
Figure 3.4.4-2	Relationship between Unconfined Strength and Absorption (Bridge Area)	3-30
Figure 3.5.1-1	Soil Profile of Approach Road Area in Cat Hai side (1/2).....	3-34
Figure 3.5.1-2	Soil Profile of Approach Road Area in Cat Hai side (2/2).....	3-35
Figure 3.5.2-1	N-value of Each Layer (Cat Hai side).....	3-36
Figure 3.5.3-1	Chart of Soil Parameters (Cat Hai side).....	3-38
Figure 3.5.3-2	Determination Method of C and ϕ using $(\sigma_{1f}+\sigma_3)/2$ and $(\sigma_{1f}-\sigma_3)$	3-40
Figure 3.5.3-3	Shear Strength of Clay for Short Term Stability (Cat Hai side)-1/2	3-42
Figure 3.5.3-4	Shear Strength of Clay for Short Term Stability (Cat Hai side)-2/2	3-43
Figure 3.5.3-5	Shear Strength of Clay for Long Term Stability (Cat Hai side)-1/2.....	3-44
Figure 3.5.3-6	Shear Strength of Clay for Long Term Stability (Cat Hai side)-2/2.....	3-45
Figure 3.5.3-7	Relationship between Cc and W_L (Cat Hai side)	3-46
Figure 3.5.3-8	$e\sim\log P$ Curve and $\log P\sim\log C_v$ Curve (Cat Hai side)-1/2	3-47

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJEC IN VIET NAM
FINAL REPORT

Figure 3.5.3-9	e~logP Curve and logP~logCv Curve (Cat Hai side)-2/2	3-48
Figure 4.4.2-1	Location of Borrow Pits	4-8
Figure 4.4.3-1	Location of Sand Resources for Embankment	4-11
Figure 4.4.5-1	Location of Rock Quarries	4-16
Figure 5.1.1-1	Plan of DVIZ	5-2
Figure 5.1.1-2	Plan of NDVIZ	5-3
Figure 5.1.1-3	Photo at Zone-2 (Land development work not started yct)	5-5
Figure 5.1.1-4	Crossing Roads	5-6
Figure 5.1.1-5	Cross Section of IZ Internal Roads	5-6
Figure 6.5.2-1	Future Road Network in 2030	6-9
Figure 6.6-1	Peak Hour & Daily PCU & Vehicle Trips for Project Road for 2015	6-14
Figure 6.6-2	Peak Hour & Daily PCU & Vehicle Trips for Project Road for 2020	6-15
Figure 6.6-3	Peak Hour & Daily PCU & Vehicle Trips for Project Road for 2030	6-16
Figure 6.6-4	Peak Hour & Daily PCU & Vehicle Trips for Project Road for 2035	6-17
Figure 6.6-5	Peak Hour Turning Movement Traffic Flows at Tan Vu Interchange (2015-2030) ...	6-19
Figure 6.6-6	Peak Hour Turning Movement Traffic Flows at Intersection#1 (2015-2030)	6-20
Figure 7.1.2-1	Cross Section (Phase-1)	7-3
Figure 7.1.2-2	Cross Section (Phase-2)	7-3
Figure 7.1.2-3	Concept of lane shift	7-4
Figure 7.1.2-4	Details of transition section	7-4
Figure 7.1.3-1	Alternatives for comparison	7-7
Figure 7.1.3-2	Slope protection at fish pond section	7-8
Figure 7.1.3-3	Slope protection at Residential area and salt field in Cat Hai	7-9
Figure 7.1.3-4	Slope protection at sea and dike relocation section	7-9
Figure 7.1.3-6	Typical cross section	7-10
Figure 7.1.4-1	Concept for land acquisition area and ROW	7-11
Figure 7.1.5-1	Plan and Photo at Thon Trung Village, Dong Bai Commune	7-12
Figure 7.1.6-1	General Layout of Underpass Box Culvert (4.0x3.2)	7-17
Figure 7.1.6-2	Typical Cross Section of Frontage Road	7-18
Figure 7.1.6-3	Photos in Hai An district	7-18
Figure 7.1.6-4	Plan and photo at Km10+4147-19	
Figure 7.1.6-5	Plan and photo at Km13+600	7-19
Figure 7.1.6-6	Pavement structure of frontage road	7-19
Figure 7.1.6-7	Plan and Photo of Intersection at Km11+520	7-21
Figure 7.1.6-8	Plan and Photos of Intersection and Relocated Road at Km15+576	7-22
Figure 7.2-1	Pavement Structure	7-25
Figure 7.3.1-2	Alternative Interchange/Intersection types	7-45

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJCT IN VIET NAM
FINAL REPORT

Figure 7.3.1-3	Traffic Demand Forecast for Tan Vu IC in 2020.....	7-51
Figure 7.3.1-4	Summary of Right Turn Ramp Dcsign	7-53
Figure 7.3.1-5	Length of Left Turn Storage Lane.....	7-54
Figure 7.3.1-6	Storage Lane and Deceleration lane for Left Turn Lane.....	7-55
Figure 7.3.1-7	Radius of Each Turning Path	7-56
Figure 7.3.1-8	Plan and Typical Cross Section.....	7-57
Figure 7.3.1-9	Road Sign Plan.....	7-58
Figure 7.3.1-10	No.1 Intersection Proposed in Dinh Vu - Cat Hai Economic Zone Master Plan ..	7-59
Figure 7.3.1-11	Alternative Intersection types	7-59
Figure 7.3.1-12	Geometric Elements.....	7-63
Figure 7.3.1-13	Plan of Local Intersection at Km11+520	7-66
Figure 7.3.1-14	Plan of Local Intersection at Km11+576	7-67
Figure 7.4.1-1	Envisioned Status of Hai An Section (Phase-1 construction is completed).....	7-68
Figure 7.4.1-2	Envisioned Status of Hai An Section (Future stage).....	7-68
Figure 7.4.1-3	Typical Drainage System	7-69
Figure 7.4.1-4	Side Ditch.....	7-70
Figure 7.4.1-5	Median Ditch	7-71
Figure 7.4.1-6	Drainage Pipe (D=0.75).....	7-72
Figure 7.4.1-7	Catch Basin Type A1.....	7-72
Figure 7.4.1-8	Catch Basin Type B1.....	7-72
Figure 7.4.1-9	Outlet Type A , B , C	7-73
Figure 7.4.2-1	Navigation Area at Km15+100	7-74
Figure 7.4.2-2	Photo of Existing Channel (From Km 13+400 to west)	7-77
Figure 7.4.2-3	Details of relocation channel.....	7-77
Figure 7.5.1-1	Traffic Load Calculation Diagram	7-79
Figure 7.5.1-2	Traffic Load Value and Distribution	7-80
Figure 7.5.2-1	Exemplary Analysis of Excess Pore Pressure and Settlement	7-81
Figure 7.5.2-2	Arrangement and design concept of SCP.....	7-83
Figure 7.6.1-1	Construction procedure of box culvert.....	7-95
Figure 7.6.1-2	Size of Drainage/Irrigation box culvert.....	7-97
Figure 7.6.1-3	Size of Drainage/Irrigation pipe culvert.....	7-97
Figure 7.6.1-4	Minimum concrete cover for box culvert.....	7-98
Figure 7.6.1-5	Cost comparison for retaining wall between SAPROF and D/D	7-99
Figure 7.6.1-6	Details of Concrete Sheet Pile Wall	7-101
Figure 7.6.1-7	Details of piled slab at Cam River Bridge.....	7-102
Figure 7.6.1-8	Details of piled slab at Approach Bridge	7-103
Figure 7.7.1-1	Installation of guardrail (cross section).....	7-104
Figure 7.7.1-2	Guardrail layout	7-104
Figure 7.7.2-1	Details of guard post	7-105
Figure 7.7.3-1	Details of concrete curb	7-105
Figure 7.7.4-1	Details of delincator	7-105

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJCT IN VIET NAM
FINAL REPORT

Figure 7.7.5-1	Details of traffic signs	7-106
Figure 8.1.1-1	Width Composition of Superstructure.....	8-1
Figure 8.1.3-1	Conditions of Live Load	8-4
Figure 8.1.3-2	Response Spectrum	8-9
Figure 8.1.6-1	Soil Profile	8-14
Figure 8.1.6-2	Definition sketch for scour components for a complex pier	8-16
Figure 8.1.6-3	Suspended pier scour ratio.	8-17
Figure 8.1.6-4	Common pier shapes.....	8-18
Figure 8.1.6-5	Pile cap equivalent width	8-19
Figure 8.1.6-6	Pile spacing factor	8-19
Figure 8.1.6-7	Adjustment factor for number of aligned rows	8-19
Figure 8.2.1-1	Navigation Clearance.....	8-23
Figure 8.2.1-2	Span Length determined from Navigation Clearance	8-23
Figure 8.2.3-1	Location of Interchange and Intersections	8-28
Figure 8.2.3-2	Typical Cross Section of Dinh Vu Ring Road.....	8-29
Figure 8.3.1-1	Cross Section of Main Bridge at Pier (Second Stage)	8-36
Figure 8.3.2-1	Erection of Main Girder with Form traveler.....	8-40
Figure 8.3.3-1	Cross Section for Main Girder of the Initial Stage.....	8-42
Figure 8.3.3-2	Cross Section for Main Girder for the Second Stage.....	8-42
Figure 8.3.3-3	Cantilever Segments and Pier Head.....	8-43
Figure 8.3.3-4	Cast-in-place Segments on False Work.....	8-43
Figure 8.3.3-5	Arrangement of Longitudinal Cantilever Tendons.....	8-44
Figure 8.3.4-1	Skelton of V-shaped Piers	8-45
Figure 8.3.4-2	Projected Pier (2.650m) above Mean High Water Level and Mean Low Water Level.....	8-50
Figure 8.3.4-3	Projected Pier (1.050m) above High Water Level and Mean Low Water Level.....	8-51
Figure 8.3.4-4	Corner Arrangement of V-shaped Wall Pier.....	8-52
Figure 8.3.4-5	Vertical Slit for Aesthetical Aspect	8-52
Figure 8.3.4-6	Span Arrangement and Profile of Main Bridge.....	8-53
Figure 8.3.4-7	Deformation and Moment due to Creep and Shrinkage.....	8-53
Figure 8.3.4-8	Longitudinal Displacement* due to Creep and Shrinkage.....	8-54
Figure 8.3.4-9	Shear Force* due to Creep and Shrinkage	8-54
Figure 8.3.4-10	Bending Moment* due to Creep and Shrinkage	8-54
Figure 8.3.4-11	Stress* of Top Fiber due to Creep and Shrinkage	8-56
Figure 8.3.4-12	Stress* of Bottom Fiber due to Creep and Shrinkage	8-56
Figure 8.3.4-13	Deformation and Moment due to Pressurization (Jacking Force).....	8-57
Figure 8.3.4-14	Procedures of Pressurization Method by Jacking Force	8-58
Figure 8.3.4-15	Structure of Pressurization by Jacks	8-59
Figure 8.3.4-16	Longitudinal Displacement due to Pressurization.....	8-60
Figure 8.3.5-1	Conceptual View of Steel Sheet Pile Foundation.....	8-66

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJCT IN VIET NAM
FINAL REPORT

Figure 8.3.5-2 Design Flow for basic design of steel pipe sheet pile foundation	8-67
Figure 8.3.5-3 The procedure for construction method of steel pipe sheet pile foundations (1)	8-68
Figure 8.3.5-4 The procedure for construction method of steel pipe sheet pile foundations (2)	8-69
Figure 8.3.5-5 The procedure for construction method of steel pipe sheet pile foundation	8-69
Figure 8.3.5-6 P76 Foundation with Boring No BP- 77 & BP-78.....	8-70
Figure 8.3.5-7 Region where the skin friction force at the inter peripheral surface of the well portion of the foundation should be taken into account.....	8-72
Figure 8.3.5-8 Calculation Model of Steel Pipe Sheet Pile Foundation	8-74
Figure 8.3.5-9 Slippage displacement of Joint Accompanying Shear Deformation of Imaginary Well	8-75
Figure 8.3.5-10 Steel pile sheet pile Foundation	8-75
Figure 8.3.5-11 Calculation Model of Imaginary well	8-76
Figure 8.3.5-12 Shape of SPSP Foundation.....	8-77
Figure 8.3.5-13 Combined stress for steel pipe sheet pile foundation.....	8-81
Figure 8.3.5-14 Section Calculation Model of Top Slab	8-82
Figure 8.3.6-1 Profile of Main Bridge	8-85
Figure 8.3.6-2 Arrangement of PC Tendons	8-87
Figure 8.3.6-3 Model for Structural Analysis	8-88
Figure 8.3.6-4 Models corresponding to Construction Sequence (1)	8-90
Figure 8.3.6-5 Models corresponding to Construction Sequence (2)	8-91
Figure 8.3.6-6 Models corresponding to Construction Sequence (3)	8-92
Figure 8.3.6-7 Sectional Forces	8-93
Figure 8.3.6-8 Fiber Stress.....	8-94
Figure 8.3.6-9 Sections for Transversal Analysis	8-96
Figure 8.3.6-10 Model for Transversal Analysis	8-97
Figure 8.3.6-11 Design Truck and Lane Loading for Transversal Analysis	8-98
Figure 8.3.6-12 Stress in Service Limit State (LL1L)	8-99
Figure 8.3.6-13 Bending Moment Diagram in Strength Limit State	8-100
Figure 8.3.6-14 Arrangement of PC Tendons	8-102
Figure 8.3.6-15 Sectional Forces in Service Limit State	8-103
Figure 8.3.6-16 Sectional Forces in Strength Limit State.....	8-103
Figure 8.3.6-17 Sectional Forces in Extreme Event Limit State	8-104
Figure 8.3.6-18 Fiber Stress (Service Limit State)	8-104
Figure 8.3.6-19 Fiber Stress (Strength Limit State).....	8-105
Figure 8.3.6-20 Fiber Stress (Extreme Event Limit State)	8-105
Figure 8.3.6-21 Reinforcement of V-shaped Wall	8-106
Figure 8.3.6-22 Relationships between resistance capacity and sectional force in Pier Members.....	8-106
Figure 8.3.6-23 Reinforcement of Lower Pier Column and Pile Cap.....	8-107
Figure 8.3.6-24 Relationships between resistance capacity	

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJEC IN VIET NAM
FINAL REPORT

and sectional force in Pier Members.....	8-107
Figure 8.3.6-25 Major Dimension and Materials used for SPSP Foundation for P76~P78	8-108
Figure 8.3.6-26 Plan of Construction Step	8-109
Figure 8.3.6-27 Stress Diagram of SPSP for P76	8-110
Figure 8.3.6-28 Calculation results of Steel Pipe Sheet Pile for P7.....	8-111
Figure 8.3.6-29 Detail of connection between Top Slab and SPSP.....	8-114
Figure 8.4.1-1 Analysis Model	8-131
Figure 8.4.1-2 Process and the schedule of the structure analysis.....	8-133
Figure 8.4.1-3 Arrangement of External PC Tendon	8-134
Figure 8.4.1-4 Stress of Top Fiber (Dead Load).....	8-136
Figure 8.4.1-5 Stress of Bottom Fiber (Dead Load).....	8-136
Figure 8.4.1-6 Stress of Top Fiber (Service Limit State).....	8-136
Figure 8.4.1-7 Stress of Bottom Fiber (Service Limit State).....	8-136
Figure 8.4.1-8 Bending Moment of Main Girder (Strength Limit State).....	8-137
Figure 8.4.1-9 Diagonal tensile stress.....	8-137
Figure 8.4.1-10 Maximum Shear stress.....	8-137
Figure 8.4.1-11 Stress of Top Fiber (Dead Load).....	8-139
Figure 8.4.1-12 Stress of Bottom Fiber (Dead Load).....	8-139
Figure 8.4.1-13 Stress of Top Fiber (Service Limit State).....	8-139
Figure 8.4.1-14 Stress of Bottom Fiber (Service Limit State).....	8-139
Figure 8.4.1-15 Bending Moment of Main Girder (Strength Limit State).....	8-140
Figure 8.4.1-16 Diagonal tensile stress.....	8-140
Figure 8.4.1-17 Maximum Shear stress.....	8-141
Figure 8.4.1-18 Stress of Top Fiber (Dead Load).....	8-142
Figure 8.4.1-19 Stress of Bottom Fiber (Dead Load).....	8-142
Figure 8.4.1-20 Stress of Top Fiber (Service Limit State).....	8-142
Figure 8.4.1-21 Stress of Bottom Fiber (Service Limit State).....	8-142
Figure 8.4.1-22 Bending Moment of Main Girder (Strength Limit State).....	8-143
Figure 8.4.1-23 Diagonal tensile stress.....	8-143
Figure 8.4.1-24 Maximum Shear stress.....	8-143
Figure 8.4.1-25 Stress of Top Fiber (Dead Load).....	8-145
Figure 8.4.1-26 Stress of Bottom Fiber (Dead Load).....	8-145
Figure 8.4.1-27 Stress of Top Fiber (Service Limit State).....	8-145
Figure 8.4.1-28 Stress of Bottom Fiber (Service Limit State).....	8-145
Figure 8.4.1-29 Bending Moment of Main Girder (Strength Limit State).....	8-146
Figure 8.4.1-30 Diagonal tensile stress.....	8-146
Figure 8.4.1-31 Maximum Shear stress.....	8-146
Figure 8.4.1-32 General Section for Arrangement of Transversal PC Tendon (ctc500).....	8-149
Figure 8.4.1-33 Arrangement of Transversal PC Tendon (intermediate support cross section) ctc500mm	8-155
Figure 8.4.1-34 Necessary thickness for anchorage of PC Tendon	8-164

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJCT IN VIET NAM
FINAL REPORT

Figure 8.4.1-35 Segment length-section area	8-166
Figure 8.4.1-36 Segment arrangement.....	8-167
Figure 8.4.1-37 Analysis Model	8-171
Figure 8.4.1-38 Process and the schedule of the structure analysis.....	8-173
Figure 8.4.1-39 Arrangement of PC Tendon.....	8-174
Figure 8.4.1-40 Bending Moment in all Dead load state.....	8-175
Figure 8.4.1-41 Bending Moment in Service load state	8-175
Figure 8.4.1-42 Stress of Top Fiber (Dead Load).....	8-175
Figure 8.4.1-43 Stress of Top Fiber (Dead Load).....	8-175
Figure 8.4.1-44 Stress of Bottom Fiber (Dead Load)	8-175
Figure 8.4.1-45 Stress of Top Fiber (Service Limit State).....	8-176
Figure 8.4.1-46 Stress of Bottom Fiber (Service Limit State).....	8-176
Figure 8.4.1-47 Bending Moment of Main Girder (Strength Limit State).....	8-176
Figure 8.4.1-48 Diagonal tensile stress.....	8-177
Figure 8.4.1-49 Maximum Shear stress.....	8-177
Figure 8.4.1-50 Bending Moment caused by Dead Load	8-178
Figure 8.4.1-51 Bending Moment in Service	8-178
Figure 8.4.1-52 Stress of Top Fiber (Dead Load).....	8-178
Figure 8.4.1-53 Stress of Bottom Fiber (Dead Load)	8-178
Figure 8.4.1-54 Stress of Top Fiber (Service Limit State).....	8-179
Figure 8.4.1-55 Stress of Bottom Fiber (Service Limit State).....	8-179
Figure 8.4.1-56 Bending Moment of Main Girder (Strength Limit State).....	8-179
Figure 8.4.1-57 Diagonal tensile stress.....	8-180
Figure 8.4.1-58 Maximum Shear stress.....	8-180
Figure 8.4.1-59 General Section for Arrangement of Transversal PC Tendon (ctc550).....	8-183
Figure 8.4.1-60 Arrangement of Transversal PC Tendon (intermediate support cross section) ctc500mm	8-187
Figure 8.4.2-1 Flowchart of Designing Cross beam.....	8-191
Figure 8.4.2-2 End cross beam A1 in FEM mesh.....	8-191
Figure 8.4.2-3 Restraint Condition of End cross beam A1	8-192
Figure 8.4.2-4 Loading Condition in FEM [A1]	8-192
Figure 8.4.2-5 Cross beam P1 [Model-1] in FEM mesh	8-193
Figure 8.4.2-6 Restraint Condition of P1 [Model-1]	8-193
Figure 8.4.2-7 Load Condition in P1 [Model-1].....	8-193
Figure 8.4.2-8 Cross beam P1 [Model-2] in FEM mesh	8-194
Figure 8.4.2-9 Restraint Condition of P1 [Model-2]	8-194
Figure 8.4.2-10 Load Condition in FEM [A1].....	8-195
Figure 8.4.3-1 Flowchart of Designing Deviator.....	8-202
Figure 8.4.3-2 Number of deviators.....	8-202
Figure 8.4.3-3 Deviator Examination in FEM mesh	8-203
Figure 8.4.3-4 Analysis model for calculation of Stress on longitudinal	

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJCT IN VIET NAM
FINAL REPORT

and transverse direction	8-204
Figure 8.4.3-5 The component force of external cable in FEM analysis.....	8-205
Figure 8.4.3-6 The study result and the amount of reinforcing bar of deviator component force	8-206
Figure 8.4.3-7 FEM mesh for examination of bottom slab.....	8-208
Figure 8.4.3-8 Result of FEM analysis in Lower side of bottom slab	8-208
Figure 8.4.3-9 FEM mesh for examination of bottom slab.....	8-210
Figure 8.4.3-10 Result of FEM analysis in Upper side of bottom slab	8-210
Figure 8.4.3-11 FEM mesh for examination of deviator	8-212
Figure 8.4.3-12 Result of FEM analysis in Upper side of deviator	8-212
Figure 8.4.3-13 Joint Filler	8-214
Figure 8.4.3-14 Sectional view of Beam	8-217
Figure 8.4.3-15 Arrangement of reinforcement at beam.....	8-217
Figure 8.4.4-1 Plan Layout for Approach Bridge and Main Bridge	8-220
Figure 8.4.4-2 Plan Layout for Approach Bridge and Main Bridge	8-222
Figure 8.4.4-3 Variations for Pile Cap Elevation.....	8-223
Figure 8.4.4-4 Design of pile foundations for downdrag	8-228
Figure 8.4.4-5 Standard Sections of a SL piles.....	8-229
Figure 8.4.4-6 Downdrag load and the range of SL pile.....	8-230
Figure 8.4.4-7 Grouping for Foundation Study	8-231
Figure 8.4.5-1 Pile Cap Elevation of Variations 2	8-232
Figure 8.4.5-2 Pile Cap Elevation of Variation 2 or 3	8-235
Figure 8.4.5-3 Pile Cap Elevation of Variation 4.....	8-237
Figure 8.4.5-4 Construction Plan of Alternative-4	8-238
Figure 8.4.6-1 Blockout at A1 abutment.....	8-241
Figure 8.4.6-2 Blockout at A2 abutment.....	8-241
Figure 8.4.6-3 Arrangement of Reinforcement at Abutment	8-242
Figure 8.4.6-4 Pile arrangement for Pier	8-254
Figure 8.4.6-5 Pile arrangement for Abutment.....	8-254
Figure 8.4.6-6 Steel Pipe Pile D=800mm (A2 abutment).....	8-255
Figure 8.4.6-7 Steel Pipe Pile D=1100mm (P8,P9,P53).....	8-256
Figure 8.4.6-8 Pile Arrangement	8-257
Figure 8.5.1-1 Cam River Box Culvert	8-259
Figure 8.5.2-1 Topographic Profile of Cam River (Km 1+700).....	8-260
Figure 8.5.2-2 Soil Profile adjacent to Cam River (Km 1+700).....	8-261
Figure 8.5.2-3 General view of Cam River Bridge.....	8-264
Figure 8.5.3-1 Girder Arrangement	8-265
Figure 8.5.3-2 Arrangement of PC Tendons	8-266
Figure 8.5.3-3 Reinforcement for Web of Girders.....	8-267
Figure 8.5.3-4 Reinforcement for Flange of Girders	8-268
Figure 8.5.3-5 Reinforcement for Cross Beam of Girders.....	8-268

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJEC IN VIET NAM
FINAL REPORT

Figure 8.5.4-1 Dimensions of Abutment	8-269
Figure 8.5.4-2 Dimensions of Pier.....	8-270
Figure 8.5.4-3 Reinforcement of Pier.....	8-271
Figure 8.5.4-4 Reinforcement of Abutment.....	8-272
Figure 8.6.1-1 Location for installation of Bearings in Main Bridge	8-273
Figure 8.6.1-2 Dimensions of Pot Bearings.....	8-276
Figure 8.6.1-3 Flow of Bearing Design.....	8-277
Figure 8.6.1-4 Dimension of End support bearing	8-285
Figure 8.6.1-5 Dimension of middle support bearing.....	8-285
Figure 8.6.1-6 Dimension of middle support bearing.....	8-294
Figure 8.6.2-1 Expansion Joint between Main Bridge and Approach Bridge	8-298
Figure 8.6.2-2 Movement of girder end.....	8-299
Figure 8.6.2-3 Movement of girder end.....	8-301
Figure 8.6.2-4 Expansion Joint on Approach Bridge.....	8-303
Figure 8.6.3-1 Expansion Joint on Approach Bridge.....	8-306
Figure 9.7-1 TYPICAL LIGHTING POLE & HIGH MAST.....	9-13
Figure 9.7-2 LIGHTING POLE MATERIAL	9-14
Figure 9.7-3 STREET LUMINAIRE.....	9-15
Figure 9.7-4 LIGHTING TRANSFORMER STATION.....	9-16
Figure 9.7-5 NAVIGATION LIGHT	9-17
Figure 9.7-6 17M HIGH MAST.....	9-18
Figure 9.7-7 25M HIGH MAST	9-19
Figure 10.2.3-1 Plan for Entrance Access Road and Site compound No1 and No2.....	10-8
Figure 10.2.3-2 Plan of Access Road Bridge km 1.7 (near Cam River).....	10-8
Figure 10.2.3-3 Plan View of Site Access Roads.....	10-9
Figure 10.2.3-4 Typical Cross Sections of Site Access Roads	10-9
Figure 10.2.3-5 Dredging Area and Dumping Area.....	10-10
Figure 10.2.3-6 Temporary Jetty.....	10-10
Figure 10.4.1-1 Road Work Procedure	10-15
Figure 10.5.2-1 Approach Bridge (SBS Method) Working Sequence.....	10-17
Figure 10.5.3-1 Construction sequence for Approach Bridge sub structure	10-18
Figure 10.5.4-1 PC segment fabrication sequence	10-23
Figure 10.5.4-2 Segment Fabrication Cycle Time	10-24
Figure 10.5.4-3 Geometry control outline	10-25
Figure 10.5.4-4 Segment fabrication and installation program showing stockpile number	10-26
Figure 10.5.5-1 Segment Erection Work Cycle Time	10-29
Figure 10.5.6-1 Pier Head Temporary Shoe Detail.....	10-30
Figure 10.5.6-2 A2-P79 Cantilever Method Working Program.....	10-31
Figure 10.6.1-1 Construction sequence	10-32

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJEC IN VIET NAM
FINAL REPORT

Figure 10.6.2-1	Main Bridge Overall Program.....	10-33
Figure 10.6.2-2	Main Bridge Foundation Work Program.....	10-33
Figure 10.6.2-3	Main Bridge Pile Cap Work Program	10-33
Figure 10.6.2-4	Main Bridge Pier Construction Program	10-34
Figure 10.6.2-5	Main Bridge Pier Head Construction Program	10-34
Figure 10.6.2-6	Main Bridge Girder Construction Program.....	10-34
Figure 10.6.4-1	Working sequence of Pier head construction	10-37
Figure 10.6.5-1	Construction sequence of Main bridge girder	10-38
Figure 10.6.5-2	Main Girder Construction Cycle Time.....	10-39
Figure 10.7.4-1	Network Program.....	10-49
Figure 10.7.5-1	Work Days Calculation for Pier 30 Substructure Works.....	10-50
Figure 10.7.5-2	Work Days Calculation Sheet for Pier 75	10-51
Figure 10.7.5-3	Time Calculation for Pier 77 Works.....	10-52
Figure 10.7.5-4	Time Calculation for Road Pavement Works.....	10-53
Figure 11.1.3-1	Example of Safety Organization Chart	11-2
Figure 11.1.4-1	Emergency Communication Network.....	11-8
Figure 12.2.3-1	Planned wall in front of the Van Co Huong Temple/Pagoda	12-17
Figure 12.2.3-2	Planned underpass at Km10+420 and the frontage road.....	12-18
Figure 12.2.3-3	Planned underpass at Km13+600 and the frontage road.....	12-18
Figure 12.2.3-4	Planned intersection at Km11+520	12-19
Figure 12.2.3-5	Planned intersection at Km15+576	12-19
Figure 12.2.4-1	Location of air quality and noise survey carried by CASST in August 2008.....	12-25
Figure 12.2.5-1	Location of the additional site for surface water quality survey	12-36
Figure 12.2.9-1	Map of sites of survey on ecosystem carried out by the Study Team (Port Portion).....	12-40
Figure 12.2.9-2	Primary Nurseries in Coastal Water	12-41
Figure 12.3.2-1	Proposed Organization Structure for EMP implementation (in construction phase).....	12-43
Figure 12.3.7-1	Locations of sampling sites of ambient air and surface water	12-50
Figure 12.3.8-1	EMP Implementing Schedule	12-53
Figure 14.1.2-1	Assumed Limits of the Operation and Maintenance for Tan Vu - Lach Huyen Highway.....	14-2
Figure 14.1.3-1	Plan for Tan Vu - Lach Huyen Highway	14-3
Figure 14.2.1-1	Organization Chart of MOT.....	14-5
Figure 14.2.1-2	Classifications of Road Maintenance Activities and Investment Projects	14-5
Figure 14.2.1-3	Details of the Activities and the Responsible Organization at Each Stage on Road Maintenance.....	14-6
Figure 14.2.1-4	Organization Chart of DRVN.....	14-7
Figure 14.4.1-1	Road Operator of Trunk Roads in Hai Phong City	14-39

THE DETAILED DESIGN STUDY FOR LACH HUYEN PORT INFRASTRUCTURE CONSTRUCTION PROJEC IN VIET NAM
FINAL REPORT

Figure 14.4.1-2	Possible of the Management Organization	14-40
Figure 14.4.2-1	Proposed Organization Chart of RRMC	14-42
Figure 15.5.1-1	Layout of Maintenance and Protection of Traffic	15-23
Figure 15.5.5-2	Quantity of Rail Foundation of Gantry Crane (7.5t).....	15-31
Figure 15.5.5-3	Shed Rail foundation.....	15-32
Figure 15.5.5-4	Quantity of Shed Rail Foundation	15-32
Figure 15.5.5-5	Short Line Equipment Foundation Side View.....	15-33
Figure 15.5.5-6	Short Line Equipment Foundation Front View	15-33
Figure 15.5.5-7	Soil Stabilization of Segment Fabrication Yard	15-34
Figure 15.5.5-8	Foundation of Segment Stockyard.....	15-34
Figure 15.5.5-9	Pavement of Segment Stockyard	15-35
Figure 15.5.5-10	Tower crane (180 t-m).....	15-38
Figure 15.5.5-11	Movable Shed.....	15-39
Figure 15.5.5-12	Curing Program.....	15-40
Figure 15.5.5-13	Japan Norm of Support Installation and Removal (per 10m)	15-41
Figure 15.5.7-1	RNo.1, 2 Erection Girder Installation	15-57
Figure 15.5.7-2	Quantity of Bent Foundation.....	15-58
Figure 15.5.7-3	Erection Girder	15-61
Figure 15.5.7-4	Construction days of Installation and Demolition	15-62
Figure 15.5.7-5	Erection of No.3 girder	15-62
Figure 15.5.7-6	Segment transshipment gantry crane 80t	15-66
Figure 15.5.7-7	Adhesives coating of Joint	15-67
Figure 16.2.2-1	Comparison of Passenger Transport PCU.....	16-6
Figure 17.3.3-1	Estimated Implementation Program.....	17-3
Figure 17.4.2-1	Alternatives on Construction Packaging Plan.....	17-5
Figure 18.1.2-1	Future Lane Requirement in JICA's Preparatory Survey	18-1
Figure 18.2.1-1	Typical Cross Section of Road Section	18-2
Figure 18.3.1-1	Cross Section at Abutment.....	18-3
Figure 18.3.2-1	Plan View of Approach Bridge	18-3
Figure 18.3.2-2	General View of Approach Bridge with Second Stage	18-4
Figure 18.3.3-1	Plan View of Main Bridge.....	18-5
Figure 18.3.3-2	Cross Section at Pier P77 of Main Bridge including	18-5
Figure 18.3.3-3	Cross Section for Main Girder for the Second Stage	18-6
Figure 18.4.1-1	Signalized At-grade Intersection	18-6
Figure 18.4.2-1	Separate-grade Interchange.....	18-7


8.5 Design of Cam River Bridge

8.5.1 Background


Tan Vu – Lach Huyen Highway is crossing Cam River at Km 1+700 and a box culvert with 8 cells, 8 x (4m x 4m), was planned, which is approved by 3139/QD-BGTVT dated 29th of October, 2010. The plan view and crosssection of box culvert is shown in the figure below.

On 5th of August, 2011, a meeting was held between Hai Phong PC and JICA Study Team, chaired by Mr Le Van Thanh, Vice Chairman, and concluded that the box culvert would be replaced by a bridge as stated in Notice No.242-TB/UBND dated 8th of August, 2011.

In accordance with the conclusion, a study was conducted to select an appropriate bridge type for crossing Cam River.



(b) Plan View



(b) Crosssection

Source: Study Team

Figure 8.5.1-1 Cam River Box Culvert

8.5.2 General Plan and Site Conditions of Cam River Bridge

In this chapter, appropriate general plan of the bridge is determined based on topographic hydrological conditions.

(1) Topographic Conditions

The figure below shows the topographic profile of Cam River. The lowest point is GL-2.2 at Km 1+700.




Figure 8.5.2-1 Topographic Profile of Cam River (Km 1+700)

(2) Hydrological Conditions

The hydrological conditions of Cam River at the intersection with Tan Vu – Lach Huyen Highway are summarized as follows;

Table 8.5.2-1 Hydrological Conditions of Cam River

Items	Quantities/ Values	Note
Design Discharge, Q*	176 m ³	Design Frequency, P =: 1%
Design Velocity, V	0.39 m/s	Design Frequency, P = 1%
Necessary Width for Drainage, W	51.35 m	Perpendicular to Flow Direction
Angle between Directions of River and Highway	59 degree	

* Based on Article 2.2.3 “Supplemental Hydrological Survey” in Basic Design Report

(3) Length of Bridge

The length of the bridge is defined based on the necessary width for drainage, W=51.35m, shown in the table above and the skew angle, $\theta=59$ degree, parallel to the river front.

As shown in the plan view below, the bridge length is defined as 69.2m.

(4) Soil Conditions

The ground conditions by D/D study are shown in below illustrations and following tables.

Table 8.5.2-2 Soil Condition at Boring No.BA-13 and BA-14

Layer Name	Soil Type	Average N-Value	Wet Density Above Water Level γ (kN/m ³)	Wet Density Under Water Level γ (kN/m ³)	Shear Strength C (kN/m ²)	Internal Friction ϕ (degree)	Horizontal Spring Constant αE_0 (kN/m ²)
3	Lean Clay	1	17.0	8.0	12.0	-	5600
4	Lean Clay	3	18.0	9.0	42.0	-	19600
6	Sandy Clay	16	19.0	10.0	78.0	-	36400
L6-1	Silty Sand	>50	19.0	10.0	78.0	30.0	36400
7B	Silt	7	18.0	9.0	42.0	-	19600
8	Lean Clay	14	19.0	10.0	84.0	-	39200
9	Clay	6	18.0	9.0	36.0	-	16800
10B	Silty Sand	>50	21.0	12.0	-	40.0	137200

Source: Study Team




Figure 8.5.2-2 Soil Profile adjacent to Cam River (Km 1+700)

(5) Scour Depth

Total scour from superposition of components is given by

$$y_s = y_{s \text{ pier}} + y_{s \text{ pc}} + y_{s \text{ pg}}$$

y_s : Total scour depth, m

$y_{s \text{ pier}}$: Scour component for the pier stem in the flow, m

$y_{s \text{ pc}}$: Scour component for the pier cap of footing in the flow, m

$y_{s \text{ pg}}$: Scour component for the piles exposed to the flow, m

Scour component for the pier stem in the flow is given by

$$y_{s \text{ pier}} = K_{h \text{ pier}} [2.0 K_1 K_2 K_3 K_4 a_{\text{pier}}^{0.65} y_1^{0.35} Fr_1^{0.43}]$$

$$Fr_1 = V_1 / (g \cdot y_1)^{0.5}$$

$K_{h \text{ pier}}$: Coefficient to account for the height of the pier stem above the bed and the shielding effect by the pier cap overhang distance "f" in front of the pier stem

$$K_{h \text{ pier}} = (0.4075 - 0.669 f/a_{\text{pier}}) - (0.4271 - 0.778 f/a_{\text{pier}}) h_1/a_{\text{pier}} + (0.1615 - 0.455 f/a_{\text{pier}})(h_1/a_{\text{pier}})^2 - (0.0269 - 0.012 f/a_{\text{pier}})(h_1/a_{\text{pier}})^3$$

Scour component for the pier cap of footing in the flow is given by

$$y_{s \text{ pc}} = 2.0 K_1 K_2 K_3 K_4 K_w a_{\text{pc}}^*^{0.65} y_2^{0.35} Fr_2^{0.43}$$

$$Fr_2 = V_2 / (g \cdot y_2)^{0.5}$$

Scour component for the piles exposed to the flow is given by

$$y_{s \text{ pg}} = K_{h \text{ pg}} [2.0 K_1 K_2 K_3 K_4 a_{\text{pg}}^*^{0.65} y_3^{0.35} Fr_3^{0.43}]$$

Where:

Δy_{xcb} : Level after scour, m

y_1 : Flow depth directly upstream of the pier, m

K_1 : Correction factor for pier nose shape

K_2 : Correction factor for angle of attack of flow

K_3 : Correction factor for bed condition

K_4 : Correction factor for armoring by bed material size (only with $D_{50} = > 60$ mm)

a : Pier width, m

V_1 : Mean velocity of flow directly upstream of the pier, m/s

K_w : Wide pier factor

K_{sp} : Coefficient for pile spacing

Fr_f : Froude number

$$Fr_f = V_f / (g \cdot y_f)^{0.5}$$

g : Acceleration of gravity (9.81 m/s²)

V_f : average velocity in the flow zone below the top of the footing, m/s

V_2 : average adjusted velocity in the vertical of flow approaching the pier, m/s

K_m : Coefficient for number of aligned rows, m

($K_m = 1$ for skewed or staggered pile group)

The parameters for calculation of the scour depth are shown in the table below.

Table 8.5.2-3 Calculation of Scour Depth

Local pier scour equation (ii)

No.	V _{tr0} (m)	y ₁ (m)	V ₁ (m/s)	Fr ₁	f	a _{pier} (m)	K _{h pier}			HD môi tr trở	K ₁	K ₂		K ₃		K ₄		y _{s pier} (m)		
							h ₀ (m)	h ₁ (m)	K _{h pier}			θ (°)	L (m)	K ₂	§, y s eng	K ₃	D ₅₀ (mm)		D ₈₅ (mm)	K ₄
P1	-2.20	4.70	0.53	0.078	0.70	1.80	-3.03	-1.03	0.661	vu eng	1.1	0	10.00	1.0	b eng ph eng	1.1	0.08	0.35	1.00	1.35
P2	-2.05	4.55	0.52	0.078	0.70	1.80	-3.18	-1.18	0.711	vu eng	1.1	0	10.00	1.0	b eng ph eng	1.1	0.08	0.35	1.00	1.43

Pier stem depth Component (iii)

No.	y ₁ (m)	V ₁ (m/s)	T (m)	h ₂ (mm)	k _s (mm)	y ₂ (m)	V ₂ (m/s)	Fr ₂	a _{pc} (m)	a [*] _{pc} (m)	K ₁		K ₂		K ₃	K ₄	K _w		y _{s pc} (m)	
											HD môi tr ở	K ₁	θ (°)	L (m)			K ₂	D ₅₀ (mm)		K _w
P1	4.70	0.53	2.00	-2.36	0.250	5.37	0.46	0.064	2.05	1.58	vu eng	1.1	0	10.00	1.0	1.1	1.00	0.08	1.00	1.72
P2	4.55	0.52	2.00	-2.47	0.250	5.26	0.45	0.062	2.05	1.83	vu eng	1.1	0	10.00	1.0	1.1	1.00	0.08	1.00	1.85

The total scour depths and the elevations at the piers, P1 and P2 are summarized in the table below.

Table 8.5.2-4 Total Scour Depth


Pier No.	Total Scour Depth y _s (m)	River Bed Elevation after scour (m)
P1	3.06	-5.26
P2	3.27	-5.32

(6) Span Length and Type of Girder

Regarding span component and bridge type, it was judges that 3 spans continuous or simply supported girder is reasonable from technical & economical view points. After comparison on three (3) alternatives as shown in the Discussion paper No.15, PC Hollow slab girder was selected from aesthetic & economical view point. However, according to the site conditions, DRVN and PMU-2 insisted that pre-cast girder shall be adopted. Finally, PC T girder simply supported was adopted and designed. (Concrete volume of PC T girder is less than PC Hollow slab girder, box girder and PC I girder with cast-in-situ deck slab.)

(7) General Plan

The general plan of Cam River Bridge is as shown in the figure below.




Source: Study Team

Figure 8.5.2-3 General view of Cam River Bridge

8.5.3 Design of Superstructure

(1) Girder Arrangement

The girder arrangement is as shown in the figure below.



Source : Study Team

Figure 8.5.3-1 Girder Arrangement

(2) Design conditions


- Bridge Type: Prestressed Concrete Bridge
- Structure Type: PC simply supported T girder
- Length: 3@23.0 = 69m
- Design Speed: 80km/h
- Construction Method: Post tension Pre-cast girder
- Erection Method: Erection girder
- Live Load: 22TCN-272-05 (AASHTO LRFD)
- Width Composition: 15.050m for design

(3) Material to be used (common to main & approach bridge)


See the article 8.1.2 in this report.

(4) Tendon Arrangement

The tendon arrangement in is as shown in the figure below.



(a) Longitudinal PC Tendons



(b) Transversal PC Tendons


Source: Study Team

Figure 8.5.3-2 Arrangement of PC Tendons

(5) Results of Design


Detailed design conditions and calculation is shown in Design Report on Cam River Bridge.

The resultant reinforcement is as shown in the figures below.




Source: Study Team

Figure 8.5.3-3 Reinforcement for Web of Girders



Source: Study Team

Figure 8.5.3-4 Reinforcement for Flange of Girders




Source: Study Team

Figure 8.5.3-5 Reinforcement for Cross Beam of Girders

8.5.4 Design of Substructure


(1) Structure Dimensions

The Dimensions of substructure are as shown in the figure below.



Source : Study Team

Figure 8.5.4-1 Dimensions of Abutment



Source : Study Team

Figure 8.5.4-2 Dimensions of Pier


(2) Material to be used (common to main & approach bridge)

See the article 8.1.2 in this report.

(5) Results of Design


Detailed design conditions and calculation is shown in Design Report on Cam River Bridge.

The resultant reinforcement is as shown in the figures below.



Source: Study Team

Figure 8.5.4-3 Reinforcement of Pier




Source : Study Team

Figure 8.5.4-4 Reinforcement of Abutment

8.5.5 Precast T Girder Erection Method

On the Cam River, 3 continuous PC Post tension T girders will be constructed by erection girder after fabricating PC Girder behind abutment.

Outline of erection is shown below.



Source: Study Team

Figure 8.5.5-2 PC T girder erection method